Databricks ML Associate

Questions 401–500 (Fifth 100)

Practice Exam Deck

How to Use This Deck

100 new questions (Q401–Q500), none repeated from Q1–Q400.

Each question slide has four options (A–D).

The next slide gives the correct answer and explains why the right option is right and why each wrong option is wrong.

This set focuses on MLflow search syntax, model signatures, pipeline persistence, Hyperopt internals, Feature Store batch/stream trade-offs, Unity Catalog lineage, Asset Bundles, MLflow evaluate, monitoring, and distributed training.

Question 401

Which MLflow search filter string finds runs where the metric `rmse` is less than 1?

A. `"metrics.rmse < 1"`

B. `"rmse < 1"`

C. `"metric_rmse < 1"`

D. `"metrics.rmse =< 1"`

Answer 401

Correct: A — filters use `metrics.<name>`.

Wrong:

B omits the `metrics.` prefix.

C is not the syntax.

D uses an invalid operator.

Question 402

Which MLflow search filter matches runs whose parameter `max_depth` equals 5?

A. `"params.max_depth = '5'"`

B. `"param.max_depth = 5"`

C. `"params.max_depth == 5"`

D. `"max_depth = 5"`

Answer 402

Correct: A — parameter filters use `params.<name>` and quoted values.

Wrong:

B uses the wrong prefix.

C uses == and no quotes.

D omits the prefix.

Question 403

Which MLflow API marks a run as finished?

A. `mlflow.end_run()`

B. `mlflow.finish_run()`

C. `mlflow.close_run()`

D. `mlflow.stop_run()`

Answer 403

Correct: A — `end_run()` finishes a run.

Wrong:

B, C, D are not the API.

Question 404

Which MLflow API deletes a run?

A. `mlflow.delete_run()`

B. `mlflow.remove_run()`

C. `mlflow.drop_run()`

D. `mlflow.end_run(delete=True)`

Answer 404

Correct: A — `delete_run()` deletes a run.

Wrong:

B, C, D are not the API.

Question 405

What does `mlflow.active_run()` return?

A. The currently active run object

B. A list of all runs

C. A metric value

D. A model

Answer 405

Correct: A — it returns the active run.

Wrong:

B, C, D are not returned.

Question 406

What is the purpose of `mlflow.set_tracking_uri()`?

A. It sets the tracking backend location

B. It sets the model registry name

C. It sets the cluster size

D. It sets the feature table

Answer 406

Correct: A — it points MLflow to a tracking backend.

Wrong:

B, C, D are unrelated.

Question 407

What does `mlflow.models.infer_signature()` do?

A. It infers input/output schema from sample data

B. It trains the model

C. It registers the model

D. It deploys the model

Answer 407

Correct: A — it infers a model signature.

Wrong:

B, C, D are unrelated.

Question 408

Why is a model signature useful for serving?

A. It validates request and response schemas

B. It trains the model

C. It stores features

D. It deletes versions

Answer 408

Correct: A — signatures validate schemas.

Wrong:

B, C, D are false.

Question 409

What does `mlflow.models.set_signature()` do?

A. It attaches a signature to a logged model

B. It creates a signature from scratch

C. It deletes a signature

D. It registers a signature

Answer 409

Correct: A — it sets a model's signature.

Wrong:

B, C, D are not its behavior.

Question 410

What does `PipelineModel.save()` do in Spark ML?

A. Persists the fitted pipeline to a path

B. Trains the pipeline

C. Registers the model

D. Serves the model

Answer 410

Correct: A — `save()` persists a fitted pipeline.

Wrong:

B, C, D are other operations.

Question 411

What does `PipelineModel.load()` do in Spark ML?

A. Loads a saved pipeline model from a path

B. Trains a pipeline

C. Registers a model

D. Serves a model

Answer 411

Correct: A — `load()` restores a saved model.

Wrong:

B, C, D are other operations.

Question 412

Why save the entire pipeline instead of only the estimator?

A. It preserves preprocessing steps needed at inference
B. It trains faster
C. It reduces storage
D. It registers the model

Answer 412

Correct: A — the pipeline includes preprocessing.

Wrong:

B, C, D are false.

Question 413

What does `Pipeline.fit()` return?

A. A `PipelineModel` with fitted stages
B. A DataFrame
C. A metric
D. A cluster

Answer 413

Correct: A — `fit()` returns a `PipelineModel`.

Wrong:

B, C, D are not returned.

Question 414

What happens if a pipeline stage is a transformer only?

A. It is applied without fitting
B. It is trained
C. It is skipped
D. It raises an error

Answer 414

Correct: A — transformers are applied, not fit.

Wrong:

B is for estimators.

C, D are false.

Question 415

What is an estimator in Spark ML?

A. An algorithm that fits data and produces a model
B. A fitted model
C. A DataFrame
D. A metric

Answer 415

Correct: A — estimators produce models via `fit()`.

Wrong:

B is a transformer/model.

C, D are not estimators.

Question 416

What is a transformer in Spark ML?

A. An object that transforms a DataFrame into another DataFrame

B. An algorithm that produces a model

C. A metric

D. A cluster

Answer 416

Correct: A — transformers map DataFrames.

Wrong:

B is an estimator.

C, D are unrelated.

Question 417

What does `hp.quniform()` define in Hyperopt?

A. A uniform distribution quantized to integer steps

B. A categorical choice

C. A log-uniform distribution

D. A constant

Answer 417

Correct: A — `hp.quniform` is a quantized uniform space.

Wrong:

B is `hp.choice`.

C is `hp.loguniform`.

D is a constant.

Question 418

What does `hp.randint()` define in Hyperopt?

A. A random integer in a range

B. A categorical choice

C. A log-uniform space

D. A constant

Answer 418

Correct: A — `hp.randint` samples integers.

Wrong:

B, C, D are other spaces.

Question 419

What does `hp.loguniform()` define in Hyperopt?

A. A log-uniform distribution between bounds

B. A uniform distribution

C. A categorical choice

D. A constant

Answer 419

Correct: A — `hp.loguniform` is log-uniform.

Wrong:

B is `hp.uniform`.

C is `hp.choice`.

D is a constant.

Question 420

What does the objective function return in Hyperopt?

A. A loss value to minimize and optional metadata

B. A model

C. A DataFrame

D. A cluster

Answer 420

Correct: A — the objective returns a loss (and optional status/dict).

Wrong:

B, C, D are not returned.

Question 421

What does `STATUS_OK` mean in a Hyperopt objective return?

A. The trial completed successfully

B. The trial failed

C. The trial was pruned

D. The trial is running

Answer 421

Correct: A — `STATUS_OK` marks success.

Wrong:

B is `STATUS_FAIL`.

C is pruned.

D is running.

Question 422

What is the benefit of pruning trials in Hyperopt?

A. It stops poor trials early to save compute
B. It improves accuracy
C. It registers models
D. It serves models

Answer 422

Correct: A — pruning saves compute on poor trials.

Wrong:

B, C, D are false.

Question 423

What does `SparkTrials(parallelism=N)` control?

A. The number of concurrent Hyperopt trials

B. The number of folds

C. The number of trees

D. The number of features

Answer 423

Correct: A — `parallelism` sets concurrent trials.

Wrong:

B, C, D are other settings.

Question 424

What does `fmin` return?

A. The best hyperparameters and the best loss
B. A trained model
C. A DataFrame
D. A cluster

Answer 424

Correct: A — `fmin` returns best params and loss.

Wrong:

B, C, D are not returned.

Question 425

What is the difference between a feature table and a training set?

A. Feature tables store features; training sets join features with labels
B. They are identical
C. Training sets store data; feature tables are views
D. Feature tables are models

Answer 425

Correct: A — training sets join features and labels.

Wrong:

B, C, D are false.

Question 426

What is the purpose of an online feature store in real-time serving?

A. It provides low-latency feature lookups
B. It trains models
C. It registers models
D. It stores notebooks

Answer 426

Correct: A — online stores serve low-latency features.

Wrong:

B, C, D are unrelated.

Question 427

What is the purpose of an offline feature store?

A. It stores features for batch training and scoring
B. It serves real-time requests
C. It registers models
D. It stores notebooks

Answer 427

Correct: A — offline stores support batch workflows.

Wrong:

B is online.

C, D are unrelated.

Question 428

What is a batch feature table used for?

A. Providing features for offline training and batch scoring
B. Serving low-latency inference
C. Registering models
D. Storing notebooks

Answer 428

Correct: A — batch feature tables support offline use.

Wrong:

B is online.

C, D are unrelated.

Question 429

What is a streaming feature table used for?

A. Continuously updated features for streaming inference
B. Offline batch training
C. Model registration
D. Notebook storage

Answer 429

Correct: A — streaming tables support live features.

Wrong:

B is offline.

C, D are unrelated.

Question 430

Why is a timestamp column important in feature tables?

A. It enables point-in-time joins

B. It trains the model

C. It registers the model

D. It serves the model

Answer 430

Correct: A — timestamps enable point-in-time joins.

Wrong:

B, C, D are unrelated.

Question 431

What is Unity Catalog lineage?

A. A record of data and model dependencies

B. A model

C. A feature table

D. A notebook

Answer 431

Correct: A — lineage tracks dependencies.

Wrong:

B, C, D are unrelated.

Question 432

Why is lineage useful for ML models?

A. It shows upstream data and downstream consumers
B. It trains models
C. It serves models
D. It registers models

Answer 432

Correct: A — lineage reveals upstream/downstream dependencies.

Wrong:

B, C, D are unrelated.

Question 433

What does a Databricks Asset Bundle define?

A. Infrastructure and jobs as code

B. A model

C. A feature table

D. A notebook

Answer 433

Correct: A — Asset Bundles define infrastructure as code.

Wrong:

B, C, D are not bundles.

Question 434

Which file format is used to define a Databricks Asset Bundle?

A. YAML

B. JSON

C. XML

D. CSV

Answer 434

Correct: A — bundles use YAML.

Wrong:

B, C, D are not the bundle format.

Question 435

What does `mlflow.evaluate()` do?

A. It evaluates a model against a dataset and logs metrics

B. It trains a model

C. It registers a model

D. It serves a model

Answer 435

Correct: A — `evaluate()` computes and logs metrics.

Wrong:

B, C, D are other operations.

Question 436

Which evaluator type does `mlflow.evaluate()` accept for classification?

A. A classifier evaluator with metrics such as F1 and ROC-AUC

B. A clustering evaluator

C. A regression evaluator

D. A summarization evaluator

Answer 436

Correct: A — classifier evaluators compute classification metrics.

Wrong:

B, C, D are other evaluator types.

Question 437

What does MLflow's model validation feature do?

A. Compares a candidate model to a baseline

B. Trains a new model

C. Registers a model

D. Serves a model

Answer 437

Correct: A — validation compares against a baseline.

Wrong:

B, C, D are unrelated.

Question 438

What is a baseline model in validation?

A. A reference model used for comparison

B. The newest model

C. The training data

D. The cluster

Answer 438

Correct: A — a baseline is a reference model.

Wrong:

B, C, D are not baselines.

Question 439

What is the purpose of monitoring model performance in production?

A. Detecting degradation and drift
B. Training new models
C. Registering models
D. Deleting models

Answer 439

Correct: A — monitoring detects degradation.

Wrong:

B, C, D are unrelated.

Question 440

What metric is typically monitored for model drift?

A. Population stability index (PSI) or distribution distance
B. Training loss
C. Cluster CPU
D. Storage size

Answer 440

Correct: A — PSI or distribution distances detect drift.

Wrong:

B, C, D are not drift metrics.

Question 441

What is a data quality expectation?

A. A rule that data should satisfy

B. A model

C. A feature table

D. A notebook

Answer 441

Correct: A — expectations are data rules.

Wrong:

B, C, D are unrelated.

Question 442

What is a model explainability method?

A. SHAP

B. PCA

C. KMeans

D. ALS

Answer 442

Correct: A — SHAP explains model predictions.

Wrong:

B, C, D are other algorithms.

Question 443

What is a permutation feature importance?

A. A method that measures accuracy drop when a feature is shuffled

B. A model

C. A feature table

D. A metric

Answer 443

Correct: A — permutation importance measures feature impact.

Wrong:

B, C, D are unrelated.

Question 444

What is partial dependence?

A. The marginal effect of a feature on predictions

B. A model type

C. A feature table

D. A metric

Answer 444

Correct: A — partial dependence shows marginal effects.

Wrong:

B, C, D are unrelated.

Question 445

What is distributed training?

A. Training across multiple machines or devices
B. Training a single model on one node
C. Serving a model
D. Registering a model

Answer 445

Correct: A — distributed training uses multiple resources.

Wrong:

B, C, D are other tasks.

Question 446

Which API enables distributed training in Spark ML?

A. `Spark ML estimators on Spark DataFrames`

B. `pandas UDFs only`

C. `Notebook widgets`

D. `SQL warehouses`

Answer 446

Correct: A — Spark ML trains across a cluster.

Wrong:

B, C, D are not distributed training APIs.

Question 447

What is a HorovodRunner used for in Databricks?

A. Distributed deep learning training

B. SQL queries

C. Model serving

D. Data storage

Answer 447

Correct: A — HorovodRunner enables distributed deep learning.

Wrong:

B, C, D are unrelated.

Question 448

What is the main benefit of distributed training?

A. Reduced training time for large data or models
B. Lower accuracy
C. Fewer features
D. Smaller storage

Answer 448

Correct: A — distribution reduces training time.

Wrong:

B, C, D are not benefits.

Question 449

What is a common challenge in distributed training?

A. Communication overhead between workers
B. Too little data
C. Too few models
D. Too few metrics

Answer 449

Correct: A — communication overhead is a key challenge.

Wrong:

B, C, D are not the challenge.

Question 450

What is a data parallel training strategy?

A. Splitting data across workers

B. Splitting the model across workers

C. Splitting metrics

D. Splitting clusters

Answer 450

Correct: A — data parallel splits data.

Wrong:

B is model parallel.

C, D are not strategies.

Question 451

What is a model parallel training strategy?

A. Splitting the model across workers

B. Splitting data across workers

C. Splitting metrics

D. Splitting clusters

Answer 451

Correct: A — model parallel splits the model.

Wrong:

B is data parallel.

C, D are not strategies.

Question 452

What is a checkpoint in distributed training?

A. A saved model state used for recovery or resumption

B. A metric

C. A cluster

D. A feature table

Answer 452

Correct: A — checkpoints save model state.

Wrong:

B, C, D are unrelated.

Question 453

Why are checkpoints useful for long training jobs?

A. They allow resuming after failure

B. They reduce features

C. They register models

D. They serve models

Answer 453

Correct: A — checkpoints enable resumption.

Wrong:

B, C, D are unrelated.

Question 454

What is early stopping in training?

A. Ending training when validation performance stops improving

B. Ending training after one epoch

C. Ending training at a fixed iteration

D. Ending training when training error is zero

Answer 454

Correct: A — early stopping uses validation performance.

Wrong:

B, C, D are arbitrary stopping rules.

Question 455

What is a learning rate in optimization?

A. The step size for parameter updates
B. The number of trees
C. The number of features
D. The number of rows

Answer 455

Correct: A — learning rate controls step size.

Wrong:

B, C, D are not learning rates.

Question 456

What happens if the learning rate is too high?

A. Training may diverge or overshoot
B. Training becomes stable
C. Accuracy always improves
D. Storage increases

Answer 456

Correct: A — a high learning rate can diverge.

Wrong:

B, C, D are false.

Question 457

What happens if the learning rate is too low?

A. Training becomes very slow
B. Training diverges
C. Accuracy always improves
D. Storage increases

Answer 457

Correct: A — low learning rates train slowly.

Wrong:

B, C, D are false.

Question 458

What is a mini-batch in training?

A. A small subset of data used for one update
B. The full dataset
C. A cluster
D. A metric

Answer 458

Correct: A — mini-batches update parameters incrementally.

Wrong:

B, C, D are unrelated.

Question 459

What is an epoch in training?

A. One full pass over the training data

B. One update step

C. One metric

D. One cluster

Answer 459

Correct: A — an epoch is a full data pass.

Wrong:

B, C, D are unrelated.

Question 460

What is a batch size in training?

A. The number of samples per update
B. The number of epochs
C. The number of trees
D. The number of features

Answer 460

Correct: A — batch size sets samples per update.

Wrong:

B, C, D are other settings.

Question 461

What is a confusion matrix useful for beyond accuracy?

A. It shows false positives and false negatives separately
B. It trains a model
C. It stores data
D. It serves a model

Answer 461

Correct: A — it separates FP and FN counts.

Wrong:

B, C, D are unrelated.

Question 462

What is a ROC curve?

A. A plot of true positive rate versus false positive rate

B. A plot of precision versus recall

C. A plot of error versus training size

D. A plot of feature importance

Answer 462

Correct: A — ROC plots TPR vs. FPR.

Wrong:

B is a PR curve.

C is a learning curve.

D is feature importance.

Question 463

What is a PR curve?

A. A plot of precision versus recall

B. A plot of TPR versus FPR

C. A plot of error versus training size

D. A plot of feature importance

Answer 463

Correct: A — PR curves plot precision vs. recall.

Wrong:

B is ROC.

C is a learning curve.

D is feature importance.

Question 464

What is log loss?

A. A classification metric that penalizes confident wrong predictions

B. A regression metric

C. A clustering metric

D. A drift metric

Answer 464

Correct: A — log loss penalizes confident errors.

Wrong:

B, C, D are other metrics.

Question 465

What is cross-entropy?

A. A loss function for classification

B. A clustering metric

C. A drift metric

D. A regression metric

Answer 465

Correct: A — cross-entropy is a classification loss.

Wrong:

B, C, D are other metrics.

Question 466

What is a target variable in supervised learning?

A. The value being predicted

B. The input features

C. The cluster

D. The model

Answer 466

Correct: A — the target is predicted.

Wrong:

B, C, D are unrelated.

Question 467

What is a feature in supervised learning?

A. An input variable used to predict the target

B. The predicted value

C. The model

D. The cluster

Answer 467

Correct: A — features are input variables.

Wrong:

B, C, D are unrelated.

Question 468

What is a label in supervised learning?

A. The known target value in training data

B. The input features

C. The model

D. The cluster

Answer 468

Correct: A — labels are known target values.

Wrong:

B, C, D are unrelated.

Question 469

What is semi-supervised learning?

A. Learning from a mix of labeled and unlabeled data
B. Learning from only labeled data
C. Learning from only unlabeled data
D. Learning without a model

Answer 469

Correct: A — semi-supervised uses both labeled and unlabeled data.

Wrong:

B is supervised.

C is unsupervised.

D is false.

Question 470

What is self-supervised learning?

A. Learning from data-generated labels
B. Learning from manual labels
C. Learning from clusters
D. Learning without data

Answer 470

Correct: A — self-supervised uses generated labels.

Wrong:

B is supervised.

C is unsupervised.

D is false.

Question 471

What is reinforcement learning?

A. Learning from rewards and penalties
B. Learning from labeled examples
C. Learning from clusters
D. Learning from no data

Answer 471

Correct: A — RL uses rewards and penalties.

Wrong:

B is supervised.

C is unsupervised.

D is false.

Question 472

What is a reward signal in reinforcement learning?

A. Feedback guiding the agent's behavior

B. A feature

C. A label

D. A cluster

Answer 472

Correct: A — rewards guide learning.

Wrong:

B, C, D are unrelated.

Question 473

What is a policy in reinforcement learning?

A. A mapping from states to actions

B. A feature

C. A label

D. A cluster

Answer 473

Correct: A — policies map states to actions.

Wrong:

B, C, D are unrelated.

Question 474

What is an agent in reinforcement learning?

A. The learner that takes actions

B. The environment

C. The reward

D. The state

Answer 474

Correct: A — the agent takes actions.

Wrong:

B, C, D are other RL components.

Question 475

What is an environment in reinforcement learning?

A. The world the agent interacts with
B. The agent
C. The reward
D. The policy

Answer 475

Correct: A — the environment is the world.

Wrong:

B, C, D are other RL components.

Question 476

What is an observation in reinforcement learning?

A. Information the agent perceives about the environment
B. The reward
C. The policy
D. The model

Answer 476

Correct: A — observations are perceived information.

Wrong:

B, C, D are other components.

Question 477

What is an action in reinforcement learning?

A. A choice the agent makes

B. A reward

C. A policy

D. A model

Answer 477

Correct: A — actions are agent choices.

Wrong:

B, C, D are other components.

Question 478

What is exploration in reinforcement learning?

A. Trying new actions to learn
B. Repeating known actions
C. Training a model
D. Serving a model

Answer 478

Correct: A — exploration tries new actions.

Wrong:

B is exploitation.

C, D are unrelated.

Question 479

What is exploitation in reinforcement learning?

A. Choosing the best-known action

B. Trying new actions

C. Training a model

D. Serving a model

Answer 479

Correct: A — exploitation uses known best actions.

Wrong:

B is exploration.

C, D are unrelated.

Question 480

What is the exploration-exploitation tradeoff?

A. Balancing trying new actions versus using known good actions
B. Balancing training and serving
C. Balancing data and models
D. Balancing clusters

Answer 480

Correct: A — the tradeoff balances exploration and exploitation.

Wrong:

B, C, D are unrelated.

Question 481

What is a Markov decision process?

A. A mathematical framework for RL with states, actions, and rewards

B. A model type

C. A feature table

D. A cluster

Answer 481

Correct: A — an MDP defines RL states/actions/rewards.

Wrong:

B, C, D are unrelated.

Question 482

What is a state in reinforcement learning?

A. A representation of the environment at a point in time

B. An action

C. A reward

D. A policy

Answer 482

Correct: A — states represent the environment.

Wrong:

B, C, D are other components.

Question 483

What is a value function in reinforcement learning?

A. An estimate of expected future reward

B. A feature

C. A label

D. A cluster

Answer 483

Correct: A — value functions estimate future reward.

Wrong:

B, C, D are unrelated.

Question 484

What is Q-learning?

A. A reinforcement learning algorithm that learns action values

B. A clustering algorithm

C. A regression algorithm

D. A dimensionality reduction algorithm

Answer 484

Correct: A — Q-learning learns action values.

Wrong:

B, C, D are other algorithms.

Question 485

What is a policy gradient method?

A. A method that optimizes the policy directly

B. A method that clusters data

C. A method that reduces features

D. A method that serves models

Answer 485

Correct: A — policy gradients optimize policies directly.

Wrong:

B, C, D are unrelated.

Question 486

What is a bandit problem?

A. A simplified RL problem with one state and multiple actions

B. A classification problem

C. A regression problem

D. A clustering problem

Answer 486

Correct: A — bandits are single-state RL problems.

Wrong:

B, C, D are other problem types.

Question 487

What is A/B testing in the context of bandits?

A. Comparing two actions using observed rewards
B. Training two models
C. Deleting two models
D. Registering two models

Answer 487

Correct: A — A/B tests compare actions.

Wrong:

B, C, D are unrelated.

Question 488

What is a multi-armed bandit?

A. A problem of choosing among multiple actions with unknown rewards
B. A clustering problem
C. A regression problem
D. A dimensionality reduction problem

Answer 488

Correct: A — multi-armed bandits involve multiple actions.

Wrong:

B, C, D are other problem types.

Question 489

What is Thompson sampling?

A. A bandit algorithm using posterior distributions
B. A clustering algorithm
C. A regression algorithm
D. A serving method

Answer 489

Correct: A — Thompson sampling uses posteriors.

Wrong:

B, C, D are unrelated.

Question 490

What is epsilon-greedy?

A. A bandit strategy that explores with probability epsilon
B. A clustering method
C. A regression method
D. A serving method

Answer 490

Correct: A — epsilon-greedy balances exploration/exploitation.

Wrong:

B, C, D are unrelated.

Question 491

What is a feature store?

A. A centralized repository for features

B. A model

C. A cluster

D. A notebook

Answer 491

Correct: A — a feature store centralizes features.

Wrong:

B, C, D are unrelated.

Question 492

What is a feature view?

A. A logical view of features for a use case

B. A model

C. A cluster

D. A table

Answer 492

Correct: A — feature views organize features.

Wrong:

B, C, D are unrelated.

Question 493

What is a feature group?

A. A set of related features

B. A model

C. A cluster

D. A notebook

Answer 493

Correct: A — feature groups are related features.

Wrong:

B, C, D are unrelated.

Question 494

What is a feature pipeline?

A. A workflow that computes and updates features

B. A model

C. A cluster

D. A notebook

Answer 494

Correct: A — feature pipelines compute features.

Wrong:

B, C, D are unrelated.

Question 495

What is a feature transformation?

A. An operation that creates or modifies features

B. A model

C. A cluster

D. A notebook

Answer 495

Correct: A — transformations modify features.

Wrong:

B, C, D are unrelated.

Question 496

What is a feature backfill?

A. Computing historical feature values

B. Training a model

C. Serving a model

D. Deleting features

Answer 496

Correct: A — backfills compute historical values.

Wrong:

B, C, D are unrelated.

Question 497

Why is a feature backfill needed after a feature definition changes?

A. Historical feature values must be recomputed consistently

B. The model retrains automatically

C. The cluster resizes

D. The notebook is deleted

Answer 497

Correct: A — backfills keep history consistent.

Wrong:

B, C, D are false.

Question 498

What is feature versioning?

A. Tracking changes to feature definitions over time
B. Training a model
C. Serving a model
D. Registering a model

Answer 498

Correct: A — feature versioning tracks definition changes.

Wrong:

B, C, D are unrelated.

Question 499

What is a feature store's primary benefit for collaboration?

A. Shared, governed feature definitions across teams
B. Faster training
C. Smaller models
D. Fewer clusters

Answer 499

Correct: A — feature stores share governed features.

Wrong:

B, C, D are false.

Question 500

What is the best practice for updating a feature table used in production?

A. Backfill, validate, and then update downstream models
B. Delete the table
C. Stop monitoring
D. Skip validation

Answer 500

Correct: A — backfill and validate before rollout.

Wrong:

B causes downtime.

C removes safeguards.

D risks bad data.