Databricks ML Associate

Questions 501–600 (Sixth 100)

Practice Exam Deck

How to Use This Deck

100 new questions (Q501–Q600), none repeated from Q1–Q500.

Each question slide has four options (A–D).

The next slide gives the correct answer and explains why the right option is right and why each wrong option is wrong.

This set emphasizes Feature Store data sources and merge behavior, MLflow statuses and artifacts, serving environments, Unity Catalog grants and external locations, Delta schema evolution and merge, Jobs parameters and notifications, Spark ML text transformers, and tracking-server architecture.

Question 501

Which data source can be used to create a Feature Store table?

A. A Spark DataFrame or a Delta table

B. A Python list only

C. A notebook only

D. A cluster only

Answer 501

Correct: A — feature tables are built from DataFrames or Delta tables.

Wrong:

B, C, D are not valid data sources.

Question 502

What happens when `fe.write_table()` is called with `mode="merge"`?

A. Rows are upserted based on the primary key

B. The table is dropped

C. Rows are appended without keys

D. The table is renamed

Answer 502

Correct: A — merge upserts by primary key.

Wrong:

B, C, D are not merge behavior.

Question 503

Which write mode fully overwrites a feature table?

A. `mode="overwrite"`

B. `mode="merge"`

C. `mode="append"`

D. `mode="upsert"`

Answer 503

Correct: A — overwrite replaces the table contents.

Wrong:

B upserts.

C appends.

D is not a supported mode name.

Question 504

Which write mode adds new rows without changing existing ones?

A. `mode="append"`

B. `mode="overwrite"`

C. `mode="merge"`

D. `mode="replace"`

Answer 504

Correct: A — append adds rows.

Wrong:

B overwrites.

C upserts.

D is not the mode name.

Question 505

Why is a merge write mode preferred for updating feature values?

A. It updates existing keys and inserts new ones

B. It drops the table

C. It appends duplicates

D. It renames columns

Answer 505

Correct: A — merge updates existing rows and inserts new ones.

Wrong:

B, C, D are false.

Question 506

What is a FeatureLookup used for in training set creation?

A. To join specific features from a feature table to a label DataFrame
B. To train a model
C. To serve a model
D. To register a model

Answer 506

Correct: A — FeatureLookup defines which features to join.

Wrong:

B, C, D are unrelated.

Question 507

What does a FeatureLookup require besides the feature table name?

A. A lookup key to join on

B. A model

C. A cluster

D. A metric

Answer 507

Correct: A — lookups need a join key.

Wrong:

B, C, D are not required.

Question 508

What is a training set's role in Feature Store?

A. A point-in-time-correct dataset for training

B. A serving endpoint

C. A model artifact

D. A cluster

Answer 508

Correct: A — training sets are point-in-time-correct datasets.

Wrong:

B, C, D are unrelated.

Question 509

Which MLflow run status indicates a failed run?

A. `FAILED`

B. `FINISHED`

C. `RUNNING`

D. `SCHEDULED`

Answer 509

Correct: A — `FAILED` marks a failed run.

Wrong:

B is success.

C is in progress.

D is not a status.

Question 510

Which MLflow run status indicates a successful run?

A. `FINISHED`

B. `FAILED`

C. `RUNNING`

D. `KILLED`

Answer 510

Correct: A — `FINISHED` marks success.

Wrong:

B is failure.

C is in progress.

D is terminated.

Question 511

Which MLflow run status indicates a terminated run?

A. `KILLED`

B. `FINISHED`

C. `FAILED`

D. `RUNNING`

Answer 511

Correct: A — `KILLED` indicates a terminated run.

Wrong:

B, C, D are other statuses.

Question 512

What does an MLflow artifact store store?

A. Files such as models, plots, and data files

B. Parameters only

C. Metrics only

D. Runs only

Answer 512

Correct: A — artifacts are files.

Wrong:

B, C, D are metadata.

Question 513

Which is a supported MLflow artifact store backend?

A. Cloud object storage

B. Only local disk

C. Only HDFS

D. Only SQLite

Answer 513

Correct: A — cloud object storage is supported.

Wrong:

B, C, D are not the only options.

Question 514

What does `mlflow.get_artifact_uri()` return?

A. The URI of the artifact store for the active run

B. The model registry URI

C. The tracking server URI

D. The cluster URI

Answer 514

Correct: A — it returns the artifact URI.

Wrong:

B, C, D are different URIs.

Question 515

What does the model registry store?

A. Model versions and their metadata
B. Training data
C. Feature tables
D. Notebooks

Answer 515

Correct: A — the registry stores model versions and metadata.

Wrong:

B, C, D are stored elsewhere.

Question 516

What is the maximum number of aliases a model version can have?

A. Multiple aliases are allowed per version

B. Exactly one

C. Exactly two

D. None

Answer 516

Correct: A — a version can have multiple aliases.

Wrong:

B, C, D are incorrect.

Question 517

What happens if an alias points to a new version?

A. Serving references to the alias resolve to the new version

B. The old version is deleted

C. The model is retrained

D. The endpoint is deleted

Answer 517

Correct: A — alias moves redirect serving references.

Wrong:

B, C, D are false.

Question 518

Which MLflow API loads a model version by alias?

A. `models:/<name>@<alias>`

B. `runs:/<alias>`

C. `models:/<alias>`

D. `models:<name>`

Answer 518

Correct: A — alias URIs use `models:/<name>@<alias>`.

Wrong:

B, C, D are malformed URIs.

Question 519

What is a serving endpoint environment in Databricks?

A. The runtime and dependency configuration used to serve a model
B. The training data
C. The model artifact
D. The cluster policy

Answer 519

Correct: A — environments configure serving runtime and deps.

Wrong:

B, C, D are unrelated.

Question 520

What is a serving endpoint's model version reference?

A. The exact version or alias the endpoint serves
B. The training data
C. The cluster config
D. The notebook

Answer 520

Correct: A — endpoints reference a version or alias.

Wrong:

B, C, D are unrelated.

Question 521

What does an endpoint's scale-to-zero setting affect?

A. Whether idle capacity is shut down

B. Whether the model is retrained

C. Whether the model is registered

D. Whether the model is archived

Answer 521

Correct: A — scale-to-zero shuts down idle capacity.

Wrong:

B, C, D are unrelated.

Question 522

Which is a valid endpoint state?

A. `READY`

B. `FINISHED`

C. `FAILED`

D. `RUNNING`

Answer 522

Correct: A — `READY` is an endpoint state.

Wrong:

B, C, D are run statuses.

Question 523

What is an external location in Unity Catalog?

A. A governed cloud storage path

B. A model

C. A feature table

D. A notebook

Answer 523

Correct: A — external locations govern cloud storage.

Wrong:

B, C, D are unrelated.

Question 524

What is a storage credential in Unity Catalog?

A. A credential used to access cloud storage

B. A model

C. A feature table

D. A notebook

Answer 524

Correct: A — storage credentials grant cloud access.

Wrong:

B, C, D are unrelated.

Question 525

Which privilege is required to use an external location?

A. `USE` or `READ FILES`

B. `SELECT`

C. `MODIFY`

D. `EXECUTE`

Answer 525

Correct: A — using an external location needs file-level privileges.

Wrong:

B, C, D are table/model privileges.

Question 526

What is a Unity Catalog grant?

A. A privilege assignment to a principal

B. A model

C. A feature table

D. A notebook

Answer 526

Correct: A — grants assign privileges.

Wrong:

B, C, D are unrelated.

Question 527

What is a principal in Unity Catalog?

A. A user, group, or service principal

B. A model

C. A feature table

D. A notebook

Answer 527

Correct: A — principals are users, groups, or SPs.

Wrong:

B, C, D are unrelated.

Question 528

What is a service principal used for in Databricks?

A. Non-human authentication for automated workflows

B. Training data

C. A model

D. A feature table

Answer 528

Correct: A — service principals authenticate automation.

Wrong:

B, C, D are unrelated.

Question 529

What is the purpose of an external table in Unity Catalog?

A. To reference data stored outside UC-managed storage
B. To store models
C. To store notebooks
D. To store clusters

Answer 529

Correct: A — external tables reference external storage.

Wrong:

B, C, D are unrelated.

Question 530

What does Delta Lake schema evolution allow?

A. Adding or changing columns without rewriting data

B. Deleting the table

C. Deleting the model

D. Deleting the cluster

Answer 530

Correct: A — schema evolution supports column changes.

Wrong:

B, C, D are unrelated.

Question 531

Which option enables schema evolution in a Delta write?

A. `mergeSchema=True`

B. `overwriteSchema=True`

C. `appendSchema=True`

D. `evolveSchema=True`

Answer 531

Correct: A — `mergeSchema` merges schemas.

Wrong:

B overwrites schema.

C, D are not options.

Question 532

What does `overwriteSchema=True` do on a Delta write?

A. Replaces the table's schema

B. Merges schemas

C. Appends rows

D. Deletes rows

Answer 532

Correct: A — `overwriteSchema` replaces the schema.

Wrong:

B is `mergeSchema`.

C, D are row operations.

Question 533

What does a Delta `MERGE INTO` statement do?

A. Upserts rows into a target table based on a condition
B. Deletes the table
C. Renames the table
D. Creates a view

Answer 533

Correct: A — `MERGE INTO` upserts rows.

Wrong:

B, C, D are other operations.

Question 534

What is a Delta table's transaction log used for?

A. Tracking table changes and enabling ACID guarantees
B. Training models
C. Serving models
D. Storing notebooks

Answer 534

Correct: A — the log tracks changes and ACID properties.

Wrong:

B, C, D are unrelated.

Question 535

What does a Databricks Job parameter do?

A. Passes values to tasks at runtime

B. Trains models

C. Serves models

D. Registers models

Answer 535

Correct: A — parameters pass runtime values.

Wrong:

B, C, D are unrelated.

Question 536

How are job parameters accessed inside a notebook?

A. With `dbutils.widgets.get()`
B. With `mlflow.get_param()`
C. With `spark.conf.get()`
D. With `dbutils.jobs.get()`

Answer 536

Correct: A — widgets retrieve job parameters.

Wrong:

B is MLflow params.

C is Spark conf.

D is not the API.

Question 537

What is a job notification used for?

A. Alerting on job success or failure
B. Training models
C. Serving models
D. Registering models

Answer 537

Correct: A — notifications alert on job events.

Wrong:

B, C, D are unrelated.

Question 538

Which event can trigger a job notification?

A. Job start, success, or failure

B. Model registration

C. Feature table creation

D. Notebook deletion

Answer 538

Correct: A — notifications trigger on job events.

Wrong:

B, C, D are unrelated events.

Question 539

What is a job's maximum concurrent runs setting?

A. It limits how many runs of a job can execute at once
B. It limits the cluster size
C. It limits the model size
D. It limits the feature count

Answer 539

Correct: A — concurrency limits simultaneous runs.

Wrong:

B, C, D are unrelated.

Question 540

What is a job timeout?

A. A maximum runtime after which a job is terminated

B. A model type

C. A feature table

D. A cluster mode

Answer 540

Correct: A — timeouts terminate long-running jobs.

Wrong:

B, C, D are unrelated.

Question 541

What is a Spark ML tokenizer used for?

A. Splitting text into words

B. Encoding categories

C. Scaling features

D. Assembling vectors

Answer 541

Correct: A — tokenizers split text.

Wrong:

B, C, D are other transformers.

Question 542

What is a Spark ML HashingTF used for?

A. Converting text tokens into feature vectors
B. Scaling numeric features
C. Encoding categories
D. Imputing values

Answer 542

Correct: A — HashingTF hashes tokens into vectors.

Wrong:

B, C, D are other transformers.

Question 543

What is a Spark ML IDF transformer used for?

A. Down-weighting common tokens in text features
B. Scaling numeric features
C. Encoding categories
D. Imputing values

Answer 543

Correct: A — IDF down-weights frequent tokens.

Wrong:

B, C, D are other transformers.

Question 544

What does a Spark ML Word2Vec model produce?

A. Word embeddings
B. Category encodings
C. Scaled features
D. Imputed values

Answer 544

Correct: A — Word2Vec produces embeddings.

Wrong:

B, C, D are other transformations.

Question 545

What is a Spark ML StopWordsRemover used for?

A. Removing common words from text

B. Encoding categories

C. Scaling features

D. Imputing values

Answer 545

Correct: A — StopWordsRemover removes common words.

Wrong:

B, C, D are other transformers.

Question 546

What is a Spark ML NGram transformer used for?

A. Generating sequences of N tokens
B. Encoding categories
C. Scaling features
D. Imputing values

Answer 546

Correct: A — NGram creates token sequences.

Wrong:

B, C, D are other transformers.

Question 547

What is a Spark ML CountVectorizer used for?

A. Converting text to token-count vectors
B. Scaling features
C. Encoding categories
D. Imputing values

Answer 547

Correct: A — CountVectorizer builds count vectors.

Wrong:

B, C, D are other transformers.

Question 548

What is a pipeline's `stages` parameter?

A. A list of transformers and estimators

B. A list of metrics

C. A list of clusters

D. A list of tables

Answer 548

Correct: A — `stages` lists pipeline steps.

Wrong:

B, C, D are unrelated.

Question 549

What does a pipeline do with an estimator stage during `fit()`?

A. It fits the estimator and stores the resulting model

B. It skips it

C. It fails

D. It deletes it

Answer 549

Correct: A — `fit()` trains estimators.

Wrong:

B, C, D are false.

Question 550

What does a pipeline do with a transformer stage during `transform()`?

A. It applies the fitted transformer

B. It fits the transformer

C. It skips it

D. It fails

Answer 550

Correct: A — `transform()` applies transformers.

Wrong:

B is for `fit()`.

C, D are false.

Question 551

What is a Spark ML `OneVsRest` classifier used for?

A. Multiclass classification using binary classifiers
B. Regression
C. Clustering
D. Dimensionality reduction

Answer 551

Correct: A — OneVsRest supports multiclass via binary models.

Wrong:

B, C, D are other tasks.

Question 552

What does a Spark ML `ChiSqSelector` do?

A. Selects features using a chi-squared test

B. Scales features

C. Encodes categories

D. Imputes values

Answer 552

Correct: A — ChiSqSelector selects features statistically.

Wrong:

B, C, D are other transformers.

Question 553

What does a Spark ML `PCA` transformer do?

A. Reduces dimensionality via principal components

B. Encodes categories

C. Scales features

D. Imputes values

Answer 553

Correct: A — PCA reduces dimensions.

Wrong:

B, C, D are other transformers.

Question 554

What is a Spark ML `PolynomialExpansion` used for?

A. Creating polynomial and interaction features
B. Encoding categories
C. Scaling features
D. Imputing values

Answer 554

Correct: A — PolynomialExpansion creates higher-order features.

Wrong:

B, C, D are other transformers.

Question 555

What is a Spark ML `Binarizer` used for?

A. Converting numeric features to binary based on a threshold

B. Encoding categories

C. Scaling features

D. Imputing values

Answer 555

Correct: A — Binarizer thresholds numeric values.

Wrong:

B, C, D are other transformers.

Question 556

What does the MLflow tracking server store in its backend store?

A. Run metadata and metrics

B. Model files

C. Feature tables

D. Notebooks

Answer 556

Correct: A — the backend store holds run metadata and metrics.

Wrong:

B is artifacts.

C, D are elsewhere.

Question 557

Which is a common backend store for MLflow?

A. A relational database such as MySQL or PostgreSQL
B. A notebook
C. A cluster
D. A feature table

Answer 557

Correct: A — relational databases are common backends.

Wrong:

B, C, D are not backend stores.

Question 558

What is the purpose of the MLflow artifact store?

A. To store artifacts such as models and plots

B. To store parameters

C. To store metrics

D. To store runs

Answer 558

Correct: A — artifact stores hold files.

Wrong:

B, C, D are backend-store data.

Question 559

What is a Databricks-managed MLflow experiment?

A. An experiment managed by the Databricks tracking server

B. A local SQLite experiment

C. A feature table

D. A cluster

Answer 559

Correct: A — Databricks manages its experiments.

Wrong:

B, C, D are not experiments.

Question 560

What does `mlflow.set_registry_uri()` do?

A. Sets the model registry backend

B. Sets the tracking server

C. Sets the artifact store

D. Sets the cluster

Answer 560

Correct: A — it sets the registry URI.

Wrong:

B is tracking URI.

C is artifact URI.

D is unrelated.

Question 561

What does a model registry webhook do?

A. It sends notifications on model registry events

B. It trains models

C. It serves models

D. It deletes models

Answer 561

Correct: A — webhooks notify on registry events.

Wrong:

B, C, D are unrelated.

Question 562

What is a model registry comment used for?

A. Recording notes about a model version
B. Storing model files
C. Storing metrics
D. Storing parameters

Answer 562

Correct: A — comments store notes.

Wrong:

B, C, D are stored elsewhere.

Question 563

What does a model version's creation timestamp indicate?

A. When the version was registered

B. When the model was trained

C. When the model was served

D. When the model was deleted

Answer 563

Correct: A — it indicates registration time.

Wrong:

B, C, D are other times.

Question 564

Which MLflow API moves a model version's alias?

A. `mlflow.set_registered_model_alias()`

B. `mlflow.move_alias()`

C. `mlflow.create_alias()`

D. `mlflow.update_alias()`

Answer 564

Correct: A — `set_registered_model_alias()` updates aliases.

Wrong:

B, C, D are not the API.

Question 565

What is a Databricks SQL warehouse used for?

A. Running SQL queries and BI workloads
B. Training ML models
C. Serving ML models
D. Managing Repos

Answer 565

Correct: A — SQL warehouses are for SQL/BI.

Wrong:

B, C, D are other tools.

Question 566

Which compute type should not be used for Spark ML training?

A. SQL warehouse

B. All-purpose cluster

C. Job cluster

D. Single-node cluster

Answer 566

Correct: A — SQL warehouses cannot run Spark ML.

Wrong:

B, C, D can run Spark ML.

Question 567

What is the purpose of a cluster library?

A. It makes a library available to all notebooks on a cluster
B. It installs a feature table
C. It registers a model
D. It serves a model

Answer 567

Correct: A — cluster libraries apply cluster-wide.

Wrong:

B, C, D are unrelated.

Question 568

Why install libraries at the cluster level instead of per notebook?

A. It ensures consistent environments across notebooks
B. It trains faster
C. It serves faster
D. It registers models

Answer 568

Correct: A — cluster libraries ensure consistency.

Wrong:

B, C, D are false.

Question 569

What is a Databricks workspace?

A. A collaborative environment for notebooks, jobs, and data

B. A model

C. A feature table

D. A cluster

Answer 569

Correct: A — workspaces host collaboration tools.

Wrong:

B, C, D are workspace objects.

Question 570

What is a Databricks notebook folder used for?

A. Organizing notebooks and files in a workspace
B. Training models
C. Serving models
D. Registering models

Answer 570

Correct: A — folders organize workspace content.

Wrong:

B, C, D are unrelated.

Question 571

What is the purpose of a Databricks secret scope?

A. To store secrets securely

B. To store models

C. To store feature tables

D. To store notebooks

Answer 571

Correct: A — secret scopes store secrets.

Wrong:

B, C, D are stored elsewhere.

Question 572

Which secret scope backend is Databricks-managed?

A. Databricks-backed scope

B. Azure Key Vault-backed scope

C. AWS Secrets Manager-backed scope

D. Local file-backed scope

Answer 572

Correct: A — Databricks-backed scopes are managed by Databricks.

Wrong:

B, C are external backends.

D is not supported.

Question 573

What does `dbutils.secrets.listScopes()` do?

A. Lists available secret scopes

B. Lists models

C. Lists tables

D. Lists clusters

Answer 573

Correct: A — it lists secret scopes.

Wrong:

B, C, D are other utilities.

Question 574

What is the purpose of a data access policy in Unity Catalog?

A. Controlling who can access data
B. Training models
C. Serving models
D. Registering models

Answer 574

Correct: A — access policies control data access.

Wrong:

B, C, D are unrelated.

Question 575

What is a row filter in Unity Catalog?

A. A rule limiting which rows a user can see

B. A model

C. A feature table

D. A notebook

Answer 575

Correct: A — row filters limit visible rows.

Wrong:

B, C, D are unrelated.

Question 576

What is a column mask in Unity Catalog?

A. A rule that hides or transforms column values for some users

B. A model

C. A feature table

D. A notebook

Answer 576

Correct: A — column masks transform visible values.

Wrong:

B, C, D are unrelated.

Question 577

What does a dynamic view in Unity Catalog allow?

A. Row- or column-level filtering based on the requesting user
B. Training models
C. Serving models
D. Registering models

Answer 577

Correct: A — dynamic views filter by user.

Wrong:

B, C, D are unrelated.

Question 578

What is a Delta Live Tables expectation?

A. A data quality rule enforced during pipeline runs

B. A model

C. A feature table

D. A cluster

Answer 578

Correct: A — DLT expectations enforce data quality.

Wrong:

B, C, D are unrelated.

Question 579

What happens when a DLT expectation fails?

A. Records may be dropped or the pipeline may fail, based on the expectation
B. The pipeline always succeeds
C. The cluster restarts
D. The model is retrained

Answer 579

Correct: A — expectations can drop records or fail the pipeline.

Wrong:

B, C, D are false.

Question 580

What does DLT's `@dlt.expect_or_drop` do?

A. Drops records that violate the expectation
B. Fails the pipeline
C. Retrains the model
D. Restarts the cluster

Answer 580

Correct: A — `expect_or_drop` drops bad records.

Wrong:

B is `expect_or_fail`.

C, D are unrelated.

Question 581

What does DLT's `@dlt.expect_or_fail` do?

A. Fails the pipeline if the expectation is violated

B. Drops bad records

C. Retrains the model

D. Restarts the cluster

Answer 581

Correct: A — `expect_or_fail` fails the pipeline.

Wrong:

B is `expect_or_drop`.

C, D are unrelated.

Question 582

What does a DLT pipeline's development mode change?

A. It reduces resource usage and supports faster iteration
B. It trains more models
C. It changes the model type
D. It changes the feature table

Answer 582

Correct: A — development mode favors faster iteration.

Wrong:

B, C, D are unrelated.

Question 583

What is a DLT pipeline's target schema?

A. The schema where pipeline tables are created

B. A model

C. A feature table

D. A notebook

Answer 583

Correct: A — target schemas hold DLT tables.

Wrong:

B, C, D are unrelated.

Question 584

What does a Databricks Asset Bundle's `databricks.yml` file contain?

A. Bundle configuration for jobs, pipelines, and resources

B. Model weights

C. Training data

D. Feature tables

Answer 584

Correct: A — `databricks.yml` defines bundle resources.

Wrong:

B, C, D are not in the bundle config.

Question 585

What is the purpose of a bundle's target environment?

A. It selects the workspace and configuration to deploy into
B. It selects the model
C. It selects the feature table
D. It selects the notebook

Answer 585

Correct: A — targets select deployment environments.

Wrong:

B, C, D are unrelated.

Question 586

Which command deploys a Databricks Asset Bundle?

A. `databricks bundle deploy`

B. `databricks deploy bundle`

C. `databricks bundle run`

D. `databricks bundle validate`

Answer 586

Correct: A — `bundle deploy` deploys.

Wrong:

B is not a command.

C runs resources.

D validates config only.

Question 587

Which command validates a Databricks Asset Bundle without deploying it?

A. `databricks bundle validate`

B. `databricks bundle deploy`

C. `databricks bundle run`

D. `databricks bundle init`

Answer 587

Correct: A — `bundle validate` checks config.

Wrong:

B deploys.

C runs resources.

D scaffolds a bundle.

Question 588

What is the purpose of a Unity Catalog metastore?

A. It stores metadata for catalogs, schemas, and tables

B. It trains models

C. It serves models

D. It stores notebooks

Answer 588

Correct: A — metastores store UC metadata.

Wrong:

B, C, D are unrelated.

Question 589

How many metastores can a Databricks account have per region?

A. One
B. Two
C. Three
D. Unlimited

Answer 589

Correct: A — one metastore per region.

Wrong:

B, C, D are incorrect.

Question 590

What is a Unity Catalog catalog?

A. A top-level container for schemas

B. A model

C. A feature table

D. A notebook

Answer 590

Correct: A — catalogs contain schemas.

Wrong:

B, C, D are unrelated.

Question 591

What does the `USE CATALOG` privilege allow?

A. Using objects within a catalog
B. Training models
C. Serving models
D. Registering models

Answer 591

Correct: A — `USE CATALOG` allows catalog use.

Wrong:

B, C, D are unrelated.

Question 592

What does the `USE SCHEMA` privilege allow?

A. Using objects within a schema
B. Training models
C. Serving models
D. Registering models

Answer 592

Correct: A — `USE SCHEMA` allows schema use.

Wrong:

B, C, D are unrelated.

Question 593

What is the purpose of a Unity Catalog function?

A. To define reusable logic callable in SQL

B. To train models

C. To serve models

D. To store notebooks

Answer 593

Correct: A — UC functions define SQL-callable logic.

Wrong:

B, C, D are unrelated.

Question 594

What does the `EXECUTE` privilege allow on a function?

A. Calling the function
B. Modifying the function
C. Deleting the function
D. Creating the function

Answer 594

Correct: A — `EXECUTE` allows calling functions.

Wrong:

B, C, D require other privileges.

Question 595

What is the benefit of a shared cluster in Databricks?

A. Multiple users can use it with isolation

B. It trains faster

C. It serves faster

D. It registers models

Answer 595

Correct: A — shared clusters support multiple users.

Wrong:

B, C, D are false.

Question 596

Why might a single-user cluster be preferred for advanced ML workloads?

A. It supports more configuration and libraries

B. It is cheaper

C. It supports multiple users

D. It supports SQL only

Answer 596

Correct: A — single-user clusters allow more customization.

Wrong:

B, C, D are false.

Question 597

What is a Databricks Repo's purpose?

A. To sync notebooks and files with a Git provider

B. To train models

C. To serve models

D. To store feature tables

Answer 597

Correct: A — Repos sync with Git.

Wrong:

B, C, D are unrelated.

Question 598

Why use Git with Databricks Repos?

A. To track changes and enable collaboration

B. To train faster

C. To serve faster

D. To register models

Answer 598

Correct: A — Git enables versioning and collaboration.

Wrong:

B, C, D are false.

Question 599

What does a Databricks notebook's revision history show?

A. Past versions of the notebook

B. Model metrics

C. Feature tables

D. Cluster configs

Answer 599

Correct: A — revision history shows notebook versions.

Wrong:

B, C, D are unrelated.

Question 600

What is the best practice for deploying ML code across environments?

A. Use Repos, bundles, and CI/CD pipelines
B. Copy notebooks manually
C. Use a single workspace only
D. Skip testing

Answer 600

Correct: A — Repos, bundles, and CI/CD are best practice.

Wrong:

B, C, D are error-prone or unsafe.