

RI.UVT.RO Redesign

Role 6 — WordPress Export Requirements

Generated: 2026-05-12

Context: Plugin activation and CPT/taxonomy configuration done locally in Laragon, but not committed to the repo.

The Problem

WordPress plugin activation, CPTUI post type and taxonomy definitions, and ACF field groups are all stored in the **MySQL database**. They do not appear as files in git. The local setup may be correct, but no one else on the team can replicate it because the configuration only exists on one machine.

Two exports are needed to fix this:

1. Export the CPTUI configuration for custom post types and taxonomies.
2. Enable ACF Local JSON Sync for field groups.

1. Export CPTUI Configuration

What this covers: all custom post types and taxonomies registered in CPTUI, including call, story, resource, programme, people, and any taxonomies.

Steps

1. Open WordPress admin:

```
http://ro.uvt.ro.test/wp-admin
```

2. Go to **CPT UI** → **Tools**.
3. Under **Export Post Types** and **Export Taxonomies**, click **Get Code**. If the current CPTUI version supports JSON export, use the JSON export option instead.
4. Save the output as a file at this path in the repo:

```
wordpress/ro.uvt.ro/cptui-export.json
```

5. Commit and push the file to the role branch.

How Teammates Import It

Teammates can import the configuration from the same menu:

```
CPT UI -> Tools -> Import Post Types / Import Taxonomies
```

They should paste the exported JSON or code into the import area, depending on the export format used.

2. Enable ACF Local JSON Sync

What this covers: all ACF field groups configured for the CPTs.

Steps

1. Create this folder inside the active theme directory:

```
wordpress/ro.uvt.ri/wp-content/themes/[your-active-theme]/acf-json/
```

2. Open WordPress admin and go to **ACF → Field Groups**.
3. Open each field group and click **Save**, even without changes. ACF will detect the `acf-json/` folder and automatically write a `.json` file for each group.
4. Commit the `acf-json/` folder and all generated `.json` files inside it to the repo.

How Teammates Use It

After pulling the repository and copying `wordpress/ro.uvt.ri/` into their local Laragon folder, teammates should open **ACF → Field Groups**. ACF will show a **Sync** notice for any local JSON field groups that are not yet in their database. They should click **Sync** to import the field groups.

```
C:/laragon/www/ro.uvt.ri/
```

3. Verify REST API Exposure

After completing the exports above, confirm that the CPTs are accessible through the REST API.

```
http://ro.uvt.ri.test/wp-json/wp/v2/call  
http://ro.uvt.ri.test/wp-json/wp/v2/story
```

```
http://ro.uvt.ri.test/wp-json/wp/v2/resource
http://ro.uvt.ri.test/wp-json/wp/v2/programme
http://ro.uvt.ri.test/wp-json/wp/v2/people
```

Each endpoint should return a JSON array.

If an endpoint returns 404, the CPT was probably registered without REST support. Enable it in CPTUI under the post type settings:

```
Show in REST API -> True
```

Summary Checklist

- ☐ CPTUI export JSON committed to `wordpress/ro.uvt.ri/cptui-export.json`
- ☐ `acf-json/` folder created in the active theme
- ☐ All ACF field groups re-saved to trigger JSON file generation
- ☐ `acf-json/*.json` files committed to the repo
- ☐ REST API endpoints verified for all five CPTs

Final Deliverable State

Role 6 export work is complete when both database-backed configuration systems have a repo-backed transfer path:

Configuration area	Repo-backed export path
CPTUI post types and taxonomies	<code>wordpress/ro.uvt.ri/cptui-export.json</code>
ACF field groups	<code>wordpress/ro.uvt.ri/wp-content/themes/[your-active-theme]/acf-json/*.json</code>
REST API verification	Confirmed manually through <code>/wp-json/wp/v2/...</code> endpoints