IBM DATA SCIENCE PROFESSIONAL CERTIFICATE

APPLIED DATA SCIENCE CAPSTONE

# SpaceX Falcon 9 First Stage Landing Prediction

Machine Learning Classification, Relational SQL, Geospatial Folium Mapping & Plotly Dash Analytics

**Author:** Muhammad Qasim

**Environment:** IBM Developer Skills Network

**Target:** Commercial Launch Bidding Optimization

**Complete Capstone Public GitHub Repository:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone

# PRESENTATION OUTLINE & PROJECT STRUCTURE

**Agenda mapped directly to Coursera / IBM Grading Template (Slides 2 – 5)**

PPT Slide 2

### 1. Executive Summary & Intro

- **Executive Summary:** Business cost differential ($62M vs. $165M market baseline).
- **Introduction:** First stage reuse mechanics and commercial bidding importance.
- **Methodological Matrix:** 6-stage end-to-end data science lifecycle.

### 2. ETL & Exploratory Analysis

- **Data Collection:** SpaceX REST API & Wikipedia Web Scraping.
- **Wrangling:** Class labeling, missing payload imputations, one-hot encoding.
- **Visual EDA:** 6 required Matplotlib & Seaborn categorical plots.
- **SQL Queries:** 10 explicit database inquiries on SPACEXTBL.

### 3. Interactive Tools & ML Models

- **Folium Maps:** Launch site markers, clusters, and Haversine proximities.
- **Plotly Dash:** Interactive callbacks, pie charts, and range sliders.
- **Predictive ML:** LR, SVM, Decision Tree, and KNN benchmarks.
- **Conclusions & Insights:** Commercial strategies & appendix.

### Primary Project GitHub Repository Link

Direct access to all executed Jupyter notebooks, raw CSV datasets, trained model weights, and the Python Dash application:
https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone

# EXECUTIVE SUMMARY

Commercial space flight cost dynamics and core analytical findings

PPT Slide 3

| $62M | $165M+ | 66.7% | 83.33% |
|---|---|---|---|
| SPACEX LAUNCH PRICE | COMPETITOR BASELINE PRICE | HISTORICAL LANDING SUCCESS | ML TEST MODEL ACCURACY |

## Core Commercial Problem & Opportunity

SpaceX has disrupted the commercial aerospace sector by offering Falcon 9 launches at an advertised price of $62 million, saving clients upwards of $100 million per mission compared to expendable legacy alternatives (e.g., Ariane 5, Atlas V).

This margin is driven by **recovering and reusing the booster first stage**. By predicting whether a first stage will successfully land, a commercial competitor can accurately determine the true operational launch cost, negotiate client contracts, and price competitive bids.

## Key Findings of the Study

- **Orbital Determinants:** Payloads destined for Low Earth Orbit (LEO) and Sun-Synchronous Orbit (SSO) achieve landing success rates of 71% to 100%, whereas Geostationary Transfer Orbits (GTO) exhibit higher recovery volatility (52%) due to high-energy re-entry thermal loads.
- **Launch Site Performance:** Kennedy Space Center LC-39A demonstrates the highest overall success rate (76.2%), serving as the primary pad for crew and complex missions.
- **Predictive Capability:** Classification algorithms achieve **83.33% out-of-sample accuracy**, confirming that telemetry (payload mass, orbit, booster flight iteration, and launch pad) reliably predicts recovery success.

# INTRODUCTION: BACKGROUND & PROBLEM STATEMENT

Understanding rocket stage recovery economics and mission profiling

PPT Slide 4

## First-Stage Recovery Mechanics

The first stage represents approximately **70% of the total vehicle manufacturing cost** (housing 9 Merlin 1D rocket engines, high-grade aluminum-lithium tanks, avionics, and carbon-fiber landing legs).

Following stage separation at Mach 6–10, the booster executes three controlled burns (Boostback burn, Re-entry burn, and Landing burn) guided by hypersonic titanium grid fins to land on either an Autonomous Spaceport Drone Ship (ASDS) or a coastal ground pad (Return to Launch Site - RTLS).

## The Core Business Problem to Solve

If an alternative aerospace company wishes to compete against SpaceX, they must determine:

- *What is the exact probability that a planned launch will successfully recover its first stage?*
- *How do payload mass, target orbit, and launch site constraints dictate recovery viability?*
- *Can machine learning models forecast landing success based purely on pre-launch parameters to guide bidding strategies?*

## Analytical Scope of the Investigation

This study analyzes 90 operational Falcon 9 launches from 2010 to 2020. It combines data engineering across REST APIs and web scraping, SQL relational analytics on IBM Db2/SQLite, interactive geospatial analytics with Folium, real-time application development using Plotly Dash, and supervised classification model tuning using Scikit-Learn.

METHODOLOGY FRAMEWORK

# Section 1: Data Collection, Processing & Methodology

Detailed walkthrough of the SpaceX REST API, Wikipedia Web Scraping, Data Wrangling, Relational SQL, Geospatial Mapping, Dashboard Development, and Machine Learning Modeling Pipelines.

# METHODOLOGICAL ARCHITECTURE OVERVIEW

End-to-End Data Science Lifecycle implemented across 6 distinct phases

PPT Slide 6 & 7

PHASE 1 **Data Collection** API & Web Scraping → PHASE 2 **Data Wrangling** Cleaning & Encoding → PHASE 3 **Exploratory EDA** Seaborn & SQL → PHASE 4 **Geospatial EDA** Folium Proximities → PHASE 5 **Interactive Dash** Plotly Callbacks → PHASE 6 **Predictive ML** GridSearchCV & Eval

## Data Engineering & Preparation

Data was queried from the SpaceX v4 REST API and scraped from Wikipedia launch manifests. Records were cross-validated to handle missing payload figures, filter developmental Falcon 1 flights, and normalize nested JSON dictionaries into structured tabular formats.

## Exploratory & Machine Learning Workflow

Exploratory analytics utilized categorical charts and relational SQL queries on SPACEXTBL. Geospatial and interactive dashboard apps isolated pad-specific trends. Supervised machine learning models were optimized via 10-fold cross-validation to prevent overfitting.

# DATA COLLECTION METHODOLOGY: SPACEX REST API

Querying endpoints, normalizing JSON objects, and extracting booster telemetry

PPT Slide 8 | Rubric 1.5

**Dedicated Completed API Notebook:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/01_spacex_data_collection_api.ipynb

STEP 1
**HTTP GET Request**
api.spacexdata.com/v4/launches/past

→

STEP 2
**pd.json_normalize**
Flatten nested metadata

→

STEP 3
**Booster Filtering**
Keep Falcon 9; remove Falcon 1

→

STEP 4
**Sub-Endpoint Queries**
/payloads, /launchpads, /cores

## API Extraction Workflow & Key Phrases

- **Endpoint Interrogation:** Sent GET requests via Python's `requests` library to `https://api.spacexdata.com/v4/launches/past`.
- **JSON Normalization:** Unpacked semi-structured JSON structures using `pd.json_normalize()` into flat tabular representations.
- **Telemetry Extraction:** Extracted flight parameters: `FlightNumber`, `Date`, `BoosterVersion`, `PayloadMass`, `Orbit`, `LaunchSite`, and `LandingOutcome`.

## Dataset Cleaning & Scope Filtering

- **Booster Filtration:** Filtered out 4 early Falcon 1 suborbital tests, isolating exactly **90 operational Falcon 9 launches**.
- **Sub-Resource Expansion:** Extracted core serial numbers, landing pad IDs, and customer classifications by issuing recursive sub-requests to linked API endpoints.
- **Output Integrity:** Verified dataframe dimensions (90 rows, 17 columns) before passing to data wrangling.

# DATA COLLECTION METHODOLOGY: WEB SCRAPING

Extracting launch manifests from Wikipedia using BeautifulSoup

PPT Slide 9 | Rubric 1.6

**Dedicated Completed Web Scraping Notebook:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/02_spacex_data_collection_scraping.ipynb

STEP 1
**HTTP Request**
Falcon 9 Launch Wikipedia Page

→

STEP 2
**HTML DOM Parsing**
BeautifulSoup(response.text, 'html.parser')

→

STEP 3
**Find Tables**
soup.find_all('table', 'wikitable')

→

STEP 4
**Parse Rows & Cells**
Extract Flight, Date, Booster, Outcome

## Web Scraping Process & Technical Execution

- **HTML Parsing:** Retrieved the Wikipedia article *"List of Falcon 9 and Falcon Heavy launches"* and constructed a DOM tree using `BeautifulSoup`.
- **Table Identification:** Located target tables containing the class attribute `wikitable plainrowheaders collapsible`.
- **Cell Extraction:** Extracted table headers (`<th>`) to construct column definitions, followed by row iterations across each `<tr>` element to gather mission observations.

## Reconciliation & Validation

- **String Cleansing:** Stripped HTML footnote reference tags (e.g., `[17]`, `[note 1]`), newlines, and non-breaking spaces.
- **Cross-Validation:** Reconciled scraped flight records against the API dataset to resolve missing or unrecorded early payload masses.
- **Outcome Verification:** Confirmed landing pad descriptions (LZ-1, LZ-2, OCISLY, JRTI) against official mission statements.

# DATA WRANGLING & PREPROCESSING METHODOLOGY

Handling missing figures, target binary encoding, and feature space expansion

PPT Slide 10 | Rubric 1.7

**Dedicated Completed Data Wrangling Notebook:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/03_spacex_eda_data_wrangling.ipynb

## 1. Imputation of Missing Payloads

Telemetry for classified government or satellite rideshares lacked explicit payload mass figures in the raw API feed.

Calculated the mean payload mass across all known commercial flights (**6,123.55 kg**) and imputed missing records using `df['PayloadMass'].fillna()` to preserve sample size (N=90).

## 2. Binary Target Variable: Class

Engineered the target label `Class` from the raw categorical landing outcome column:

- **Class = 1 (Successful Landing):** `True ASDS` (drone ship landing) and `True RTLS` (ground pad landing). Total = **60 launches**.
- **Class = 0 (Unsuccessful Landing):** `False ASDS`, `False RTLS`, `None ASDS`, `None None`, and ocean water crashes. Total = **30 launches**.

## 3. One-Hot Feature Encoding

Applied `pd.get_dummies()` to transform categorical predictors into numeric representations:

- **Encoded Categoricals:** `Orbit` (11 categories), `LaunchSite` (3 sites), `LandingPad` (5 pads), and booster `Serial`.
- **Final Model Input:** Expanded feature space to **83 independent numeric features**, scaled via `StandardScaler()`.

**Data Pipeline Verification:** The resulting dataset comprises 90 rows and 83 normalized predictor columns. Missing values were eliminated, and target class distribution (66.7% success, 33.3% failure) reflects real-world operations.

# EDA WITH DATA VISUALIZATION METHODOLOGY

Analytical chart selections and statistical visualization strategy

PPT Slide 11 | Rubric 1.8

**Dedicated Completed Data Visualization Notebook:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/EDA_Data_Visualization.ipynb

## Visualization Library & Chart Strategy

Exploratory Data Analysis utilized Python's **Matplotlib** and **Seaborn** libraries to inspect correlations, distributions, and multi-variable interactions:

- **Scatter Plots (`sns.catplot`, `plt.scatter`):** Selected to plot flight numbers and payload masses across categorical launch sites and orbital destinations, with hue set to `Class` (Success vs. Failure).
- **Grouped Bar Charts (`sns.barplot`):** Chosen to display mean landing success ratios grouped across the 10 distinct orbital configurations.
- **Line Plots (`sns.lineplot`):** Designed to calculate and display the longitudinal annual success rate trend from 2010 through 2020.

## Specific Questions Addressed by Visual EDA

- *Does launch location correlate with higher payload capacity or success rate?* Evaluated by comparing Cape Canaveral (CCAFS), Kennedy Space Center (KSC), and Vandenberg AFB (VAFB).
- *Does payload mass constrain booster recovery?* Analyzed across low (<3,000 kg), medium (3,000–6,000 kg), and heavy (>8,000 kg) payload profiles.
- *Are certain orbital trajectories inherently unrecoverable?* Investigated by isolating Polar, GTO, LEO, ISS, and interplanetary launch vectors.
- *Is there evidence of institutional learning over time?* Assessed via annual recovery rate progression.

# EDA WITH RELATIONAL SQL METHODOLOGY

Database configuration, SQL query execution, and aggregate analytics on SPACEXTBL

PPT Slide 12 | Rubric 1.9

**Dedicated Completed SQL Notebook:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/04_spacex_eda_sql.ipynb

## Relational Database Architecture

The consolidated Falcon 9 dataset was loaded into an SQL database (SQLite / IBM Db2) under the table identifier **SPACEXTBL**. Queries were executed using the `ipython-sql` extension directly within Jupyter Notebook.

Relational queries enabled exact deterministic filtering, subqueries, group-by aggregations, and date-range evaluations to cross-verify visual and algorithmic findings.

## Summary of 10 Required SQL Inquiries

- **Task 1:** Identify all distinct launch sites in the dataset.
- **Task 2:** Query 5 launch records from sites beginning with 'CCA'.
- **Task 3:** Calculate total payload mass carried on behalf of NASA.
- **Task 4:** Determine average payload carried by Falcon 9 v1.1 boosters.
- **Task 5:** Retrieve the date of the first successful ground pad landing.
- **Task 6:** Identify drone ship landing successes for payloads 4,000–6,000 kg.
- **Task 7:** Count total successful versus failed mission outcomes.
- **Task 8:** List booster versions carrying the maximum payload mass.
- **Task 9:** Retrieve 2015 drone ship landing failure details.
- **Task 10:** Rank landing outcomes between 2010-06-04 and 2017-03-20.

# INTERACTIVE GEOSPATIAL ANALYTICS: FOLIUM METHODOLOGY

Spatial plotting, MarkerCluster groupings, and proximity analysis architecture

PPT Slide 13 | Rubric 1.10

**Dedicated Completed Folium Notebook:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/Interactive_Visual_Analytics_Folium.ipynb

## 1. Launch Pad Coordinate Plotting

Instantiated a base map centered on the continental United States using `folium.Map(location=[28.5, -80.6], zoom_start=4)`.

Added `folium.Circle` and `folium.Marker` elements for all launch complexes: Cape Canaveral SLC-40, Kennedy Space Center LC-39A, and Vandenberg SLC-4E.

## 2. Outcome Clustering (MarkerCluster)

Applied `folium.plugins.MarkerCluster` to manage dense, overlapping launch pins across identical launch pad coordinates.

Dynamic marker coloring: assigned **green** icons to successful recoveries (`Class=1`) and **red** icons to landing failures (`Class=0`) with popup mission details.

## 3. Haversine Distance Calculations

Implemented the Haversine trigonometric formula in Python to compute geodesic distances between launch complexes and nearby infrastructure.

Rendered `folium.PolyLine` vectors displaying exact distances to coastlines, railways, highways, and municipal population centers.

# INTERACTIVE DASHBOARD METHODOLOGY: PLOTLY DASH

Real-time analytical web application with dynamic callbacks and input widgets

PPT Slide 14 | Rubric 1.10

**Dedicated Completed Dash Python Script:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/spacex_dash_app.py

## Application Layout & Reactive UI Components

- **Application Framework:** Built using `dash`, `dash_html_components`, `dash_core_components`, and `plotly.express`.
- **Dropdown Selector (`site-dropdown`):** Allows users to toggle between viewing aggregated metrics across all facilities (`ALL`) or isolating specific pads (`CCAFS LC-40`, `CCAFS SLC-40`, `KSC LC-39A`, `VAFB SLC-4E`).
- **Payload RangeSlider (`payload-slider`):** Interactive dual-handle slider spanning 0 kg to 10,000 kg in 1,000 kg intervals to filter records dynamically.

## Reactive Callback Architecture ( `@app.callback` )

- **Callback 1 (Success Pie Chart):** Listens to `site-dropdown`. If 'ALL' is selected, outputs total successful launches per site. If a specific site is chosen, renders a binary success vs. failure pie chart for that facility.
- **Callback 2 (Payload Scatter Plot):** Listens to both `site-dropdown` and `payload-slider` inputs. Renders a scatter plot of payload mass versus landing outcome, colored by booster version category.

# PREDICTIVE ANALYSIS (CLASSIFICATION) METHODOLOGY

Machine learning pipelines, hyperparameter search, and evaluation protocol

PPT Slide 15 | Rubric 1.10

**Dedicated Completed ML Classification Notebook:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone/blob/main/07_spacex_machine_learning_prediction.ipynb

## Data Partitioning & Preprocessing Pipeline

The feature matrix X (83 one-hot encoded variables) and target array Y (binary `Class`) were processed as follows:

- **Standardization:** Scaled feature variables using `StandardScaler().fit_transform(X)` to zero mean and unit variance.
- **Train/Test Split:** Applied `train_test_split(test_size=0.2, random_state=2)`, reserving **72 training samples** and **18 unseen test samples**.

## Algorithms & GridSearchCV Optimization

Four classification algorithms were trained using **10-fold cross-validation** via `GridSearchCV` to optimize hyperparameters:

- **Logistic Regression:** Evaluated regularization strengths C [0.01, 0.1, 1.0], penalty norms (`l1`, `l2`), and solvers (`lbfgs`, `liblinear`).
- **Support Vector Machine (SVM):** Tuned kernel functions (`linear`, `rbf`, `poly`, `sigmoid`), C, and `gamma`.
- **Decision Tree Classifier:** Tuned split criteria (`gini`, `entropy`), maximum depths (2 to 20), and minimum split samples.
- **K-Nearest Neighbors (KNN):** Tested neighbor counts k (1 to 10), distance metrics (p=1 Manhattan, p=2 Euclidean), and leaf sizes.

EMPIRICAL DISCOVERIES

# Section 2: Exploratory Data Analysis Results


Presentation of the 6 core visualization charts (Flight Number, Payload Mass, Orbital Recovery, and Longitudinal Trends) alongside 10 explicit Relational SQL query outputs.

# EDA CHART 1: FLIGHT NUMBER VS. LAUNCH SITE

Categorical scatter plot evaluating landing outcome progression by launch complex

PPT Slide 18 | Rubric 1.11

## Visual Representation




## Analytical Findings & Explanations


- **Early Developmental Phase (Flights 1 to 25):** Concentrated almost exclusively at **CCAFS SLC-40**, with a low success rate reflecting initial controlled landing trials.
- **Pad Diversification (Flights 26 to 60):** Launches expanded into **KSC LC-39A** and **VAFB SLC-4E**. A sharp rise in green points illustrates improved flight control and reliability.
- **Operational Maturity (Flights 61 to 90):** Success rates exceed 85% across all sites, demonstrating that recovery procedures matured into reliable operations.

# EDA CHART 2: PAYLOAD MASS VS. LAUNCH SITE

Analyzing pad payload capacities and launch site landing correlations

PPT Slide 19 | Rubric 1.11

## Visual Representation




## Analytical Findings & Explanations


- **Vandenberg (VAFB SLC-4E) Operational Ceiling:** No launches from VAFB exceeded 9,600 kg. High-inclination polar launches impose energy penalties that restrict maximum payload capacity.
- **Heavy Payload Performance at KSC LC-39A:** Heavy missions (>8,000 kg, including Starlink clusters and deep-space missions) launched from KSC LC-39A show high landing success on drone ships.
- **Cape Canaveral (CCAFS SLC-40) Volume:** Supports a broad spread of commercial payloads (2,000 to 7,000 kg). Failures cluster in earlier sub-5,000 kg flights rather than recent heavy missions.

# EDA CHART 3: LANDING SUCCESS RATE VS. ORBIT TYPE

Categorical bar chart displaying landing success ratios across all 10 orbital configurations

PPT Slide 20 | Rubric 1.11

## Orbital Success Rate Distribution




## Analytical Findings & Explanations


- **Perfect Recovery Profiles (100%):** Orbits such as **ES-L1**, **GEO**, **HEO**, and **SSO** show 100% recovery in this dataset, as these missions generally employed mature booster configurations.
- **Constellation Orbits (VLEO & LEO):** Very Low Earth Orbit (Starlink missions) achieved an **85% recovery rate**, benefiting from standardized flight profiles.
- **GTO Flight Profile Challenges (52%):** Geostationary Transfer Orbits require higher stage-separation velocity, leaving less residual propellant for the re-entry deceleration burn and creating harsher aerodynamic conditions during recovery.

# EDA CHART 4: FLIGHT NUMBER VS. ORBIT TYPE

Analyzing orbital mission assignments across flight history

PPT Slide 21 | Rubric 1.11

## Visual Representation




## Analytical Findings & Explanations


- **LEO Mission Evolution:** Low Earth Orbit carried the earliest flights (1–20), serving as test flights where landing techniques were developed.
- **GTO Flight Density:** GTO commercial communications satellites dominated the middle flight sequence (Flights 25–65), showing an increasing proportion of successful recoveries over time.
- **VLEO Dominance in Late Flights:** Flights beyond #65 are dominated by VLEO missions (Starlink deployment), which show consistently successful recoveries using Block 5 boosters.

# EDA CHART 5: PAYLOAD MASS VS. ORBIT TYPE

Assessing payload mass ranges and recovery outcomes across orbital regimes

PPT Slide 22 | Rubric 1.11

## Visual Representation




## Analytical Findings & Explanations


- **Heavy Payloads to VLEO (15,600 kg):** Maximum payload launches correspond to internal Starlink missions. Despite high payload mass, low-altitude orbital insertion allows sufficient fuel reserves for drone ship landings.
- **GTO Payload Sensitivity:** GTO payloads cluster between 3,000 kg and 6,500 kg. When GTO payload exceeds 5,000 kg, landing margins tighten due to increased fuel consumption during ascent.
- **ISS Resupply Operations (2,000–4,500 kg):** Dragon resupply missions show high recovery rates on both drone ships and ground landing pads.

# EDA CHART 6: ANNUAL SUCCESS RATE PROGRESSION (2010 – 2020)

Line chart tracking longitudinal landing success rates and technological maturity

PPT Slide 23 | Rubric 1.11

## Visual Representation




## Analytical Findings & Explanations

- **Experimental Era (2010–2013):** 0% recovery success. Boosters were expendable or conducted ocean water landing experiments without physical recovery assets.
- **First Recoveries (2014–2015):** Success rate increased to ~33% with initial ocean platform trials, culminating in the first ground pad landing in December 2015.
- **Fleet Maturity (2017–2020):** Block 5 booster upgrades (titanium grid fins, upgraded heat shields, higher thrust) brought operational success rates to 80–90%.

# SQL TASK 1: IDENTIFY DISTINCT LAUNCH SITES

Querying all unique launch pad facilities recorded in SPACEXTBL

PPT Slide 24 | Rubric 1.12

## Executed SQL Query

```
SELECT DISTINCT Launch_Site FROM SPACEXTBL;
```

## Returned Query Result Set

| # | LAUNCH_SITE | OPERATIONAL STATUS |
|---|---|---|
| 1 | CCAFS LC-40 | Active (Cape Canaveral Air Force Station) |
| 2 | CCAFS SLC-40 | Active (Renamed Space Launch Complex 40) |
| 3 | KSC LC-39A | Active (Kennedy Space Center Pad 39A) |
| 4 | VAFB SLC-4E | Active (Vandenberg Space Force Base Pad 4E) |

## Business Interpretation

SpaceX operates from two primary geographical regions: the **East Coast (Florida)** for equatorial, ISS, and GTO flights, and the **West Coast (California)** for polar-orbit missions.

The distinction between CCAFS LC-40 and CCAFS SLC-40 reflects administrative naming updates following launch complex refurbishment.

# SQL TASK 2: RETRIEVE RECORDS BEGINNING WITH 'CCA'

Filtering the first 5 records originating from Cape Canaveral facilities

PPT Slide 25 | Rubric 1.12

## Executed SQL Query

```
SELECT Flight_Number, Date, Launch_Site, Booster_Version, Payload_Mass__kg_ FROM SPACEXTBL WHERE Launch_Site LIKE 'CCA%' LIMIT 5;
```

## Returned Query Result Set

| F# | DATE | LAUNCH_SITE | BOOSTER | MASS (KG) |
|---|---|---|---|---|
| 1 | 2010-06-04 | CCAFS LC-40 | F9 v1.0 B0003 | 0 |
| 2 | 2010-12-08 | CCAFS LC-40 | F9 v1.0 B0004 | 0 |
| 3 | 2012-05-22 | CCAFS LC-40 | F9 v1.0 B0005 | 525 |
| 4 | 2012-10-08 | CCAFS LC-40 | F9 v1.0 B0006 | 500 |
| 5 | 2013-03-01 | CCAFS LC-40 | F9 v1.0 B0007 | 677 |

## Business Interpretation

The query confirms that the earliest Falcon 9 missions launched from **Cape Canaveral LC-40** carrying lightweight prototype capsules and Dragon test articles (under 700 kg).

Zero-mass entries represent non-commercial maiden qualification test flights carrying telemetry instrumentation rather than revenue payloads.

# SQL TASK 3: CALCULATE TOTAL PAYLOAD MASS CARRIED FOR NASA

Summing commercial resupply and scientific mission payload tonnage

PPT Slide 26 | Rubric 1.12

## Executed SQL Query

```
SELECT SUM(PAYLOAD_MASS__KG_) AS Total_NASA_Payload_Mass FROM SPACEXTBL WHERE Customer LIKE '%NASA%';
```

## Returned Query Result Set

| CUSTOMER FILTER | CALCULATED TOTAL PAYLOAD | TOTAL MISSIONS INCLUDED |
|---|---|---|
| %NASA% (Commercial Resupply, CRS, Scientific) | **99,965 kg** | 23 Dedicated Missions |

## Business Interpretation

NASA accounts for approximately **100 metric tons** of payload delivered by Falcon 9 across the study window.

NASA's Commercial Resupply Services (CRS) contract provided consistent flight cadence and operational revenue, enabling SpaceX to iteratively test and refine booster recovery maneuvers during operational missions.

# SQL TASK 4: AVERAGE PAYLOAD MASS FOR BOOSTER VERSION F9 V1.1

Evaluating launch mass capacities during the intermediate booster lifecycle

PPT Slide 27 | Rubric 1.12

## Executed SQL Query

```sql
SELECT AVG(PAYLOAD_MASS__KG_) AS Avg_Payload_F9_v1_1 FROM SPACEXTBL WHERE Booster_Version LIKE '%F9 v1.1%';
```

## Returned Query Result Set

| BOOSTER VERSION FILTER | AVERAGE PAYLOAD | OPERATIONAL WINDOW |
|---|---|---|
| Falcon 9 v1.1 (All Sub-Variants) | **2,928.4 kg** | September 2013 – January 2016 |

## Business Interpretation

The Falcon 9 v1.1 variant achieved an average payload delivery of **2,928 kg** per mission.

This variant introduced lengthened propellant tanks and the octagonal Merlin engine arrangement (Octaweb), demonstrating increased lift capability over the original v1.0 design while remaining below the 5,000+ kg capacity of subsequent Block 5 configurations.

# SQL TASK 5: DATE OF FIRST SUCCESSFUL GROUND PAD LANDING

Locating the historical milestone for first-stage recovery

PPT Slide 28 | Rubric 1.12

## Executed SQL Query

```sql
SELECT MIN(Date) AS First_Successful_Ground_Pad_Date FROM SPACEXTBL WHERE Landing_Outcome = 'Success (ground pad)';
```

## Returned Query Result Set

| TARGET OUTCOME | HISTORICAL DATE | BOOSTER / MISSION |
|---|---|---|
| Success (ground pad) | 2015-12-22 | Booster B1019 (OG2 Mission, LZ-1) |

## Business Interpretation

On **December 22, 2015**, Falcon 9 flight 20 deployed 11 ORBCOMM satellites and returned its first-stage booster (B1019) to Landing Zone 1 at Cape Canaveral.

This mission marked the first successful vertical recovery of an orbital-class rocket booster in commercial aerospace history, providing empirical validation of the reusable launch concept.

# SQL TASK 6: DRONE SHIP RECOVERIES (PAYLOAD 4,000 TO 6,000 KG)

Filtering mid-heavy commercial recoveries landing on Autonomous Spaceport Drone Ships

PPT Slide 29 | Rubric 1.12

## Executed SQL Query

```
SELECT Booster_Version, PAYLOAD_MASS__KG_, Landing_Outcome, Date FROM SPACEXTBL WHERE Landing_Outcome = 'Success (drone ship)' AND PAYLOAD_MASS__KG_ BETWEEN 4000 AND 6000;
```

## Returned Query Result Set

| BOOSTER VERSION | MASS (KG) | OUTCOME | LAUNCH DATE |
|---|---|---|---|
| F9 FT B1022 | 4,696 kg | Success (drone ship) | 2016-05-06 |
| F9 FT B1026 | 4,600 kg | Success (drone ship) | 2016-08-14 |
| F9 FT B1021.2 | 5,300 kg | Success (drone ship) | 2017-03-30 |
| F9 FT B1031.2 | 5,200 kg | Success (drone ship) | 2017-10-11 |

## Business Interpretation

This query identifies successful recoveries for payloads between 4,000 and 6,000 kg, including the re-flight of booster **B1021.2 on March 30, 2017**.

This marked the first commercial re-flight and re-recovery of an orbital booster, providing a baseline metric for reusability economics.

# SQL TASK 7: TOTAL NUMBER OF SUCCESSFUL AND FAILURE OUTCOMES

Aggregating primary mission delivery success rates across SPACEXTBL

PPT Slide 30 | Rubric 1.12

## Executed SQL Query

```
SELECT Mission_Outcome, COUNT(*) AS Total_Count FROM SPACEXTBL GROUP BY Mission_Outcome;
```

## Returned Query Result Set

| MISSION OUTCOME CATEGORY | COUNT | PERCENT |
|---|---|---|
| Success | 98 | 97.0% |
| Success (payload status unclear) | 1 | 1.0% |
| Failure (in flight) | 1 | 1.0% |
| Failure (pre-launch / Amos-6) | 1 | 1.0% |

## Business Interpretation

Primary mission delivery succeeded in **98% of all flights**. Even when booster recovery was not achieved, the upper stage placed customer payloads into the designated orbit in almost all instances.

This reliability metric illustrates that first-stage recovery testing did not compromise baseline mission delivery success.

# SQL TASK 8: BOOSTER VERSIONS CARRYING MAXIMUM PAYLOAD MASS

Identifying the boosters supporting maximum-mass commercial flights

PPT Slide 31 | Rubric 1.12

## Executed SQL Query

```
SELECT Booster_Version, PAYLOAD_MASS__KG_ FROM SPACEXTBL WHERE PAYLOAD_MASS__KG_ = ( SELECT MAX(PAYLOAD_MASS__KG_) FROM SPACEXTBL );
```

## Returned Query Result Set

| BOOSTER VERSION | MAX PAYLOAD MASS | FLIGHT MISSION |
|---|---|---|
| F9 B5 B1048.4 | **15,600 kg** | Starlink v1.0 L1 |
| F9 B5 B1049.4 | **15,600 kg** | Starlink v1.0 L2 |
| F9 B5 B1051.3 | **15,600 kg** | Starlink v1.0 L3 |
| F9 B5 B1056.4 | **15,600 kg** | Starlink v1.0 L4 |
| F9 B5 B1058.3 | **15,600 kg** | Starlink v1.0 L8 |
| F9 B5 B1060.2 | **15,600 kg** | Starlink v1.0 L11 |

## Business Interpretation

The maximum payload recorded across the dataset is **15,600 kg**, representing full stacks of 60 Starlink satellites launched to Low Earth Orbit.

All boosters handling this mass belong to the **Falcon 9 Block 5** configuration, which was engineered for repeated turnaround without full teardown between flights.

# SQL TASK 9: 2015 FAILED DRONE SHIP LANDING DETAILS

Retrieving booster versions, launch sites, and landing failure descriptions

PPT Slide 32 | Rubric 1.12

## Executed SQL Query

```
SELECT Booster_Version, Launch_Site, Landing_Outcome, Date FROM SPACEXTBL WHERE Landing_Outcome = 'Failure (drone ship)' AND substr(Date, 1, 4) = '2015';
```

## Returned Query Result Set

| BOOSTER VERSION | LAUNCH SITE | LANDING OUTCOME | DATE |
|---|---|---|---|
| F9 v1.1 B1012 | CCAFS LC-40 | Failure (drone ship) | 2015-01-10 |
| F9 v1.1 B1015 | CCAFS LC-40 | Failure (drone ship) | 2015-04-14 |

## Business Interpretation

In 2015, two controlled recovery attempts on the drone ship *Just Read the Instructions* resulted in hard impacts (hydraulic fluid exhaustion and sticking throttle valves).

Telemetry from these early attempts informed updates to grid-fin hydraulic reserves and throttle response times, contributing to the first successful ocean recovery in April 2016 (CRS-8).

# SQL TASK 10: RANK LANDING OUTCOMES (2010-06-04 TO 2017-03-20)

Rank-ordered frequency analysis of landing results across the initial 7-year era

PPT Slide 33 | Rubric 1.12

## Executed SQL Query

```
SELECT Landing_Outcome, COUNT(*) AS Outcome_Count FROM SPACEXTBL WHERE Date BETWEEN '2010-06-04' AND '2017-03-20' GROUP BY Landing_Outcome ORDER BY Outcome_Count DESC;
```

## Returned Query Result Set

| RANK | LANDING_OUTCOME | COUNT | CATEGORY |
|---|---|---|---|
| 1 | No Attempt | 10 | Expendable Mission |
| 2 | Success (drone ship) | 5 | Ocean Recovery |
| 3 | Failure (drone ship) | 5 | Ocean Recovery Attempt |
| 4 | Success (ground pad) | 3 | Land Recovery |
| 5 | Controlled (ocean) | 3 | Water Landing Trial |
| 6 | Uncontrolled (ocean) | 2 | Water Landing Trial |

## Business Interpretation

Across the initial 7-year operational window, No Attempt was the most frequent outcome (10 flights), reflecting the expendable architecture of early Falcon 9 versions.


Drone ship successes (5) and failures (5) were initially evenly split, marking the gradual transition from experimental trials to operational recovery routines.

# GEOSPATIAL ANALYTICS 1: GLOBAL LAUNCH SITE LOCATIONS

Interactive geographical mapping of Cape Canaveral, Kennedy Space Center, and Vandenberg

PPT Slide 35 | Rubric 1.13

## Folium Launch Pad Map Visualization




## Geographical Site Selection Rationale


- **East Coast Operations (Florida - 28.5° N):** Located closer to the equator to leverage Earth's rotational velocity (~410 m/s eastward boost), reducing propellant requirements for GTO and equatorial orbits.
- **West Coast Operations (California - 34.6° N):** Vandenberg supports southern flight corridors over the Pacific Ocean, enabling polar and sun-synchronous insertions without overflying populated areas.
- **Downrange Safety Corridors:** Both locations border open water, providing designated emergency ditching and booster recovery zones.

# GEOSPATIAL ANALYTICS 2: LAUNCH OUTCOME MARKER CLUSTERS

Visualizing landing outcomes and success densities across launch facilities

PPT Slide 36 | Rubric 1.13

## Folium MarkerCluster Visualization




## Spatial Clustering Findings

- **Kennedy Space Center (KSC LC-39A):** Demonstrates the highest concentration of successful green markers. Over 76% of all launches from Pad 39A achieved successful booster recoveries.
- **Cape Canaveral (CCAFS SLC-40):** Contains an even split between early red markers (pre-2016 development flights) and recent green markers (operational Block 5 commercial missions).
- **Vandenberg (VAFB SLC-4E):** Primarily green markers for polar satellite insertions, showing consistent drone ship recoveries in the Pacific.

# GEOSPATIAL ANALYTICS 3: LAUNCH SITE PROXIMITY ANALYSIS

Haversine distance measurements to coastlines, railways, highways, and cities

PPT Slide 37 | Rubric 1.13

## Infrastructure Proximity Measurements

| ENTITY | CALCULATED DISTANCE | STRATEGIC JUSTIFICATION |
|---|---|---|
| **Coastline** | **0.52 km** | Minimizes time over land, directing initial flight trajectories over open water. |
| **Railway Line** | **1.31 km** | Enables delivery of oversized rocket stages, engine assemblies, and propellants. |
| **Highway (NASA Pkwy)** | **0.75 km** | Provides transportation access for technical teams and support vehicles. |
| **City (Titusville)** | **28.4 km** | Maintains an acoustic and blast safety perimeter away from populated areas. |

## Operational Insights


- **Safety Clearance:** Launch complexes are situated at least **25 km away from major population centers** to keep noise, blast overpressures, and launch failure hazards outside residential areas.
- **Logistical Access:** Complexes maintain close proximity (<2 km) to heavy railways and highways to facilitate transit of oversized first-stage cores from Hawthorne, California.
- **Coastal Alignment:** Proximity to the coast (<1 km) minimizes overland flight duration during the initial ascent phase.

# INTERACTIVE DASHBOARD 1: TOTAL SUCCESS LAUNCHES BY SITE

Plotly Dash pie chart displaying the distribution of successful booster landings across all pads

PPT Slide 39 | Rubric 1.14

## Plotly Dash Pie Chart (All Sites Selected)




## Analytical Findings & Explanations


- **Kennedy Space Center (KSC LC-39A) Share:** Accounts for **41.7% of all successful first-stage landings**, leading all facilities in total recoveries.
- **Cape Canaveral (CCAFS SLC-40) Share:** Generated **33.3% of total recoveries**, reflecting a high cadence of commercial satellite launches.
- **Vandenberg (VAFB SLC-4E) Share:** Represents **16.7% of total recoveries**, dedicated to polar orbital insertions.

# INTERACTIVE DASHBOARD 2: SUCCESS RATIO FOR HIGHEST SUCCESS SITE

Drill-down pie chart isolating Kennedy Space Center LC-39A (76.2% success rate)

PPT Slide 40 | Rubric 1.14

## Plotly Dash Pie Chart (KSC LC-39A Filtered)




## Site-Specific Performance Insights


- **Recovery Leadership:** Filtering the dashboard to **KSC LC-39A** reveals a **76.2% landing success rate**, the highest of all SpaceX facilities.
- **Pad Utilization Context:** SpaceX began utilizing Pad 39A in 2017 after retrofitting the historic Apollo/Shuttle pad. Because this occurred during Falcon 9's operational maturity, Pad 39A avoided the early experimental failures seen at CCAFS.
- **Mission Types:** Pad 39A is used for high-profile missions, including Crew Dragon astronaut launches and heavy commercial payloads.

# INTERACTIVE DASHBOARD 3: PAYLOAD VS. OUTCOME RANGESLIDER

Plotly Dash interactive scatter plot evaluating landing outcome across payload mass intervals

PPT Slide 41 | Rubric 1.14

## RangeSlider Filtered Scatter Plot (0 to 10,000 kg)




## RangeSlider Filtering Findings

- **Optimal Recovery Window (2,000–4,500 kg):** Payloads in this range exhibit the highest landing success density across all booster versions, balancing ascent fuel needs with re-entry reserve margins.
- **Mid-Range Variance (4,500–6,500 kg):** Shows greater outcome spread, primarily involving GTO missions where higher stage-separation speeds make re-entry conditions more demanding.
- **Heavy Payload Category (>6,500 kg):** Demonstrates consistent recovery when paired with Falcon 9 Block 5 boosters, confirming that booster configuration is a key recovery determinant for heavy payloads.

# PREDICTIVE MACHINE LEARNING MODEL EVALUATION

Benchmark comparison, hyperparameter specifications, and test accuracy metrics

PPT Slide 43 | Rubric 1.15

## Classification Algorithm Performance Table

| ALGORITHM | OPTIMAL HYPERPARAMETERS (GRIDSEARCHCV) | 10-FOLD CV ACCURACY | TEST ACCURACY (18 SAMPLES) |
|---|---|---|---|
| **Logistic Regression** | `{'C': 0.01, 'penalty': 'l2', 'solver': 'lbfgs'}` | 84.64% | **83.33%** |
| **Support Vector Machine (SVM)** | `{'C': 1.0, 'gamma': 0.03, 'kernel': 'sigmoid'}` | 84.82% | **83.33%** |
| **Decision Tree Classifier** | `{'criterion': 'gini', 'max_depth': 4, 'splitter': 'best'}` | **87.14%** | **83.33%** |
| **K-Nearest Neighbors (KNN)** | `{'algorithm': 'auto', 'n_neighbors': 10, 'p': 1}` | 84.82% | **83.33%** |

## Model Selection Analysis

All four algorithms achieved identical **83.33% test accuracy** on the 18 unseen validation samples (correctly predicting 15 of 18 outcomes).

The **Decision Tree Classifier** achieved the highest 10-fold cross-validation score (**87.14%**) on training data, demonstrating stronger capability to capture nonlinear threshold boundaries (e.g., payload mass limits for GTO orbits).

## Production Implementation Recommendation


The **Decision Tree Classifier** is selected as the recommended production model because it provides clear interpretability, transparent decision rules, and actionable threshold logic for commercial bidding teams.

# CLASSIFICATION ACCURACY COMPARISON CHART

Visual benchmark of cross-validation vs. test set performance across all algorithms

PPT Slide 43b | Rubric 1.15

## Visual Accuracy Distribution (CV vs. Test)




## Evaluation Analysis & Generalization


- **Consistent Test Accuracy:** All four models achieved an identical test accuracy of **83.33%** (15 correct out of 18 unseen test samples).
- **Cross-Validation Distinction:** 10-fold cross-validation identifies the **Decision Tree Classifier (87.14%)** as the top-performing architecture on training splits, marginally outperforming SVM (84.82%) and Logistic Regression (84.64%).
- **Generalization Stability:** The close gap between CV scores (84–87%) and test accuracy (83.33%) confirms that models did not overfit the training feature space.

# CONFUSION MATRIX: BEST PERFORMING MODEL

Granular error breakdown and classification performance metrics across test data

PPT Slide 44 | Rubric 1.15

## Test Data Confusion Matrix (18 Samples)




## Diagnostic Performance Metrics

| METRIC | FORMULA | SCORE |
|---|---|---|
| **Accuracy** | (TP + TN) / Total | **83.33%** (15/18) |
| **Precision (Success)** | TP / (TP + FP) | **80.00%** (12/15) |
| **Recall / Sensitivity** | TP / (TP + FN) | **100.0%** (12/12) |
| **Specificity (Failure)** | TN / (TN + FP) | **50.00%** (3/6) |
| **F1-Score** | 2 × (Prec × Rec) / (Prec + Rec) | **88.89%** |


**Operational Meaning:** The model achieves **100% recall**, meaning zero actual landing successes were misclassified as failures. The primary error mode stems from 3 false positives (failed experimental landings that shared feature attributes with routine successful missions).

# DECISION TREE ARCHITECTURE & FEATURE THRESHOLDS

Interpretable decision rules driving first stage recovery predictions

PPT Slide 44b | Rubric 1.15

## Decision Logic Tree Diagram




## Feature Importance Ranking

| PREDICTOR FEATURE | RELATIVE WEIGHT | IMPACT DIRECTION |
|---|---|---|
| `FlightNumber` (Experience) | **34.2%** | Positive (Maturity improves landing odds) |
| `PayloadMass` | **23.6%** | Negative when combined with high-energy orbits |
| `Orbit_GTO` / `Orbit_VLEO` | **18.4%** | VLEO positive (+85%); GTO volatile (52%) |
| `LaunchSite_KSC LC-39A` | **13.1%** | Positive (Highest facility success: 76.2%) |
| Booster Re-flight Iteration | **10.7%** | Positive (Block 5 boosters reliably recovered) |

# CONCLUSIONS & COMMERCIAL RECOMMENDATIONS

Synthesis of findings and actionable business bidding strategies

PPT Slide 45 | Rubric 1.13

## Core Empirical Conclusions

- **Technological Learning Curve:** First-stage recovery transitioned from a 0% experimental concept (2010–2013) into an operational routine exceeding **85% reliability by 2020**.
- **Orbital Trajectory Sensitivity:** LEO and SSO missions present low recovery risk (>75% success), whereas GTO missions require conservative contingency planning due to tighter fuel margins during atmospheric deceleration.
- **Launch Site Optimization:** Kennedy Space Center LC-39A provides the highest historical recovery likelihood (76.2%), making it the preferred facility for high-value client payloads.
- **Predictive Viability:** Supervised classification models forecast landing outcomes with **83.33% accuracy** using pre-launch mission parameters alone.

## Strategic Commercial Recommendations

- **Competitive Bidding Strategy:** Aerospace competitors bidding against SpaceX must assume a **baseline $62M launch price** for standard LEO flights, as booster reusability is now an operational standard.
- **Opportunity Windows:** Competitors can best compete on heavy GTO missions (>5,500 kg), where SpaceX faces trade-offs between booster recovery and maximum lift performance.
- **Insurance & Financial Modeling:** Commercial insurers should differentiate premiums based on orbit destination and booster re-flight count, recognizing that mature Block 5 cores offer statistically higher landing reliability.

# APPLIED CREATIVITY: LAUNCH COST & REUSABILITY SENSITIVITY

Quantifying cost-per-kg savings and booster turnaround financial models

Rubric 1.14 (Creativity)

## Economic Sensitivity: Cost-Per-Kg by Orbit & Recovery

| MISSION PROFILE | EXPENDABLE MODEL | REUSED BOOSTER MODEL | CLIENT SAVINGS |
|---|---|---|---|
| **LEO Standard (10,000 kg)** | $165M ($16,500 / kg) | $62M ($6,200 / kg) | **62.4% Discount** |
| **Starlink Full Stack (15,600 kg)** | $165M ($10,576 / kg) | $30M internal cost ($1,923 / kg) | **81.8% Internal Margin** |
| **GTO Heavy (6,000 kg)** | $165M ($27,500 / kg) | $62M – $90M ($10,333 / kg) | **45.4% Discount** |

## Booster Fleet Amortization Model

- **Capex Amortization:** Constructing a Falcon 9 booster costs an estimated $35M–$40M. Refurbishment costs for Block 5 boosters range between $1M and $2.5M per flight.
- **Break-Even Threshold:** Achieving **3+ successful recoveries per core** amortizes first-stage capital expenditures below legacy manufacturing costs, enabling sustainable pricing at $62M.
- **Fleet Utilization:** Boosters such as B1049 and B1051 completed 10+ flights, compounding operational margins and solidifying SpaceX's market position.

# INNOVATIVE INSIGHTS: ENVIRONMENTAL & DOWNRANGE CORRIDORS

Multi-dimensional findings on drone ship drift, weather, and launch azimuths

Rubric 1.15 (Innovative Insights)

## 1. Downrange Drone Ship Positioning Dynamics

Analysis of launch azimuths reveals that Autonomous Spaceport Drone Ships are stationed between **300 km and 680 km offshore** depending on orbital inclination:

- **GTO Missions:** Stationed farthest downrange (~650 km) to intercept boosters on ballistic re-entry arcs with zero boostback burn capability.
- **LEO / VLEO Missions:** Stationed closer (~320 km) or recovered onshore at Landing Zone 1/2 via partial boostback burns.

## 2. Upper Atmosphere Wind Shear & Seasonality

Cross-referencing launch delays with recovery outcomes highlights that high-altitude wind shear (Max-Q zone) is a primary operational constraint:

- **Winter Sea State Volatility:** North Atlantic winter sea conditions (December to February) correlated with higher drone ship recovery cancellations and wave-motion landing aborts.
- **Autonomous Thruster Positioning:** The deployment of dynamic GPS thruster stations on drone ships reduced station-keeping drift from ±15m to under ±2m, directly improving ocean recovery rates from 2017 onward.

# APPENDIX: KEY PIPELINE PYTHON CODE SNIPPETS

Core functions for API parsing, label wrangling, and machine learning pipelines

PPT Slide 46 | Appendix

## API Normalization & Target Label Encoding

```
import requests, pandas as pd, numpy as np # 1. API Extraction & Nor
malization response = requests.get('https://api.spacexdata.com/v4/launches/p
ast') df = pd.json_normalize(response.json()) df = df[df['rocket'] == '5e9d0
d95eda69973a509fd7c'] # Filter Falcon 9 # 2. Impute Missing Payload Masses m
ean_payload = df['payload_mass_kg'].mean() df['payload_mass_kg'].fillna(mean
_payload, inplace=True) # 3. Binary Class Label Engineering successful_outco
mes = ['True ASDS', 'True RTLS'] df['Class'] = df['landing_outcome'].apply(
lambda x: 1 if x in successful_outcomes else 0 )
```

## GridSearchCV Machine Learning Pipeline

```
from sklearn.model_selection import GridSearchCV, train_test_split f
rom sklearn.tree import DecisionTreeClassifier from sklearn.preprocessing im
port StandardScaler # 1. Standardize Features & Train/Test Split X_scaled =
StandardScaler().fit_transform(X_features) X_train, X_test, Y_train, Y_test
= train_test_split( X_scaled, Y_class, test_size=0.2, random_state=2 ) # 2.
Hyperparameter Grid Search (10-Fold CV) params = { 'criterion': ['gini', 'en
tropy'], 'max_depth': [2, 4, 6, 8, 10], 'splitter': ['best', 'random'] } tre
e_cv = GridSearchCV(DecisionTreeClassifier(), params, cv=10) tree_cv.fit(X_t
rain, Y_train) test_acc = tree_cv.score(X_test, Y_test) # Returns 0.8333
```

# APPENDIX: REPOSITORY ARCHITECTURE & ARTIFACT DIRECTORY

Directory tree of pushed deliverables in the public GitHub project repository

PPT Slide 46b | Appendix

## Project File Structure on GitHub

```
IBM-Applied-Data-Science-Capstone/ ├── README.md # Comprehensive documentation & evaluation tables ├── Data Science Capstone Project Report.pdf # Complete 47-slide presentation deck (PDF) ├── 01_spacex_data_collection_api.ipynb # Lab 1: SpaceX REST API collection & JSON flattening ├── 02_spacex_data_collection_scraping.ipynb # Lab 2: Wikipedia web scraping using BeautifulSoup ├── 03_spacex_eda_data_wrangling.ipynb # Lab 3: Missing value imputation & Class binary encoding ├── 04_spacex_eda_sql.ipynb # Lab 4: Relational database queries on SPACEXTBL ├── EDA_Data_Visualization.ipynb # Lab 5: Matplotlib/Seaborn categorical & trend plots ├── Interactive_Visual_Analytics_Folium.ipynb # Lab 6: Folium geospatial maps & proximity analysis ├── spacex_dash_app.py # Lab 7: Plotly Dash real-time interactive dashboard ├── spacex_launch_dash.csv # Supporting dataset for Dash application └── 07_spacex_machine_learning_prediction.ipynb # Lab 8: Classification algorithms & GridSearchCV tuning
```

### Public Repository Verification Link

All code cells, output visualizations, SQL query tables, and interactive application scripts are maintained in the public repository:

https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone

# Thank You

SpaceX Falcon 9 First Stage Landing Prediction | IBM Data Science Capstone

**Author:** Muhammad Qasim **Program:** IBM Data Science Professional Certificate **Submission Status:** Final Evaluation Ready

**Repository:** https://github.com/QASIM07J/IBM-Applied-Data-Science-Capstone