

Attend, Adapt and Transfer: Attentive Deep Architecture for Adaptive Transfer from multiple sources in the same domain

Janarthanan Rajendran, Aravind S. Lakshminarayanan, Mitesh M. Khapra, P Prasanna, Balaraman Ravindran

University of Michigan, Indian Institute of Technology Madras, McGill University


ICLR 2017

Presenter: Jack Lanchantin

Outline

- 1 Knowledge Transfer and A2T
- 2 Knowledge Transfer with A2T
 - Reinforcement Learning
 - Policy Transfer
 - Value Transfer
- 3 Experiments and Results
 - Selective Transfer
 - Avoiding Transfer
 - Choosing When to Transfer
- 4 Conclusions

Knowledge Transfer



Knowledge Transfer

- N source tasks with K_1, K_2, \dots, K_N being the solutions of the source tasks (e.g. tennis coaches)
- K_B is the base solution for the target task which starts learning from scratch (tennis student's initial knowledge)
- K_T is the solution we want to learn for target task T (tennis student's final skills)

Knowledge Transfer

- N source tasks with K_1, K_2, \dots, K_N being the solutions of the source tasks (e.g. tennis coaches)
- K_B is the base solution for the target task which starts learning from scratch (tennis student's initial knowledge)
- K_T is the solution we want to learn for target task T (tennis student's final skills)


This paper: Using combination of the solutions to obtain K_T

$$K_T(s) = w_{N+1,s}K_B(s) + \sum_{i=1}^N w_{i,s}K_i(s) \quad (1)$$

$w_{i,s}$ is the weight of solution i at state s (learned by a separate network)

Attention Network for Selective Transfer (A2T)

$$K_T(s) = w_{N+1,s} K_B(s) + \sum_{i=1}^N w_{i,s} K_i(s) \quad (1)$$



Outline

- 1 Knowledge Transfer and A2T
- 2 Knowledge Transfer with A2T
 - Reinforcement Learning
 - Policy Transfer
 - Value Transfer
- 3 Experiments and Results
 - Selective Transfer
 - Avoiding Transfer
 - Choosing When to Transfer
- 4 Conclusions

Background: Reinforcement Learning

- S : finite set of states

Background: Reinforcement Learning

- S : finite set of states
- A : finite set of actions

Background: Reinforcement Learning

- S : finite set of states
- A : finite set of actions
- P : state transition probability matrix,
 $P_{ss'}^a = \mathbb{P}[S_{t+1} = s' | S_t = s, A_t = a]$

Background: Reinforcement Learning

- S : finite set of states
- A : finite set of actions
- P : state transition probability matrix,
 $P_{ss'}^a = \mathbb{P}[S_{t+1} = s' | S_t = s, A_t = a]$
- $r(s, a)$: reward function

Background: Reinforcement Learning

- S : finite set of states
- A : finite set of actions
- P : state transition probability matrix,
 $P_{ss'}^a = \mathbb{P}[S_{t+1} = s' | S_t = s, A_t = a]$
- $r(s, a)$: reward function
- R_t : return, sum of rewards over the agent's trajectory: $R_t = r_t + r_{t+1} + r_{t+2} + \dots + r_T = \sum_{k=0:\infty} \gamma^k r_{t+k}$

Background: Reinforcement Learning

- S : finite set of states
- A : finite set of actions
- P : state transition probability matrix,
 $P_{ss'}^a = \mathbb{P}[S_{t+1} = s' | S_t = s, A_t = a]$
- $r(s, a)$: reward function
- R_t : return, sum of rewards over the agent's trajectory: $R_t = r_t + r_{t+1} + r_{t+2} + \dots + r_T = \sum_{k=0:\infty} \gamma^k r_{t+k}$
- π : policy function, distribution over actions given states:
 $\pi(a, s) = \mathbb{P}[A_t = a | S_t = s]$

Background: Reinforcement Learning

- S : finite set of states
- A : finite set of actions
- P : state transition probability matrix,
 $P_{ss'}^a = \mathbb{P}[S_{t+1} = s' | S_t = s, A_t = a]$
- $r(s, a)$: reward function
- R_t : return, sum of rewards over the agent's trajectory: $R_t = r_t + r_{t+1} + r_{t+2} + \dots + r_T = \sum_{k=0:\infty} \gamma^k r_{t+k}$
- π : policy function, distribution over actions given states:
 $\pi(a, s) = \mathbb{P}[A_t = a | S_t = s]$
- $V(s)$: state value function, the expected return of a policy π , for every state: $V_\pi(s) = \mathbb{E}_\pi[R_t | S_t = s]$

- 1 Knowledge Transfer and A2T
- 2 Knowledge Transfer with A2T
 - Reinforcement Learning
 - Policy Transfer
 - Value Transfer
- 3 Experiments and Results
 - Selective Transfer
 - Avoiding Transfer
 - Choosing When to Transfer
- 4 Conclusions

Policy Transfer

- Transferring source task policies
- We have $K_1, \dots, K_N, K_B, K_T \leftarrow \pi_1, \dots, \pi_N, \pi_B, \pi_T$
- The agent acts in the target task by sampling actions from the target distribution π_T , obtained from:

$$K_T(s) = w_{N+1,s}K_B(s) + \sum_{i=1}^N w_{i,s}K_i(s) \quad (1)$$

Policy Transfer using REINFORCE

REINFORCE

Direct policy search by making weight adjustments along the gradient of expected reinforcement.

$$\theta_a \leftarrow \theta_a + \alpha_{\theta_a} (r - b) \frac{\partial \sum_{t=1}^M \log(\pi_T(s_t, a_t))}{\partial \theta_a} \quad (2)$$


$$\theta_b \leftarrow \theta_b + \alpha_{\theta_b} (r - b) \frac{\partial \sum_{t=1}^M \log(\pi_B(s_t, a_t))}{\partial \theta_b} \quad (3)$$

where α is learning rate, r is return obtained in the episode, b is a reinforcement baseline, M is the length of the episode

Policy Transfer in Actor-Critic

Actor-Critic

Temporal Difference (TD) method where the actor proposes a policy and the critic estimates the value function to critique the actors policy. The updates to the actor happens through TD-error



Outline

- 1 Knowledge Transfer and A2T
- 2 Knowledge Transfer with A2T
 - Reinforcement Learning
 - Policy Transfer
 - Value Transfer
- 3 Experiments and Results
 - Selective Transfer
 - Avoiding Transfer
 - Choosing When to Transfer
- 4 Conclusions

- Transferring source task's action-value functions (Q functions):

$$Q_{\pi}(s, a) = \mathbb{E}_{\pi}[R_t | S_t = s, A_t = a] \quad (4)$$

- The Q function is used to guide the agent to selecting the optimal action a at a state s .


Q-learning

One way to learn optimal policies for an agent is to estimate the optimal $Q(s, a)$ for the task. Q-learning is an off-policy learning algorithm that estimates the Q function (e.g. using a deep neural net).

Outline

- 1 Knowledge Transfer and A2T
- 2 Knowledge Transfer with A2T
 - Reinforcement Learning
 - Policy Transfer
 - Value Transfer
- 3 Experiments and Results
 - Selective Transfer
 - Avoiding Transfer
 - Choosing When to Transfer
- 4 Conclusions


Selective Transfer with Policy Function



(a) Chain World


- Task LT is to start in A or B with uniform probability and end up in C in the least number of steps.
- Two source tasks, $L1$ and $L2$ are available. $L1$ has learned to reach A from B and $L2$ has learned to reach B from A.
- Model learns to solve LT using REINFORCE

Selective Transfer with Policy Function



(a) The weights given by the attention network. Selective transfer in REINFORCE


Selective Transfer with Policy Function



(c) Puddle World 2

- Task LT is to start in S1 or S2 and end up in G1 in the least number of steps
- $L1$ has learned to reach G1 from S1 and $L2$ has learned to reach G1 from S2
- Model learns to solve LT using Actor-Critic

Selective Transfer with Policy Function



(b) Selective transfer in Actor-Critic

Selective Transfer with Value Function




Figure 4: Visualisation of the attention weights in the Selective Transfer with Attention Network

- L1 performs poorly on upper right quadrant
- L2 performs poorly on lower right quadrant

Selective Transfer with Value Function





Figure 4: Visualisation of the attention weights in the Selective Transfer with Attention Network

- L1 performs poorly on upper right quadrant
- L2 performs poorly on lower right quadrant
- L1 score of 9.2, L2 score of 8, LT score of 17.2 ($[-21, 21]$)


Selective Transfer with Value Function



Outline

- 1 Knowledge Transfer and A2T
- 2 Knowledge Transfer with A2T
 - Reinforcement Learning
 - Policy Transfer
 - Value Transfer
- 3 Experiments and Results
 - Selective Transfer
 - **Avoiding Transfer**
 - Choosing When to Transfer
- 4 Conclusions


Avoiding Negative Transfer and Ability to Transfer from Favorable Task (policy transfer in puddle world)




(b) Puddle World 1

- Reach goal state by starting in S1,S2,S3,S4
- L1 is favorable (good) model
- L2 is unfavorable (inverse output weights of L1)


Avoiding Negative Transfer and Ability to Transfer from Favorable Task (policy transfer in puddle world)



Avoiding Negative Transfer and Ability to Transfer from Favorable Task (value transfer in pong)




(a) Avoiding negative transfer(Pong) and transferring from a favorable task



(b) Avoiding negative transfer(Freeway) and transferring from a favorable task

Attention Map for Favorable/Unfavorable Sources (value transfer in pong)




Outline

- 1 Knowledge Transfer and A2T
- 2 Knowledge Transfer with A2T
 - Reinforcement Learning
 - Policy Transfer
 - Value Transfer
- 3 Experiments and Results
 - Selective Transfer
 - Avoiding Transfer
 - Choosing When to Transfer
- 4 Conclusions

When a Perfect Expert is Not Available Among Tasks

- Pong with partially favorable and unfavorable source tasks



Conclusions

- General deep neural network architecture, A2T, for transfer learning
- A2T avoids negative transfer while enabling selective transfer from multiple source tasks in the same domain