

CakeJDR

One-page app summary generated from repo evidence only

What It Is

CakeJDR is a Next.js app for playing tabletop RPGs online with shared rooms, real-time collaboration, character sheets, chat, and dice tools. README notes online features are still incomplete and local run only.

Who It's For

Primary users are tabletop RPG groups: players and a game master sharing rooms, sheets, chat, dice, and a board.

What It Does

- Lets users log in locally with a saved profile and room selection stored in browser storage.
- Creates, lists, joins, renames, and deletes rooms, including password-protected rooms.
- Provides a collaborative canvas with drawing, erasing, live cursors, and image upload/placement.
- Supports real-time chat, dice rolling, dice history, and live participant/avatar presence.
- Manages character sheets with stats, equipment, description tabs, leveling, and GM selection.
- Imports/exports character sheets locally or from cloud storage; README says Blob storage is menu-page only.
- Includes music playback/queue, side notes, and session-summary structures in room state.

How It Works

- UI: Next.js App Router routes users from / to /menu, then into /menu-accueil, /rooms, and /room/[id].
- Real-time room shell: app/Room.tsx wraps each room in LiveblocksProvider and RoomProvider with storage for characters, images, strokes, music, summary, quick notes, editor data, events, and rooms.
- Services: /api/liveblocks-auth authorizes room access; /api/rooms and lib/liveRooms manage room records; /api/roomstorage persists character data in Liveblocks storage; /api/cloudinary uploads canvas images; /api/blob uploads/lists/deletes character-sheet files in Vercel Blob.
- Data flow: browser localStorage keeps profile, theme, and current selections; Liveblocks syncs room state; Cloudinary stores image assets; Vercel Blob stores character-sheet files. Database: Not found in repo.

How To Run

- Install dependencies: npm install
- Copy .env.example to .env.local and set CLOUDINARY_*, LIVEBLOCKS_SECRET_KEY, BLOB_READ_WRITE_TOKEN, and VERCEL_OIDC_TOKEN.
- Start the dev server: npm run dev
- Open http://localhost:3000