一、医院详情(接口)

1、添加service方法和实现

(1) 在HospService定义方法

(2) 在HospServiceImpl定义方法

```
1 @Override
 2 public Map<String, Object> show(String id) {
 3
      Map<String, Object> result = new HashMap<>();
 4
      Hospital hospital = this.packHospital(hospitalRepository.findById(id).get());
      //医院基本信息(包含医院等级)
 5
      result.put("hospital",hospital);
 6
 7
      //单独处理更直观
 8
      result.put("bookingRule", hospital.getBookingRule());
9
      //不需要重复返回
      hospital.setBookingRule(null);
10
11
      return result;
12 }
```

2、添加controller方法

```
1 @ApiOperation(value = "获取医院详情")
2 @GetMapping("show/{id}")
3 public R show(
4 @ApiParam(name = "id", value = "医院id", required = true)
```

```
@PathVariable String id) {
   return R.ok().data("hospital",hospitalService.show(id));
}
```

二、医院详情(前端)

1、添加隐藏路由

在router/index.js添加

```
1 {
2  path: 'hospital/show/:id',
3  name: '查看',
4  component: () => import('@/views/hosp/show'),
5  meta: { title: '查看', noCache: true },
6  hidden: true
7 }
```

2、创建医院详情页面



(1) 添加查看按钮

(2) 封装api请求

```
1 //查看医院详情
2 getHospById(id) {
3 return request ({
```

```
4  url: `/admin/hosp/hospital/show/${id}`,
5  method: 'get'
6  })
7 }
```

(3) 修改显示页面组件

```
1 <template>
2 <div class="app-container">
    <h4>基本信息</h4>
3
    4
      5
6
         7
           医院名称
8
           <b style="font-size: 14px">{{ hospital.hosname }}</b>
9
           医院logo
           10
              <img :src="'data:image/jpeg;base64,'+hospital.logoData" width="80</pre>
11
           13
         14
         15
           医院编码
           {{ hospital.hoscode }}
16
           地址
17
           {{ hospital.param.fullAddress }}
18
19
         20
           坐车路线
21
           {{ hospital.route }}
22
23
         24
         医院简介
25
           {{ hospital.intro }}
26
27
         28
29
      30
      <h4>预约规则信息</h4>
31
      <table class="table table-striped table-condenseda table-bordered" width="100
32
33
      34
```

```
35
             预约周期
             {{ bookingRule.cycle }}天
36
             放号时间
37
             {{ bookingRule.releaseTime }}
38
39
          40
41
             停挂时间
             {{ bookingRule.stopTime }}
42
             退号时间
43
             {{ bookingRule.quitDay == -1 ? '就诊前一工作日' : '就诊当日' }}{{ b
44
          45
46
          预约规则
47
             48
49
             {{ item }}
50
51
             52
53
          54
       <br>
55
          <el-row>
56
          <el-button @click="back">返回</el-button>
57
          </el-row>
58
       59
    60 </div>
61 </template>
62
63 <script>
64 import hospApi from '@/api/yygh/hosp'
65 export default {
66
    data() {
67
       return {
          hospital: null, //医院信息
68
          bookingRule: null //预约信息
69
       }
70
71
    },
72
    created() {
       //获取路由id
73
       const id = this.$route.params.id
74
       //调用方法,根据id查询医院详情
75
       this.fetachHospDetail(id)
76
77
    },
```

```
78
       methods:{
           //根据id查询医院详情
79
           fetachHospDetail(id) {
80
               hospApi.getHospById(id)
81
82
                   .then(response => {
83
                       this.hospital = response.data.hospital.hospital
84
                       this.bookingRule = response.data.hospital.bookingRule
                   })
85
           },
86
           //返回医院列表
87
           back() {
88
               this.$router.push({ path: '/hospSet/hosp/list' })
89
90
           }
91
       }
92 }
93 </script>
```

(4) 引入样式

第一、将show.css文件复制到src/styles目录



第二、在src/main.js文件添加引用

```
import '@/styles/show.css'
```