

---

# EPToolbox package file

This notebook auto-generates the `EPToolbox.m` package file.

## Package Start

```
BeginPackage["EPToolbox`"];
```

## Complex root finder

```
FindComplexRoots[equations_List, domainSpecifiers__, ops : OptionsPattern[]] :=  
Block[{seeds, tolerances},  
  If[! IntegerQ[Rationalize[OptionValue[Seeds]]] || OptionValue[Seeds] ≤ 0,  
    Message[FindComplexRoots::seeds, OptionValue[Seeds]]];  
  If[! (OptionValue[Tolerance] === Automatic || OptionValue[Tolerance] ≥ 0),  
    Message[FindComplexRoots::tol, OptionValue[Seeds]]];  
  
  seeds = OptionValue[SeedGenerator][  
    {domainSpecifiers}[[All, {2, 3}]], OptionValue[Seeds]];  
  tolerances = Which[  
    ListQ[OptionValue[Tolerance]], OptionValue[Tolerance],  
    True, ConstantArray[  
      Which[  
        NumberQ[OptionValue[Tolerance]], OptionValue[Tolerance],  
        True, 10^If[NumberQ[OptionValue[WorkingPrecision]],  
          2 - OptionValue[WorkingPrecision], 2 - $MachinePrecision]  
      ]  
    ], Length[{domainSpecifiers}]]  
];  
  
If[OptionValue[Verbose], Hold[], Hold[FindRoot::lstol]] /. {  
  Hold[messagesSequence___] :> Quiet[  
    DeleteDuplicates[  
      Select[  
        Check[  
          FindRoot[  
            equations  
            , Evaluate[Sequence@@Table[{domainSpecifiers}[[j, 1],  
              #[[j]]], {j, Length[{domainSpecifiers}]}]]  
            , Evaluate[Sequence@@FilterRules[{ops},  
              Options[FindRoot]]]  
          ],  
          ## &[]  
        ] & /@ seeds,  
      Function[  
        replist,
```

```

ReplaceAll[
  Evaluate[And@@Table[
    And[
      Re[{domainSpecifiers}[[j, 2]] ≤ Re[{domainSpecifiers}[[
        j, 1]]] ≤ Re[{domainSpecifiers}[[j, 3]]],
      Im [{domainSpecifiers}[[j, 2]]] ≤ Im [
        {domainSpecifiers}[[j, 1]]] ≤ Im [
        {domainSpecifiers}[[j, 3]]]
    ]
    , {j, Length[{domainSpecifiers}]}]]]
  , repList]
],
Function[{repList1, repList2},
  And@@Table[
    Abs[( {domainSpecifiers}[[j, 1]] /. repList1) -
      ( {domainSpecifiers}[[j, 1]] /. repList2)] < tolerances[[j]]
    , {j, Length[{domainSpecifiers}]}]]
]
, {messageSequence }]]}
]
FindComplexRoots [e1_==e2_, {z_, zmin_ , zmax_ }, ops:OptionsPattern[]] :=
  FindComplexRoots [{e1==e2}, {z, zmin , zmax }, ops]

```

```

FindComplexRoots ::usage =
    "FindComplexRoots [e1==e2, {z, zmin, zmax}] attempts to
      find complex roots of the equation e1==e2 in the
      complex rectangle with corners zmin and zmax .

FindComplexRoots [{e1==e2, e3==e4, ...}, {z1, z1min, z1max }, {z2, z2min,
      z2max }, ...] attempts to find complex roots of the given
      system of equations in the multidimensional complex
      rectangle with corners z1min, z1max, z2min, z2max, ....";
Seeds::usage = "Seeds is an option for FindComplexRoots which
      determines how many initialseeds are used to
      attempt to find roots of the given equation.";
SeedGenerator::usage = "SeedGenerator is an option for FindComplexRoots
      which determines the function used to generate the
      seeds for the internal FindRoot call. Its value can
      be RandomComplex, RandomNiederreiterComplexes,
      RandomSobolComplexes, DeterministicComplexGrid, or any
      function f such that f[{zmin, zmax}, n] returns n complex
      numbers in the rectangle with corners zmin and zmax .";

Options[FindComplexRoots] =
    Join[Options[FindRoot], {Seeds -> 50, SeedGenerator -> RandomComplex,
      Tolerance -> Automatic, Verbose -> False}];
SyntaxInformation[FindComplexRoots] = {"ArgumentsPattern" ->
    {_, {_, _, _}, OptionsPattern[]}, "LocalVariables" -> {"Table", {2, ∞}}};
FindComplexRoots ::seeds =
    "Value of option Seeds -> `1` is not a positive integer.";
FindComplexRoots ::tol =
    "Value of option Tolerance -> `1` is not Automatic or a number in [0,∞).";

Protect[Seeds];
Protect[SeedGenerator];

Begin["`Private`"];
FindComplexRoots [equations_List, domainSpecifiers__, ops : OptionsPattern[]] :=
    Block[{seeds, tolerances},
        If[! IntegerQ[Rationalize[OptionValue[Seeds]]] || OptionValue[Seeds] ≤ 0,
            Message[FindComplexRoots ::seeds, OptionValue[Seeds]];
        If[! (OptionValue[Tolerance] === Automatic || OptionValue[Tolerance] ≥ 0),
            Message[FindComplexRoots ::tol, OptionValue[Seeds]];

        seeds = OptionValue[SeedGenerator][
            {domainSpecifiers}][[All, {2, 3}]], OptionValue[Seeds]];
        tolerances = Which[
            ListQ[OptionValue[Tolerance]], OptionValue[Tolerance],
            True, ConstantArray[
                Which[
                    NumberQ [OptionValue[Tolerance]], OptionValue[Tolerance],

```

```

        True, 10^If[NumberQ [OptionValue[WorkingPrecision]],
            2-OptionValue[WorkingPrecision], 2- $\$MachinePrecision$ ]
    ]
    , Length[{domainSpecifiers}]]
];

If[OptionValue[Verbose], Hold[], Hold[FindRoot::lstol]] /. {
    Hold[messageSequence___ ] :> Quiet[
        DeleteDuplicates[
            Select[
                Check[
                    FindRoot[
                        equations
                        , Evaluate[Sequence@@Table[{domainSpecifiers}[[j, 1]],
                            #[[j]], {j, Length[{domainSpecifiers}]}]]
                        , Evaluate[Sequence@@FilterRules[{ops},
                            Options[FindRoot]]]
                    ],
                    ## &[]
                ] &/@seeds,
            Function[
                repList,
                ReplaceAll[
                    Evaluate[And@@Table[
                        And[
                            Re[{domainSpecifiers}[[j, 2]]] ≤ Re[{domainSpecifiers}[[
                                j, 1]]] ≤ Re[{domainSpecifiers}[[j, 3]]],
                            Im [{domainSpecifiers}[[j, 2]]] ≤ Im [
                                {domainSpecifiers}[[j, 1]]] ≤ Im [
                                    {domainSpecifiers}[[j, 3]]
                                ]
                        ]
                        , {j, Length[{domainSpecifiers}]}]]
                    , repList]
                ]
            ],
        Function[{repList1, repList2},
            And@@Table[
                Abs[( {domainSpecifiers}[[j, 1]] /. repList1) -
                    ( {domainSpecifiers}[[j, 1]] /. repList2)] < tolerances[[j]]
                , {j, Length[{domainSpecifiers}]}]]
            ]
        , {messageSequence }]]
]

FindComplexRoots [e1_ == e2_, {z_, zmin_ , zmax_ }, ops:OptionsPattern[]] :=
    FindComplexRoots [{e1 == e2}, {z, zmin , zmax }, ops]
End[];

```

## Quasirandom number generators

### RandomSobolComplexes

```
RandomSobolComplexes ::usage =
  "RandomSobolComplexes [{zmin , zmax }, n] generates a
    low-discrepancy Sobol sequence of n quasirandom complex
    numbers in the rectangle with corners zmin and zmax .

RandomSobolComplexes [{z1min , z1max }, {z2min , z2max }, ..., n]
  generates a low-discrepancy Sobol sequence of n
  quasirandom complex numbers in the multi -dimensional
  rectangle with corners {z1min , z1max }, {z2min , z2max }, ....";

Begin["`Private`"];
RandomSobolComplexes [pairsList_, number_] := Map[
  Function[randomsList ,
    pairsList[[All, 1]]+Complex @@@Times [
      ReIm [pairsList[[All, 2]]-pairsList[[All, 1]]],
      randomsList
    ]
  ],
  BlockRandom [
    SeedRandom [
      Method->{"MKL", Method->{"Sobol", "Dimension" -> 2 Length[pairsList]}}];
    SeedRandom [];
    RandomReal [{0, 1}, {number , Length[pairsList], 2}]
  ]
]
RandomSobolComplexes [{zmin_ ?NumericQ , zmax_ ?NumericQ }, number_] :=
  RandomSobolComplexes [{zmin , zmax }, number ][[All, 1]]
End[];
```

### RandomNiederreiterComplexes

```
RandomNiederreiterComplexes ::usage =
  "RandomNiederreiterComplexes [{zmin , zmax }, n] generates a
    low-discrepancy Niederreiter sequence of n quasirandom complex
    numbers in the rectangle with corners zmin and zmax .

RandomNiederreiterComplexes [{z1min , z1max }, {z2min , z2max }, ..., n]
  generates a low-discrepancy Niederreiter sequence of n
  quasirandom complex numbers in the multi -dimensional
  rectangle with corners {z1min , z1max }, {z2min , z2max }, ....";
```

```

Begin["`Private`"];
RandomNiederreiterComplexes [pairsList_ , number_ ] := Map[
  Function[randomsList ,
    pairsList[[All, 1]]+Complex @@@Times [
      ReIm [pairsList[[All, 2]]-pairsList[[All, 1]] ,
      randomsList
    ]
  ],
  BlockRandom [
    SeedRandom [Method→
      {"MKL", Method→{"Niederreiter", "Dimension" → 2 Length[pairsList]}}];
    SeedRandom [];
    RandomReal [{0, 1}, {number , Length[pairsList], 2}]
  ]
];
RandomNiederreiterComplexes [{zmin_ ?NumericQ , zmax_ ?NumericQ }, number_ ] :=
  RandomNiederreiterComplexes [{zmin , zmax }, number ][[All, 1]]
End[];

```

## DeterministicComplexGrid

```

DeterministicComplexGrid ::usage =
  "DeterministicComplexGrid [{zmin , zmax }, n] generates
    a grid of about n equally spaced complex numbers
    in the rectangle with corners zmin and zmax .

DeterministicComplexGrid [{z1min , z1max }, {z2min , z2max }, ..., n]
  generates a regular grid of about n equally spaced
  complex numbers in the multi -dimensional rectangle
  with corners {z1min , z1max }, {z2min , z2max }, ....";

```

```

Begin["`Private`"];
DeterministicComplexGrid [pairsList_, number_] :=
  Block[{sep, separationsList, gridPointBasis},
    sep = NestWhile[0.99 # &, Min[Flatten[ReIm [pairsList[[All, 2]] - pairsList[[All, 1]]]],
      Times @@  $\frac{1}{0.99 \#}$  Floor[Flatten[ReIm [pairsList[[All, 2]] - pairsList[[All, 1]]]],
      0.99 #] ≤ number &];
    separationsList = Round[ $\frac{1}{sep}$  Floor[Flatten[ReIm [
      pairsList[[All, 2]] - pairsList[[All, 1]]], sep]];
    gridPointBasis = MapThread[
      Function[{1, n}, Range[1[[1]], 1[[2]],  $\frac{1[[2]] - 1[[1]]}{n + 1}$ ][[2 ;; -2]],
      {Flatten[Transpose[ReIm [pairsList], {1, 3, 2}], 1], separationsList}
    ];
    Flatten[Table[
      Table[k[2 j - 1] + i k[2 j], {j, 1, Length[pairsList]}],
      Evaluate[
        Sequence @@ Table[{k[j], gridPointBasis[[j]]}, {j, 1, 2 Length[pairsList]}]]
    ], Evaluate[Range[1, 2 Length[pairsList]]]]
  ]
DeterministicComplexGrid [{zmin_ ?NumericQ, zmax_ ?NumericQ}, number_] :=
  DeterministicComplexGrid [{zmin, zmax}, number][[All, 1]]
End[];

```

## Contour plot cleaner

This function cleans up automatically generated contour plots. Generically, a contour plot is made of a Polygon with a vast number of vertices in its interior, which are not necessary and only slow the plot down - including a large use of CPU when the mouse hovers above it, which is definitely unwanted. (In addition, these polygons can give rise to white edges inside each contour when printed to pdf, which is also undesirable.) This function changes such Polygons to FilledCurve constructs which no longer contain the unwanted mid-contour points.

This function was written by Szabolcs Horvát

(<http://mathematica.stackexchange.com/users/12/szabolcs>) and was originally posted at <http://mathematica.stackexchange.com/a/3279> under a CC-BY-SA license.

```

cleanContourPlot::usage =
  "cleanContourPlot[plot] Cleans up a contour plot by coalescing
    complex polygons into single FilledCurve instances.
    See MM.SE/a/3279 for source and documentation .";

```

```

Begin["`Private`"];
cleanContourPlot[cp_] :=
Module[{points, groups, regions, lines},
groups =
Cases[cp, {style_, g_GraphicsGroup} :> {{style}, g}, Infinity];
points =
First@Cases[cp, GraphicsComplex[pts_, ___] :> pts, Infinity];
regions = Table[
Module[{group, style, polys, edges, cover, graph},
{style, group} = g;
polys = Join@@Cases[group, Polygon[pt_, ___] :> pt, Infinity];
edges = Join@@(Partition[#, 2, 1, 1] & /@ polys);
cover = Cases[Tally[Sort /@ edges], {e_, 1} :> e];
graph = Graph[UndirectedEdge@@@ cover];
{Sequence @@ style,
FilledCurve[
List/@Line/@First/@
Map[First,
FindEulerianCycle/@(Subgraph[graph, #] &) /@
ConnectedComponents[graph], {3}]]]}
],
{g, groups}];
lines = Cases[cp, _Tooltip, Infinity];
Graphics[GraphicsComplex[points, {regions, lines}],
Sequence @@ Options[cp]]
]
End[];

```

## Dynamics profiler

This function produces a profiling suite for any dynamics constructs, which can be used to see which parts of a Dynamic application take up the most processing time and calls.

This function was written by Rui Rojo (<http://mathematica.stackexchange.com/users/109/rojo>) and was originally posted at <http://mathematica.stackexchange.com/a/8047> under a CC-BY-SA license.

```

profileDynamics::usage =
  "profileDynamics[dynamicsConstruct] Produces a profiling suite
    for the Dynamic statements in its argument .
    See MM.SE/a/8047 for source and documentation .";

```



```

Begin["`Private`"];
ClearAll[profileDynamics];
Options[profileDynamics] = {"Print" -> False};
profileDynamics[d_, OptionsPattern[]] := With[
  {print = OptionValue["Print"]},
  Module[{counter = {}},
    DynamicModule [
      {diag, start, tag},
      diag[] := CreateDocument [Column [{
        Button["Reset counter", counter = start],
        Dynamic @Grid[Join[
          {"Dynamic expression", "Count", "Time "}],
          MapAt[Short, #, 1] & /@ counter
        ]
      }]];
      CellPrint@
      ExpressionCell[Button["See profiling information", diag[]]];
      d //. {
        i: Annotation[_ , {tag, ___}] :> i,
        e: Dynamic [sth: Except[First[{_, tag}]], rest___] :> With[
          {pos = 1 + Length@counter,
           catalog =
            Annotation[
              InputForm @e, {tag, Unique["profileDynamics`annot "]}]},
          AppendTo[counter, {catalog, 0, 0.}];
          Dynamic [First@{Refresh[
            If[print, Print[catalog]]; ++counter[[pos, 2]];
            (counter[[pos, 3]] += First@#; Last@#) &[
              AbsoluteTiming [Refresh[sth]]],
            None], tag}, rest] /; True
          ]
        } // (start = counter; #) &
      ]
    ]
  ]
End[];

```

## Package End

```
EndPackage[];
```