
FNFTpy Documentation

Release 0.1

Christoph Mahnke

Jul 17, 2018

CONTENTS:

1	Module overview	1
2	Korteweg-de-Fries equation	3
2.1	kdvv - calculate the Nonlinear Fourier Transform	3
2.2	kdvv_wrapper - interact with FNFT library	3
2.3	get, set and view options for kdvv_wrapper	4
2.4	options structure	4
3	Nonlinear Schroedinger equation with periodic boundaries	5
3.1	nsep - calculate the Nonlinear Fourier Transform	5
3.2	nsep_wrapper - interact with FNFT library	6
3.3	get, set and view options for nsep_wrapper	6
3.4	options structure	7
4	Nonlinear Schroedinger equation with vanishing boundaries	9
4.1	nsev_inverse - calculate the Inverse Nonlinear Fourier Transform	9
4.2	nsev_inverse_wrapper - interact with FNFT library	9
4.3	get, set and view options for nsev_inverse_wrapper	10
4.4	options structure	10
5	Nonlinear Schroedinger equation with vanishing boundaries - Inverse Nonlinear Fourier Transform	11
5.1	nsev_inverse_wrapper - interact with FNFT library	11
5.2	get, set and view options for nsev_inverse_wrapper	12
5.3	options structure	12
6	example functions	13
	Python Module Index	15
	Index	17

MODULE OVERVIEW

This file is part of FNFTpy. FNFTpy provides wrapper functions to interact with FNFT, a library for the numerical computation of nonlinear Fourier transforms.

For FNFTpy to work, a copy of FNFT has to be installed. For general information, source files and installation of FNFT, visit FNFT's github page: <https://github.com/FastNFT>

For information about setup and usage of FNFTpy see README.md or documentation.

FNFTpy is free software; you can redistribute it and/or modify it under the terms of the version 2 of the GNU General Public License as published by the Free Software Foundation.

FNFTpy is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Contributors:

Christoph Mahnke, 2018

KORTEWEG-DE-FRIES EQUATION

2.1 kdvv - calculate the Nonlinear Fourier Transform

`FNFTpy.fnft_kdvv_wrapper.kdvv(u, tvec, M=128, Xi1=-2, Xi2=2, dis=None)`

Calculate the Nonlinear Fourier Transform for the Korteweg-de Vries equation with vanishing boundaries.

This function is intended to be 'convenient', which means it automatically calculates some variables needed to call the C-library and uses some default options. Own options can be set by passing optional arguments (see below).

It converts all Python input into the C equivalent and returns the result from FNFT. If a more C-like interface is desired, the function 'kdvv_wrapper' can be used (see documentation there).

Arguments:

`u` : numpy array holding the samples of the field to be analyzed

`tvec` : time vector

`M` : number of samples for the continuous spectrum to calculate,

Optional arguments:

`Xi1, Xi2` [min and max frequency for the continuous spectrum] default = -2, 2

`dis` : determines the discretization, default = 17

0 = 2split1a 1 = 2split1b 2 = 2split2a 3 = 2split2b 4 = 2split2s 5 = 2split3a 6 = 2split3b
7 = 2split3s 8 = 2split4a 9 = 2split4b 10 = 2split5a 11 = 2split5b 12 = 2split6a 13 =
2split6b 14 = 2split7a 15 = 2split7b 16 = 2split8a 17 = 2split8b

Returns:

`rdict` : dictionary holding the fields (depending on options)

`return_value` : return value from FNFT

`cont` : continuous spectrum

2.2 kdvv_wrapper - interact with FNFT library

`FNFTpy.fnft_kdvv_wrapper.kdvv_wrapper(D, u, T1, T2, M, Xi1, Xi2, K, options)`

Calculate the Nonlinear Fourier Transform for the Korteweg-de Vries equation with vanishing boundaries.

This function's interface mimics the behavior of the function 'fnft_kdvv' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'kdvv' can be used (see documentation there).

Arguments:

D : number of samples

u : numpy array holding the samples of the field to be analyzed

T1, T2 : time positions of the first and the last sample

M : number of values for the continuous spectrum to calculate

Xi1, Xi2 : min and max frequency for the continuous spectrum

K : maximum number of bound states to calculate (no effect yet)

options : options for kdvv as KdvvOptionsStruct. Can be generated e.g. with 'get_kdvv_options()'

Returns:

rdict : dictionary holding the fields (depending on options)

return_value : return value from FNFT

cont : continuous spectrum

2.3 get, set and view options for kdvv_wrapper

`FNFTpy.options_handling.fnft_kdvv_default_opts_wrapper()`

Get the default options for kdvv directly from the FNFT C-library.

Returns:

options : KdvvOptionsStruct with options for kdvv_wrapper

`FNFTpy.options_handling.print_kdvv_options(opts=None)`

Print options of a KdvvOptionsStruct for kdvv.

When called without additional argument, the default options from FNFT are printed.

Optional arguments:

opts : KdvvOptionsStruct, e.g. created by get_kdvv_options()

`FNFTpy.options_handling.get_kdvv_options(dis=None)`

Get an KdvvOptionsStruct struct for use with kdvv_wrapper.

When called without additional optional arguments, the default values from FNFT are used.

Optional arguments:

dis: discretization, default = 17

0 = 2split1a 1 = 2split1b 2 = 2split2a 3 = 2split2b 4 = 2split2s 5 = 2split3a 6 = 2split3b
7 = 2split3s 8 = 2split4a 9 = 2split4b 10 = 2split5a 11 = 2split5b 12 = 2split6a 13 =
2split6b 14 = 2split7a 15 = 2split7b 16 = 2split8a 17 = 2split8b

Returns:

options : KdvvOptionsStruct

2.4 options structure

`class FNFTpy.typesdef.KdvvOptionsStruct`

Ctypes options struct for interfacing fnft_kdvv

NONLINEAR SCHROEDINGER EQUATION WITH PERIODIC BOUNDARIES

3.1 nsep - calculate the Nonlinear Fourier Transform

`FNFTpy.fnft_nsep_wrapper.nsep(q, T1, T2, kappa=1, loc=None, filt=None, bb=None, maxev=None, dis=None, nf=None)`

Calculate the Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with periodic boundaries.

This function is intended to be 'convenient', which means it automatically calculates some variables needed to call the C-library and uses some default options. Own options can be set by passing optional arguments (see below). Options can be set by passing optional arguments (see below).

It converts all Python input into the C equivalent and returns the result from FNFT. If a more C-like interface is desired, the function 'nsep_wrapper' can be used (see documentation there).

Arguments:

`q` : numpy array holding the samples of the field to be analyzed

`T1, T2` : time positions of the first and the (d+1) sample

Optional arguments:

`kappa` : +/- 1 for focussing/defocussing nonlinearity, default = 1

`loc` : localization method for the spectrum, default = 2

0=Subsample and refine 1=Gridsearch 2=Mixed

`filt` : filtering of spectrum, default = 2

0=None 1=Manual 2=Auto

`bb`: bounding box used for manual filtering, default = [-inf, inf, -inf, inf]

`maxev` : maximum number of evaluations for root refinement, default = 20

`nf` : normalization Flag default = 1

0=off 1=on

`dis` : discretization, default = 2

0=2split2modal 1=2split2a 2=2split4a 3=2split4b 4=BO

Returns:

`rdict` : dictionary holding the fields (depending on options)

`return_value` : return value from FNFT

`K` : number of points in the main spectrum

`main` : main spectrum

m: number of points in the auxiliary spectrum

aux: auxiliary spectrum

3.2 nsep_wrapper - interact with FNFT library

`FNFTpy.fnft_nsep_wrapper.nsep_wrapper(D, q, T1, T2, kappa, options)`

Calculate the Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with periodic boundaries.

This function's interface mimics the behavior of the function 'fnft_nsep' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'nsep' can be used (see documentation there).

Arguments:

D : number of sample points

q : numpy array holding the samples of the field to be analyzed

T1, T2 : time positions of the first and the (D+1) sample

kappa : +/- 1 for focussing/defocussing nonlinearity

options : options for nsep as NsepOptionsStruct. Can be generated e.g. with 'get_nsep_options()'

Returns:

rdict : dictionary holding the fields (depending on options)

return_value : return value from FNFT

K : number of points in the main spectrum

main : main spectrum

M: number of points in the auxiliary spectrum

aux: auxiliary spectrum

3.3 get, set and view options for nsep_wrapper

`FNFTpy.options_handling.fnft_nsep_default_opts_wrapper()`

Get the default options for nsep directly from the FNFT C-library.

Returns:

options : NsepOptionsStruct for nsep_wrapper

`FNFTpy.options_handling.print_nsep_options(opts=None)`

Print options of a NsepOptionsStruct for nsep.

When called without additional arguments, the default options from FNFT are printed.

Optional arguments:

opts : NsepOptionsStruct, e.g. created by get_nsep_options

`FNFTpy.options_handling.get_nsep_options(loc=None, filt=None, bb=None, maxev=None, dis=None, nf=None)`

Get a NsepOptionsStruct struct for use with nsep_wrapper.

When called without additional optional argument, the default values from FNFT are used.

Optional arguments:

loc : localization of spectrum, default = 2

0=Subsample and Refine 1=Gridsearch 2=Mixed

filt : filtering of spectrum, default = 2

0=None 1=Manual 2=Auto

bb : bounding box used for manual filtering, default = [-inf, inf, -inf, inf]

maxev : maximum number of evaluations for root refinement, default = 20

nf : normalization flag, default = 1

0=off 1=on

dis : discretization, default = 1

0=2split2modal 1=2split2a 2=2split4a 3=2split4b 4=BO

Returns:

options : NsepOptionsStruct with options for nsep_wrapper

3.4 options structure

```
class FNFTpy.typesdef.NsepOptionsStruct
    Ctypes options struct for interfacing fnft_nsep
```


NONLINEAR SCHROEDINGER EQUATION WITH VANISHING BOUNDARIES

4.1 nsev_inverse - calculate the Inverse Nonlinear Fourier Transform

nsev_inverse .. autofunction:: FNFTpy.fnft_nsev_inverse_wrapper.nsev_inverse

4.2 nsev_inverse_wrapper - interact with FNFT library

FNFTpy.fnft_nsev_inverse_wrapper.**nsev_inverse_wrapper**(*M, contspec, Xi1, Xi2, K, bound_states, normconst_or_residues, D, T1, T2, kappa, options*)

Calculate the Inverse Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with vanishing boundaries.

This function's interface mimics the behavior of the function 'fnft_nsev_inverse' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'nsev_inverse' can be used (see documentation there).

Arguments:

M : number of sample points for continuous spectrum
contspec : numpy array holding the samples of the continuous spectrum
Xi1, Xi2 : frequencies defining the frequency range (cont spectrum)
K : number of bound states (currently no effect)
bound_states : bound states (currently no effect)
normconst_or_residues : bound state spectral coefficients (currently no effect)
D : number of samples for the output field
T1, T2 : borders of the desired time window
kappa : +1/-1 for focussing / defocussing NSE
options : options for nsev_inverse as NsevInverseOptionsStruct

Returns:

rdict : dictionary holding the fields (depending on options)
return_value : return value from FNFT
q : time field resulting from inverse transform
options : options for nsev_inverse as NsevInverseOptionsStruct

4.3 get, set and view options for nsev_inverse_wrapper

`FNFTpy.options_handling.fnft_nsev_default_opts_wrapper()`

Get the default options for nsev directly from the FNFT C-library.

Returns:

options : NsevOptionsStruct with options for nsev_wrapper

`FNFTpy.options_handling.print_nsev_options(opts=None)`

Print options of a NsevOptionsStruct for nsev.

When called without additional argument, the default options from FNFT are printed.

Optional arguments:

opts : NsevOptionsStruct, e.g. created by `get_nsev_options()`

`FNFTpy.options_handling.get_nsev_options(bsf=None, bsl=None, niter=None, Dsub=None, dst=None, cst=None, nf=None, dis=None)`

Get a NsevOptionsStruct for use with nsev_wrapper.

When called without additional optional arguments, the default values from FNFT are used.

Optional arguments:

bsf : bound state filtering, default = 2

0=none 1=basic 2=full

bsl : bound state localization, default = 2

0=Fast Eigenvalue 1=Newton 2=Subsample and refine

niter : number of iterations for Newton bound state location, default = 10

Dsub : number of samples used for ‘subsampling and refine’-method, default = 0 (auto)

dst : type of discrete spectrum, default = 0

0=norming constants 1=residues 2=both

cst : type of continuous spectrum, default = 0

0=reflection coefficient 1=a and b 2=both

dis : discretization, default = 3

0=2split2modal 1=2split2a 2=2split4a 3=2split4b 4=BO

nf : normalization flag, default = 1

0=off 1=on

Returns:

options : NsevOptionsStruct with options for nsev

4.4 options structure

`class FNFTpy.typesdef.NsevOptionsStruct`

Ctypes options struct for interfacing fnft_kdvv

NONLINEAR SCHROEDINGER EQUATION WITH VANISHING BOUNDARIES - INVERSE NONLINEAR FOURIER TRANSFORM

5.1 nsev_inverse_wrapper - interact with FNFT library

`FNFTpy.fnft_nsev_wrapper.nsev_wrapper` (*D, q, T1, T2, Xi1, Xi2, M, K, kappa, options*)

Calculate the Nonlinear Fourier Transform for the Nonlinear Schroedinger equation with vanishing boundaries.

This function's interface mimics the behavior of the function 'fnft_nsev' of FNFT. It converts all Python input into the C equivalent and returns the result from FNFT. If a more simplified version is desired, 'nsev' can be used (see documentation there).

Arguments:

D : number of sample points

q : numpy array holding the samples of the field to be analyzed

T1, T2 : time positions of the first and the last sample

Xi1, Xi2 : min and max frequency for the continuous spectrum

M : number of values for the continuous spectrum to calculate

K : maximum number of bound states to calculate

kappa : +/- 1 for focussing/defocussing nonlinearity

options : options for nsev as NsevOptionsStruct

Returns:

rdict : dictionary holding the fields (depending on options)

return_value : return value from FNFT

bound_states_num : number of bound states found

bound_states : array of bound states found

disc_norm : discrete spectrum - norming constants

disc_res : discrete spectrum - residues

cont_ref : continuous spectrum - reflection coefficient

cont_a : continuous spectrum - scattering coefficient a

cont_b : continuous spectrum - scattering coefficient b

5.2 get, set and view options for nsev_inverse_wrapper

`FNFTpy.options_handling.fnft_nsev_inverse_default_opts_wrapper()`

Get the default options for nsev_inverse directly from the FNFT C-library.

Returns:

options : NsevInverseOptionsStruct with options for nsev_inverse_wrapper

`FNFTpy.options_handling.print_nsev_inverse_options(opts=None)`

Print options of a NsevInverseOptionsStruct for nsev_inverse.

When called without additional argument, the default options from FNFT are printed.

Optional arguments:

opts : NsevInverseOptionsStruct, e.g. created by `get_nsev_options()`

`FNFTpy.options_handling.get_nsev_inverse_options(dis=None, cst=None, csim=None, max_iter=None, osf=None)`

Get a NsevInverseOptionsStruct for use with nsev_inverse_wrapper.

When called without additional optional arguments, the default values from FNFT are used.

Optional arguments:

dis : discretization, default = 3

0=2split2modal 1=2split2a 2=2split4a 3=2split4b 4=BO

cst : type of continuous spectrum, default = 0

0=Reflection coefficient 1=B of tau

csim : inversion method for the continuous part, default = 0

0=default 1=Transfermatrix with reflection coefficients 2=Transfermatrix with a,b from iteration

max_iter : maximum number of iterations for iterative methods, default = 100

osf : oversampling factor

Returns:

options : NsevInverseOptionsStruct with options for nsev_inverse_wrapper.

5.3 options structure

`class FNFTpy.typesdef.NsevInverseOptionsStruct`

Ctypes options struct for interfacing fnft_nsev_inverse.

EXAMPLE FUNCTIONS

`FNFTpy.tests.print_default_options()`

Print the default options for kdvv, nsep and nsev.

`FNFTpy.tests.kdvvexample()`

Mimics the C example for calling `fnft_kdvv`.

`FNFTpy.tests.nsepexample()`

Mimics the C example for calling `fnft_nsep`.

`FNFTpy.tests.nsevexample()`

Mimics the C example for calling `fnft_nsev`.

`FNFTpy.tests.nsevinversetest()`

Mimics the C example for calling `fnft_nsev_inverse`.

PYTHON MODULE INDEX

f

`FNFTpy`, [1](#)

INDEX

F

fnft_kdvv_default_opts_wrapper() (in module FN-
FTpy.options_handling), 4
fnft_nsep_default_opts_wrapper() (in module FN-
FTpy.options_handling), 6
fnft_nsev_default_opts_wrapper() (in module FN-
FTpy.options_handling), 10
fnft_nsev_inverse_default_opts_wrapper() (in module
FNFTpy.options_handling), 12
FNFTpy (module), 1

G

get_kdvv_options() (in module FN-
FTpy.options_handling), 4
get_nsep_options() (in module FN-
FTpy.options_handling), 6
get_nsev_inverse_options() (in module FN-
FTpy.options_handling), 12
get_nsev_options() (in module FN-
FTpy.options_handling), 10

K

kdvv() (in module FNFTpy.fnft_kdvv_wrapper), 3
kdvv_wrapper() (in module FN-
FTpy.fnft_kdvv_wrapper), 3
kdvvexample() (in module FNFTpy.tests), 13
KdvvOptionsStruct (class in FNFTpy.typesdef), 4

N

nsep() (in module FNFTpy.fnft_nsep_wrapper), 5
nsep_wrapper() (in module FN-
FTpy.fnft_nsep_wrapper), 6
nsepexample() (in module FNFTpy.tests), 13
NsepOptionsStruct (class in FNFTpy.typesdef), 7
nsev_inverse_wrapper() (in module FN-
FTpy.fnft_nsev_inverse_wrapper), 9
nsev_wrapper() (in module FN-
FTpy.fnft_nsev_wrapper), 11
nsevexample() (in module FNFTpy.tests), 13
NsevInverseOptionsStruct (class in FNFTpy.typesdef),
12
nsevinversetest() (in module FNFTpy.tests), 13
NsevOptionsStruct (class in FNFTpy.typesdef), 10

P

print_default_options() (in module FNFTpy.tests), 13

print_kdvv_options() (in module FN-
FTpy.options_handling), 4
print_nsep_options() (in module FN-
FTpy.options_handling), 6
print_nsev_inverse_options() (in module FN-
FTpy.options_handling), 12
print_nsev_options() (in module FN-
FTpy.options_handling), 10