

asciidoc-preview real-time asciidoc preview

Basic info

Date: 2020.01.23
Author: Shieber
Version: 0.1

Lang	Name
English	Asdp-introduction-en
中文	Asdp-introduction-zh

Introduction

Asdp-introduction-en

Use the asciidoc-preview.vim plugin you can preview asciidoc on real-time through a browser. this plugin need your vim support py2 or py3

Usage:

Command:

AsciidocPreview

" open preview window in asciidoc buffer

AsciidocPreviewStop

" close the preview window and server

(when AsciidocPreview command can't open preview window, you can use the AsciidocPreviewStop command before using AsciidocPreview command)

Default Setting:

```
g:asdp_path_to_chrome = ""
```

```
" path to the chrome or the command to open chrome
```

```
" if set, g:asdp_browserfunc would be ignored
```

```
let g:asdp_browserfunc = 'ASDP_browserfunc_default'
```

```
" callback vim function to open browser, the only param is the url to open
```

```
g:asdp_auto_start = 0
```

```
" set to 1, the vim will open the preview window once enter the asciidoc buffer
```

```
g:asdp_auto_open = 0
```

```
" set to 1, the vim will auto open preview window when you edit the asciidoc file
```

```

g:asdp_auto_close = 1
" set to 1, the vim will auto close current preview window when change
" from asciidoc buffer to another buffer

g:asdp_refresh_slow = 0
" set to 1, the vim will just refresh asciidoc when save the buffer or
" leave from insert mode, default 0 is auto refresh asciidoc as you edit or
" move the cursor

let g:asdp_command_for_global = 0
" set to 1, the AsciidocPreview command can be use for all files,
" by default it just can be use in asciidoc file

let g:asdp_open_to_the_world = 0
" set to 1, server available to others in your network
" by default, the server only listens on localhost

```

Key Mapping:

By default this Plugin has no mapping, if you want to has your own mapping you can map the keys to “AsciidocPreview” for opening asciidoc preview window and map keys to “StopAsciidocPreview” for closing the preview window.

Examples for mapping the F8 key to open asciidoc preview window and F9 key to close preview window:

```

nmap <silent> <F8> <Plug>AsciidocPreview      " for normal mode
imap <silent> <F8> <Plug>AsciidocPreview      " for insert mode
nmap <silent> <F9> <Plug>StopAsciidocPreview  " for normal mode
imap <silent> <F9> <Plug>StopAsciidocPreview  " for insert mode

```

FAQ:

Q: the firefox preview window didn’ t close when leave the asciidoc file in vim

A: if you want the plugin auto close the preview window on firefox, you have to do some config:

1. open firefox
2. type **about:config** in the address bar and press Enter key
3. search **dom.allow_scripts_to_close_windows** item and set the value to **true**

说明

Asdp-introduction-zh

使用asciidoc-preview.vim插件可以实时通过浏览器预览asciidoc文件。使用该插件需要vim支持py2或py3。

使用和设置

命令:

AsciidocPreview

在打开asciidoc文件后, 使用该命令可以打开预览窗口

AsciidocPreviewStop

关闭 asciidoc预览窗口, 并停止开启的服务进程。在AsciidocPreview命令无效的情况下, 可以先AsciidocPreviewStop再AsciidocPreview

默认配置:

```
g:asdp_path_to_chrome = ""
```

设置chrome浏览器的路径(或是启动chrome的命令)若设置了该参数, g:asdp_browserfunc将被忽略

```
let g:asdp_browserfunc = 'ASDP_browserfunc_default'
```

vim回调函数, 参数为要打开的url

```
g:asdp_auto_start = 0
```

设置为1可以在打开asciidoc文件的时候自动打开浏览器预览, 只在打开asciidoc文件的时候打开一次

```
g:asdp_auto_open = 0
```

设置为 1 在编辑 asciidoc 的时候检查预览窗口是否已经打开, 否则自动打开预览窗口

```
g:asdp_auto_close = 1
```

在切换buffer的时候自动关闭预览窗口, 设置为 0 则在切换buffer的时候不动关闭预览窗口

```
g:asdp_refresh_slow = 0
```

设置为 1 则只有在保存文件, 或退出插入模式的时候更新预览, 默认为 0, 实时更新预览

```
let g:asdp_command_for_global = 0
```

设置为 1 则所有文件都可以使用 AsciidocPreview 进行预览, 默认只有asciidoc文件可以使用改命令

```
let g:asdp_open_to_the_world = 0
```

设置为 1, 在使用的网络中的其他计算机也能访问预览页面。默认只监听本地 (127.0.0.1), 其他计算机不能访问

键位绑定:

默认情况下, 插件没有进行任何的按键绑定, 如果想绑定按键去预览asciidoc文件, 可以绑定按键到 AsciidocPreview来打开预览窗口, 绑定按键到StopAsciidocPreview来关闭预览窗口。

按键绑定例子 (F8打开预览窗口, F9关闭预览窗口):

```
nmap <silent> <F8> <Plug>AsciidocPreview      "  
imap <silent> <F8> <Plug>AsciidocPreview      "  
nmap <silent> <F9> <Plug>StopAsciidocPreview  "  
imap <silent> <F9> <Plug>StopAsciidocPreview  "
```

FAQ:

Q: 在火狐浏览器中，预览页面不能自动关闭

A: 如果需要在火狐浏览器中启用自动关闭预览窗口，需要相关设置:

1. 打开火狐浏览器
2. 地址栏敲入`about:config`回车
3. 搜索`dom.allow_scripts_to_close_windows`选项，设置value为true