

Passive Error Resilience Through Ultrametric Geometry: A Proposal for p-Adic Quantum Metrology

Rowan Brad Quni-Gudzinis

2026-08-01

Author: Rowan Brad Quni-Gudzinis | **Date:** 2026-08-01 | **License:** CC-BY-4.0

Abstract

Active quantum error correction is the dominant paradigm for achieving fault-tolerant quantum computation, but its thermodynamic cost at utility scale remains unaddressed. Each round of syndrome extraction, decoding, and feedback erases information — and under Landauer’s principle, that erasure carries an irreducible energy cost that scales with system size. We explore an alternative: passive error resilience through ultrametric (p-adic) geometry, where noise self-organizes into hierarchical clusters that a single global measurement averages out automatically, without ancilla qubits, syndrome extraction, or feedback loops. Building on the Bruhat-Tits tree — the natural state space for the p-adic group $SL(2, \mathbb{Q}_p)$ — we propose a room-temperature photonic metrology architecture that exploits the hierarchical structure of noise as a computational resource rather than treating it as an enemy. We present the theoretical framework, a candidate experimental protocol, and a structured forecast assessing the probability of demonstrating standard-quantum-limit-beating precision within 24 months.

1. Introduction

The fault-tolerant quantum computing roadmap has been “roughly ten years away” since the mid-1990s [speculative — the timeline claim is widely repeated but the author considers it a self-perpetuating institutional forecast, not a falsifiable prediction]. While qubit counts and coherence times have improved, the fundamental architecture remains unchanged: encode logical qubits in a subspace of a larger physical Hilbert space, measure error syndromes, decode, and feed back — continuously, at cryogenic temperatures, with overhead factors of 10^{3-10} physical qubits per logical qubit. The energy cost of this process has received surprisingly little attention in the published literature [my conjecture — the author has searched for a peer-reviewed scaling analysis of the thermodynamic cost of fault-tolerant quantum computation at utility scale and has not found one, see Section 2].

Meanwhile, a separate line of inquiry has developed around ultrametric (p-adic) geometry in quantum physics. Beginning with the p-adic string theory program of the late 1980s and early 1990s, continuing through the p-adic AdS/CFT correspondence of the 2010s, and most recently extending to the Adelic Physics Programme’s structured assessment of when and whether non-Archimedean geometry will displace the Archimedean default in at least one scientific or engineering domain by

2036 [established — see ACRP-08, DOI: 10.5281/zenodo.21747228], the mathematical machinery of p-adic spaces has been gradually accumulating in the physics literature — but it has never been applied to the specific problem of passive error resilience in quantum metrology.

This paper proposes exactly that synthesis. We assess whether ultrametric geometry can provide a path to near-term quantum advantage that bypasses the thermodynamic wall facing active quantum error correction entirely — not by building a better quantum computer, but by building a quantum sensor that reads noise the way nature organizes it: hierarchically.

The structure is as follows. Section 2 reviews the thermodynamic argument against active QEC at scale. Section 3 introduces the mathematical framework of ultrametric spaces and the Bruhat-Tits tree. Section 4 presents the proposed metrology architecture. Section 5 provides a structured forecast with calibration register entries. Section 6 discusses practical applications and Section 7 concludes with open questions.

2. The Thermodynamic Wall

2.1 Landauer’s Principle and Active Error Correction

Landauer’s principle states that erasing one bit of information in a memory at temperature T dissipates at least $kT \ln 2$ of energy as heat [established — Landauer, 1961]. This is not an engineering constraint; it is a consequence of the second law of thermodynamics.

Active quantum error correction requires, at minimum, the following irreversible operations per error-correction round:

1. **Syndrome measurement:** The ancilla qubits are measured, collapsing their state and erasing the pre-measurement superposition. Each measurement of m ancilla qubits erases m bits.
2. **Decoding:** The classical decoder processes the syndrome data and selects a recovery operation. While the decoding algorithm itself can be implemented reversibly in principle, the practical need to complete decoding within the coherence time forces the use of irreversible classical logic gates, each of which dissipates heat.
3. **Feedback:** The recovery operation is applied to the data qubits. This step is unitary and therefore does not directly erase information — but the decision to apply it does, since the decoder’s output must be committed (erased) to trigger the feedback.

For a surface code with distance d protecting k logical qubits, the number of physical qubits scales as $O(d^2)$ and the number of syndrome measurement rounds between logical operations scales as $O(d)$. Each round involves $O(d^2)$ ancilla measurements. The total information-erasure burden per logical gate is therefore $O(d^3)$.

At utility scale — say, $k = 10^6$ logical qubits operating at a surface-code distance sufficient for a logical error rate of 10^{-15} per gate — the distance d must be several hundred. The information erasure per logical gate is then on the order of 10^8 bits. At a cryogenic operating temperature of 10 mK, the Landauer bound is approximately 10^{-25} J/bit, giving a minimum energy cost of approximately 10^{-17} J per logical gate. At a clock speed of 1 MHz, this yields roughly 10 kW of heat dissipation from Landauer-limited erasure alone — before accounting for the energy cost of the classical decoder, the dilution refrigerator, the control electronics, or any inefficiency in the measurement chain.

2.2 The Missing Scaling Analysis

The author has searched the published literature for a peer-reviewed analysis that closes the full thermodynamic budget for a utility-scale fault-tolerant quantum computer. To date, no such analysis has been found [my conjecture — the search was conducted across OpenAlex, Crossref, Zenodo records, arXiv, and web search as part of the due diligence for this project; see the companion Phase 1 report in the project repository]. The published error-correction literature focuses almost exclusively on threshold theorems and code performance as functions of physical error rate, not on the system-level energy budget.

This absence is concerning. If the thermodynamic argument outlined above is correct — even to within an order of magnitude — then active QEC at utility scale faces a heat-dissipation problem that no amount of engineering optimization can circumvent. The laws of thermodynamics are not a roadmap item; they are a physical constraint that must be satisfied before any other consideration.

2.3 The Sensing Escape Hatch

Quantum metrology does not face the same thermodynamic wall. A quantum sensor does not need to maintain coherence across millions of qubits for thousands of gate operations. It needs to maintain entanglement across a small number of probes ($N \sim 10$) for the duration of a single measurement cycle. This radically reduces the information-erasure burden — and, as we will argue, the ultrametric structure of noise in certain physical platforms may eliminate it almost entirely.

3. Ultrametric Geometry and the Bruhat-Tits Tree

3.1 The Strong Triangle Inequality

A metric space (X, d) is called *ultrametric* if its distance function satisfies the strong triangle inequality:

$$d(x, z) \leq \max(d(x, y), d(y, z)) \text{ for all } x, y, z \in X.$$

This is a strictly stronger condition than the ordinary triangle inequality. Its most striking consequence is that *all triangles are isosceles with two equal long sides* — the two largest of the three distances $d(x, y)$, $d(y, z)$, $d(x, z)$ must be equal. This forces the space to organize into a nested hierarchy of clopen balls: at any fixed radius r , the balls of radius r partition the space into disjoint clusters, with the clusters at smaller radii nested inside those at larger radii.

The p -adic numbers $\mathbb{Q}_p$, for any prime p , are the canonical example of an ultrametric space. The p -adic absolute value $|\cdot|_p$ induces the metric $d_p(x, y) = |x - y|_p$, which satisfies the strong triangle inequality.

3.2 The Bruhat-Tits Tree

The Bruhat-Tits tree T_p is the natural geometric object associated with the p -adic group $SL(2, \mathbb{Q}_p)$. It is a $(p+1)$ -regular tree whose vertices correspond to homothety classes of lattices in $\mathbb{Q}_p^2$ and whose edges correspond to inclusion relations.

For our purposes, the key properties of the Bruhat-Tits tree are:

1. **Hierarchical structure:** The tree organizes vertices into levels based on their distance from any chosen root. Vertices at the same level form clusters whose mutual distances are bounded

by the tree depth.

2. **Apartment structure:** Maximal flat subspaces (apartments) of the Bruhat-Tits building provide a natural coordinate system for labeling error syndromes. In the $SL(2, \mathbb{Q}_p)$ case, an apartment is simply an infinite path through the tree, corresponding to a choice of basis for the underlying p -adic vector space.
3. **Automorphism group:** The tree automorphism group includes $SL(2, \mathbb{Q}_p)$, which acts transitively on vertices. This group structure can be exploited for transversal logical gates in a code construction — an automorphism of the tree induces a unitary on the encoded Hilbert space that preserves the code subspace.

Underlying this approach are several critical assumptions. First, existing QEC code constructions must admit a reformulation on Bruhat-Tits trees without catastrophic performance loss — a plausible claim given that geometric reformulations (e.g., symplectic codes to toric codes) typically preserve or improve performance. Second, the tree structure must admit a tensor-product operation compatible with concatenated coding, which is an open mathematical question for buildings of rank greater than one. Third, and most critically, a tree-based code must achieve a threshold within a factor of two of the surface-code threshold — currently an unbuilt construction [speculative — these assumptions are enumerated and assessed in ACRP-08].

3.3 Error Hierarchies in Ultrametric Spaces

The ultrametric property has a direct physical interpretation for error correction. Consider a noise process that acts on N physical qudits. In an ordinary Euclidean metric, the distinguishability of two error patterns depends on their Hamming distance — the number of qudits on which they differ. In an ultrametric space, distinguishability is governed by tree depth: two error patterns that diverge at a shallow level of the tree (i.e., belong to different coarse clusters) are more easily distinguished than two that diverge at a deep level.

This hierarchical distinguishability suggests a decoding strategy: resolve coarse errors first (shallow divergences), then refine. Because the strong triangle inequality forces errors into a nested hierarchy of clusters, a decoder that processes syndromes level-by-level — from root to leaves — naturally separates large-scale from small-scale correlations without requiring a global optimization.

4. Proposed Metrology Architecture

4.1 From Code to Sensor

The standard QEC paradigm asks: “Given a noisy quantum channel and a desired logical error rate, what is the smallest overhead required?” The metrology paradigm asks a different question: “Given a noisy quantum sensor and a desired measurement precision, what is the smallest resource cost required to beat the standard quantum limit?”

The distinction is not merely semantic. In QEC, the figure of merit is the logical error rate after decoding. In metrology, the figure of merit is the estimator variance after measurement. An ultrametric code that cannot achieve a competitive logical error rate for computation may still achieve SQL-beating precision for sensing — because the requirement is weaker (precision, not fidelity) and the measurement is final (no need for repeated rounds of correction).

4.2 Photonic Platform

We propose a photonic implementation using spontaneous parametric down-conversion (SPDC) as the entangled photon source. The experimental requirements are modest by current standards:

- **Photon source:** Type-II SPDC in a periodically poled KTP crystal, producing $N \sim 8\text{--}10$ polarization-entangled photon pairs.
- **Encoding:** Each photon’s path degree of freedom encodes a qudit in a p-adic basis, with the p-adic coordinate corresponding to the photon’s transverse spatial mode.
- **Hierarchical measurement:** A sequence of dichroic beam splitters implements a tree-structured measurement that projects onto the Bruhat-Tits apartment coordinates. The measurement order follows the tree hierarchy — coarse splitting first (apartment identification), then fine splitting (vertex within apartment).
- **Detection:** Single-photon avalanche diodes (SPADs) with coincidence counting.
- **Operating conditions:** Room temperature (~ 300 K). No cryogenic cooling required.

The key empirical question — and the primary risk to the proposal — is whether the photonic noise in this platform exhibits the ultrametric correlation structure that the theoretical framework assumes. Section 5 registers a dated prediction for this test.

4.3 Resource Comparison

Resource	Surface-Code FTQC	p-Adic Metrology (Proposed)
Physical qubits/qudits	$\sim 10^6$	~ 10
Ancilla qubits	$\sim 99\%$ of total	0
Operating temperature	~ 10 mK	~ 300 K
Error correction	Active (syndrome + decode + feedback)	Passive (geometry)
Gate/model complexity	Universal circuit model	Single-shot measurement
Timeline to practical advantage	“10 years” (since 1995)	24 months (forecast, see §5)

5. Structured Forecast

The following analysis is a structured judgment exercise — not a Bayesian computation. Probability ranges are the analyst’s estimates, loosely anchored to historical reference classes where available. The primary value is in making assumptions explicit and registering dated, falsifiable predictions.

5.1 Candidate Assessment

We assess the candidate comparatively against three alternatives:

Candidate	Probability Range	Impact (1-10)	Timeline
Ultrametric p-adic metrology (this work)	0.20–0.40	8	≤ 2 years
Dissipative QEC sensing (Reiter et al., 2017)	0.15–0.30	7	Medium
Standard SQL-limited sensing	1.0 (baseline)	0	Now

The probability range for the proposed approach is higher than the general Bruhat-Tits QEC forecast (ACRP-08: 0.12–0.25 by 2036 for computation) because metrology has a relaxed threshold — SQL beating is easier than fault-tolerant logical gates.

5.2 Enabling Assumptions

#	Assumption	Confidence	Type
A1	Photonic noise exhibits hierarchical (ultrametric) correlation structure	0.70	Empirical
A2	A global measurement protocol achieves noise suppression $\geq 1/\sqrt{N}$	0.60	Theoretical
A3	Room-temperature operation does not introduce unstructured noise that overwhelms the ultrametric benefit	0.50	Empirical
A4	Existing photonic hardware (SPDC + SPADs) is sufficient for prototyping	0.85	Infrastructure
A5	The hierarchical measurement can be reduced to a feasible optical setup	0.55	Engineering

The dependency chain is: $A4 \rightarrow A5 \rightarrow A1 \rightarrow A2 \rightarrow A3 \rightarrow \text{DEMONSTRATION}$. The ranking is **CONDITIONAL** on A1: if photonic noise proves non-ultrametric, the dissipative QEC approach of Reiter et al. becomes the preferred near-term path.

5.3 Calibration Register

[CHECK: 2026-10-01] Noise correlation measurements in a photonic SPDC source will show ultrametric violator fraction $< 30\%$ compared to a random-noise baseline ($\sim 80\%$ violators), confirming A1.
Likelihood-Anchor: Calibrated Subjective

Strength: [WEAK]
Status: [PENDING]

[CHECK: 2027-01-01] A p-adic hierarchical measurement protocol on $N=8$ entangled photons will demonstrate precision improvement over the standard quantum limit by factor $\geq 1.5\times$, measured by Allan deviation in a room-temperature interferometric setup.

Likelihood-Anchor: Calibrated Subjective (P ≈ 0.30 overall)

Strength: [WEAK]
Status: [PENDING]

[CHECK: 2027-08-01] If A1 and A2 are confirmed, a full experimental demonstration paper will be published on Zenodo.

Likelihood-Anchor: Calibrated Subjective (P ≈ 0.15 conditional on A1+A2)

Strength: [WEAK]
Status: [PENDING]

6. Practical Applications

If the proposed metrology architecture succeeds, the near-term applications span three domains with combined market values exceeding \$100 billion annually [speculative — market estimates are approximate; the key claim is that precision sensing is not a niche application]:

1. **Magnetic field sensing.** A room-temperature p-adic magnetometer with sub-femtotesla sensitivity would replace cryogenic SQUID-based systems in medical imaging (MEG/MCG), mineral exploration, and navigation.
2. **Molecular spectroscopy.** Ultrametric spectral resolution at the single-molecule level would enable portable, low-cost chemical analysis for pharmaceutical quality control, environmental monitoring, and security screening.
3. **Clock synchronization.** p-Adic timing networks could provide GPS-independent synchronization with nanosecond precision — critical for telecommunications, financial trading networks, and distributed sensor arrays.

7. Discussion and Open Questions

7.1 Limitations

The approach has several important limitations. First, the empirical claim that photonic noise is ultrametrically structured is untested — A1 carries confidence 0.70 specifically because it is the weakest link. Second, even if the sensor works as predicted, it does not scale to universal quantum computation; it is a metrology tool, not a computer. Third, the market for precision sensors, while large, is fragmented across industries with different regulatory and certification requirements.

7.2 What Would Disconfirm This Approach?

The proposal is falsifiable. It would be disconfirmed if:

1. Noise correlation measurements on an SPDC source show a violator fraction consistent with random noise ($\geq 70\%$), indicating that photonic noise is NOT ultrametrically structured.

2. The hierarchical measurement protocol, when implemented, shows precision no better than the standard quantum limit.
3. Room-temperature environmental noise — thermal photons, vibrations, electronic interference — introduces unstructured noise that overwhelms any ultrametric benefit.

Any of these outcomes would be a publishable scientific result: “Photonic noise does not exhibit the ultrametric correlation structure assumed in p-adic quantum metrology proposals” is a useful constraint for the field.

7.3 The Broader Question

This paper is motivated by a set of open questions that the author has been unable to resolve through literature search alone. They are presented here not as rhetorical devices but as genuine invitations to the community:

1. **The energy wall:** Is there a published scaling analysis that closes the thermodynamic budget for a utility-scale fault-tolerant quantum computer? If not, why is this gap not discussed more openly?
2. **The geometry of noise:** If noise in real physical platforms exhibits hierarchical structure, why do standard QEC codes assume independent or short-range correlated noise?
3. **The circuit assumption:** Is the circuit model of quantum computation a physical necessity or a historical choice? Does the very need for active error correction signal that we have chosen the wrong representation?
4. **Falsification:** What empirical result would demonstrate that the FTQC roadmap needs fundamental revision? If the field has no answer to this question, how do we distinguish a research programme from a belief?

The author does not claim to have definitive answers to these questions. The proposed metrology architecture is one attempt to explore what happens when you take a different geometry seriously — not as a replacement for existing approaches, but as a complementary path that bypasses the thermodynamic wall entirely.

Declarations

Funding: This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

Conflicts of Interest: The author declares no competing interests.

Ethics Approval: Not applicable — no human subjects, animal research, or sensitive data.

Consent to Participate: Not applicable.

Author Contributions: Sole author — R.B.Q.-G. conceived the approach, conducted the literature search, performed the structured forecast, and wrote the manuscript.

Data Availability: All artifacts (due diligence report, literature classification, structured forecast protocol, red-team audit) are available in the project repository at <https://github.com/QNFO/ultrametric-p-adic-metrology>. The structured forecast builds on ACRP-08 (DOI: 10.5281/zenodo.21747228).

Code Availability: Literature search scripts and classification tools are available in the project repository.

Use of Artificial Intelligence: The literature search (Phase 1) and structured forecast (Phase 4) were carried out with the assistance of large language models (DeepSeek-v4-pro via the DeepChat agent platform) for API query construction, data parsing, and structured analysis. All external search results were independently verified against the source APIs. The structured forecast was reviewed by a cross-review subagent (same underlying model) and a parent-agent red-team audit.

Bibliography

1. Landauer, R. (1961). Irreversibility and heat generation in the computing process. *IBM Journal of Research and Development*, 5(3), 183–191.
2. Brekke, L. & Freund, P. G. O. (1993). p-adic numbers in physics. *Physics Reports*, 233(1), 1–66. DOI: 10.1016/0370-1573(93)90043-d.
3. Reiter, F. et al. (2017). Dissipative quantum error correction and application to quantum sensing with trapped ions. *Nature Communications*, 8, 1822. DOI: 10.1038/s41467-017-01895-5.
4. Quni-Gudzinias, R. B. (2026). When Will Non-Archimedean Geometry Displace the Real Numbers? A Structured Assessment of the Adelic Substrate Thesis. Zenodo. DOI: 10.5281/zenodo.21747228.
5. Quni-Gudzinias, R. B. (2026). Adelic Shannon Theory v2.1. Zenodo. DOI: 10.5281/zenodo.21698976.
6. Quni-Gudzinias, R. B. (2026). Adelic Entropic Numbers v1.1. Zenodo. DOI: 10.5281/zenodo.21698978.
7. Quni-Gudzinias, R. B. (2026). Adelic Rate-Distortion Theory v1.0. Zenodo. DOI: 10.5281/zenodo.21705076.
8. Quni-Gudzinias, R. B. (2026). Zitterbewegung as a p-Adic Observable: P1 Correction (ACRP-02). Zenodo. DOI: 10.5281/zenodo.21736091.
9. Gilli, M. et al. (2017). Geodesic bulk diagrams on the Bruhat-Tits tree. *Physical Review D*, 96, 066024. DOI: 10.1103/physrevd.96.066024.
10. Heydeman, M. et al. (2018). Tensor networks, p-adic fields, and algebraic curves: arithmetic and the AdS₃/CFT₂ correspondence. *Advances in Theoretical and Mathematical Physics*, 22(1), 93–176. DOI: 10.4310/atmp.2018.v22.n1.a4.