

Content tabs

Content tabs group related content, letting readers switch between alternatives without scrolling.

Syntax

Use `===` to define tabs:

```
=== "Tab 1"
    Content for tab 1. Must be indented.

=== "Tab 2"
    Content for tab 2. Must be indented.
```

Example: Installation methods

```
=== "pip"
    `` bash
    pip install mypackage
    ``

=== "conda"
    `` bash
    conda install mypackage
    ``

=== "Docker"
    `` bash
    docker pull mypackage:latest
    ``
```

```
pip install mypackage
```

```
conda install mypackage
```

```
docker pull mypackage:latest
```

```
pip
```

conda

Docker

Example: Operating systems

```
=== "Linux"  
    `` bash  
    docsforge serve  
    ``  
  
=== "macOS"  
    `` bash  
    docsforge serve  
    ``  
  
=== "Windows"  
    `` powershell  
    docsforge serve  
    ``
```

docsforge serve

docsforge serve

docsforge serve

Linux

macOS

Windows

Example: Programming languages

```
=== "Python"  
    `` python  
    def greet(name):  
        return f"Hello, {name}!"  
    ``  
  
=== "JavaScript"
```

```

    `` javascript
    function greet(name) {
        return `Hello, ${name}!`;
    }
    ``

=== "Rust"
    `` rust
    fn greet(name: &str) -> String {
        format!("Hello, {}!", name)
    }
    ``

```

```

def greet(name):
    return f"Hello, {name}!"

```

```

function greet(name) {
    return `Hello, ${name}!`;
}

```

```

fn greet(name: &str) -> String {
    format!("Hello, {}!", name)
}

```

Python

JavaScript

Rust

Nested tabs

Tabs can contain any Markdown, including other tabs:

```

=== "Setup"
    === "Linux"
        `` bash
        sudo apt install python3
        ``

    === "Windows"
        `` powershell
        winget install Python.Python.3.11
        ``

```

```
=== "Configuration"
    Edit `docsforge.yml` to customize your site.
```

Tab labels with icons

Use icons in tab labels:

```
=== ":material-linux: Linux"
    Linux-specific content.

=== ":material-apple: macOS"
    macOS-specific content.

=== ":material-microsoft-windows: Windows"
    Windows-specific content.
```

Configuration

Content tabs require the `pymdownx.tabbed` extension:

```
markdown_extensions:
  - pymdownx.tabbed:
      alternate_style: true
```

The `alternate_style` option provides the modern tabbed interface.

Next steps

- [Code blocks](#)
- [Admonitions](#)

 Jun 01, 2026