

Online Contests Solutions

Saman Saadi

Contents

1	HackerRank	1
1.1	New Year Chaos	1
1.2	Minimum Swaps 2	2

Chapter 1

HackerRank

1.1 New Year Chaos

You can find the question in this link.

We define $index_i$ as the current index for person i . For example if we have 1,2,3,4 and 4 bribes 3, the queue looks like 1,2,4,3. So $index_4 = 3$. Since no body can bribe more than 2 times, $index_i \geq i - 2$ for $1 \leq i \leq n$. Consider person n . No body can bribe that person. So $n - 2 \leq index_n \leq n$. After we retruned that person to his actual place we can consider $n - 1$. So we have $n - 3 \leq index_{n-1} \leq n - 1$ (note that at this moment $index_n = n$).

```
void minimumBribes(vector<int> q) {  
  
    const auto& n = q.size();  
    int res = 0;  
    for (int num = n; num > 0; --num)  
    {  
        for (int i = max(0, num - 3); i < num - 1; ++i)  
        {  
            if (q[i] == num)  
            {  
                ++res;  
                swap(q[i], q[i + 1]);  
            }  
        }  
        if (q[num - 1] != num)  
        {  
            cout << "Too chaotic" << endl;  
            return;  
        }  
    }  
    cout << res << endl;  
}
```

}

1.2 Minimum Swaps 2

See the problem statement in this link.

We define $index_i$ as the current index of number i . Suppose we have n numbers, so $1 \leq index_i \leq n$. The goal is to have $index_i = i$. Without losing generality suppose $i < j \wedge index_i = j$. There are two cases to consider:

1. If $index_j = i$, then by swapping arr_i and arr_j , we put both i and j in their corresponding positions.
2. If $index_j = k \wedge k \neq i \wedge k \neq j$. In this case by swapping arr_i and arr_j we only put i in its corresponding position. So we need to do an extra swap to put j in its correct position.

We can start from $i = 1$ to $i = n$ and make sure i is in correct position; otherwise we perform a swap. In each iteration we fix the position of one or two numbers. A good example is $\{4, 3, 2, 1\}$.

```
int minimumSwaps(vector<int> arr) {

    const auto& n = arr.size();
    vector<int> index(n + 1);

    for (int i = 0; i < n; ++i)
        index[arr[i]] = i;
    int cnt = 0;
    for (int num = 1; num <= n; ++num)
    {
        if (index[num] != num - 1)
        {
            ++cnt;
            index[arr[num - 1]] = index[num];
            swap(arr[index[num]], arr[num - 1]);
            index[num] = num - 1;
        }
    }
    return cnt;
}
```