

CalcPauliTransferMatrix

```
SetDirectory @ NotebookDirectory[];  
Import["../Link/QuESTlink.m"];
```

Doc

? CalcPauliTransferMatrix

Symbol

CalcPauliTransferMatrix[circuit] returns a PTM operator equivalent to the given circuit.
CalcPauliTransferMatrix accepts optional argument AssertValidChannels.



? AssertValidChannels

Symbol

Optional argument to CalcCircuitMatrix, GetCircuitSuperoperator and CalcPauliTransferMatrix (default True), specifying whether to simplify their outputs by asserting that all channels therein are completely-positive and trace-preserving. For example, this asserts that the argument to a damping channel lies between 0 and 1 (inclusive).



? PTM

Symbol

PTM[matrix] is a Pauli-transfer matrix representation of an operator or channel.
The subscript indices specify which Paulis of a Pauli string are operated upon.



Correctness

CalcPauliTransferMatrix @ Rz₅[x]

MatrixForm @ First @ %


PTM₅ [SparseArray [ Specified elements: 6
Dimensions: {4, 4}]]]

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos[x] & -\sin[x] & 0 \\ 0 & \sin[x] & \cos[x] & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

CalcPauliTransferMatrix @ C₀[X₁]

MatrixPlot @ First @ %


PTM_{1,0} [SparseArray[ Specified elements: 16
Dimensions: {16, 16}]]




CalcPauliTransferMatrix @ C₁[X₀]

MatrixPlot @ First @ %

PTM_{0,1} [SparseArray[ Specified elements: 16
Dimensions: {16, 16}]]



CalcPauliTransferMatrix @ C_{5,7}[R[x, X₄ Y₂]]

PTM_{4,2,5,7} [SparseArray[ Specified elements: 1056
Dimensions: {256, 256}]]

AssertValidChannels -> False

CalcPauliTransferMatrix[Rz₀[x], AssertValidChannels → False]

MatrixForm @ First @ %

PTM₀ [SparseArray[ Specified elements: 6
Dimensions: {4, 4}]]

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & \frac{1}{2} (e^{-ix} + e^{ix}) & \frac{1}{2} (-i e^{-ix} + i e^{ix}) & 0 \\ 0 & \frac{1}{2} (i e^{-ix} - i e^{ix}) & \frac{1}{2} (e^{-ix} + e^{ix}) & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

CalcPauliTransferMatrix[Damp₀[x], AssertValidChannels → False]

Normal @ First @ %

PTM₀ [SparseArray[ Specified elements: 8
Dimensions: {4, 4}]]

$$\left\{ \left\{ \frac{1}{2} (1 + \sqrt{1-x} \text{Conjugate}[\sqrt{1-x}] + \sqrt{x} \text{Conjugate}[\sqrt{x}]), \right. \right. \\ \left. 0, 0, \frac{1}{2} (1 - \sqrt{1-x} \text{Conjugate}[\sqrt{1-x}] - \sqrt{x} \text{Conjugate}[\sqrt{x}]) \right\}, \\ \left\{ 0, \frac{1}{2} (\sqrt{1-x} + \text{Conjugate}[\sqrt{1-x}]), \frac{1}{2} (i \sqrt{1-x} - i \text{Conjugate}[\sqrt{1-x}]), 0 \right\}, \\ \left\{ 0, \frac{1}{2} (-i \sqrt{1-x} + i \text{Conjugate}[\sqrt{1-x}]), \frac{1}{2} (\sqrt{1-x} + \text{Conjugate}[\sqrt{1-x}]), 0 \right\}, \\ \left. \left\{ \frac{1}{2} (1 - \sqrt{1-x} \text{Conjugate}[\sqrt{1-x}] + \sqrt{x} \text{Conjugate}[\sqrt{x}]), \right. \right. \\ \left. 0, 0, \frac{1}{2} (1 + \sqrt{1-x} \text{Conjugate}[\sqrt{1-x}] - \sqrt{x} \text{Conjugate}[\sqrt{x}]) \right\} \right\}$$

Errors

CalcPauliTransferMatrix[]

 **CalcPauliTransferMatrix**: Invalid arguments. See ?CalcPauliTransferMatrix

\$Failed

CalcPauliTransferMatrix[X₀, BadOption → Yes]

 **OptionValue**: Unknown option BadOption for CalcPauliTransferMatrix.

\$Failed

CalcPauliTransferMatrix[Blob₀]

 **CalcPauliTransferMatrix**: Circuit contained an unrecognised or unsupported gate: Blob₀


\$Failed

CalcPauliTransferMatrix @ U₀[x]

 **CalcPauliTransferMatrix**: Circuit contained an unrecognised or unsupported gate: U₀[x]

\$Failed

CalcPauliTransferMatrix[{G[x], Fac[2]}]

 **CalcPauliTransferMatrix**: Circuit must explicitly target at least one qubit.

\$Failed

CalcPauliTransferMatrix[Rx₀[]]

 **CalcPauliTransferMatrix**: Invalid arguments. See ?CalcPauliTransferMatrix

\$Failed

```
CalcPauliTransferMatrix[{}]
```

... **CalcPauliTransferMatrix**: Circuit must explicitly target at least one qubit.

```
$Failed
```