

# CLup - Customer Line-up

**ITD**  
**Implementation and Testing Deliverable**

Andrea Franchini(10560276)  
Ian Di Dio Lavore (10580652)  
Luigi Fusco(10601210)



10-01-2020

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Scope . . . . .	1
1.2	List of definitions and abbreviations . . . . .	1
1.3	Abbreviations . . . . .	1
1.4	Definitions . . . . .	1
1.5	Reference documents . . . . .	2
1.6	Document structure . . . . .	2
<b>2</b>	<b>Implemented Requirements</b>	<b>2</b>
2.1	Implemented . . . . .	2
2.2	Not implemented . . . . .	2
<b>3</b>	<b>Adopted Technologies</b>	<b>3</b>
3.1	Frameworks and programming languages . . . . .	3
3.1.1	Back-end . . . . .	3
3.1.2	Front-end . . . . .	3
3.2	Additional software . . . . .	3
<b>4</b>	<b>Source Code Structure</b>	<b>4</b>
<b>5</b>	<b>Testing</b>	<b>5</b>
<b>6</b>	<b>Installation Instructions</b>	<b>5</b>
6.1	Installing the toolchain . . . . .	5
6.2	Setting up the database . . . . .	6
6.2.1	Alternative without Docker . . . . .	6
6.3	Verify the installation . . . . .	6

## 1 Introduction

### 1.1 Scope

This document describes the implementation and testing process of a working prototype of the service described in the "Requirement Analysis and Specification Document" and "Design Document". This document is intended to be a reference for the developer team and explains the choices regarding used software, frameworks, programming languages. It also provide input on how to perform integration testing between the implemented components.

### 1.2 List of definitions and abbreviations

### 1.3 Abbreviations

- **RASD** - Requirement Analysis and Specification Document
- **DD** - Design Document
- **JS** - JavaScript
- **R $n$**  - Requirement  $n$
- **IT $n$**  - Integration Test  $n$

### 1.4 Definitions

- **Client** - In this document client means a web app.

## 1.5 Reference documents

- Requirement Analysis and Specification Document (rasd.pdf)
- Design Document (dd.pdf)

## 1.6 Document structure

- Chapter 1 presents the requirements that have been implemented in the prototype.
- Chapter 2 presents the adopted programming languages and frameworks, justifying each choice.
- Chapter 3 covers the structure of the source code.
- Chapter 4 explains the testing process in greater detail.
- Chapter 5 provides explanations on how to run, test and build the prototype.

# 2 Implemented Requirements

Requirements have the same nomenclature present in the RASD and DD.

We anticipate that the prototype implementation of the *Totem* is an exemplification of what described in the RASD and DD, but of course lacks the extra hardware, such a scanner. The main features are present, for example validating a ticket or joining the queue.

## 2.1 Implemented

- R1 - Allow a User to sign up for an Account after providing a mobile phone number.
- R2 - Allow a Registered User to find Stores nearby ~~a specified the user or an hardcoded~~ location. **Note:** *This is because the Google Maps API that converts addresses to coordinates is paid.*
- R4 - Allow a Registered User to get in the virtual line at a specified store.
- R6 - Allow a Registered User to preview an estimate of the queue time.
- R8 - Allow a Registered User to cancel their reservation.
- R9 - Allow a Registered User to leave the virtual queue.
- R10 - Allow a Registered User and a Totem User to retrieve a scannable QR Code/Barcode that they must present in order to be granted access to a store.
- R12 - The System cancels User reservations in case of a major delay.
- R14 - The System grants a User with a reservation access only within a short time (set by the manager) after the User's time of reservation.

## 2.2 Not implemented

- R3 - Allow a Registered User to filter out stores based on available timeframes, days and distance. **Explanation:** *while the implementation isn't difficult, implementing this feature would have slowed down the development and testing process.*
- R5 - Allow a Totem User to get in the virtual line of the store where the totem is installed. **Explanation:** *implementing the totem interface it's not really useful for a prototype, since this functionality works identically to a customer's client one.*
- R11 - The System notifies the Users affected by delay. **Explanation:** *it requires external paid service that isn't needed for a prototype, especially a web based one. Had we implemented a native mobile app, this feature would have been implemented.*
- R13 - The System enforces the limits on the allowed number of concurrent Customers inside a store by restricting the access at the entry points (for example, automatic doors or turnstile). **Explanation:** *The Store*

*API component is not implemented in the prototype as it requires custom integrations with existing API or hardware.*

- R15 - Allow System Managers to set the division of the maximum number of people allowed between the normal queue, the priority queue for people with special needs and the book a visit slot capacity.
- R16 - The System calculates the average shopping time by recording every time a user enters and exits the store.
- R17 - Allow System Managers to set a limit to the people allowed into the store at a time.
- R18 - Allow System Managers to choose the frequency and size of the time slots.
- R19 - Allow System Managers to know the average time spent in the store. **Explanation:** Same reason of R13, it would require access to an existing store API/hardware.
- R20 - Allow System Managers to know the current and past number of people in the store.
- R21 - Allow System Managers to check the current status of the queue and of the time slots.

### 3 Adopted Technologies

The chosen frameworks and technologies have been chosen with regards the Component View (Section 2.2) of the Design Document. Components not critical for a prototype such as a reverse proxy, a CDN, or firewalls have been disregarded in this implementation.

#### 3.1 Frameworks and programming languages

##### 3.1.1 Back-end

We decided to implement the *Application Server* with JavaScript and NodeJS, because it offers great horizontal scalability and generally good performance in handling multiple simultaneous requests. In order to ease development, we chose the industry standard server framework ExpressJS, which allows us to easily implement a REST API for the clients.

The chosen DBMS is MySQL, because it's a time-tested, fast and secure platform.

##### 3.1.2 Front-end

In order to develop a working prototype in a short timeframe, we decided to implement only the web application client, which offers the same functionalities of a native application, exception made for push notifications. The web app can be also easily ported into a Progressive Web App (PWA), which allows users to use it offline.

Of course, being the client a web application, the obvious choice regarding suitable programming languages is JavaScript, allowing us to have a codebase written in the same language.

We decided to use an industry-standard framework such as React to better organize the structure of the web app, while maintaining high extendability, modularity and tidiness of the code. In order to make requests against the REST API, we used the new standard `fetch` API.

#### 3.2 Additional software

In this part other notable tools are briefly explained.

**Yarn** In order to better organize the project dependencies, it's a wise choice to use a packet manager. By having a codebase written entirely in JS, we adopted Yarn, a fast and reliable packet manager for JavaScript. It also handles custom scripts to ease the development workflow.

**Jest** To perform unit and integration testing, we've chosen Jest, an industry-standard JavaScript testing framework.

**Docker** To easily deploy a configured database for development, we utilized a MySQL image with Docker, an industry-standard container solution.

## 4 Source Code Structure

The whole project is contained in a single repository. In the root directory (while referring to the repository of this project, such directory is /ITD/). In the root folder are present many config files, notable entries are:

- `package.json` specifies the project dependencies and contains scripts to ease development.
- `docker-compose.yml` specifies the deploy configuration of this prototype and allow to setup easily the needed services.
- `.env` contains some system parameters. Albeit it should not be committed in a Git repository, we believe it's an acceptable exception for a prototype.

The relevant folders are the following:

- `database` contains configurations and dump for the MySQL database.
- `src` contains the source code of the prototype.
  - `client` contains the client source code.
    - \* `components` contains React modules that implement one single function.
      - `App.js` is the root of the web application.
      - `Button.js` represent a simple button component.
      - `ErrorMsg.js` is a panel to display errors.
      - `Field.js` is a form field with options to limit input.
      - `PrivateRoute.js` is a custom routing component needed to route an unauthorized user to the login page.
      - `StoreMap.js` display a maps to display stores through the Google Maps API and draws markers on it.
      - `TicketCache.js` reroutes users that have a ticket to the ticket view.
    - \* `css` contains `styles.css`, a CSS file to tweak minor aspects of the web app. The overall style is handled through a library loaded from the dependencies.
    - \* `images` contains various icons for the web app.
    - \* `views` contains the various views that the web app can show. Views handles the fetching of data from servers and display it.
      - `LoginView.js` handles the login process (corresponds to RASD Fig. 5A, 5B).
      - `SettingsView.js` handles the logout of a user. Various, not-implemented settings would be configurable from here.
      - `StoreDetailView.js` shows the details of a single store, and allow a user to join the queue or go the timeslot view (corresponds to RASD Fig. 5E).
      - `StoreListView.js` shows the stores in the vicinity of a user (corresponds to RASD Fig. 5C)
      - `TicketListView.js` shows active tickets of a user (corresponds to RASD Fig. 5G, 5H)

- `TimeslotsView.js` shows the available timeslots to a user, allowing them to make a reservation (corresponds to RASD Fig. 5A, 5F).
  - `WelcomeView.js` is the first view an new user sees.
- \* `defaults.js` contains constants used in the web app.
- \* `index.html` is the root of the web app. Mandatory since it's a website.
- \* `index.js` is the entry point of the web app logic. It is loaded by `index.html` and loads `components/App.js`
- `server` contains the server source code.
  - \* `components` contains the various service components needed by the server. They correspond to the homonymous components presented in the DD. In particular `QueryManager` handles the connection to the DBMS service. Certain methods of these components have been slightly changed to simplify the implementation (for example, the id of a reservation is generated by the database instead of being send to it). The overall functionality of a component is kept unchanged.
    - `AccountManager`
    - `QueryManager`
    - `QueueManager`
    - `ReservationManager`
    - `SmsApi` (stub, instead of sending an SMS prints it to `stdout`)
    - `StoreSearch`
    - `TicketManager`
  - \* `errors` contains definitions of various errors that the server can throw.
  - \* `main.js` the entry point of the server. Contains the REST API endpoints. The REST API is developed according to the DD.
  - \* `utils.js` contains utility functions.
- `totem` contains an example of the totem interface and software.

## 5 Testing

TODO

(Refer to DD + procedure, explain at least system tests, would be good to consider integration tests)

## 6 Installation Instructions

Here we report the instructions to install all software dependencies needed to run the service. This instructions are also available in the GitHub repository in the ITD folder.

### 6.1 Installing the toolchain

- Install NodeJS, possibly the LTS version (14.15.4).
  - If you use tools such `nvm`, please run `nvm install --lts` and `nvm use --lts`
- Open the terminal and run `npm install -g yarn` to install the packet manager we're using, Yarn

- If you are developing this project, installing Nodemon is recommended `npm install -g nodemon`. Please note that it's already included in the *developer dependencies*, so if you do not wish to install it globally, skip this step.
- Clone the repository using either one of the following commands
  - `git clone https://github.com/ian-ofgod/DiDioLavoreFuscoFranchini-CLup`
  - `gh repo clone ian-ofgod/DiDioLavoreFuscoFranchini-CLup`
- Change directory into the ITD folder `cd DiDioLavoreFuscoFranchini-CLup/ITD`
- Run `yarn install` to install the dependencies

## 6.2 Setting up the database

You'll have to install Docker on your device, and make sure docker-compose is installed as well.

- Run `docker-compose up -d` to spin up the images specified in the `docker-compose.yml` file.

Visit <http://localhost:8081> to see if Adminer is running, and log in with the credentials specified in the `.env` file (server: db, username: clup\_admin, password: clup, database: db\_clup).

### 6.2.1 Alternative without Docker

- Install MySQL server, then create a schema and a user with the credentials found in the `.env` file, otherwise create your own and edit the `.env` file.
- In case of errors about permissions, try running the following command, especially if you are not using Docker:

```
create user clup_admin@localhost identified with mysql_native_password by 'clup';
grant all privileges on * . * to clup_admin@localhost;
```

## 6.3 Verify the installation

- Run `yarn server-dev` to run the developer server
- Run `yarn client-dev` to run the client server
- Run `yarn client-build` to compile the client package (output is in dist)
- Run `yarn test` to run the full test suite with Jest