



Beyond MLE and GLRT

SIGNAL MODELS


- MLE and GLRT both require reliable [signal models](#)
- Many anticipated GW sources do not have reliable signal models, for example:
 - Core-collapse supernova signals for ground-based detectors: turbulent dynamics → fundamentally unpredictable waveforms
 - Extreme mass ratio inspiral signals for LISA: two-body problem in GR but very challenging to compute accurately
- It is possible to extend MLE and GLRT to the case of where signal models are not known: Requires [regularization techniques](#)
- Various types of [time-frequency analysis](#) methods may also be used
- MLE and GLRT also require reliable [noise models](#)
- Data analysis techniques (e.g., [vetoes](#)) are needed to bring the performance of MLE and GLRT closer to the ideal one

TIME-FREQUENCY ANALYSIS

TIME FREQUENCY ANALYSIS OF NOISY DATA




EXCESS POWER




TF clustering

Assume that a signal occupies a simply connected region of the time-frequency plane



Apply a threshold: set pixels below threshold to 0 and above to 1



Cluster
Find groups of pixels that are
“connected” to each other





Retain only clusters above a
certain threshold size

Further threshold on average
value of pixels in the cluster

TF methods in GW data analysis

- Time-frequency methods plays an important role in searches for **unmodeled** gravitational wave signals
 - GW150914 discovered with Coherent WaveBurst (CWb): TF analysis with **Wavelets** (Klimenko, Yakushin, Rakhmanov, Mitselmakher, CQG, 2004) combined with **regularized network analysis** (Klimenko, Mohanty, Rakhmanov, Mitselmakher, PRD, 2005)
 - *Klimenko et al, PRD, 2016*
- Q-transform (used in Omicron)
 - *Brown, JASA, 1991; Chatterji, Blackburn, Martin, Katsavounidis, CQG, 2004*

TF clustering and CCSN signals



Core bounce

- Single Cluster
- Signal power well-localized \Rightarrow cluster easily detectable

Post-Shock

- Fragmented Cluster
- Individual clusters can be too weak or too small
- Aggregation of multiple clusters \Rightarrow additional ad hoc algorithm parameters

Note: Multi-resolution TF analysis is a must (not shown here)

Analyzing real data

- The concepts we have learnt so far are adequate to do a preliminary analysis of real GW data
- Matlab live scripts provided in DATASCIENCE_COURSE / GWDATA

Homework

Readings

- ▶ GWTC-3: Compact Binary Coalescences Observed by LIGO and Virgo During the Second Part of the Third Observing Run, [arXiv:2111.03606](#)
- ▶ Papers related to GW150914 and GW170817

Windowing

- Application of convolution theorem in the reverse direction
- Example: Windowed sinusoid

$$s(t) = \begin{cases} \cos(2\pi f_0 t); & t \in [-T/2, T/2] \\ 0; & \text{otherwise} \end{cases}$$

- **Windowing:** Box-car window

$$s(t) = \Pi(t/T) \cos(2\pi f_0 t)$$

$$\Pi(t) = \begin{cases} 1, & t \in [-1, 1] \\ 0, & \text{otherwise} \end{cases}$$

- Fourier transform of Box car window:

$$\tilde{\Pi}(f) = T \text{sinc}(fT) = T \sin(\pi fT) / (\pi fT)$$

- Fourier transform of sinusoid (Lecture 3):

$$\frac{1}{2} (\delta(f - f_0) + \delta(f + f_0))$$

- Convolution theorem:

$$\begin{aligned} \tilde{s}(f) &= \int_{-\infty}^{\infty} df' T \text{sinc}((f - f')T) \left[\frac{1}{2} (\delta(f' - f_0) + \delta(f' + f_0)) \right] \\ &= \frac{T}{2} [\text{sinc}((f - f_0)T) + \text{sinc}((f + f_0)T)] \end{aligned}$$

- Using a different window (e.g., Hann) results in a different trade-off between the main lobe width and side lobe height

