

# Object Oriented Development with Java

(CT038-3-2 and Version VC1)



**A . P . U**  
ASIA PACIFIC UNIVERSITY  
OF TECHNOLOGY & INNOVATION

## Graphical User Interface (GUI)

GUI-based Development

# Topic & Structure of the lesson

- AWT <sub>vs</sub> Swing
- Swing components
- Creating a window
- Adding components
- Handling action events

# Learning outcomes

- At the end of this lecture you should be able to:
  - Differentiate between AWT and Swing
  - Create a Window
  - Understand GUI Classes in a main method
  - Radio Buttons and Check Boxes
  - Focus on Problem Solving: Extending Classes from Jpanel

# Key terms you must be able to use

If you have mastered this topic, you should be able to use the following terms correctly in your assessments:


- AWT
- Swing

# Introduction

- A GUI is a graphical window or windows that provide interaction with the user
- GUIs accept input from:
  - the keyboard
  - a mouse
- A window in a GUI consists of components that:
  - present data to the user
  - allow interaction with the application


# Introduction

- Some common GUI components are:
  - buttons, labels, text fields, check boxes, radio buttons, combo boxes, and sliders.



# Introduction

- Java is equipped with a set of classes for drawing graphics and creating graphical user interfaces
- These classes are part of the *Abstract Window Toolkit (AWT)*



# Abstract Window Toolkit (AWT)

- The AWT allows creation of applications and applets with GUI components
- Java programs using the AWT:
  - look consistent with other applications on the same system
  - can offer only components that are common to all the operating systems that support Java



# Swing

- *Swing* is a library of classes that provide an improved alternative for creating GUI applications and applets
- Part of Oracle's Java Foundation Classes (JCF)
- Developed to provide a more sophisticated set of GUI components than AWT
- Swing components have a consistent look and predictable behavior on any operating system
- Swing components can be easily extended

# Event Driven programming

- Programs that operate in a GUI environment must be *event-driven*
- An *event* is an action that takes place within a program, such as the clicking of a button
- Part of writing a GUI application is creating event listeners
- An *event listener* is an object that automatically executes one of its methods when a specific event occurs

# javax.swing and java.awt

- In an application that uses Swing classes, it is necessary to use the following statement:

```
import javax.swing.*;
```


- In an application that uses an AWT class, it is necessary to use the following statement.

```
import java.awt.*;
```



# Swing Components


- Two classes: *Container* and *Component*
- Container holds components and/or containers



# Creating a window in Swing

- A window is a *container*, which is simply a component that holds other components
- A container that can be displayed as a window is a *frame*
- In a Swing application, you create a frame from the `JFrame` class (top-level container)

`javax.swing.JFrame`



# Creating a window

```
import javax.swing.*;    // Needed for Swing classes
```

```
public class ShowWindow  
{
```


```
    public static void main(String[] args)  
    {
```

```
        // Window width and height in pixels  
        final int WINDOW_WIDTH = 350;  
        final int WINDOW_HEIGHT = 250;
```

```
        JFrame window = new JFrame(); // Create a window  
        window.setTitle("A Simple Window"); // Set the title  
        window.setSize(WINDOW_WIDTH, WINDOW_HEIGHT); // Set the size of  
                                                    //the window
```

```
        // Specify what happens when the close button is clicked  
        window.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
```

```
        window.setVisible(true); // Display the window
```



# Creating a window

## Extending JFrame

```
import javax.swing.*;    // Needed for Swing classes
```

```
public class SimpleWindow extends JFrame {
```

```
    /* Constructor */
```

```
    public SimpleWindow() {
```

```
        final int WINDOW_WIDTH = 350;    // Window width in pixels
```

```
        final int WINDOW_HEIGHT = 250;   // Window height in pixels
```

```
        setTitle("A Simple Window"); // Set this window's title
```

```
        setSize(WINDOW_WIDTH, WINDOW_HEIGHT); // Set the size of  
                                                //this window
```

```
        // Specify what happens when the close button is clicked.
```

```
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
```

```
        setVisible(true); // Display the window
```

```
    }
```

```
}
```

*Note: You will need to  
create a main program to  
run this code*





# Adding Components

- Swing provides numerous components that can be added to a window.

- Swing components begin with a J

- Three fundamental components are:


`JLabel:` An area that can display text

`JTextField:` An area in which the user may type a single line of input from the keyboard

`JButton:` A button that can cause an action to occur when it is clicked



# Adding Components



# Adding Components

```
private JLabel message;  
private JTextField kilometers;  
private JButton calcButton;  
  
...  
message = new JLabel("Enter a distance in kilometers");  
kilometers = new JTextField(10);  
calcButton = new JButton("Calculate");
```

# Adding Components

- A content pane is a container that is part of every `JFrame` object
- A *panel* is also a container that can hold GUI components
  - Panels cannot be displayed by themselves
  - Panels are commonly used to hold and organize collections of related components
  - Create panels with the `JPanel` class

# Adding Components

```
private JPanel panel;  
...  
panel = new JPanel();  
panel.add(message);  
panel.add(kilometers);  
panel.add(calcButton);
```

- Components are typically placed on a panel and then the panel is added to the JFrame's content pane

```
add(panel);
```

# Handling action events

- An *event* is an action that takes place within a program, such as the clicking of a button
- When an event takes place, the component that is responsible for the event creates an *event object* in memory
- The event object contains information about the event
- The component that generated the event object is known as the *event source*

# Handling action events

- An *event listener* is an object that responds to events
- All event listener classes must *implement an interface*



# Handling action events

- JButton components generate *action events*, which require an *action listener* class
- Action listener classes must meet the following requirements:
  - It must implement the ActionListener interface
  - It must have a method named actionPerformed
- The actionPerformed method takes an argument of the(ActionEvent) type

```
public void actionPerformed(ActionEvent e)
```

```
{
```

*Code to be executed when button is pressed goes here*

# Registering a listener

- The process of connecting an event listener object to a component is called *registering* the event listener
- JButton components have a method named `addActionListener`

```
calcButton.addActionListener(  
    new CalcButtonListener() );
```



# The `ActionEvent` object

- Event objects contain certain information about the event
- This information can be obtained by calling one of the event object's methods
- Two of these methods are:
  - `getSource` - returns a reference to the object that generated this event
  - `getActionCommand` - returns the action command for this event as a `String`


# Radio button

- **JRadioButton constructors:**
  - `JRadioButton(String text)`
  - `JRadioButton(String text, boolean selected)`
- **Example:**

```
JRadioButton radio1 = new JRadioButton("Choice 1");  
or  
JRadioButton radio1 = new JRadioButton(  
    "Choice 1", true);
```

# Button group

- Radio buttons normally are grouped together
- In a radio button group only one of the radio buttons in the group may be selected at any time
- The `ButtonGroup` class provides a *mutually exclusive* relationship between the radio buttons that



# Button group

```
JRadioButton radio1 = new JRadioButton("Choice 1",  
                                         true);  
  
JRadioButton radio2 = new JRadioButton("Choice 2");  
JRadioButton radio3 = new JRadioButton("Choice 3");  
ButtonGroup group = new ButtonGroup();  
group.add(radio1);  
group.add(radio2);  
group.add(radio3);
```

# Button group

- `ButtonGroup` objects are not containers like `JPanel` objects, or content frames
- If you wish to add the radio buttons to a panel or a content frame, you must add them individually

```
panel.add( radio1 );  
panel.add( radio2 );  
panel.add( radio3 );
```



# Check boxes

- Two JCheckBox constructors:

```
JCheckBox(String text)
```

```
JCheckBox(String text, boolean selected)
```


Check appears in  
box if true

- Example:

```
JCheckBox check1 = new JCheckBox("Macaroni");
```

or

```
JCheckBox check1 = new JCheckBox("Macaroni", true);
```






# Check boxes

- When a `JCheckBox` object is selected or deselected, it generates an *item event*
- Handling item events is similar to handling action events
- When writin an *item listener* class, the following requirements must be met:
  - It must implement the `ItemListener` interface
  - It must have a method named `itemStateChanged`
  - This method must take an argument of the

- Many more components available to be used ...






# Quick Review Questions


- What is GUI based programming?
- What is the difference between Swing and AWT?
- What is event handling?
- What is event listener?
- How to handle the event?

# Summary of Main Teaching Points

- AWT vs Swing
- Swing components
- Creating a window
- Adding components
- Handling action events



# Q & A



# Next Session

- File Class
- I/O Stream

