

文延欢第六章作业

通过广播接收器实现两个 app 之间通过自定义广播进行数据通信核心代码：
在 activity_main.xml 加入发送广播按钮 button：

```
<Button
    android:id="@+id/btn_send"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:layout_marginEnd="140dp"
    android:layout_marginRight="140dp"
    android:text="发发发广播"
    android:textAllCaps="false"
    app:layout_constraintBottom_toBottomOf="parent"
    app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintTop_toTopOf="parent"
    app:layout_constraintVertical_bias="0.499" />
```

新建 MyBroadcastReceiver.java，加入 Toast 弹出消息：

```
public class MyBroadcastReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        //处理收到广播的逻辑：
        Toast.makeText(context.getApplicationContext(), " 广 播 来 了",
            Toast.LENGTH_LONG).show();
    }
}
```

在 Androidmanifest.xml 中注册 MyBroadcastReceiver 加入以下代码：

```
<receiver android:name="com.example.taskactivity.MyBroadcastReceiver">
    <intent-filter >
        <action
            android:name="com.example.taskactivity.MyBroadcastReceiver"/>
        </intent-filter>
    </receiver>
```

在 MainActivity.java 文件中加入按钮相关逻辑：

```
@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
    mSendButton = (Button) findViewById(R.id.btn_send);
    mSendButton.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            Intent intent = new
            Intent("com.example.activitylifecycletest.SecondBroadcaseReceiver");
```

```

        intent.setComponent(new
ComponentName("com.example.taskactivity",
"com.example.taskactivity.MyBroadcastReceiver"));
        //括号中分别指定包名与类名
        sendBroadcast(intent);
//
        Toast.makeText(getApplicationContext(), "dfsaf",
Toast.LENGTH_LONG).show();
    }
});
}

```

以上是在同一应用实现广播通信，现在新建 SecondbroadcastReceiver.java，并在 AndroidManifest.xml 注册。

SecondbroadcastReceiver.java 代码如下：

```

public class SecondBroadcastReceiver extends BroadcastReceiver {
    @Override
    public void onReceive(Context context, Intent intent) {
        //处理手动广播的逻辑
        Intent intent1 = new Intent();
intent1.getBooleanArrayExtra("com.example.activitylifecyletest.SecondBroadcastR
eceiver");
        Toast.makeText(context(getApplicationContext(), "收到上个的广播",
Toast.LENGTH_SHORT).show();
    }
}

```

AndroidManifest.xml 中加入：

```

<receiver
android:name="com.example.activitylifecyletest.SecondBroadcastReceiver">
    <intent-filter >
        <action
android:name="com.example.activitylifecyletest.SecondBroadcastReceiver"/>
    </intent-filter>
</receiver>

```

更改第一个应用中 MainActivity.java 中为：

```

@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);

    mSendButton = (Button) findViewById(R.id.btn_send);
    mSendButton.setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            Intent intent = new
Intent("com.example.activitylifecyletest.SecondBroadcastReceiver");

```

```

        intent.setComponent(new
ComponentName("com.example.activitylifecyletest",
"com.example.activitylifecyletest.SecondBroadcaseReceiver"));
        //更改包名和类名为第二个应用中注册的广播，指定广播接收
方
        sendBroadcast(intent);
//
        Toast.makeText(getApplicationContext(), "dfsaf",
Toast.LENGTH_LONG).show();
    }
    });
}

```

以下是两次的效果图

