

第六章

6.3 通过广播接收器实现两个 App 之间通过自定义广播进行数据通信。
这里有两个 app，一个是发送广播 app(senderAPP)，另一个是接收广播 app(receiverAPP)

senderAPP

MainActivity.java

```
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
    //发送标准广播
    findViewById(R.id.button).setOnClickListener(new View.OnClickListener() {
        @Override
        public void onClick(View v) {
            Intent intent=new Intent();
            intent.setAction("MyBroadcastReceiver.Custom");
            intent.putExtra("info","这是一条广播!!!");
            intent.addFlags(Intent.FLAG_ACTIVITY_PREVIOUS_IS_TOP);
            sendBroadcast(intent);
        }
    });
}
```

MyReceiver.java

```
private static final String TAG = "MyBroadcastReceiver";
@Override
public void onReceive(Context context, Intent intent) {
    Log.d(TAG, "-----Receivers1-----");
    Log.d(TAG, "Action: " + intent.getAction());
    Log.d(TAG, "URI: " + intent.toUri(Intent.URI_INTENT_SCHEME));
    Log.d(TAG, intent.getStringExtra("info"));
}
}
```

activity_main.xml

```
<Button
    android:id="@+id/button"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:layout_marginTop="292dp"
    android:text="发送广播"
    android:textSize="28sp"
    app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintHorizontal_bias="0.0"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintTop_toTopOf="parent" />
```

ReceiverAPP

MainActivity.java

```
public class MainActivity extends AppCompatActivity {
    private MyReceiver2 myReceiver = new MyReceiver2();
    private boolean mRegistered = false;
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main); //注册广播接收器
        IntentFilter intentFilter = new IntentFilter();
        intentFilter.addAction(ConnectivityManager.CONNECTIVITY_ACTION);
        intentFilter.addAction(Intent.ACTION_SCREEN_ON);
        intentFilter.addAction(Intent.ACTION_SCREEN_OFF);
        intentFilter.addAction(Intent.ACTION_USER_PRESENT);
        intentFilter.addAction(Intent.ACTION_BATTERY_OKAY);
        intentFilter.addAction(Intent.ACTION_BATTERY_LOW);
        intentFilter.addAction(Intent.ACTION_BATTERY_CHANGED);

        //
        intentFilter.addAction("com.vt.c0701.MyBroadcastReceiver.ss");
        registerReceiver(myReceiver, intentFilter);
        mRegistered = true;
    }
    @Override
    protected void onDestroy() {
        super.onDestroy();
        if(mRegistered) {
            unregisterReceiver(myReceiver);
        }
    }
}
```

MyReceiver2.java

```
public void onReceive(Context context, Intent intent) {
    // TODO: This method is called when the BroadcastReceiver is receiving
    // an Intent broadcast.
    Log.d(TAG, "-----Receiver-----");
    Log.d(TAG, "Action: " + intent.getAction());
    Log.d(TAG, "URI: " + intent.toUri(Intent.URI_INTENT_SCHEME));
    // 自定义广播
    if ("MyBroadcastReceiver.Custom".equals(intent.getAction())) {
        Log.d(TAG, intent.getStringExtra("info"));
    }
}
```

SenderApp

发送广播

发送广播

点击发送广播后，接收 app 显示：

```
D/MyBroadcastReceiver: -----Receiver-----  
D/MyBroadcastReceiver: Action: MyBroadcastReceiver.Custom  
D/MyBroadcastReceiver: URI: intent:#Intent;action=MyBroadcastReceiver  
.Custom;launchFlags=0x1000010;component=com.example.resiverapp/  
.MyReceiver2;S.info=%E8%BF%99%E6%98%AF%E4%B8%80%E6%9D%A1%E5%B9%BF%E6%92  
%AD%EF%BC%81%EF%BC%81%EF%BC%81;end  
D/MyBroadcastReceiver: 这是一条广播!!!
```