

第四章

4.3 实现京东首页的轮播广告效果，至少包括 3 个产品广告的图片。

MainActivity.java 部分代码：

```
//单击监听事件
@Override
public void onClick(View v) {
    int id = v.getId();
    if (id == R.id.image_button_left) {
        if (mCurrentPosition > 0) {
            mCurrentPosition--;
        }
        mViewPager.setCurrentItem(mCurrentPosition, true);
    } else if (id == R.id.image_button_right) {
        if (mCurrentPosition < 3) {
            mCurrentPosition++;
        }
        mViewPager.setCurrentItem(mCurrentPosition, true);
    } else if (id == R.id.image_view_page0) {
        mCurrentPosition = 0;
        mViewPager.setCurrentItem(mCurrentPosition, true);
    } else if (id == R.id.image_view_page1) {
        mCurrentPosition = 1;
        mViewPager.setCurrentItem(mCurrentPosition, true);
    } else if (id == R.id.image_view_page2) {
        mCurrentPosition = 2;
        mViewPager.setCurrentItem(mCurrentPosition, true);
    } else if (id == R.id.image_view_page3) {
        mCurrentPosition = 3;
        mViewPager.setCurrentItem(mCurrentPosition, true);
    }
}

//页面改变监听器
public class PageChangeListener implements ViewPager.OnPageChangeListener
{
    //页面选择事件
    public void onPageSelected(int position) {
        //翻页时当前 page，改变当前状态圆点图片。
        mCurrentPosition = position;
        switch (position) {
            case 0:
                mPage0.setImageResource(R.mipmap.img_page_now);
            case 1:
                mPage1.setImageResource(R.mipmap.img_page_now);
            case 2:
                mPage2.setImageResource(R.mipmap.img_page_now);
            case 3:
                mPage3.setImageResource(R.mipmap.img_page_now);
        }
    }
}
```

```

        mPage1.setImageResource(R.mipmap.img_page);
        mPage2.setImageResource(R.mipmap.img_page);
        mPage3.setImageResource(R.mipmap.img_page);
        break;
    case 1:
        mPage1.setImageResource(R.mipmap.img_page_now);
        mPage0.setImageResource(R.mipmap.img_page);
        mPage2.setImageResource(R.mipmap.img_page);
        mPage3.setImageResource(R.mipmap.img_page);
        break;
    case 2:
        mPage2.setImageResource(R.mipmap.img_page_now);
        mPage0.setImageResource(R.mipmap.img_page);
        mPage1.setImageResource(R.mipmap.img_page);
        mPage3.setImageResource(R.mipmap.img_page);
        break;
    case 3:
        mPage3.setImageResource(R.mipmap.img_page_now);
        mPage0.setImageResource(R.mipmap.img_page);
        mPage1.setImageResource(R.mipmap.img_page);
        mPage2.setImageResource(R.mipmap.img_page);
        break;
    }
}
//页面滚动事件
@SuppressWarnings("SetTextI18n")
public void onPageScrolled(int position, float positionOffset, int
positionOffsetPixels) {
}
//页面滚动状态改变事件
public void onPageScrollStateChanged(int state) {
    switch (state) {
        case ViewPager.SCROLL_STATE_IDLE:
            mPageStateTextView.setText("空闲状态");
            break;
        case ViewPager.SCROLL_STATE_DRAGGING:
            mPageStateTextView.setText("拖动状态");
            break;
        case ViewPager.SCROLL_STATE_SETTLING:
            mPageStateTextView.setText("结束状态");
            break;
    }
}
}

```

```

WelcomePagerAdapter.java
WelcomePagerAdapter(ArrayList<View> pagerViews) {
    mPagerViews = pagerViews;
}
//获取分页视图的数量
@Override
public int getCount() {
    return mPagerViews.size();
}
//判断是否由对象生成界面。
@Override
public boolean isViewFromObject(View view, Object object) {
    return view == object;
}
//显示分页视图或缓存分页时进行布局的初始化。
@Override
public Object instantiateItem(ViewGroup container, int position) {
    container.addView(mPagerViews.get(position));
    return mPagerViews.get(position);
}
//销毁分页视图时移除相应的分页。
@Override
public void destroyItem(ViewGroup container, int position, Object object) {
    container.removeView(mPagerViews.get(position));
}

```

效果展示：



