

第七章:

p213 7.2 使用 SQLite 实现记录登录时间的功能，并且能够查询登录的历史记录。

```
public class HistoryActivity extends AppCompatActivity
implements View.OnClickListener {
    private Button cancel;
    public EditText mIdEditText;
    public EditText mNameEditText;
    public EditText mPhoneEditText;
    private Context mContext;
    private SQLiteDatabase mSQLiteDatabase;
    private ContactSQLiteOpenHelper
mContactSQLiteOpenHelper;
    private String mDataBaseName = "contacts.db";
    private String mTableName = "contacts";
    private List<ContactModel> mContactModel;
    private ContactListAdapter mContactListAdapter;
    private ListView mContactListView;
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        setContentView(R.layout.activity_history);
        super.onCreate(savedInstanceState);

        this.setTitle("登录历史");

        mContext = this;
        mContactModel = new ArrayList<>();
        mContactListView =
findViewById(R.id.list_view_contacts);
        //findViewById(R.id.btn_list).setOnClickListener(this);
        init();
        cancel = (Button) findViewById(R.id.btn_cancel);
        findViewById(R.id.btn_cancel).setOnClickListener(new
View.OnClickListener() {
            public void onClick(View view) {
                finish();
            }
        });
    }

    // 初始化

    private void init(){
        mContactSQLiteOpenHelper = new
ContactSQLiteOpenHelper(mContext, mDataBaseName, null,
```

```

1);
    mSQLiteDatabase =
mContactSQLiteOpenHelper.getWritableDatabase();
    mContactListAdapter = new ContactListAdapter(this,
mContactModel);
    mContactListView.setAdapter(mContactListAdapter);
    listAllContacts();
}

// 显示所有联系人

private void listAllContacts() {
    mContactModel.clear();
    Cursor cursor = mSQLiteDatabase.rawQuery("SELECT *
FROM " + mTableName + " order by id asc", null);
    while (cursor.moveToNext()) { String id =
cursor.getString(cursor.getColumnIndex("id"));
        String name =
cursor.getString(cursor.getColumnIndex("name"));
        String phone =
cursor.getString(cursor.getColumnIndex("phone"));
        mContactModel.add(new ContactModel(id, name, phone));
    }
    cursor.close();

    // 更新 ListView

    mContactListAdapter.notifyDataSetChanged();
}
@Override
public void onClick(View v) {
    String id = mIdEditText.getText().toString();
    String name = mNameEditText.getText().toString();
    String phone = mPhoneEditText.getText().toString();
    switch (v.getId()) {
    }
}
}

```

```

public class ContactListAdapter extends BaseAdapter {
    private HistoryActivity mContext;
    private List<ContactModel> mContactModel;
    private ViewHolder mViewHolder;

```

//构造方法

```

    public ContactListAdapter(HistoryActivity mContext,
List<ContactModel> mContactModel) {
        this.mContext = mContext;
        this.mContactModel = mContactModel;}
    @Override
    public int getCount() {
        return mContactModel.size(); }
    @Override
    public Object getItem(int position) {
        return mContactModel;}
    @Override
    public long getItemId(int position) {
        return position;}

    //获取列表项视图

    @Override
    public View getView(int position, View convertView,
ViewGroup parent) {

        if (convertView == null) {//convertView 未实例化时

            convertView =
LayoutInflater.from(mContext).inflate(R.layout.list_view_
item_contact, parent, false);
            mViewHolder = new ViewHolder();
            mViewHolder.idTextView =
convertView.findViewById(R.id.text_view_id);
            mViewHolder.nameTextView =
convertView.findViewById(R.id.text_view_name);
            mViewHolder.phoneTextView =
convertView.findViewById(R.id.text_view_phone);

            convertView.setTag(mViewHolder);//holder 缓存到
convertView

        } else {//convertView 实例化时

            mViewHolder = (ViewHolder)
convertView.getTag();//从 convertView 获取 holder 缓存
            mViewHolder.idTextView.setText(mContactModel.get(position)
.id);
            mViewHolder.idTextView.setId(position);

            mViewHolder.idTextView.setOnClickListener(mTextViewOnClic
kListener);

```

```

mViewHolder.nameTextView.setText(mContactModel.get(position).name);
        mViewHolder.nameTextView.setId(position);
mViewHolder.nameTextView.setOnClickListener(mTextViewOnClickListener);
mViewHolder.phoneTextView.setText(mContactModel.get(position).phone);
        mViewHolder.phoneTextView.setId(position);
mViewHolder.phoneTextView.setOnClickListener(mTextViewOnClickListener);
        return convertView;
    }

    private View.OnClickListener
mTextViewOnClickListener = new View.OnClickListener() {
        public void onClick(View v)
        {
            (mContext.mIdEditText).setText(mContactModel.get(v.getId()).id);
            (mContext.mNameEditText).setText(mContactModel.get(v.getId()).name);
            (mContext.mPhoneEditText).setText(mContactModel.get(v.getId()).phone);
        }
    };

    class ViewHolder {
        TextView idTextView;
        TextView nameTextView;
        TextView phoneTextView;
    }

    public class ContactSQLiteOpenHelper extends
SQLiteOpenHelper {
        public ContactSQLiteOpenHelper(Context context, String
name, SQLiteDatabase.CursorFactory factory, int version){
            super(context, name, factory, version);
        }
        @Override
        public void onCreate(SQLiteDatabase db) {

            // 创建 contacts 表

            db.execSQL("CREATE TABLE contacts(id INTEGER
PRIMARY KEY AUTOINCREMENT,name VARCHAR(16),phone
VARCHAR(11))");
        }
        @Override
        public void onUpgrade(SQLiteDatabase db, int
oldVersion, int newVersion) {
            if (newVersion > oldVersion) {

```

```
// contacts 表添加 notes 列  
db.execSQL("ALTER TABLE contacts ADD notes  
VARCHAR(20)"); }}
```





