

喻婷婷第七章作业

```
public class HistoryActivity extends AppCompatActivity implements View.OnClickListener
{ private Button cancel; public EditText mIdEditText; public EditText mNameEditText; public
EditText mPhoneEditText; private Context mContext;
private SQLiteDatabase mSQLiteDatabase; private ContactSQLiteOpenHelper
mContactSQLiteOpenHelper; private String mDataBaseName = "contacts.db"; private
String mTableName = "contacts"; private List<ContactModel> mContactModel;
private ContactListAdapter mContactListAdapter; private ListView
mContactListView; @Override protected void onCreate(Bundle savedInstanceState)
{ setContentView(R.layout.activity_history);
super.onCreate(savedInstanceState); this.setTitle("登录历史"); mContext = this;
mContactModel = new ArrayList<>(); mContactListView =
findViewById(R.id.list_view_contacts);
//findViewById(R.id.btn_list).setOnClickListener(this); init(); cancel =
(Button) findViewById(R.id.btn_cancel);
findViewById(R.id.btn_cancel).setOnClickListener(new
View.OnClickListener() { public void onClick(View view) { finish(); } }); } //
初始化 private void init(){ mContactSQLiteOpenHelper = new
ContactSQLiteOpenHelper(mContext, mDataBaseName, null, 1); mSQLiteDatabase =
mContactSQLiteOpenHelper.getWritableDatabase(); mContactListAdapter = new
ContactListAdapter(this, mContactModel);
mContactListView.setAdapter(mContactListAdapter); listAllContacts(); } // 显示
所有联系人 private void listAllContacts() { mContactModel.clear(); Cursor
cursor = mSQLiteDatabase.rawQuery("SELECT * FROM " + mTableName + " order by id
asc", null); while (cursor.moveToNext()) { String id =
cursor.getString(cursor.getColumnIndex("id"));
String name = cursor.getString(cursor.getColumnIndex("name")); String phone =
cursor.getString(cursor.getColumnIndex("phone")); mContactModel.add(new
ContactModel(id, name, phone));
} cursor.close(); // 更新 ListView mContactListAdapter.notifyDataSetChanged(); }
@Override public void onClick(View v) { String id =
mIdEditText.getText().toString(); String name =
mNameEditText.getText().toString(); String phone =
mPhoneEditText.getText().toString(); switch (v.getId()) { } }
public class ContactListAdapter extends BaseAdapter { private HistoryActivity mContext;
private List<ContactModel> mContactModel; private ViewHolder mViewHolder; //构造方法
public ContactListAdapter(HistoryActivity mContext, List<ContactModel> mContactModel)
{ this.mContext = mContext; this.mContactModel = mContactModel; } @Override public int
getCount() { return mContactModel.size(); } @Override public Object getItem(int position)
{ return mContactModel.get(position); } @Override public long getItemId(int position) { return position; } //
获取列表项视图 @Override public View getView(int position, View convertView, ViewGroup
```

```

parent) { if (convertView == null) { //convertView 未实例化时 convertView =
LayoutInflater.from(mContext).inflate(R.layout.list_view_item_contact, parent, false);
mViewHolder = new ViewHolder(); mViewHolder.idTextView =
convertView.findViewById(R.id.text_view_id); mViewHolder.nameTextView =
convertView.findViewById(R.id.text_view_name); mViewHolder.phoneTextView =
convertView.findViewById(R.id.text_view_phone);
convertView.setTag(mViewHolder); //holder 缓存到 convertView } else { //convertView
实例化时 mViewHolder = (ViewHolder) convertView.getTag(); //从 convertView 获取
holder 缓存 mViewHolder.idTextView.setText(mContactModel.get(position).id);
mViewHolder.idTextView.setId(position);
mViewHolder.idTextView.setOnClickListener(mTextViewOnClickListener);
mViewHolder.nameTextView.setText(mContactModel.get(position).name);
mViewHolder.nameTextView.setId(position);
mViewHolder.nameTextView.setOnClickListener(mTextViewOnClickListener);
mViewHolder.phoneTextView.setText(mContactModel.get(position).phone);
mViewHolder.phoneTextView.setId(position);
mViewHolder.phoneTextView.setOnClickListener(mTextViewOnClickListener); return
convertView; } private View.OnClickListener mTextViewOnClickListener = new
View.OnClickListener() { public void onClick(View v)
{ (mContext.mIdEditText).setText(mContactModel.get(v.getId()).id);
(mContext.mNameEditText).setText(mContactModel.get(v.getId()).name);
(mContext.mPhoneEditText).setText(mContactModel.get(v.getId()).phone); }}; class
ViewHolder { TextView idTextView; TextView nameTextView; TextView
phoneTextView; }
public class ContactSQLiteOpenHelper extends SQLiteOpenHelper { public
ContactSQLiteOpenHelper(Context context, String name, SQLiteDatabase.CursorFactory
factory, int version){ super(context, name, factory, version); } @Override public void
onCreate(SQLiteDatabase db) { // 创建 contacts 表 db.execSQL("CREATE TABLE contacts(id
INTEGER PRIMARY KEY AUTOINCREMENT,name VARCHAR(16),phone VARCHAR(11));"}
@Override public void onUpgrade(SQLiteDatabase db, int oldVersion, int newVersion) { if
(newVersion > oldVersion) { // contacts 表添加 notes 列 db.execSQL("ALTER TABLE
contacts ADD notes VARCHAR(20); } }
<?xmlversion="1.0"encoding="utf8"?><LinearLayoutxmlns:android="http://schemas.android.co
m/apk/res/android"xmlns:app
="http://schemas.android.com/apk/res-auto"xmlns:tools="http://schemas.android.com/tools"an
droid:layout_width="match_parent"
android:layout_height="match_parent"android:background="#E3CD6D"android:orientation
="vertical"android:padding="10dp"tools:context=".MainActivity"><TextViewandroid:id="@
+id/tv_1"android:layout_width="match_parent"android:layout_height="50dp"android:layout
_marginTop="150dp"android:gravity="center"android:text="贾祎娜
"android:textColor="#B10544"android:textSize="25sp"/><EditTextandroid:id="@+id/et_1"an
droid:layout_width="match_parent"android:layout_height="50dp"android:layout_marginTo
p="10dp"android:hint="用户名
"android:maxLines="1"android:padding="5dp"android:textColor="#000000"android:textSize

```

```

="25dp"/><EditTextandroid:id="@+id/et_2"android:layout_width="match_parent"android:la
yout_height="50dp"android:layout_marginTop="5dp"android:hint="          密          码
"android:inputType="textPassword"android:maxLines="1"android:padding="5dp"
android:textColor="#000000"android:textSize="25dp"/><LinearLayoutandroid:layout_width
="match_parent"android:layout_height="wrap_content"android:orientation="horizontal"and
roid:layout_marginTop="20dp"><Buttonandroid:id="@+idn_login1"android:layout_width="
0dp"android:layout_weight="1"android:layout_height="wrap_content"android:layout_gravity
="center"android:text="登录
"android:textSize="15dp"/><Buttonandroid:id="@+id_zc"android:layout_width="0dp"andro
id:layout_weight="1"android:layout_height="wrap_content"android:text="注册
"android:layout_marginLeft="4dp"/></LinearLayout></LinearLayout>packagecom.prt.test1;
importandroidx.appcompat.app.AppCompatActivity;importandroid.content.Intent;importand
roid.os.Bundle;importandroid.view.View;importandroid.widget.Button;
importandroid.widget.EditText;importcom.prt.test1.util.ToastUtil;publicclassMainActivitye
ndsAppCompatActivity{//声明控件
privateButtonmBtnLogin;privateButtonmBtnLogin2;privateEditTextmEtUser;privateEditTextm
EtPassword;privateButtonmBtnNew;@OverrideprotectedvoidonCreate(Bundle savedInstanceState)
{super.onCreate(savedInstanceState);setContentView(R.layout.activity_main);//找到控
件
mBtnLogin=findViewById(R.id.btn_login1);mEtUser=findViewById(R.id.et_1);mEtPassword=fi
ndViewById(R.id.et_2);mBtnNew=findViewById(R.id.bt_zc);mBtnNew.setOnClickListener(new
View.OnClickListener(){@OverridepublicvoidonClick(Viewview){//显示注册界面
Intentintent=newIntent(MainActivity.this,ZhuceActivity2.class);startActivity(intent);}});mBtnLo
gin2=findViewById(R.id.btn_login2);mBtnLogin2.setOnClickListener(newView.OnClickListener
(){@OverridepublicvoidonClick(Viewview){//显示忘记密码界面
Intentintent=newIntent(MainActivity.this,ForgetActivity.class);startActivity(intent);
}});

```

