

MUSHROOM TOXICITY DETECTION

—
WITH

JINGHAN ZHANG ISABELLA LIU RUIXIN DUAN

MOTIVATION

- There are many mushroom poisoning outbreaks because people can't tell whether a mushroom is toxic.
- We were interested in exploring how far a relatively simple convolutional neural network (CNN) or/and MLP can go in performing a task related to plant species detection.
- Our motivation is to apply what we have learned in machine learning to address a meaningful real-world challenge, even with modest resources.

BACKGROUND

- A Global Health Problem:
- Worldwide, hundreds of people die each year from wild mushroom poisoning, and experts believe the actual number is higher due to underreporting.
- Human visual identification is unreliable:
- Since humans are not good at this, machines can be trained on thousands of samples and give more accurate results.

RELATED WORK



- Improved AlexNet for poisonous vs edible mushrooms (Thailand / general):
- Ketwongsa et al. (2022) propose an improved AlexNet-based CNN to classify poisonous vs edible mushrooms from images. They report high accuracy on their dataset and show that deep networks outperform traditional feature-based methods.
- Automatic mushroom species classification for wild mushrooms:
- Wang et al. (2022) present an automatic mushroom species classification model, aiming to help consumers avoid eating toxic wild mushrooms. Their model achieves strong performance on a curated species dataset and demonstrates that CNNs can handle fine-grained species differences.


TARGET TASK

- Identify toxic mushrooms from 3000 mushroom images photographed in different environments.
- Reach about 70% accuracy.
- Optimize running time and validation accuracy.



INTUITIVE
FIGURE

INTUITIVE GRAPH



Above is a figure that clearly shows the increasing trend of mushroom poisoning outbreaks in China, justifying our the meaningfulness and the need of our study.

PROPOSED
SOLUTION


ANALYSIS PLAN

- Data Analysis: Labeling & Splitting, Randomization
- CNN & MobileNetV2
- Optimization: Add features
- Testing
- Compare and Select the Best.
- Conclusion: Graphs, Tables, Accuracy rates.

DATA SUMMARY

DATA SUMMARY

- **image-mushroom-dataset**
- <https://www.kaggle.com/datasets/quanghn2001/image-mushroom-dataset>
- The dataset contained 3000+ labeled images. (Edible VS. Poisonous)
- Split: 2000+ Training (80% Training Set / 20% Validation Set), & 300 Testing images.
- Labeling: In our case, all images in the edible/ folder are labeled edible, and all images in the poisonous/ folder are labeled poisonous. (Deleted the 400 random labels. Plus one additional dataset)



DATA SUMMARY

Create

Home

Competitions

Datasets

Models

Benchmarks

Game Arena

Code

Discussions

Learn

More

Search

image-mushroom-dataset

Data CardCode (0)Discussion (0)Suggestions (0)

poisonous mushroom sporocarp (758 files)

274_Hg0Etk30u.jpg
160.65 kB

275_pltq4xw22Ag.jpg
141.15 kB

276_xj0pN3hg-Rl.jpg
207.03 kB

277_wizV30u8kA.jpg
173.57 kB

278_010rYw4FvoY.jpg
146.57 kB

279_Ogh02UcQ_cA.jpg
64.22 kB

279_7BwdZgYTJOY.jpg
171.57 kB

280_dQwEUpoNmU.jpg
187.28 kB

281_0d007phwV8.jpg
184.15 kB

281_annw48Du7ec.jpg
903.23 kB

282_Ugspwe2-yb0.jpg
137.53 kB

283_9v3LcOK010.jpg
205.69 kB

283_k0xQesKuzY8.jpg
159.61 kB

284_m02jZJaelec.jpg
192.05 kB

285_rVxKQZTf8M.jpg
143.71 kB

286_h3-3FWFZc8.jpg
118.01 kB

287_5LBFw0WLE.jpg
81.05 kB

287_a5nnHXszX8g.jpg
129.12 kB

289_q_9DmUp5v4.jpg
156.65 kB

292_GneoeXDSchM.jpg
69.63 kB

Data Explorer



Version 1 (374.29 MB)

image-mushroom-dataset

Summary

3886 files


BASELINE CNN MODEL RESULTS



accuracy: 0.7772 - loss: 0.4876

Final validation accuracy: 0.7797

Final validation loss: 0.4826



Classification Report:


| | precision | recall | f1-score | support |
|--------------|-----------|--------|----------|---------|
| edible | 0.60 | 0.52 | 0.56 | 137 |
| poisonous | 0.83 | 0.88 | 0.85 | 376 |
| accuracy | | | 0.78 | 513 |
| macro avg | 0.72 | 0.70 | 0.71 | 513 |
| weighted avg | 0.77 | 0.78 | 0.77 | 513 |

Detailed Metrics:

True Negatives (TN): 71
False Positives (FP): 66
False Negatives (FN): 47
True Positives (TP): 329

Overall Accuracy: 0.7797
Precision: 0.8329
Recall: 0.8750
F1-Score: 0.8534

MOBILENETV2 + FINE-TUNNING CNN MODEL RESULTS




Classification Report:

| | precision | recall | f1-score | support |
|--------------|-----------|--------|----------|---------|
| edible | 0.86 | 0.77 | 0.81 | 137 |
| poisonous | 0.92 | 0.95 | 0.94 | 376 |
| accuracy | | | 0.90 | 513 |
| macro avg | 0.89 | 0.86 | 0.87 | 513 |
| weighted avg | 0.90 | 0.90 | 0.90 | 513 |

accuracy: 0.9139 - loss: 0.2969

Final validation accuracy: 0.9045
Final validation loss: 0.2957



Detailed Metrics:

True Negatives (TN): 105
False Positives (FP): 32
False Negatives (FN): 17
True Positives (TP): 359

Overall Accuracy: 0.9045
Precision: 0.9182
Recall: 0.9548
F1-Score: 0.9361

RESULTS

ANALYSIS


```
Test accuracy: 0.4800  
Test loss:    0.8638
```

```
edible: 759  
poisonous: 1808
```

```
Test accuracy: 0.5644  
Test loss:    1.5081
```

- The predicting is not much better compare to random guess, does that mean we failed?
 - No. We put a focus on recall! That is to say, we don't want poisonous mushrooms to be classified as edible.
 - To do that, we trained the data with a rather imbalanced dataset.

OTHER METRICS EXCEPT ACCURACY



Classification Report (Test Set):

| | precision | recall | f1-score | support |
|-----------|-----------|--------|----------|---------|
| edible | 0.61 | 0.33 | 0.43 | 416 |
| poisonous | 0.55 | 0.79 | 0.65 | 422 |

FINAL OPTIMIZED MODEL RESULTS

- DATASET ADDED:

[HTTPS://WWW.KAGGLE.COM/DATASETS/MARCOSVOLPATO/EDIBLE-AND-POISONOUS-FUNGI/DATA](https://www.kaggle.com/datasets/marcosvolpato/edible-and-poisonous-fungi/data)

- FINE-TUNING DELETED

POISONOUS MUSHROOMS


- CORRECTLY IDENTIFIED 752 / 894
- RECALL \approx 84%
- 16% OF POISONOUS MUSHROOMS ARE MISCLASSIFIED AS EDIBLE (HIGH RISK)

EDIBLE MUSHROOMS

- CORRECTLY IDENTIFIED 350 / 472
- RECALL \approx 74%
- 122 EDIBLE MUSHROOMS ARE INCORRECTLY LABELED AS POISONOUS

OVERALL EVALUATION

- MODEL SHOWS MODERATE PERFORMANCE
- ACCURACY IS ACCEPTABLE, BUT ERROR RATE IS STILL TOO HIGH FOR SAFE USE, ESPECIALLY FOR POISONOUS CASES




FUTURE

FUTURE

- Use a more diverse set of images, train on more samples, and evaluate on a larger test set. (pictures of different daytimes, lights, colors, angles, etc.)
- Improve performance and reduce overfitting. (Add additional features: eg, more effective validation, regularization)
- Try to train the models with different threshold or different weights on the train dataset. e.g. >0.5 threshold for classifying as poisonous or edible pictures to have heavier weight when training to find a reasonable accuracy and recall tradeoff.

REFERENCE

- Li, H.-J., Zhang, H.-S., Zhang, Y.-Z., et al. (2020). Mushroom Poisoning Outbreaks — China, 2019. China CDC Weekly, 2(2), 19–24. <https://doi.org/10.46234/ccdcw2020.005>
- https://www.researchgate.net/publication/359553408_A_New_Deep_Learning_Model_for_the_Classification_of_Poisonous_and_Edible_Mushrooms_Based_on_Improved_AlexNet_Convolutional_Neural_Network
- <https://onlinelibrary.wiley.com/doi/full/10.1155/2022/1173102?msocid=0278f1d25948690f3cfce774581e6823>

The background of the image is a landscape featuring a green field in the foreground and a blue sky with large, white, fluffy clouds in the background. The text "THE END" is centered in the upper half of the image.

THE END

|

THANK YOU