Qeedji

User manual

SBL10e m365_user

1.12.10 001A

Legal notice

SBL10e m365_user 1.12.10 (001A_en)

Rights and Responsibilities

Product information

Product design and specifications are subject to change at any time and `Qeedji` reserves the right to modify them without notice. This includes the hardware, the embedded software and this manual, which should be considered as a general guide to the product. The accessories supplied with the product may differ slightly from those described in this manual, depending on the developments of the various suppliers.

Precautions for use

Please read and heed the following warnings before turning on the power: - installation and maintenance must be carried out by professionals. - do not use the device near water. - do not place anything on top of the device, including liquids (beverages) or flammable materials (fabrics, paper). - do not expose the device to direct sunlight, near a heat source, or in a place susceptible to dust, vibration or shock.

Warranty clauses

The `Qeedji` device is guaranteed against material and manufacturing defects for a certain duration. Check the device warranty duration value at the end of the document. These warranty conditions do not apply if the failure is the result of improper use of the device, inappropriate maintenance, unauthorized modification, operation in an unspecified environment (see operating precautions at the beginning of the manual) or if the device has been damaged by shock or fall, incorrect operation, improper connection, lightning, insufficient protection against heat, humidity or frost.

WEEE Directive

This symbol means that your appliance at the end of its service life must not be disposed of with household waste, but must be taken to a collection point for waste electrical and electronic equipment or returned to your dealer. Your action will protect the environment. In this context, a collection and recycling system has been set up by the European Union.

Table of contents

Part I

Description and installation

1.1 Introduction

This manual explains how to install and configure your device SBL10e device.

Recommendations and warnings

This device is designed for indoor use only.

To ensure better rendering of the SBL10e, the device should not be installed under direct sunlight.

The SBL10e device is designed to be illuminated 12 hours a day, 7 days a week.

Package Contents

Articles	Description
Device	SBL10e device with the default `regular` [1] application embedded.

[1] *It is possible to easily update the device with the `m365_user` application afterwards.*

> ☛ *In this documentation, the unit of measurement for dimensions is done in millimeters followed by its equivalent value in inches.*

1.1.1 Device dimensions





1.1.2 Labelling

Product label

The model of the device, the power supply characteristics, the serial number (PSN) and the MAC address are written on a label stuck on the case.



> ☛ *The QR code on the product label is corresponding to the product identification URL, for example:*
> `i.qeedji.tech?model=SBL10e&sn=01320-00009&mac.lan1=00-1C-E6-02-4C-EC&mac.wpan1=DF-27-83-3C-8A-90` .

Packingbox label

This is the label stuck also on the packingbox. It is showing:

- the device model,
- the product serial number (PSN) (embedded also in the QR code),
- the manufacturer Website.



> ☛ *The QR code on the packingbox label is corresponding to the product PSN, for example:*
> `PSN01320-00009 CD1` .

> ☛ *The serial number of the device may be requested in case of technical support.*

1.1.3 Installation

> ☛ *Install the SBL10e device on the Ethernet wall plugs of the buildings following the installation map given by your IT departement.*

The SBL10e device has to be plugged to an Ethernet wall plug supporting PoE IEEE802.3af.



Given the device footprint, it is preconised to use Ethernet wall plug plastron with a right insertion.

Consequently, the Ethernet wall plug whose plastron is angled is not supported.

> ☛ *Thanks to the lock pin of its Ethernet connector, the SBL10e device can be installed on vertical surfaces, like walls as well as horizontal surfaces, like ceilings.*

1.1.4 Uninstallation

With a screw driver, hold down the pin of the Ethernet connector ① of the SBL10e device at the same time you are releasing with the hand ② the SBL10e device from the Ethernet wall plug.



1.2 Smart Busy Light applications

The `m365_user` application periodically connects to your `M365` (Microsoft 365) solution and to get information about a specific *user* `Teams` state. Depending on the user is available or not, the appropriate light state/color is displayed.

Light states and colors

The device can support the states and colors values showed below.

Color	State
	`OFF`
`Red`	`ON steady` or `ON flashing`
`Green`	`ON steady` or `ON flashing`
`Blue`	`ON steady` or `ON flashing`
`Orange`	`ON steady` or `ON flashing`
`Yellow`	`ON steady` or `ON flashing`

> ☛ *The `ON flashing` state is flashing with this sequence: `ON` for 0,5 seconds then `OFF` for 0,5 seconds every one second.*

> ☛ *Depending on the application running on it, some color/state may be never used.*

> ☛ *The light color and state values are stored in the volatile memory (RAM). That means that in case the SBL10e device is unplugged from the Ethernet wall plug then plugged back again, the light comes back to its default state: `OFF` until its state is then modified by the App or by the user.*

Configuration

The `Smart Busy Light` application supports the configuration update:

- by connecting to the device configuration Web user interface `http://<device-ip-addr>/` and changing parameters,
- by pushing, from a WebDAV client or with the device Web user interface, a `prefs.json` configuration file on the device WebDAV directory `http://<device-ip-addr>/.conf/`,
- by pushing, from a WebDAV client or with the device Web user interface, a `.js` configuration script on the device WebDAV directory `http://<device-ip-addr>/.conf/`,
- by receiving a `configure` command with an appropriate `.js` configuration script from the `Qether` tool (Qether V1.12.10 or above).

Firmware upgrade

The `Smart Busy Light` application supports the firmware upgrade:

- by connecting to the device configuration Web user interface `http://<device-ip-addr>/` and loading an appropriate `bm0032_m365_user-sbl10e-xx.yy.zz.bin` [1] firmware file,
- by pushing a new `bm0032_m365_user-sbl10e-xx.yy.zz.bin` [1] firmware file at the root of the device WebDAV directory `http://<device-ip-addr>/`, pushed with a WebDAV client,
- by receiving an `install` command with an appropriate `bm0032_m365_user-sbl10e-xx.yy.zz.bin` [1] firmware file from the `Qether` tool.

[1] *Can work also with any other `bm0032_<custom>-sbl10e-xx.yy.zz` compatible firmware.*

> ☛ *After a firmware upgrade, the device is rebooting once.*
>
> ☛ *When the `configuration` command or the `install` command has been processed, the last `Smart Busy Light` state and color are restored.*

Preprogrammed flashing sequence

The SBL10e device has two modes:

- `Nominal mode` : the `Smart Busy Light` application runs properly and sets the light state and color as expected. When a configuration or a firmware upgrade is in progress, the light illumination can be temporarily inconsistent and follows the light flashing sequence shown in the table hereafter.
- `Recovery mode` : the `Smart Busy Light` application can not be executed. The light state or color can not be modified anymore. It is required to update the firmware to return to the `nominal mode`.

Depending on these modes, the `Smart Busy Light` applications can fall into one of these preprogrammed flashing sequences:

Mode	`Smart Busy light` **behaviour**	**Information**
Recovery	**2** very short and consecutive blue flashs (250 ms) with a 4,5 seconds periodicity	The Smart Busy Light application can not be executed. It should never happen. The device Web user interface is so not available. This sequence is displayed until a new firmware update is done with `Qether` tool. For further information, contact support@qeedji.tech.
Recovery	**3** very short and consecutive blue flashs (250 ms) with a 5 seconds periodicity	The software resource of the SBL10e device set at factory are not valid. It should never happen. For further information, contact support@qeedji.tech.
Nominal or recovery	**4** very short and consecutive blue flashs (250 ms) with a 5,5 seconds periodicity	A SBL10e device `Firmware update` is in progress. Please wait a couple of seconds.
Nominal	**5** very short and consecutive blue flashs (150 ms)	A SBL10e device `configuration` is in progress. Please wait a couple of seconds.
Nominal	**6** very short and consecutive blue flashs (150 ms)	The datasource is not consistent because some of the parameters are missing or have a wrong value. For further information about the datasource form, refer to the chapter § Configuration > Servers. For further information about the reporting of the problems faced with some datasource parameters, refer to the chapter § Maintenance > Logs.

Part II

Applicative user interface

2.1 Applicative user interface

The SBL10e device supports a Web user interface that can be accessed with a Web browser. The supported Web browsers are: `Google Chrome`, `Mozilla Firefox`, `MS-Edge (Chromium)`.

It is available from the URL: `http://<device_IP_addr>/`.

The URL falls into the `m365_user` applicative user interface: `http://<device_IP_addr>/webui/`.

This pane allows to watch, according on the `MS Teams` availability status from your company employee :

- the current light color/state,
- the `Activity` state,
- the `Availability` state.

`MS Teams` **availability status**	**LED light Status**	**LED light color**	`Availability`	`Activity`
Available	ON steady	green	*Available*	*Available*
Be right back	ON steady	orange	*BeRightBack*	*BeRightBack*
Busy	ON steady	red	*Busy*	*Busy*
Do not disturb	ON steady	red	*DoNotDisturb*	*DoNotDisturb*
Appear away	ON steady	red	*Away*	*Away*
Appear offline	ON steady	red	*Offline*	*OffWork*

> ☛ *The LED light Status is OFF when the M365 datasource is not properly configured.*
>
> ☛ *Note that `MS Teams` change automatically the `MS Teams` availability status to the `Busy` value when a meeting takes place right now in the M365's calendar of the company employee.*

Part III

Administration console user interface

3.1 device configuration Web user interface

The SBL10e device supports a device configuration Web user interface that can be accessed with a Web browser. The supported Web browsers are: `Google Chrome`, `Mozilla Firefox` and `MS-Edge (Chromium)`.

It is available from the URL: `http://<device_IP_addr>/`.

The default credentials values, put at factory, to access to the device Web user interface are:

- login: `admin`,
- password: `admin`.

The URL falls automatically into the applicative user interface[1]. At the top right corner, click on the `Administration Console` button.



[1] *For further information, refer to the chapter § Applicative user interface.*

This is the device configuration Web user interface.



> ⚠ After you have changed and saved all your settings in the different panes, be sure to perform a device restart by clicking on the `Reboot the device` (2) button so that your changes are fully reflected.

Click on the device logo (1) at the left top corner to return to the applicative user interface.

3.1.1 Configuration > Administrator

In the `Configuration` tab, select the **Administrator** menu to change:

- the `Hostname`,
- the login credentials:
  - `Administrator name`,
  - `Password`.

> ☛ *It is recommended that you enter one unique `Hostname` value for each device. In case several SBL10e devices are located in different buildings or geographical locations, we recommend that you enter hostname values with information about the building and the location (e.g. `Hall-RD-Paris-1`).*

For security reasons, it may be useful to change the login credentials values. Please keep them in a safe place afterwards.

> ☛ *The same login credentials are used to access to the WebDAV server and to use Web services.*

3.1.2 Configuration > LAN

In the `Configuration` tab, select the **LAN** menu to set up the network configuration of the `LAN` interface of your device.



> ☛ *The device supports the UPnP and can be for example detected automatically in the local network environment of your computer.*

Enter a suitable LAN network configuration so that the device can access to the Web to get the local time with a NTP server.

> ☛ *By default, the device is configured with `Obtain an IP address automatically by DHCP` activated and `Time for attempts` deactivated. As soon as the DHCP server becomes available, the device ends by getting back a valid IP address given by the DHCP server within less than one minute.*
>
> ☛ *After a device reboot, when the device is configured with `Obtain an IP address automatically by DHCP` activated and `Time for attempts` is activated, in case the DHCP server is unavailable after the `Time for attempts` duration (ten minutes for the maximum and default value) has expired, the device ends up using the static IP address entered in the LAN configuration. The default static IP address is 192.168.0.2 when it has never been changed yet by the user. It is recommended to set an appropriate IP address, netmask and gateway if this case would happen. In case a daily reboot task is programmed, the device will restart this operation every days.*
>
> ☛ *When only the `Time for attempts` value is modified, press on TAB key of your keyboard to make appear the `Validate` button.*

3.1.3 Configuration > Servers

In the `Configuration` tab, select the **Servers** menu to enter the configuration to connect to the servers peripheral to your device.

The `Datasource Server` pane allows to configure the SBL10e device to that it can access to the current Microsoft Teams availability status of an employee of your company.

The granting for some permissions required for the `Azure AD` application to control the MS-Teams availability status from an company employee implies to use an M365 delegate account. For further information, refer to the chapter § Appendix: Create a delegate account.

> ☛ *When only the heartbeat value is modified, press on TAB key of your keyboard to make appear the `Validate` button.*



- `Datasource Server` :
  - `Type` (1): type of application (e.g.*M365_user*),
  - `Tenant Id` (2): *Azure AD* application Directory Tenant Id,
  - `Client Id` (3): *Azure AD* application client Id,
  - `Client Secret` (4): *Azure AD* application secret value,
  - `Username` (5): email of the *M365* delegate account used to get the *MS Teams* availability status for your company employee,
  - `Password` (6): password of the *M365* delegate account used to get the *MS Teams* availability status for your company employee,
  - `Resource Id` (7): email of the *M365* company employee whose *MS Teams* availability status must be controlled,
  - `Heartbeat` (8): periodicity of the connection to the *MS Teams* server:
    - from 10 (default value) to 900 seconds,
- `HTTPS proxy server` (9):[1]
  - `Address` : enter the IPv4 address, or the domain name of your *proxy* server,
  - `Port` : enter the operating port of your *proxy* server,
- `DNS servers` (10),
- `NTP time server` (11): ensure that `NTP time server` is checked and has a valid IP address.

> ☛ *The `m365_user` application can get the current MS-Teams availability status without having a valid date.*
>
> ☛ *The NTP time server is the only way for the SBL10e device to be on time and control the time of the daily reboot task. When the NTP time server is configured, ensure to have a valid gateway and to have a valid DNS server.*

The `m365_user` application for busylight implies to create an *Azure Active Directory (Azure AD) application*. After consent success, fill with the appropriate values:

- *Azure AD* application `Tenant Id` (1),
- *Azure AD* application `Client Id` (2),
- *Azure AD* application `Client Secret` (3).

> ☛ *The same `Tenant Id` , `Client Id` , `Client Secret` value can be then used for all your `SBL10e` devices having a `m365_user` application.*

[1] *HTTPS Proxy server is not supported in the `m365_user` application. Activating proxy server may prevent the device to connect to M365.*

For further information about the procedure to create an *Azure Active Directory* application using the *Azure AD* portal, refer to the chapter § Appendix: Create M365 application with Azure AD portal.

For further information about the procedure to create an *Azure Active Directory* application using the *AAD* PowerShell module, refer to the chapter § Appendix: Create M365 application with Powershell.

> ⚠ Some organization can use an alias for the `Resource Id` email instead of using the official one. For the user `Resource Id` (4), do ensure to only enter the `User principal Name` of the `resource Id. For further information, refer to the chapter § Appendix: Azure AD User Principal Name.

This is an example with a `M365 Resource Id` called `employee1@contoso.onmicrosoft.com` (fake values):

- *Azure AD* application `Client Id` : *269d8878-f581-43fe-b53d-fea6c181b7f4*
- *Azure AD* application `Tenant Id` : *967b7cc3-847f-41ec-bd74-997a4df1855b*
- *Azure AD* application `Client secret` : *6-CdOVxv6p1wwH4y0Q6Yr11SY7.dU~Tt*

- *M365* `Username` : *myDelegate@contoso.onmicrosoft.com*
- *M365* `Password` : *myDelegate_pwd1*
- *M365* `Resource Id` : *employee1@contoso.onmicrosoft.com*

> ☛ *When only the* `Heartbeat` *value is modified, press on TAB key of your keyboard to make appear the* `Validate` *button.*
>
> ☛ *If the server is not available after 20 (default value stored in the* `appli.network.datasource.nb_retries_before_cache_reset` *user preference) consecutive unsuccessful connection attempts, the light is switched Off until the next successful connection attempt.*
>
> ⚠ Upgrading the device with another application type will clear the current datasource's configuration data. When the device is properly configured, it is advised to build and save an appropriate configuration script (`.js`) by using the configuration script template or save at least the `prefs.json` configuration file of your device. For further information, refer to the chapter § Maintenance > Files.

3.1.4 Configuration > Date and time

In the `Configuration` tab, select the **Date and Time** menu to check the time configuration:

- timezone,
- system date of your device (day and time).



> ☛ *The application can work even though the device is not on time. Anyway, in case the `Reboot` task is activated, it is advised to set an appropriate date and time, synchronized with a NTP server, to control exactly when the SBL10e must reboot. For further information, refer to the chapter § Configuration > Servers.*

3.1.5 Configuration > Tasks

In the `Configuration` tab, select the **Tasks** menu to activate a device `reboot manager` task and adjust the `reboot manager` task time.



> ☛ *During the reboot task, the light state is `Off` for a couple of seconds until the next data source server connection.*

> ☛ *If the NTP server set by the user is not available anymore and the `system.task.reboot.enable` user preference is true, the device is rebooting automatically every days, 24 hours after the last device reboot.*

3.1.6 Maintenance > Firmware

In the `Maintenance` tab, select the **Firmware** menu to view the version of the application installed on your device.

Drop your `.bin` file in the `Drop file here or click to add one` location or click on it to add one, then click on the `Send` button to update the firmware version of your device. Wait a couple of seconds, the time to load and install the new firmware version. Connect again to the device configuration Web user interface and check the new firmware version.

The user preferences common to the applications are kept when upgrading from `regular` application to another application (and reciprocally) meaning:

- network configuration,
- file system,
- hostname,
- web user interface credentials.

> ⚠ Do not electrically disconnect the device during the firmware upgrade.

3.1.7 Maintenance > Preferences

In the `Maintenance` tab, select the **Preferences** menu to view all the preferences.

The filter allows to display only the preferences whose name contains the string entered in the filter. All the preferences have optimal default values.

Double click on a preference to change its value.

At the bottom right of the page, the `Restore factory preferences` button allows to reset a subset of preferences allowing the device to reprogram its factory preferences. In this case, the LAN network configuration returns to DHCP.

Click on the `Reboot the device` button so that the modifications are taken into account.

> ⚠ After a user preference restoration, in case a `.js` configuration script, suitable for the application of this SBL10e device, is available on the `TFTP` server, the user preference `system.tftp.enable` is set to *true*. Consequently, the SBL10e device is rebooting once again to take into account the `.js` configuration script available on the `TFTP` server.

Timezone

Continent	***Country/Town* pair values supported for the `system.datetime.timezone` preference**
Africa	Africa/Brazzaville, Africa/Cairo, Africa/Casablanca, Africa/Harare, Africa/Lagos, Africa/Nairobi, Africa/Onitsha, Africa/Windhoek
America	America/Anchorage, America/Argentina/Buenos_Aires, America/Barbados, America/Bogota, America/Boston, America/Caracas, America/Chicago, America/Chihuahua, America/Costa_Rica, America/Dallas, America/Denver, America/Godthab, America/Halifax, America/Houston, America/Los_Angeles, America/Manaus, America/Mexico_City, America/Montevideo, America/New_York, America/Phoenix, America/Recife, America/Regina, America/Rio_de_Janeiro, America/San_Francisco, America/Santiago, America/Sao_Paulo, America/St_Johns, America/Tijuana, America/Washington,_D.C.
Asia	Asia/Ahmedabad, Asia/Almaty, Asia/Amman, Asia/Baghdad, Asia/Baku, Asia/Bangalore, Asia/Bangkok, Asia/Beijing, Asia/Beirut, Asia/Chengdu, Asia/Chennai, Asia/Chongqing, Asia/Colombo, Asia/Delhi, Asia/Dongguan, Asia/Dubai, Asia/Guangzhou, Asia/Hangzhou, Asia/Hanoi, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hyderabad, Asia/Irkutsk, Asia/Jakarta, Asia/Jerusalem, Asia/Kabul, Asia/Karachi, Asia/Kathmandu, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuwait, Asia/Lahore, Asia/Magadan, Asia/Mumbai, Asia/Nagoya, Asia/Nanjing, Asia/Oral, Asia/Osaka, Asia/Pune, Asia/Quanzhou, Asia/Seoul, Asia/Shanghai, Asia/Shenyang, Asia/Shenzhen, Asia/Surat, Asia/Taipei, Asia/Tbilisi, Asia/Tehran, Asia/Tianjin, Asia/Tokyo, Asia/Vladivostok, Asia/Wuhan, Asia/Xi'an, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Asia/Zhengzhou
Atlantic	Atlantic/Azores, Atlantic/Cape_Verde, Atlantic/South_Georgia
Australia	Australia/Adelaide, Australia/Brisbane, Australia/Darwin, Australia/Hobart, Australia/Perth, Australia/Sydney
Europe	Europe/Amsterdam, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Brussels, Europe/Dusseldorf, Europe/Helsinki, Europe/Istanbul, Europe/London, Europe/Madrid, Europe/Minsk, Europe/Moscow, Europe/Paris, Europe/Sarajevo, Europe/Warsaw
Pacific	Pacific/Auckland, Pacific/Fiji, Pacific/Guam, Pacific/Honolulu, Pacific/Majuro, Pacific/Midway, Pacific/Noumea, Pacific/Tongatapu
UTC	Etc/UTC

3.1.8 Maintenance > Logs

In the `Maintenance` tab, select the **Logs** menu to view the logs.



In the example, there is no error raised in the logs.

When the `system.tftp.server` user preference is *true*:

- in case there is some available `.js` configuration script on the `TFTP` server with the appropriate file name pattern, this message is printed: `TFTP client enable: matching configuration script available on TFTP server (<IP address>)`.
- in case there is no `.js` configuration script on the `TFTP` server with the appropriate file name pattern, this message is printed: `TFTP client enable: no configuration script available on TFTP server for this device (<IP address value>)`.
- in case the `TFTP` server is not available, this message is printed: `TFTP client enable: error server did not respond (<IP address>)`.

When the `system.tftp.server` user preference is *false*: this message is printed: `TFTP client disable`.

> ⚠ To be successfully taken into account, the content of the `.js` configuration script available on the `TFTP` server must also be suitable for the SBL10e device and for the middleware version.

In case your device is flashing 6 times every 4 seconds meaning that the device configuration is probably not correct, you are invited to check the logs in this window to try to fix the trouble.

The logs are allowing to know whether:

- **the M365 server is available**: if not, check your internet connection and check with your administrator account that your M365 system is properly configured and available,
- **the `Tenant Id` is valid**: if not, check again that your directory *Tenant Id* value is really existing and some `m365_user` application has been already registered with your `Azure AD` system configuration,
- **the `Client Id` is valid**: if not, check again that your application *Client Id* value is really existing and some `m365_user` application has been already registered with your `Azure AD` system configuration,
- **the `Client Secret` is valid**: if not, check again that your application *Client secret* value has been properly copied/pasted at the right location and is really existing and that a `m365_user` application has been already registered with your `Azure AD` system configuration. In case it has been generated with *AAD Powershell script*, ensure it has been generated with the version of *AAD Powershell script* V1.10.18 (or above),
- **the `Username` is valid**: if not, meaning that the *The user account {EmailHidden} does not exist* error message is raised in the logs, check again that the *Username* value, corresponding to the email value of the delegate account, is really existing in your M365 system configuration and is effectively the *User Principal Name* of the resource (and not an alias),
- **the `Password` is valid**: if not, meaning that the *Error validating credentials due to invalid username or password* error message is raised in the logs, check again that the *Password* value, corresponding to the password value of the provided delegate account, is the right one,
- **the `Resource Id` is valid**: if not, check again that the provided *Resource Id*, email value from which the calendar availability is controled, is really existing in your M365 system configuration, and is effectively the *User Principal Name* of the resource (and not an alias).
- **the system date is valid**: if not, check that *NTP time server* is activated and has a valid IP address. After a reboot, in case a Web connection is available, the device should be on time.

For any other error, contact support@qeedji.tech.

3.1.9 Maintenance > Tools

[1] *The flash memory storage is used to store all the directories and files hosted at the root of the WebDAV directory, and the user preferences as well. In case a flash formatting, the device returns to the default factory settings.*

3.1.10 Maintenance > Files

In the `Maintenance` tab, select the **Files** menu to see the directories and files hosted at the root directory of the WebDAV server.

As soon as a modification is done through the device configuration Web user interface, a `prefs.json` file, corresponding to the new device configuration, is created in the `.conf` folder.

When the user preference `system.tftp.enable` is *true*, a `tftp_crc` file, containing the CRC of the `.js` configuration script downloaded from the `TFTP` server is written in the `.conf` folder. To be downloaded again from the `TFTP` server, either the suitable configuration script must be modified on the `TFTP` server, or the `tftp_crc` file must be removed.

> ⚠ After having pressed on the `Restore factory preferences` button, the `prefs.json` file and the `tftp_crc` file are erased.

> ⚠ The content of the `prefs.json` ③ configuration file can be different for `m365_user` application and other applications.

Save or restore the device configuration

> ⚠ It is recommended to save the `configuration.js` preciously to configure your SBL10e device in order to be able to restore its configuration afterwards.
>
> ⚠ The content of the `configuration.js` is depending on the used application. Do use the suitable `configuration.js` for the `m365-user` application.



Application upgrade

The current application can be upgraded by pushing a new firmware file `bm0032_m365_user-sbl10e-xx.yy.zz.bin` at the root of the device WebDAV directory `http://<device-ip-addr>/` with a WebDAV client.

After the firmware file pushing, a device reboot is required so that the new firmware file is taken into account.

Configuration update

The configuration of the application can be updated also by pushing an appropriate `.js` configuration script (or a suitable `prefs.json` file) suitable for your application in the `.conf` WebDAV directory (`http://<device-ip-addr>/.conf`) with the Web user interface or with a WebDAV client.

> ⚠ Loading a wrong `prefs.json` would lead to some loss of data like the datasource server configuration. So check the consistency of the `prefs.json` file before uploading it in the device. To avoid any error on the configuration of the application and the configuration of the SBL10e device, it is advised to use a `.js` configuration script (and not with a `prefs.json` file) which is testing before executing anything that it is suitable for the SBL10e device and suitable for the application running on the device. Qeedji provides configuration script template. It is then highly recommended for the user to save an appropriate `.js` configuration script for each SBL10e device installed in his building.

A `000000000000.js` template is available for download here.

In this case, the file pattern must be either:

- `configuration.js` : suitable for any device whatever its MAC address,
- `000000000000.js` : suitable for any device whatever its MAC address,
- `<device_LAN1_MAC_address>.js` (with the format `ABCDEFABCDEF.js`): suitable for device whose MAC address is matching.

After having downloaded the configuration script template:

- edit the `000000000000.js` configuration script and uncomment/modify the appropriate lines according to your needs,
- rename the configuration script if required,
- once saved, drop it in the `.conf` WebDAV directory like explained above,
- when the .js configuration script is satisfying, save it preciously to be able to restore its configuration after wards.

After a `.js` configuration script uploading in the device, the device is rebooting automatically once to take the new configuration into account.

> ☛ *The `prefs.json` file is available in the `.conf` WebDAV directory of the devive as soon as the SBL10e device configuration is modified at least once by the user. After a device configuration updating with a `prefs.json` file, a device reboot is required so that the new configuration is taken into account.*
>
> ☛ *Pushing a `.js` configuration script in the `.conf` WebDAV directory (`http://<device-ip-addr>/.conf`) with a WebDAV client could raise a warning at the WebDAV client end, after the `.js` file transferring is completed because the device is automatically rebooting once when it is received. For example, after the `.js` file sending with BitKinex WebDAV is done, another network request is done by the WebDAV client while the device is currently rebooting. So a WebDAV error at the WebDAV client end leads to an automatic file resending which is causing another device reboot and so on, and this, until the WebDAV client application is closed. For example, after the `.js` file sending with CarotDAV WebDAV client, the error leads only to the displaying of a warning message. The user has just to ignore the error at the WebDAV client end.*

3.1.11 Information > Device

In the `Information` tab, select the **Device** menu to view system information about the device.

- `Firmware` : label and version of the firmware embedded in the device,
- `Model` : model of the `Qeedji` device,
- `Manufacturer` : product manufacturer name,
- `Manufacturer URL` : manufacturer Website,
- `Hostname` : name of the device on the network,
- `UUID` : Universal Unique IDentifier,
- `PSN` : Product Serial Number.

3.1.12 Information > Network

In the `Information` tab, select the **Network** menu to view a summary of the device's network configuration.

Part IV

Technical information

4.1 Technical specifications

Model	Manufacturer
SBL10e	Qeedji

Power supply	Information
PoE IEEE802.3af	POE power supply input: ES1 / PS2 (48 V – 100 VA)

Processors	
CPU	Nordic Semiconductor nRF52
Security processor	ARM CryptoCell 310

Storage	
Flash Memory for file system	8 MBytes

Network	Other information
1x Ethernet	10/100 Base T, male connector

WPAN
Bluetooth Low Energy 5
Frequency band: 2.402 to 2.480 GHz
Tx Power: +8 dBm

Operating temperature	Storage temperature
+0 °C to +40 °C	-20 °C to +60 °C
+32 °F to +104 °F	-4 °F to +140 °F

Operating humidity	Storage humidity
< 80 %	< 85 %

Weight	Dimensions (W x H x D) (RJ45 male connector included)
35 g	60,5 mm x 60,5 mm x 67 mm
0,077 lb	2,36" x 2,36" x 2,63"

Plastic enclosure flame rating
Base: PVC UL 94-5VA, bulb: Polycarbonate UL 94 V-2

Warranty
1 year

4.2 Conformities

EUROPE

In conformity with the following European directives:

- `LVD 2014/35/EU`,
- `EMC 2014/30/EU`,
- `RED 2014/53/EU`.

USA

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference's by one or more of the following measures:

- reorient or relocate the receiving antenna,
- increase the separation between the equipment and the receiver,
- connect the equipment into an outlet on a circuit different from that to which the receiver is connected,
- consult the dealer or an experienced radio/TV technician for help.

This equipment complies with FCC's radiation exposure limits set forth for an uncontrolled environment under the following conditions:

- this equipment should be installed and operated such that a minimum separation distance of 20 cm is maintained between the radiator (antenna) and user's/nearby person's body at all times,
- this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- this device may not cause harmful interference,
- this device must accept any interference received, including interference that may cause undesired operation.

Qeedji is not responsible for any changes or modifications not expressly approved by the party responsible for compliance. such modifications could void the user's authority to operate the equipment.

CANADA

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- this device may not cause interference,
- this device must accept any interference, including interference that may cause undesired operation of the device.

Part V

Contacts

5.1 Contacts

For further information, please contact us:

- **Technical support**: support@qeedji.tech,
- **Sales department**: sales@qeedji.tech.

Refer to the `Qeedji` Website for FAQ, application notes, and software downloads: https://www.qeedji.tech/


```
Qeedji FRANCE
INOVELEC-INNES SA
5A rue Pierre Joseph Colin
35700 RENNES

Tel: +33 (0)2 23 20 01 62
Fax: +33 (0)2 23 20 22 59
```

Part VI

Appendix

6.1 Appendix: Web services

These are the supported Web services for the `m365_user` application to command and control the SBL10e:

Webservice path	HTTP method				Query string parameters	Body	Function	From the m365_user application version
	GET	POST	PUT	DELETE				
api/v1/sys/power			yes		<state>=rebooting	""	Reboot the device	1.10.13
api/v1/software/version	yes				None	i.e.: {"value":"1.10.13"}	Get the device delivery software version	1.10.13
api/v1/software/label	yes				None	{"value":"bm0032_m365_user"}	Get the device delivery software label	1.10.13
api/v1/sys/sn	yes					PSN Short representation: i.e.: {"value":"01320-00004"}	Get the device SN	1.10.13
api/v1/sys/model-name	yes				None	{"value":"SBL10e"}	Get the device model name	1.10.13
api/v1/sys/mnufacturer	yes				None	{"value":"Qeedji"}	Get the mnufacturer	1.10.13
api/v1/sys/mnufacturer-url	yes				None	{"value":"www.qeedji.tech"}	Get Web Site of mnufacturer	1.10.13
api/v1/sys/uuid	yes				None	Uuid string value: <uuid> = <psn>-<48x0>-<mac-48> i.e.: {"value":"08400004-0000-0000-0000-001ce6024cad"}	Get the device UUID	1.10.13
api/v1/wpan1/mac	yes				None	Bluetooth MAC address value user formatted: i.e.: {"value":"db:f0:8c:72:64:a3"}	Get the device Bluetooth MAC address	1.10.13
api/v1/leds/light	yes				None	Get (plain text, separator CR): i.e.: {"state":"steady","color":"blue"} <state>= off | steady | flashing <color>=red | orange | blue | yellow | green	Get busylight led color and state	1.10.13
api/v1/sys/datetime	yes				None	{"value":"2021-08-11T06:09:58-02:30"}	Get busylight date and time	1.10.13

Examples syntax with CURL tool:

- reboot the device:

```
curl --user "<USERNAME>:<PASSWORD>" -i -X PUT "http://<DEVICE_IP_ADDR>/api/v1/sys/power?state=rebooting"
```

- get device state & color:

```
curl --user "<USERNAME>:<PASSWORD>" -X GET "http://<DEVICE_IP_ADDR>/api/v1/leds/light"
```

- get device firmware version:

```
curl --user "<USERNAME>:<PASSWORD>" -X GET "http://<DEVICE_IP_ADDR>/api/v1/software/version"
```

6.2 Appendix: Qether

In case an application can not be executed, the SBL10e returns to a `Recovery` mode, waiting for firmare update.

The provided `Qether` tool allows to make some remote operations on the SBL10e, based on its device MAC address like:

- SBL10e device firmware upgrade,
- SBL10e device configuration update,
- SBL10e device reboot.

The `<product_type>` is an extract of the device PSN value. For example, the *0132x-xxxx* `PSN` value leads to the *0132* `<product_type>`.

The `<SBL10e_device_MAC_address>` is the MAC address of the device with the format `00:1C:E6:AB:CD:EF`.

> ⚠ The MAC address of the device is written on the label stuck at the back of the SBL10e device with the format `00-1C-E6-AB-CD-EF`.

Discover command example

This command allows to find out the SBL10e devices available on the local network:

```
qether.exe FF 0132 discover
```

Configuration command syntax

Send a `.js` configuration script and apply it (default parameters):

```
qether.exe <SBL10e_device_MAC_address> <product_type> configure -f configuration.js
```

> ☛ *When using `Qether`, no specific filename pattern is required for the `.js` configuration script, except the `.js` file extension.*

> ☛ *The `system.httpd.username` preference value is limited to 15 characters max. The `system.httpd.password` preference value is limited to 100 characters max. The alphanumeric characters and the following characters `{}|~[]!#_$&()/;<=@|^%?+~(),'` are supported for the `system.httpd.username` and `system.httpd.password` preference values.*
>
> ☛ *The `system.hostname` preference value is limited to 15 characters max. The alphanumeric characters, the character `-` and the character `.` are supported for the `system.hostname` preference value.*
>
> ☛ *To get an IP address with the DHCP server, set `system.lan1.ipv4.static-addr` with the value `false`. Else to work with a static IP address, set `system.lan1.ipv4.static-addr` with the value `true`.*

Reboot command syntax

Reboot the target device:

```
qether.exe <SBL10e_device_MAC_address> <product_type> reboot
```

Firmware upgrade command syntax

Send a firmware file, with default transfer parameters, and install it. For example:

```
qether.exe <SBL10e_device_MAC_address> <product_type> install -f bm0032_m365_user-sbl10e-setup-1.11.12.bin
```

> ☛ *Qether needs first to be installed first on your MS-Windows computer. For further information, refer to the Qether user manual.*

6.3 Appendix: Device configuration with TFTP server (+ DHCP server code 66)

The SBL10e device can be configured thanks to a `.js` configuration script (Javascript) hosted on a `TFTP` [1] server associated to a `DHCP` server (code *66* option) properly configured and available on the local network.

[1] Trivial File Transfer Protocol

The `.js` configuration script downloading can be done as soon as a `DHCP` server is available, even whether the device is configured with a static IP address. Once connected to the `DHCP` server, the device can get:

- the IP address value of its network interface, when the option `Obtain IP address automatically by DHCP` is activated then,
- the primary DNS value when the `system.lan1.dns.static` user preference is *false* then,
- the `.js` configuration script from the `TFTP` server when the `system.tftp.enable` user preference is *true*.

Prerequisites:

- the approriate `.js` configuration script must be is available in the exported directory of the `TFTP server`. It must:
  - be suitable for the device, its firmware type and its firmware version,
  - match an appropriate filename pattern:
    - `000000000000.js` or,
    - `<device_LAN1_MAC_address>.js` (with the format `ABCDEFABCDEF.js`).

When a `.js` configuration script is modified on the `TFTP` server, the device must be restarted once so that the new configuration script is taken into account by the device.

> ☛ *When using a `TFTP` server, the `configuration.js` filename pattern is not supported.*
>
> ⚠ The downloading of a `.js` configuration script from a `TFTP` server can be done only at the device booting-up and when the device has never downloaded it before or when the script content has been modified since the last download (CRC check).

DHCP server configuration

The `DHCP` server must be configured to be associated to a `TFTP` server. For that, you need to use code 66 option (TFTP Server), using the IPv4 address value of the `TFTP` server.

For example, for a `Microsoft DHCP server`, you need to define the option *Boot Server Host Name* and give the IPv4 address of the `TFTP` server. It can be in *Extended option* and/or *Server Options*.

> ☛ *The service must be restarted so that the modifications are fully reflected.*



TFTP server configuration

The configuration is depending on the used software client. In all cases, you need to:

- get the directory URL that can be seen by `TFTP` clients,
- choose a `TFTP` security *None*,
- keep the default port (69).

Here is an example of the `tftpd32` software with MS-Windows.



In this example, the `TFTP` server address is `192.168.1.15` and the exported directory is `D:/usr/tftp`.

> ☛ *In this pane, enter the IP address of the `TFTP` server. Indeed entering the `TFTP` server domain name may prevent the feature to work properly.*

Copy the `.js` configuration script in the exported directory of the `TFTP server`.

> ☛ *It is recommended to have one `.js` configuration script per device by following the pattern `<MAC>`.js.*

6.4 Appendix: Check Azure AD User Principal Name

To get the only suitable name for your resource, your have to use the *User principal name* of your resource.

Connect to the `Microsoft Azure` portal with your Administrator login credentials then open the `Users` menu on the left.



Select the appropriate resource to see its *User principal name*.



Get list of Azure AD User Principal Names with Powershell

For the Graph module of Azure Active Directory PowerShell, you must use PowerShell version 5.1.

```
PS C:\WINDOWS\system32> $PSVersionTable

Name                           Value
----                           -----
PSVersion                      5.1.19041.1023
PSEdition                      Desktop
PSCompatibleVersions           {1.0, 2.0, 3.0, 4.0...}
BuildVersion                   10.0.19041.1023
CLRVersion                     4.0.30319.42000
WSManStackVersion              3.0
PSRemotingProtocolVersion      2.3
SerializationVersion           1.1.0.1
```

These procedures are intended for users who are members of a `Microsoft 365` administrator role group.

Open an elevated *MS-Windows PowerShell* command prompt window running *MS-Windows PowerShell* as an administrator.

```
PS C:\WINDOWS\system32> Install-Module -Name AzureAD
```

By default, the *PowerShell Gallery* (*PSGallery*) is not configured as a trusted repository for *PowerShellGet*. The first time you use the *PSGallery*, you will see the following message:

```
Untrusted repository

You are installing the modules from an untrusted repository. If you trust this repository, change
its InstallationPolicy value by running the `Set-PSRepository` cmdlet.

Are you sure you want to install the modules from 'PSGallery'?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help (default is "N"):
```

Type [A] for *Yes to All*.

```
PS C:\WINDOWS\system32> Connect-AzureAD
```

Once connected, you can use the cmdlets of *Azure Active Directory* PowerShell module for Graph.

```
PS C:\WINDOWS\system32> Get-AzureADUser

ObjectId                             DisplayName           UserPrincipalName                 UserType
--------                             -----------           -----------------                 --------
bb1ff602-943c-42dc-a890-45caf0504afa DEMO 01               demo01@innesrd.onmicrosoft.com    Member
bb1ff602-943c-42dc-a890-45caf0504afb DEMO 02               demo02@innesrd.onmicrosoft.com    Member
bb1ff602-943c-42dc-a890-45caf0504afc DEMO 03               demo03@innesrd.onmicrosoft.com    Member
bb1ff602-943c-42dc-a890-45caf0504afd DEMO 04               demo04@innesrd.onmicrosoft.com    Member
```

Get the resource user principal name from a resource email alias

Some organization use a resource email `alias` instead of using the resource user principal name, to avoid to use very long resource email values. The resource email alias is not supported in SBL10e device. To know the user principal name of a resource email value, type the cmdlet with the syntax below:

`Get-Mailbox -Identity <resource_email_address> | Format-List UserPrincipalName`

Example

```
PS C:\WINDOWS\system32> Get-Mailbox -Identity demo01_alias@innes.com | Format-List UserPrincipalName

UserPrincipalName: demo01@innesrd.onmicrosoft.com
```

6.5 Appendix: Create M365 application with Powershell

Download the `Powershell_Innes_AAD-1.10.18.zip` from the Innes Site Web then follow the instructions below.

Introduction

This set of *Powershell* functions allows to:

- create an *Azure Active Directory* application, with the `New-AADApplication` function,
- remove an *Azure Active Directory* application, with the `Remove-AADApplication` function.

These functions are defined in the `PSAAD` PowerShell module stored in the `Modules\PSAAD\` directory.

The result of the *Powershell* functions is also stored in a JSON file.

Edit the file and store preciously the values which could be required for your application:

- the `clientId` value,
- the `tenantId` value,
- the `clientSecret` value.

Security

By default, the execution of local *Powershell* scripts are not allowed. You can change their execution rights by changing the *PowerShell* security policy. This modification has to be done once with the `Set-ExecutionPolicy` *Powershell* function. Your organization may have to change it according to your security rules.

For example, to authorize the execution of all scripts, launch a *Powershell* console with administrator rights, and type:

```
PS > Set-ExecutionPolicy -ExecutionPolicy Unrestricted -scope CurrentUser
```

For further information, look at the cmdlet `Set-ExecutionPolicy` help page.

If you cannot allow the execution of unsigned local scripts, you can install the provided certificate in the list of authorized root certificates with the command:

```
PS > cd <your_path_to_the_scripts>\Powershell_Innes_AAD\Certificate\
PS > Import-PfxCertificate -FilePath InnesCodeSigningRootCA_1.pfx -CertStoreLocation ../..
cert:\CurrentUser\Root -Password $(ConvertTo-SecureString "1234" -AsPlainText -Force)
```

To import the .pfx certificate, you can also use the MS-Windows application `certmgr.msc`, select the `Trusted Root Certification Authorities`, right click on `All Tasks`, select the `Import` item, select the file and enter the password `1234`. When ended, close the current Powershell console.

Prerequisite

Install the Azure AD module

Install the *AzureAD* module with the command below:

```
PS > Install-Module -name AzureAD -scope CurrentUser
```

Dependency

If this message is prompted, enter `Y`.

```
The NuGet supplier is required to continue
PowerShellGet requires the NuGet vendor, version 2.8.5.201 or later, to interact with the repositories.
The NuGet provider must be available in "C:\Program Files\PackageManagement\ProviderAssemblies" or ../..
"C:\Users\<username>\AppData\Local\PackageManagement\ProviderAssemblies".
You can also install the provider NuGet by executing the command "Install-PackageProvider -Name NuGet ../..
-MinimumVersion 2.8.5.201 -Force". Do you want that PowerShellGet installs and imports the NuGet provider now?
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"):
```

If this message is prompted, enter `Y`.

```
Unapproved repository
You install the modules from an unapproved repository. If you approve this repository, change its ../..
InstallationPolicy value by running the Set-PSRepository command applet. Do you really want to install From PSGallery ?
[Y] Yes [T] Yes for all [N] No [U] No for all [S] Suspend [?] Help (default is "N"):
```

Usage

To use one of the *Powershell* modules, you have to define the environment variable for PSAAD. You have 3 possibilities:

1. Either copy the directories under `Modules\` into a standard *Powershell* module installation directory, for example `C:\Program Files\WindowsPowerShell\Modules`. Then launch a *Powershell* console.
2. Or redefine the search variable for *Powershell* modules (the `$Env:PSModulePath` *Powershell* variable) each time you will use theses functions. In this case, launch a *Powershell* console, and type the line below, adapting it to your path. Each time you launch a new *Powershell* console, you need to enter it again.

Example:

```
PS > $Env:PSModulePath="$Env:PSModulePath;C:\Program Files (x86)\WindowsPowerShell\Modules"
```

3. Or redefine the search variable for *Powershell* modules in the Windows environment variables. For that, add the path `<your_path_to_the_scripts>\Powershell_Innes_AAD\Modules` to the environment variable `PSModulePath`. Then, launch afterwards a *Powershell* console.

To use the functions or get help, you must then import the module(s) with the `Import-Module` function. Example:

```
PS > Import-Module PSAAD
```

Depending on how you get the scripts, you may have this following warning:

```
Security Warning Run only scripts that you trust. While scripts from the Internet can be useful, ../..
this script can potentially harm your computer. Do you want to run \server\scripts\my.ps1? ../..
[D] Do not run [R] Run once [S] Suspend [?] Help (default is "D"):
```

To avoid this message, you can unblock the script files (to do only once):

```
PS > cd <your_path_to_the_scripts>\Powershell_Innes_AAD\
PS > dir -Recurse | Unblock-File
```

The `Get-Command` function allows you to list the functions defined in a module. Example:

```
PS > Get-Command -Module PSAAD
```

Answer example:

```
CommandType     Name                       Version    Source
-----------     ----                       -------    ------
Function        New-AADApplication         1.10.18    PSAAD
Function        Remove-AADApplication      1.10.18    PSAAD
```

You can get help on each function of the module by using the standard cmdlet `Get-Help` with options:

- `-detailed`,
- `-full`,
- `-examples`.

Example:

```
PS > Get-Help -detailed New-AADApplication
```

```
NAME
    New-AADApplication

SYNOPSIS
    This function creates a Azure Active Directory application.


SYNTAX
    New-AADApplication [[-Credential] <PSCredential>] [[-tenantId] <String>] [-appName] <String> [-authorizations]
    <String[]> [[-LogFile] <String>] [[-PublicClient] <Boolean>] [[-multiTenants] <Boolean>] [<CommonParameters>]


DESCRIPTION
    This function creates a Azure Active Directory application.


PARAMETERS
    -Credential <PSCredential>
        Credential (admin profile) used to create the Azure Active Directory application. If absent, a dialog is
        displayed in the browser to enter the credentials.

    -tenantId <String>
        Azure Active Directory Tenant Id of the tenant in which the application has been created. This parameter is
        not mandatory. If absent, the tenantId is retrieved automatically after the credentials have been entered in
        the dialog.

    -appName <String>
        Name of the Azure Active Directory application.

    -authorizations <String[]>
        Authorization type:
        - "signcom_m365" : to access to M365 files and folders resources and Web sites for SignCom application
        - "url_launcher_m365" : to access to M365 Web sites for URL launcher application
        - "signmeeting_ews": to access to MS-Exchange room mailbox resources for SignMeeting MS-Exchange application
        - "signmeeting_m365": to access to M365 room mailbox resources for SignMeeting-M365 application
        - "briva_calendar_ews": to access to MS-Exchange room mailbox resources for Briva Calendar EWS application
        - "m365_room": to access to M365 room mailbox resource for SBL10e m365_room application
        - "m365_user": to access to M365 user presence resource for SBL10e m365_user application
        - "powerbi": to access to Power BI report and Power BI dashboards

    -LogFile <String>
        Log file path

    -PublicClient <Boolean>
        The application is a public client (false by default).
        In this mode, it is possible to obtain a user type connection with the pair (susername, password) only
        (without secret client).
        But then the application type premissions and the secret client are no longer generated; it is then no longer
        possible to connect in application mode.
        Only autorization types "signcom_m365", "url_launcher_m365", "m365_user" and "powerbi"  are allowed for a
        public client.

    -multiTenants <Boolean>

    <CommonParameters>
        This cmdlet supports the common parameters: Verbose, Debug,
        ErrorAction, ErrorVariable, WarningAction, WarningVariable,
        OutBuffer, PipelineVariable, and OutVariable. For more information, see
        about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

    -------------------------- EXAMPLE 1 --------------------------

    PS C:\>$result = New-AADApplication -appname "SignMeeting"  -authorizations "signmeeting_ews"

    A consent request will be sent in 30 seconds in your browser.
    You must log into an administrator account of your organization and grant the necessary permissions.
    PS C:\>$result
    Name                           Value
    ----                           -----
    clientId                       xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
    objectId                       xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
    spId                           xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
    name                           SignMeeting
    tenantId                       xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
    clientSecret                   xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx

REMARKS
    To see the examples, type: "get-help New-AADApplication -examples".
    For more information, type: "get-help New-AADApplication -detailed".
    For technical information, type: "get-help New-AADApplication -full".
```

Create an Azure Active Directory application for SBL10e

For example, to create a *SBL10e-M365user (free text) Azure AD application for* `m365_user` *, generate the client Id, the tenant Id and the client secret and store temporarily these values in the sbl10em365_user* variable:

```
PS > $sbl10e_m365_user2 = New-AADApplication -appname "SBL10e-M365_user2"  -authorizations "m365_user"
```

> ☛ *Don't use an already existing appname else an error is returned.*
>
> ☛ *Don't use space characters in appname else an error is returned.*
>
> ⚠ Clicking on a Powershell window can suspend the command. In this case click again in the window to resume the command.

A login popup is displayed. Enter once your M365 login credentials.

This message is then displayed in a *Powershell* context.

```
You must log into an administrator account of your organization and grant the necessary permissions.
A consent request will be sent within 30 seconds in your browser.
```

After 30 seconds, a login popup should be prompted (https://login.microsoftonline.com/) automatically in your default Web browser.

Enter again your M365 login credentials.

A new popup message with the *Permission requested, review for your organization* title is prompted in your Web browser. Press on the `Accept` button. Then a message is displayed in your Web browser showing that the consent is successful: *Success of the consent request.*

You can view the data of the created application by typing the following syntax

> ⚠ The following variable name is the same as the one you have used in the previous command above.

For example, to display the result of the previous command allowing to watch the *client Id*, the *tenant Id* and the *client secret* values:

```
PS > $sbl10e_m365_user
Name                           Value
----                           -----
clientId                       xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
objectId                       xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
spId                           xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
name                           SBL10e-M365_user
tenantId                       xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx
clientSecret                   xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
```

The result of the *Powershell* function is also stored in a JSON file (in the example: `SBL10e-M365_user.json`).

Edit the file and store preciously the values required for your application:

- the `clientId` value,
- the `tenantId` value,
- the `clientSecret` value.

Example to delete an Azure Active Directory application

```
PS > Remove-AADApplication -appname "SBL10e-M365_user"
```

A login popup is opened. Enter your M365 credentials.

In case the values do not allow SBL10e m365_room to work properly, check in `Microsoft Azure` portal that the application has been created succesfully and the rights are properly granted. If not, wait for a while, the rights granting may take few hours.

6.6 Appendix: Create M365 application with Azure AD portal

You can create your `Azure Active Directory` (or `Azure AD`) application by following this Microsoft tutorial https://docs.microsoft.com/en-us/graph/auth-register-app-v2.

A procedure example is shown here after by connecting to the *Microsoft Azure* portal.

This procedure allows to generate you own ID and SECRET required in SBL10e configuration pane. To support `Microsoft 365`:

- `Application (client) ID`,
- `Directory (Tenant) ID`,
- `Client secret`.

Connect on Microsoft Azure portal: https://portal.azure.com/ and sign in with your `Microsoft 365` (`M365`) administrator account login credentials. Click on the left top menu and choose the *Azure Active Directory* item.





Application (client) ID and directory (Tenant) ID

On the App registrations menu, click on *New registration*.



Enter an application name (e.g.: *SBL10e-M365-user*), Select the appropriate Account in the organization directory only (organization only – Single tenant) radio button, and press on the `Register` button.



In the `Overview` menu, copy to clipboard the `Application (client) ID` value, the 1st value required in SBL10e configuration tab and store it preciously.



In the `Overview` menu, copy to clipboard the Directory (tenant) ID value, the 2nd value required in SBL10e configuration tab and store it preciously.



Client secret

In the `Certificates & secrets` menu, click on the `New client secret` button.



Enter a name (e.g.: `my_client_secret`) and press on the `Add` button.



Copy into clipboard the `client secret` value, the 3rd input for the SBL10e configuration tab and store it preciously.

> ⚠ Do it right now because the *client secret* value is not visible anymore as soon as you click on a new Web page.


Microsoft Azure
Search resources, services, and docs (G+/)
frederic.inizan@innes.fr
INNES (INNES.FR)
Home > | App registrations > SBL10e-M365-user
SBL10e-M365-user | Certificates & secrets
Search
Overview
Quickstart
Integration assistant
Manage
Branding & properties
Authentication
Certificates & secrets
Token configuration
API permissions
Expose an API
App roles
Owners
Roles and administrators
Manifest
Support + Troubleshooting
Got feedback?
Got a second to give us some feedback?
Credentials enable confidential applications to identify themselves to the authentication service when receiving tokens at a web addressable location (using an HTTPS scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.
Application registration certificates, secrets and federated credentials can be found in the tabs below.
Certificates (0)
Client secrets (1)
Federated credentials (0)
A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.
New client secret
Description
Expires
Value
Copy to clipboard
t ID
my_client_secret
8/12/2024
AVa8Q~Cv0k1WURaV_f_Zn2H9K3V-RYK...
db24669f-ba5d-4240-9f40-ad86d7113d...

Grant permissions

In the API permissions menu, press on the `Add` a permission button.

For the `m365_user` application, these permissions must be granted:

- `Directory.AccessAsUser.All`,
- `Presence.Read.All`,
- `User.Read`.



Click on the `Microsoft graph` button.



Select then the `Application permissions` button.



In the display filter input, enter the text *Directory.AccessAsUser* and check the option `Directory.AccessAsUser.All`.

> ☛ *Do not press now on the `Add permissions` button right now.*



In the display filter input, enter the text *Presence.Read* and scroll to the bottom to find the *Presence.Read.All* entry and check it.



Click on the `Add permissions` button.

At this step, the permissions are not yet granted.



Click on the `Grant admin consent` for `<your_organization>` button then click on *Yes* button.



Now the permissions are granted.



6.7 Appendix: Create a delegate account

To control the `MS Teams` availability of your employee, you must create a delegate account whose password will persist in the configuration Web user interface of the SBL10e device.



6.8 Appendix: Microsoft Teams status

These are the different availability status labels (Feb. 2024) of `Microsoft Teams` :

- *Available*,
- *Busy*,
- *Do not disturb*,
- *Be right back*,
- *Appear away*,
- *Appear offline*.