

# Termination of Injective DPO Graph Rewriting Systems using Subgraph Counting

Qi QIU

Supervisor: Xavier URBAIN  
Universite Claude Bernard Lyon 1, France  
Univ. Grenoble Alpes, France

# Double-pushout (DPO) rewriting with injective rules and matches

- ▶ Graph : finite edge-labeled directed multigraph
- ▶ Rules  $\varphi = (L \xleftarrow{l} K \xrightarrow{r} R)$  consist of two **inclusions**  $l$  and  $r$ .
- ▶ Rule  $\varphi' = (L' \xleftarrow{l'} K' \xrightarrow{r'} R')$  and  $\varphi$  are **equivalent** if there are **isomorphisms**  $a, b, c$  such that:

$$\begin{array}{ccccc} L' & \xleftarrow{l'} & K' & \xrightarrow{r'} & R' \\ \downarrow a & & \downarrow b & & \downarrow c \\ L & \xleftarrow{l} & K & \xrightarrow{r} & R \end{array}$$

- ▶ Rewriting steps  $G \Rightarrow_{\varphi} H$  are double-pushouts

$$\begin{array}{ccccc} L' & \xleftarrow{l'} & K' & \xrightarrow{r'} & R' \\ \downarrow & & \downarrow & & \downarrow \\ G & \xleftarrow{\quad} & C & \xrightarrow{\quad} & H \end{array}$$

where **all arrows are inclusions**.

## Termination <sup>2</sup>

- ▶  $\mathcal{R}$  : set of DPO graph rewriting rules
- ▶ impossibility of transforming any graph  $G_0$  indefinitely

$$G_0 \Rightarrow_{\mathcal{R}} G_1 \Rightarrow_{\mathcal{R}} G_2 \Rightarrow_{\mathcal{R}} \dots$$

with the non-deterministic strategy

“apply rules as long as possible”

- ▶ Corresponds to program termination on all inputs in conventional programming languages
- ▶ Undecidable in general<sup>1</sup>


---

<sup>1</sup>Plu98.


<sup>2</sup>this slide is from the slides of a presentation given by Plump

# One-rule examples


Rule  $a$  :



Looping:




Rule  $b$ :



**Terminating:** the number of edges labeled by “a” strictly decreases.

# Visualization of injective graph morphism


Visualization of an injective graph morphism:



- ▶ Graphs are contained in boxes
- ▶ Graph name is placed in the top left corner
- ▶ Domain is represented as a subgraph of codomain
- ▶ Some nodes are numbered for identification
- ▶ Morphism name is placed in between the boxes.

# Termination by Subgraph Counting

- ▶ Motivating rule  $\varphi$ :




- ▶ Termination by strict decrease of the number of occurrences of  $\bullet \xrightarrow{s} \bullet \xleftarrow{s} \bullet$
- ▶ Can we prove its termination by a machine-checkable condition?

# Plan

- ▶ Pre-graphs
- ▶ Analysis of subgraph change before and after rewriting
- ▶ Sufficient conditions for termination by subgraph counting

# Pre-graphs




- ▶ Pre-graphs are graphs with missing nodes and dangling edges.
- ▶ Example:








# Pre-graph operations

**Union**  $C \cup R$  of two pre-graphs  $C \subseteq G$  and  $R \subseteq G$



**Relative complement** of  $R$  in  $H$  where  $R \subseteq H$ , denoted  $H \setminus R$ :




# Running example

We will use the following running example to analyze the subgraph changes before and after a rewriting step.




It replaces chain  $\bullet \xrightarrow{a} \bullet \xrightarrow{a} \bullet$  with  $\bullet \xrightarrow{a} \bullet \xrightarrow{b} \bullet \xrightarrow{a} \bullet$ .

# Analysis of rewriting steps





All arrows are inclusions by definition.

Graphs can be decomposed as unions of pre-graphs:




# Example



# Implicit, Explicit and Shared Occurrences

An **X-occurrence** in a graph  $G$  is a **subgraph** of  $G$  isomorphic to  $X$ .



$X$  : a subgraph of  $L$

$X$ -occurrence in  $G$  is


- **shared** if included in  $C$
- **explicit** if included in  $L$
- **implicit** if having elements in both  $C'$  and  $L'$

$X$ -occurrence in  $H$  is

- **shared** if included in  $C$
- **explicit** if included in  $R$
- **implicit** if having elements in both  $C'$  and  $R'$

## Example

Consider the occurrences of the graph  $\bullet \xrightarrow{a} \bullet \xrightarrow{a} \bullet$  in



- ▶ Occurrence shared by  $G$  and  $H$ : 2-6-7
- ▶ Explicit occurrence in  $G$ : 1-3-2
- ▶ Implicit occurrences in  $G$ : 3-2-6
- ▶ 0 explicit occurrence in  $H$
- ▶ Implicit occurrences in  $H$ : 5-2-6

# $X$ -occurrences in a graph $G$

Remark:

$$\begin{aligned} |X\text{-occurrences}| = & | \text{explicit } X\text{-occurrences} | + \\ & | \text{shared } X\text{-occurrences} | + \\ & | \text{implicit } X\text{-occurrences} | \end{aligned}$$

Shared  $X$ -occurrences in  $G$  and  $H$  are the same.

# Termination of a graph rewriting rule $\varphi$

- ▶  $\varphi$  : rewriting rule
- ▶  $X$ : a subgraph of the left-hand side graph of  $\varphi$
- ▶  $\varphi$  terminates if for all  $G \Rightarrow_{\varphi} H$ , the number of  $X$ -occurrences strictly decreases.
- ▶  $\varphi$  terminates if for all  $G \Rightarrow_{\varphi} H$ ,

$$\begin{aligned} & (|\text{explicit } X\text{-occurrences in } G| - |\text{explicit } X\text{-occurrences in } H|) + \\ & (|\text{implicit } X\text{-occurrences in } G| - |\text{implicit } X\text{-occurrences in } H|) \\ & > 0 \end{aligned}$$

- ▶  $\varphi$  terminates if for all  $G \Rightarrow_{\varphi} H$ ,

$$\begin{aligned} & |\text{explicit } X\text{-occurrences in } G| > |\text{explicit } X\text{-occurrences in } H| \\ & |\text{implicit } X\text{-occurrences in } G| \geq |\text{implicit } X\text{-occurrences in } H| \end{aligned}$$




# Termination of a graph rewriting rule

The first condition

$$|\text{explicit } X\text{-occurrences in } G| > |\text{explicit } X\text{-occurrences in } H|$$

is equivalent to

$$|X\text{-occurrences in } L| > |X\text{-occurrences in } R|$$



Therefore, the key challenge is to show


$$|\text{implicit } X\text{-occurrences in } G| \geq |\text{implicit } X\text{-occurrences in } H|$$

for all rewriting steps  $G \Rightarrow_{\varphi} H$ .


We construct an injection from the implicit  $X$ -occurrences in  $H$  to the implicit  $X$ -occurrences in  $G$ .

# Analysis of Implicit Occurrences

Consider the implicit occurrence of  $\bullet \xrightarrow{a} \bullet \xrightarrow{a} \bullet$  in  $H$ :




The occurrence is  $C' \cup R'$ .  $C'$  is shared by  $G$  and  $H$ .  $R'$  is not in  $G$  but there  $L'$  is in  $G$  and  $C' \cup L'$  is an implicit occurrence in  $G$ .




Distinguished Subgraph  $D(R, X)$  : subgraphs of  $R$  which can form an implicit  $X$ -occurrence in some rewriting step


Running example:



$D(R, X)$  consists of :



Observation: For every  $R_i \in D(R, X)$ , there is a morphism  $h_i : R_i \rightarrowtail L$  which preserves the interface elements



# $X$ -non-increasing rule

## Definition

A rule  $\varphi$  is  $X$ -non-increasing rule if

1. For every  $R_i \in D(R, X)$ , there is a morphism  $h_i : R_i \rightarrowtail L$  which preserves the interface elements,
2. three more conditions on  $h_i$

**Condition 1** guarantees every implicit  $X$ -occurrence in  $H$  has a corresponding implicit  $X$ -occurrence in  $G$  with the same interface elements

**Other conditions** guarantee: different implicit  $X$ -occurrences in  $H$  have different corresponding implicit  $X$ -occurrences in  $G$

# Main Results

Let  $\varphi$  be a  $X$ -non-increasing rule.


**Lemma (More  $X$ -occurrences before rewriting)**

*For all  $G \Rightarrow_{\varphi} H$ , there are more implicit  $X$ -occurrences in  $G$  than in  $H$ .*

**Theorem (Sufficient Termination Condition)**

*$\varphi$  is terminating if there are strictly more explicit  $X$ -occurrences in  $L$  than in  $R$ .*


# Terminating of Running Example



- ▶  $X : \bullet \xrightarrow{a} \bullet \xrightarrow{a} \bullet$
- ▶  $X$ -non-increasing rule
- ▶ Strictly more explicit  $X$ -occurrences in  $L$  than in  $R$ :  $1 > 0$ .



# Termination of Motivating Rule




- ▶  $X : \bullet \xrightarrow{s} \bullet \xleftarrow{s} \bullet$
- ▶  $D(R, X)$  consists of  $R_1: (1 \xrightarrow{s} 3)$  and  $R_2: (1 \xrightarrow{s} 3) (2)$
- ▶  $X$ -non-increasing rule because inclusions from  $h_1 : R_1 \rightarrowtail L$  and  $h_2 : R_2 \rightarrowtail L$  satisfy all conditions.
- ▶ Strictly more explicit  $X$ -occurrences in  $L$  than in  $R : 1 > 0$
- ▶ Terminating
- ▶ Its termination can only be shown using our technique.

# Relative work

- ▶ Termination of PBPO+ rewriting using weighted subgraph counting [OE24]
  - ▶ same idea
  - ▶ more general
  - ▶ cannot prove termination of the motivating rule
- ▶ Forward Closure Method [Plu95]
  - ▶ proves termination of the motivating rule
  - ▶ not easy to apply: necessary and sufficient termination condition
- ▶ Termination of rewriting systems using weighted type graphs [ZKB14; BKZ14; Bru+15; EO24; Qiu25]
  - ▶ more general
  - ▶ cannot prove termination of the motivating rule
- ▶ Modular Termination Method [Plu18]
  - ▶ termination of the union of two rule sets
  - ▶ our method complements this method

# An extension for counting subgraphs with antipattern

An extension has been developed and implemented for termination of the following rule:



by counting  $L$ -occurrences which are not included in  $R$ -occurrences.

# Future Work

- ▶ Extension to rules with negative application conditions

# Conclusion

## Subgraph Counting method

- ▶ machine-checkable sufficient termination condition
- ▶ for injective DPO graph rewriting
- ▶ by counting occurrences of a subgraph  $X$
- ▶ implemented in **LyonParallel**<sup>3</sup>

---

<sup>3</sup>[github.com/Qi-tchi/LyonParallel/tree/icgt2025](https://github.com/Qi-tchi/LyonParallel/tree/icgt2025), MIT License

# Acknowledgements

- ▶ Thanks to reviewers for their valuable comments and suggestions.
- ▶ Termination section uses a slide from a presentation by Plump in 2018.

# References I

- [BKZ14] H. J. Sander Bruggink, Barbara König, and Hans Zantema. “Termination Analysis for Graph Transformation Systems”. In: *Theoretical Computer Science - 8th IFIP TC 1/WG 2.2 International Conference, TCS 2014, Rome, Italy, September 1-3, 2014. Proceedings*. Ed. by Josep Diaz, Ivan Lanese, and Davide Sangiorgi. Vol. 8705. Lecture Notes in Computer Science. Springer, 2014, pp. 179–194. DOI: [10.1007/978-3-662-44602-7\\_15](https://doi.org/10.1007/978-3-662-44602-7_15).
- [Bru+15] H. J. Sander Bruggink et al. “Proving Termination of Graph Transformation Systems using Weighted Type Graphs over Semirings”. In: *CoRR abs/1505.01695* (2015). arXiv: [1505.01695](https://arxiv.org/abs/1505.01695).

# References II

- [EO24] J. Endrullis and R. Overbeek. *Generalized Weighted Type Graphs for Termination of Graph Transformation Systems*. 2024. arXiv: 2307.07601v2 [cs.LG].
- [OE24] Roy Overbeek and Jorg Endrullis. “Termination of Graph Transformation Systems Using Weighted Subgraph Counting”. In: *Logical Methods in Computer Science* Volume 20, Issue 4, 12 (Nov. 2024). ISSN: 1860-5974. DOI: 10.46298/lmcs-20(4:12)2024.



# References III

- [Plu18] Detlef Plump. “Modular Termination of Graph Transformation”. In: *Graph Transformation, Specifications, and Nets - In Memory of Hartmut Ehrig*. Ed. by Reiko Heckel and Gabriele Taentzer. Vol. 10800. Lecture Notes in Computer Science. Springer, 2018, pp. 231–244. DOI: 10.1007/978-3-319-75396-6\_13.
- [Plu95] Detlef Plump. “On Termination of Graph Rewriting”. In: *Graph-Theoretic Concepts in Computer Science, 21st International Workshop, WG '95, Aachen, Germany, June 20-22, 1995, Proceedings*. Ed. by Manfred Nagl. Vol. 1017. Lecture Notes in Computer Science. Springer, 1995, pp. 88–100. DOI: 10.1007/3-540-60618-1\_68.

# References IV

- [Plu98] Detlef Plump. “Termination of Graph Rewriting is Undecidable”. In: *Fundam. Informaticae* 33.2 (1998), pp. 201–209. DOI: 10.3233/FI-1998-33204.
- [Qiu25] Qi Qiu. *Termination of Graph Rewriting using Weighted Type Graphs over Non-well-founded Semirings*. Tech. rep. Universite Claude Bernard Lyon 1 (UCBL), Lyon, FRA., Feb. 2025. URL: <https://hal.science/hal-04954960v2>.

# References V

- [ZKB14] Hans Zantema, Barbara König, and H. J. Sander Bruggink. “Termination of Cycle Rewriting”. In: *Rewriting and Typed Lambda Calculi - Joint International Conference, RTA-TLCA 2014, Held as Part of the Vienna Summer of Logic, VSL 2014, Vienna, Austria, July 14-17, 2014. Proceedings*. Ed. by Gilles Dowek. Vol. 8560. Lecture Notes in Computer Science. Springer, 2014, pp. 476–490. DOI: 10.1007/978-3-319-08918-8\_33.