Lecture 9 Dimensional Analysis Mathematical Modeling

Prof. Dr. Jingzhi Li

Department of Mathematics, Southern University of Science and Technology

2025 Spring



- 1 Focus in this lecture on modeling of some physical processes
- 2 Dimensional Analysis
- 3 Using similitude and prototyping an example

- 1 Focus in this lecture on modeling of some physical processes
- ② Dimensional Analysis
- Using similitude and prototyping an example

Background

- Explored so far mostly hypothesis-driven and data-driven modeling
 - In the former case, we know the main interactions and test how well they fit the data
 - Focus on how much the hypothesis can explain the data
 - Mostly a problem of model fitting
 - In the later case, we only have data and are willing to accept any (reasonable) model confirming them
 - Interested in describing the trends of the data
 - Often a problem of interpolation

- Discuss here a different approach to modeling, based on dimensional analysis
 - In this case we know the main variables important for the model
 - We know their units of measure (or dimension)
 - We do not know their interactions
 - We do not have the data at the moment when we build the model
 - We have in this case a problem of model identification

- 1 Focus in this lecture on modeling of some physical processes
- ② Dimensional Analysis
- Using similitude and prototyping an example

Dimensional Analysis –Basics

- It is a method for determining how the selected variables are related
- Important also in reducing significantly the amount of experimental data needed later on for fitting the model
- Main ideas in dimensional analysis:
 - Physical quantities have dimensions
 - Physical laws are not altered by changing the units measuring dimensions
 - Any equation must be expressed in the same dimension on both sides of the equality (equations must be dimensionally correct)


Department of Mathematics. Southern University of Science and Technology

Example: a simple pendulum

- Problem: for a given pendulum, determine its period
 - the time required for the pendulum bob to swing through one complete cycle and return to its initial position

Assumptions

- Identify the factors influencing the period:
 - the length r
 - the acceleration due to gravity g
 - the mass m
 - the initial angle heta
 - frictional forces
 - the drag on the pendulum
- For simplicity, assume that the hinge is frictionless, the drag force is negligible, and the mass of the pendulum is concentrated at one end of the pendulum



Example: a simple pendulum

- Problem formulation: determine/approximate the function $t = f(r, m, \theta, g)$
- Data-driven approach
 - Gravity is constant
 - t only depends on r, m, θ
 - Collect enough data on the value of t depending on various values of r, m, θ
 - Question: how many experiments are needed?
 - Assume that N points are to be considered for each variable
 - Then we need 3^N experiments
 - Clear need to reduce the number of independent variables as much as possible
 - In fact, minimize the number of independent variables in function f

About dimensions

Some elementary concepts in physics:

- mass, length, time, velocity, acceleration, force, energy, work, pressure
- For each such concept there is a unit of measurement
- For a physical law, e.g., F = ma, to make sense, the units of measurement on both sides of the equality have to be consistent
 - If the mass is measured in kilograms and the acceleration in meters per second squared, then the force must be measured in newtons: the MKS (meter-kilogram-second) system
 - It would be inconsistent with the equation F = ma to measure mass in slugs, acceleration in feet per second squared, and force in newtons
 - It would become consistent if force were expressed in pounds: the American Engineering System of measurement

About dimensions

- The three main physical quantities we consider in this lecture are mass, length, and time
 - Associate with these quantities the (generic) dimensions M, L, and T, respectively
 - We do not specify which unit of measurement to use for each
 - The dimension of other quantities with respect to M, L, T follow from basic laws of physics
 - Numerical (dimensionless) constants may be involved in defining some more complex quantities; they are ignored in finding the dimension of that concept
 - There are also dimensional variables that in our application may be considered a constant, such as the gravity - for them we need to consider their dimensions

About dimensions

- More complex entities, such as momentum or kinetic energy, may be defined as products of simpler entities, which in turn are products of M, L, T)
- Each product will get a dimension associated to it, in terms of a product $M^nL^pT^q$
 - Dimensionless quantities: n = p = q = 0

Table 14.1 Dimensions of physical entities in the MLT system

| Mass | M | Momentum | MLT^{-1} |
|----------------------|-----------------|--------------------|-----------------|
| Length | L | Work | ML^2T^{-2} |
| Time | T | Density | ML^{-3} |
| Velocity | LT^{-1} | Viscosity | $ML^{-1}T^{-1}$ |
| Acceleration | LT^{-2} | Pressure | $ML^{-1}T^{-2}$ |
| Specific weight | $ML^{-2}T^{-2}$ | Surface tension | MT^{-2} |
| Force | MLT^{-2} | Power | $ML^{2}T^{-3}$ |
| Frequency | T^{-1} | Rotational inertia | ML^2 |
| Angular velocity | T^{-1} | Torque | ML^2T^{-2} |
| Angular acceleration | T^{-2} | Entropy | $ML^{2}T^{-2}$ |
| Angular momentum | ML^2T^{-1} | Heat | $ML^{2}T^{-2}$ |
| Energy | ML^2T^{-2} | | |
| | | | |

Dimensions

Dimensionally compatible sums

- All terms in a sum must have compatible dimensions
- Example: $F = mv + v^2$ must be incorrect: mv has dimension MLT^{-1} , whereas v^2 has dimension L^2T^{-2}

Dimensional homogeneity

- Equations that are true regardless of the system of units for its variables are called dimensionally homogeneous
- Example: the time a body falls a distance s under gravity g, neglecting air resistance:

$$t = \sqrt{\frac{2s}{g}}$$
 is dimensionally homogeneous

$$t=\sqrt{\frac{\mathrm{s}}{16.1}}$$
 is not dimensionally homogeneous

Applying dimensional analysis

- **Main assumption**: the model is given by a dimensionally homogenous equation in terms of the appropriate variables
- **Task**: determine the form of that equation
- **Approach**: find an appropriate **dimensionless** equation and solve it for the dependent variable of interest
 - Choose which are the relevant variables to consider
 - Determine/describe all possible dimensionless products of those variables
 - Use some of these products to construct dimensionally homogeneous equations

Lecture 9 Dimensional Analysis

Another example

Wind force on a van: you are driving a van on a highway with gusty winds

- **Problem**: how does the speed of the van affect the wind force you are experiencing?
- **Assumptions**: the force F of the wind is affected by the speed v of the van and the surface area A of the van directly exposed to the wind's direction
- Hypothesis: the force is proportional to some power of the speed times some power of the surface area:

$$F = kv^a A^b$$

| Variable | F | k | V | Α |
|-----------|------------|-------------|-----------|-------|
| Dimension | MLT^{-2} | $M^0L^0T^0$ | LT^{-1} | L^2 |

• In terms of dimensions:

$$MLT^{-2} = (M^0L^0T^0)(LT^{-1})^a(L^2)^b$$

- But this cannot be correct: M has a zero exponent on the right-hand side
- Conclusion: error in the model formulation
- **Rework the hypothesis**: the strength of the wind is also affected by its density ρ

$$F = kv^a A^b \rho^c$$

Dimensionally: $MLT^{-2} = (M^0L^0T^0)(LT^{-1})^a(L^2)^b(ML^{-3})^c$

Dimensionally:

$$MLT^{-2} = (M^0L^0T^0)(LT^{-1})^a(L^2)^b(ML^{-3})^c$$

Equivalent with:

$$c = 1$$
, $a + 2b - 3c = 1$, $-a = -2$

- In other words: a = 2, b = 1, c = 1
- Final model:

$$F = kv^2 A \rho$$

- **Note**: for a particular situation, the density ρ is a constant
 - One might reformulate the model to say that F is proportional to v^2A
 - The reason this model seemed to fail in the beginning of our reasoning is because we assumed the proportionality constant to be dimensionless

Department of Mathematics. Southern University of Science and Technology

Example: simple pendulum revisited

The main variables of interest:

| Variable | m | g | t | r | θ |
|-----------|---|-----------|---|---|-------------|
| Dimension | М | LT^{-2} | Т | L | $M^0L^0T^0$ |

- Find all of their dimensionless products: $m^a g^b t^c r^d \theta^e$
 - Its dimension is $(M)^a(LT^{-2})^b(T)^c(L)^d(M^0L^0T^0)^e$
 - In other words: $M^a L^{b+d} T^{-2b+c}$
 - Dimensionless condition: a = 0, b + d = 0, -2b + c = 0
 - In other words: a = 0, c = 2b, d = -b, where b, e are arbitrary
 - Infinitely many dimensionless products
- Consider here only two of them, for b = 0, e = 1 and for b = 1, e = 0


Department of Mathematics. Southern University of Science and Technology

- Two dimensionless products:
 - b = 0, e = 1: $\Pi_1 = m^0 g^0 t^0 r^0 \theta^1 = \theta$
 - b=1, e=0: $\Pi_2=m^0g^1t^2r^{-1}\theta^0=\frac{gt^2}{r}$
- Any other solution of the linear system on the previous slide is a linear combination of the solutions for (b,e)=(0,1) and for (b,e)=(1,0)
- ullet In other words, any other dimensionless product is of the form $\Pi_1^{ extit{ extit{a}}}\Pi_2^{ extit{ extit{b}}}$
- Recall our main assumption: the solution is given by a dimensionally homogeneous equation in terms of the appropriate variables
 - By rewriting that equation, we get a dimensionless equation
 - But a dimensionless equation can only involve an expression in terms of Π_1 , Π_2
- In other words, a solution to the problem must be of the form $f(\Pi_1, \Pi_2) = 0$, for some (as yet unknown) function f

- $f(\Pi_1, \Pi_2) = 0$, i.e., $f(\theta, gt^2/r) = 0$
 - If we managed to solve this equation in terms of t (invert function f), then the expression we got would be $gt^2/r = \varphi(\theta)$ for some function φ
- Final solution: $t = \sqrt{r/g} \cdot h(\theta)$, for some function $h(\theta) = (\varphi(\theta))^{1/2}$
 - Test the solution: keep g and θ constant, vary r; check the dependency between t and $r^{1/2}$
 - Determine the unknown function h: collect data on t for fixed r and various values of θ, do a data-driven modeling approach

■ Figure 14.4

Testing the assumptions of the simple pendulum model by plotting the period t versus the square root of the length r for constant displacement θ



■ Figure 14.5

Determining the unknown function *h*



The process of dimensional analysis

Recall:

- **Main assumption:** the solution is given by a dimensionally homogenous equation in terms of the appropriate variables
- Task: determine the form of that equation
- Approach: find an appropriate dimensionless equation and solve it for the dependent variable of interest

- Focus on determining the form of all dimensionless products
 - Similarly as in our previous example, this leads to a linear system of equations, where each equation stands for the exponent of one of the basic dimensions you consider (in our examples, M, L, and T)
 - Elementary result in linear algebra: the solution of any linear system of equations is a linear space;
 - Idea: determine its linear basis: a complete, independent set of solutions
 - Each of these "basic" solutions gives a "basic" dimensionless product
 - Any solution of the system of equations is a linear combination of the basic solutions
 - Any dimensionless product is a product of some powers of the basic dimensionless products

The process of dimensional analysis (2)

• Main tool: Buckingham's theorem

Intuition:

- We have a physically meaningful (dimensionally homogenous) equation involving *n* physical variables, and these variables are expressible in terms of k independent fundamental physical quantities
- Then the original equation is equivalent to an equation involving a set of p = n - k dimensionless parameters constructed from the original variables
- This provides a method for computing sets of dimensionless parameters from the given variables, even if the form of the equation is still unknown
- **Note:** the choice of dimensionless parameters is not unique; up to the modeler to choose the most "physically meaningful" such parameters

The process of dimensional analysis (3)

Buckingham's theorem / the pi-theorem (1914):

An equation

$$f(q_1,\ldots,q_n)=0$$

is dimensionally homogeneous, where q_i are physical variables expressed in terms of k independent physical units if and only if the equation can be restated as

$$F(\pi_1,\ldots,\pi_p)=0$$

where π_i are dimensionless parameters constructed from the q_i by n-k equations of the form

$$\pi_j=q_1^{a_1}q_2^{a_2}\ldots q_n^{a_n}$$

where the exponents a_i are integers



Example

Problem: determine the terminal velocity v of a raindrop falling from a motionless cloud

Variables to consider:

- size of the raindrop (say its radius r),
- density ρ of the air,
- viscosity μ of the air (resistance to motion; sort of internal molecular friction)
- gravity g

| Variable | Dimension | | |
|----------|-----------------|--|--|
| V | LT^{-1} | | |
| r | L | | |
| g | LT^{-2} | | |
| ho | ML^{-3} | | |
| μ | $ML^{-1}T^{-1}$ | | |

Department of Mathematics. Southern University of Science and Technology

- By Buckingham's theorem, we are interested in all dimensionless products of powers of these variables: $v^a r^b g^c \rho^d \mu^e$
- Dimensionally: $(LT^{-1})^a(L)^b(LT^{-2})^c(ML^{-3})^d(ML^{-1}T^{-1})^e$ is dimensionless
- Equivalently: d + e = 0: a + b + c 3d = 0: -a 2c e = 0
- Solution: b = 1.5d 0.5a; c = 0.5d 0.5a; e = -d; a. d arbitrary
- Consider the independent solutions obtained for (a, d) = (1, 0), (a, d) = (0, 1)

Department of Mathematics. Southern University of Science and Technology

Lecture 9 Dimensional Analysis

- Basic solutions: $\Pi_1 = vr^{-1/2}g^{-1/2}$, $\Pi_2 = r^3g^{1/2}\rho\mu^{-1}$
- Buckingham's theorem: there is a function f such that

$$f(\textit{vr}^{-1/2}\textit{g}^{-1/2},\textit{r}^{3}\textit{g}^{1/2}\rho\mu^{-1})=0$$

- Assuming we could invert this function, we obtain $vr^{-1/2}g^{-1/2}$ as a function of $r^3g^{1/2}\rho\mu^{-1}$
 - Equivalently:

$$v = \sqrt{rg} \cdot h\left(\frac{r^{3/2}g^{1/2}\rho}{\mu}\right)$$

where h is some (unknown) function

Notes

- The n-k dimensionless products stated in Buckingham's theorem are not unique
 - For the purpose of modeling in the way we showed in the example, it is necessary to choose them in such a way that the dependent variable of interest only occurs in one of the products
 - In that way we can continue our reasoning with the inversion of the (unknown) function in Buckingham's theorem
- We did not discuss here when the function in Buckingham's theorem is invertible
 - Deeper discussion related to the implicit function theorem in advanced calculus

Usefulness of Buckingham's theorem for modeling

- Get information about how the variables are related to each other; in some cases, lead to complete model identification
- Identify incompleteness of a model
- Help in experiment design: if $\pi_1 = h(\pi_2, \pi_3, \dots, \pi_p)$, then design the experiments so that π_3, \dots, π_p are constant to isolate the effect of π_2 on π_1
- Reduce the number of experiments needed to fully identify the model: no need to sample *n* variables x_1, \ldots, x_n , only sample the products π_1, \ldots, π_p where p < n
- Helps in presenting the model in a standard form: choose the dimensionless products to be widely used coefficients in that particular field of study (Reynolds number, Froude number, Mach number, etc)

- Focus in this lecture on modeling of some physical processes
- 2 Dimensional Analysis
- 3 Using similitude and prototyping an example

Using prototypes

- Sometimes it is impossible to study the actual object of interest
 - Example: effects of wave action on a large ship at sea, heat loss of a submarine, wind effects on an aircraft wing
- Solution: construct a scaled-down model (prototype) and simulate the environment
- Problem: how do we scale the experiments to ensure that the
 effects observed on the model are the same as those that will
 take place on the final product?
- Approach here: use dimensional analysis

Example: drag force on a submarine

- Assumptions: the variables affecting the drag D are
 - Fluid velocity v
 - Length of the submarine: r
 - Fluid density ρ
 - Fluid viscosity μ
 - Velocity of sound in the fluid c

Describing the shape factors related to the submarine

- Describing the shape factors related to the submarine
 - **Assumption:** assume the submarine having an ellipsoidal shape; describe it through two ellipses –two cross-sections, one length-wise, the other width-wise
 - Shape factors
 - Length of the submarine (an axis in the length-wise cross-section): r
 - Ratio of the lengths of the two axis in the first cross-section: r_1
 - Ratio of the lengths of the two axis in the second cross-section: ro
- **In general:** collect enough shape factors to be able to describe in enough details the 3D shape of the object of interest

Dimensional analysis

- We are highly interested in the drag D –the pressure (force per unit area) times the area
 - ullet For geometrically similar objects, the area is proportional to r^2
 - So D is proportional to pr^2
- We have six fluid mechanics variables: D, v, r, ρ, μ, c
- We have two other dimensionless (shape) factors: r_1, r_2
- The MLT-based dimensional analysis will give an equation in 6-3=3 dimensional variables and in the 2 dimensionless variables
 - We can choose three independent variables that are widely used in physics
 - For example: Reynolds number $R = \frac{vr\rho}{\mu}$, Mach number $M = \frac{v}{c}$, pressure coefficient $P = \frac{p}{\rho v^2}$

- Buckingham's theorem gives an equation $h(P, M, R, r_1, r_2) = 0$
- Assuming we could solve it for P, we get $P = H(M, R, r_1, r_2)$
- Substitute $P = \frac{p}{\rho v^2}$ and we get $p = \rho v^2 H(M, R, r_1, r_2)$
- Drag force is proportional to pr^2 , i.e. $D = k\rho v^2 r^2 H(M, R, r_1, r_2)$

- Drag force is proportional to pr², i.e. $D = k \rho v^2 r^2 H(M, R, r_1, r_2)$
- A condition of the same form holds both for the model/prototype and for the final object:

$$D_{m} = k \rho_{m} v_{m}^{2} r_{m}^{2} H(M_{m}, R_{m}, r_{1m}, r_{2m})$$

Conclusion: design conditions for the model

- 1 $R_m = R$, i.e. $v_m r_m \rho_m / \mu_m = v r_0 / \mu$
- **2** $M_m = M$, i.e. $v_m/c_m = v/c$
- $r_{1m} = r_1$
- $\frac{d}{d} r_{2m} = r_2$
- In these conditions, $\frac{D_m}{D} = \frac{\rho_m v_m^2 r_m^2}{\rho v^2 r^2}$
 - Compute D_m and then calculate D



Lecture 9 Dimensional Analysis

Discuss the design conditions

- Conditions c and d imply geometric similarity
- If the velocities are small compared to the speed of sound in a fluid, then v/c can be considered constant, as required by condition b
- If the same fluid is used both for the model and the final object, then condition a is satisfied iff $v_m r_m = v r$, i.e. $v_m/v = r/r_m$
 - Setting the velocity of the model in this way yields $D = D_m$

Learning objectives

- Understand the principles of dimensional analysis: physical quantities have dimensions, models should be dimensionally coherent
- Be able to perform dimensional analysis for simple models
- Be able to apply Buckingham's theorem to simple models
- Understand the application of dimensional analysis in the form of similitude analysis

Department of Mathematics. Southern University of Science and Technology