Machine Learning 1

Lecture 1.3 - Types of Machine Learning

Erik Bekkers

(Bishop 1.0 and 1.1)

Slide credits: Rianne van den Berg

Image credit: Kirillm | Getty Images

Machine Learning 1

Lecture 1.3 - Types of Machine Learning

Erik Bekkers

(Bishop 1.0 and 1.1)

Slide credits: Rianne van den Berg

Image credit: Kirillm | Getty Images

$\{x_i\}_{i=1}^N$ $\{x_i\}_{i=1}^N$ $\{t_i\}_{i=1}^N$



"Experience" / data is gathered along the way

Image source : www.techleer.com



Image source : www.techleer.com

Supervised learning



Dataset		
features:	$\{\mathbf{x}_1, \ldots, \mathbf{x}_N\}$	x = x = 0.25
targets:	$\{t_1, \ldots, t_N\}$	t = 2 t = 0.707





discrete

continuous

Supervised learning







Task: Find function f such that $f(\mathbf{x}) \approx t$ for all known and unknown ($\mathbf{x}$, t)

generalization


Meaningful
Compression
Structure
Discovery
Big data
Visualistaion
Dimensionality
Reduction
Feature
Elicitatio
Unsupervised
Learning
Recommender
Systems
Clustering
Targetted
Marketing

Unsupervised learning



100 x 108

Dataset:



...

Task: Compression

why ? Save on disk space

Unsupervised learning

100 x 100 = 10,000

Dataset:

Task: Compress image

Method: Expand along principle components (PCA) ~ Ch 12

Result:

Save M=150 & coefficients

Original

$$\approx \sum_{i=1}^{M} \alpha_i \mu_i$$

M=1



M=10



M=50

M=150



Unsupervised learning

Dataset:



similar



Task: Assign every datapoint to a cluster (hidden class variable)

Result:



Other types of learning

Semi-supervised learning

- data points: $\{x_1, \ldots, x_n\}$
- targets: $\{t_1, \ldots, t_k\}$ (k<n)

- Not all datapoints have a known target/label!
- Use all data, also those with unknown target, to create predictor.

Other types of learning

Reinforcement Learning

- Dynamic environment: provides information on its state.
- Agent: takes actions, receives rewards from environment.
- Task: maximize total reward
- Learning by trial and error
- Application: Games
  Robotics

What is machine learning?



"A computer program is said to learn from experience E with respect to some class of tasks T and performance measure P if its performance at tasks in T, as measured by P, improves with experience E."

- Tom M. Mitchell

Machine Learning, Tom Mitchell, McGraw Hill, 1997