ECE571: Advanced Microprocessor Design – Homework 5
Spring 2016

Due: Thursday 25 February 2016, 3:30pm

Create a document that contains the data and answers described in the sections below. A .pdf or .txt file is preferred but I can accept MS Office or Libreoffice format if necessary.

1. **Cache paramaters**

   A Haswell machine has a 44-bit physical address space, 32-kB L1 data cache, 8-way set associative, 64-bytes per line.

   (a) How many bits are used to calculate the offset?

   (b) How many bits are used to calculate the line?

   (c) How many bits are used for the tag?

2. **Cache problem**

   This question assumes a 512-byte cache, 16-bytes per line, 2-way associative, 32-bit address size. (24 bits of tag, 4 bits for line, 4 bits for offset).

line	V	D	LRU	Tag	V	D	LRU	Tag
			Way 0				Way 1	
0	1	0	1	0000 00	1	0	0	0000 08
1	1	0	0	0000 00	1	1	1	0000 0a
2	0				0			
3	0				0			
4	0				0			
5	0				0			
...								
b	0				0			
c	0				0			
d	0				0			
e	0				0			
f	0				0			

   For each of the following memory accesses state whether it is a cache hit or miss, and if it's a miss state whether the old contents of the cache have to be written back to memory or not.

   (a) `ldrb r0, 0x0000080f`

   (b) `ldrb r0, 0xffffffff`

   (c) `strb r0, 0x00000810`

3. **Bzip2 cache behavior on the x86 Haswell Machine**

   For this section, log into the Haswell machine just like in previous homeworks. Run the bzip2 benchmark, recall you will use a command line something like this:
   ```
   perf stat -e instructions:u,L1-icache-load-misses:u \
   /opt/ece571/401.bzip2/bzip2 -k -f ./input.source
   ```

   (a) Measure and report the L1 instruction cache miss rate.
       Use `instructions:u` and `L1-icache-load-misses:u` for the events.

   (b) Measure and report the L1 data cache load miss rate.
       Use `L1-dcache-loads:u` and `L1-dcache-load-misses:u`

   (c) Measure and report the L3 cache miss rate
       Use `cache-references:u` and `cache-misses:u`

4. **equake_l cache behavior on the x86 Haswell Machine**

   Recall that running equake looks something like this:
   ```
   perf stat -e instructions:u,L1-icache-load-misses:u \
   /opt/ece571/equake_l.specomp/equake_l < \
   /opt/ece571/equake_l.specomp/inp.in
   ```

   (a) Measure and report the L1 instruction cache miss rate.
       Use `instructions:u` and `L1-icache-load-misses:u` for the events.

   (b) Measure and report the L1 data cache load miss rate.
       Use `L1-dcache-loads:u` and `L1-dcache-load-misses:u`

   (c) Measure and report the L1 data cache store miss rate.
       Use `L1-dcache-stores:u` and `L1-dcache-store-misses:u`

   (d) Measure and report the L3 cache miss rate
       Use `cache-references:u` and `cache-misses:u`

5. **Bzip2 cache behavior on the Jetson**

   Now run the bzip2 benchmark on the ARM64 jetson machine. (recall from the last homework, just ssh from haswell, `ssh jetson`).

   You will note on the jetson machine that `perf list` shows a lot of events missing. For some reason the linux-kernel is missing support for them, but if you look at the ARM Cortex-A57 manual:
   ```
   http://web.eece.maine.edu/~vweaver/classes/ece571/DDI0488C_cortex_a57_
   mpcore_r1p0_trm.pdf
   ```
   in Chapter 11.8 you will see support is listed for them.

   The perf built-in events for Cortex-A57 were not really updated until Linux 4.4 but we are running 3.10 on our system.

   (a) For icache rate try measuring `r14:u` (which is `L1_ICACHE`) and `r01:u` (which is `L1I_CACHE_REFILL`

   (b) Measure and report the L1 data cache load miss rate.
       Use `r40:u` (which is `L1D_CACHE_LD`) and `r42:u` (which is `L1D_CACHE_REFILL_LD`).

   (c) Measure and report the L1 data cache store miss rate.
       Use `r41:u` (which is `L1D_CACHE_ST`) and `r43:u` (which is `L1D_CACHE_REFILL_ST`).

6. Measure and report the L2 data cache load miss rate.
   Use `r50:u` (which is `L2D_CACHE_LD`) and `r52:u` (which is `L2D_CACHE_REFILL_LD`).

7. Measure and report the L2 data cache store miss rate.
   Use `r51:u` (which is `L2D_CACHE_ST`) and `r53:u` (which is `L2D_CACHE_REFILL_ST`).

8. **Short Answer Questions**

   (a) How do the various cache miss rates for bzip2 compare between the Haswell and the Jetson?

   (b) How do the various cache miss rates on the Haswell machine compare between the bzip2 and equake benchmarks?

9. Submitting your work.

   - Create the document containing the data as well as answers to the questions asked.
   - Please make sure your name appears in the document.
   - e-mail the file to me by the homework deadline.