

# Modeling Hippocampal-Cortical Interaction During Event Processing

Qihong Lu, Uri Hasson, Kenneth A. Norman

Department of Psychology and Princeton Neuroscience Institute, Princeton University;



## Summary

- Saving episodic memories at event boundaries reduce is protective against lure memories during retrieval.
- There is a speed-accuracy trade-off on “retrieval-conservativeness”.
- Inhibiting recently-retrieved memory is necessary.

## Model Architecture

### Cortex

- Context-dependent state prediction.
- Actively maintains the current situation model.

### Hippocampus

- Encoding: store episodes.
- Retrieval: pre-load situation models.




Figure 1: The model architecture. Cortex is an RNN that predict the next state, and it has a buffer. Hippocampus is another RNN with some encoding/retrieval mechanism.

## References & Acknowledgement

- [1] Ben-Yakov A., & Dudai, Y. (2011). J Neurosci
- [2] Ben-Yakov A., Eshel, N., & Dudai, Y. (2013). J Exp Psychol Gen
- [3] Ben-Yakov A., & Henson, N. (2018). biorxiv.
- [4] Chen, J., et al. (2016). Cereb Cortex

**Acknowledgement:** This work was supported by a Multi-University Research Initiative grant to KAN and UH (ONR/DoD N00014-17-1-2961). Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the Office of Naval Research or the U.S. Department of Defense.  
**Download the poster:** <http://blablabla.com/>

## Task formulation

- **Schema structure** is encoded in the default transition matrix.
- The transition matrix also depends on some trial-specific **context**.




Figure 2: In this schema graph, each node represents an event, and each edge has a default transitional probability.

## Shared situation model enhance inter-subject correlation (ISC)<sup>[4]</sup>




Figure 3: Experimental design<sup>[4]</sup>. Participants watched an twilight zone episode while being scanned.




Figure 4: Empirical fMRI inter-subject correlation (ISC)<sup>[4]</sup> during the second half of the movie.

## ISC simulation

### Model simplifications, hippocampus

- Encoding: save the situation model from the 1<sup>st</sup> part of the movie as one chunk.
- Retrieval: we force all models to retrieve at t=5.





Figure 5: Top: Model state prediction accuracy; Bottom: after functional alignment, model ISC pattern qualitatively capture the empirical result<sup>[4]</sup>, shown in Figure 4.

## Parameterize hippocampus

### Retrieval:

- Value of a episode = # match - # mismatch
- Min-match and Max-mismatch.
- Inhibit recently retrieved memories.

### Encoding:

- Chunksize: chunk the observed event sequence into pieces.
- Lure episode = actual episode + noise

## Recall performance

**Metric:** how often does the model pre-loaded the required situation model parameters.




Figure 6: Recall performance.

**Chunk size:** Larger chunk size is better

- protect the model from retrieving lure episodes.

**Min-Match:** speed-accuracy trade-off

- Too small: error prone
- Too big: delay retrieval

plots/lines1.png

Figure 7:

plots/lines2.png

Figure 8: