



Modeling Hippocampal-Cortical Interaction During Event Processing

Qihong Lu, Uri Hasson, Kenneth A. Norman

Department of Psychology and Princeton Neuroscience Institute, Princeton University



Summary

Our simulations support that...

- Shared situation model enhances inter-subject correlation^[4].
- Hippocampus should saving episodic memories at event boundaries^[1, 2, 3], because this is protective against retrieving lure memories.
- There is a speed-accuracy trade-off on the consistency criterion for recall.

Model

Cortex

- Context-dependent state prediction.
- Actively maintains the current situation model.

Hippocampus

- Encoding: store episodes.
- Retrieval: pre-load situation models.




Figure 1: The model architecture. Cortex is an RNN that predict the next state, and it has a buffer. Hippocampus is another RNN with some encoding/retrieval mechanism.

References & Acknowledgement

- [1] Ben-Yakov A., & Dudai, Y. (2011). J Neurosci
- [2] Ben-Yakov A., Eshel, N., & Dudai, Y. (2013). J Exp Psychol Gen
- [3] Ben-Yakov A., & Henson, N. (2018). biorxiv.
- [4] Chen, J., et al. (2016). Cereb Cortex

Acknowledgement: This work was supported by a Multi-University Research Initiative grant to KAN and UH (ONR/DoD N00014-17-1-2961). Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the Office of Naval Research or the U.S. Department of Defense. Download the poster: tinyurl.com/ccn18-q1

Task formulation

- Schema:** The default transition matrix represent the schema.
- Context:** The true ongoing situation model can alter the default transition matrix.




Figure 2: In this schema graph, each node represents an event and each edge has a default transitional probability.

Shared situation model enhances inter-subject correlation (ISC)^[4]




Figure 3: Experimental design^[4]. Participants watched an episode of twilight zone movie while being scanned.




Figure 4: Empirical fMRI ISC^[4] during the second half of the movie. DM-RM ISC gradually converged to RM-RM ISC.

ISC simulation

Model simplifications: Save the 1st part of the movie as 1 chunk and retrieve it during the 2nd part.





Figure 5: Top: Model state prediction accuracy. We forced all models to retrieve memory at t=5; Bottom: after functional alignment, the model ISC pattern qualitatively captures the empirical result^[4] in Figure 4.

Parameterize the hippocampus

Retrieval:

- Retrieve the episode that matches the actively maintained situation model the most
- Min-match: a threshold on required consistency
- Reject episodes with any mismatch
- Inhibit recently retrieved memories.

Encoding:

- Chunk size: chunk the observed event sequence into episodes.
- Lure episode = actual episode + noise

Recall performance

Metric: how often does the model pre-loaded the required situation model parameters.




Figure 6: Recall performance with different combinations of chunk size and min match.





Figure 7: The correctness of the actively maintained situation model as event sequences unfold.

- Top: varying min match while holding chunk size fixed
- Bottom: varying chunk size while holding min match fixed