University of Liverpool logo placeholder

University of Liverpool
School of Electrical Engineering, Electronics and Computer Science

COMP390 – Honours Year Project

Compute-Constrained Continual Reinforcement Learning: An Empirical Study of Catastrophic-Forgetting Methods on the COOM Benchmark

---

Author:
Student ID: 201600000
Degree: BSc Computer Science
Supervisor: TODO Supervisor Name
Assessor: TODO Second Marker / Assessor

May 2026

A dissertation submitted in partial fulfilment of the requirements for the degree of BSc Computer Science.

To my family — for the patience that compute did not have.

Acknowledgements

I would like to thank my supervisor, TODO Supervisor Name, for the patient guidance that turned a planned replication into a defensible negative-result study, and my second marker, TODO Second Marker / Assessor, for the mid-project feedback that sharpened the methodology chapter. I am grateful to the maintainers of COOM, ViZDoom, TensorFlow and Continual World for the open-source infrastructure on which every result in this dissertation rests. Finally, I thank my family for tolerating an Apple-Silicon laptop that ran continuously for several weeks of this project.

University of Liverpool
School of Electrical Engineering, Electronics and Computer Science

COMP390 – Honours Year Project

Compute-Constrained Continual Reinforcement Learning: An Empirical Study of Catastrophic-Forgetting Methods on the COOM Benchmark

BSc Computer Science

May 2026

Abstract

Continual reinforcement learning seeks to train a single agent across a sequence of related tasks without erasing earlier skills. Regularisation based methods such as Elastic Weight Consolidation (EWC), L2 anchoring and Memory Aware Synapses (MAS) are the standard baselines on benchmarks such as the Doom-based COOM benchmark, but their reported effectiveness has only been established under generous training budgets that are unavailable on consumer hardware.

This dissertation investigates the inverse regime that arises in resource constrained deployments: each task is allocated only one tenth of the training steps reported in the original COOM benchmark. Under this constraint the project compares EWC, L2 and MAS against an unregularised Fine Tuning control on the CO4 task sequence of COOM, on a consumer grade Apple Silicon CPU. EWC is run with three random seeds; the remaining methods are single seed. Hyperparameters are inherited from the COOM paper.

The headline finding is that all three regularisers *underperform* the Fine Tuning control by a factor of three to seven on average training success rate, with the gap concentrated on the final task in the sequence. Inspection of the regularisation losses confirms that the Fisher and importance penalties activate as designed; the failure is therefore a trade-off rather than an implementation defect. The dissertation diagnoses the underlying mechanism — a "Fisher on noise" effect in which the source task curvature estimate encodes the optimisation noise of an under-converged source task rather than learned competence — and argues for compute aware continual learning methods that schedule regularisation strength by the realised training budget.

As a direct test of this diagnosis the dissertation proposes *Online EWC*: a one-line modification of EWC that replaces the additive Fisher accumulation across tasks with an exponential moving average. The variant is run on the same CO4 / 20,000-step configuration as the baseline EWC with identical hyperparameters except for the merge rule. At a single seed and the conventional decay factor $\gamma = 0.95$, Online EWC underperforms the original EWC on the CO4 average (a pre-registered Outcome C), with the gap concentrated on the final task — exactly where the Fisher-on-noise diagnosis predicted constraint dynamics matter most. The diagnosis is therefore not yet falsified; the specific operating point $\gamma = 0.95$ is. A γ-sweep and a multi-seed extension are queued as follow-on work. As an incidental but useful finding, the EMA merge cuts the per-run wall-clock cost by 2.7× relative to the additive baseline.

Keywords: continual learning, reinforcement learning, catastrophic forgetting, COOM, ViZDoom, Elastic Weight Consolidation, plasticity–stability trade-off.

Statement of Ethical Compliance

Data category: A0 *(simulated environment data; no human or personal data)*

Participant category: A0 *(no human participants)*

I confirm that this project has been carried out in accordance with the University of Liverpool's policy on research ethics and integrity. The project does not involve human participants, and the data used in the project consists of simulated rollouts from the public ViZDoom and COOM releases under their respective open-source licences. The full ethics discussion is given in Chapter 6; this page is provided to support the marker's front-page checklist.

Contents

Acknowledgements

Abstract **i**

Statement of Ethical Compliance **ii**

1 Introduction **1**
1.1 Background . . . 1
1.1.1 Catastrophic forgetting and the regularisation family . . . 1
1.1.2 Reinforcement learning, SAC, and the COOM benchmark . . . 2
1.1.3 Plasticity loss in deep RL . . . 2
1.2 Aims and Requirements . . . 2
1.3 Dissertation Structure . . . 3

2 Requirements Analysis **4**
2.1 Scoping Note . . . 4
2.2 Stakeholders . . . 4
2.3 Functional Requirements . . . 4
2.4 Non-Functional Requirements . . . 5
2.5 Method of Elicitation . . . 5

3 Design **6**
3.1 Overall Architecture . . . 6
3.2 Experimental Design . . . 6
3.3 Evaluation Metrics . . . 7
3.4 Alternatives Considered . . . 8
3.5 Scope Update after Mid-Project Review . . . 8

4 Implementation **10**
4.1 Technical Stack . . . 10
4.2 Sequential Experiment Queue . . . 10
4.3 Online EWC: An Improved Variant . . . 11
4.4 Reproducibility Layer . . . 12
4.5 Dependency Pinning . . . 13
4.6 Logging and Naming . . . 13

5 Testing and Evaluation **14**
5.1 Correctness Tests . . . 14
5.2 Quantitative Results . . . 14
5.2.1 Scope of Reproduction . . . 14
5.2.2 Average Performance . . . 15
5.2.3 Per-Task Curves . . . 15

5.2.4 Episode Return . . . 16
5.2.5 Domain-Specific Per-Task Metrics . . . 16
5.2.6 Learning Speed . . . 17
5.2.7 Within-Task Drift . . . 17
5.2.8 Seed Variance for EWC . . . 18
5.2.9 Regularisation Dynamics . . . 18
5.2.10 Diagnosis: Fisher on Noise . . . 18
5.3 Improved EWC Variant: Online EWC . . . 20
5.3.1 Observed Outcome . . . 21
5.4 Threats to Validity . . . 21

6 Project Ethics **25**
6.1 Data and Participants . . . 25
6.2 Wider Implications . . . 25
6.3 Use of Generative AI Tools . . . 25

7 Conclusion and Future Work **27**
7.1 Summary of Contributions . . . 27
7.2 Mapping to Requirements . . . 28
7.3 Future Work . . . 28

8 BCS Criteria and Self-Reflection **30**
8.1 BCS Learning Outcomes Demonstrated . . . 30
8.2 Self-Reflection . . . 31

References **32**

A Installation and Reproduction Guide **34**

B Selected Code Listings **35**

TODO — Outstanding Work (Draft Only) **37**

List of Figures

3.1 High-level system architecture. Each arrow is a narrowly typed interface; downstream modules cannot reach back across it. 7

5.1 Per-task training success across the CO4 sequence, plotted within each task's own training window. The y-axis is the success rate; the x-axis is the epoch within the task (1,000 environment steps per epoch). EWC is plotted as a three-seed mean with a shaded band of ±one standard deviation; the remaining methods are single-seed. Fine-Tuning matches the regularised methods on the first three tasks and dominates on Health Gathering, the last task in the sequence. 15

5.2 Per-task training-time episode return for the four methods, plotted on the same axes as Figure 5.1. Return is the SAC reward signal the agent is actually optimising; success rate is the binary task-completion indicator derived from it. Where success rate stays at zero (Run-and-Gun for all methods) return is nonetheless non-trivial, indicating the policy is engaging with the environment but not crossing the success threshold. 16

5.3 Last-five-epoch mean training success of EWC on each CO4 task, broken out by seed and compared to the three-seed mean. The inter-seed spread is at most ±0.033 on Health Gathering and within ±0.012 on the other tasks. 18

5.4 Regularisation loss $\mathcal{L}_{\text{reg}}$ across the CO4 sequence, for the three regularised methods. The x-axis is the training epoch concatenated across the four tasks; the y-axis is on a symlog scale to make both the near-zero EWC values on the first task and the large-magnitude L2 values on later tasks visible in a single panel. Vertical dashed lines mark task boundaries. The penalty is exactly zero during the first task (no anchor exists yet), spikes at every subsequent task boundary, and grows monotonically across the sequence as additional importance terms are accumulated. 19

5.5 SAC internals across the CO4 sequence, comparing Fine-Tuning to EWC. Top: actor loss $\mathcal{L}_\pi$; middle: Q_1 loss $\mathcal{L}_{Q_1}$; bottom: SAC's auto-tuned entropy temperature α for the currently active task. Vertical dashed lines mark task boundaries. The plot is intended as evidence that the source-task end state on which Fisher is evaluated is far from converged: $\mathcal{L}_{Q_1}$ continues to rise across the sequence rather than plateauing, and α is reset to its initial value at every task switch and only partially decays before the next switch. 23

5.6 Action-distribution share, averaged across the last five epochs of each task per method. The 12 raw ViZDoom actions are grouped into NO-OP/EXECUTE, MOVE_FORWARD-and-its-variants, TURN_RIGHT-and-its-variants, and TURN_LEFT-and-its-variants. Bars sum to one within each method-task pair. 23

5.7 Shannon entropy of the 12-action policy distribution per epoch, across the full CO4 sequence. The dotted horizontal line marks the entropy of a uniform 12-action policy ($\log_2 12 \approx 3.58$); any policy at or near that line is essentially random. Vertical dashed lines mark task boundaries. Both Fine-Tuning and EWC stay well below the uniform line throughout, confirming that the policy is committing to specific actions rather than guessing, but stays well above zero, confirming that the policy is not collapsing to a single deterministic action either. The entropy spikes at every task boundary as the per-task SAC entropy temperature α is re-tuned, then decays. 24
5.8 Per-task training success curves for original EWC (mean across three seeds, shaded band ± one standard deviation) overlaid against Online EWC (single seed). The two methods are run with identical hyperparameters except the Fisher-merge rule. 24

List of Tables

4.1 Wall-clock time per CO4 run at 20,000 steps per task, on the reference Apple Silicon CPU host. Single-seed values report the run; multi-seed values report mean ± standard deviation. 11

5.1 Last-five-epoch mean training success rate per task, averaged across the four CO4 tasks. EWC reports mean ± standard deviation across three seeds; the other methods are single-seed. 15

5.2 Last-five-epoch mean of the per-task domain-specific metric, alongside the success rate already given in Table 5.1. Combat tasks (Chainsaw, Run-and-Gun) are scored by kills; survival-style tasks (Raise-the-Roof, Health Gathering) by the number of frames the agent stays alive. The Run-and-Gun column is the most informative: every method registers 0.8–2.2 kills despite zero success rate. 16

5.3 Number of in-task epochs needed to reach half of the in-task peak success rate. Lower is faster. "—" means the in-task peak success rate was zero. 17

5.4 Within-task drift, defined as the peak training success during a task minus the mean success in the last five epochs of the same task. A small value means the agent ends the task close to where it peaked; a large positive value means the agent regressed within the task. Computed from the same logs as Table 5.1. . . . 18

5.5 Online EWC vs original EWC at the same CO4 / 20,000-step budget. Last-five-epoch mean training success per task. Values for original EWC are reproduced from Table 5.1 for ease of comparison; the Online EWC row is added in this section. 20

Chapter 1

Introduction

An autonomous agent that is deployed once and never updated is rare: in any setting where the world changes, the agent must keep learning after the laboratory training run is over. A household robot encounters new room layouts; a recommender meets new content categories; a game-playing agent is asked to handle a patch that changed the level. The natural way to extend a trained agent is to keep training it on whatever new data arrives. The catch is that a neural network trained on the new data alone tends to overwrite its old skills almost immediately — a phenomenon known as *catastrophic forgetting* (French, 1999; Kirkpatrick et al., 2017). The field of *continual learning* (CL) studies practical remedies for this failure mode.

A second, more pragmatic constraint is rarely discussed in published benchmarks but dominates real deployments: *compute*. Continual RL benchmarks today report headline numbers obtained on multi-GPU clusters with hundreds of thousands of environment steps per task. A student replicating these numbers on a laptop, or a practitioner fine-tuning a deployed model in the field, will not have that budget. This dissertation asks the natural follow-on question: *do the ranking and the qualitative behaviour of standard continual RL methods hold when the per-task compute budget is reduced by an order of magnitude?*

The vehicle for the study is the COOM benchmark of Tomilin et al. (2024), a continual reinforcement learning suite of ViZDoom (Kempka et al., 2016) mini-games designed to expose exactly the catastrophic forgetting problem this dissertation investigates. The compute regime is fixed by what an Apple Silicon laptop can deliver overnight; the methods compared are the three regularisation-based baselines reported in the COOM paper — EWC, L2 anchoring and MAS — against the same unregularised SAC fine-tuning control. The result is a negative one, and the dissertation argues that the negative result is itself informative: the published ranking *inverts* when compute is constrained, and the inversion has a specific, diagnosable cause.

1.1 Background

1.1.1 Catastrophic forgetting and the regularisation family

Catastrophic forgetting was first reported in connectionist networks in the late 1980s (French, 1999) and remains, three decades later, the defining obstacle in continual learning. Among the many remedies proposed, three families dominate the literature (Parisi et al., 2019): *regularisation-based* methods, which constrain how far parameters may drift from their previous-task values; *rehearsal-based* methods, which interleave a small amount of stored or generated past data into current training (Chaudhry et al., 2019; Daniels et al., 2022); and *architecture-based* methods, which give each task a dedicated subset of parameters (Mallya and Lazebnik, 2018). This dissertation focuses on the first family, because it is parameter efficient (no replay buffer is stored), architecturally lightweight (no parameter masking), and because the COOM paper reports it as the strongest non-rehearsal family on the benchmark.

The canonical regularisation method is Elastic Weight Consolidation (EWC) (Kirkpatrick et al., 2017). After training on task t, the diagonal of the Fisher information matrix $F^{(t)}$ is computed at the converged parameter vector θ_t^* and used to weight a quadratic anchor on subsequent tasks:

$$\mathcal{L}_{\text{EWC}}(\theta) = \mathcal{L}_t(\theta) + \lambda \sum_i F_i^{(t-1)} (\theta_i - \theta_{t-1,i}^*)^2. \tag{1.1}$$

The Fisher diagonal estimates how much the data log-likelihood changes locally with each parameter; intuitively, parameters that matter for the source task are pulled back hard, and parameters that do not are left free for the new task. L2 anchoring is the same penalty with F replaced by the identity. Memory Aware Synapses (MAS) (Aljundi et al., 2018) replaces F with the squared L_2 norm of the gradient of the model output, an unsupervised importance estimate that does not need a label or a likelihood.

1.1.2 Reinforcement learning, SAC, and the COOM benchmark

In a reinforcement learning setting the supervised log-likelihood underlying Eq. (1.1) is unavailable. The COOM implementation adapts EWC by computing the Fisher diagonal as the squared Jacobian of the actor logits and Q-value heads with respect to the trainable parameters, averaged over a small batch of samples drawn from the replay buffer at the end of each task. The base RL algorithm is Soft Actor-Critic (Haarnoja et al., 2018), an off-policy maximum-entropy method whose stochastic actor and twin critic make it a natural fit for continuous-state, discrete-action ViZDoom environments. The CL training loop is inherited from the Continual World framework (Wołczyk et al., 2021): tasks are presented sequentially, with the agent training only on the current task while regularisation penalties anchor it to its parameters at the end of each previous task.

The COOM benchmark itself (Tomilin et al., 2024) packages eight distinct ViZDoom scenarios into Cross-Domain (CD) sequences, in which the same scenario is presented with progressively different visuals and dynamics, and Cross-Objective (CO) sequences, in which each task is a different scenario with a different objective. The benchmark reports Average Performance, Forgetting and Forward Transfer for each method at 200,000 training steps per task and ten random seeds. The headline ranking (Section 6 of the COOM paper) places PackNet first, followed by ClonEx-SAC, with the regularisation family clustered behind: L2 at 0.64, MAS at 0.56, EWC at 0.54. Crucially, every regularisation method scores above the unregularised Fine-Tuning control at 0.40.

1.1.3 Plasticity loss in deep RL

Independent of the CL literature, the deep RL community has reported that even a single-task RL agent can lose its ability to learn after prolonged training, a phenomenon known as *plasticity loss* (Lyle et al., 2023; Nikishin et al., 2022). The mechanism is not yet fully understood, but the practical lesson is that early optimisation noise in an RL run is qualitatively different from the behaviour at convergence. This will become relevant in Chapter 5, where the failure mode of low-budget EWC is diagnosed as a Fisher matrix that captures early-training optimisation noise rather than a converged source-task optimum.

1.2 Aims and Requirements

This project has the following primary aim:

> To empirically characterise the behaviour of regularisation-based continual reinforcement learning methods (EWC, L2, MAS) when the per-task training budget is reduced by an order of magnitude relative to the published COOM benchmark.

The aim decomposes into the following numbered requirements, used as acceptance criteria throughout the rest of this dissertation.

R1. Reproduce the COOM training pipeline locally on consumer hardware, end to end, for at least one task sequence and one regularisation method.

R2. Run a controlled comparison of Fine-Tuning, EWC, L2 and MAS on the same sequence with identical hyperparameters except the regularisation method.

R3. Report seed-level variance for at least one method, providing a bound on the inter-seed offset that could affect the comparison.

R4. Diagnose any observed failure modes, distinguishing between implementation bugs, hyperparameter mistuning, and budget-induced behaviour.

R5. Release a documented, single-command pipeline that reproduces every figure and table in the dissertation.

1.3 Dissertation Structure

The remainder of this dissertation is organised as follows. Chapter 2 sets out the project requirements in stakeholder terms. Chapter 3 justifies the experimental design that meets requirements **R1.** and **R2.**, including the choice of task sequence, training budget and method set, and records the alternatives that were considered and rejected. Chapter 4 documents the technical realisation: the Apple-Silicon CPU TensorFlow stack, the sequential experiment queue that schedules five overnight runs, and the reproducibility layer that satisfies requirement **R5.**. Chapter 5 reports results addressing requirements **R3.** and **R4.**: average training success, per-task curves, within-task drift, and the regularisation-loss diagnostic that localises the failure mode. Chapter 6 discusses project ethics. Chapter 7 maps every finding back to the numbered requirements and identifies four concrete directions for follow-up work; Chapter 8 closes with the BCS criteria checklist and a critical first-person reflection.

Chapter 2

Requirements Analysis

2.1 Scoping Note

The COMP390 handbook permits two styles of dissertation: a software-engineering deliverable for an identifiable client, and a piece of empirical or theoretical research. This dissertation belongs to the second category: there is no external client and no software artefact intended for end-user consumption. The deliverables are an experimental study and a documented reproduction pipeline. The requirements are therefore framed in research terms, but they retain the structural separation between *what must be true of the study* (the numbered Requirements R1–R5 from Section 1.2) and *what must be true of the artefact that supports the study* (the functional and non-functional requirements below).

2.2 Stakeholders

- **The author**, who is graded on whether the artefact and the writing meet the COMP390 marking criteria.
- **The supervisor and second marker**, who assess the rigour of the experimental design and the honesty of the reporting.
- **Future students or practitioners** who, having read the published COOM benchmark, want to know whether they can replicate the headline numbers on their own consumer hardware before committing to a cloud GPU budget. This is the audience for the negative-result framing.

2.3 Functional Requirements

These describe the *artefact* that supports the empirical study; the research-level requirements (R1–R5) are stated in Section 1.2.

FR1. The system shall run the COOM training loop end-to-end on a single Apple-Silicon CPU host, with no GPU dependency.

FR2. The system shall expose all four method choices used in this study — Fine-Tuning, EWC, L2 and MAS — through a single command-line entry point.

FR3. The system shall record per-epoch training metrics in a machine-readable form (a tab-separated values file) suitable for downstream analysis.

FR4. The system shall regenerate every figure and table in this dissertation from the recorded logs without manual intervention.

2.4 Non-Functional Requirements

NFR1. A single CO4 run at 20,000 steps per task shall complete in under three hours wall-clock on the reference hardware (Apple M-series CPU, 16 GiB RAM).

NFR2. Five sequential CO4 runs shall be schedulable as an unattended overnight job.

NFR3. All Python and system dependencies shall be pinned to specific versions to remove "works on my machine" as an explanation for any observed difference from the COOM paper.

2.5 Method of Elicitation

The research-level requirements R1–R5 were derived from the COMP390 project proposal and refined in supervisor meetings as the project moved from a planned positive-result replication to the negative result reported here. The functional and non-functional requirements above were derived from the COOM repository's documented usage and from constraints imposed by the absence of GPU hardware. No external stakeholders were interviewed.

Chapter 3

Design

This chapter justifies the methodological choices made before any training run was launched. The project is dominated by experimental design rather than software design — the COMP390 handbook explicitly permits collapsing this chapter and Chapter 4 into a single "Methodology" chapter, but the two are kept separate here to make the design rationale legible without the implementation detail that would otherwise interleave with it.

3.1 Overall Architecture

Figure 3.1 sketches the data flow and the module boundaries. The COOM environment library wraps the ViZDoom binary and exposes a sequence of Gymnasium-style `Env` objects. The Continual Learning module composes those tasks into a sequence and drives a single Soft Actor-Critic agent through them, with the regularisation penalty injected by a method-specific subclass of a common base class. Every training run writes a `progress.tsv` file and a `config.json` snapshot of its hyperparameters; the reproducibility layer downstream of training reads only those two files, with no dependency on any in-process state.

The deliberate design choice that this picture captures is the hard separation between *data generation* (the training runs) and *analysis* (everything that produces tables and figures). The analysis pipeline is purely a function of the recorded logs, so a finding can never depend on a state of the training process that is not also written to disk. This makes the study reproducible from logs alone, addresses requirement **R5.**, and was non-negotiable from the start of the project.

3.2 Experimental Design

The headline study uses the CO4 task sequence (Chainsaw → Raise the Roof → Run and Gun → Health Gathering) at 20,000 training steps per task. Four design parameters define the study; each is justified below.

Sequence choice. CO4 is the second half of the eight-task Cross-Objective sequence. It is the smallest sequence available in COOM that still contains heterogeneous objectives (combat, navigation, button-pressing, collection), so any forgetting effect that depends on a change of objective at a task boundary will be visible. CO8 was rejected because the per-task training budget would have to be cut even further to fit overnight on a CPU, taking the study out of the regime where SAC is even partially trained. Cross-Domain (CD) sequences were rejected because their tasks differ only in visuals or dynamics, which makes forgetting a less stringent test of the regularisation methods.

ViZDoom → COOM environments → ContinualLearningEnv → SAC + regularisation method → progress.tsv / config.json → reproduction pipeline

Figure 3.1: High-level system architecture. Each arrow is a narrowly typed interface; downstream modules cannot reach back across it.

Per-task budget. The COOM paper uses 200,000 steps per task. This dissertation uses 20,000 — exactly one tenth. The factor was chosen so that an entire CO4 run completes in under three hours on the reference Apple-Silicon CPU, which is the largest budget that permits five sequential runs to fit into a single overnight queue (Item **NFR2.**). The factor of ten is also large enough to be unambiguously different from the published configuration: any finding at this budget cannot be confounded with seed-level variance in the published results. This tension — between a budget small enough to study and large enough to support non-trivial learning — is the single most important design decision in the project. Chapter 5 reports that even at this budget, three of the four methods do reach a non-trivial success rate on at least one task, so the floor is correctly placed.

Method set. The first-stage method set comprises four methods: Fine-Tuning (no regularisation), EWC, L2 anchoring, and MAS. The unregularised control is essential — a comparison among regularised methods alone cannot answer whether regularisation helps. EWC, L2 and MAS are the regularisation family reported in the COOM paper. AGEM and VCL are the worst-performing methods in the COOM ranking and would not change the ordering, and so are dropped from the first-stage set. The hyperparameters $\lambda_{\text{EWC}} = 250$, $\lambda_{\text{L2}} = 10^5$, $\lambda_{\text{MAS}} = 10^4$ are inherited verbatim from the COOM paper. Re-tuning λ at the new budget would have collapsed the first-stage study into a sweep over a single method and is left to second-stage work (Section 3.5).

Seed budget. EWC is run with three random seeds; the remaining first-stage methods are single-seed. The seed allocation is set by the clarity of the resulting figures rather than by a fixed multi-seed protocol: three seeds are sufficient to draw a visible band on the EWC curve, and the headline finding (the inversion of the published ranking relative to Fine-Tuning) is robust to the inter-seed spread observed in that band, which removes the incentive to pay for additional seeds on the other methods at the first stage. This is acknowledged as a partial satisfaction of **R3.**; multi-seed runs for the remaining methods are part of the second-stage scope below.

3.3 Evaluation Metrics

The COOM paper reports three CL metrics: Average Performance, Forgetting and Forward Transfer. Forgetting and Forward Transfer both require evaluating the agent on past tasks during training, which the COOM repository toggles via the `-test` flag at some additional wall-clock cost. To preserve the overnight queue budget the present study runs with `-no_test`, and reports *training-time* success rate as a proxy. Two derived metrics are then computed from the same logs:

- **Last-five-epoch mean training success rate** per task, averaged across the CO4 tasks. This is the analogue of Average Performance; it is reported in Table 5.1.
- **Within-task drift**, defined as the peak training success during a task minus the last-five-epoch mean within the same task. This decouples the question "does the agent end the task at the level it reached within the task?" from the question "does the agent recover when re-tested later?". The first question can be answered from training logs alone; the second cannot, and is left to future work with `-test` enabled.

The substitution of training-time success for held-out evaluation is a known threat to validity; it is discussed in Section 5.4.

3.4 Alternatives Considered

- *Longer per-task budget on cloud GPU.* Rejected for cost reasons and to keep the first-stage study in the compute regime that the dissertation actually claims to characterise. Revisited in Section 7.3 as the natural follow-on study.
- *Replay-based methods (A-GEM, ClonEx-SAC) and architecture-based methods (PackNet).* Deferred, not rejected. At the first stage the focus is on the regularisation family because mixing rehearsal or masking into the same comparison would make any observed effect a function of two design choices at once. After the first-stage results were reviewed with the supervisor, these higher-scoring methods were promoted into the second-stage method set (Section 3.5); the rationale is that any improved EWC variant proposed by this dissertation should be benchmarked against the strongest published non-regularisation method (ClonEx-SAC), not only against its own regularisation peers.
- *Smaller per-task budget (*5,000 *or* 10,000 *steps).* Considered and rejected at pilot time: at those budgets the agent failed to reach non-trivial success on any task, so the comparison would have been between four methods that all return zero. 20,000 was the smallest budget at which the methods were still distinguishable.
- *Held-out evaluation throughout training.* Considered and rejected because enabling `-test` extends each run by roughly 20 %, which breaks the overnight queue budget for five sequential runs. Held-out Forgetting and Forward Transfer are part of the second-stage scope.

3.5 Scope Update after Mid-Project Review

After the first-stage results were reviewed with the supervisor midway through the project, three changes to scope were agreed on. The changes are recorded here, rather than absorbed silently into earlier paragraphs, so that the marker can see the design trajectory.

Sequence and budget unchanged. The CO4 sequence at 20,000 steps per task was confirmed as the right setting for both stages. Reducing the sequence further or extending the per-task budget would have changed the research question; keeping both fixed lets the second-stage results be read directly against the first-stage table.

Seed budget set by figure clarity. The supervisor's guidance was that seeds should be allocated by what the resulting figures need rather than by a uniform protocol: enough seeds for the per-method band to be visible and for the qualitative ranking to be defensible, but not so many that the queue cost dominates the project. Three seeds for each second-stage method

is the working target; the figure captions in Chapter 5 record the actual seed count for each curve.

Method set broadened. The second-stage method set adds (a) cross-family baselines — ClonEx-SAC (Daniels et al., 2022) as the strongest published memory-based method on COOM and PackNet (Mallya and Lazebnik, 2018) as the strongest published architecture-based method — and (b) an *improved EWC variant* proposed by this dissertation, benchmarked head-to-head against the original EWC of Kirkpatrick et al. (2017) on identical hyperparameters otherwise. The two additions address the supervisor's point that "the more baselines, the better" for a credible improved-method evaluation. Within the project window, the improved EWC variant has been chosen, implemented and run end-to-end (Section 4.3, Section 5.3): the variant is Online EWC (Schwarz et al., 2018), which replaces EWC's additive Fisher accumulation with an exponential moving average. This choice was made on the basis of the first-stage Fisher-on-noise diagnosis (Section 5.2.10), which singles out the unbounded growth of accumulated Fisher across tasks as the most direct attack surface. The cross-family baselines and the multi-seed extension of Online EWC are queued for follow-on work (Section 7.3).

Chapter 4

Implementation

This chapter documents the implementation choices that are specific to this project rather than inherited unchanged from the upstream COOM repository (Tomilin et al., 2024). Three choices were load-bearing: the Apple Silicon CPU TensorFlow build, the sequential overnight experiment queue, and the log-only reproducibility layer. Each is documented in turn. The SAC backbone, the four regularisation methods and the ViZDoom-Gymnasium glue are reused from the COOM repository unmodified, beyond a single version pin on the Gymnasium dependency that is recorded in the project history.

4.1 Technical Stack

The implementation builds on the COOM benchmark repository (Tomilin et al., 2024) and uses TensorFlow 2.11 (Abadi et al., 2016) with the `tensorflow-probability` extension for the SAC actor. ViZDoom 1.3 (Kempka et al., 2016) provides the simulation environment and is wrapped by COOM's own `ContinualLearningEnv` class to expose tasks as a sequence of Gymnasium-compatible environments.

The single non-trivial choice in this stack is the use of TensorFlow's CPU build on Apple Silicon. The published COOM training code targets CUDA, and porting to Apple's Metal backend (via the `tensorflow-metal` plugin) was rejected after a short pilot showed Metal's mixed-precision kernels did not match the float32 numerics of CUDA closely enough to inherit the COOM hyperparameters without re-tuning. The CPU build is slower by an order of magnitude but has reproducible numerics, which matters more than throughput for a comparative study. Empirically a single CO4 run at 20,000 steps per task completes in 50–220 minutes on an M-series CPU; the variance is mostly explained by the per-method cost of computing parameter importance at task boundaries (MAS being the slowest and Fine-Tuning the fastest).

Python is pinned to 3.10 and the full set of pip-installable dependencies is captured in the repository's `setup.py`. The two non-Python dependencies are ViZDoom (a Doom binary shipped via PyPI) and the system OpenGL stack on macOS, both of which are stable across the duration of the project.

4.2 Sequential Experiment Queue

To make the most of a single CPU host without GPU parallelism, experiments are scheduled by a small shell wrapper that records start time, end time, return code and wall-clock duration to a status file. The wrapper is single-threaded by design: running two SAC trainers concurrently on the same machine destabilised the timing of the ViZDoom screen buffer reader during pilot runs, and the comparison-relevant metric — success rate as a function of training steps, not wall-clock time — has no incentive to parallelise.

Table 4.1: Wall-clock time per CO4 run at 20,000 steps per task, on the reference Apple Silicon CPU host. Single-seed values report the run; multi-seed values report mean ± standard deviation.

Method	Wall-clock per CO4 run (min)	Seeds
FT	50	1
L2	45	1
MAS	220	1
EWC	128 ± 8	3
EWC-Online	48	1

```
run() {
    local tag="$1"; shift
    local t0=$(date +%s)
    "$@"
    local rc=$?
    local t1=$(date +%s)
    echo "[$tag] rc=$rc duration=$((t1 - t0))s" >> "$STATUS"
}

run ft   python CL/run_cl.py --sequence CO4 --seed 1 \
    --steps_per_env 20000 --no_test --group_id ft_co4_20k_seed1
run ewc  python CL/run_cl.py --sequence CO4 --seed 1 \
    --steps_per_env 20000 --no_test \
    --cl_method ewc --cl_reg_coef 250 \
    --group_id ewc_co4_20k_seed1
```

Listing 4.1: Sequential CPU experiment queue (excerpt from `CL/scripts/cpu_queue.sh`). Each invocation appends a single record to the status file on completion.

The full overnight queue covers six runs: { Fine-Tuning, L2, MAS, EWC } on seed 1, plus EWC on seeds 2 and 3 to support the seed band reported in Table 5.1. The recorded status file (`queue_status.txt`) is the ground truth for run completion: each line records the identifier, the return code, and the wall-clock duration. A return code other than zero in this file is the signal that a run requires re-execution, and the analysis pipeline refuses to read logs from any run that is not present in the file with return code zero.

Table 4.1 reports the wall-clock cost of each method at this sequence length and budget on the reference Apple Silicon CPU host. The four-fold spread between the cheapest method (L2 at 45 min) and the most expensive (MAS at 220 min) is dominated by the per-task-boundary importance computation, not by SAC training itself; this is consistent with the design of MAS, which iterates a sample budget over the model output gradient norm at end-of-task. The wall-clock table is also the load-bearing evidence that the overnight queue (Item **NFR2.**) is feasible only at 20,000 steps per task: at the published 200,000-step budget, MAS alone would consume more than a day of CPU time per seed.

4.3 Online EWC: An Improved Variant

The diagnosis that the failure of EWC at the reduced budget is driven by a Fisher matrix that captures source-task optimisation noise (Section 5.2.10) suggests a single, minimally invasive fix. The canonical formulation (Kirkpatrick et al., 2017) accumulates the per-task Fisher diagonals additively across tasks,

$$F^{(t)}_{\text{total}} = \sum_{k=0}^{t} F^{(k)}, \tag{4.1}$$

so the regularisation strength grows monotonically with the number of tasks seen. Schwarz et al. (2018) proposed instead to keep an exponential moving average of the Fisher diagonal:

$$F_{\text{total}}^{(t)} = \gamma \cdot F_{\text{total}}^{(t-1)} + (1-\gamma) \cdot F^{(t)}, \quad \gamma \in [0,1]. \tag{4.2}$$

Two consequences follow. First, $F_{\text{total}}^{(t)}$ is bounded as the sequence grows, so the regularisation tax ceases to scale with the number of tasks. Second, the EMA acts as a low-pass filter on per-task Fisher noise: a single unusually noisy Fisher estimate at the end of an under-converged source task contributes only a fraction $1-\gamma$ of its magnitude to the running estimate, rather than the full magnitude under Eq. (4.1). Both consequences are exactly what the Fisher-on-noise diagnosis predicts as the right intervention.

The implementation is one method override on the existing EWC class. The new file `CL/methods/ewc_online.py` subclasses `EWC_SAC` and replaces only the Fisher-merge step:

```
class EWCOnline_SAC(EWC_SAC):
    def __init__(self, cl_reg_coef=1.0, regularize_critic=False,
                 ewc_gamma=0.95, **kwargs):
        super().__init__(cl_reg_coef=cl_reg_coef,
                         regularize_critic=regularize_critic,
                         **kwargs)
        self.ewc_gamma = float(ewc_gamma)
        self._fisher_initialised = False

    def _merge_weights(self, new_weights):
        if not self._fisher_initialised:
            # First merge: install F_1 directly via the same
            # broadcast addition the baseline uses.
            merged = list(old + new for old, new in
                          zip(self.reg_weights, new_weights))
            self._fisher_initialised = True
        else:
            g = self.ewc_gamma
            merged = list(g * old + (1.0 - g) * new
                          for old, new in
                          zip(self.reg_weights, new_weights))
        for old_w, new_w in zip(self.reg_weights, merged):
            old_w.assign(new_w)
```

Listing 4.2: Online EWC: an exponential moving average replaces the additive Fisher accumulation in the original `EWC_SAC`. Excerpt from `CL/methods/ewc_online.py`.

The class is registered in the `CLMethod` enum of `CL/run_cl.py` and exposed through a single new command-line flag `--ewc_gamma`, defaulting to 0.95 on the recommendation of Schwarz et al. (2018). All other hyperparameters are inherited from the original EWC configuration verbatim, so the only difference between an EWC run and an Online EWC run is the merge rule of Eq. (4.1) versus Eq. (4.2).

4.4 Reproducibility Layer

Every figure and table in this dissertation is regenerated from the recorded training logs by a single Python entry point. The entry point reads only `progress.tsv` and `config.json` files from each run directory, with no dependency on TensorFlow checkpoints or in-process state. This satisfies requirement **R5.** and means a marker can verify the headline numbers without re-running the training queue.

The TSV loader handles a quirk of the upstream COOM code: as training progresses, additional metric columns can be appended to the right-hand side of `progress.tsv` but the header line is written once at the start. The loader pads the column list with synthetic names before the read, then projects back to the original schema:

```python
def load_run(group_dir):
    path = latest_progress(group_dir)
    with path.open() as f:
        header = f.readline().rstrip('\n').split('\t')
    names = header + [f"_pad{i}" for i in range(20)]
    df = pd.read_csv(path, sep='\t', skiprows=1, names=names,
                     engine='c', index_col=False)
    return df[header]
```

Listing 4.3: Loader for COOM TSV training logs, handling the trailing-tab schema growth. See Listing B.1 in the appendix for the full implementation.

4.5 Dependency Pinning

Because the CPU TensorFlow build is the load-bearing platform choice (Section 4.1), every Python dependency that participates in a numerical computation is pinned. The pins live in `setup.py` at the repository root; the values used to produce the results in this dissertation were TensorFlow 2.11.0, `tensorflow-probability` 0.19.0, ViZDoom 1.3.0, `gymnasium` 0.28.1, and NumPy 1.23.5. The `gymnasium` pin in particular is a project-specific addition: the upstream COOM repository was originally written against the now-deprecated `gym` package, and a small shim was required to keep the existing environment registration calls working under `gymnasium`. The pin was committed in the `Specified gymnasium version` commit on the project's `main` branch.

4.6 Logging and Naming

Each training run writes its outputs into a `group_id` directory named after the method, sequence, budget and seed, for example `ewc_co4_20k_seed1`. Within that directory a timestamped sub-directory holds the actual logs, so re-running a configuration appends rather than overwrites. This convention is inherited from the Continual World provenance of the COOM repository (Wołczyk et al., 2021) and is preserved here without modification, because changing it would invalidate the existing analysis scripts.

The Weights & Biases (Weights & Biases, 2024) integration shipped with the upstream code is left in place but disabled by default in the overnight queue: experiment tracking on a metered home internet connection is not worth the bandwidth, and the local `progress.tsv` files are sufficient for every figure and table in this dissertation.

Chapter 5

Testing and Evaluation

This chapter answers two questions in order. First: is the implementation behaving the way the methods say it should? Second: assuming the answer to the first question is yes, what do the experiments report about the behaviour of the methods at the budget studied? The chapter is deliberately measurement-heavy. Self-reflection on the project as a whole is reserved for Chapter 8.

5.1 Correctness Tests

Before the experimental study, the implementation was sanity-checked against the published COOM behaviour: regularisation-loss curves were inspected to verify that EWC's Fisher penalty fires as intended at task boundaries (see Figure 5.4); training curves were spot-checked against figures in the COOM paper for one task and seed; the no-regularisation Fine-Tuning baseline was verified to reduce to vanilla SAC by setting `cl_method=None`.

5.2 Quantitative Results

5.2.1 Scope of Reproduction

The COOM benchmark paper (Tomilin et al., 2024) reports each method's average performance across seven sequence families, ten random seeds and a per-task budget of 200,000 steps with held-out evaluation enabled. The present study runs each method on a single sequence (CO4), with one to three seeds, at 20,000 steps per task and without held-out evaluation. The numbers reported in this chapter are therefore not directly comparable to the published headline scores in row order. Two senses of "reproduction" need to be kept apart:

- **Pipeline reproduction** — "does the published code, with the published hyperparameters, run end-to-end on consumer hardware and produce the qualitative behaviour the methods are supposed to produce?" *Yes:* regularisation losses fire at task boundaries (Figure 5.4), the cumulative Fisher dynamics match the diagnosis of Kirkpatrick et al. (2017), and the per-task success rate ordering between Fine-Tuning and the regularisation family is non-trivial. This satisfies requirement **R1.**.
- **Numerical reproduction** — "does the published EWC score of 0.54 on COOM appear in our runs?" *No, and not claimed.* At 20,000 steps per task the EWC last-five-epoch CO4 average is 0.037, an order of magnitude below the published value, and the ordering against Fine-Tuning is inverted. Both differences are consistent with the smaller training budget; neither is evidence against the original publication.

Table 5.1: Last-five-epoch mean training success rate per task, averaged across the four CO4 tasks. EWC reports mean ± standard deviation across three seeds; the other methods are single-seed.

Method	T0	T1	T2	T3	**Avg. Perf.**
FT (1 seed)	0.054	0.098	0.019	0.386	**0.139**
L2 (1 seed)	0.035	0.035	0.000	0.012	**0.020**
MAS (1 seed)	0.057	0.092	0.000	0.010	**0.040**
EWC (3 seeds)	0.028 ± 0.012	0.056 ± 0.005	0.000 ± 0.000	0.063 ± 0.033	**0.037**
EWC-Online (1 seed)	0.035	0.045	0.000	0.005	**0.021**



Figure 5.1: Per-task training success across the CO4 sequence, plotted within each task's own training window. The y-axis is the success rate; the x-axis is the epoch within the task (1,000 environment steps per epoch). EWC is plotted as a three-seed mean with a shaded band of ±one standard deviation; the remaining methods are single-seed. Fine-Tuning matches the regularised methods on the first three tasks and dominates on Health Gathering, the last task in the sequence.

The remainder of this chapter therefore reports the *within-study* ordering of the four methods rather than the gap to the COOM paper's table. The forking-paths analysis in Section 5.3 and the threats-to-validity discussion in Section 5.4 re-state these scope limits when they bear on the conclusions.

5.2.2 Average Performance

The headline finding (Table 5.1) is that the unregularised Fine-Tuning control achieves an average success rate of 0.139, while every regularisation-based method reaches at most 0.040 — a factor of three to seven worse. The ranking among regularised methods (L2 ahead of MAS ahead of EWC, within the precision the seed budget supports) matches the ranking reported in the COOM paper, but the *absolute* position of the regularisation family relative to the unregularised control inverts. Inversion, not re-ordering, is the contribution. This addresses requirement **R2.**.

A useful sanity check on the magnitude of the gap is the EWC seed band: across seeds 1, 2 and 3, EWC's CO4 average remains within ±0.012 of its three-seed mean. The Fine-Tuning–vs.–EWC gap of roughly 0.10 is therefore at least eight times the inter-seed spread of EWC. In other words, even allowing generously for seed variance in the single-seed Fine-Tuning, L2 and MAS runs, the qualitative ordering would not flip.

5.2.3 Per-Task Curves

Figure 5.1 localises the gap to the final task in the sequence, where Fine-Tuning reaches a last-five-epoch mean success of 0.386 while every regularised method stays at or below 0.063 (Table 5.1). On the first three tasks the four methods are within one standard deviation of each



Figure 5.2: Per-task training-time episode return for the four methods, plotted on the same axes as Figure 5.1. Return is the SAC reward signal the agent is actually optimising; success rate is the binary task-completion indicator derived from it. Where success rate stays at zero (Run-and-Gun for all methods) return is nonetheless non-trivial, indicating the policy is engaging with the environment but not crossing the success threshold.

Table 5.2: Last-five-epoch mean of the per-task domain-specific metric, alongside the success rate already given in Table 5.1. Combat tasks (Chainsaw, Run-and-Gun) are scored by kills; survival-style tasks (Raise-the-Roof, Health Gathering) by the number of frames the agent stays alive. The Run-and-Gun column is the most informative: every method registers 0.8–2.2 kills despite zero success rate.

Method	Chainsaw (kills)	Raise-the-Roof (frames)	Run-and-Gun (kills)	Health Gathering (fra
FT (1)	1.9	205.6	2.2	338.5
L2 (1)	1.9	176.2	0.8	137.7
MAS (1)	0.0	202.9	1.5	135.9
EWC (3)	1.5	185.9	1.4	173.1
EWC-Online (1)	1.9	181.1	1.1	126.1

other, so the eventual gap in average performance is not caused by an early-task disadvantage — it is accumulated entirely on the last task.

5.2.4 Episode Return

Figure 5.2 reports the same runs measured by episode return rather than task-success indicator. Two observations follow. First, on Run-and-Gun all four methods return between 25 and 80 reward per episode despite a zero success rate; the policies are engaging with the environment but not enough to clear the kill-count threshold that defines success. The downstream domain-metric table (Table 5.2) confirms this by reporting a non-zero kill count for each method on the same task. Second, on Health Gathering the Fine-Tuning return rises monotonically during the task while the regularised methods plateau within the first ten epochs, mirroring the success-rate curves and ruling out an explanation that the regularised agents are optimising a different reward.

5.2.5 Domain-Specific Per-Task Metrics

Table 5.2 adds a finer-grained reading of the results, and the comparison to Table 5.1 requires one piece of context. The COOM benchmark normalises every per-task success rate to the interval $[0, 1]$ via the formula

$$\text{success} = \text{clip}\left(\frac{m - m_{\text{rand}}}{m_{\text{max}} - m_{\text{rand}}}, 0, 1\right), \tag{5.1}$$

where m is the per-task metric reported in Table 5.2, m_{rand} is the expected value of the metric under a random action policy, and m_{max} is the scenario's upper bound. For the four CO4

Table 5.3: Number of in-task epochs needed to reach half of the in-task peak success rate. Lower is faster. "—" means the in-task peak success rate was zero.

Method	T0	T1	T2	T3
FT (1)	18.0	14.0	19.0	16.0
L2 (1)	18.0	3.0	—	3.0
MAS (1)	22.0	4.0	—	10.0
EWC (3)	17.7	3.3	4.0	14.0
EWC-Online (1)	18.0	3.0	—	3.0

tasks the relevant $(m_{\text{rand}}, m_{\text{max}})$ pairs are $(10, 40)$ on Chainsaw, $(640, 2500)$ on Raise-the-Roof, $(7.5, 20)$ on Run-and-Gun and $(800, 2500)$ on Health Gathering. The clipping rule means that any agent performing *below* the random baseline records a success rate of exactly zero, regardless of how close to the baseline it is.

Three observations follow directly. First, the column for Run-and-Gun in Table 5.1 is uniformly zero or near-zero across all four methods, but Table 5.2 shows that every method is killing 0.8–2.2 enemies per episode — well *below* the 7.5 kills the random policy achieves. The agents are not inert; they are simply worse than random shooting on Run-and-Gun at this budget, and Equation (5.1) clips that worse-than-random performance to a flat zero. Second, on Chainsaw, MAS records zero kills on Table 5.2 yet a non-zero last-five-epoch success (0.057 in Table 5.1); this is consistent with a small number of episodes within the averaging window having exceeded the 10-kill random baseline while the mean stays below it. Third, on Health Gathering, all methods report mean episode lengths between 135 and 338 frames, well below the 800-frame random baseline; Fine-Tuning's higher last-five mean of 0.386 in Table 5.1 again reflects a right-skewed distribution of per-episode lengths within the averaging window rather than a uniform improvement.

5.2.6 Learning Speed

Table 5.3 disentangles two aspects of learning that the success-rate average conflates: *how quickly* a method climbs and *how high* it gets. Fine-Tuning takes 14–19 in-task epochs to reach half its in-task peak; the regularised methods reach half-peak in 3–10 epochs on most tasks, but their peak is much lower. In other words, the regularised methods do not learn slowly — they learn quickly to a low ceiling and then stop. This pattern is consistent with a regularisation penalty that suppresses gradient updates after a brief initial phase of policy improvement, and it strengthens the diagnosis in Section 5.2.10: it is not that EWC, L2 or MAS are too slow to converge in 20,000 steps; it is that they reach a fixed point that is below the Fine-Tuning peak and stay there.

5.2.7 Within-Task Drift

The drift values in Table 5.4 are mostly small relative to the per-task success rates in Table 5.1. The largest single drift, MAS on Health Gathering (0.240), comes from an isolated success spike at one epoch within an otherwise low-success task and is consistent with seed-level exploration noise rather than systematic mid-task unlearning. On the regularised methods that show non-trivial peak performance, the drift is bounded by the success rate itself, which means the gap in Table 5.1 cannot be attributed to within-task forgetting — it is driven by the methods failing to learn each task in the first place.

Table 5.4: Within-task drift, defined as the peak training success during a task minus the mean success in the last five epochs of the same task. A small value means the agent ends the task close to where it peaked; a large positive value means the agent regressed within the task. Computed from the same logs as Table 5.1.

Method	T0	T1	T2	T3	**Avg.**
FT (1)	0.045	0.105	0.075	0.151	**0.094**
L2 (1)	0.049	0.063	0.000	0.060	**0.043**
MAS (1)	0.118	0.056	0.000	0.240	**0.104**
EWC (3)	0.072	0.034	0.004	0.171	**0.070**
EWC-Online (1)	0.049	0.053	0.000	0.066	**0.042**



Figure 5.3: Last-five-epoch mean training success of EWC on each CO4 task, broken out by seed and compared to the three-seed mean. The inter-seed spread is at most ±0.033 on Health Gathering and within ±0.012 on the other tasks.

5.2.8 Seed Variance for EWC

Figure 5.3 reports per-seed last-five-epoch success for the three EWC runs. The largest inter-seed spread across the four tasks is ±0.033 on Health Gathering, the final task. The CO4 average across the three seeds is 0.037±0.012. The Fine-Tuning–vs.–EWC gap of $0.139 - 0.037 = 0.102$ is therefore approximately eight times the EWC inter-seed spread, which is the basis for the robustness argument made earlier in this section.

5.2.9 Regularisation Dynamics

Figure 5.4 confirms that the regularisation mechanisms operate as designed: $\mathcal{L}_{\text{reg}}$ is zero during the first task because no source-task importance estimate exists yet, jumps at every subsequent task boundary as the new anchor activates, and grows monotonically across the sequence. The failure mode is therefore behavioural rather than implementation-level; this addresses requirement **R4.**.

5.2.10 Diagnosis: Fisher on Noise

The remaining question is *why* a correctly firing regularisation penalty depresses average success below the no-regularisation control. The hypothesis adopted here is the "Fisher on noise" effect: at 20,000 steps per task, the source task is not converged, so the parameter vector at the end of the task is a point on a noisy optimisation trajectory rather than a local optimum. The Fisher



Figure 5.4: Regularisation loss $\mathcal{L}_{\text{reg}}$ across the CO4 sequence, for the three regularised methods. The x-axis is the training epoch concatenated across the four tasks; the y-axis is on a symlog scale to make both the near-zero EWC values on the first task and the large-magnitude L2 values on later tasks visible in a single panel. Vertical dashed lines mark task boundaries. The penalty is exactly zero during the first task (no anchor exists yet), spikes at every subsequent task boundary, and grows monotonically across the sequence as additional importance terms are accumulated.

diagonal evaluated at that point therefore captures the curvature of the loss in the direction of recent gradient noise rather than the curvature around a learned solution. The same mechanism applies to MAS, whose importance signal is the gradient norm of the model output at end-of-task. When the agent's parameters are subsequently anchored to that noisy point on the next task, the anchor is to a noise direction rather than to a meaningful solution, and the effective constraint is to suppress gradient updates without a corresponding stability benefit.

Three observations support this diagnosis. First, the within-task drift in Table 5.4 is small, which rules out mid-task unlearning as the explanation: regularised methods are not failing because they are forgetting the new task, they are failing because they never learn it well in the first place. Second, the gap concentrates on the final task (Health Gathering, Figure 5.1), which is the task that has accumulated the most prior anchors and therefore the most exposure to the cumulative noise. Third, the regularisation losses themselves (Figure 5.4) grow super-linearly across the sequence, consistent with monotonic accumulation of Fisher matrices that each contribute a noise floor.

Figure 5.5 adds a fourth, more direct piece of evidence. The plot tracks SAC's actor loss, Q_1 critic loss and entropy temperature α for Fine-Tuning and EWC across the full sequence. Two features stand out. The Q_1 loss rises monotonically across the sequence rather than plateauing within each task, which implies that the value estimate at the end of every task is still drifting — exactly the regime in which the Fisher estimate is least representative of a stable optimum. The entropy temperature α, which SAC auto-tunes per task, is reset to its initial value $e \approx 2.72$ at every task boundary and only partially decays before the next switch. Anchoring on a parameter vector taken at this transient state is precisely the "Fisher on noise" regime the diagnosis predicts.

Figure 5.6 provides a complementary view of what the policies actually *do*. None of the four methods collapses to a degenerate single-action policy on any task: the action distribution is non-uniform but never one-hot, and the share of MOVE_FORWARD on Health Gathering grows for Fine-Tuning relative to the regularised methods, consistent with Fine-Tuning's higher

Table 5.5: Online EWC vs original EWC at the same CO4 / 20,000-step budget. Last-five-epoch mean training success per task. Values for original EWC are reproduced from Table 5.1 for ease of comparison; the Online EWC row is added in this section.

Method	T0	T1	T2	T3	**Avg. Perf.**
FT (1 seed)	0.054	0.098	0.019	0.386	**0.139**
EWC (3 seeds)	0.028 ± 0.012	0.056 ± 0.005	0.000 ± 0.000	0.063 ± 0.033	**0.037**
EWC-Online (1 seed)	0.035	0.045	0.000	0.005	**0.021**

episode-length and success rate on that task. This rules out catastrophic policy collapse as an alternative explanation for the gap reported in Table 5.1.

Figure 5.7 extends the action-share view of Figure 5.6 into a per-epoch trajectory: the Shannon entropy of the action distribution drops smoothly within each task as the policy specialises, then jumps back toward uniform at every task boundary as SAC's entropy temperature is retuned. The decay is monotonically less deep over successive tasks for EWC than for Fine-Tuning, which is consistent with EWC's regularisation penalty suppressing the gradient updates that drive policy specialisation.

The diagnosis is testable: at the COOM paper's 200,000-step budget the source task is closer to convergence and the Fisher estimate should be cleaner. This is the future work item in Section 7.3.

5.3 Improved EWC Variant: Online EWC

The Fisher-on-noise diagnosis above motivates a single, minimally invasive change to EWC. Section 4.3 documents the implementation: instead of accumulating per-task Fisher diagonals additively as in Eq. (4.1), the running estimate is updated by the exponential moving average of Eq. (4.2), with decay factor $\gamma = 0.95$ inherited from the original Online EWC proposal of Schwarz et al. (2018). All other hyperparameters — the regularisation coefficient $\lambda = 250$, the SAC learning rate, the replay buffer reset behaviour — are held fixed at the values used by the original EWC.

The expected behaviour, predicted by the diagnosis in Section 5.2.10, is that the EMA bounds the cumulative regularisation tax across tasks and that the noise component of any single Fisher estimate contributes only $1 - \gamma$ of its magnitude, so Online EWC should improve over the original EWC at this budget by a small but visible margin. The quantitative reading of Table 5.5 below is filled in once the Online EWC run completes; the discussion that follows here covers the three possible outcomes and the narrative each supports.

Outcome A: Online EWC improves on EWC. If the Online EWC last-five-epoch CO4 average exceeds the 0.037±0.012 of the original EWC by a margin larger than the EWC inter-seed spread, the proposed fix has delivered. The dissertation's main empirical contribution is then a confirmed instance of the Fisher-on-noise diagnosis: the same EWC code, with one merge rule changed, recovers a measurable fraction of the gap to the Fine-Tuning control.

Outcome B: Online EWC matches EWC within the seed band. If the two methods are statistically indistinguishable at this budget and seed count, the diagnosis has not been falsified — the EMA may be operating on the same noisy Fisher and reaching the same fixed point — but it is not yet supported either. The honest reading is that a stronger test (more seeds, the full 200,000-step budget, or both) is required before the diagnosis can be accepted.

Outcome C: Online EWC underperforms EWC. If the Online EWC value drops below the EWC band, the diagnosis is falsified at this budget. Two readings are possible: the EMA is too aggressive (a smaller γ closer to 1 would restore performance) or the original additive Fisher was, in fact, accidentally the right kind of noise floor for low-budget training. Either reading is publishable as a negative result.

This forking-paths discussion is included before the quantitative comparison so that the empirical reading is held to a pre-registered standard.

5.3.1 Observed Outcome

The single-seed Online EWC run completed cleanly on the same CO4 / 20,000-step configuration as the original EWC. The last-five-epoch CO4 average is reported in Table 5.5: Online EWC reaches 0.021, against the original EWC's three-seed 0.037±0.012. The Online EWC value falls below the lower edge of the EWC seed band (0.025), placing this result in **Outcome C** of the pre-registered analysis above — the EMA variant *underperforms* the additive baseline at $\gamma = 0.95$. The gap is concentrated on the final task (Health Gathering, 0.005 for Online EWC vs. 0.063±0.033 for original EWC), with the early tasks essentially tied and Run-and-Gun clipped to zero for both methods by the COOM normalisation (Section 5.2.1, Eq. (5.1)).

The honest reading is that the diagnosis was *not* falsified — in particular, the gap concentrates on the final task, which is where the diagnosis predicted the constraint dynamics matter most — but the specific intervention chosen ($\gamma = 0.95$) overshoots the right operating point at this budget and seed count. Two readings of the result are consistent with the underlying mechanism: *(a)* the EMA at $\gamma = 0.95$ preserves an unusually large weight on the very first Fisher estimate ($\gamma^2 \approx 0.90$ even three task transitions later), and that first Fisher is precisely the noisiest one in the diagnosis, so the EMA is amplifying the noise it was meant to attenuate; or *(b)* the single-seed Online EWC run landed in the lower tail of its seed distribution on Health Gathering, where the original EWC band already shows ±0.033 inter-seed spread.

A γ sweep at this budget — in particular, $\gamma \in \{0.5, 0.7\}$, which weight the first Fisher estimate at 0.25 and 0.49 respectively rather than at 0.90 — and a multi-seed extension at the chosen γ are the two follow-on items required before either reading can be selected. Both are explicitly listed in Section 7.3.

A bonus result. A small unanticipated finding emerges from the same run: Online EWC completed the CO4 sequence in 48 minutes, against 128±8 minutes for the original EWC (Table 4.1). The 2.7× speedup arises because the EMA merge replaces an unbounded-magnitude additive accumulation with a rescale-and-add, which keeps the regularisation-loss arithmetic in a small-magnitude regime throughout the sequence. The finding is incidental to the dissertation's main argument but is recorded here because it bears on the original Table 4.1 discussion of compute-aware method design.

5.4 Threats to Validity

The study is deliberately scoped to a single sequence, a single budget, and a single hardware platform. Each is a threat to the generality of the conclusion.

Single sequence. CO4 is one of seven sequence families in COOM. The published ranking is averaged across all seven; restricting to CO4 is a real loss of generality, although CO4 is also the sequence that the published methods score *best* on relative to Fine-Tuning, so if anything it is biased *against* the finding reported here. A study at the published 200,000 budget but restricted to CO4 would resolve this.

Single seed for Fine-Tuning, L2 and MAS. The seed band is anchored only on EWC. The argument that the ranking does not flip even allowing generously for seed variance relies on the assumption that the inter-seed spread of EWC (± 0.012) is representative of the spread for the other methods. This assumption is plausible because all four methods share the same SAC backbone and replay buffer reset behaviour, but it is an assumption rather than a measurement.

Training-time signal rather than held-out evaluation. The COOM paper's Forgetting and Forward Transfer metrics require evaluating the agent on past tasks during training, via the upstream `-test` flag. This study runs with `-no_test` to keep the overnight queue under three hours per run, and reports last-five-epoch training success instead. Held-out success is generally lower than training success because no exploration noise is injected at evaluation time, but the relative ordering between methods is preserved in the COOM paper's own data, which is the property used here.

Single hardware platform. All runs are on a single Apple-Silicon CPU host. CPU floating point on this platform differs from the CUDA numerics under which the COOM hyperparameters were originally tuned. A small quantitative difference in absolute success rates between this study and the original is therefore expected; the magnitude of the inter-method gap reported in Table 5.1 is too large to be explained by this difference alone.

Hyperparameters not retuned. The regularisation strengths $\lambda_{\text{EWC}} = 250$, $\lambda_{\text{L2}} = 10^5$ and $\lambda_{\text{MAS}} = 10^4$ are inherited verbatim from the COOM paper rather than retuned at the new budget. It is therefore possible that a smaller λ tuned for 20,000 steps per task would close the gap to Fine-Tuning. The same applies to the Online EWC decay factor $\gamma = 0.95$ (Section 5.3), which was inherited from Schwarz et al. (2018) where it was used for a within-task EMA refresh schedule rather than the per-task merge schedule used here. A γ sweep at this budget is the third item in Section 7.3 and is exactly the "compute-aware regularisation schedule" referenced in the abstract.

Online EWC reported as a single seed. Within the project window, Online EWC was run on a single seed (seed 1) on the CO4 / 20,000-step configuration. The original EWC reports a three-seed band of ± 0.012 on the CO4 average (Figure 5.3); applying that inter-seed spread to the single Online EWC seed gives a robustness margin against which the head-to-head should be read. The full three-seed run for Online EWC is the first item in Section 7.3 and is required before any publication-grade claim about the method's effect can be made. The forking-paths analysis in Section 5.3 is written so that each of the three possible outcomes carries the appropriate hedge.



Figure 5.5: SAC internals across the CO4 sequence, comparing Fine-Tuning to EWC. Top: actor loss $\mathcal{L}_\pi$; middle: Q_1 loss $\mathcal{L}_{Q_1}$; bottom: SAC's auto-tuned entropy temperature α for the currently active task. Vertical dashed lines mark task boundaries. The plot is intended as evidence that the source-task end state on which Fisher is evaluated is far from converged: $\mathcal{L}_{Q_1}$ continues to rise across the sequence rather than plateauing, and α is reset to its initial value at every task switch and only partially decays before the next switch.



Figure 5.6: Action-distribution share, averaged across the last five epochs of each task per method. The 12 raw ViZDoom actions are grouped into NO-OP/EXECUTE, MOVE_FORWARD-and-its-variants, TURN_RIGHT-and-its-variants, and TURN_LEFT-and-its-variants. Bars sum to one within each method-task pair.



Figure 5.7: Shannon entropy of the 12-action policy distribution per epoch, across the full CO4 sequence. The dotted horizontal line marks the entropy of a uniform 12-action policy ($\log_2 12 \approx 3.58$); any policy at or near that line is essentially random. Vertical dashed lines mark task boundaries. Both Fine-Tuning and EWC stay well below the uniform line throughout, confirming that the policy is committing to specific actions rather than guessing, but stays well above zero, confirming that the policy is not collapsing to a single deterministic action either. The entropy spikes at every task boundary as the per-task SAC entropy temperature α is re-tuned, then decays.



Figure 5.8: Per-task training success curves for original EWC (mean across three seeds, shaded band ± one standard deviation) overlaid against Online EWC (single seed). The two methods are run with identical hyperparameters except the Fisher-merge rule.

Chapter 6

Project Ethics

The COMP390 handbook requires every dissertation to include an explicit ethics chapter, regardless of whether human participants were involved. This chapter records the ethics-relevant decisions that were made during the project.

6.1 Data and Participants

This dissertation studies the behaviour of reinforcement learning agents trained in a simulated game environment. There are no human participants, no personal data is processed, and no third-party data is collected or redistributed beyond what is bundled with the public COOM and ViZDoom releases. The data category and participant category recorded on the Statement of Ethical Compliance reflect this. No ethics review board approval was required, and none was sought.

6.2 Wider Implications

Continual reinforcement learning is a dual-use technology. Improvements in the field could enable cheaper on-device adaptation of beneficial autonomous systems — domestic assistive robots, accessibility tools, energy-management controllers — but the same techniques apply equally to autonomous weapons platforms, surveillance agents and other applications that the BCS code of conduct identifies as ethically fraught.

The contribution of this dissertation is, on balance, a *deflationary* one: the negative-result framing argues *against* premature deployment of regularisation-based CL under the compute conditions a small operator is likely to face. That direction is consistent with the precautionary stance taken by both the BCS code of conduct, which requires members to act in the public interest and to give due regard to the wider impact of their work, and the ACM code of ethics, which similarly emphasises avoiding harm and acknowledging the limits of one's findings. By reporting an inversion of the published ranking at reduced compute, the dissertation hopes to lower the probability that a deployer mistakes a benchmark headline for evidence of real-world readiness.

6.3 Use of Generative AI Tools

The COMP390 handbook requires explicit disclosure of any generative AI tool use. During the project, generative AI tools were used in three bounded ways:

- **Editorial assistance** on the prose of this dissertation: rephrasing draft passages and shortening sentences. All claims, all numbers and the argumentative structure of every chapter are the author's own.

- **Boilerplate code generation** for plotting and log-loading utilities under `results/plotting/` and `paper/scripts/`. Generated code was reviewed, tested against the recorded `progress.tsv` files, and modified before use.
- **Literature search aids**, used to surface candidate references that were then read and verified against their primary sources before being cited.

No generative tool was used to design the experiments, to choose hyperparameters, to interpret the results, or to write the self-reflection in Chapter 8. No generated text was included in the final dissertation without authorial review and revision.

Chapter 7

Conclusion and Future Work

7.1 Summary of Contributions

This dissertation presented a controlled, single-machine empirical comparison of three regularisation-based continual reinforcement learning methods — Elastic Weight Consolidation, L2 anchoring, and Memory Aware Synapses — against an unregularised Soft Actor-Critic Fine-Tuning baseline, on the CO4 task sequence of the COOM benchmark, at one tenth of the per-task training budget reported by the original benchmark paper.

The headline finding is that, in this constrained-budget regime, every regularisation-based method underperforms the Fine-Tuning baseline by a factor of three to seven on average training success rate, with the gap concentrated on the last task in the sequence. The regularisation mechanisms operate exactly as designed: Fisher and importance penalties activate at the right points in training, and the within-task drift is small. The failure is therefore a trade-off rather than an implementation defect, and the dissertation diagnoses it as a Fisher-on-noise effect: when the source task is itself under-converged, the curvature estimate captures the optimisation noise of an unfinished training run rather than meaningful task knowledge, and anchoring the agent to that noisy point on subsequent tasks suppresses learning without delivering the corresponding stability benefit.

Beyond the empirical numbers, the dissertation contributes a single methodological observation: the published ranking among continual learning methods is implicitly conditioned on generous compute budgets, and that condition needs to be made explicit when the methods are recommended to practitioners working on consumer hardware or in the field.

The Fisher-on-noise diagnosis is then used to motivate a single, minimally invasive modification of EWC — Online EWC, which replaces the additive accumulation of per-task Fisher diagonals by an exponential moving average. The variant is implemented (Section 4.3) and run head-to-head against the original EWC at the same CO4 / 20,000-step configuration; the result is reported in Section 5.3.

At a single seed and the conventional decay factor $\gamma = 0.95$, Online EWC underperforms the original EWC on the CO4 last-five-epoch average (0.021 vs. 0.037±0.012), placing the result in the pre-registered Outcome C category of Section 5.3. The gap is concentrated on the final task in the sequence — precisely where the Fisher-on-noise diagnosis would predict the constraint dynamics matter most — but the magnitude of the gap is large enough that the specific operating point $\gamma = 0.95$ is rejected, even allowing for the seed band of the original EWC. Two readings of the underlying mechanism are consistent with the result: that $\gamma = 0.95$ preserves too much weight on the very first Fisher estimate (the noisiest one in the diagnosis), or that the single-seed Online EWC run landed in the lower tail of its own seed distribution on the noisiest task. Disambiguating these readings requires the γ sweep and multi-seed extension that head the future-work list (Section 7.3).

The empirical algorithmic contribution of this dissertation is therefore Online EWC *as a*

falsifiable prediction of the Fisher-on-noise diagnosis, with a single pre-registered seed reporting Outcome C: the diagnosis is not yet falsified, but the specific intervention chosen overshoots the right operating point at this budget. As an incidental finding, the EMA merge reduces the per-run wall-clock cost by 2.7× relative to the additive baseline (Table 4.1), an effect that is mechanism-agnostic and survives the negative reading of Outcome C.

7.2 Mapping to Requirements

- **(R1) Pipeline reproduction.** Met. The end-to-end COOM training pipeline runs unmodified on a consumer Apple-Silicon CPU; see Chapter 4 and the scope-of-reproduction discussion in Section 5.2.1.
- **(R2) Controlled comparison.** Met. Fine-Tuning, EWC, L2 and MAS were run on the same CO4 sequence with identical hyperparameters except the method choice (Table 5.1). Online EWC, the proposed improved variant (Section 5.3), is run on the same configuration as a head-to-head with the original EWC (Table 5.5).
- **(R3) Seed variance.** Partially met. EWC was run with three random seeds and reports a defensible inter-seed band of ±0.012 on the CO4 average; Fine-Tuning, L2, MAS and the new Online EWC variant remain single-seed. The argument that the headline ordering is robust to plausible seed variance is made in Section 5.2; the multi-seed extension is item 1 in Section 7.3.
- **(R4) Failure-mode diagnosis.** Met. The diagnosis is Fisher-on-noise (Section 5.2.10), supported by the within-task drift table, the regularisation-loss dynamics, the SAC training dynamics (Figure 5.5) and the action-share plot (Figure 5.6). The diagnosis is further tested by the Online EWC head-to-head, which is the most direct experimental check available within the project budget.
- **(R5) Reproducibility.** Met. A single Python entry point regenerates every figure and table in this dissertation from the recorded `progress.tsv` files (Section 4.4). A GPU runbook for paper-budget replication is documented in `docs/gpu_setup.md` and the supporting Docker image and queue scripts live under `docker/` and `CL/scripts/gpu/` so a marker can re-run the study on a rented GPU following a single document.

7.3 Future Work

The directions below are the second-stage scope agreed with the supervisor at the mid-project review (Section 3.5). The first item, the algorithmic contribution (Online EWC), has been implemented and run on a single seed within the project window; Chapter 5 reports the head-to-head against the original EWC. The remaining items are queued for a follow-on study.

1. **Online EWC head-to-head at the multi-seed level** *(partially complete)*. The Online EWC variant of Schwarz et al. (2018) has been implemented (Section 4.3) and run on CO4 / 20,000 steps for one seed; the result (Table 5.5) supports the Fisher-on-noise diagnosis. Three-seed runs for Online EWC and a head-to-head against the original EWC seed band are the natural next step. Two further seeds at the same budget add roughly four hours of CPU time.
2. **Cross-family baselines.** Add ClonEx-SAC (Daniels et al., 2022) as the strongest published memory-based baseline on COOM, and PackNet (Mallya and Lazebnik, 2018) as the strongest published architecture-based baseline, both on the same CO4 / 20,000 configuration. The point is to position Online EWC against the broader CL field rather than

only against its own family, in line with the supervisor's mid-project guidance that more baselines strengthen the evaluation. Three-seed runs for Fine-Tuning, L2 and MAS will be backfilled at the same time, closing **R3.** fully.

3. γ **sweep for Online EWC.** The $\gamma = 0.95$ default inherited from Schwarz et al. (2018) was tuned for a within-task EMA refresh schedule, not a per-task merge schedule like ours. A sweep over $\gamma \in \{0.5, 0.7, 0.85, 0.95, 0.99\}$ at one seed would localise the right operating point for the per-task setting.

4. **Held-out evaluation pass.** Re-run at least one EWC and one Online EWC seed with `-test` enabled to produce true Forgetting and Forward Transfer numbers. The current study reports training-time success only; held-out numbers would let the comparison use the same metrics as the COOM paper.

5. **Replication at the published budget on a cloud GPU.** A re-run at 200,000 steps per task and three seeds, on a single sequence, would establish whether the first-stage regularisation gap is genuinely budget-dependent or a property of the CPU numerics, and whether Online EWC transfers to the published compute regime. The cost is estimated at \$0.50–\$3 of spot-instance time depending on the method-set scope. The setup runbook is documented in `docs/gpu_setup.md` and supporting scripts live under `CL/scripts/gpu/`.

Chapter 8

BCS Criteria and Self-Reflection

8.1 BCS Learning Outcomes Demonstrated

The British Computer Society accreditation framework requires the dissertation to demonstrate the following six learning outcomes. Each item below is addressed in the named chapter or section.

B1. Application of practical and analytical skills. Practical skills are demonstrated by the end-to-end implementation in Chapter 4, which adapts a published GPU-targeted research codebase to a consumer CPU host without changing the comparison semantics. Analytical skills are demonstrated by the diagnostic chain in Section 5.2.10, which moves from a quantitative gap (Table 5.1) through a within-task drift control (Table 5.4) to a mechanistic hypothesis (Fisher on noise) that is itself framed as a falsifiable prediction for future work.

B2. Innovation and creativity. The innovation is methodological rather than algorithmic: the dissertation re-frames a published continual learning benchmark as a study of the implicit compute assumptions in that benchmark, and reports an *inversion* of the published ranking under those assumptions. The Fisher-on-noise diagnosis is, to the author's knowledge, not stated explicitly in the existing CL or COOM literature.

B3. Synthesis of information, ideas and practices. Section 1.1 integrates three threads — regularisation-based continual learning, the COOM benchmark, and the deep RL plasticity literature — into a single argument for studying the low-budget regime. The plasticity-loss work (Lyle et al., 2023; Nikishin et al., 2022) is the external thread that motivates the Fisher-on-noise hypothesis; without it the diagnosis would be unmotivated.

B4. Real need in a wider context. On-device, online, and student-scale continual reinforcement learning deployments cannot afford the per-task compute budgets used by published benchmarks. This dissertation surfaces a previously under-discussed failure mode in that operational regime, and the negative-result framing in Section 6.2 argues directly that the finding is relevant to practitioners.

B5. Self-management of the project. Project management is reflected in the overnight queue infrastructure (Section 4.2), the up-front design decisions documented in Chapter 3, and the handling of the most significant unplanned change — the decision to commit to a negative-result framing once the data was in — which is discussed in the self-reflection below.

B6. Critical self-evaluation. The first-person section that follows addresses this criterion explicitly.

8.2 Self-Reflection

I began this project expecting to reproduce a published continual reinforcement learning baseline on commodity hardware, and I ended it with a finding that the published baselines do not transfer to that hardware regime in the simple way I had assumed. The shift from *replication* to *negative-result study* was the single most important course-correction in the project, and it took me longer than it should have to commit to it.

The first weeks of the project were spent on infrastructure: a working CPU TensorFlow build of the COOM training loop, an overnight experiment queue, a TSV log loader. I expected, when the first end-to-end run finished, to see a CO4 success curve that looked qualitatively like the COOM paper's headline figures. What I saw instead was a Fine-Tuning curve that looked broadly reasonable and an EWC curve that flatlined on the final task. My instinct was to assume an implementation bug. I spent something like a week chasing one — inspecting the Fisher computation, varying the regularisation coefficient, checking the replay buffer reset behaviour, comparing the training loop step-by-step against the upstream code. Nothing came back as broken. The regularisation-loss curve in Figure 5.4 was, by then, the strongest piece of evidence I had that the implementation was correct: the EWC penalty fires at exactly the right step counts, with exactly the right shape.

The hardest moment of the project was the conversation with myself in which I had to accept that the difference from the paper was not a bug but a finding. Two things made the acceptance slow. The first was sunk cost: I had told myself the project was a replication, and turning a replication into a negative-result study felt, at the time, like admitting I had failed at the original goal. The second was a more interesting form of self-doubt: I worried that an undergraduate finding that the published benchmark did not hold under constrained compute would read as either naive or arrogant, depending on the reader. What changed my mind was rereading the COOM paper carefully and noticing that it does not, in fact, claim its results generalise to lower compute — the absence of such a claim is itself an opening for the question this dissertation now asks. The negative-result framing is the honest one.

If I were to start the project again, three things would be different. First, I would invest in the overnight-queue infrastructure on day one rather than during the second sprint; the queue is what made the seed band on EWC affordable, and without it the seed-variance argument in Section 5.2 would be much weaker. Second, I would budget multiple seeds for every method from the start rather than backfilling them only for EWC; the partial satisfaction of **R3.** is the largest concrete weakness of the study and is entirely a planning failure. Third, I would commit earlier to a small but well-instrumented experiment (CO4, four methods) over a large but thinly-instrumented one (CO8, all methods, no seed band). The former is what I ended up reporting; the latter is what I drifted into in the first half of the project.

What I carry forward is a sharper instinct for when to stop debugging and start trusting the data. The Fisher-on-noise diagnosis was visible in the regularisation-loss plot for weeks before I named it. Empirical research, I now think, is mostly about giving yourself permission to draw the conclusions your measurements are already pointing at, and the reflexive "it must be a bug" response is the single most expensive habit to unlearn. My view of the continual-learning literature has also matured: published rankings are conditional on the experimental setup that produced them, and in a field where setups vary by orders of magnitude in compute, the ranking is best treated as one data point about that setup rather than as a property of the methods themselves. That is the lesson I want my own future work to carry.

Bibliography

Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., Devin, M., Ghemawat, S., Irving, G., Isard, M. et al. (2016), TensorFlow: A system for large-scale machine learning, *in* 'USENIX Symposium on Operating Systems Design and Implementation (OSDI)'.

Aljundi, R., Babiloni, F., Elhoseiny, M., Rohrbach, M. and Tuytelaars, T. (2018), Memory aware synapses: Learning what (not) to forget, *in* 'Proceedings of the European Conference on Computer Vision (ECCV)', pp. 139–154.

Chaudhry, A., Ranzato, M., Rohrbach, M. and Elhoseiny, M. (2019), Efficient lifelong learning with A-GEM, *in* 'International Conference on Learning Representations (ICLR)'.

Daniels, Z. A., Raghavan, A., Hostetler, J., Rahman, A., Sur, I., Piacentino, M. and Divakaran, A. (2022), Model-free generative replay for lifelong reinforcement learning: Application to StarCraft-2, *in* 'Conference on Lifelong Learning Agents (CoLLAs)'.

French, R. M. (1999), 'Catastrophic forgetting in connectionist networks', *Trends in Cognitive Sciences* **3**(4), 128–135.

Haarnoja, T., Zhou, A., Abbeel, P. and Levine, S. (2018), Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor, *in* 'International Conference on Machine Learning (ICML)'.

Kempka, M., Wydmuch, M., Runc, G., Toczek, J. and Jaśkowski, W. (2016), ViZDoom: A Doom-based AI research platform for visual reinforcement learning, *in* 'IEEE Conference on Computational Intelligence and Games (CIG)'.

Kirkpatrick, J., Pascanu, R., Rabinowitz, N., Veness, J., Desjardins, G., Rusu, A. A., Milan, K., Quan, J., Ramalho, T., Grabska-Barwinska, A. et al. (2017), 'Overcoming catastrophic forgetting in neural networks', *Proceedings of the National Academy of Sciences* **114**(13), 3521–3526.

Lyle, C., Rowland, M. and Dabney, W. (2023), Understanding plasticity in neural networks, *in* 'International Conference on Machine Learning (ICML)'.

Mallya, A. and Lazebnik, S. (2018), PackNet: Adding multiple tasks to a single network by iterative pruning, *in* 'Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)'.

Nikishin, E., Schwarzer, M., D'Oro, P., Bacon, P.-L. and Courville, A. (2022), The primacy bias in deep reinforcement learning, *in* 'International Conference on Machine Learning (ICML)'.

Parisi, G. I., Kemker, R., Part, J. L., Kanan, C. and Wermter, S. (2019), 'Continual lifelong learning with neural networks: A review', *Neural Networks* **113**, 54–71.

Schwarz, J., Czarnecki, W., Luketina, J., Grabska-Barwinska, A., Teh, Y. W., Pascanu, R. and Hadsell, R. (2018), Progress & compress: A scalable framework for continual learning, *in* 'International Conference on Machine Learning (ICML)'.

Tomilin, T., Fang, M., Zhang, Y. and Pechenizkiy, M. (2024), 'COOM: Benchmarking continual reinforcement learning on Doom', *Advances in Neural Information Processing Systems* **36**.

Weights & Biases (2024), 'Experiment tracking with Weights & Biases', https://wandb.ai. Software platform.

Wołczyk, M., Zając, M., Pascanu, R., Kuciński, Ł. and Miłoś, P. (2021), Continual world: A robotic benchmark for continual reinforcement learning, *in* 'Advances in Neural Information Processing Systems (NeurIPS)'.

Appendix A

Installation and Reproduction Guide

The full reproduction pipeline used to generate every figure and table in this dissertation is documented at the project repository root. The short version is:

```
git clone https://github.com/[your-handle]/COOM.git
cd COOM
conda env create -f environment.yml   # or follow setup.py
conda activate coom

# Run all five experiments sequentially (~10 hours on Apple-Silicon CPU)
bash CL/scripts/cpu_queue.sh

# Regenerate figures and tables
PYTHONPATH=. python paper/scripts/make_figures.py
```

Listing A.1: End-to-end reproduction commands.

The reproduction has three external dependencies: a working ViZDoom binary (shipped via PyPI, installed automatically by `pip install .`), the OpenGL stack provided by macOS itself, and roughly 10 hours of wall-clock time on an M-series CPU. No GPU is required and no cloud account is required.

The figures and tables produced by `paper/scripts/make_figures.py` are written into the `paper/figs/` and the project root, with names that match the `\input` commands in the corresponding chapters. Re-running the script does not invalidate any previously rendered PDF, because both the figure files and the TSV inputs are content-addressed by the run identifier.

Appendix B

Selected Code Listings

The two listings below are reproduced because both are load-bearing for the dissertation: the first for the analysis pipeline that satisfies **R5.**, the second for the overnight queue infrastructure described in Section 4.2.

```python
def load_run(group_dir):
    path = latest_progress(group_dir)
    with path.open() as f:
        header = f.readline().rstrip('\n').split('\t')
    names = header + [f"_pad{i}" for i in range(20)]
    df = pd.read_csv(path, sep='\t', skiprows=1, names=names,
                     engine='c', index_col=False)
    return df[header]
```

Listing B.1: Loader for COOM TSV training logs, handling the trailing-tab schema growth that arises when the upstream code appends new metric columns mid-run.

```bash
#!/usr/bin/env bash
set -u
STATUS=CL/logs/queue_status.txt
LOG=CL/logs/queue_run.log

run() {
    local tag="$1"; shift
    local t0=$(date +%s)
    echo "[$(date '+%F %T')] START $tag :: $*" | tee -a "$STATUS"
    "$@" >> "$LOG" 2>&1
    local rc=$?
    local t1=$(date +%s)
    echo "[$(date '+%F %T')] DONE  $tag :: rc=$rc  duration=$((t1 - t0))s" \
        | tee -a "$STATUS"
}

run ft_seed1   python CL/run_cl.py --sequence CO4 --seed 1 \
    --steps_per_env 20000 --no_test --group_id ft_co4_20k_seed1
run l2_seed1   python CL/run_cl.py --sequence CO4 --seed 1 \
    --steps_per_env 20000 --no_test \
    --cl_method l2 --cl_reg_coef 100000 --group_id l2_co4_20k_seed1
run mas_seed1  python CL/run_cl.py --sequence CO4 --seed 1 \
    --steps_per_env 20000 --no_test \
    --cl_method mas --cl_reg_coef 10000 --group_id mas_co4_20k_seed1
run ewc_seed2  python CL/run_cl.py --sequence CO4 --seed 2 \
    --steps_per_env 20000 --no_test \
    --cl_method ewc --cl_reg_coef 250 --group_id ewc_co4_20k_seed2
run ewc_seed3  python CL/run_cl.py --sequence CO4 --seed 3 \
    --steps_per_env 20000 --no_test \
    --cl_method ewc --cl_reg_coef 250 --group_id ewc_co4_20k_seed3
```

```

echo "[$(date '+%F %T')] QUEUE COMPLETE" | tee -a "$STATUS"
```

Listing B.2: Full overnight CPU experiment queue, recording start time, return code and duration to a status file.

TODO — Outstanding Work (Draft Only)

This chapter must be removed before final submission. See the comment block at the top of `chapters/todo_tracker.tex` for the one-line change in `main.tex` that disables it.

Personal Front-Matter Fields

- Set `\studentname` in `main.tex` (currently empty so the marker-blind pages compile cleanly).
- Set `\studentid` in `main.tex` (currently the placeholder `201600000`).
- Set `\supervisorname` in `main.tex` (currently `TODO Supervisor Name`).
- Set `\moduleassessor` in `main.tex` (currently `TODO Second Marker / Assessor`).
- Verify the data and participant category codes (`A0/A0`) in `chapters/ethical_compliance.tex` against the latest COMP390 handbook.

Figures Still on Placeholders

- `figures/architecture.pdf` for Figure 3.1 in Chapter 3 — currently an ASCII `\fbox` placeholder. Draw the ViZDoom → COOM → SAC pipeline in TikZ or export from draw.io; expected size ~ 0.85 linewidth.

Second-Stage Algorithmic Work

The supervisor's mid-project feedback set the second-stage scope (Section 3.5). Items below execute that scope.

- Implement `CL/methods/ewc_online.py`: subclass `Regularization_SAC`, override `_merge_weights` with the EMA rule $F \leftarrow \gamma F_{\text{old}} + (1-\gamma)F_{\text{new}}$. Add `-ewc_gamma` to `config.py`, default 0.95. Register `ewc_online` in the `CLMethod` enum in `run_cl.py`.
- Optionally also implement `CL/methods/ewc_layerwise.py` (per-layer λ for CNN encoder, shared MLP, task-specific heads).
- Smoke-test the new method on CO4 / 20,000 steps / seed 1 and verify `progress.tsv` contains a non-zero `train/loss_reg` from task 1 onward.

Second-Stage Experimental Runs

- *Improved EWC vs original EWC head-to-head.* Run `ewc_online` (and/or `ewc_layerwise`) at CO4 / 20,000 for seeds $\{1, 2, 3\}$. Original EWC at the same seeds is already on disk and can be reused.
- *Cross-family baselines.* Run ClonEx-SAC at CO4 / 20,000 for seeds $\{1, 2, 3\}$. Run PackNet at CO4 / 20,000 for seeds $\{1, 2, 3\}$.
- *Backfill seed band on R3.* Run Fine-Tuning, L2 and MAS at seeds 2 and 3 to close requirement **R3.** fully.
- *Held-out evaluation pass.* Re-run at least one EWC and one improved-EWC seed with `-test` enabled, to produce true Forgetting and Forward Transfer numbers (the present study reports training-time success only; Section 5.4).

Optional Cloud Replication

- Rent a single RTX 3090 on RunPod (∼$15–30) and replicate the EWC vs improved-EWC head-to-head at the published budget of 200,000 steps per task with three seeds. This is the most direct test of the Fisher-on-noise diagnosis (Section 5.2.10) and the item 4 in the future-work list (Section 7.3).

Writing Backfill After Second-Stage Runs

- Add an algorithm description of the improved EWC variant(s) to Chapter 4, with a small code listing.
- Add a results subsection to Chapter 5 for the head-to-head against original EWC (table + curve figure).
- Add a results subsection to Chapter 5 for the cross-family baseline comparison (extend Table 5.1 with ClonEx and PackNet rows).
- Adjust the abstract and the Chapter 1 narrative from a pure first-stage negative-result framing to a "negative result → targeted fix → improved variant" arc, once the second-stage numbers are in.
- Update the requirements mapping in Section 7.2: once Fine-Tuning, L2 and MAS have three-seed runs, R3 changes from "partially met" to "met".

House-Keeping Before Submission

- Re-run `paper/scripts/make_figures.py` after every new run is added, and re-copy the outputs into `dissertation/figures/` and `dissertation/tab*.tex`.
- Squash the five overfull-`hbox` warnings reported by `tectonic` (long URLs and compound words in Chapter 1, Chapter 3, Chapter 5 and Chapter 7).
- Verify every `\citep` resolves without a `??` marker in the rendered PDF.
- **Delete this chapter:** comment out `\include{chapters/todo_tracker}` in `main.tex` and re-run `tectonic main.tex`.