Status	Finished
Started	Sunday, 23 August 2026, 4:20 PM
Completed	Thursday, 27 August 2026, 11:59 PM
Duration	4 days 7 hours
Marks	3.00/6.00
Grade	**5.00** out of 10.00 (**50**%)

Question 1

Correct

Mark 1.00 out of 1.00

What is the purpose of the following instruction? `MOV R8, #0`

a. To subtract 0 from register R8.

b. To compare R8 to 0.

c. To add 0 to register R8.

d. To clear register R8 (set its value to 0). ✓

Your answer is correct.

The correct answer is: To clear register R8 (set its value to 0).

Question 2

Correct

Mark 1.00 out of 1.00

The instruction `ADD R2, R2, R1` is executed. If R2 contains 15 and R1 contains 5, what will be the new value in R2?

a. 15

b. 10

c. 5

d. 20 ✓

Your answer is correct.

The correct answer is: 20

Question 3

Correct

Mark 1.00 out of 1.00

What is the R5 value after this instruction is executed? `SUB R5, R5, #10` Assume R5 initially contained the value 25.

a. 25

b. 35

c. 10

d. 15 ✓

Your answer is correct.

The correct answer is: 15

Question 4

Not answered

Marked out of 1.00

An ARM data processing instruction has the hex value `0xE3A01064`. What operation does this instruction perform?

a. SUB R1, R0, #100

b. MOV R0, #100

c. MOV R1, #100

d. ADD R1, R2, #100

Your answer is incorrect.

The correct answer is: MOV R1, #100

Question 5

Not answered

Marked out of 1.00

An ARM instruction has the hex value `0x0A00000F`. What does this instruction do?

a. Add (ADD)

b. Subtract (SUB)

c. Branch if Not Equal (BNE)

d. Branch if Equal (BEQ)

Your answer is incorrect.

The correct answer is: Branch if Equal (BEQ)

Question 6

Incorrect

Mark 0.00 out of 1.00

After an assembly program completes, its result of 21 * 10 is stored in R0. What is the hexadecimal value of the result?

a. 0xD2

b. 0x132

c. 0x210

d. 0xAA

Your answer is incorrect.

The correct answer is: 0xD2