

绪论

渐进复杂度：多项式

Computational problems can be feasibly computed on some computational device only if they can be computed in polynomial time.

- A. Cobham & J. Edmonds

邓俊辉

deng@tsinghua.edu.cn

$O(1)$: constant

❖ 常数

//含RAM各基本操作

- $2 = 2019 = 2019 \times 2019 = O(1)$, 甚至
- $2019^{2019} = O(1)$

❖ 从渐进的角度来看, 再大的常数, 也要小于递增的变数

//尽管实际并非如此...

❖ [General twin prime conjecture, de Polignac 1849]

For every natural number k , there are infinitely many prime pairs p and q such that $p - q = 2k$

❖ [Yitang Zhang, April 2013] $k \leq 35,000,000$

❖ [Terence Tao, May 2013] $k \leq 6,500,000$

❖ [Polymath Project, April 2014] $k \leq 123$

$O(1)$: constant

❖ 这类算法的效率最高

// 总不能奢望不劳而获吧

❖ 什么样的代码段对应于常数执行时间？

// 应具体分析...

❖ 一定不含循环？

```
for ( i = 0; i < n; i += n/2019 + 1 );
```

// 2019, 常数

```
for ( i = 1; i < n; i = 1 << i );
```

// $\log^* n$, 几乎常数

❖ 一定不含分支转向？

```
if ( (n + m) * (n + m) < 4 * n * m ) goto UNREACHABLE;
```

// 不考虑溢出

❖ 一定不能有（递归）调用？

```
if ( 2 == (n * n) % 5 ) O1op(n);
```

// $O(1)$ -time Operation

...

$\mathcal{O}(\log^c n)$: poly-log

❖ 对数 $\mathcal{O}(\log n)$: $\ln n$ $\lg n$ $\log_{100} n$ $\log_{2017} n$ //为何不注明底数？

❖ 常底数无所谓 : $\forall a, b > 1, \log_a n = \boxed{\log_a b} \cdot \log_b n = \Theta(\log_b n)$

❖ 常数次幂无所谓 : $\forall c > 0, \log n^c = c \cdot \log n = \Theta(\log n)$

❖ 对数多项式 : $123 \cdot \log^{321} n + \log^{205} (7 \cdot n^2 - 15 \cdot n + 31) = \Theta(\log^{321} n)$

❖ 这类算法非常有效，复杂度无限接近于常数 : $\forall c > 0, \log n = \mathcal{O}(n^c)$

$\mathcal{O}(n^c)$: polynomial

❖ 多项式 : $a_k \cdot n^k + a_{k-1} \cdot n^{k-1} + \cdots + a_2 \cdot n^2 + a_1 \cdot n + a_0 = \mathcal{O}(n^k), \quad a_k > 0$

$$100 \cdot n + 203 = \mathcal{O}(n) \quad \sqrt{23 \cdot n - 472} \times \sqrt{101 \cdot n + 203} = \mathcal{O}(n)$$

$$(100 \cdot n - 532) \cdot (20 \cdot n^2 - 445 \cdot n + 2019) = \mathcal{O}(n^3)$$

$$(2019 \cdot n^2 - 129) / (1991 \cdot n - 37) = \mathcal{O}(n)$$

$$\sqrt[3]{2 \cdot n^3 - \sqrt[3]{3 \cdot n^4 - \sqrt[3]{4 \cdot n^5 + \sqrt[3]{5 \cdot n^6 + \sqrt[3]{6 \cdot n^7 + \sqrt[3]{7 \cdot n^8 + \sqrt[3]{8 \cdot n^9 + n^{2019} / \sqrt{n^6 - 5 \cdot n^3 + 1970}}}}} = \mathcal{O}(n^7)$$

❖ 线性 (linear function) : 所有 $\mathcal{O}(n)$ 类函数

❖ 从 $\mathcal{O}(n)$ 到 $\mathcal{O}(n^2)$: 本课程编程习题主要覆盖的范围

❖ 这类算法的效率通常认为已可令人满意 , 然而... 这个标准是否太低了 ?

//P难度!