

*Title:* HM Software Manual  
*Status:* Software AHG working document  
*Purpose:* Information  
*Author(s):* Frank Bossen *frank@bossentech.com*  
David Flynn *dflynn@blackberry.com*  
Karl Sharman *karl.sharman@eu.sony.com*  
Karsten Sühring *karsten.suehring@hhi.fraunhofer.de*  
*Source:* AHG chairs

---

## Abstract

This document is a user manual describing usage of reference software for the HEVC project. It applies to version 16.1 of the software.

## Contents

<b>1 General Information</b>	<b>2</b>
<b>2 Installation and compilation</b>	<b>2</b>
<b>3 Using the encoder</b>	<b>3</b>
3.1 GOP structure table . . . . .	3
3.2 Encoder parameters . . . . .	6
3.3 Encoder SEI parameters . . . . .	17
3.4 Hardcoded encoder parameters . . . . .	25
<b>4 Using the decoder</b>	<b>26</b>
4.1 General . . . . .	26
4.2 Using the decoder analyser . . . . .	27

## List of Tables

1 Available project files . . . . .	2
2 GOP structure example . . . . .	5
3 File, I/O and source parameters. . . . .	6
4 Profile and level parameters . . . . .	8
5 Unit definition parameters . . . . .	8
6 Coding structure parameters . . . . .	9
7 Motion estimation parameters . . . . .	9
8 Mode decision parameters . . . . .	10
9 Quantization parameters . . . . .	10
10 Slice coding parameters . . . . .	11
11 Deblocking filter parameters . . . . .	12
12 Coding tools parameters . . . . .	12
13 Rate control parameters . . . . .	14
14 VUI parameters . . . . .	14
15 Range Extensions (Version 2) tool parameters . . . . .	16
16 List of Version 1 and RExt SEI messages . . . . .	17
17 Buffering period SEI message encoder parameters . . . . .	18
18 Picture timing SEI message encoder parameters . . . . .	18
19 Recovery point SEI message encoder parameters . . . . .	18
20 Tone mapping information SEI message encoder parameters . . . . .	18

21	Frame packing arrangement SEI message encoder parameters . . . . .	20
22	Display orientation SEI message encoder parameters . . . . .	21
23	Structure of pictures information SEI message encoder parameters . . . . .	21
24	Active parameter sets SEI message encoder parameters . . . . .	21
25	Decoding unit information SEI message encoder parameters . . . . .	21
26	Temporal sub-layer zero index SEI message encoder parameters . . . . .	21
27	Decoded picture hash SEI message encoder parameters . . . . .	21
28	Scalable nesting SEI message encoder parameters . . . . .	22
29	Region refresh information SEI message encoder parameters . . . . .	22
30	No display SEI message encoder parameters . . . . .	22
31	Time code SEI message encoder parameters . . . . .	22
32	Mastering display colour volume SEI message encoder parameters . . . . .	23
33	Segmented rectangular frame packing arrangement SEI message encoder parameters . . . . .	23
34	Temporal motion-constrained tile sets SEI message encoder parameters . . . . .	24
35	Chroma resampling filter hint SEI message encoder parameters . . . . .	24
36	Knee function SEI message encoder parameters . . . . .	24
37	CommonDef.h constants . . . . .	25
38	Decoder options . . . . .	26

## 1 General Information

Reference software is being made available to provide a reference implementation of the HEVC standard being developed by the Joint Collaborative Team on Video Coding (JCT-VC) regrouping experts from ITU-T SG 16 and ISO/IEC SC29 WG11. One of the main goals of the reference software is to provide a basis upon which to conduct experiments in order to determine which coding tools provide desired coding performance. It is not meant to be a particularly efficient implementation of anything, and one may notice its apparent unsuitability for a particular use. It should not be construed to be a reflection of how complex a production-quality implementation of a future HEVC standard would be.

This document aims to provide guidance on the usage of the reference software. It is widely suspected to be incomplete and suggestions for improvements are welcome. Such suggestions and general inquiries may be sent to the general JCT-VC email reflector on [jct-vc@lists.rwth-aachen.de](mailto:jct-vc@lists.rwth-aachen.de) (registration required).

### Bug reporting

Bugs should be reported on the issue tracker set up at <http://hevc.kw.bbc.co.uk/trac/>

## 2 Installation and compilation

The software may be retrieved from one of the following SVN servers (mirrored):

- [https://hevc.hhi.fraunhofer.de/svn/svn\\_HEVCSoftware/](https://hevc.hhi.fraunhofer.de/svn/svn_HEVCSoftware/)
- <svn://hevc.kw.bbc.co.uk/svn/jctvc-hm/>

Table 1 enumerates various project files that are provided for development environments.

Table 1: Available project files

Environment	Location of project file
MS Visual Studio 8	build/HM_vc8.sln
MS Visual Studio 9	build/HM_vc9.sln
MS Visual Studio 10	build/HM_vc10.sln
Xcode	HM.xcodeproj
Linux	build/linux/makefile

For encoding large picture sizes (like UHDTV) it is strongly advised to build 64-bit binaries and to use a 64-bit OS. This will allow the software to use more than 2GB of RAM.

### 3 Using the encoder

TAppEncoder [--help] [-c config.cfg] [--parameter=value]

Option	Description
--help	Prints parameter usage.
-c	Defines configuration file to use. Multiple configuration files may be used with repeated -c options.
--parameter=value	Assigns value to a given parameter as further described below. Some parameters are also supported by shorthand “-opt value”. These are shown in brackets after the parameter name in the tables of this document

Sample configuration files are provided in the `cfg/` folder. Parameters are defined by the last value encountered on the command line. Therefore if a setting is set via a configuration file, and then a subsequent command line parameter changes that same setting, the command line parameter value will be used.

#### 3.1 GOP structure table

Defines the cyclic GOP structure that will be used repeatedly throughout the sequence. The table should contain `GOPSize` lines, named `Frame1`, `Frame2`, etc. The frames are listed in decoding order, so `Frame1` is the first frame in decoding order, `Frame2` is the second and so on. Among other things, the table specifies all reference pictures kept by the decoder for each frame. This includes pictures that are used for reference for the current picture as well as pictures that will be used for reference in the future. The encoder will not automatically calculate which pictures have to be kept for future references, they must be specified. Note that some specified reference frames for pictures encoded in the very first GOP after an IDR frame might not be available. This is handled automatically by the encoder, so the reference pictures can be given in the GOP structure table as if there were infinitely many identical GOPs before the current one. Each line in the table contains the parameters used for the corresponding frame, separated by whitespace:

**Type:** Slice type, can be either I, P or B.

**POC:** Display order of the frame within a GOP, ranging from 1 to `GOPSize`.

**QPOffset:** QP offset is added to the QP parameter to set the final QP value to use for this frame.

**QPFactor:** Weight used during rate distortion optimization. Higher values mean lower quality and less bits. Typical range is between 0.3 and 1.

**tcOffsetDiv2:** In-loop deblocking filter parameter `tcOffsetDiv2` is added to the base parameter `LoopFilterTcOffset_div2` to set the final `tc_offset_div2` parameter for this picture signalled in the slice segment header. The final value of `tc_offset_div2` shall be an integer number in the range  $-6..6$ .

**betaOffsetDiv2:** In-loop deblocking filter parameter `betaOffsetDiv2` is added to the base parameter `LoopFilterBetaOffset_div2` to set the final `beta_offset_div2` parameter for this picture signalled in the slice segment header. The final value of `beta_offset_div2` shall be an integer number in the range  $-6..6$ .

**temporal\_id:** Temporal layer of the frame. A frame cannot predict from a frame with a higher temporal id. If a frame with higher temporal IDs is listed among a frame’s reference pictures, it is not used, but is kept for possible use in future frames.

**num\_ref\_pics\_active:** Size of reference picture lists L0 and L1, indicating how many reference pictures in each direction that are used during coding.

**num\_ref\_pics:** The number of reference pictures kept for this frame. This includes pictures that are used for reference for the current picture as well as pictures that will be used for reference in the future.

**reference\_pictures:** A space-separated list of `num_ref_pics` integers, specifying the POC of the reference pictures kept, relative the POC of the current frame. The picture list shall be ordered,

first with negative numbers from largest to smallest, followed by positive numbers from smallest to largest (e.g. -1 -3 -5 1 3). Note that any pictures not supplied in this list will be discarded and therefore not available as reference pictures later.

**predict:** Defines the value of the syntax element `inter_ref_pic_set_prediction_flag`. A value of 0 indicates that the reference picture set is encoded without inter RPS prediction and the subsequent parameters `deltaRIdx-1`, `deltaRPS`, `num_ref_ids` and `Reference_ids` are ignored and do not need to be present. A value of 1 indicates that the reference picture set is encoded with inter prediction RPS using the subsequent parameters `deltaRIdx-1`, `deltaRPS`, `num_ref_ids` and `Reference_ids` in the line. A value of 2 indicates that the reference picture set is encoded with inter RPS but only the `deltaRIdx-1` parameters is needed. The `deltaRPS`, `num_ref_ids` and `Reference_ids` values are automatically derived by the encoder based on the POC and `refPic` values of the current line and the RPS pointed to by the `deltaRIdx-1` parameters.

**deltaRIdx-1:** The difference between the index of the current RPS and the predictor RPS minus 1.


**deltaRPS:** The difference between the POC of the predictor RPS and POC the current RPS.

**num\_ref\_ids:** The number of `ref_ids` to encode for the current RPS. The value is equal to the value of `num_ref_pics` of the predictor RPS plus 1.

**reference\_ids:** A space-separated list of `num_ref_ids` integers, specifying the `ref_ids` of the inter RPS prediction. The value of `ref_ids` may be 0, 1 or 2 indicating that the reference picture is a reference picture used by the current picture, a reference picture used for future picture or not a reference picture anymore, respectively. The first `num_ref_pics` of `ref_ids` correspond to the Reference pictures in the predictor RPS. The last `ref_ids` corresponds to the predictor picture.

For example, consider the coding structure of Figure 1. This coding structure is of size 4. The pictures are listed in decoding order. Frame1 shall therefore describe picture with POC = 4. It references picture 0, and therefore has -4 as a reference picture. Similarly, Frame2 has a POC of 2, and since it references pictures 0 and 4, its reference pictures are listed as -2 2. Frame3 is a special case: even though it only references pictures with POC 0 and 2, it also needs to include the picture with POC 4, which must be kept in order to be used as a reference picture in the future. The reference picture list for Frame3 therefore becomes -1 1 3. Frame4 has a POC of 3 and its list of reference pictures is -1 1.

Figure 1: A GOP structure



Inter RPS prediction may be used for Frame2, Frame3 and Frame4, hence the `predict` parameter is set to 1 for these frames. Frame2 uses Frame1 as the predictor hence the `deltaRIdx-1` is 0. Similarly for Frame3 and Frame4 which use Frame2 and Frame3 as predictors, respectively. The `deltaRPS` is equal to the POC of the predictor minus the POC of the current picture, therefore the `deltaRPS` for Frame2 is  $4 - 2 = 2$ , for Frame3 is  $2 - 1 = 1$  and for Frame4 is  $1 - 3 = -2$ .

In Frame2, reference pictures with POC 0 and 2 are used, so the reference ids for Frame2 are 1 1 indicating that the reference picture, -4, in Frame1 is still a reference picture in Frame2 and Frame1 is also a reference picture in Frame2. The reference ids for Frame3 are 1 1 1. The first and second "1"s indicating that the reference pictures "-2 2" in Frame2 are still reference pictures in Frame3 and the last "1" indicating that Frame2 is also a reference picture in Frame3. In Frame 4, the reference ids are 0 1 1 0. The first "0" indicates that the reference pictures "-1" in Frame 3 is no longer a reference

picture in Frame4. The next two “1”s indicate that the reference pictures “1 3” are now reference pictures of Frame4. The final “0” indicates that Frame3 is not a reference picture.

In order to specify this to the encoder, the parameters in Table 2 could be used.

Table 2: GOP structure example

	Frame1	Frame2	Frame3	Frame4
Type	P	B	B	B
POC	4	2	1	3
QPoffset	1	2	3	3
QPfactor	0.5	0.5	0.5	0.5
tcOffsetDiv2	0	1	2	2
betaOffsetDiv2	0	0	0	0
temporal_id	0	1	2	2
num_ref_pics_active	1	1	1	1
num_ref_pics	1	2	3	2
reference_pictures	-4	-2 2	-1 1 3	-1 1
predict	0	1	1	1
deltaRIdx-1		0	0	0
deltaRPS		2	1	-2
num_ref_idcs		2	3	4
reference_idcs		1 1	1 1 1	0 1 1 0

Here, the frames used for prediction have been given higher quality by assigning a lower QP offset. Also, the non-reference frames have been marked as belonging to a higher temporal layer, to make it possible to decode only every other frame. Note: each line should contain information for one frame, so this configuration would be specified as:

```

Frame1: P 4 1 0.5 0 0 0 1 1 -4 0
Frame2: B 2 2 0.5 1 0 1 1 2 -2 2 1 0 2 2 1 1
Frame3: B 1 3 0.5 2 0 2 1 3 -1 1 3 1 0 1 3 1 1 1
Frame4: B 3 3 0.5 2 0 2 1 2 -1 1 1 0 -2 4 0 1 1 0

```

The values of  $\text{deltaRIdx}_K - 1$ ,  $\text{deltaRPS}_K$ ,  $\text{num\_ref\_idcs}_K$  and  $\text{reference\_idcs}_K$  of  $\text{Frame}_K$  can be derived from the POC value of  $\text{Frame}_K$  and the POC,  $\text{num\_ref\_pics}_M$  and  $\text{reference\_pictures}_M$  values of  $\text{Frame}_M$ , where  $K$  is the index of the RPS to be inter coded and the  $M$  is the index of the reference RPS, as follows.

```

deltaRIdxK - 1 ← K - M - 1 ;
deltaRPSK ← POCM - POCK ;
num_ref_idcsK ← num_ref_picsM + 1 ;
for j ← 0 to num_ref_picsM do
    for i ← 0 to num_ref_idcsK do
        if reference_picturesM,j + deltaRPSK == reference_picturesK,i then
            if reference_picturesK,i is used by the current frame then reference_idcsK,j = 1 ;
            else reference_idcsK,j = 2 ;
        else
            reference_idcsK[j] = 0 ;
        end
    end
end
/* reference_picturesM,num_ref_picsM does not exist and is assumed to be 0 */

```

Note: The above (automatic) generation of the inter RPS parameter values has been integrated into the encoder, and is activated by the value of  $\text{predict} = 2$  followed by the value of  $\text{deltaRIdx} - 1$ , only, as described above.

## 3.2 Encoder parameters

Shorthand alternatives for the parameter that can be used on the command line are shown in brackets after the parameter name.

Table 3: File, I/O and source parameters.

Option	Default	Description
InputFile (-i)		Specifies the input video file. Video data must be in a raw 4:2:0, or 4:2:2 planar format, 4:4:4 planar format (Y'CbCr, RGB or GBR), or in a raw 4:0:0 format. Note: When the bit depth of samples is larger than 8, each sample is encoded in 2 bytes (little endian, LSB-justified).
BitstreamFile (-b)		Specifies the output coded bit stream file.
ReconFile (-o)		Specifies the output locally reconstructed video file.
SourceWidth (-wdt)	0	Specifies the width and height of the input video in luma samples.
SourceHeight (-hgt)	0	
InputBitDepth	8	Specifies the bit depth of the input video.
MSBExtendedBitDepth	0	Extends the input video by adding MSBs of value 0. When 0, no extension is applied and the InputBitDepth is used. The MSBExtendedBitDepth becomes the effective file InputBitDepth for subsequent processing.
InternalBitDepth	0	Specifies the bit depth used for coding. When 0, the setting defaults to the value of the MSBExtendedBitDepth. If the input video is a different bit depth to InternalBitDepth, it is automatically converted by: $\left\lfloor \frac{Pel * 2^{InternalBitDepth}}{2^{MSBExtendedBitDepth}} \right\rfloor$ <p>Note: The effect of this option is as if the input video is externally converted to the MSBExtendedBitDepth and then to the InternalBitDepth and then coded with this value as InputBitDepth. The codec has no notion of different bit depths.</p>
OutputBitDepth	0	Specifies the bit depth of the output locally reconstructed video file. When 0, the setting defaults to the value of InternalBitDepth. Note: This option has no effect on the decoding process.
InputBitDepthC	0	Specifies the various bit-depths for chroma components. These only need to be specified if non-equal luma and chroma bit-depth processing is required. When 0, the setting defaults to the corresponding non-Chroma value.
MSBExtendedBitDepthC	0	
InternalBitDepthC	0	
OutputBitDepthC	0	
InputColourSpaceConvert		The colour space conversion to apply to input video. Permitted values are: UNCHANGED      No colour space conversion is applied YCbCrToYCrCb    Swap the second and third components YCbCrToYYY      Set the second and third components to the values in the first RGBtoGBR        Reorder the three components If no value is specified, no colour space conversion is applied. The list may eventually also include RGB to YCbCr or YCgCo conversions.
SNRInternalColourSpace	false	When this is set true, then no colour space conversion is applied prior to PSNR calculation, otherwise the inverse of InputColourSpaceConvert is applied.
OutputInternalColourSpace	false	When this is set true, then no colour space conversion is applied to the reconstructed video, otherwise the inverse of InputColourSpaceConvert is applied.

Continued...

Table 3: File, I/O and source parameters. (Continued)

Option	Default	Description
InputChromaFormat	420	Specifies the chroma format used in the input file. Permitted values (depending on the profile) are 400, 420, 422 or 444.
ChromaFormatIDC (-cf)	0	Specifies the chroma format to use for processing. Permitted values (depending on the profile) are 400, 420, 422 or 444; the value of 0 indicates that the value of InputChromaFormat should be used instead.
MSEBasedSequencePSNR	false	When 0, the PSNR output is a linear average of the frame PSNRs; when 1, additional PSNRs are output which are formed from the average MSE of all the frames. The latter is useful when coding near-losslessly, where occasional frames become lossless.
PrintFrameMSE	false	When 1, the Mean Square Error (MSE) values of each frame will also be output alongside the default PSNR values.
PrintSequenceMSE	false	When 1, the Mean Square Error (MSE) values of the entire sequence will also be output alongside the default PSNR values.
CabacZeroWordPaddingEnabled	false	When 1, CABAC zero word padding will be enabled. This is currently not the default value for the setting.
ConformanceWindowMode	0	Specifies how the parameters related to the conformance window are interpreted (cropping/padding). The following modes are available: 0 No cropping / padding 1 Automatic padding to the next minimum CU size 2 Padding according to parameters HorizontalPadding and VerticalPadding 3 Cropping according to parameters ConfWinLeft, ConfWinRight, ConfWinTop and ConfWinBottom
HorizontalPadding (-pdx) VerticalPadding (-pdy)	0	Specifies the horizontal and vertical padding to be applied to the input video in luma samples when ConformanceWindowMode is 2. Must be a multiple of the chroma resolution (e.g. a multiple of two for 4:2:0).
ConfWinLeft ConfWinRight ConfWinTop ConfWinBottom	0	Specifies the horizontal and vertical cropping to be applied to the input video in luma samples when ConformanceWindowMode is 3. Must be a multiple of the chroma resolution (e.g. a multiple of two for 4:2:0).
FrameRate (-fr)	0	Specifies the frame rate of the input video. Note: This option only affects the reported bit rates.
FrameSkip (-fs)	0	Specifies a number of frames to skip at beginning of input video file.
FramesToBeEncoded (-f)	0	Specifies the number of frames to be encoded. When 0, all frames are coded.
FieldCoding	false	When 1, indicates that field-based coding is to be applied.
TopFieldFirst (-Tff)	0	Indicates the order of the fields packed into the input frame. When 1, the top field is temporally first.

Table 4: Profile and level parameters

Option	Default	Description
Profile	none	<p>Specifies the profile to which the encoded bitstream complies.</p> <p>Valid HEVC Ver. 1 values are: none, main, main10, main-still-picture</p> <p>Valid HEVC Ver. 2 (RExt) values are: main-RExt, high-throughput-RExt, monochrome, monochrome12, monochrome16, main12, main_422_10, main_422_12, main_444, main_444_10, main_444_12, main_444_16, main_intra, main_10_intra, main_12_intra, main_422_10_intra, main_422_12_intra, main_444_intra, main_444_10_intra, main_444_12_intra, main_444_16_intra.</p> <p>When main-RExt is specified, the constraint flags are either manually specified, or calculated via the other supplied settings.</p> <p>Compatibility flags are automatically determined according to the profile.</p> <p>NB: There is currently only limited validation that the encoder configuration complies with the profile, level and tier constraints.</p>
Level	none	<p>Specifies the level to which the encoded bitstream complies. Valid values are: none, 1, 2, 2.1, 3, 3.1, 4, 4.1, 5, 5.1, 5.2, 6, 6.1, 6.2, 8.5</p> <p>NB: There is currently only limited validation that the encoder configuration complies with the profile, level and tier constraints.</p>
Tier	main	<p>Specifies the level tier to which the encoded bitstream complies. Valid values are: main, high.</p> <p>NB: There is currently only limited validation that the encoder configuration complies with the profile, level and tier constraints.</p>
MaxBitDepthConstraint	0	For <code>-profile=main-RExt</code> , specifies the value to use to derive the <code>general_max_bit_depth</code> constraint flags for RExt profiles; when 0, use <code>max(InternalBitDepth, InternalBitDepthC)</code>
MaxChromaFormatConstraint	0	For <code>-profile=main-RExt</code> , specifies the chroma-format to use for the general profile constraints for RExt profiles; when 0, use the value of <code>ChromaFormatIDC</code> .
IntraConstraintFlag	false	For <code>-profile=main-RExt</code> , specifies the value of <code>general_intra_constraint_flag</code> to use for RExt profiles.
LowerBitRateConstraintFlag	true	Specifies the value of <code>general_lower_bit_constraint_flag</code> to use for RExt profiles.
ProgressiveSource	false	Specifies the value of <code>general_progressive_source_flag</code>
InterlacedSource	false	Specifies the value of <code>general_interlaced_source_flag</code>
NonPackedSource	false	Specifies the value of <code>general_non_packed_constraint_flag</code>
FrameOnly	false	Specifies the value of <code>general_frame_only_constraint_flag</code>

Table 5: Unit definition parameters

Option	Default	Description
MaxCUWidth	64	Defines the maximum CU width.
MaxCUHeight	64	Defines the maximum CU height.
MaxCUSize (-s)	64	Defines the maximum CU size.
MaxPartitionDepth (-h)	4	Defines the depth of the CU tree.
QuadtreeTULog2MaxSize	6 (= $\log_2(64)$ )	Defines the Maximum TU size in logarithm base 2.

Continued...



Table 5: Unit definition parameters (Continued)

Option	Default	Description
QuadtreeTULog2MinSize	2 (= $\log_2(4)$ )	Defines the Minimum TU size in logarithm base 2.
QuadtreeTUMaxDepthIntra	1	Defines the depth of the TU tree for intra CUs.
QuadtreeTUMaxDepthInter	2	Defines the depth of the TU tree for inter CUs.

Table 6: Coding structure parameters

Option	Default	Description
IntraPeriod (-ip)	-1	Specifies the intra frame period. A value of -1 implies an infinite period.
DecodingRefreshType (-dr)	0	Specifies the type of decoding refresh to apply at the intra frame period picture. 0 Applies an I picture (not a intra random access point). 1 Applies a CRA intra random access point (open GOP). 2 Applies an IDR intra random access point (closed GOP). 3 Use recovery point SEI messages to indicate random access.
GOPSize (-g)	1	Specifies the size of the cyclic GOP structure.
FrameN		Multiple options that define the cyclic GOP structure that will be used repeatedly throughout the sequence. The table should contain GOPSize elements. See section 3.1 for further details.

Table 7: Motion estimation parameters

Option	Default	Description
FastSearch	1	Enables or disables the use of a fast motion search. 0 Full search method 1 Fast search method 2 Previous motion vector fast search method
SearchRange (-sr)	96	Specifies the search range used for motion estimation. Note: the search range is defined around a predictor. Motion vectors derived by the motion estimation may thus have values larger than the search range.
BipredSearchRange	4	Specifies the search range used for bi-prediction refinement in motion estimation.
HadamardME	true	Enables or disables the use of the Hadamard transform in fractional-pel motion estimation. 0 SAD for cost estimation 1 Hadamard for cost estimation
ASR	false	Enables or disables the use of adaptive search ranges, where the motion search range is dynamically adjusted according to the POC difference between the current and the reference pictures.  $\text{SearchRange}' = \text{Round} \left( \text{SearchRange} * \text{ADAPT\_SR\_SCALE} * \frac{\text{abs}(\text{POC}_{\text{cur}} - \text{POC}_{\text{ref}})}{\text{RateGOPSize}} \right)$
MaxNumMergeCand	5	Specifies the maximum number of merge candidates to use.

Table 8: Mode decision parameters

Option	Default	Description
LambdaModifier $N$ (-LMN)	1.0	Specifies a value that is multiplied with the Lagrange multiplier $\lambda$ , for use in the rate-distortion optimised cost calculation when encoding temporal layer $N$ . $N$ may be in the range 0 (inclusive) to 7 (exclusive).
ECU	false	Enables or disables the use of early CU determination. When enabled, skipped CUs will not be split further.
CFM	false	Enables or disables the use of Cbf-based fast encoder mode. When enabled, once a $2N \times 2N$ CU has been evaluated, if the RootCbf is 0, further PU splits will not be evaluated.
ESD	false	Enables or disables the use of early skip detection. When enabled, the skip mode will be tested before any other.
FEN	false	Enables or disables the use of fast encoder mode. When enabled, the following occurs: <ul style="list-style-type: none"> <li>• In the SAD computation for blocks having size larger than 8, only the lines of even rows in the block are considered.</li> <li>• The number of iterations used in the bi-directional motion vector refinement in the motion estimation process is reduced from 4 to 1.</li> </ul>
FDM	true	Enables or disables the use of fast encoder decisions for $2N \times 2N$ merge mode. When enabled, the RD cost for the merge mode of the current candidate is not evaluated if the merge skip mode was the best merge mode for one of the previous candidates.
RDpenalty	0	RD-penalty for $32 \times 32$ TU for intra in non-intra slices. Enabling this parameter can reduce the visibility of CU boundaries in the coded picture. <ul style="list-style-type: none"> <li>0 No RD-penalty</li> <li>1 RD-penalty</li> <li>2 Maximum RD-penalty (no <math>32 \times 32</math> TU)</li> </ul>

Table 9: Quantization parameters

Option	Default	Description
QP (-q)	30.0	Specifies the base value of the quantization parameter. If it is non-integer, the QP is switched once during encoding.
CbQpOffset (-cbqpofs)	0	Global offset to apply to the luma QP to derive the QP of Cb and Cr respectively. These options correspond to the values of cb_qp_offset and cr_qp_offset, that are transmitted in the PPS. Valid values are in the range $[-12, 12]$ .
CrQpOffset (-crqpofs)	0	
MaxCuDQPDepth (-dqd)	0	Defines maximum depth of a minimum CuDQP for sub-LCU-level delta QP. MaxCuDQPDepth shall be greater than or equal to SliceGranularity.
RDOQ	true	Enables or disables rate-distortion-optimized quantization for transformed TUs.
RDOQTS	true	Enables or disables rate-distortion-optimized quantization for transform-skipped TUs.
DeltaQpRD (-dqr)	0	Specifies the maximum QP offset at slice level for multi-pass slice encoding. When encoding, each slice is tested multiple times by using slice QP values in the range $[-\text{DeltaQpRD}, \text{DeltaQpRD}]$ , and the best QP value is chosen as the slice QP.

Continued...

Table 9: Quantization parameters (Continued)

Option	Default	Description
MaxDeltaQP (-d)	0	Specifies the maximum QP offset at the largest coding unit level for the block-level adaptive QP assignment scheme. In the encoder, each largest coding unit is tested multiple times by using the QP values in the range $[-\text{MaxDeltaQP}, \text{MaxDeltaQP}]$ , and the best QP value is chosen as the QP value of the largest coding unit.
dQPFile (-m)		Specifies a file containing a list of QP deltas. The $n$ -th line (where $n$ is 0 for the first line) of this file corresponds to the QP value delta for the picture with POC value $n$ .
AdaptiveQp (-aq)	false	Enable or disable QP adaptation based upon a psycho-visual model.
MaxQPAdaptationRange (-aqr)	6	Specifies the maximum QP adaptation range.
AdaptiveQpSelection (-aqps)	false	Specifies whether QP values for non-I frames will be calculated on the fly based on statistics of previously coded frames.
RecalculateQP... AccordingToLambda	false	Recalculate QP values according to lambda values. Do not suggest to be enabled in all intra case.
ScalingList	0	Controls the specification of scaling lists: 0 Scaling lists are disabled 1 Use default scaling lists 2 Scaling lists are specified in the file indicated by ScalingListFile
ScalingListFile		When ScalingList is set to 2, this parameter indicates the name of the file, which contains the defined scaling lists. If ScalingList is set to 2 and this parameter is an empty string, information on the format of the scaling list file is output and the encoder stops.
MaxCUChromaQpAdjustmentDepth	-1	Specifies the maximum depth for CU chroma QP adjustment; if negative, CU chroma QP adjustment is disabled.

Table 10: Slice coding parameters

Option	Default	Description
SliceMode	0	Controls the slice partitioning method in conjunction with SliceArgument. 0 Single slice 1 Maximum number of CTUs per slice 2 Maximum number of bytes per slice 3 Maximum number of tiles per slice
SliceArgument		Specifies the maximum number of CTUs, bytes or tiles in a slice depending on the SliceMode setting.
SliceSegmentMode	0	Enables (dependent) slice segment coding in conjunction with SliceSegmentArgument. 0 Single slice 1 Maximum number of CTUs per slice segment 2 Maximum number of bytes per slice segment 3 Maximum number of tiles per slice segment
SliceSegmentArgument		Defines the maximum number of CTUs, bytes or tiles a slice segment depending on the SliceSegmentMode setting.
WaveFrontSynchro	false	Enables the use of specific CABAC probabilities synchronization at the beginning of each line of CTBs in order to produce a bitstream that can be encoded or decoded using one or more cores.

Continued...

Table 10: Slice coding parameters (Continued)

Option	Default	Description
TileUniformSpacing	false	Controls the mode used to determine per row and column tile sizes. 0 Each tile column width and tile row height is explicitly set by TileColumnWidthArray and TileRowHeightArray respectively 1 Tile columns and tile rows are uniformly spaced.
NumTileColumnsMinus1 NumTileRowsMinus1	0	Specifies the tile based picture partitioning geometry as NumTileColumnsMinus1 + 1 × NumTileRowsMinus1 + 1 columns and rows.
TileColumnWidthArray TileRowHeightArray		Specifies a space or comma separated list of widths and heights, respectively, of each tile column or tile row. The first value in the list corresponds to the leftmost tile column or topmost tile row.

Table 11: Deblocking filter parameters

Option	Default	Description
LoopFilterDisable	false	Enables or disables the in-loop deblocking filter.
LFCrossSliceBoundaryFlag	true	Enables or disables the use of in-loop filtering across slice boundaries.
DeblockingFilterControlPresent	false	Enables or disables the presence of the deblocking filter control parameters in the picture parameter set and in the slice segment header. When disabled, the default deblocking filter parameters are used.
LoopFilterOffsetInPPS	false	If enabled, the in-loop deblocking filter control parameters are sent in PPS. Otherwise, the in-loop deblocking filter control parameters are sent in the slice segment header. If deblocking filter parameters are sent in PPS, the same values of deblocking filter parameters are used for all pictures in the sequence (i.e. deblocking parameter = base parameter value). If deblocking filter parameters are sent in the slice segment header, varying deblocking filter parameters can be specified by setting parameters tcOffsetDiv2 and betaOffsetDiv2 in the GOP structure table. In this case, the final value of the deblocking filter parameter sent for a certain GOP picture is equal to (base parameter + GOP parameter for this picture). Intra-pictures use the base parameters values.
LoopFilterTcOffset_div2	0	Specifies the base value for the in-loop deblocking filter parameter tc_offset_div2. The final value of tc_offset_div2 shall be an integer number in the range −6..6.
LoopFilterBetaOffset_div2	0	Specifies the base value for the in-loop deblocking filter parameter beta_offset_div2. The final value of beta_offset_div2 shall be an integer number in the range −6..6.
DeblockingFilterMetric	false	Enables or disables the use of a deblocking filter metric to evaluate the suitability of deblocking..
LFCrossSliceBoundaryFlag	true	Enables or disables the use of a deblocking across tile boundaries.

Table 12: Coding tools parameters

Option	Default	Description
AMP	true	Enables or disables the use of asymmetric motion partitions.
SAO	true	Enables or disables the sample adaptive offset (SAO) filter.

Continued...

Table 12: Coding tools parameters (Continued)

Option	Default	Description
SAOLcuBoundary	false	Enables or disables SAO parameter estimation using non-deblocked pixels for LCU bottom and right boundary areas.
ConstrainedIntraPred	false	Enables or disables constrained intra prediction. Constrained intra prediction only permits samples from intra blocks in the same slice as the current block to be used for intra prediction.
TransquantBypassEnableFlag	false	Enables or disables the ability to bypass the transform, quantization and filtering stages at CU level. This option corresponds to the value of <code>transquant_bypass_enable_flag</code> that is transmitted in the PPS. See <code>CUTransquantBypassFlagForce</code> for further details.
CUTransquantBypassFlagForce	0	Controls the per CU transformation, quantization and filtering mode decision. This option controls the value of the per CU <code>cu_transquant_bypass_flag</code> . 0 Bypass is searched on a CU-by-CU basis and will be used if the cost is lower than not bypassing. 1 Bypass is forced for all CUs. This option has no effect if <code>TransquantBypassEnableFlag</code> is disabled.
PCMEnabledFlag	false	Enables or disables the use of PCM. The encoder will use cost measures on a CU-by-CU basis to determine if PCM mode is to be applied.
PCMLog2MaxSize	5 (= $\log_2(32)$ )	Specifies log2 of the maximum PCM block size. When PCM is enabled, the PCM mode is available for $2N \times 2N$ intra PUs smaller than or equal to the specified maximum PCM block size
PCMLog2MinSize	3	Specifies log2 of the minimum PCM block size. When PCM is enabled, the PCM mode is available for $2N \times 2N$ intra PUs larger than or equal to the specified minimum PCM block size. When larger than <code>PCMLog2MaxSize</code> , PCM mode is not used.
PCMInputBitDepthFlag	true	If enabled specifies that PCM sample bit-depth is set equal to <code>InputBitDepth</code> . Otherwise, it specifies that PCM sample bit-depth is set equal to <code>InternalBitDepth</code> .
PCMFilterDisableFlag	false	If enabled specifies that loop-filtering on reconstructed samples of PCM blocks is skipped. Otherwise, it specifies that loop-filtering on reconstructed samples of PCM blocks is not skipped.
WeightedPredP (-wpP)	false	Enables the use of weighted prediction in P slices.
WeightedPredB (-wpB)	false	Enables the use of weighted prediction in B slices.
Log2ParallelMergeLevel	2	Defines the PPS-derived <code>Log2ParMrgLevel</code> variable.
SignHideFlag (-SBH)	true	If enabled specifies that for each $4 \times 4$ coefficient group for which the number of coefficients between the first nonzero coefficient and the last nonzero coefficient along the scanning line exceeds 4, the sign bit of the first nonzero coefficient will not be directly transmitted in the bitstream, but may be inferred from the parity of the sum of all nonzero coefficients in the current coefficient group.
StrongIntraSmoothing (-sis)	true	If enabled specifies that for $32 \times 32$ intra prediction block, the intra smoothing when applied is either the 1:2:1 smoothing filter or a stronger bi-linear interpolation filter. Key reference sample values are tested and if the criteria is satisfied, the stronger intra smoothing filter is applied. If disabled, the intra smoothing filter when applied is the 1:2:1 smoothing filter.

Continued...

Table 12: Coding tools parameters (Continued)

Option	Default	Description
TMVPMODE	1	Controls the temporal motion vector prediction mode. 0 Disabled for all slices. 1 Enabled for all slices. 2 Disabled only for the first picture of each GOPSize.
TransformSkip	false	Enables or disables transform-skipping mode decision.
TransformSkipFast	false	Enables or disables reduced testing of the transform-skipping mode decision for chroma TUs. When enabled, no RDO search is performed for chroma TUs, instead they are transform-skipped if the four corresponding luma TUs are also skipped. This option has no effect if TransformSkip is disabled.

Table 13: Rate control parameters

Option	Default	Description
RateControl	false	Rate control: enables rate control or not.
TargetBitrate	0	Rate control: target bitrate, in bps.
KeepHierarchicalBit	0	Rate control: 0: equal bit allocation among pictures; 1: fix ratio hierarchical bit allocation; 2: adaptive hierarchical ratio bit allocation. It is suggested to enable hierarchical bit allocation for hierarchical-B coding structure.
LCULevelRateControl	true	Rate control: true: LCU level RC; false: picture level RC.
RCLCUSeparateModel	true	Rate control: use LCU level separate R-lambda model or not. When LCULevelRateControl is equal to false, this parameter is meaningless.
InitialQP	0	Rate control: initial QP value for the first picture. 0 to auto determine the initial QP value.
RCForceIntraQP	false	Rate control: force intra QP to be equal to initial QP or not.

Table 14: VUI parameters

Option	Default	Description
VuiParametersPresent (-vui)	false	Enable generation of vui_parameters().
AspectRatioInfoPresent	false	Signals whether aspect_ratio_idc is present.
AspectRatioIdc	0	aspect_ratio_idc
SarWidth	0	Specifies the horizontal size of the sample aspect ratio.
SarHeight	0	Specifies the vertical size of the sample aspect ratio.
OverscanInfoPresent	false	Signals whether overscan_info_present_flag is present.
OverscanAppropriate	false	Indicates whether cropped decoded pictures are suitable for display using overscan. 0 Indicates that the decoded pictures should not be displayed using overscan. 1 Indicates that the decoded pictures may be displayed using overscan.

Continued...

Table 14: VUI parameters (Continued)

Option	Default	Description
VideoSignalTypePresent	false	Signals whether video_format, video_full_range_flag, and colour_description_present_flag are present.
VideoFormat	5	Indicates representation of pictures.
VideoFullRange	false	Indicates the black level and range of luma and chroma signals. 0 Indicates that the luma and chroma signals are to be scaled prior to display. 1 Indicates that the luma and chroma signals are not to be scaled prior to display.
ColourDescriptionPresent	false	Signals whether colour_primaries, transfer_characteristics and matrix_coefficients are present.
ColourPrimaries	2	Indicates chromaticity coordinates of the source primaries.
TransferCharacteristics	2	Indicates the opto-electronic transfer characteristics of the source.
MatrixCoefficients	2	Describes the matrix coefficients used in deriving luma and chroma from RGB primaries.
ChromaLocInfoPresent	false	Signals whether chroma_sample_loc_type_top_field and chroma_sample_loc_type_bottom_field are present.
ChromaSampleLocTypeTopField	0	Specifies the location of chroma samples for top field.
ChromaSampleLocTypeBottomField	0	Specifies the location of chroma samples for bottom field.
NeutralChromaIndication	false	Indicates that the value of all decoded chroma samples is equal to 1«(BitDepthCr-1).
DefaultDisplayWindowFlag	flag	Indicates the presence of the Default Window parameters. false Disabled true Enabled
DefDispWinLeftOffset DefDispWinRightOffset DefDispWinTopOffset DefDispWinBottomOffset	0	Specifies the horizontal and vertical offset to be applied to the input video from the conformance window in luma samples. Must be a multiple of the chroma resolution (e.g. a multiple of two for 4:2:0).
FrameFieldInfoPresentFlag	false	Specifies the value of the VUI syntax element 'frame_field_info_present_flag', which indicates that pic_struct and field coding related values are present in picture timing SEI messages.
PocProportionalToTimingFlag	false	Specifies the value of the VUI syntax element 'vui_poc_proportional_to_timing_flag', which indicates that the POC value is proportional to the output time with respect to the first picture in the CVS.
NumTicksPocDiffOneMinus	0	Specifies the value of the VUI syntax element 'vui_num_ticks_poc_diff_one_minus1', which specifies the number of clock ticks corresponding to a difference of picture order count values equal to 1, and is used only when PocProportionalToTimingFlag is true.
BitstreamRestriction	false	Signals whether bitstream restriction parameters are present.
TilesFixedStructure	false	Indicates that each active picture parameter set has the same values of the syntax elements related to tiles.
MotionVectorsOverPicBoundaries	false	Indicates that no samples outside the picture boundaries are used for inter prediction.
MaxBytesPerPicDenom	2	Indicates a number of bytes not exceeded by the sum of the sizes of the VCL NAL units associated with any coded picture.

Continued...

Table 14: VUI parameters (Continued)

Option	Default	Description
MaxBitsPerMinCuDenom	1	Indicates an upper bound for the number of bits of coding_unit() data.
Log2MaxMvLengthHorizontal	15	Indicate the maximum absolute value of a decoded horizontal MV component in quarter-pel luma units.
Log2MaxMvLengthVertical	15	Indicate the maximum absolute value of a decoded vertical MV component in quarter-pel luma units.

Table 15: Range Extensions (Version 2) tool parameters

Option	Default	Description
CostMode	lossy	Specifies the cost mode to use. lossy $cost = distortion + \lambda \times bits$ sequence_level_lossless $cost = distortion / \lambda + bits$ . lossless As with sequence_level_lossless, but QP is also set to 0 (this will be deprecated in the future) mixed_lossless_lossy As with sequence_level_lossless, but QP'=4 is used for pre-estimates of transquant-bypass blocks
ExtendedPrecision	false	Specifies the use of extended_precision_processing flag. Note that unless the HIGH_BIT_DEPTH_SUPPORT macro in TypeDef.h is enabled, all internal bit depths must be 8 when the ExtendedPrecision setting is enabled. This setting is only valid for the 16-bit RExt profiles.
HighPrecisionPredictionWeighting	false	Specifies the value of high_precision_prediction_weighting_flag. This setting is only valid for the 16-bit or 4:4:4 RExt profiles.
CrossComponentPrediction	false	When true, specifies the use of the cross component prediction tool (4:4:4 processing only). Version 1 and some Version 2 (RExt) profiles require this to be false.
ReconBasedCrossCPredictionEstimate	false	If true, then when determining the alpha value for cross-component prediction, use the reconstructed residual rather than the pre-transform encoder-side residual
SaoLumaOffsetBitShift	0	Specifies the shift to apply to the SAO parameters. If negative, an estimate will be calculated based upon the initial QP. Version 1 and some Version 2 (RExt) profiles require this to be 0.
SaoChromaOffsetBitShift	0	
TransformSkipLog2MaxSize	2	Specifies the maximum TU size for which transform-skip can be used; the minimum value is 2. Version 1 and some Version 2 (RExt) profiles require this to be 2.
ImplicitResidualDPCM	false	When true, specifies the use of the implicitly signalled residual RDPCM tool (for intra). Version 1 and some Version 2 (RExt) profiles require this to be false.
ExplicitResidualDPCM	false	When true, specifies the use of the explicitly signalled residual RDPCM tool (for intra-block-copy and inter). Version 1 and some Version 2 (RExt) profiles require this to be false.
ResidualRotation	false	When true, specifies the use of the residual rotation tool. Version 1 and some Version 2 (RExt) profiles require this to be false.
SingleSignificanceMapContext	false	When true, specifies the use of a single significance map context for transform-skipped and transquant-bypassed TUs. Version 1 and some Version 2 (RExt) profiles require this to be false.

Continued...



Table 15: Range Extensions (Version 2) tool parameters (Continued)

Option	Default	Description
GolombRiceParameterAdaptation	false	When true, enable the adaptation of the Golomb-Rice parameter over the course of each slice. Version 1 and some Version 2 (RExt) profiles require this to be false.
AlignCABACBeforeBypass	false	When true, align the CABAC engine to a defined fraction of a bit prior to coding bypass data (including sign bits) when coeff_abs_level_remaining syntax elements are present in the group. This must always be true for the high-throughput-RExt profile, and false otherwise.
IntraReferenceSmoothing	true	When true, enable intra reference smoothing, otherwise disable it. Version 1 and some Version 2 (RExt) profiles require this to be true.

### 3.3 Encoder SEI parameters

The table below lists the SEI messages defined for Version 1 and Range-Extensions, and if available, the respective table that lists the controls within the HM Encoder to include the messages within the bit stream.

Table 16: List of Version 1 and RExt SEI messages

SEI Number	SEI Name	Table number of encoder controls, if available
0	Buffering period	Table 17
1	Picture timing	Table 18
2	Pan-scan rectangle	(Not handled)
3	Filler payload	(Not handled)
4	User data registered by Rec. ITU-T T.35	(Not handled)
5	User data unregistered	Decoded only
6	Recovery point	Table 19
9	Scene information	(Not handled)
15	Picture snapshot	(Not handled)
16	Progressive refinement segment start	(Not handled)
17	Progressive refinement segment end	(Not handled)
19	Film grain characteristics	(Not handled)
22	Post-filter hint	(Not handled)
23	Tone mapping information	Table 20
45	Frame packing arrangement	Table 21
47	Display orientation	Table 22
128	Structure of pictures information	Table 23
129	Active parameter sets	Table 24
130	Decoding unit information	Table 25
131	Temporal sub-layer zero index	Table 26

Continued...

Table 16: List of Version 1 and RExt SEI messages (Continued)

SEI Number	SEI Name	Table number of encoder controls, if available
132	Decoded picture hash	Table 27
133	Scalable nesting	Table 28
134	Region refresh information	Table 29
135	No display	Table 30
136	Time code	Table 31
137	Mastering display colour volume	Table 32
138	Segmented rectangular frame packing arrangement	Table 33
139	Temporal motion-constrained tile sets	Table 34
140	Chroma resampling filter hint	Table 35
141	Knee function information	Table 36
142	Colour remapping information	(Not handled)
143	Deinterlaced field identification	(Not handled)

Table 17: Buffering period SEI message encoder parameters

Option	Default	Description
SEIBufferingPeriod	0	Enables or disables the insertion of the Buffering period SEI messages. This option has no effect if VuiParametersPresent is disabled. SEIBufferingPeriod requires SEIActiveParameterSets to be enabled.

Table 18: Picture timing SEI message encoder parameters

Option	Default	Description
SEIPictureTiming	0	Enables or disables the insertion of the Picture timing SEI messages. This option has no effect if VuiParametersPresent is disabled.

Table 19: Recovery point SEI message encoder parameters

Option	Default	Description
SEIRecoveryPoint	0	Enables or disables the insertion of the Recovery point SEI messages.

Table 20: Tone mapping information SEI message encoder parameters

Option	Default	Description
SEIToneMappingInfo	0	Enables or disables the insertion of the Tone Mapping SEI message.

Continued...

Table 20: Tone mapping information SEI message encoder parameters (Continued)

Option	Default	Description
SEIToneMapId	0	Specifies Id of Tone Mapping SEI message for a given session.
SEIToneMapCancelFlag	false	Indicates that Tone Mapping SEI message cancels the persistence or follows.
SEIToneMapPersistenceFlag	true	Specifies the persistence of the Tone Mapping SEI message.
SEIToneMapCodedDataBitDepth	8	Specifies Coded Data BitDepth of Tone Mapping SEI messages.
SEIToneMapTargetBitDepth	8	Specifies Output BitDepth of Tome mapping function.
SEIToneMapModelId	0	Specifies Model utilized for mapping coded data into target_bit_depth range. 0 linear mapping with clipping 1 sigmoidal mapping 2 user-defined table mapping 3 piece-wise linear mapping 4 luminance dynamic range mapping
SEIToneMapMinValue	0	Specifies the minimum value in mode 0.
SEIToneMapMaxValue	1023	Specifies the maximum value in mode 0.
SEIToneMapSigmoidMidpoint	512	Specifies the centre point in mode 1.
SEIToneMapSigmoidWidth	960	Specifies the distance between 5the target_bit_depth in mode 1.
SEIToneMapStartOfCodedInterval		Array of user-defined mapping table. Default table can be set to the following: 0 12 24 36 48 60 72 84 96 108 120 132 144 156 168 180 192 192 196 204 208 216 220 228 232 240 248 252 260 264 272 276 284 292 292 296 300 304 308 312 320 324 328 332 336 344 348 352 356 360 368 372 376 380 384 388 396 400 404 408 412 420 424 428 432 436 444 444 444 448 452 456 460 464 468 472 476 476 480 484 488 492 496 500 504 508 508 512 516 520 524 528 532 536 540 540 544 548 552 556 560 564 568 572 572 576 580 584 588 592 596 600 604 604 608 612 616 620 624 628 632 636 636 640 644 648 652 656 660 664 668 672 672 672 676 680 680 684 688 692 692 696 700 704 704 708 712 716 716 720 724 724 728 732 736 736 740 744 748 748 752 756 760 760 764 768 768 772 776 780 780 784 788 792 792 796 800 804 804 808 812 812 816 820 824 824 828 832 836 836 840 844 848 848 852 856 860 860 860 864 864 868 872 872 876 880 880 884 884 888 892 892 896 900 900 904 908 908 912 912 916 920 920 924 928 928 932 936 936 940 940 944 948 948 952 956 956 960 964 964 968 968 972 976 976 980 984 984 988 992 992 996 996 1000 1004 1004 1008 1012 1012 1016 1020 1024
SEIToneMapNumPivots	0	Specifies the number of pivot points in mode 3.
SEIToneMapCodedPivotValue		Array of coded pivot point in mode 3. A suggested table is: 64 128 256 512 768
SEIToneMapTargetPivotValue		Array of target pivot point in mode 3. A suggested table is: 48 73 111 168 215
SEIToneMap... CameraIsoSpeedIdc	0	Indicates the camera ISO speed for daylight illumination.
SEIToneMap... CameraIsoSpeedValue	400	Specifies the camera ISO speed for daylight illumination of Extended.ISO.
SEIToneMap... ExposureIndexIdc	0	Indicates the exposure index setting of the camera.

Continued...

Table 20: Tone mapping information SEI message encoder parameters (Continued)

Option	Default	Description
SEIToneMap... ExposureIndexValue	400	Specifies the exposure index setting of the cameran of Extended.ISO.
SEIToneMapExposure... CompensationValueSignFlag	0	Specifies the sign of ExposureCompensationValue.
SEIToneMapExposure... CompensationValueNumerator	0	Specifies the numerator of ExposureCompensationValue.
SEIToneMapExposure... CompensationValueDenomIdc	2	Specifies the denominator of ExposureCompensationValue.
SEIToneMapRef... ScreenLuminanceWhite	350	Specifies reference screen brightness setting in units of candela per square metre.
SEIToneMapExtended... RangeWhiteLevel	800	Indicates the luminance dynamic range.
SEIToneMapNominal... BlackLevelLumaCodeValue	16	Specifies luma sample value of the nominal black level assigned decoded pictures.
SEIToneMapNominal... WhiteLevelLumaCodeValue	235	Specifies luma sample value of the nominal white level assigned decoded pictures.
SEIToneMapExtended... WhiteLevelLumaCodeValue	300	Specifies luma sample value of the extended dynamic range assigned de-coded pictures.

Table 21: Frame packing arrangement SEI message encoder parameters

Option	Default	Description
SEIFramePacking	0	Enables or disables the insertion of the Frame packing arrangement SEI messages.
SEIFramePackingType	0	Indicates the arrangement type in the Frame packing arrangement SEI message. This option has no effect if SEIFramePacking is disabled. 3 Side by Side 4 Top Bottom 5 Frame Alternate
SEIFramePackingInterpretation	0	Indicates the constituent frames relationship in the Frame packing arrangement SEI message. This option has no effect if SEIFramePacking is disabled. 0 Unspecified 1 Frame 0 is associated with the left view of a stereo pair 2 Frame 0 is associated with the right view of a stereo pair
SEIFramePackingQuincunx	0	Enables or disables the quincunx_sampling signalling in the Frame packing arrangement SEI messages. This option has no effect if SEIFramePacking is disabled.
SEIFramePackingId	0	Indicates the session number in the Frame packing arrangement SEI messages. This option has no effect if SEIFramePacking is disabled.

Table 22: Display orientation SEI message encoder parameters

Option	Default	Description
SEIDisplayOrientation	0	Enables or disables the insertion of the Display orientation SEI messages. 0 Disabled N: $0 < N < (2^{16} - 1)$ Enable display orientation SEI message with anticlockwise_rotation = N and display_orientation_repetition_period = 1

Table 23: Structure of pictures information SEI message encoder parameters

Option	Default	Description
SEISOPDescription	0	Enables or disables the insertion of the Structure of pictures information SEI messages.

Table 24: Active parameter sets SEI message encoder parameters

Option	Default	Description
SEIActiveParameterSets	0	Enables or disables the insertion of the Active parameter sets SEI messages.

Table 25: Decoding unit information SEI message encoder parameters

Option	Default	Description
SEIDecodingUnitInfo	0	Enables or disables the insertion of the Decoding unit information SEI messages. This option has no effect if VuiParametersPresent is disabled.

Table 26: Temporal sub-layer zero index SEI message encoder parameters

Option	Default	Description
SEITemporalLevel0Index	0	Enables or disables the insertion of the Temporal level zero index SEI messages.

Table 27: Decoded picture hash SEI message encoder parameters

Option	Default	Description
SEIPictureDigest	0	Deprecated alias for SEIDecodedPictureHash and should no longer be used.
Continued...		

Table 27: Decoded picture hash SEI message encoder parameters (Continued)

Option	Default	Description
SEIDecodedPictureHash	0	Enables or disables the calculation and insertion of the Decoded picture hash SEI messages. 0 Disabled 1 Transmits MD5 in SEI message and writes the value to the encoder log 2 Transmits CRC in SEI message and writes the value to the encoder log 3 Transmits checksum in SEI message and writes the value to the encoder log

Table 28: Scalable nesting SEI message encoder parameters

Option	Default	Description
SEIScalableNesting	0	Enables or disables the use of the scalable nesting SEI messages.

Table 29: Region refresh information SEI message encoder parameters

Option	Default	Description
SEIGradualDecodingRefreshInfo	0	Enables or disables the insertion of the Gradual decoding refresh information SEI messages.

Table 30: No display SEI message encoder parameters

Option	Default	Description
SEINoDisplay	0	When non-zero, generate no-display SEI message for temporal layer N or higher.

Table 31: Time code SEI message encoder parameters

Option	Default	Description
SEITimeCodeEnabled	false	When true (non-zero), generate Time code SEI messages.
SEITimeCodeNumClockTs	0	Number of clock time sets, in the range of 0 to 3 (inclusive).
SEITimeCodeTimeStampFlag		Time stamp flag associated to each time set (comma or space separated list of entries).
SEITimeCodeFieldBasedFlag		Field based flag associated to each time set (comma or space separated list of entries).
SEITimeCodeCountingType		Counting type associated to each time set (comma or space separated list of entries).
SEITimeCodeFullTsFlag		Full time stamp flag associated to each time set (comma or space separated list of entries).

Continued...

Table 31: Time code SEI message encoder parameters (Continued)

Option	Default	Description
SEITimeCodeDiscontinuityFlag		Discontinuity flag associated to each time set (comma or space separated list of entries).
SEITimeCodeCntDroppedFlag		Counter dropped flag associated to each time set (comma or space separated list of entries).
SEITimeCodeNumFrames		Number of frames associated to each time set (comma or space separated list of entries).
SEITimeCodeSecondsFlag		Flag to signal seconds value presence in each time set (comma or space separated list of entries).
SEITimeCodeMinutesFlag		Flag to signal minutes value presence in each time set (comma or space separated list of entries).
SEITimeCodeHoursFlag		Flag to signal hours value presence in each time set (comma or space separated list of entries).
SEITimeCodeSecondsValue		Seconds value for each time set (comma or space separated list of entries).
SEITimeCodeMinutesValue		Minutes value for each time set (comma or space separated list of entries).
SEITimeCodeHoursValue		Hours value for each time set (comma or space separated list of entries).
SEITimeCodeOffsetLength		Time offset length associated to each time set (comma or space separated list of entries).
SEITimeCodeTimeOffset		Time offset associated to each time set (comma or space separated list of entries).

Table 32: Mastering display colour volume SEI message encoder parameters

Option	Default	Description
SEIMasteringDisplayColourVolume	false	When true (non-zero), generate Mastering display colour volume SEI message.
SEIMasteringDisplayMaxLuminance	10000	Specifies the mastering display maximum luminance value in units of 1/10000 candela per square metre.
SEIMasteringDisplayMinLuminance	0	Specifies the mastering display minimum luminance value in units of 1/10000 candela per square metre.
SEIMasteringDisplayPrimaries	0,50000, 0,0, 50000,0	Mastering display primaries for all three colour planes in CIE xy coordinates in increments of 1/50000 (results in the ranges 0 to 50000 inclusive).
SEIMasteringDisplayWhitePoint	16667, 16667	Mastering display white point CIE xy coordinates in normalized increments of 1/50000 (e.g. 0.333 = 16667).

Table 33: Segmented rectangular frame packing arrangement SEI message encoder parameters

Option	Default	Description
SEISegmentedRectFramePacking	0	Controls generation of segmented rectangular frame packing SEI messages.
SEISegmentedRectFramePackingCancel	false	If true, cancels the persistence of any previous SRFPA SEI message.

Continued...

Table 33: Segmented rectangular frame packing arrangement SEI message encoder parameters (Continued)

Option	Default	Description
SEISegmentedRectFramePackingType	0	Specifies the arrangement of the frames in the reconstructed picture.
SEISegmentedRectFramePackingPersistence	false	If false the SEI applies to the current frame only.

Table 34: Temporal motion-constrained tile sets SEI message encoder parameters

Option	Default	Description
SEITempMotionConstrainedTileSets	false	When true (non-zero), generates example temporal motion constrained tile sets SEI messages.

Table 35: Chroma resampling filter hint SEI message encoder parameters

Option	Default	Description
SEIChromaSamplingFilterHint	false	When true (non-zero), generates example chroma sampling filter hint SEI messages.
SEIChromaSamplingHorizontalFilterType	2	Defines the index of the chroma sampling horizontal filter: 0 Unspecified 1 Filters signalled within the SEI message 2 Filters as described by SMPTE RP 2050-1:2012
SEIChromaSamplingVerticalFilterType	2	Defines the index of the chroma sampling vertical filter: 0 Unspecified 1 Filters signalled within the SEI message 2 Filters as described in the 5/3 filter description of ITU-T Rec. T.800   ISO/IEC 15444-1

Table 36: Knee function SEI message encoder parameters

Option	Default	Description
SEIKneeFunctionInfo	false	Enables (true) or disables (false) the insertion of the Knee function SEI messages.
SEIKneeFunctionId	0	Specifies Id of Knee function SEI message for a given session.
SEIKneeFunctionCancelFlag	false	Indicates that Knee function SEI message cancels the persistence (true) or follows (false).
SEIKneeFunctionPersistenceFlag	true	Specifies the persistence of the Knee function SEI message.
SEIKneeFunctionInputDrange	1000	Specifies the peak luminance level for the input picture of Knee function SEI messages.
SEIKneeFunctionInputDispLuminance	100	Specifies the expected display brightness for the input picture of Knee function SEI messages.
SEIKneeFunctionOutputDrange	4000	Specifies the peak luminance level for the output picture of Knee function SEI messages.
SEIKneeFunctionOutputDispLuminance	800	Specifies the expected display brightness for the output picture of Knee function SEI messages.

Continued...



Table 36: Knee function SEI message encoder parameters (Continued)

Option	Default	Description
SEIKneeFunctionNumKneePointsMinus1	2	Specifies the number of knee points - 1.
SEIKneeFunctionInputKneePointValue		Array of input knee point. Default table can be set to the following: 600 800 900
SEIKneeFunctionOutputKneePointValue		Array of output knee point. Default table can be set to the following: 100 250 450

### 3.4 Hardcoded encoder parameters

Table 37: CommonDef.h constants

Option	Default	Description
ADAPT_SR_SCALE	1	Defines a scaling factor used to derive the motion search range is adaptive (see ASR configuration parameter). Default value is 1.
MAX_GOP	64	maximum size of value of hierarchical GOP.
MAX_NUM_REF	4	maximum number of multiple reference frames
MAX_NUM_REF_LC	8	maximum number of combined reference frames
AMVP_MAX_NUM_CANDS	2	maximum number of final candidates
AMVP_MAX_NUM_CANDS_MEM	3	
MRG_MAX_NUM_CANDS	5	
DYN_REF_FREE	off	dynamic free of reference memories
MAX_TLAYER	8	maximum number of temporal layers
HB_LAMBDA_FOR_LDC	on	use of B-style lambda for non-key pictures in low-delay mode
GPB_SIMPLE	on	Fast estimation of generalized B in low-delay mode
GPB_SIMPLE_UNI	on	Fast estimation of generalized B in low-delay mode for uni-direction
FASTME_SMOOTHER_MV	on	Fast ME using smoother MV assumption
ADAPT_SR_SCALE	on	division factor for adaptive search range
CLIP_TO_709_RANGE	off	
EARLY_SKIP_THRES	1.5	early skip if $RD < EARLY\_SKIP\_THRES * avg[BestSkipRD]$
MAX_NUM_REF_PICS	16	
MAX_CHROMA_FORMAT_IDC	3	

#### TypeDef.h

Numerous constants that guard individual adoptions are defined within [source/Lib/TLibCommon/TypeDef.h](#).

## 4 Using the decoder

### 4.1 General

TAppDecoder -b str.bin -o dec.yuv [options]

Table 38: Decoder options

Option	Default	Description
(-help)		Prints usage information.
BitStreamFile (-b)		Defines the input bit stream file name.
ReconFile (-o)		Defines reconstructed YUV file name. If empty, no file is generated.
SkipFrames (-s)	0	Defines the number of pictures in decoding order to skip.
MaxTemporalLayer (-t)	-1	Defines the maximum temporal layer to be decoded. If -1, then all layers are decoded.
TarDecLayerIdSetFile (-l)		Specifies the targetDecLayerIdSet file name. The file would contain white-space separated LayerId values of the layers that are to be decoded. Omitting the parameter, or using a value of -1 in the file decodes all layers.
OutputBitDepth (-d)	0 (Native)	Specifies the luma bit-depth of the reconstructed YUV file (the value 0 indicates that the native bit-depth is used)
OutputBitDepthC	0 (Native)	Defines the chroma bit-depth of the reconstructed YUV file (the value 0 indicates that the native bit-depth is used)
SEIDecodedPictureHash	1	<p>Enable or disable verification of any Picture hash SEI messages. When this parameter is set to 0, the feature is disabled and all messages are ignored. When set to 1 (default), the feature is enabled and the decoder has the following behaviour:</p> <ul style="list-style-type: none"> <li>• If Picture hash SEI messages are included in the bit stream, the same type of hash is calculated for each decoded picture and written to the log together with an indication whether the calculated value matches the value in the SEI message. Decoding will continue even if there is a mismatch.</li> <li>• After decoding is complete, if any MD5sum comparison failed, a warning is printed and the decoder exits with the status EXIT_FAILURE</li> <li>• The per-picture MD5 log message has the following formats: [MD5:d41d8cd98f00b204e9800998ecf8427e,(OK)], [MD5:d41d8cd98f00b204e9800998ecf8427e,(unk)], [MD5:d41d8cd98f00b204e9800998ecf8427e,(***ERROR***)] [rxMD5:b9e1...] where, “(unk)” implies that no MD5 was signalled for this picture, “(OK)” implies that the decoder agrees with the signalled MD5, “(***ERROR***)” implies that the decoder disagrees with the signalled MD5. “[rxMD5:...]” is the signalled MD5 if different.</li> </ul>
OutputDecodedSEIMessagesFilename		When a non-empty file name is specified, information regarding any decoded SEI messages will be output to the indicated file. If the file name is '-', then stdout is used instead.
RespectDefDispWindow (-w)	0	<p>Video region to be output by the decoder.</p> <p>0 Output content inside the conformance window.</p> <p>1 Output content inside the default window.</p>

Continued...

Table 38: Decoder options (Continued)

Option	Default	Description
OutputColourSpaceConvert		<p>Specifies the colour space conversion to apply to 444 video. Permitted values are:</p> <p>UNCHANGED      No colour space conversion is applied</p> <p>YCrCbToYCbCr    Swap the second and third components</p> <p>GBRtoRGB        Reorder the three components</p> <p>If no value is specified, no colour space conversion is applied. The list may eventually also include RGB to YCbCr or YCgCo conversions.</p>
SEINoDisplay	false	When true, do not output frames for which there is an SEI NoDisplay message.

## 4.2 Using the decoder analyser

If the decoder is compiled with the macro `RExt_DECODER_DEBUG_BIT_STATISTICS` defined as 1 (either externally, or by editing `TypeDef.h`), the decoder will gather fractional bit counts associated with the different syntax elements, producing a table of the number of bits per syntax element, and where appropriate, according to block size and colour component/channel. The Linux makefile will compile both the analyser and standard version when the ‘all’ or ‘everything’ target is used (where the latter will also build high-bit-depth executables).