

# **Grade 12 Physics**

SPH4U

Qinghao Hu

November 5, 2025

# Contents

<b>1</b>	<b>Unit 1A</b>	<b>3</b>
1.1	Review of Describing and Graphing Motion . . . . .	3
1.1.1	Position: $\vec{d}$ . . . . .	3
1.1.2	displacement: $\Delta\vec{d}$ . . . . .	3
1.1.3	Velocity: $\vec{v}$ . . . . .	3
1.1.4	Acceleration: $\vec{a}$ . . . . .	3
1.1.5	Graphing motion . . . . .	3
1.2	Equations of Motion . . . . .	5
1.2.1	Format requirements for answering Motion questionss . . . . .	5
1.3	Adding and Subtracting 2-Dimensional Vectors . . . . .	6
1.3.1	Vector addition and subtraction key words . . . . .	6
1.3.2	Steps for solving a vector problem . . . . .	6
1.3.3	Another question type . . . . .	6
1.4	Frame of Reference . . . . .	7
1.4.1	1 Dimension Frame of Reference . . . . .	7
1.5	Relative Velocities in Two Dimensions . . . . .	9
1.5.1	Recall . . . . .	9
1.5.2	Definition . . . . .	9
1.6	F.O.R in 2-D . . . . .	10
1.7	Review of Netwon's Laws of Montion . . . . .	11
1.7.1	Netwon's First Laws . . . . .	11
1.7.2	Newton's second Law . . . . .	11
1.7.3	Newton's Third Law . . . . .	11
1.7.4	Free Body Diagrams (FBD) . . . . .	12
1.7.5	Application of Newton's second Law . . . . .	12
1.8	Review of Projectile Motion . . . . .	13
1.8.1	basic . . . . .	13
1.8.2	Special formula . . . . .	13
1.8.3	An example question . . . . .	14
1.9	Friction . . . . .	14
1.9.1	Kinetic Friction . . . . .	15
1.9.2	Static Friction . . . . .	15
1.9.3	Remainder . . . . .	15
1.10	Tension, compression and Pulleys . . . . .	16
1.10.1	Tention: T . . . . .	16
1.10.2	Compression: C . . . . .	16
1.11	Inclined plane with Friction . . . . .	17
1.11.1	How to determine the direction that the system will likely to accelerate . . . . .	17
1.11.2	Example template . . . . .	17

<b>2</b>	<b>Unit 1B</b>	<b>18</b>
2.1	Proportionality . . . . .	18
2.2	Fictitious Forces and Apparent Weight . . . . .	19
2.2.1	Compare Inertial and non-inertial F.O.R . . . . .	19
2.2.2	Fictitious Forces . . . . .	19
2.2.3	Apparent Weight . . . . .	19
2.2.4	Some of the formulas . . . . .	19
2.3	Lecture 2.5 . . . . .	20
2.3.1	Uniform Circular Motion . . . . .	20
2.3.2	Centripetal acceleration . . . . .	20
2.3.3	Formulas . . . . .	20
2.4	Motion of a car on Banked Turn . . . . .	21
2.4.1	Forces . . . . .	21
2.4.2	Critical Speed . . . . .	21
2.5	Universal Gravitation, Gravitational field . . . . .	21
2.5.1	Force of Gravity . . . . .	21
2.5.2	Gravational Fields . . . . .	22
2.5.3	Differences between strength of gravity and acceleration . . . . .	22
2.6	Satellites . . . . .	23
2.6.1	Newton's Cannon . . . . .	23
2.6.2	Geosynchronous . . . . .	23
2.6.3	Formulas related to satellite . . . . .	23
2.7	Rotating Frame of Reference . . . . .	25
2.7.1	Little problem . . . . .	25
2.7.2	Perceived Acceleration in a Rotating Frame of Reference . . . . .	26
<b>3</b>	<b>Unit 2: Energy and Momentum</b>	<b>28</b>
3.1	Types of Collisions . . . . .	28
3.1.1	Definitions . . . . .	28
3.1.2	Elastic Collisions . . . . .	28
3.1.3	Inelastic Collision . . . . .	29

## Chapter 3

# Unit 2: Energy and Momentum

### 3.1 Types of Collisions

#### 3.1.1 Definitions

Collisions are typically classified based on the amount of **kinetic energy** the system has after the collision, in comparison to the amount of kinetic energy the system had before the collision. In other words, **how does  $E'_k$  with  $E_k$ ?**

#### 3.1.2 Elastic Collisions

In an elastic collision, the kinetic energy of the system after the collision is **equal** to the kinetic energy of the system before the collision. In mathematics, the equation can be represented by:

$$E'_k = E_k$$

*Remark.* This does not mean the kinetic energy of the system after the collision is **equal** to the kinetic energy of the system before the collision (Unlike momentum)

#### Steps of the collision

*Remark.* This is on a horizontal frictionless surface, so we can ignore Gravitational Potential Energy

**Before the collision:** The mechanical energy is entirely in the form of kinetic energy

**First half of collision:** The interaction forces cause the object to start deform. As the object deforms, they transfer  $E_k$  to  $E_s$ .

**At the approximate midpoint of the collision:** The deformation of the object is at a maximum.  $E_s$  is the maximum and  $E_k$  is the minimum.

**During the second half of the collision:** The restoring forces are now doing *positive work* on the system, transferring elastic potential energy **back into**  $E_k$

**After the collision:** The system's mechanical energy is now entirely  $E_k$ , at this time,  $E_s = 0$ . All  $E_s$  is transferred to  $E_k$ .

#### Head-on Collision

**Before the Collision:** System's mechanical energy is entirely  $E_k$

**During the first half of the collision:** The spring get compressed.  $E_k$  is transformed into  $E_s$ .

**At the mid-point of the collision:**

- Spring is at the most compressed point.
- Distance between cars are minimumized
- $\vec{v}_A = \vec{v}_B$
- $E_k$  is minimumized
- $E_s$  is maximumized

**During the second half of the collision:**

- $\vec{v}_A < \vec{v}_B$
- Distance between the carts is increasing
- $E_s$  is being transferred back into  $E_k$

**After the collision:** The system is entirely  $E_k$  now

### 3.1.3 Inelastic Collision

So for this collision,  $E_k'$  is less than  $E_k$

It is impossible for a system to have more kinetic energy after the collision, than it had before the collision, unless:

1. One of the object had **stored energy** before the collision, which was transferred into kinetic energy during the collision.
2. An **external** force (such as force of gravity) is doing positive work on the system, during the collision.

#### Completely inelastic collision

In this collision, the maximum amount of kinetic energy that could be "lost" is lost as a result of the collision.

After the collision, the objects involved in the collision will be **stack/attached together**

**Apple and Arrow** is an example of this question.

The following condition must be met for a Perfectly Inelastic Collision:

- $\vec{v}_A' = \vec{v}_B' = \vec{v}^*$