

Grade 12 Physics

SPH4U

Qinghao Hu

November 5, 2025

Contents

1 Unit 1A	3
1.1 Review of Describing and Graphing Motion	3
1.1.1 Position: \vec{d}	3
1.1.2 displacement: $\Delta\vec{d}$	3
1.1.3 Velocity: \vec{v}	3
1.1.4 Acceleration: \vec{a}	3
1.1.5 Graphing motion	3
1.2 Equations of Motion	5
1.2.1 Format requirements for answering Motion questionss	5
1.3 Adding and Subtracting 2-Dimensional Vectors	6
1.3.1 Vector addition and subtraction key words	6
1.3.2 Steps for solving a vector problem	6
1.3.3 Another question type	6
1.4 Frame of Reference	7
1.4.1 1 Dimension Frame of Reference	7
1.5 Relative Velocities in Two Dimensions	9
1.5.1 Recall	9
1.5.2 Definition	9
1.6 F.O.R in 2-D	10
1.7 Review of Netwon's Laws of Montion	11
1.7.1 Netwon's First Laws	11
1.7.2 Newton's second Law	11
1.7.3 Newton's Third Law	11
1.7.4 Free Body Diagrams (FBD)	12
1.7.5 Application of Newton's second Law	12
1.8 Review of Projectile Motion	13
1.8.1 basic	13
1.8.2 Special formula	13
1.8.3 An example question	14
1.9 Friction	14
1.9.1 Kinetic Friction	15
1.9.2 Static Friction	15
1.9.3 Remainder	15
1.10 Tension, compression and Pulleys	16
1.10.1 Tention: T	16
1.10.2 Compression: C	16
1.11 Inclined plane with Friction	17
1.11.1 How to determine the direction that the system will likely to accelerate	17
1.11.2 Example template	17

2 Unit 1B	18
2.1 Proportionality	18
2.2 Fictitious Forces and Apparent Weight	19
2.2.1 Compare Inertial and non-inertial F.O.R	19
2.2.2 Fictitious Forces	19
2.2.3 Apparent Weight	19
2.2.4 Some of the formulas	19
2.3 Lecture 2.5	20
2.3.1 Uniform Circular Motion	20
2.3.2 Centripetal acceleration	20
2.3.3 Formulas	20
2.4 Motion of a car on Banked Turn	21
2.4.1 Forces	21
2.4.2 Critical Speed	21
2.5 Universal Gravitation, Gravitational field	21
2.5.1 Force of Gravity	21
2.5.2 Gravational Fields	22
2.5.3 Differences between strength of gravity and acceleration	22
2.6 Satellites	23
2.6.1 Netwon's Cannon	23
2.6.2 Geosynchronous	23
2.6.3 Formulas related to satellite	23
2.7 Rotating Frame of Reference	25
2.7.1 Little problem	25
2.7.2 Perceived Acceleration in a Rotating Frame of Reference	26
3 Unit 2: Energy and Momentum	28
3.1 Conservation of Momentum	28
3.1.1 Equation	28
3.2 Types of Collisions	29
3.2.1 Definitions	29
3.2.2 Elastic Collisions	29
3.2.3 Inelastic Collision	30

Chapter 3

Unit 2: Energy and Momentum

3.1 Conservation of Momentum

Definition 3.1.1. Two or more objects interact and exert forces from each other. The forces in the interaction are a Newton's Third Law pair of forces (ie $\vec{F}_{A/B} = -\vec{F}_{B/A}$)

3.1.1 Equation

Consider a person standing on any icy surface throws a heavy object horizontally:

FBD for the person (Left) and the object (Right)




Figure 3.1: We will assume that the interaction forces are essentially the net force acting on the object

Equation for the object A:

$$\begin{aligned}\sum \vec{F}_A &= m_A * \vec{a}_A \\ \vec{F}_{B/A} &= m_A \vec{a}_A \\ \vec{F}_{B/A} &= m_A \frac{\vec{v}_{fA} - \vec{v}_{iA}}{\Delta t_A}\end{aligned}\tag{3.1}$$

Equation for the object B:

$$\begin{aligned}\sum \vec{F}_B &= m_B * \vec{a}_B \\ \vec{F}_{A/B} &= m_B \vec{a}_B \\ \vec{F}_{A/B} &= m_B \frac{\vec{v}_{fB} - \vec{v}_{iB}}{\Delta t_B}\end{aligned}\tag{3.2}$$

Lemma 3.1.2. From Newton's third law, we know $\vec{F}_{A/B} + \vec{F}_{B/A} = 0$

We add 3.1 and 3.2 together:

$$m_A \frac{\vec{v}_{fA} - \vec{v}_{iA}}{\Delta t_A} + m_B \frac{\vec{v}_{fB} - \vec{v}_{iB}}{\Delta t_B} = 0$$

We know the time for both object should be the same.

$$\begin{aligned}m_A * \vec{v}_{fA} + m_B * \vec{v}_{fB} &= m_A * \vec{v}_{iA} + m_B * \vec{v}_{iB} \\ \vec{P}_{A2} + \vec{P}_{B2} &= \vec{P}_{A1} + \vec{P}_{B1}\end{aligned}\tag{3.3}$$

3.3 is the law of **Conservation of Momentum**

Always write this line at the beginning of your analysis

Definition 3.1.3. (*The Law of Conservation of Momentum*): The total momentum of a system of objects after an interaction is **equal** to the total momentum of the system before the interaction.

According to the 3.1.3, we can understand the total momentum of the system is **constant through out** the interaction.

The law assume that any other force that could **accelerate** any objects in the system during the interaction is **negligible**

3.2 Types of Collisions

3.2.1 Definitions

Collisions are typically classified based on the amount of **kinetic energy** the system has after the collision, in comparison to the amount of kinetic energy the system had before the collision. In other words, **how does E'_k with E_k ?**

3.2.2 Elastic Collisions

In an elastic collision, the kinetic energy of the system after the collision is **equal** to the kinetic energy of the system before the collision. In mathematics, the equation can be represented by:

$$E'_k = E_k$$

Remark. This does not mean the kinetic energy of the system after the collision is **equal** to the kinetic energy of the system before the collision (Unlike momentum)

Steps of the collision

Remark. This is on a horizontal frictionless surface, so we can ignore Gravitational Potential Energy

Before the collision: The mechanical energy is entirely in the form of kinetic energy

First half of collision: The interaction forces cause the object to start deform. As the object deform, they transfer E_k to E_s .

At the approximate midpoint of the collision: The deformation of the object is at a maximum. E_s is the maximum and E_k is the minimum.

During the second half of the collision: The restoring forces are now doing *positive work* on the system, transferring elastic potential energy **back into** E_k

After the collision: The system's mechanical energy is now entirely E_k , at this time, $E_s = 0$. All E_s is transferred to E_k .

Head-on Collision

Before the Collision: System's mechanical energy is entirely E_k

During the first half of the collision: The spring get compressed. E_k is transformed into E_s .

At the mid-point of the collision:

- Spring is at the most compressed point.
- Distance between cars are minimized
- $\vec{v}_A = \vec{v}_B$
- E_k is minimized
- E_s is maximized

During the second half of the collision:

- $\vec{v}_A < \vec{v}_B$
- Distance between the carts is increasing
- E_s is being transferred back into E_k

After the collision: The system is entirely E_k now

Remark. Elastic collisions **cannot occur** between visible objects in real life. At least some of the energy will be lost as thermal or sound.

3.2.3 Inelastic Collision

So for this collision, E_k' is less than E_k

It is impossible for a system to have more kinetic energy after the collision, than it had before the collision, unless:

1. One of the object had **stored energy** before the collision, which was transferred into kinetic energy during the collision.
2. An **external force** (such as force of gravity) is doing positive work on the system, during the collision.

Completely inelastic collision

In this collision, the maximum amount of kinetic energy that could be "lost" is lost as a result of the collision.

After the collusion, the objects involved in the collision will be **stack/attached together**

Apple and Arrow is an example of this question.

The following condition must be met for a Perfectly Inelastic Collision:

- $\vec{v}_A' = \vec{v}_B' = \vec{v}^*$