

RodSystemEstimator

Generated by Doxygen 1.9.3

1 Hierarchical Index	1
1.1 Class Hierarchy	1
2 Class Index	3
2.1 Class List	3
3 File Index	5
3.1 File List	5
4 Class Documentation	9
4.1 RSE::Core::AbstractDataObject Class Reference	9
4.1.1 Detailed Description	10
4.1.2 Member Function Documentation	10
4.1.2.1 addItem()	11
4.1.2.2 clone()	11
4.1.2.3 deserialize()	11
4.1.2.4 import()	11
4.2 RSE::Viewers::AbstractGraphData Class Reference	11
4.2.1 Member Function Documentation	12
4.2.1.1 data()	12
4.3 RSE::Core::Array< T > Class Template Reference	13
4.3.1 Detailed Description	14
4.4 RSE::Core::Cable Struct Reference	14
4.4.1 Detailed Description	15
4.5 RSE::Viewers::ConvergenceViewer Class Reference	15
4.5.1 Detailed Description	16
4.6 RSE::Core::Damper Class Reference	16
4.6.1 Detailed Description	17
4.7 RSE::Core::DataBaseCables Class Reference	17
4.7.1 Detailed Description	17
4.8 RSE::Models::DoubleSpinBoxItemDelegate Class Reference	18
4.8.1 Detailed Description	18
4.9 KLP::EnergyFrame Struct Reference	18
4.9.1 Detailed Description	19
4.10 KLP::FrameCollection Struct Reference	19
4.10.1 Detailed Description	20
4.11 KLP::FrameObject< T > Class Template Reference	20
4.12 KLP::FrameObjectIterator< T > Class Template Reference	20
4.12.1 Detailed Description	21
4.13 RSE::Viewers::Graph Class Reference	22
4.14 RSE::Models::GraphListModel Class Reference	23
4.15 KLP::Index Struct Reference	23
4.15.1 Detailed Description	24

4.16 KLP::IndexData Struct Reference	24
4.16.1 Detailed Description	24
4.17 RSE::Core::IO Class Reference	25
4.17.1 Detailed Description	25
4.18 RSE::Viewers::KinematicsGraphData Class Reference	25
4.18.1 Detailed Description	26
4.18.2 Member Function Documentation	26
4.18.2.1 data()	26
4.18.2.2 type()	26
4.19 RSE::Viewers::KLPGraphViewer Class Reference	27
4.19.1 Detailed Description	28
4.20 RSE::App::MainWindow Class Reference	28
4.20.1 Detailed Description	31
4.21 RSE::Core::Project Class Reference	31
4.22 RSE::Viewers::PropertyTreeWidget Class Reference	32
4.23 KLP::Result Class Reference	33
4.23.1 Detailed Description	34
4.24 KLP::ResultInfo Struct Reference	35
4.25 RSE::Models::ResultListModel Class Reference	35
4.26 RSE::Core::RodSystem Class Reference	36
4.27 RSE::Core::RodSystemParameters Struct Reference	36
4.27.1 Detailed Description	37
4.28 RSE::Models::RodSystemTableModel Class Reference	37
4.28.1 Detailed Description	38
4.29 RSE::Core::Array< T >::Row< U > Class Template Reference	38
4.29.1 Detailed Description	38
4.30 RSE::Core::ScalarDataObject Class Reference	38
4.30.1 Detailed Description	39
4.30.2 Member Function Documentation	39
4.30.2.1 addItem()	39
4.30.2.2 clone()	40
4.30.2.3 import()	40
4.31 RSE::Solution::SolutionManager Class Reference	40
4.31.1 Detailed Description	41
4.32 RSE::Solution::SolutionOptions Class Reference	41
4.33 RSE::Viewers::SpaceTimeGraphData Class Reference	42
4.33.1 Detailed Description	43
4.33.2 Member Function Documentation	43
4.33.2.1 data()	43
4.33.2.2 type()	43
4.34 RSE::Core::Spans Struct Reference	43
4.34.1 Detailed Description	44

4.35 KLP::StateFrame Struct Reference	44
4.35.1 Detailed Description	44
4.36 RSE::Core::Support Class Reference	44
4.36.1 Detailed Description	45
4.37 RSE::Core::VectorDataObject Class Reference	45
4.37.1 Detailed Description	46
4.37.2 Member Function Documentation	46
4.37.2.1 addItem()	46
4.37.2.2 clone()	46
4.37.2.3 import()	46
5 File Documentation	47
5.1 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/doublespinboxitemdelegate.cpp File Reference	47
5.1.1 Detailed Description	47
5.2 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/doublespinboxitemdelegate.h File Reference	47
5.2.1 Detailed Description	48
5.3 doublespinboxitemdelegate.h	48
5.4 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/mainwindow.cpp File Reference	48
5.4.1 Detailed Description	49
5.5 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/mainwindow.h File Reference	49
5.5.1 Detailed Description	50
5.6 mainwindow.h	50
5.7 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/rodsystemtablemodel.cpp File Reference	52
5.7.1 Detailed Description	52
5.8 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/rodsystemtablemodel.h File Reference	52
5.8.1 Detailed Description	53
5.9 rodsystemtablemodel.h	53
5.10 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/uiconstants.h File Reference	53
5.10.1 Detailed Description	54
5.11 uiconstants.h	54
5.12 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/abstractdataobject.cpp File Reference	54
5.12.1 Detailed Description	55
5.13 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/abstractdataobject.h File Reference	55
5.13.1 Detailed Description	55
5.14 abstractdataobject.h	56
5.15 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/aliasdata.h File Reference	56
5.15.1 Detailed Description	57

5.16 aliasdata.h	57
5.17 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/array.cpp File Reference . .	57
5.17.1 Detailed Description	58
5.18 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/array.h File Reference	58
5.18.1 Detailed Description	59
5.19 array.h	59
5.20 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/constants.h File Reference .	60
5.20.1 Detailed Description	61
5.21 constants.h	61
5.22 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/damper.cpp File Reference .	61
5.22.1 Detailed Description	61
5.23 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/damper.h File Reference . .	62
5.23.1 Detailed Description	62
5.24 damper.h	62
5.25 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/databasecables.cpp File Ref- erence	63
5.25.1 Detailed Description	63
5.26 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/databasecables.h File Refer- ence	63
5.26.1 Detailed Description	63
5.27 databasecables.h	64
5.28 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/fileutilities.cpp File Reference	64
5.28.1 Detailed Description	64
5.29 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/fileutilities.h File Reference .	65
5.29.1 Detailed Description	65
5.30 fileutilities.h	65
5.31 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/io.cpp File Reference	66
5.31.1 Detailed Description	66
5.32 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/io.h File Reference	66
5.32.1 Detailed Description	67
5.33 io.h	67
5.34 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/project.cpp File Reference .	67
5.34.1 Detailed Description	68
5.35 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/project.h File Reference . . .	68
5.35.1 Detailed Description	69
5.36 project.h	69
5.37 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/rodsystem.cpp File Reference	70
5.37.1 Detailed Description	70
5.38 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/rodsystem.h File Reference .	71
5.38.1 Detailed Description	71
5.39 rodsystem.h	71
5.40 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/scalardataobject.cpp File Reference	72

5.40.1 Detailed Description	72
5.41 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/scalardataobject.h File Reference	72
5.41.1 Detailed Description	73
5.42 scalardataobject.h	73
5.43 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionmanager.cpp File Reference	73
5.43.1 Detailed Description	74
5.44 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionmanager.h File Reference	74
5.44.1 Detailed Description	74
5.45 solutionmanager.h	75
5.46 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionoptions.cpp File Reference	75
5.46.1 Detailed Description	75
5.47 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionoptions.h File Reference	76
5.47.1 Detailed Description	76
5.48 solutionoptions.h	76
5.49 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.cpp File Reference	77
5.49.1 Detailed Description	77
5.50 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.h File Reference	77
5.50.1 Detailed Description	78
5.51 support.h	78
5.52 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/vectordataobject.cpp File Reference	78
5.52.1 Detailed Description	79
5.53 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/vectordataobject.h File Reference	79
5.53.1 Detailed Description	79
5.54 vectordataobject.h	79
5.55 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/aliasklp.h File Reference	80
5.55.1 Detailed Description	80
5.56 aliasklp.h	80
5.57 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/framecollection.h File Reference	80
5.57.1 Detailed Description	81
5.58 framecollection.h	81
5.59 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobject.cpp File Reference	82
5.59.1 Detailed Description	82
5.60 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobject.h File Reference	82
5.60.1 Detailed Description	83
5.61 frameobject.h	83
5.62 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobjectiterator.cpp File Reference	84

5.62.1 Detailed Description	84
5.63 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobjectiterator.h File Reference	84
5.63.1 Detailed Description	84
5.64 frameobjectiterator.h	85
5.65 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/index.h File Reference	85
5.65.1 Detailed Description	86
5.66 index.h	86
5.67 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/result.cpp File Reference	86
5.67.1 Detailed Description	87
5.68 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/result.h File Reference	87
5.68.1 Detailed Description	87
5.69 result.h	88
5.70 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/types.h File Reference	88
5.70.1 Detailed Description	89
5.71 types.h	89
5.72 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/main/main.cpp File Reference	90
5.72.1 Detailed Description	90
5.73 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/abstractgraphdata.cpp File Reference	90
5.73.1 Detailed Description	91
5.74 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/abstractgraphdata.h File Reference	91
5.74.1 Detailed Description	91
5.75 abstractgraphdata.h	92
5.76 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/aliasviewers.h File Reference	92
5.76.1 Detailed Description	93
5.77 aliasviewers.h	93
5.78 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/apputilities.cpp File Reference	93
5.78.1 Detailed Description	93
5.79 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/apputilities.h File Reference	94
5.79.1 Detailed Description	94
5.80 apputilities.h	94
5.81 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.cpp File Reference	95
5.81.1 Detailed Description	95
5.82 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.h File Reference	95
5.82.1 Detailed Description	95
5.83 convergenceviewer.h	96
5.84 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graph.cpp File Reference	96
5.84.1 Detailed Description	96

5.85	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graph.h File Reference . .	97
5.85.1	Detailed Description	97
5.86	graph.h	97
5.87	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graphlistmodel.cpp File Reference	98
5.87.1	Detailed Description	98
5.88	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graphlistmodel.h File Reference	98
5.88.1	Detailed Description	99
5.89	graphlistmodel.h	99
5.90	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/kinematicsgraphdata.cpp File Reference	99
5.90.1	Detailed Description	100
5.91	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/kinematicsgraphdata.h File Reference	100
5.91.1	Detailed Description	100
5.92	kinematicsgraphdata.h	101
5.93	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/klpgraphviewer.cpp File Reference	101
5.93.1	Detailed Description	101
5.94	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/klpgraphviewer.h File Reference	102
5.94.1	Detailed Description	102
5.95	klpgraphviewer.h	102
5.96	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/propertytreewidget.cpp File Reference	103
5.96.1	Detailed Description	104
5.97	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/propertytreewidget.h File Reference	104
5.97.1	Detailed Description	104
5.98	propertytreewidget.h	105
5.99	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/resultlistmodel.cpp File Reference	105
5.99.1	Detailed Description	106
5.100	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/resultlistmodel.h File Reference	106
5.100.1	Detailed Description	106
5.101	resultlistmodel.h	107
5.102	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/spacetimegraphdata.cpp File Reference	107
5.102.1	Detailed Description	107
5.103	/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/spacetimegraphdata.h File Reference	108
5.103.1	Detailed Description	108
5.104	spacetimegraphdata.h	108

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

RSE::Core::Array< T >	13
RSE::Core::Array< double >	13
RSE::Core::Cable	14
RSE::Core::Damper	16
RSE::Core::DataBaseCables	17
KLP::EnergyFrame	18
KLP::FrameCollection	19
KLP::FrameObject< T >	20
KLP::FrameObject< float >	20
KLP::FrameObjectIterator< T >	20
RSE::Viewers::Graph	22
KLP::Index	23
KLP::IndexData	24
RSE::Core::IO	25
RSE::Core::Project	31
QMainWindow	
RSE::App::MainWindow	28
QObject	
RSE::Core::AbstractDataObject	9
RSE::Core::ScalarDataObject	38
RSE::Core::VectorDataObject	45
RSE::Solution::SolutionManager	40
RSE::Viewers::AbstractGraphData	11
RSE::Viewers::KinematicsGraphData	25
RSE::Viewers::SpaceTimeGraphData	42
QStandardItemModel	
RSE::Models::GraphListModel	23
RSE::Models::ResultListModel	35
RSE::Models::RodSystemTableModel	37
QStyledItemDelegate	
RSE::Models::DoubleSpinBoxItemDelegate	18
QTreeWidget	
RSE::Viewers::PropertyTreeWidget	32
QWidget	
RSE::Viewers::ConvergenceViewer	15

RSE::Viewers::KLPGraphViewer	27
KLP::Result	33
KLP::ResultInfo	35
RSE::Core::RodSystem	36
RSE::Core::RodSystemParameters	36
RSE::Core::Array< T >::Row< U >	38
RSE::Solution::SolutionOptions	41
RSE::Core::Spans	43
KLP::StateFrame	44
RSE::Core::Support	44

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

RSE::Core::AbstractDataObject	9
Data object which is designed in the way to be represented in a table easily	
RSE::Viewers::AbstractGraphData	11
RSE::Core::Array< T >	
Numerical array class	13
RSE::Core::Cable	
Mechanical properties of a cable	14
RSE::Viewers::ConvergenceViewer	
Class to represent convergence of viscosities	15
RSE::Core::Damper	
Class to compute and collect properties of a damper	16
RSE::Core::DataBaseCables	
Aggregate data of cables	17
RSE::Models::DoubleSpinBoxItemDelegate	
Class to specify how table values can be edited	18
KLP::EnergyFrame	
Energy quantities associated with a frame	18
KLP::FrameCollection	
Set of all quantities belonged to a frame	19
KLP::FrameObject< T >	20
KLP::FrameObjectIterator< T >	
Class to iterate through data of a record	20
RSE::Viewers::Graph	22
RSE::Models::GraphListModel	23
KLP::Index	
Structure to navigate through records	23
KLP::IndexData	
Data of each record	24
RSE::Core::IO	
Class to save the project and solution data	25
RSE::Viewers::KinematicsGraphData	
Class to deal with kinematics of KLP-data	25
RSE::Viewers::KLPGraphViewer	
Class to graphically represent content of KLP output files	27
RSE::App::MainWindow	
Central window of the program	28

RSE::Core::Project	31
RSE::Viewers::PropertyTreeWidget	32
KLP::Result	
Class to aggregate all the records	33
KLP::ResultInfo	35
RSE::Models::ResultListModel	35
RSE::Core::RodSystem	36
RSE::Core::RodSystemParameters	
Parameters of a rod system	36
RSE::Models::RodSystemTableModel	
Table model to set and represent data of a rod system	37
RSE::Core::Array< T >::Row< U >	
Proxy class to acquire a row by index	38
RSE::Core::ScalarDataObject	
Scalar data object	38
RSE::Solution::SolutionManager	
Class to control the solution process	40
RSE::Solution::SolutionOptions	41
RSE::Viewers::SpaceTimeGraphData	
Class to deal with spacetime KLP-data	42
RSE::Core::Spans	
Computed parameters of spans	43
KLP::StateFrame	
Kinematic and dynamic quantities associated with a frame	44
RSE::Core::Support	
Class to aggregate data of supports	44
RSE::Core::VectorDataObject	
Vector data object	45

Chapter 3

File Index

3.1 File List

Here is a list of all documented files with brief descriptions:

/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/ doublespinboxitemdelegate.cpp	
DoubleSpinBoxItemDelegate	47
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/ doublespinboxitemdelegate.h	
DoubleSpinBoxItemDelegate	47
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/ mainwindow.cpp	
Definition of the MainWindow class	48
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/ mainwindow.h	
Declaration of the MainWindow class	49
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/ rodsystemtablemodel.cpp	
Definition of the RodSystemTableModel class	52
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/ rodsystemtablemodel.h	
Declaration of the RodSystemTableModel class	52
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/ uiconstants.h	
Graphical constants shared between several widgets	53
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ abstractdataobject.cpp	
Implementation of the AbstractDataObject class	54
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ abstractdataobject.h	
Declaration of the AbstractDataObject class	55
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ aliasdata.h	
Specification of data types used in a project	56
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ array.cpp	
Implementation of the Array class	57
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ array.h	
Declaration of the Array class	58
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ constants.h	
Computational constants	60
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ damper.cpp	
Definition of the Damper class	61
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ damper.h	
Declaration the Damper class	62
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ databasecables.cpp	
Definition of the DataBaseCables class	63
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ databasecables.h	
Declaration of the DataBaseCables class	63
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/ fileutilities.cpp	
Definition of utilites targeted to working with files	64

/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/fileutilities.h	
Declaration of utilities targeted to working with files	65
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/io.cpp	
Definition of the IO class	66
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/io.h	
Declaration of the IO class	66
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/project.cpp	
Definition of the Project class	67
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/project.h	
Declaration of the Project class	68
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/rodsystem.cpp	
Definition of the RodSystem class	70
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/rodsystem.h	
Declaration of the RodSystem class	71
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/scalardataobject.cpp	
Implementation of the ScalarDataObject class	72
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/scalardataobject.h	
Declaration of the ScalarDataObject class	72
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionmanager.cpp	
Definition of the SolutionManager class	73
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionmanager.h	
Declaration of the SolutionManager class	74
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionoptions.cpp	
Definition of the SolutionOptions class	75
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionoptions.h	
Declaration of the SolutionOptions class	76
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.cpp	
Definition of the Support class	77
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.h	
Declaration of the Support class	77
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/vectordataobject.cpp	
Implementation of the VectorDataObject class	78
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/vectordataobject.h	
Declaration of the VectorDataObject class	79
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/aliasklp.h	
Declaration of aliases used in KLP results	80
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/framecollection.h	
Collection of the data associated with the specified frame	80
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobject.cpp	
Definition of the FrameObject class	82
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobject.h	
Declaration of the FrameObject class	82
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobjectiterator.cpp	
Definition of the FrameObjectIterator class	84
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobjectiterator.h	
Declaration of the FrameObjectIterator class	84
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/index.h	
Specification of a structure to index records	85
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/result.cpp	
Definition of the Result class	86
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/result.h	
Declaration of the Result class	87
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/types.h	
Specification of data types in a KLP file	88
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/main/main.cpp	
Startup	90
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/abstractgraphdata.cpp	
Definition of the AbstractGraphData class	90

/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/abstractgraphdata.h	
Declaration of the AbstractGraphData class	91
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/aliasviewers.h	
Declaration of aliases used in viewers	92
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/apputilities.cpp	
Definition of utilites targeted to working with application data	93
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/apputilities.h	
Declaration of utilities targeted to working with application data	94
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.cpp	
Definition of the ConvergenceViewer class	95
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.h	
Declaration of the ConvergenceViewer class	95
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graph.cpp	
Definition of the Graph class	96
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graph.h	
Declaration of the Graph class	97
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graphlistmodel.cpp	
Definition of the GraphListModel class	98
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graphlistmodel.h	
Declaration of the GraphListModel class	98
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/kinematicsgraphdata.cpp	
Definition of the KinematisGraphData class	99
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/kinematicsgraphdata.h	
Declaration of the KinematisGraphData class	100
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/klpgraphviewer.cpp	
Definition of the KLPGraphViewer class	101
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/klpgraphviewer.h	
Declaration of the KLPGraphViewer class	102
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/propertytreewidget.cpp	
Definition of the PropertyTreeWidget class	103
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/propertytreewidget.h	
Declaration of the PropertyTreeWidget class	104
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/resultlistmodel.cpp	
Definition of the KLPResultListModel class	105
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/resultlistmodel.h	
Declaration of the KLPResultListModel class	106
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/spacetimegraphdata.cpp	
Definition of the SpaceTimeGraphData class	107
/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/spacetimegraphdata.h	
Declaration of the SpaceTimeGraphData class	108

Chapter 4


Class Documentation

4.1 RSE::Core::AbstractDataObject Class Reference

Data object which is designed in the way to be represented in a table easily.

```
#include <abstractdataobject.h>
```

Inheritance diagram for RSE::Core::AbstractDataObject:



Public Types

- enum **ObjectType** { **kScalar** , **kVector** , **kMatrix** , **kSurface** }

Public Member Functions

- **AbstractDataObject** (ObjectType type, QString const &name)
Base constructor.
- virtual **AbstractDataObject** * **clone** () const =0
- virtual **DataItemType** & **addItem** (DataKeyType key)=0
- void **removeItem** (DataValueType key)
Remove the entity paired to the specified key.
- bool **changeItemKey** (DataKeyType oldKey, DataKeyType newKey, DataHolder *items=nullptr)
Modify an existing key.
- bool **setArrayValue** (DataKeyType key, DataValueType newValue, IndexType iRow=0, IndexType iColumn=0)
Set an array value with the specified indices.
- DataValueType **arrayValue** (DataKeyType key, IndexType iRow=0, IndexType iColumn=0)
Retrieve a value from an array.

- `std::vector< DataKeyType > keys () const`
Retrieve all the keys.
- `quint32 numberItems () const`
- `DataHolder const & getItems ()`
- `DataIDType id () const`
- `ObjectType type () const`
- `QString const & name () const`
- `void setName (QString const &name)`
- `virtual void serialize (QDataStream &stream) const`
Serialize an abstract data object.
- `virtual void deserialize (QDataStream &stream)`
Partly deserialize an abstract data object.
- `virtual void import (QTextStream &stream)=0`
- `void write (QTextStream &stream) const`
Write an abstract data object to a file.

Static Public Member Functions

- `static DataIDType maxObjectID ()`
- `static void setMaxObjectID (DataIDType iMaxObjectID)`

Protected Attributes

- `const ObjectType mkType`
- `QString mName`
- `DataIDType mID`
- `DataHolder mItems`

Static Private Attributes

- `static DataIDType smMaxObjectID = 0`

Friends

- `QDataStream & operator<< (QDataStream &stream, AbstractDataObject const &obj)`
Print a data object to a binary stream.

4.1.1 Detailed Description

Data object which is designed in the way to be represented in a table easily.

4.1.2 Member Function Documentation

4.1.2.1 addItem()

```
virtual DataItemType & RSE::Core::AbstractDataObject::addItem (
    DataKeyType key ) [pure virtual]
```

Implemented in [RSE::Core::ScalarDataObject](#), and [RSE::Core::VectorDataObject](#).

4.1.2.2 clone()

```
virtual AbstractDataObject * RSE::Core::AbstractDataObject::clone ( ) const [pure virtual]
```

Implemented in [RSE::Core::ScalarDataObject](#), and [RSE::Core::VectorDataObject](#).

4.1.2.3 deserialize()

```
void AbstractDataObject::deserialize (
    QDataStream & stream ) [virtual]
```

Partly deserialize an abstract data object.

It is assumed that a type and name have already been assigned. So, only an identifier and items need to be set.

4.1.2.4 import()

```
virtual void RSE::Core::AbstractDataObject::import (
    QTextStream & stream ) [pure virtual]
```


Implemented in [RSE::Core::ScalarDataObject](#), and [RSE::Core::VectorDataObject](#).

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/[abstractdataobject.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/[abstractdataobject.cpp](#)

4.2 RSE::Viewers::AbstractGraphData Class Reference

Inheritance diagram for RSE::Viewers::AbstractGraphData:



Public Types

- enum **Category** {
 cSpaceTime , **cKinematics** , **cForce** , **cEnergy** ,
 cModal , **cEstimation** }
- enum **Direction** { **dFirst** , **dSecond** , **dThird** , **dFull** }

Public Member Functions

- **AbstractGraphData** (Category category, Direction direction)
- virtual GraphDataset **data** ([KLP::FrameCollection](#) const &collection)=0
- virtual int **type** () const =0
- Category **category** () const
- Direction **direction** () const
- bool **isSliced** () const
- quint64 **sliceIndex** () const

Protected Member Functions

- GraphDataset **getAbsoluteData** ([KLP::FloatFrameObject](#) const components[])
 Compute the module of specified components.
- GraphDataset **sliceDataByDirection** ([KLP::FloatFrameObject](#) const components[], Direction direction)
 Slice data through the specified direction.

Protected Attributes

- Category **mCategory**
- Direction **mDirection**
- quint64 **mSliceIndex** = -1

4.2.1 Member Function Documentation

4.2.1.1 data()

```
virtual GraphDataset RSE::Viewers::AbstractGraphData::data (  
    KLP::FrameCollection const & collection ) [pure virtual]
```

Implemented in [RSE::Viewers::KinematicsGraphData](#), and [RSE::Viewers::SpaceTimeGraphData](#).

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[abstractgraphdata.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[abstractgraphdata.cpp](#)

4.3 RSE::Core::Array< T > Class Template Reference

Numerical array class.

```
#include <array.h>
```

Classes

- class [Row](#)
Proxy class to acquire a row by index.

Public Member Functions

- **Array** (IndexType numRows=0, IndexType numCols=0)
- **Array** ([Array](#)< T > const &another)
Copy constructor.
- **Array** ([Array](#)< T > &&another)
Move constructor.
- T * **data** ()
- void **resize** (IndexType numRows, IndexType numCols)
Resize and copy previous values if possible.
- void **removeColumn** (IndexType iRemoveColumn)
Remove a column by index.
- void **swapColumns** (IndexType iFirstColumn, IndexType iSecondColumn)
Swap two columns.
- void **clear** ()
Remove all the values.
- IndexType **rows** () const
- IndexType **cols** () const
- IndexType **size** () const
- [Row](#)< T > **operator[]** (IndexType iRow)
- [Row](#)< T > **operator[]** (IndexType iRow) const
- [Array](#) & **operator=** ([Array](#)< T > const &another)
Assignment operator.

Private Attributes

- IndexType **mNumRows**
Number of rows.
- IndexType **mNumCols**
Number of columns.
- T * **mpData** = nullptr
Pointer to the data stored.

Friends

- `template<typename K >`
`QDebug operator<< (QDebug stream, Array< K > &array)`
Print all array values using the matrix format.
- `template<typename K >`
`QDataStream & operator<< (QDataStream &stream, Array< K > const &array)`
Write an array to a binary stream.
- `template<typename K >`
`QDataStream & operator>> (QDataStream &stream, Array< K > &array)`
Read an array from a stream.
- `template<typename K >`
`QTextStream & operator<< (QTextStream &stream, Array< K > const &array)`
Write an array to a text stream.

4.3.1 Detailed Description

```
template<typename T>
class RSE::Core::Array< T >
```

Numerical array class.

The documentation for this class was generated from the following files:

- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/array.h](#)
- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/array.cpp](#)

4.4 RSE::Core::Cable Struct Reference

Mechanical properties of a cable.

```
#include <databasecables.h>
```

Public Attributes

- `std::string name`
Name of a cable.
- `double bendingStiffness`
Bending stiffness, N.
- `double torsionalStiffness`
Torsional stiffness, N.
- `double massPerLength`
Mass per length, kg/m.
- `double youngsModulus`
Youngs modulus, Pa.
- `double area`
Area of a cross-section, m².

4.4.1 Detailed Description

Mechanical properties of a cable.

The documentation for this struct was generated from the following file:


- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/databasecables.h>

4.5 RSE::Viewers::ConvergenceViewer Class Reference

Class to represent convergence of viscosities.

```
#include <convergenceviewer.h>
```

Inheritance diagram for RSE::Viewers::ConvergenceViewer:



Public Member Functions

- **ConvergenceViewer** (QString const &pathFile, QWidget *pParent=nullptr)
- void **plot** ()
Represent the convergence.

Private Member Functions

- void **initialize** ()
Initialize the widget.
- bool **read** ()
Read the file contained viscosities of dampers.

Private Attributes

- QString const **mkPathFile**
- QCustomPlot * **mpFigure**
- QStringList **mAvailableColors**
- QVector< QCPScatterStyle::ScatterShape > **mAvailableShapes**
- QVector< int > **mCalcModes**
- [Core::Array](#)< double > **mDampingValues**

4.5.1 Detailed Description

Class to represent convergence of viscosities.

The documentation for this class was generated from the following files:

- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.h](#)
- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.cpp](#)

4.6 RSE::Core::Damper Class Reference

Class to compute and collect properties of a damper.

```
#include <damper.h>
```

Public Member Functions

- **Damper** (double massCable, double massLoadedCable, double workingLength, double bouncerLength, double springLength=0, double springStiffness=0)
- double **massCable** () const
- double **massLoadedCable** () const
- double **workingLength** () const
- double **bouncerLength** () const
- double **springLength** () const
- double **springStiffness** () const
- void **setMassCable** (double massCable)
- void **setMassLoadedCable** (double massLoadedCable)
- void **setWorkingLength** (double workingLength)
- void **setBouncerLength** (double bouncerLength)
- void **setSpringLength** (double springLength)
- void **setSpringStiffness** (double springStiffness)
- void **computeSpring** ()

Compute parameters of a spring belonged to a damper.

Private Attributes

- double **mMassCable**
Mass of a cable, kg.
- double **mMassLoadedCable**
Mass of a cable with ice on it, kg.
- double **mWorkingLength**
Working length, m.
- double **mBouncerLength**
Length of a bouncer, m.
- double **mSpringLength** = 0.0
Length of a spring, m.
- double **mSpringStiffness** = 0.0
Spring stiffness, N/m.

4.6.1 Detailed Description

Class to compute and collect properties of a damper.

The documentation for this class was generated from the following files:

- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/damper.h](#)
- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/damper.cpp](#)

4.7 RSE::Core::DataBaseCables Class Reference

Aggregate data of cables.

```
#include <databasecables.h>
```

Public Member Functions

- **DataBaseCables** (QString const &directory, QString const &fileName)
- `std::vector< std::string > names () const`
Names of available cables.
- [Cable](#) const & **getItem** (std::string const &name) const

Private Member Functions

- `bool readDataBase (QString const &pathFile)`
Read a database from a file.

Private Attributes

- `std::unordered_map< std::string, Cable > mData`

4.7.1 Detailed Description

Aggregate data of cables.

The documentation for this class was generated from the following files:


- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/databasecables.h](#)
- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/databasecables.cpp](#)

4.8 RSE::Models::DoubleSpinBoxItemDelegate Class Reference

Class to specify how table values can be edited.

```
#include <doublespinboxitemdelegate.h>
```

Inheritance diagram for RSE::Models::DoubleSpinBoxItemDelegate:



Public Member Functions

- **DoubleSpinBoxItemDelegate** (QObject *parent=nullptr)
- QWidget * **createEditor** (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const override
Create a double value editor.
- void **setEditorData** (QWidget *pEditor, const QModelIndex &index) const override
Specify data to show.
- void **setModelData** (QWidget *pEditor, QAbstractItemModel *pModel, const QModelIndex &index) const override
Set data to a model.
- void **updateEditorGeometry** (QWidget *pEditor, const QStyleOptionViewItem &option, const QModelIndex &index) const override
Set a geometry to render.

4.8.1 Detailed Description

Class to specify how table values can be edited.

The documentation for this class was generated from the following files:

- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/doublespinboxitemdelegate.h>
- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/doublespinboxitemdelegate.cpp>

4.9 KLP::EnergyFrame Struct Reference

Energy quantities associated with a frame.

```
#include <framecollection.h>
```

Public Attributes

- FloatFrameObject **kinetic**
- FloatFrameObject **potential**
- FloatFrameObject **full**

4.9.1 Detailed Description

Energy quantities associated with a frame.

The documentation for this struct was generated from the following file:

- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/framecollection.h>

4.10 KLP::FrameCollection Struct Reference

Set of all quantities belonged to a frame.

```
#include <framecollection.h>
```

Public Attributes

- **int numRods**
Number of rods.
- **float time**
Time.
- **FloatFrameObject parameter**
Parameter.
- **FloatFrameObject naturalLength**
Natural length.
- **FloatFrameObject accumulatedNaturalLength**
- **FloatFrameObject coordinates** [kNumDirections]
Coordinates.
- **StateFrame state**
Regular state.
- **StateFrame projectedState**
Projected regular state.
- **StateFrame firstDerivativeState**
First-order derivate of the state with respect to time.
- **StateFrame secondDerivativeState**
Second-order derivate of the state with respect to time.
- **StateFrame errorState**
State error.
- **FloatFrameObject strain**
Strain.
- **std::vector< StateFrame > modalStates**
Set of modal states.
- **FloatFrameObject frequencies**
Frequencies.
- **EnergyFrame energy**
Energy.

4.10.1 Detailed Description

Set of all quantities belonged to a frame.

The documentation for this struct was generated from the following file:

- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/framecollection.h>

4.11 KLP::FrameObject< T > Class Template Reference

Public Types

- using **iterator** = [FrameObjectIterator](#)< T >

Public Member Functions

- **FrameObject** (T const *pData=nullptr, T normFactor=1.0, qint64 size=0, qint64 step=1)
- bool **isEmpty** () const
- qint64 **size** () const
- [iterator](#) **begin** () const
- [iterator](#) **end** () const
- [iterator](#) **operator[]** (int index) const

Private Attributes

- T const * **mpData**
- T **mNormFactor**
- qint64 **mSize**
- qint64 **mStep**

Friends

- `template<typename K >`
QDebug **operator**<< (QDebug stream, [FrameObject](#)< K > &frameObject)

The documentation for this class was generated from the following files:

- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobject.h>
- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/frameobject.cpp>

4.12 KLP::FrameObjectIterator< T > Class Template Reference

Class to iterate through data of a record.

```
#include <frameobjectiterator.h>
```

Public Types

- using **self_type** = [FrameObjectIterator](#)< T >
- using **iterator_category** = std::random_access_iterator_tag
- using **difference_type** = std::ptrdiff_t
- using **value_type** = T
- using **pointer** = T const *
- using **reference** = T const &

Public Member Functions

- **FrameObjectIterator** (pointer pData, T normFactor, qint64 step)
- value_type **operator*** ()
- [self_type](#) & **operator++** ()
- [self_type](#) **operator++** (int)
- [self_type](#) **operator+** (const difference_type &movement)
- difference_type **operator-** (const [FrameObjectIterator](#) &another) const

Private Attributes

- pointer **mpData**
- T **mNormFactor**
- qint64 const **mStep**

Friends

- bool **operator==** ([self_type](#) const &first, [self_type](#) const &second)
- bool **operator!=** ([self_type](#) const &first, [self_type](#) const &second)

4.12.1 Detailed Description

```
template<typename T>
class KLP::FrameObjectIterator< T >
```

Class to iterate through data of a record.

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/[frameobjectiterator.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/[frameobjectiterator.cpp](#)

4.13 RSE::Viewers::Graph Class Reference

Public Member Functions

- **Graph** (QString const &name)
- QString const & **name** () const
- GraphIDType **id** () const
- [AbstractGraphData](#) ** **data** ()
- QCPGraph::LineStyle **lineStyle** () const
- uint **lineWidth** () const
- QColor **color** () const
- QCPScatterStyle **scatterStyle** () const
- double **scatterSize** () const
- QStringList const & **axesLabels** () const
- void **setName** (QString const &name)
- void **setData** ([AbstractGraphData](#) *pData, int iData)
Replace directional data with a new one.
- void **setData** ([AbstractGraphData](#) *pXData=nullptr, [AbstractGraphData](#) *pYData=nullptr, [AbstractGraphData](#) *pZData=nullptr)
Specify data for all axes.
- void **eraseData** (int iData)
- void **setLineStyle** (QCPGraph::LineStyle const &lineStyle)
- void **setLineWidth** (uint lineWidth)
- void **setColor** (QColor const &color)
- void **setScatterStyle** (QCPScatterStyle const &scatterStyle)
- void **setScatterSize** (double scatterSize)
- void **setAxesLabels** (QStringList const &axesLabels)

Static Public Member Functions

- static GraphIDType **maxGraphID** ()

Private Attributes

- QString **mName**
- GraphIDType **mID**
- [AbstractGraphData](#) * **mpData** [KLP::kNumDirections] = {nullptr, nullptr, nullptr}
- QCPGraph::LineStyle **mLineStyle** = QCPGraph::lsLine
- uint **mLineWidth** = 1
- QColor **mColor** = Qt::blue
- QCPScatterStyle **mScatterStyle** = QCPScatterStyle::ssNone
- double **mScatterSize** = 5
- QStringList **mAxesLabels** = QStringList({" X", " Y", " Z"})

Static Private Attributes


- static GraphIDType **smMaxGraphID** = 0

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graph.h
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graph.cpp

4.14 RSE::Models::GraphListModel Class Reference

Inheritance diagram for RSE::Models::GraphListModel:



Public Member Functions

- **GraphListModel** (Viewers::MapGraphs &graphs, QObject *pParent=nullptr)
- void **create** ()
Create a new default graph.
- void **updateContent** ()
Create items linked to graphs.
- void **removeSelected** ()
Remove selected graphs.
- void **selectItem** (int iSelect=-1)
Select an item by index.

Private Member Functions

- void **clearContent** ()
Remove all the items created.
- void **renameItem** (QStandardItem *pltem)
Rename a graph after editing.

Private Attributes

- Viewers::MapGraphs & **mGraphs**

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[graphlistmodel.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[graphlistmodel.cpp](#)

4.15 KLP::Index Struct Reference

Structure to navigate through records.

```
#include <index.h>
```

Public Member Functions

- **Index ()**
Base constructor.

Public Attributes

- `std::vector< IndexData > data`
Data.
- `quint64 recordShift = 0`
Shift of the main record.
- `quint64 relativeDataShift = 0`
Relative shift of data.

4.15.1 Detailed Description

Structure to navigate through records.

The documentation for this struct was generated from the following file:

- `/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/index.h`

4.16 KLP::IndexData Struct Reference

Data of each record.

```
#include <index.h>
```

Public Attributes

- `quint64 position = 0`
Position of a record in the buffer.
- `quint64 size = 0`
Size of a record.
- `quint64 step = 1`
Step for iterating inside a record.
- `quint64 partSize = 0`
Partial length of a quantity inside a record.

4.16.1 Detailed Description

Data of each record.

The documentation for this struct was generated from the following file:

- `/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/index.h`

4.17 RSE::Core::IO Class Reference

Class to save the project and solution data.

```
#include <io.h>
```

Public Member Functions

- **IO** (QString const &lastPath)
- QString const & **lastPath** () const
- QString const & **extension** () const
- void **saveAs** (QString const &pathFile, [Project](#) &project, [Solution::SolutionOptions](#) &options)
Save the project and solution data to a file.
- IOPair **open** (QString const &pathFile, [DataBaseCables](#) const &dataBaseCables)
Read the computational data from a file.

Private Attributes

- const QString **mkProjectExtension** = ".rse"
- QString **mLastPath**

4.17.1 Detailed Description

Class to save the project and solution data.

The documentation for this class was generated from the following files:


- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/[io.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/[io.cpp](#)

4.18 RSE::Viewers::KinematicsGraphData Class Reference

Class to deal with kinematics of KLP-data.

```
#include <kinematicsgraphdata.h>
```

Inheritance diagram for RSE::Viewers::KinematicsGraphData:



Public Types

- enum **KinematicsType** {
kStrain , **kDisplacement** , **kRotation** , **kSpeed** ,
kAngularSpeed , **kAcceleration** , **kAngularAcceleration** }

Public Member Functions

- KinematicsGraphData** (KinematicsType type, Direction direction=Direction::dFull)
- GraphDataset **data** (KLP::FrameCollection const &collection) override
Retrieve the data of the specified type and direction from a given frame.
- int **type** () const override

Private Attributes

- KinematicsType **mType**

Additional Inherited Members

4.18.1 Detailed Description

Class to deal with kinematics of KLP-data.

4.18.2 Member Function Documentation

4.18.2.1 data()

```
GraphDataset KinematicsGraphData::data (
    KLP::FrameCollection const & collection ) [override], [virtual]
```

Retrieve the data of the specified type and direction from a given frame.

Implements [RSE::Viewers::AbstractGraphData](#).

4.18.2.2 type()

```
int RSE::Viewers::KinematicsGraphData::type ( ) const [inline], [override], [virtual]
```

Implements [RSE::Viewers::AbstractGraphData](#).

The documentation for this class was generated from the following files:


- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[kinematicsgraphdata.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[kinematicsgraphdata.cpp](#)

4.19 RSE::Viewers::KLPGraphViewer Class Reference

Class to graphically represent content of KLP output files.

```
#include <klpgraphviewer.h>
```

Inheritance diagram for RSE::Viewers::KLPGraphViewer:



Public Member Functions

- **KLPGraphViewer** (QString const &lastPath, QSettings &settings, QWidget *pParent=nullptr)
- void **openResultsDialog** ()
Open results using a file system dialog.
- void **openResults** (QStringList const &locationFiles)
Open a set of results using their locations.
- void **setGraphs** (MapGraphs &&graphs)
Replace the current set of graphs with the new one.

Private Member Functions

- void **initialize** ()
Intialize default graphical objects.
- void **createContent** ()
Construct graphical interface.
- ads::CDockWidget * **createResultWidget** ()
Create a widget to open and deal with KLP results.
- ads::CDockWidget * **createFigureWidget** ()
Create a widget to plot graphs.
- ads::CDockWidget * **createConstructorWidget** ()
Create a widget to construct graphs.
- ads::CDockWidget * **createPropertyWidget** ()
Create a widget to modify properties of graphs.
- void **processSelectedResults** ()
Process selected results.
- void **showResultInfo** (KLP::ResultInfo const &info)
Show information about the selected result.
- void **processSelectedGraphs** ()
Process selected graphs.
- void **saveSettings** ()
Save settings to a file.
- void **restoreSettings** ()
Restore settings from a file.
- void **closeEvent** (QCloseEvent *pEvent) override
Save settings and delete handling widgets before closing the window.

Private Attributes

- QString **mLastPath**
- QSettings & **mSettings**
- ads::CDockManager * **mpDockManager** = nullptr
- QCustomPlot * **mpFigure**
- QListView * **mpListResults**
- QTextEdit * **mpTextInfo**
- QListView * **mpListGraphs**
- RSE::Viewers::PropertyTreeWidget * **mpPropertyTreeWidget**
- RSE::Models::ResultListModel * **mpResultListModel**
- RSE::Models::GraphListModel * **mpGraphListModel**
- KLP::Results **mResults**
- MapGraphs **mGraphs**

4.19.1 Detailed Description

Class to graphically represent content of KLP output files.

The documentation for this class was generated from the following files:


- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[klpgraphviewer.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[klpgraphviewer.cpp](#)

4.20 RSE::App::MainWindow Class Reference

Central window of the program.

```
#include <mainwindow.h>
```

Inheritance diagram for RSE::App::MainWindow:



Public Member Functions

- **MainWindow** (QWidget *parent=nullptr)
- void **setMassCable** (double value)
Set mass of a cable.
- void **setMassLoadedCable** (double value)
Set mass of a cable with ice on it.
- void **setWorkingLength** (double value)
Specify working length.
- void **setBouncerLength** (double value)
Set length of a bouncer.

- void **setSpringLength** (double value)
Assign length of a spring.
- void **setSpringStiffness** (double value)
Set spring stiffness of a damper.
- void **setCable** (QString const &name)
Assign cables to a rod system.
- void **setForce** (double value)
Specify stretching force.
- void **setLongitudinalStiffness** (double value)
Specify longitudinal stiffness of all supports.
- void **setVerticalStiffness** (double value)
Specify vertical stiffness of all supports.
- void **createProject** ()
Open a new project.
- void **openProjectDialog** ()
Open a project by means of a dialog window.
- void **openProject** (QString const &pathFile)
Open a project using a path specified.
- void **saveAsProject** ()
Save the project using a dialog window.
- void **saveProject** ()
Save the current project.

Private Slots

- void **saveSettings** ()
Save current graphical settings of floating widgets.
- void **restoreSettings** ()
Read graphical settings from a file.
- void **computeSpring** ()
Compute parameters of a spring.
- void **computeSpans** ()
Compute length of all cables.
- void **runRodSystemSolution** ()
Solve the rod system.
- void **runOptimizationSolution** ()
Optimize viscosities of dampers.
- void **appendOutputData** (QByteArray const &data)
Process the message from the solution process.
- void **showConvergence** ()
Represent the convergence of the optimization process.
- void **showResults** ()
Represent the results obtained via KLPALGSYS.
- void **setProjectTitle** ()
Set the name of a project.
- void **setProjectData** ()
Set project data.
- void **setSolutionOptions** ()
Set the data to be used as the solution parameters.
- void **setCurrentCable** ()

- *Select a current cable.*
- void **setBlockedSignals** (bool)
(Un)Block all the signals from widget
- void **aboutProgram** ()
Show the information about the program.

Private Member Functions

- void **initialize** ()
Set the state and geometry of the central window.
- void **createContent** ()
Create all the widgets and links between them.
- void **createDefaultProject** ()
Create a default project.
- void **createDefaultSolutionOptions** ()
Create default solution options.
- void **closeEvent** (QCloseEvent *pEvent) override
Save settings and parameters of project while closing the central window.
- ads::CDockWidget * **createDamperWidget** ()
Create a widget to specify data of a damper.
- ads::CDockWidget * **createRodSystemWidget** ()
Create a widget to set and control data of a rod system.
- ads::CDockWidget * **createSupportWidget** ()
Create a widget to specify data of supports.
- ads::CDockWidget * **createCalculationWidget** ()
Create a widget to control the solution process.
- ads::CDockWidget * **createConsole** ()
Construct a widget to view solution information.
- void **specifyMenuConnections** ()
Specify menu interactions.

Private Attributes

- Ui::MainWindow * **mpUi**
- ads::CDockManager * **mpDockManager**
- [Models::RodSystemTableModel](#) * **mpRodSystemTableModel**
- [Models::DoubleSpinBoxItemDelegate](#) * **mpDoubleSpinBoxItemDelegate**
- std::shared_ptr< [Viewers::KLPGraphViewer](#) > **mpGraphViewer**
- QDoubleSpinBox * **mpMassCable**
- QDoubleSpinBox * **mpMassLoadedCable**
- QDoubleSpinBox * **mpWorkingLength**
- QDoubleSpinBox * **mpBouncerLength**
- QDoubleSpinBox * **mpSpringLength**
- QDoubleSpinBox * **mpSpringStiffness**
- QComboBox * **mpNameCable**
- QDoubleSpinBox * **mpForce**
- QDoubleSpinBox * **mpLongitudinalStiffness**
- QDoubleSpinBox * **mpVerticalStiffness**
- QSpinBox * **mpNumCalcModes**
- QSpinBox * **mpNumDampModes**

- QSpinBox * **mpStepModes**
- QDoubleSpinBox * **mpTolTrunc**
- QTextEdit * **mpConsole**
- [RSE::Core::Project](#) * **mpProject**
- [RSE::Solution::SolutionManager](#) * **mpSolutionManager**
- [RSE::Solution::SolutionOptions](#) * **mpSolutionOptions**
- [RSE::Core::IO](#) * **mpIO**
- QSharedPointer< QSettings > **mpSettings**

4.20.1 Detailed Description

Central window of the program.

The documentation for this class was generated from the following files:

- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/mainwindow.h](#)
- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/mainwindow.cpp](#)

4.21 RSE::Core::Project Class Reference

Public Member Functions

- **Project** (QString const &name, [DataBaseCables](#) dataBaseCables, [Damper](#) damper, [RodSystem](#) rodSystem, [Support](#) support)
- QString const & **name** () const
- void **setName** (QString const &name)
- [Damper](#) & **damper** ()
- [RodSystem](#) & **rodSystem** ()
- [Support](#) & **support** ()
- [DataBaseCables](#) const & **dataBaseCables** () const
- void **readTemplateData** (QString const &path)
Read template data.
- void **writeCalcData** (QString const &path, [Solution::SolutionOptions](#) const &options)
Write the computational data.

Private Member Functions

- [AbstractDataObject](#) * **addDataObject** (AbstractDataObject::ObjectType type)
Create a data object with the specified type.
- void **importDataObjects** (QString const &path, QString const &fileName)
Import several data objects from a file.
- void **readProjectID** (QString const &path)
Read the identifier of a project.
- void **modifyScalarDataObjects** ()
Modify scalar data objects.
- void **modifyVectorDataObjects** ([Spans](#) const &spans)
Modify vector data objects.
- void **writeDataObjects** (DataObjects const &dataObjects, QString const &path, QString const &fileName)
Write data objects to a file.
- void **writeRods** (QString const &path, QString const &fileName)
Write data of rods.
- void **writeProgram** (QString const &path, QString const &fileName, int numRods, int numCalcModes)
Write data of a program.

Private Attributes

- QString **mName**
Name of a project.
- [Damper](#) **mDamper**
Parameters of a damper.
- [RodSystem](#) **mRodSystem**
Parameters of a rod system.
- [Support](#) **mSupport**
Parameters of supports.
- [DataBaseCables](#) **mDataBaseCables**
Database of cables.
- DataObjects **mScalarDataObjects**
Data objects.
- DataObjects **mVectorDataObjects**
- int **mProjectID**
[Project](#) identifier.
- QStringList **mRods**
Content of the file named RODS.
- QStringList **mProgram**
Content of the file name PROG.

Static Private Attributes


- static const QString **skProjectExtension**
[Project](#) extension.

The documentation for this class was generated from the following files:

- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/project.h>
- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/project.cpp>

4.22 RSE::Viewers::PropertyTreeWidget Class Reference

Inheritance diagram for RSE::Viewers::PropertyTreeWidget:



Public Member Functions

- **PropertyTreeWidget** (QWidget *pParent=nullptr)
- void **setSelectedGraph** (PointerGraph pGraph)
Specify the single graph which properties need to be edited.

Private Member Functions

- void **initialize** ()
Intialize the widget and specify service data.
- void **updateValues** ()
Represent values of properties.
- void **createHierarchy** ()
Create a hierachy of properties: keys and empty values.
- QTreeWidgetItem * **createDirectionalDataItem** (QString const &name)
Create a nested hierarchy of directional items.
- QTreeWidgetItem * **createSliceDataItem** (QString const &name)
Create a nested hierarchy of items to slice data.
- void **createAxesLabelsItem** ()
Create an item to specify labels for axes.
- void **specifyConnections** ()
Enable widgets to communicate.
- int **currentDataIndex** (int iData, int iChild)
Get current data index.
- void **setTypeValue** (int iData)
Represent the type of the given graph data.
- void **setColorItem** (QColor const &color)
Set the color of the graph.
- void **setBlockedSignals** (bool flag)
Set the blocked state of all widgets.
- void **assignGraphData** (int iData)
Assign new graph data.
- void **assignVisualProperties** ()
Assign visual properties of current graph.
- EnumData **getEnumData** (QMetaObject const &metaObject, std::string const &nameEnumerator)
Retrieve translated keys and icons from a meta object.
- void **makeTranslationMap** ()
Specify translations for enum options.

Private Attributes

- PointerGraph **mpGraph** = nullptr
- QMap< QString, QString > **mEnumTranslator**
- QList< QTreeWidgetItem * > **mDataItems**
- QList< QTreeWidgetItem * > **mSliceDataItems**
- QComboBox * **mpLineStyleWidget**
- QSpinBox * **mpLineWidthWidget**
- QTreeWidgetItem * **mpColorItem**
- QComboBox * **mpScatterStyleWidget**
- QDoubleSpinBox * **mpScatterSizeWidget**
- QTreeWidgetItem * **mpAxesLabelsItem**

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[propertytreewidget.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[propertytreewidget.cpp](#)

4.23 KLP::Result Class Reference

Class to aggregate all the records.

```
#include <result.h>
```

Public Member Functions

- **Result** (QString const &pathFile)
- bool **isEmpty** () const
- std::vector< float > const & **time** () const
- QString const & **pathFile** () const
- int **numRods** (qint64 iFrame) const
Get the number of rods associated with the requested frame.
- qint64 **numTotalRecords** () const
- qint64 **numTimeRecords** () const
- [ResultInfo](#) **info** () const
Retrieve general information about a result file.
- [FrameCollection](#) **getFrameCollection** (qint64 iFrame) const
Retrieve the collection of the frame objects.
- void **update** ()
Retrieve the updated content from the file.

Private Member Functions

- bool **read** ()
Read all the content of the file.
- void **buildIndex** ()
Construct an object to navigate through records.
- void **setStateFrameData** ([StateFrame](#) &state, [RecordType](#) type, qint64 iFrame, qint64 iStartData, std::vector< float > const &normFactors) const
Specify state data for each direction.
- [FloatFrameObject](#) **getFrameObject** (qint64 iFrame, [RecordType](#) type, float normFactor=1.0f, qint64 shift=0) const
Get the object associated with the requested frame.

Private Attributes

- QString const **mkPathFile**
Path to the KLP file.
- QByteArray **mContent**
Content of the file.
- std::vector< [Index](#) > **mIndex**
[Index](#) of the data buffer.
- qint64 **mNumTotalRecords**
Number of records.
- std::vector< float > **mTime**
Time array.
- char **mNumBytesRod**
Number of bytes per rod.

4.23.1 Detailed Description

Class to aggregate all the records.

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/[result.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/[result.cpp](#)

4.24 KLP::ResultInfo Struct Reference

Public Attributes


- QDateTime **creationDateTime**
- qint64 **numTotalRecords** = 0
- qint64 **numTimeRecords** = 0
- uint **fileSize** = 0
- uint **ID** = -1

The documentation for this struct was generated from the following file:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/[result.h](#)

4.25 RSE::Models::ResultListModel Class Reference

Inheritance diagram for RSE::Models::ResultListModel:



Public Member Functions

- **ResultListModel** (KLP::Results &results, QObject *pParent=nullptr)
- void **updateData** ()
Update results from files.
- void **updateContent** ()
Create items linked to results.
- void **removeSelected** ()
Remove selected results.
- void **selectItem** (int iSelect=-1)
Select an item by index.

Private Member Functions

- void **clearContent** ()
Remove all the items created.

Private Attributes

- KLP::Results & **mResults**

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[resultlistmodel.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/[resultlistmodel.cpp](#)

4.26 RSE::Core::RodSystem Class Reference

Public Member Functions

- **RodSystem** (std::vector< double > distances, [Cable](#) const &cable, double force)
- std::vector< double > const & **distances** () const
- std::string const & **nameCable** () const
- double **force** () const
- int **numRods** () const
- double **massPerLength** () const
- void **setDistances** (std::vector< double > const &distances)
Specify distances between supports.
- void **setCable** ([Cable](#) const &cable)
Modify the cable used in the rod system.
- void **setForce** (double force)
- [Spans](#) **computeSpans** ()
Compute characteristics of spans.

Private Attributes

- [RodSystemParameters](#) **mParameters**
- std::string **mNameCable**

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/[rodsystem.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/[rodsystem.cpp](#)

4.27 RSE::Core::RodSystemParameters Struct Reference

Parameters of a rod system.

```
#include <rodsystem.h>
```

Public Attributes

- `std::vector< double > distances`
Distance between supports, m.
- `double massPerLength`
Mass per length, kg.
- `double youngsModulus`
Youngs modulus, Pa.
- `double area`
Area of a cross-section, m^2 .
- `double force`
Stretching force, N.
- `int numRods = 0`
Number of rods.

4.27.1 Detailed Description

Parameters of a rod system.

The documentation for this struct was generated from the following file:


- `/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/rodsystem.h`

4.28 RSE::Models::RodSystemTableModel Class Reference

Table model to set and represent data of a rod system.

```
#include <rodsystemtablemodel.h>
```

Inheritance diagram for RSE::Models::RodSystemTableModel:



Signals

- `void modified ()`

Public Member Functions

- `RodSystemTableModel (QObject *pParent=nullptr)`
- `void setRodSystem (Core::RodSystem *pRodSystem)`
Acquire the pointer to a rod system.
- `void updateContent ()`
Represent all data of a rod system.
- `void insertAfterSelected ()`
Insert fresh rows after selected ones.
- `void removeSelected ()`
Remove the selected rows.

Private Member Functions

- void **clearContent** ()
Remove all the objects created.
- void **setChangedData** (QStandardItem *pltem)
Set the changed distances between supports.

Private Attributes

- [Core::RodSystem](#) * **mpRodSystem** = nullptr

4.28.1 Detailed Description

Table model to set and represent data of a rod system.

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/[rodsystemtablemodel.h](#)
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/[rodsystemtablemodel.cpp](#)

4.29 RSE::Core::Array< T >::Row< U > Class Template Reference

Proxy class to acquire a row by index.

Public Member Functions

- **Row** (T *pData)
- T & **operator[]** (IndexType iCol)
- T const & **operator[]** (IndexType iCol) const
- T * **data** ()

Private Attributes

- T * **mpRow**

4.29.1 Detailed Description

```
template<typename T>
template<typename U>
class RSE::Core::Array< T >::Row< U >
```

Proxy class to acquire a row by index.

The documentation for this class was generated from the following file:


- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/[array.h](#)

4.30 RSE::Core::ScalarDataObject Class Reference

Scalar data object.

```
#include <scalardataobject.h>
```

Inheritance diagram for RSE::Core::ScalarDataObject:



Public Member Functions

- **ScalarDataObject** (QString const &name)
Construct a scalar data object.
- **~ScalarDataObject** ()
Decrease a number of instances while being destroyed.
- **AbstractDataObject * clone** () const override
Clone a scalar data object.
- **DataItem** & **addItem** (DataValueType key) override
Insert a new item into [ScalarDataObject](#).
- void **import** (QTextStream &stream) override
Import a scalar data object from a file.

Static Public Member Functions

- static quint32 **numberInstances** ()

Static Private Attributes

- static quint32 **smNumInstances** = 0

Additional Inherited Members

4.30.1 Detailed Description

Scalar data object.

4.30.2 Member Function Documentation

4.30.2.1 addItem()

```
DataItemType & ScalarDataObject::addItem (
    DataValueType key ) [override], [virtual]
```

Insert a new item into [ScalarDataObject](#).

Implements [RSE::Core::AbstractDataObject](#).

4.30.2.2 clone()

```
AbstractDataObject * ScalarDataObject::clone ( ) const [override], [virtual]
```

Clone a scalar data object.

Implements [RSE::Core::AbstractDataObject](#).

4.30.2.3 import()

```
void ScalarDataObject::import (
    QTextStream & stream ) [override], [virtual]
```

Import a scalar data object from a file.

Implements [RSE::Core::AbstractDataObject](#).

The documentation for this class was generated from the following files:


- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/scalardataobject.h>
- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/scalardataobject.cpp>

4.31 RSE::Solution::SolutionManager Class Reference

Class to control the solution process.

```
#include <solutionmanager.h>
```

Inheritance diagram for RSE::Solution::SolutionManager:



Public Slots

- void **stopSolution** ()
Stop the solution process.

Signals

- void **outputSent** (QByteArray)
- void **rodSystemSolved** ()
- void **optimizationSolved** ()
- void **optimizationStepPerformed** ()

Public Member Functions

- **SolutionManager** (QString const &rootPath, QString const &relativeInputPath, QString const &relativeOutputPath)
- void **solveRodSystem** (Core::Project &project, [SolutionOptions](#) const &options)
Solve a rod system.
- void **solveOptimization** (Core::Project &project, [SolutionOptions](#) const &options)
Optimize viscosities of dampers as to damp selected set of modes.
- void **runVisualizer** ()
Run the visualizer of a rod system.

Private Member Functions

- void **processRodSystemStream** ()
Process the output of the rod system solver.
- void **processOptimizationStream** ()
Process the optimization output.
- void **runParserProcess** ()
Prepare data for the optimization process.
- void **writeOptimizationInput** (QString const &pathFile, int numDampers, [SolutionOptions](#) const &options)
Write the input data for optimization of viscosities.
- int **getRodSystemStatus** ()
Check if the solution process if finished.

Private Attributes

- QString **mRootPath**
- QString **mInputPath**
- QString **mOutputPath**
- QProcess * **mpRodSystemSolver** = nullptr
- QProcess * **mpOptimizationSolver** = nullptr

4.31.1 Detailed Description

Class to control the solution process.

The documentation for this class was generated from the following files:

- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionmanager.h>
- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionmanager.cpp>

4.32 RSE::Solution::SolutionOptions Class Reference

Public Member Functions

- **SolutionOptions** (int numCalcModes, int numDampModes, int stepModes, double tolTrunc)
- int **numCalcModes** () const
- int **numDampModes** () const
- int **stepModes** () const
- double **tolTrunc** () const
- void **setNumCalcModes** (int numCalcModes)
- void **setNumDampModes** (int numDampModes)
- void **setStepModes** (int stepModes)
- void **setTolTrunc** (double tolTrunc)

Private Attributes

- int **mNumCalcModes**
Number of computational modes.
- int **mNumDampModes**
Number of modes to be damped.
- int **mStepModes**
Step through computational modes.
- double **mTolTrunc**
Limit to truncate computational modes.

The documentation for this class was generated from the following files:


- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionoptions.h>
- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionoptions.cpp>

4.33 RSE::Viewers::SpaceTimeGraphData Class Reference

Class to deal with spacetime KLP-data.

```
#include <spacetimegraphdata.h>
```

Inheritance diagram for RSE::Viewers::SpaceTimeGraphData:



Public Types

- enum **SpaceTimeType** {
stTime , **stParameter** , **stNaturalLength** , **stAccumulatedNaturalLength** ,
stCoordiante }

Public Member Functions

- **SpaceTimeGraphData** (SpaceTimeType type, Direction direction=Direction::dFull)
- GraphDataset **data** (KLP::FrameCollection const &collection) override
Retrieve the data of the specified type and direction from a given frame.
- int **type** () const override

Private Attributes

- SpaceTimeType **mType**

Additional Inherited Members

4.33.1 Detailed Description

Class to deal with spacetime KLP-data.

4.33.2 Member Function Documentation

4.33.2.1 data()

```
GraphDataset SpaceTimeGraphData::data (
    KLP::FrameCollection const & collection ) [override], [virtual]
```

Retrieve the data of the specified type and direction from a given frame.

Implements [RSE::Viewers::AbstractGraphData](#).

4.33.2.2 type()

```
int RSE::Viewers::SpaceTimeGraphData::type ( ) const [inline], [override], [virtual]
```

Implements [RSE::Viewers::AbstractGraphData](#).

The documentation for this class was generated from the following files:

- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/spacetimegraphdata.h
- /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/spacetimegraphdata.cpp

4.34 RSE::Core::Spans Struct Reference

Computed parameters of spans.

```
#include <rodsystem.h>
```

Public Member Functions

- **Spans** (int numRods)

Public Attributes

- `std::vector< double > u0`
Constant at the left end.
- `std::vector< double > uL`
Constant at the right end.
- `std::vector< double > L`
Length of a rod, m .
- `double projectedForce`
Projected stretching force, N .

4.34.1 Detailed Description

Computed parameters of spans.

The documentation for this struct was generated from the following file:

- `/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/rodsystem.h`

4.35 KLP::StateFrame Struct Reference

Kinematic and dynamic quantities associated with a frame.

```
#include <framecollection.h>
```

Public Attributes

- `FloatFrameObject displacements` [kNumDirections]
- `FloatFrameObject rotations` [kNumDirections]
- `FloatFrameObject forces` [kNumDirections]
- `FloatFrameObject moments` [kNumDirections]

4.35.1 Detailed Description

Kinematic and dynamic quantities associated with a frame.

The documentation for this struct was generated from the following file:

- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/framecollection.h>

4.36 RSE::Core::Support Class Reference

Class to aggregate data of supports.

```
#include <support.h>
```

Public Member Functions

- **Support** (double longitudinalStiffness, double verticalStiffness)
- double **longitudinalStiffness** () const
- double **verticalStiffness** () const
- void **setLongitudinalStiffness** (double longitudinalStiffness)
- void **setVerticalStiffness** (double verticalStiffness)

Private Attributes

- double **mLongitudinalStiffness**
Longitudinal stiffness (1), N/m.
- double **mVerticalStiffness**
Vertical stiffness (2), N/m.

4.36.1 Detailed Description

Class to aggregate data of supports.

The documentation for this class was generated from the following files:


- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.h>
- </home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.cpp>

4.37 RSE::Core::VectorDataObject Class Reference

Vector data object.

```
#include <vectordataobject.h>
```

Inheritance diagram for RSE::Core::VectorDataObject:



Public Member Functions

- **VectorDataObject** (QString const &name)
Construct a vector data object.
- **~VectorDataObject** ()
Decrease a number of instances while being destroyed.
- **AbstractDataObject** * **clone** () const override
Clone a vector data object.
- **DataItemType** & **addItem** (DataValueType key) override
Insert a new item into [VectorDataObject](#).
- void **import** (QTextStream &stream) override
Import a vector data object from a file.

Static Public Member Functions

- static quint32 **numberInstances** ()

Static Private Attributes

- static quint32 **smNumInstances** = 0

Additional Inherited Members

4.37.1 Detailed Description

Vector data object.

4.37.2 Member Function Documentation

4.37.2.1 addItem()

```
DataItemType & VectorDataObject::addItem (
    DataValueType key ) [override], [virtual]
```

Insert a new item into [VectorDataObject](#).

Implements [RSE::Core::AbstractDataObject](#).

4.37.2.2 clone()

```
AbstractDataObject * VectorDataObject::clone ( ) const [override], [virtual]
```

Clone a vector data object.

Implements [RSE::Core::AbstractDataObject](#).

4.37.2.3 import()

```
void VectorDataObject::import (
    QTextStream & stream ) [override], [virtual]
```

Import a vector data object from a file.

Implements [RSE::Core::AbstractDataObject](#).

The documentation for this class was generated from the following files:

- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/vectordataobject.h](#)
- [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/vectordataobject.cpp](#)

Chapter 5

File Documentation

5.1 [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/doublespinboxitemdelegate.cpp](#) File Reference

DoubleSpinBoxItemDelegate.

```
#include <QDoubleSpinBox>
#include "doublespinboxitemdelegate.h"
```

5.1.1 Detailed Description

DoubleSpinBoxItemDelegate.

Author

Date

2022

5.2 [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/doublespinboxitemdelegate.h](#) File Reference

DoubleSpinBoxItemDelegate.

```
#include <QStyledItemDelegate>
```

Classes

- class [RSE::Models::DoubleSpinBoxItemDelegate](#)
Class to specify how table values can be edited.

5.2.1 Detailed Description

DoubleSpinBoxItemDelegate.

Author

Date

2022

5.3 doublespinboxitemdelegate.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef DOUBLESPINBOXITEMDELEGATE_H
9 #define DOUBLESPINBOXITEMDELEGATE_H
10
11 #include <QStyledItemDelegate>
12
13 namespace RSE::Models
14 {
15
16
17 class DoubleSpinBoxItemDelegate : public QStyledItemDelegate
18 {
19 public:
20     DoubleSpinBoxItemDelegate(QObject* parent = nullptr);
21     QWidget* createEditor(QWidget* parent, const QStyleOptionViewItem& option, const QModelIndex& index)
22         const override;
23     void setEditorData(QWidget* pEditor, const QModelIndex& index) const override;
24     void setModelData(QWidget* pEditor, QAbstractItemModel* pModel, const QModelIndex& index) const
25         override;
26     void updateEditorGeometry(QWidget* pEditor, const QStyleOptionViewItem& option, const QModelIndex&
27         index) const override;
28 };
29 #endif // DOUBLESPINBOXITEMDELEGATE_H

```

5.4 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/central/mainwindow.cpp File Reference

Definition of the MainWindow class.

```

#include <QVBoxLayout>
#include <QGridLayout>
#include <QLabel>
#include <QTextEdit>
#include <QDoubleSpinBox>
#include <QSpinBox>
#include <QSpacerItem>
#include <QSettings>
#include <QTableView>
#include <QHeaderView>
#include <QToolBar>
#include <QComboBox>
#include <QFileDialog>
#include <QMessageBox>

```

```
#include "DockManager.h"
#include "DockWidget.h"
#include "DockAreaWidget.h"
#include "ads_globals.h"
#include "mainwindow.h"
#include "ui_mainwindow.h"
#include "uiconstants.h"
#include "rodsystemtablemodel.h"
#include "doublespinboxitemdelegate.h"
#include "core/project.h"
#include "core/solutionoptions.h"
#include "core/solutionmanager.h"
#include "core/io.h"
#include "viewers/convergenceviewer.h"
#include "viewers/klpgraphviewer.h"
```

Functions

- QDoubleSpinBox * **createDoubleField** (double value, double maxValue=1e3, int numDecimals=3)
Create a field to input a floating-point number.
- QSpinBox * **createIntegerField** (int value, int maxValue=1000)
Create a field to input an integer.

5.4.1 Detailed Description

Definition of the MainWindow class.

Author

Pavel Lakiza

Date

July 2022

5.5 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/central/mainwindow.h File Reference

Declaration of the MainWindow class.

```
#include <QMainWindow>
```

Classes

- class [RSE::App::MainWindow](#)
Central window of the program.

5.5.1 Detailed Description

Declaration of the MainWindow class.

Author

Pavel Lakiza

Date

July 2022

5.6 mainwindow.h

[Go to the documentation of this file.](#)

```
1
2
3 #ifndef MAINWINDOW_H
4 #define MAINWINDOW_H
5
6 #include <QMainWindow>
7
8 QT_BEGIN_NAMESPACE
9 namespace Ui
10 {
11     class MainWindow;
12 }
13
14 class QSettings;
15 class QDoubleSpinBox;
16 class QSpinBox;
17 class QTableView;
18 class QTextEdit;
19 class QProcess;
20 class QComboBox;
21 QT_END_NAMESPACE
22
23 namespace ads
24 {
25     class CDockManager;
26     class CDockWidget;
27 }
28
29 namespace RSE
30 {
31 }
32
33 namespace Core
34 {
35     class Project;
36     class IO;
37 }
38
39 namespace Solution
40 {
41     class SolutionManager;
42     class SolutionOptions;
43 }
44
45 namespace Models
46 {
47     class RodSystemTableModel;
48     class DoubleSpinBoxItemDelegate;
49 }
50
51 namespace Viewers
52 {
53     class KLPGraphViewer;
54 }
55
56 namespace App
57 {
58     class MainWindow : public QMainWindow
59     {
60     public:
61         Q_OBJECT
62     public:
```

```

68     MainWindow(QWidget* parent = nullptr);
69     ~MainWindow();
70     // Set parameters of a damper
71     void setMassCable(double value);
72     void setMassLoadedCable(double value);
73     void setWorkingLength(double value);
74     void setBouncerLength(double value);
75     void setSpringLength(double value);
76     void setSpringStiffness(double value);
77     // Set parameters of a rod system
78     void setCable(QString const& name);
79     void setForce(double value);
80     // Set parameters of supports
81     void setLongitudinalStiffness(double value);
82     void setVerticalStiffness(double value);
83     // Deal with projects
84     void createProject();
85     void openProjectDialog();
86     void openProject(QString const& pathFile);
87     void saveAsProject();
88     void saveProject();
89
90 private:
91     // Content
92     void initialize();
93     void createContent();
94     void createDefaultProject();
95     void createDefaultSolutionOptions();
96     void closeEvent(QCloseEvent* pEvent) override;
97     ads::CDockWidget* createDamperWidget();
98     ads::CDockWidget* createRodSystemWidget();
99     ads::CDockWidget* createSupportWidget();
100    ads::CDockWidget* createCalculationWidget();
101    ads::CDockWidget* createConsole();
102    // Signals & Slots
103    void specifyMenuConnections();
104
105 private slots:
106    // Settings
107    void saveSettings();
108    void restoreSettings();
109    // Recompute
110    void computeSpring();
111    void computeSpans();
112    // Controlling the solution process
113    void runRodSystemSolution();
114    void runOptimizationSolution();
115    void appendOutputData(QByteArray const& data);
116    void showConvergence();
117    void showResults();
118    // Set project data
119    void setProjectTitle();
120    void setProjectData();
121    void setSolutionOptions();
122    void setCurrentCable();
123    void setBlockedSignals(bool);
124    void aboutProgram();
125
126 private:
127    // GUI
128    Ui::MainWindow* mpUi;
129    ads::CDockManager* mpDockManager;
130    Models::RodSystemTableModel* mpRodSystemTableModel;
131    Models::DoubleSpinBoxItemDelegate* mpDoubleSpinBoxItemDelegate;
132    std::shared_ptr<Viewers::KLPGraphViewer> mpGraphViewer;
133    // Parameters of a damper
134    QDoubleSpinBox* mpMassCable;
135    QDoubleSpinBox* mpMassLoadedCable;
136    QDoubleSpinBox* mpWorkingLength;
137    QDoubleSpinBox* mpBouncerLength;
138    QDoubleSpinBox* mpSpringLength;
139    QDoubleSpinBox* mpSpringStiffness;
140    // Parameters of a rod system
141    QComboBox* mpNameCable;
142    QDoubleSpinBox* mpForce;
143    // Parameters of supports
144    QDoubleSpinBox* mpLongitudinalStiffness;
145    QDoubleSpinBox* mpVerticalStiffness;
146    // Options of computational process
147    QSpinBox* mpNumCalcModes;
148    QSpinBox* mpNumDampModes;
149    QSpinBox* mpStepModes;
150    QDoubleSpinBox* mpTolTrunc;
151    QTextEdit* mpConsole;
152    // Project
153    RSE::Core::Project* mpProject;
154    RSE::Solution::SolutionManager* mpSolutionManager;

```

```

155     RSE::Solution::SolutionOptions* mpSolutionOptions;
156     RSE::Core::IO* mpIO;
157     // Settings
158     QSharedPointer<QSettings> mpSettings;
159 };
160
161 }
162
163 }
164
165 #endif // MAINWINDOW_H

```

5.7 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/central/rodsystemtablemodel.cpp File Reference

Definition of the RodSystemTableModel class.

```

#include <QTableView>
#include "rodsystemtablemodel.h"
#include "core/rodsystem.h"

```

5.7.1 Detailed Description

Definition of the RodSystemTableModel class.

Author

Pavel Lakiza

Date

July 2022

5.8 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/central/rodsystemtablemodel.h File Reference

Declaration of the RodSystemTableModel class.

```

#include <QStandardItemModel>

```

Classes

- class [RSE::Models::RodSystemTableModel](#)
Table model to set and represent data of a rod system.

5.8.1 Detailed Description

Declaration of the RodSystemTableModel class.

Author

Pavel Lakiza

Date

July 2022

5.9 rodsystemtablemodel.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef RODSYSTEMTABLEMODEL_H
9 #define RODSYSTEMTABLEMODEL_H
10
11 #include <QStandardItemModel>
12
13 namespace RSE
14 {
15
16 namespace Core
17 {
18 class RodSystem;
19 }
20
21 namespace Models
22 {
23
24
25 class RodSystemTableModel : public QStandardItemModel
26 {
27     Q_OBJECT
28
29 public:
30     RodSystemTableModel(QObject* pParent = nullptr);
31     ~RodSystemTableModel() = default;
32     void setRodSystem(Core::RodSystem* pRodSystem);
33     void updateContent();
34     void insertAfterSelected();
35     void removeSelected();
36
37 signals:
38     void modified();
39
40 private:
41     void clearContent();
42     void setChangedData(QStandardItem* pItem);
43
44 private:
45     Core::RodSystem* mpRodSystem = nullptr;
46 };
47
48 }
49
50 }
51
52
53
54 #endif // RODSYSTEMTABLEMODEL_H

```

5.10 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/central/uiconstants.h File Reference

Graphical constants shared between several widgets.

```
#include <QString>
```

Variables

- `const QString RSE::UiConstants::Settings::skGeometry = "geometry"`
- `const QString RSE::UiConstants::Settings::skState = "state"`
- `const QString RSE::UiConstants::Settings::skDockingState = "dockingState"`

5.10.1 Detailed Description

Graphical constants shared between several widgets.

Author

Pavel Lakiza

Date

July 2022

5.11 uiconstants.h

[Go to the documentation of this file.](#)

```
1
8 #ifndef UICONSTANTS_H
9 #define UICONSTANTS_H
10
11 #include <QString>
12
13 namespace RSE::UiConstants
14 {
15
16     namespace Settings
17     {
18         const QString skGeometry      = "geometry";
19         const QString skState         = "state";
20         const QString skDockingState = "dockingState";
21     }
22
23 }
24
25 #endif // UICONSTANTS_H
```

5.12 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/core/abstractdataobject.cpp File Reference

Implementation of the AbstractDataObject class.

```
#include "abstractdataobject.h"
#include "constants.h"
```

5.12.1 Detailed Description

Implementation of the AbstractDataObject class.

Author

Pavel Lakiza

Date

July 2022

5.13 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/abstractdataobject.h File Reference

Declaration of the AbstractDataObject class.

```
#include <QObject>
#include <QString>
#include <QDataStream>
#include <map>
#include "array.h"
#include "aliasdata.h"
```

Classes

- class [RSE::Core::AbstractDataObject](#)
Data object which is designed in the way to be represented in a table easily.

Typedefs

- using **RSE::Core::DataItemType** = Array< DataValueType >
- using **RSE::Core::DataHolder** = std::multimap< DataKeyType, DataItemType >

Functions

- QDataStream & **RSE::Core::operator<<** (QDataStream &stream, AbstractDataObject const &obj)
Print a data object to a binary stream.

5.13.1 Detailed Description

Declaration of the AbstractDataObject class.

Author

Pavel Lakiza

Date

July 2022

5.14 abstractdataobject.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef ABSTRACTDATAOBJECT_H
9 #define ABSTRACTDATAOBJECT_H
10
11 #include <QObject>
12 #include <QString>
13 #include <QDataStream>
14 #include <map>
15 #include "array.h"
16 #include "aliasdata.h"
17
18 namespace RSE::Core
19 {
20
21 using DataItemType = Array<DataValueType>;
22 using DataHolder = std::multimap<DataKeyType, DataItemType>;
23
24 class AbstractDataObject : public QObject
25 {
26 public:
27     enum ObjectType
28     {
29         kScalar,
30         kVector,
31         kMatrix,
32         kSurface
33     };
34     AbstractDataObject(ObjectType type, QString const& name);
35     virtual ~AbstractDataObject() = 0;
36     virtual AbstractDataObject* clone() const = 0;
37     virtual DataItemType& addItem(DataKeyType key) = 0;
38     void removeItem(DataValueType key);
39     bool changeItemKey(DataKeyType oldKey, DataKeyType newKey, DataHolder* items = nullptr);
40     bool setArrayValue(DataKeyType key, DataValueType newValue, IndexType iRow = 0, IndexType iColumn = 0);
41     DataValueType arrayValue(DataKeyType key, IndexType iRow = 0, IndexType iColumn = 0);
42     std::vector<DataKeyType> keys() const;
43     quint32 numberItems() const { return mItems.size(); }
44     DataHolder const& getItems() { return mItems; }
45     DataIDType id() const { return mID; }
46     ObjectType type() const { return mkType; }
47     QString const& name() const { return mName; }
48     void setName(QString const& name) { mName = name; }
49     static DataIDType maxObjectID() { return smMaxObjectID; }
50     static void setMaxObjectID(DataIDType iMaxObjectID) { smMaxObjectID = iMaxObjectID; }
51     virtual void serialize(QDataStream& stream) const;
52     virtual void deserialize(QDataStream& stream);
53     friend QDataStream& operator<<(QDataStream& stream, AbstractDataObject const& obj);
54     virtual void import(QTextStream& stream) = 0;
55     void write(QTextStream& stream) const;
56
57 protected:
58     const ObjectType mkType;
59     QString mName;
60     DataIDType mID;
61     DataHolder mItems;
62
63 private:
64     static DataIDType smMaxObjectID;
65 };
66
67 inline QDataStream& operator<<(QDataStream& stream, AbstractDataObject const& obj)
68 {
69     obj.serialize(stream);
70     return stream;
71 }
72
73
74
75
76
77 #endif // ABSTRACTDATAOBJECT_H

```

5.15 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/core/aliasdata.h File Reference

Specification of data types used in a project.

```
#include <QtGlobal>
```

Typedefs

- using **RSE::Core::DataValueType** = double
- using **RSE::Core::DataKeyType** = double
- using **RSE::Core::DataIDType** = qint64

5.15.1 Detailed Description

Specification of data types used in a project.

Author

Pavel Lakiza

Date

May 2021

5.16 aliasdata.h

[Go to the documentation of this file.](#)

```
1
2
3 #ifndef ALIASDATA_H
4 #define ALIASDATA_H
5
6 #include <QtGlobal>
7
8 namespace RSE::Core
9 {
10
11     using DataValueType = double;
12     using DataKeyType = double;
13     using DataIDType = qint64;
14
15 }
16
17 #endif // ALIASDATA_H
```

5.17 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/core/array.cpp File Reference

Implementation of the Array class.

```
#include "array.h"
```

5.17.1 Detailed Description

Implementation of the Array class.

Author

Pavel Lakiza

Date

March 2021

5.18 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/core/array.h File Reference

Declaration of the Array class.

```
#include <QDebug>
#include "constants.h"
```

Classes

- class [RSE::Core::Array< T >](#)
Numerical array class.
- class [RSE::Core::Array< T >::Row< U >](#)
Proxy class to acquire a row by index.

Typedefs

- using **RSE::Core::IndexType** = quint32

Functions

- template<typename K >
QDebug **RSE::Core::operator**<< (QDebug stream, Array< K > &array)
Print all array values using the matrix format.
- template<typename K >
QDataStream & **RSE::Core::operator**<< (QDataStream &stream, Array< K > const &array)
Write an array to a binary stream.
- template<typename K >
QDataStream & **RSE::Core::operator**>> (QDataStream &stream, Array< K > &array)
Read an array from a stream.
- template<typename K >
QTextStream & **RSE::Core::operator**<< (QTextStream &stream, Array< K > const &array)
Write an array to a text stream.

5.18.1 Detailed Description

Declaration of the Array class.

Author

Pavel Lakiza

Date

July 2022

5.19 array.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef ARRAY_H
9 #define ARRAY_H
10
11 #include <QDebug>
12 #include "constants.h"
13
14 namespace RSE::Core
15 {
16
17 using IndexType = quint32;
18
19 template<typename T>
20 class Array
21 {
22 private:
23     template <typename U> class Row;
24
25 public:
26     Array(IndexType numRows = 0, IndexType numCols = 0);
27     Array(Array<T> const& another);
28     Array(Array<T>&& another);
29     ~Array();
30     T* data() { return mpData; }
31     void resize(IndexType numRows, IndexType numCols);
32     void removeColumn(IndexType iRemoveColumn);
33     void swapColumns(IndexType iFirstColumn, IndexType iSecondColumn);
34     void clear();
35     IndexType rows() const { return mNumRows; };
36     IndexType cols() const { return mNumCols; };
37     IndexType size() const { return mNumRows * mNumCols; };
38     Row<T> operator[](IndexType iRow) { return Row<T>(&mpData[mNumCols * iRow]); };
39     Row<T> operator[] (IndexType iRow) const { return Row<T>(&mpData[mNumCols * iRow]); };
40     Array& operator=(Array<T> const& another);
41     template<typename K> friend QDebug operator<<(QDebug stream, Array<K>& array);
42     template<typename K> friend QDataStream& operator<<(QDataStream& stream, Array<K> const& array);
43     template<typename K> friend QDataStream& operator>>(QDataStream& stream, Array<K>& array);
44     template<typename K> friend QTextStream& operator<<(QTextStream& stream, Array<K> const& array);
45     template<typename K> friend QTextStream& operator>>(QTextStream& stream, Array<K>& array);
46
47 private:
48     IndexType mNumRows;
49     IndexType mNumCols;
50     T* mpData = nullptr;
51     template <typename U>
52     class Row
53     {
54     public:
55         Row() = delete;
56         Row(T* pData) : mpRow(pData) { };
57         ~Row() { }
58         T& operator[] (IndexType iCol) { return mpRow[iCol]; }
59         T const& operator[] (IndexType iCol) const { return mpRow[iCol]; }
60         T* data() { return mpRow; }
61     private:
62         T* mpRow;
63     };
64 };
65
66 template<typename K>

```

```

72 inline QDebug operator<<(QDebug stream, Array<K>& array)
73 {
74     IndexType const& numRows = array.mNumRows;
75     IndexType const& numCols = array.mNumCols;
76     stream = stream.noquote();
77     stream << QString("Array size: %1 x %2").arg(QString::number(numRows), QString::number(numCols));
78     stream << Qt::endl;
79     for (IndexType iRow = 0; iRow != numRows; ++iRow)
80     {
81         for (IndexType jCol = 0; jCol != numCols; ++jCol)
82             stream << QString::number(array[iRow][jCol]);
83         stream << Qt::endl;
84     }
85     return stream;
86 }
87
89 template<typename K>
90 inline QDataStream& operator<<(QDataStream& stream, Array<K> const& array)
91 {
92     stream << array.mNumRows << array.mNumCols;
93     IndexType const& size = array.size();
94     for (IndexType i = 0; i != size; ++i)
95         stream << array.mpData[i];
96     return stream;
97 }
98
100 template<typename K>
101 inline QDataStream& operator>>(QDataStream& stream, Array<K>& array)
102 {
103     delete[] array.mpData;
104     stream >> array.mNumRows >> array.mNumCols;
105     IndexType const& size = array.size();
106     array.mpData = new K[size];
107     for (IndexType i = 0; i != size; ++i)
108         stream >> array.mpData[i];
109     return stream;
110 }
111
113 template<typename K>
114 inline QTextStream& operator<<(QTextStream& stream, Array<K> const& array)
115 {
116     IndexType const& numRows = array.mNumRows;
117     IndexType const& numCols = array.mNumCols;
118     for (IndexType iRow = 0; iRow != numRows; ++iRow)
119     {
120         for (IndexType jCol = 0; jCol != numCols; ++jCol)
121             stream << QString::number(array[iRow][jCol], 'g', RSE::Constants::kWritingPrecision);
122         stream << Qt::endl;
123     }
124     return stream;
125 }
126
127 }
128
129 #endif // ARRAY_H

```

5.20 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/core/constants.h File Reference

Computational constants.

Variables

- const double **RSE::Constants::kGravitationalAcceleration** = 9.8067
Gravitational acceleration, m/s².
- const int **RSE::Constants::kWritingPrecision** = 15
Number of digits to be written to a file.

5.20.1 Detailed Description

Computational constants.

Author

Pavel Lakiza

Date

July 2022

5.21 constants.h

[Go to the documentation of this file.](#)

```
1
2
3 #ifndef CONSTANTS_H
4 #define CONSTANTS_H
5
6 namespace RSE::Constants
7 {
8
9     const double kGravitationalAcceleration = 9.8067;
10
11     const int kWritingPrecision = 15;
12
13 }
14
15 #endif // CONSTANTS_H
```

5.22 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/core/damper.cpp File Reference

Definition of the Damper class.

```
#include "damper.h"
#include "constants.h"
```

5.22.1 Detailed Description

Definition of the Damper class.

Author

Pavel Lakiza

Date

July 2022

5.23 /home/qinterfly/Library/Projects/Current/RodSystem↔ Estimator/src/core/damper.h File Reference

Declaration the Damper class.

```
#include <QPair>
```

Classes

- class [RSE::Core::Damper](#)

Class to compute and collect properties of a damper.

5.23.1 Detailed Description

Declaration the Damper class.

Author

Pavel Lakiza

Date

July 2022

5.24 damper.h

[Go to the documentation of this file.](#)

```
1
2
3
4
5
6
7
8 #ifndef DAMPER_H
9 #define DAMPER_H
10
11 #include <QPair>
12
13 namespace RSE::Core
14 {
15
16
17 class Damper
18 {
19 public:
20     Damper(double massCable, double massLoadedCable, double workingLength, double bouncerLength,
21           double springLength = 0, double springStiffness = 0);
22     ~Damper() = default;
23     // Get parameteres of damper
24     double massCable() const { return mMassCable; }
25     double massLoadedCable() const { return mMassLoadedCable; }
26     double workingLength() const { return mWorkingLength; }
27     double bouncerLength() const { return mBouncerLength; }
28     double springLength() const { return mSpringLength; }
29     double springStiffness() const { return mSpringStiffness; }
30     // Set parameters of a damper
31     void setMassCable(double massCable) { mMassCable = massCable; }
32     void setMassLoadedCable(double massLoadedCable) { mMassLoadedCable = massLoadedCable; }
33     void setWorkingLength(double workingLength) { mWorkingLength = workingLength; }
34     void setBouncerLength(double bouncerLength) { mBouncerLength = bouncerLength; }
35     void setSpringLength(double springLength) { mSpringLength = springLength; }
36     void setSpringStiffness(double springStiffness) { mSpringStiffness = springStiffness; }
37     // Compute characteristics of a damper
38     void computeSpring();
39
40 private:
41     double mMassCable;
42     double mMassLoadedCable;
43     double mWorkingLength;
44     double mBouncerLength;
45     double mSpringLength = 0.0;
46     double mSpringStiffness = 0.0;
47 };
48
49
50
51
52
53
54
55
56
57 #endif // DAMPER_H
```

5.25 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/databasecables.cpp File Reference

Definition of the DataBaseCables class.

```
#include <QFile>
#include <QTextStream>
#include "databasecables.h"
```

5.25.1 Detailed Description

Definition of the DataBaseCables class.

Author

Pavel Lakiza

Date

July 2022

5.26 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/databasecables.h File Reference

Declaration of the DataBaseCables class.

```
#include <QString>
#include <unordered_map>
```

Classes

- struct [RSE::Core::Cable](#)
Mechanical properties of a cable.
- class [RSE::Core::DataBaseCables](#)
Aggregate data of cables.

5.26.1 Detailed Description

Declaration of the DataBaseCables class.

Author

Pavel Lakiza

Date

July 2022

5.27 databasecables.h

[Go to the documentation of this file.](#)

```

1
8 #ifndef DATACABLES_H
9 #define DATACABLES_H
10
11 #include <QString>
12 #include <unordered_map>
13
14 namespace RSE::Core
15 {
16
17     struct Cable
18     {
19     {
20         std::string name;
21         double bendingStiffness;
22         double torsionalStiffness;
23         double massPerLength;
24         double youngsModulus;
25         double area;
26     };
27
28     class DataBaseCables
29     {
30     {
31     public:
32         DataBaseCables(QString const& directory, QString const& fileName);
33         ~DataBaseCables() = default;
34         std::vector<std::string> names() const;
35         Cable const& getItem(std::string const& name) const { return mData.at(name); }
36
37     private:
38         bool readDataBase(QString const& pathFile);
39
40     private:
41         std::unordered_map<std::string, Cable> mData;
42     };
43 }
44
45 #endif // DATACABLES_H

```

5.28 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/core/fileutilities.cpp File Reference

Definition of utilites targeted to working with files.

```

#include <QDebug>
#include <QString>
#include <QFile>
#include <QDir>
#include <QPair>
#include "fileutilities.h"

```

5.28.1 Detailed Description

Definition of utilites targeted to working with files.

Author

Pavel Lakiza

Date

July 2022

5.29 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/fileutilities.h File Reference

Declaration of utilities targeted to working with files.

```
#include <QSharedPointer>
#include "abstractdataobject.h"
```

Functions

- QPair< Core::AbstractDataObject::ObjectType, QSharedPointer< QFile > > **RSE::Utilities::File::getDataObjectFile** (QString const &path, QString const &fileName)
Retrieve a pair consisted of a data object file and its type.
- QString **RSE::Utilities::File::loadFileContent** (QString const &path)
Load all the content of a file.

5.29.1 Detailed Description

Declaration of utilities targeted to working with files.

Author

Pavel Lakiza

Date

July 2022

5.30 fileutilities.h

[Go to the documentation of this file.](#)

```
1
2
3 #ifndef FILEUTILITIES_H
4 #define FILEUTILITIES_H
5
6 #include <QSharedPointer>
7 #include "abstractdataobject.h"
8
9 class QFile;
10 class QString;
11
12 namespace RSE
13 {
14     namespace Utilities
15     {
16         namespace File
17         {
18             QPair<Core::AbstractDataObject::ObjectType, QSharedPointer<QFile>> getDataObjectFile(QString const& path,
19                 QString const& fileName);
20             QString loadFileContent(QString const& path);
21         }
22     }
23 }
24
25 #endif // FILEUTILITIES_H
```

5.31 [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/io.cpp](#) File Reference

Definition of the IO class.

```
#include <QFile>
#include <QFileInfo>
#include <QDir>
#include "io.h"
#include "project.h"
```

5.31.1 Detailed Description

Definition of the IO class.

Author

Pavel Lakiza

Date

July 2022

5.32 [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/io.h](#) File Reference

Declaration of the IO class.

```
#include <QString>
#include <QPair>
#include "solutionoptions.h"
```

Classes

- class [RSE::Core::IO](#)
Class to save the project and solution data.

Typedefs

- using [RSE::Core::IOPair](#) = QPair< Project *, [RSE::Solution::SolutionOptions](#) * >

5.32.1 Detailed Description

Declaration of the IO class.

Author

Pavel Lakiza

Date

July 2022

5.33 io.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef IO_H
9 #define IO_H
10
11 #include <QString>
12 #include <QPair>
13 #include "solutionoptions.h"
14
15 namespace RSE
16 {
17
18     namespace Core
19     {
20
21         class Project;
22         class DataBaseCables;
23
24         using IOPair = QPair<Project*, RSE::Solution::SolutionOptions*>;
25
26         class IO
27         {
28         public:
29             IO(QString const& lastPath);
30             ~IO() = default;
31             QString const& lastPath() const { return mLastPath; }
32             QString const& extension() const { return mkProjectExtension; }
33             void saveAs(QString const& pathFile, Project& project, Solution::SolutionOptions& options);
34             IOPair open(QString const& pathFile, DataBaseCables const& dataBaseCables);
35
36         private:
37             const QString mkProjectExtension = ".rse";
38             QString mLastPath;
39         };
40     };
41
42 }
43
44 }
45
46 #endif // IO_H

```

5.34 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/core/project.cpp File Reference

Definition of the Project class.

```

#include <QFile>
#include <QLocale>
#include "project.h"
#include "scalardataobject.h"
#include "vectordataobject.h"
#include "fileutilities.h"
#include "solutionoptions.h"

```

Functions

- void **clearDataObjects** (DataObjects &dataObjects)
Helper function to clear a container consisted of pointers to data objects.
- QStringList **readAllLines** (QString const &path, QString const &fileName)
Read all the lines from a file.
- void **replaceStringEntry** (QString &string, int numSkipEntries, QString subString)
Replace a substring after specified number of skips.
- void **writeAllLines** (QStringList const &lines, QString const &path, QString const &fileName)
Write all the lines to a file.

5.34.1 Detailed Description

Definition of the Project class.

Author

Pavel Lakiza

Date

July 2022

5.35 /home/qinterfly/Library/Projects/Current/RodSystem↔ Estimator/src/core/project.h File Reference

Declaration of the Project class.

```
#include <QString>
#include "abstractdataobject.h"
#include "damper.h"
#include "rodsystem.h"
#include "support.h"
#include "databasecables.h"
```

Classes

- class [RSE::Core::Project](#)

Typedefs

- using **RSE::Core::DataObjects** = std::vector< AbstractDataObject * >

5.35.1 Detailed Description

Declaration of the Project class.

Author

Pavel Lakiza

Date

July 2022

5.36 project.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef PROJECT_H
9 #define PROJECT_H
10
11 #include <QString>
12 #include "abstractdataobject.h"
13 #include "damper.h"
14 #include "rodsystem.h"
15 #include "support.h"
16 #include "databasecables.h"
17
18 namespace RSE
19 {
20
21     namespace Solution
22     {
23         class SolutionOptions;
24     }
25
26     namespace Core
27     {
28         class ScalarDataObject;
29         class VectorDataObject;
30     }
31
32     using DataObjects = std::vector<AbstractDataObject*>;
33
34     class Project
35     {
36     public:
37         Project(QString const& name, DataBaseCables dataBaseCables, Damper damper, RodSystem rodSystem,
38             Support support);
39         ~Project();
40         QString const& name() const { return mName; }
41         void setName(QString const& name) { mName = name; }
42         Damper& damper() { return mDamper; }
43         RodSystem& rodSystem() { return mRodSystem; }
44         Support& support() { return mSupport; }
45         DataBaseCables const& dataBaseCables() const { return mDataBaseCables; }
46         // IO
47         void readTemplateData(QString const& path);
48         void writeCalcData(QString const& path, Solution::SolutionOptions const& options);
49
50     private:
51         AbstractDataObject* addDataObject(AbstractDataObject::ObjectType type);
52         void importDataObjects(QString const& path, QString const& fileName);
53         void readProjectID(QString const& path);
54         // Modify data objects
55         void modifyScalarDataObjects();
56         void modifyVectorDataObjects(Spans const& spans);
57         // IO
58         void writeDataObjects(DataObjects const& dataObjects, QString const& path, QString const& fileName);
59         void writeRods(QString const& path, QString const& fileName);
60         void writeProgram(QString const& path, QString const& fileName, int numRods, int numCalcModes);
61
62     private:
63         QString mName;
64         Damper mDamper;
65         RodSystem mRodSystem;
66         Support mSupport;
67     };
68

```

```

70     DataBaseCables mDataBaseCables;
72     DataObjects mScalarDataObjects;
73     DataObjects mVectorDataObjects;
75     int mProjectID;
77     QStringList mRods;
79     QStringList mProgram;
81     static const QString skProjectExtension;
82 };
83
84 }
85
86 }
87
88 #endif // PROJECT_H

```

5.37 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/core/rodsystem.cpp File Reference

Definition of the RodSystem class.

```

#include <functional>
#include <stdlib.h>
#include <stdio.h>
#include <gsl/gsl_multiroots.h>
#include "rodsystem.h"
#include "constants.h"
#include "databasecables.h"

```

Typedefs

- using **IntegralFun** = std::function< double(double)>

Functions

- double **integrate** (IntegralFun const &f, double const &a, double const &b, int const &n)
Compute integral using the MidPoint rule.
- double **x1** (double u, double u0, double uL)
- double **x2** (double u, double u0, double uL)
- double **Q1** (double u0, double uL)
- double **Q2** (double u, double u0, double uL)
- double **Nf** (double u, double u0, double uL)
- double **LL** (double L, double u0, double uL, [RodSystemParameters](#) const *pParameters)
- double **projForce** (double u0, double uL, double L, [RodSystemParameters](#) const *pParameters)
- int **equations** (const gsl_vector *pState, void *pVoidParameters, gsl_vector *pFun)
System of equations.

5.37.1 Detailed Description

Definition of the RodSystem class.

Author

Pavel Lakiza

Date

July 2022

5.38 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/rodsystem.h File Reference

Declaration of the RodSystem class.

```
#include <QString>
#include <vector>
#include <gsl/gsl_vector.h>
```

Classes

- struct [RSE::Core::Spans](#)
Computed parameters of spans.
- struct [RSE::Core::RodSystemParameters](#)
Parameters of a rod system.
- class [RSE::Core::RodSystem](#)

5.38.1 Detailed Description

Declaration of the RodSystem class.

Author

Pavel Lakiza

Date

July 2022

5.39 rodsystem.h

[Go to the documentation of this file.](#)

```
1
2
3 #ifndef RODSYSTEM_H
4 #define RODSYSTEM_H
5
6 #include <QString>
7 #include <vector>
8 #include <gsl/gsl_vector.h>
9
10 namespace RSE::Core
11 {
12     struct Cable;
13
14     struct Spans
15     {
16         Spans(int numRods) : u0(numRods), uL(numRods), L(numRods) { }
17
18         std::vector<double> u0;
19         std::vector<double> uL;
20         std::vector<double> L;
21         double projectedForce;
22     };
23
24     struct RodSystemParameters
25     {
```

```

39     std::vector<double> distances;
40     double massPerLength;
41     double youngsModulus;
42     double area;
43     double force;
44     int numRods = 0;
45 };
46
47 class RodSystem
48 {
49 public:
50     RodSystem(std::vector<double> distances, Cable const& cable, double force);
51     // Get parameters of a system
52     std::vector<double> const& distances() const { return mParameters.distances; }
53     std::string const& nameCable() const { return mNameCable; }
54     double force() const { return mParameters.force; }
55     int numRods() const { return mParameters.numRods; }
56     double massPerLength() const { return mParameters.massPerLength; }
57     // Set parameters of a system
58     void setDistances(std::vector<double> const& distances);
59     void setCable(Cable const& cable);
60     void setForce(double force) { mParameters.force = force; };
61     // Compute parameters of spans
62     Spans computeSpans();
63
64 private:
65     RodSystemParameters mParameters;
66     std::string mNameCable;
67 };
68
69 #endif // RODSYSTEM_H

```

5.40 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/core/scalardataobject.cpp File Reference

Implementation of the ScalarDataObject class.

```
#include "scalardataobject.h"
```

5.40.1 Detailed Description

Implementation of the ScalarDataObject class.

Author

Pavel Lakiza

Date

July 2022

5.41 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/core/scalardataobject.h File Reference

Declaration of the ScalarDataObject class.

```
#include "abstractdataobject.h"
```

Classes

- class [RSE::Core::ScalarDataObject](#)
Scalar data object.

5.41.1 Detailed Description

Declaration of the ScalarDataObject class.

Author

Pavel Lakiza

Date

July 2022

5.42 scalardataobject.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef SCALARDATAOBJECT_H
9 #define SCALARDATAOBJECT_H
10
11 #include "abstractdataobject.h"
12
13 namespace RSE::Core
14 {
15
16
17 class ScalarDataObject : public AbstractDataObject
18 {
19 public:
20     ScalarDataObject(QString const& name);
21     ~ScalarDataObject();
22     AbstractDataObject* clone() const override;
23     DataItemType& addItem(DataValueType key) override;
24     static quint32 numberInstances() { return smNumInstances; }
25     void import(QTextStream& stream) override;
26
27 private:
28     static quint32 smNumInstances;
29 };
30
31 }
32
33 #endif // SCALARDATAOBJECT_H

```

5.43 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/core/solutionmanager.cpp File Reference

Definition of the SolutionManager class.

```

#include <QFileInfo>
#include <QDir>
#include "solutionoptions.h"
#include "solutionmanager.h"

```

5.43.1 Detailed Description

Definition of the SolutionManager class.

Author

Pavel Lakiza

Date

July 2022

5.44 [/home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/solutionmanager.h](#) File Reference

Declaration of the SolutionManager class.

```
#include <QString>
#include <QProcess>
#include <QObject>
#include <QTextStream>
#include "project.h"
```

Classes

- class [RSE::Solution::SolutionManager](#)
Class to control the solution process.

5.44.1 Detailed Description

Declaration of the SolutionManager class.

Author

Pavel Lakiza

Date

July 2022

5.45 solutionmanager.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef SOLUTIONMANAGER_H
9 #define SOLUTIONMANAGER_H
10
11 #include <QString>
12 #include <QProcess>
13 #include <QObject>
14 #include <QTextStream>
15 #include "project.h"
16
17 namespace RSE::Solution
18 {
19
20 class SolutionOptions;
21
22 class SolutionManager : public QObject
23 {
24     Q_OBJECT
25
26 public:
27     SolutionManager(QString const& rootPath, QString const& relativeInputPath, QString const&
28         relativeOutputPath);
29     ~SolutionManager();
30     void solveRodSystem(Core::Project& project, SolutionOptions const& options);
31     void solveOptimization(Core::Project& project, SolutionOptions const& options);
32     void runVisualizer();
33
34 signals:
35     void outputSent(QByteArray);
36     void rodSystemSolved();
37     void optimizationSolved();
38     void optimizationStepPerformed();
39
40 public slots:
41     void stopSolution();
42
43 private:
44     void processRodSystemStream();
45     void processOptimizationStream();
46     void runParserProcess();
47     void writeOptimizationInput(QString const& pathFile, int numDampers, SolutionOptions const& options);
48     int getRodSystemStatus();
49
50 private:
51     QString mRootPath;
52     QString mInputPath;
53     QString mOutputPath;
54     QProcess* mpRodSystemSolver = nullptr;
55     QProcess* mpOptimizationSolver = nullptr;
56 };
57
58 }
59
60
61
62 #endif // SOLUTIONMANAGER_H

```

5.46 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/core/solutionoptions.cpp File Reference

Definition of the SolutionOptions class.

```
#include "solutionoptions.h"
```

5.46.1 Detailed Description

Definition of the SolutionOptions class.

Author

Pavel Lakiza

Date

July 2022

5.47 [/home/qinterfly/Library/Projects/Current/RodSystem←](#) Estimator/src/core/solutionoptions.h File Reference

Declaration of the SolutionOptions class.

Classes

- class [RSE::Solution::SolutionOptions](#)

5.47.1 Detailed Description

Declaration of the SolutionOptions class.

Author

Pavel Lakiza

Date

July 2022

5.48 solutionoptions.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef SOLUTIONOPTIONS_H
9 #define SOLUTIONOPTIONS_H
10
11 namespace RSE
12 {
13
14 namespace Solution
15 {
16
17 class SolutionOptions
18 {
19 public:
20     SolutionOptions() = default;
21     SolutionOptions(int numCalcModes, int numDampModes, int stepModes, double tolTrunc);
22     ~SolutionOptions() = default;
23     // Get parameters
24     int numCalcModes() const { return mNumCalcModes; }
25     int numDampModes() const { return mNumDampModes; }
26     int stepModes() const { return mStepModes; }
27     double tolTrunc() const { return mTolTrunc; }
28     // Set parameters
29     void setNumCalcModes(int numCalcModes) { mNumCalcModes = numCalcModes; }
30     void setNumDampModes(int numDampModes) { mNumDampModes = numDampModes; }
31     void setStepModes(int stepModes) { mStepModes = stepModes; }

```



```

32     void setTolTrunc(double tolTrunc) { mTolTrunc = tolTrunc; }
33
34 private:
35     int mNumCalcModes;
36     int mNumDampModes;
37     int mStepModes;
38     double mTolTrunc;
39 };
40
41
42
43
44
45
46
47
48
49
50 #endif // SOLUTIONOPTIONS_H

```

5.49 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.cpp File Reference ↩

Definition of the Support class.

```
#include "support.h"
```

5.49.1 Detailed Description

Definition of the Support class.

Author

Pavel Lakiza

Date

July 2022

5.50 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/support.h File Reference ↩

Declaration of the Support class.

Classes

- class [RSE::Core::Support](#)

Class to aggregate data of supports.

5.50.1 Detailed Description

Declaration of the Support class.

Author

Pavel Lakiza

Date

July 2022

5.51 support.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef SUPPORT_H
9 #define SUPPORT_H
10
11 namespace RSE::Core
12 {
13
14
15 class Support
16 {
17 public:
18     Support(double longitudinalStiffness, double verticalStiffness);
19     ~Support() = default;
20     // Get characteristics
21     double longitudinalStiffness() const { return mLongitudinalStiffness; }
22     double verticalStiffness() const { return mVerticalStiffness; }
23     // Set characteristics
24     void setLongitudinalStiffness(double longitudinalStiffness) { mLongitudinalStiffness =
        longitudinalStiffness; }
25     void setVerticalStiffness(double verticalStiffness) { mVerticalStiffness = verticalStiffness; }
26
27 private:
28     double mLongitudinalStiffness;
29     double mVerticalStiffness;
30 };
31
32
33
34 }
35
36 #endif // SUPPORT_H

```

5.52 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/core/vectordataobject.cpp File Reference

Implementation of the VectorDataObject class.

```
#include "vectordataobject.h"
```

Variables

- const IndexType **skNumElements** = 3

5.52.1 Detailed Description

Implementation of the VectorDataObject class.

Author

Pavel Lakiza

Date

July 2022

5.53 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/core/vectordataobject.h File Reference

Declaration of the VectorDataObject class.

```
#include "abstractdataobject.h"
```

Classes

- class [RSE::Core::VectorDataObject](#)
Vector data object.

5.53.1 Detailed Description

Declaration of the VectorDataObject class.

Author

Pavel Lakiza

Date

July 2022

5.54 vectordataobject.h

[Go to the documentation of this file.](#)

```
1
2
3
4
5
6
7
8 #ifndef VECTORDATAOBJECT_H
9 #define VECTORDATAOBJECT_H
10
11 #include "abstractdataobject.h"
12
13 namespace RSE::Core
14 {
15
16
17 class VectorDataObject : public AbstractDataObject
18 {
19 public:
20     VectorDataObject(QString const& name);
21     ~VectorDataObject();
22     AbstractDataObject* clone() const override;
23     DataItemType& addItem(DataValueType key) override;
24     static quint32 numberInstances() { return smNumInstances; }
25     void import(QTextStream& stream) override;
26
27 private:
28     static quint32 smNumInstances;
29 };
30
31 }
32
33 #endif // VECTORDATAOBJECT_H
```

5.55 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/klp/aliasklp.h File Reference

Declaration of aliases used in KLP results.

```
#include <vector>
#include <memory>
```

Typedefs

- using **KLP::Results** = std::vector< std::shared_ptr< Result > >

5.55.1 Detailed Description

Declaration of aliases used in KLP results.

Author

Pavel Lakiza

Date

July 2022

5.56 aliasklp.h

[Go to the documentation of this file.](#)

```
1
2
3
4
5
6
7
8 #ifndef ALIASKLP_H
9 #define ALIASKLP_H
10
11 #include <vector>
12 #include <memory>
13
14 namespace KLP
15 {
16
17 class Result;
18 using Results = std::vector<std::shared_ptr<Result>;
19
20 }
21
22 #endif // ALIASKLP_H
```

5.57 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/klp/framecollection.h File Reference

Collection of the data associated with the specified frame.

```
#include "frameobject.h"
```

Classes

- struct [KLP::EnergyFrame](#)
Energy quantities associated with a frame.
- struct [KLP::StateFrame](#)
Kinematic and dynamic quantities associated with a frame.
- struct [KLP::FrameCollection](#)
Set of all quantities belonged to a frame.

Typedefs

- using **KLP::FloatFrameObject** = FrameObject< float >

Variables

- const int **KLP::kNumDirections** = 3

5.57.1 Detailed Description

Collection of the data associated with the specified frame.

Author

Pavel Lakiza

Date

July 2022

5.58 framecollection.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef FRAMECOLLECTION_H
9 #define FRAMECOLLECTION_H
10
11 #include "frameobject.h"
12
13 namespace KLP
14 {
15
16     const int kNumDirections = 3;
17
18     using FloatFrameObject = FrameObject<float>;
19
20     struct EnergyFrame
21     {
22     public:
23         FloatFrameObject kinetic;
24         FloatFrameObject potential;
25         FloatFrameObject full;
26     };
27
28     struct StateFrame
29     {
30     public:
31         FloatFrameObject displacements[kNumDirections];
32         FloatFrameObject rotations[kNumDirections];
33         FloatFrameObject forces[kNumDirections];
34         FloatFrameObject moments[kNumDirections];
35     };

```

```

36
37 struct FrameCollection
38 {
39     int numRods;
40     float time;
41     FloatFrameObject parameter;
42     FloatFrameObject naturalLength;
43     FloatFrameObject accumulatedNaturalLength;
44     FloatFrameObject coordinates[kNumDirections];
45     StateFrame state;
46     StateFrame projectedState;
47     StateFrame firstDerivativeState;
48     StateFrame secondDerivativeState;
49     StateFrame errorState;
50     FloatFrameObject strain;
51     std::vector<StateFrame> modalStates;
52     FloatFrameObject frequencies;
53     EnergyFrame energy;
54 };
55
56 #endif // FRAMECOLLECTION_H

```

5.59 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/klp/frameobject.cpp File Reference

Definition of the FrameObject class.

```
#include "frameobject.h"
```

5.59.1 Detailed Description

Definition of the FrameObject class.

Author

Pavel Lakiza

Date

July 2022

5.60 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/klp/frameobject.h File Reference

Declaration of the FrameObject class.

```
#include <QDebug>
#include "frameobjectiterator.h"
```

Classes

- class [KLP::FrameObject< T >](#)

Functions

- `template<typename K >`
`QDebug KLP::operator<< (QDebug stream, FrameObject< K > &frameObject)`

5.60.1 Detailed Description

Declaration of the FrameObject class.

Author

Pavel Lakiza

Date

July 2022

5.61 frameobject.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef FRAMEOBJECT_H
9 #define FRAMEOBJECT_H
10
11 #include <QDebug>
12 #include "frameobjectiterator.h"
13
14 namespace KLP
15 {
16
17 template <typename T>
18 class FrameObject
19 {
20 public:
21     using iterator = FrameObjectIterator<T>;
22
23 public:
24     FrameObject(T const* pData = nullptr, T normFactor = 1.0, qint64 size = 0, qint64 step = 1);
25     ~FrameObject() = default;
26     bool isEmpty() const { return !mpData; }
27     qint64 size() const { return mSize; }
28     iterator begin() const { return iterator(&mpData[0], mNormFactor, mStep); }
29     iterator end() const { return iterator(&mpData[mSize], mNormFactor, mStep); }
30     iterator operator[](int index) const { return begin() + index; }
31     template<typename K> friend QDebug operator<<(QDebug stream, FrameObject<K>& frameObject);
32
33 private:
34     T const* mpData;
35     T mNormFactor;
36     qint64 mSize;
37     qint64 mStep;
38 };
39
40 template<typename K>
41 inline QDebug operator<<(QDebug stream, FrameObject<K>& frameObject)
42 {
43     stream = stream.noquote();
44     for (auto it = frameObject.begin(); it != frameObject.end(); ++it)
45         stream << QString::number(*it) << Qt::endl;
46     return stream;
47 }
48
49 }
50
51 #endif // FRAMEOBJECT_H

```

5.62 [/home/qinterfly/Library/Projects/Current/RodSystem←](#) Estimator/src/klp/frameobjectiterator.cpp File Reference

Definition of the FrameObjectIterator class.

```
#include "frameobjectiterator.h"
```

5.62.1 Detailed Description

Definition of the FrameObjectIterator class.

Author

Pavel Lakiza

Date

July 2022

5.63 [/home/qinterfly/Library/Projects/Current/RodSystem←](#) Estimator/src/klp/frameobjectiterator.h File Reference

Declaration of the FrameObjectIterator class.

```
#include <QtGlobal>
```

Classes

- class [KLP::FrameObjectIterator< T >](#)
Class to iterate through data of a record.

5.63.1 Detailed Description

Declaration of the FrameObjectIterator class.

Author

Pavel Lakiza

Date

July 2022

5.64 frameobjectiterator.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef FRAMEOBJECTITERATOR_H
9 #define FRAMEOBJECTITERATOR_H
10
11 #include <QtGlobal>
12
13 namespace KLP
14 {
15
16
17 template <typename T>
18 class FrameObjectIterator
19 {
20 public:
21     using self_type          = FrameObjectIterator<T>;
22     using iterator_category  = std::random_access_iterator_tag;
23     using difference_type    = std::ptrdiff_t;
24     using value_type         = T;
25     using pointer            = T const*;
26     using reference          = T const&;
27
28 public:
29     FrameObjectIterator(pointer pData, T normFactor, qint64 step);
30     // Access
31     value_type operator*() { return *mpData * mNormFactor; }
32     // Operators
33     self_type& operator++() { mpData += mStep; return *this; }
34     self_type operator++(int) { self_type temp = *this; ++(*this); return temp; }
35     self_type operator+(const difference_type& movement) { auto pOldData = mpData; mpData += movement * mStep; self_type temp = *this; mpData = pOldData; return temp; }
36     difference_type operator-(const FrameObjectIterator& another) const { return mpData - another.mpData; }
37     // Comparison
38     friend bool operator==(self_type const& first, self_type const& second) { return first.mpData == second.mpData; }
39     friend bool operator!=(self_type const& first, self_type const& second) { return !(first == second); }
40
41 private:
42     pointer mpData;
43     T mNormFactor;
44     qint64 const mStep;
45 };
46
47 }
48
49 #endif // FRAMEOBJECTITERATOR_H

```

5.65 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/klp/index.h File Reference

Specification of a structure to index records.

```

#include <QtGlobal>
#include "types.h"
#include <vector>

```

Classes

- struct [KLP::IndexData](#)
Data of each record.
- struct [KLP::Index](#)
Structure to navigate through records.

5.65.1 Detailed Description

Specification of a structure to index records.

Author

Pavel Lakiza

Date

July 2022

5.66 index.h

[Go to the documentation of this file.](#)

```

1
2 #ifndef INDEX_H
3 #define INDEX_H
4
5 #include <QtGlobal>
6 #include "types.h"
7 #include <vector>
8
9 namespace KLP
10 {
11
12 struct IndexData
13 {
14     quint64 position = 0;
15     quint64 size = 0;
16     quint64 step = 1;
17     quint64 partSize = 0;
18 };
19
20 struct Index
21 {
22     Index() { data.resize(RecordType::MAX_RECORD); }
23     std::vector<IndexData> data;
24     quint64 recordShift = 0;
25     quint64 relativeDataShift = 0;
26 };
27
28 }
29 #endif // INDEX_H

```

5.67 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/klp/result.cpp File Reference

Definition of the Result class.

```

#include <QFile>
#include <QDateTime>
#include "result.h"

```

5.67.1 Detailed Description

Definition of the Result class.

Author

Pavel Lakiza

Date

July 2022

5.68 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/klp/result.h File Reference

Declaration of the Result class.

```
#include <QString>
#include <QDateTime>
#include "index.h"
#include "framecollection.h"
```

Classes

- struct [KLP::ResultInfo](#)
- class [KLP::Result](#)

Class to aggregate all the records.

5.68.1 Detailed Description

Declaration of the Result class.

Author

Pavel Lakiza

Date

July 2022

5.69 result.h

[Go to the documentation of this file.](#)

```

1
8 #ifndef RESULT_H
9 #define RESULT_H
10
11 #include <QString>
12 #include <QDateTime>
13 #include "index.h"
14 #include "framecollection.h"
15
16 namespace KLP
17 {
18
19 struct ResultInfo
20 {
21     QDateTime creationDateTime;
22     quint64 numTotalRecords = 0;
23     quint64 numTimeRecords = 0;
24     uint fileSize = 0;
25     uint ID = -1;
26 };
27
28 class Result
29 {
30 public:
31     explicit Result(QString const& pathFile);
32     ~Result() = default;
33     bool isEmpty() const { return mContent.isEmpty(); }
34     std::vector<float> const& time() const { return mTime; }
35     QString const& pathFile() const { return mkPathFile; }
36     int numRods(quint64 iFrame) const;
37     quint64 numTotalRecords() const { return mNumTotalRecords; }
38     quint64 numTimeRecords() const { return mTime.size(); }
39     ResultInfo info() const;
40     FrameCollection getFrameCollection(quint64 iFrame) const;
41     void update();
42
43 private:
44     bool read();
45     void buildIndex();
46     void setStateFrameData(StateFrame& state, RecordType type, quint64 iFrame, quint64 iStartData,
47         std::vector<float> const& normFactors) const;
48     FloatFrameObject getFrameObject(quint64 iFrame, RecordType type, float normFactor = 1.0f, quint64 shift
49         = 0) const;
50 private:
51     QString const mkPathFile;
52     QByteArray mContent;
53     std::vector<Index> mIndex;
54     quint64 mNumTotalRecords;
55     std::vector<float> mTime;
56     char mNumBytesRod;
57 };
58
59 #endif // RESULT_H

```

5.70 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/klp/types.h File Reference

Specification of data types in a KLP file.

Enumerations

- enum [KLP::RecordType](#) {
R = 2 , **Xi** = 3 , **S** = 4 , **SS** = 5 ,
X1 = 6 , **X2** = 7 , **X3** = 8 , **U** = 9 ,
Ut = 10 , **Utt** = 11 , **EPS** = 12 , **UI** = 13 ,
BETA = 15 , **Qm** = 16 , **qm** = 17 , **AE** = 18 ,

```

MF = 19 , MV = 20 , ND = 21 , FM = 22 ,
ERR = 23 , MASS = 24 , RMASS = 25 , IP = 26 ,
CSM = 27 , CS = 28 , CSP = 29 , CSE = 30 ,
CSG = 31 , FI = 32 , FM2 = 33 , EM = 34 ,
EN = 35 , MAX_RECORD }

```

Types of records.

- enum `KLP::NondimensionalType` {
Time = 0 , **Displacement** = 1 , **Force** = 2 , **Moment** = 3 ,
DistributedForce = 7 , **DistributedMoment** = 8 , **Speed** = 9 , **Acceleration** = 10 ,
MAX_NONDIM }

Types of nondimensional coefficients.

5.70.1 Detailed Description

Specification of data types in a KLP file.

Author

Pavel Lakiza

Date

July 2022

5.71 types.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef TYPES_H
9 #define TYPES_H
10
11 namespace KLP
12 {
13
14     enum RecordType
15     {
16         R      = 2, // Rods
17         Xi     = 3, // Parameter
18         S      = 4, // Natural length
19         SS     = 5, // Accumulated natural length
20         X1     = 6, // Coordinate X1
21         X2     = 7, // Coordinate X2
22         X3     = 8, // Coordinate X3
23         U      = 9, // State vector: [U1, U2, U3, w1, w2, w3, Q1, Q2, Q3, M1, M2, M3]
24         Ut     = 10, // First-order derivative of the state vector with respect to time
25         Utt    = 11, // Second-order derivative of the state vector with respect to time
26         EPS    = 12, // Tensile-compressive strain
27         U1     = 13, // Projected state vector: [U1L, U2L, U3L, w1, w2, w3, Q1L, Q2L, Q3L, M1L, M2L, M3L]
28         BETA   = 15, // Rotation matrix
29         Qm     = 16, // Loads
30         qm     = 17, // Distributed loads
31         AE     = 18, // Aerodynamic
32         MF     = 19, // Eigenfrequencies
33         MV     = 20, // Eigenvectors
34         ND     = 21, // Nondimensional coefficients [use NondimensionalType to navigate]
35         FM     = 22, // Finite element model
36         ERR    = 23, // Computational errors of the state vector
37         MASS   = 24, // Total mass and the center of gravity
38         RMASS  = 25, // Masses of rods
39         IP     = 26, // Cross sections
40         CSM    = 27, // ?
41         CS     = 28, // ?
42         CSP    = 29, // ?
43         CSE    = 30, // ?
44         CSG    = 31, // ?
45     }
46
47 }
48
49 #endif

```

```

46     FI    = 32, // Finite element image: set of coordinates (X, Y, Z) to plot lines
47     FM2   = 33, // ?
48     EM    = 34, // Effective masses
49     EN    = 35, // Energy
50     MAX_RECORD
51 };
52
54 enum NondimensionalType
55 {
56     Time           = 0,
57     Displacement   = 1,
58     Force          = 2,
59     Moment         = 3,
60     DistributedForce = 7,
61     DistributedMoment = 8,
62     Speed          = 9,
63     Acceleration    = 10,
64     MAX_NONDIM
65 };
66
67 }
68
69 #endif // TYPES_H

```

5.72 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/main/main.cpp File Reference

Startup.

```

#include <QFile>
#include <QApplication>
#include "central/mainwindow.h"
#include "viewers/apputilities.h"

```

Functions

- int **main** (int argc, char *argv[])
Startup point.

5.72.1 Detailed Description

Startup.

Author

Pavel Lakiza

Date

July 2022

5.73 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/abstractgraphdata.cpp File Reference

Definition of the AbstractGraphData class.

```

#include "abstractgraphdata.h"

```

5.73.1 Detailed Description

Definition of the AbstractGraphData class.

Author

Pavel Lakiza

Date

July 2022

5.74 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/abstractgraphdata.h File Reference

Declaration of the AbstractGraphData class.

```
#include <QObject>
#include "aliasviewers.h"
#include "framecollection.h"
```

Classes

- class [RSE::Viewers::AbstractGraphData](#)

5.74.1 Detailed Description

Declaration of the AbstractGraphData class.

Author

Pavel Lakiza

Date

July 2022

5.75 abstractgraphdata.h

[Go to the documentation of this file.](#)

```

1
2 #ifndef ABSTRACTGRAPHDATA_H
3 #define ABSTRACTGRAPHDATA_H
4
5 #include <QObject>
6 #include "aliasviewers.h"
7 #include "framecollection.h"
8
9 namespace RSE::Viewers
10 {
11     class AbstractGraphData : public QObject
12     {
13         Q_OBJECT
14
15     public:
16         enum Category
17         {
18             cSpaceTime,
19             cKinematics,
20             cForce,
21             cEnergy,
22             cModal,
23             cEstimation
24         };
25         enum Direction
26         {
27             dFirst,
28             dSecond,
29             dThird,
30             dFull
31         };
32         Q_ENUM(Category)
33         Q_ENUM(Direction)
34         AbstractGraphData(Category category, Direction direction);
35         virtual ~AbstractGraphData() = 0;
36         virtual GraphDataset data(KLP::FrameCollection const& collection) = 0;
37         virtual int type() const = 0;
38         Category category() const { return mCategory; }
39         Direction direction() const { return mDirection; }
40         bool isSliced() const { return mSliceIndex > 0; }
41         qint64 sliceIndex() const { return mSliceIndex; }
42
43     protected:
44         GraphDataset getAbsoluteData(KLP::FloatFrameObject const components[]);
45         GraphDataset sliceDataByDirection(KLP::FloatFrameObject const components[], Direction direction);
46
47     protected:
48         Category mCategory;
49         Direction mDirection;
50         qint64 mSliceIndex = -1;
51     };
52 }
53
54 #endif // ABSTRACTGRAPHDATA_H

```

5.76 /home/qinterfly/Library/Projects/Current/RodSystem← Estimator/src/viewers/aliasviewers.h File Reference

Declaration of aliases used in viewers.

```

#include <QtGlobal>
#include <QVector>
#include <map>

```

Typedefs

- using **RSE::Viewers::GraphIDType** = qint64
- using **RSE::Viewers::GraphDataset** = QVector< float >
- using **RSE::Viewers::MapGraphs** = std::map< GraphIDType, std::shared_ptr< Graph > >

5.76.1 Detailed Description

Declaration of aliases used in viewers.

Author

Pavel Lakiza

Date

July 2022

5.77 aliasviewers.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef ALIASVIEWERS_H
9 #define ALIASVIEWERS_H
10
11 #include <QtGlobal>
12 #include <QVector>
13 #include <map>
14
15 namespace RSE::Viewers
16 {
17
18 class Graph;
19 using GraphIDType = qint64;
20 using GraphDataset = QVector<float>;
21 using MapGraphs = std::map<GraphIDType, std::shared_ptr<Graph>>;
22
23 }
24
25 #endif // ALIASVIEWERS_H

```

5.78 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/apputilities.cpp File Reference

Definition of utilites targeted to working with application data.

```

#include <QApplication>
#include <QFontDatabase>
#include <QScreen>
#include <QWidget>
#include "apputilities.h"
#include "fileutilities.h"

```

5.78.1 Detailed Description

Definition of utilites targeted to working with application data.

Author

Pavel Lakiza

Date

July 2022

5.79 /home/qinterfly/Library/Projects/Current/RodSystem↔ Estimator/src/viewers/apputilities.h File Reference

Declaration of utilities targeted to working with application data.

```
#include <QWidget>
```

Functions

- void **RSE::Utilities::App::setStyle** ()
Assign style features to the application.
- void **RSE::Utilities::App::moveToCenter** (QWidget *pChildWidget, QWidget *pLeadingWidget=nullptr)
Align the child widget to the center of the leading widget or, if not specified, to the screen center.

5.79.1 Detailed Description

Declaration of utilities targeted to working with application data.

Author

Pavel Lakiza

Date

July 2022

5.80 apputilities.h

[Go to the documentation of this file.](#)

```
1
2
3 #ifndef APPUTILITIES_H
4 #define APPUTILITIES_H
5
6 #include <QWidget>
7
8 namespace RSE
9 {
10     namespace Utilities
11     {
12         namespace App
13         {
14             void setStyle();
15             void moveToCenter(QWidget* pChildWidget, QWidget* pLeadingWidget = nullptr);
16         }
17     }
18 }
19
20 #endif // APPUTILITIES_H
```

5.81 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.cpp File Reference

Definition of the ConvergenceViewer class.

```
#include <QVBoxLayout>
#include "convergenceviewer.h"
```

5.81.1 Detailed Description

Definition of the ConvergenceViewer class.

Author

Pavel Lakiza

Date

July 2022

5.82 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/convergenceviewer.h File Reference

Declaration of the ConvergenceViewer class.

```
#include <QWidget>
#include "array.h"
#include "qcustomplot.h"
```

Classes

- class [RSE::Viewers::ConvergenceViewer](#)
Class to represent convergence of viscosities.

5.82.1 Detailed Description

Declaration of the ConvergenceViewer class.

Author

Pavel Lakiza

Date

July 2022

5.83 convergenceviewer.h

[Go to the documentation of this file.](#)

```

1
8 #ifndef CONVERGENCEVIEWER_H
9 #define CONVERGENCEVIEWER_H
10
11 #include <QWidget>
12 #include "array.h"
13 #include "qcustomplot.h"
14
15 namespace RSE
16 {
17
18 namespace Viewers
19 {
20
22 class ConvergenceViewer : public QWidget
23 {
24 public:
25     ConvergenceViewer(QString const& pathFile, QWidget* pParent = nullptr);
26     ~ConvergenceViewer();
27     void plot();
28
29 private:
30     void initialize();
31     bool read();
32
33 private:
34     QString const mkPathFile;
35     QCustomPlot* mpFigure;
36     QStringList mAvailableColors;
37     QVector<QCPScatterStyle::ScatterShape> mAvailableShapes;
38     QVector<int> mCalcModes;
39     Core::Array<double> mDampingValues;
40 };
41
42 }
43
44 }
45
46 #endif // CONVERGENCEVIEWER_H

```

5.84 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/graph.cpp File Reference

Definition of the Graph class.

```
#include "graph.h"
```

5.84.1 Detailed Description

Definition of the Graph class.

Author

Pavel Lakiza

Date

July 2022

5.85 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/graph.h File Reference

Declaration of the Graph class.

```
#include <QString>
#include <QColor>
#include "qcustomplot.h"
#include "abstractgraphdata.h"
#include "aliasviewers.h"
```

Classes

- class [RSE::Viewers::Graph](#)

5.85.1 Detailed Description

Declaration of the Graph class.

Author

Pavel Lakiza

Date

July 2022

5.86 graph.h

[Go to the documentation of this file.](#)

```
1
2
3 8 #ifndef GRAPH_H
4 9 #define GRAPH_H
5 10
6 11 #include <QString>
7 12 #include <QColor>
8 13 #include "qcustomplot.h"
9 14 #include "abstractgraphdata.h"
10 15 #include "aliasviewers.h"
11 16
12 17 namespace RSE::Viewers
13 18 {
14 19
15 20 class Graph
16 21 {
17 22 public:
18 23     Graph(QString const& name);
19 24     ~Graph();
20 25     // Getters
21 26     static GraphIDType maxGraphID() { return smMaxGraphID; }
22 27     QString const& name() const { return mName; }
23 28     GraphIDType id() const { return mID; }
24 29     AbstractGraphData** data() { return mpData; }
25 30     QCPGraph::LineStyle lineStyle() const { return mLineStyle; }
26 31     uint lineWidth() const { return mLineWidth; }
27 32     QColor color() const { return mColor; }
28 33     QCPScatterStyle scatterStyle() const { return mScatterStyle; }
29 34     double scatterSize() const { return mScatterSize; }
30 35     QStringList const& axesLabels() const { return mAxesLabels; }
```

```

36 // Setters
37 void setName(QString const& name) { mName = name; }
38 void setData(AbstractGraphData* pData, int iData);
39 void setData(AbstractGraphData* pXData = nullptr, AbstractGraphData* pYData = nullptr,
AbstractGraphData* pZData = nullptr);
40 void eraseData(int iData) { setData(nullptr, iData); }
41 void setLineStyle(QCPGraph::LineStyle const& lineStyle) { mLineStyle = lineStyle; }
42 void setLineWidth(uint lineWidth) { mLineWidth = lineWidth; }
43 void setColor(QColor const& color) { mColor = color; }
44 void setScatterStyle(QCPScatterStyle const& scatterStyle) { mScatterStyle = scatterStyle; }
45 void setScatterSize(double scatterSize) { mScatterSize = scatterSize; }
46 void setAxesLabels(QStringList const& axesLabels) { mAxesLabels = axesLabels; }
47
48 private:
49     QString mName;
50     GraphIDType mID;
51     // Data
52     AbstractGraphData* mpData[KLP::kNumDirections] = {nullptr, nullptr, nullptr};
53     // Line options
54     QCPGraph::LineStyle mLineStyle = QCPGraph::lsLine;
55     uint mLineWidth = 1;
56     QColor mColor = Qt::blue;
57     // Scatter options
58     QCPScatterStyle mScatterStyle = QCPScatterStyle::ssNone;
59     double mScatterSize = 5;
60     // Axes labels
61     QStringList mAxesLabels = QStringList({" X", " Y", " Z"});
62
63 private:
64     static GraphIDType smMaxGraphID;
65 };
66
67 }
68
69 #endif // GRAPH_H

```

5.87 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/graphlistmodel.cpp File Reference

Definition of the GraphListModel class.

```

#include <QListView>
#include "graphlistmodel.h"
#include "graph.h"

```

5.87.1 Detailed Description

Definition of the GraphListModel class.

Author

Pavel Lakiza

Date

July 2022

5.88 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/graphlistmodel.h File Reference

Declaration of the GraphListModel class.

```

#include <QStandardItemModel>
#include "aliasviewers.h"

```

Classes

- class [RSE::Models::GraphListModel](#)

5.88.1 Detailed Description

Declaration of the GraphListModel class.

Author

Pavel Lakiza

Date

July 2022

5.89 graphlistmodel.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef GRAPHLISTMODEL_H
9 #define GRAPHLISTMODEL_H
10
11 #include <QStandardItemModel>
12 #include "aliasviewers.h"
13
14 namespace RSE
15 {
16
17 namespace Models
18 {
19
20 class GraphListModel : public QStandardItemModel
21 {
22     Q_OBJECT
23
24 public:
25     GraphListModel(Viewers::MapGraphs& graphs, QObject* pParent = nullptr);
26     void create();
27     void updateContent();
28     void removeSelected();
29     void selectItem(int iSelect = -1);
30
31 private:
32     void clearContent();
33     void renameItem(QStandardItem* pItem);
34
35 private:
36     Viewers::MapGraphs& mGraphs;
37 };
38
39 }
40
41 }
42
43 #endif // GRAPHLISTMODEL_H

```

5.90 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/kinematicsgraphdata.cpp File Reference

Definition of the KinematisGraphData class.

```

#include "kinematicsgraphdata.h"
#include "klp/framecollection.h"

```

5.90.1 Detailed Description

Definition of the KinematisGraphData class.

Author

Pavel Lakiza

Date

July 2022

5.91 [/home/qinterfly/Library/Projects/Current/RodSystem←](#) Estimator/src/viewers/kinematicsgraphdata.h File Reference

Declaration of the KinematisGraphData class.

```
#include "abstractgraphdata.h"
```

Classes

- class [RSE::Viewers::KinematicsGraphData](#)
Class to deal with kinematics of KLP-data.

5.91.1 Detailed Description

Declaration of the KinematisGraphData class.

Author

Pavel Lakiza

Date

July 2022

5.92 kinematicsgraphdata.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef KINEMATICSGRAPHDATA_H
9 #define KINEMATICSGRAPHDATA_H
10
11 #include "abstractgraphdata.h"
12
13 namespace RSE::Viewers
14 {
15
16
17 class KinematicsGraphData : public AbstractGraphData
18 {
19     Q_OBJECT
20
21 public:
22     enum KinematicsType
23     {
24         kStrain,
25         kDisplacement,
26         kRotation,
27         kSpeed,
28         kAngularSpeed,
29         kAcceleration,
30         kAngularAcceleration
31     };
32     Q_ENUM(KinematicsType)
33     KinematicsGraphData(KinematicsType type, Direction direction = Direction::dFull);
34     ~KinematicsGraphData();
35     GraphDataset data(KLP::FrameCollection const& collection) override;
36     int type() const override { return mType; }
37
38 private:
39     KinematicsType mType;
40 };
41
42 }
43
44 #endif // KINEMATICSGRAPHDATA_H

```

5.93 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/klpgraphviewer.cpp File Reference

Definition of the KLPGraphViewer class.

```

#include <QSettings>
#include <QTextEdit>
#include "qcustomplot.h"
#include "DockManager.h"
#include "DockWidget.h"
#include "DockAreaWidget.h"
#include "ads_globals.h"
#include "central/uiconstants.h"
#include "klp/result.h"
#include "apputilities.h"
#include "klpgraphviewer.h"
#include "resultlistmodel.h"
#include "graphlistmodel.h"
#include "propertytreewidget.h"

```

5.93.1 Detailed Description

Definition of the KLPGraphViewer class.

Author

Pavel Lakiza

Date

July 2022

5.94 [/home/qinterfly/Library/Projects/Current/RodSystem](#) Estimator/src/viewers/klpgraphviewer.h File Reference

Declaration of the KLPGraphViewer class.

```
#include "qcustomplot.h"  
#include "klp/aliasklp.h"  
#include "aliasviewers.h"
```

Classes

- class [RSE::Viewers::KLPGraphViewer](#)
Class to graphically represent content of KLP output files.

5.94.1 Detailed Description

Declaration of the KLPGraphViewer class.

Author

Pavel Lakiza

Date

July 2022

5.95 klpgraphviewer.h

[Go to the documentation of this file.](#)

```
1  
8 #ifndef KLPGRAPHVIEWER_H  
9 #define KLPGRAPHVIEWER_H  
10  
11 #include "qcustomplot.h"  
12 #include "klp/aliasklp.h"  
13 #include "aliasviewers.h"  
14  
15 QT_BEGIN_NAMESPACE  
16 class QSettings;  
17 QT_END_NAMESPACE  
18  
19 namespace ads  
20 {  
21 class CDockManager;  
22 class CDockWidget;
```

```

23 }
24
25 namespace KLP
26 {
27 class ResultInfo;
28 }
29
30 namespace RSE
31 {
32
33 namespace Models
34 {
35 class ResultListModel;
36 class GraphListModel;
37 }
38
39 namespace Viewers
40 {
41
42 class PropertyTreeWidget;
43
44 class KLPGraphViewer : public QWidget
45 {
46     Q_OBJECT
47
48 public:
49     KLPGraphViewer(QString const& lastPath, QSettings& settings, QWidget* pParent = nullptr);
50     ~KLPGraphViewer();
51     // Results
52     void openResultsDialog();
53     void openResults(QStringList const& locationFiles);
54     // Graphs
55     void setGraphs(MapGraphs&& graphs);
56
57 private:
58     // Content
59     void initialize();
60     void createContent();
61     ads::CDockWidget* createResultWidget();
62     ads::CDockWidget* createFigureWidget();
63     ads::CDockWidget* createConstructorWidget();
64     ads::CDockWidget* createPropertyWidget();
65     // Results
66     void processSelectedResults();
67     void showResultInfo(KLP::ResultInfo const& info);
68     // Graphs
69     void processSelectedGraphs();
70     // Settings
71     void saveSettings();
72     void restoreSettings();
73     void closeEvent(QCloseEvent* pEvent) override;
74
75 private:
76     QString mLastPath;
77     QSettings& mSettings;
78     // GUI
79     ads::CDockManager* mpDockManager = nullptr;
80     QCustomPlot* mpFigure;
81     QListView* mpListResults;
82     QTextEdit* mpTextInfo;
83     QListView* mpListGraphs;
84     RSE::Viewers::PropertyTreeWidget* mpPropertyTreeWidget;
85     // Models
86     RSE::Models::ResultListModel* mpResultListModel;
87     RSE::Models::GraphListModel* mpGraphListModel;
88     // Data
89     KLP::Results mResults;
90     MapGraphs mGraphs;
91 };
92
93
94 }
95
96 }
97
98 #endif // KLPGRAPHVIEWER_H

```

5.96 /home/qinterfly/Library/Projects/Current/RodSystemEstimator/src/viewers/propertytreewidget.cpp File Reference

Definition of the PropertyTreeWidget class.

```
#include <QMetaEnum>
#include <QComboBox>
#include <QSpinBox>
#include <QSlider>
#include <QHeaderView>
#include "propertytreewidget.h"
#include "abstractgraphdata.h"
#include "graph.h"
#include "spacetimegraphdata.h"
#include "kinematicsgraphdata.h"
```

5.96.1 Detailed Description

Definition of the PropertyTreeWidget class.

Author

Pavel Lakiza

Date

July 2022

5.97 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/propertytreewidget.h File Reference

Declaration of the PropertyTreeWidget class.

```
#include <QTreeWidget>
#include "abstractgraphdata.h"
```

Classes

- class [RSE::Viewers::PropertyTreeWidget](#)

Typedefs

- using **RSE::Viewers::PointerGraph** = std::shared_ptr< Graph >
- using **RSE::Viewers::EnumData** = QPair< QStringList, QList< QIcon > >

5.97.1 Detailed Description

Declaration of the PropertyTreeWidget class.

Author

Pavel Lakiza

Date

July 2022

5.98 propertytreewidget.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef PROPERTYTREWIDGET_H
9 #define PROPERTYTREWIDGET_H
10
11 #include <QTreeWidget>
12 #include "abstractgraphdata.h"
13
14 QT_BEGIN_NAMESPACE
15 class QComboBox;
16 class QSpinBox;
17 class QDoubleSpinBox;
18 QT_END_NAMESPACE
19
20 namespace RSE
21 {
22
23 namespace Viewers
24 {
25
26 class Graph;
27 using PointerGraph = std::shared_ptr<Graph>;
28 using EnumData = QPair<QStringList, QList<QIcon>>;
29
30 class PropertyTreeWidget : public QTreeWidget
31 {
32 public:
33     PropertyTreeWidget(QWidget* pParent = nullptr);
34     void setSelectedGraph(PointerGraph pGraph);
35
36 private:
37     void initialize();
38     void updateValues();
39     // Construct widgets
40     void createHierarchy();
41     QTreeWidgetItem* createDirectionalDataItem(QString const& name);
42     QTreeWidgetItem* createSliceDataItem(QString const& name);
43     void createAxesLabelsItem();
44     void specifyConnections();
45     // Set values of properties
46     int currentDataIndex(int iData, int iChild);
47     void setTypeValue(int iData);
48     void setColorItem(QColor const& color);
49     void setBlockedSignals(bool flag);
50     // Assign new properties to the current graph
51     void assignGraphData(int iData);
52     void assignVisualProperties();
53     // Translation of enum keys
54     EnumData getEnumData(QMetaObject const& metaObject, std::string const& nameEnumerator);
55     void makeTranslationMap();
56
57 private:
58     PointerGraph mpGraph = nullptr;
59     QMap<QString, QString> mEnumTranslator;
60     QList<QTreeWidgetItem*> mDataItems;
61     QList<QTreeWidgetItem*> mSliceDataItems;
62     QComboBox* mpLineStyleWidget;
63     QSpinBox* mpLineWidthWidget;
64     QTreeWidgetItem* mpColorItem;
65     QComboBox* mpScatterStyleWidget;
66     QDoubleSpinBox* mpScatterSizeWidget;
67     QTreeWidgetItem* mpAxesLabelsItem;
68 };
69
70 }
71
72 }
73
74 #endif // PROPERTYTREWIDGET_H

```

5.99 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/resultlistmodel.cpp File Reference

Definition of the KLPRResultListModel class.

```
#include <QFileInfo>
#include <QListView>
#include "resultlistmodel.h"
#include "klp/result.h"
```

5.99.1 Detailed Description

Definition of the KLPRestultListModel class.

Author

Pavel Lakiza

Date

July 2022

5.100 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/resultlistmodel.h File Reference

Declaration of the KLPRestultListModel class.

```
#include <QStandardItemModel>
#include "klp/aliasklp.h"
```

Classes

- class [RSE::Models::ResultListModel](#)

5.100.1 Detailed Description

Declaration of the KLPRestultListModel class.

Author

Pavel Lakiza

Date

July 2022

5.101 resultlistmodel.h

[Go to the documentation of this file.](#)

```

1
2
3
4
5
6
7
8 #ifndef RESULTLISTMODEL_H
9 #define RESULTLISTMODEL_H
10
11 #include <QStandardItemModel>
12 #include "klp/aliasklp.h"
13
14 namespace RSE
15 {
16
17     namespace Models
18     {
19
20         class ResultListModel : public QStandardItemModel
21         {
22             Q_OBJECT
23
24         public:
25             ResultListModel(KLP::Results& results, QObject* pParent = nullptr);
26             void updateData();
27             void updateContent();
28             void removeSelected();
29             void selectItem(int iSelect = -1);
30
31         private:
32             void clearContent();
33
34         private:
35             KLP::Results& mResults;
36     };
37
38 }
39
40 }
41
42 #endif // RESULTLISTMODEL_H

```

5.102 /home/qinterfly/Library/Projects/Current/RodSystem↵ Estimator/src/viewers/spacetimegraphdata.cpp File Reference

Definition of the SpaceTimeGraphData class.

```

#include "spacetimegraphdata.h"
#include "klp/framecollection.h"

```

5.102.1 Detailed Description

Definition of the SpaceTimeGraphData class.

Author

Pavel Lakiza

Date

July 2022

5.103 [/home/qinterfly/Library/Projects/Current/RodSystem](#)↵ Estimator/src/viewers/spacetimegraphdata.h File Reference

Declaration of the SpaceTimeGraphData class.

```
#include "abstractgraphdata.h"
```

Classes

- class [RSE::Viewers::SpaceTimeGraphData](#)
Class to deal with spacetime KLP-data.

5.103.1 Detailed Description

Declaration of the SpaceTimeGraphData class.

Author

Pavel Lakiza

Date

July 2022

5.104 spacetimegraphdata.h

[Go to the documentation of this file.](#)

```
1
2
3
4
5
6
7
8 #ifndef SPACETIMEGRAPHDATA_H
9 #define SPACETIMEGRAPHDATA_H
10
11 #include "abstractgraphdata.h"
12
13 namespace RSE::Viewers
14 {
15
16
17 class SpaceTimeGraphData : public AbstractGraphData
18 {
19     Q_OBJECT
20
21 public:
22     enum SpaceTimeType
23     {
24         stTime,
25         stParameter,
26         stNaturalLength,
27         stAccumulatedNaturalLength,
28         stCoordiante
29     };
30     Q_ENUM(SpaceTimeType)
31     SpaceTimeGraphData(SpaceTimeType type, Direction direction = Direction::dFull);
32     ~SpaceTimeGraphData();
33     GraphDataset data(KLP::FrameCollection const& collection) override;
34     int type() const override { return mType; }
35
36 private:
37     SpaceTimeType mType;
38 };
39
40 }
41
42 #endif // SPACETIMEGRAPHDATA_H
```