

- Vấn đề nằm ở việc R1 không biết tìm được tới PC3 thông qua R2. Vì thế ta cần định tuyến lại router.

```
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is 0.0.0.0 to network 0.0.0.0

    192.168.1.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.1.0/24 is directly connected, GigabitEthernet0/0
L       192.168.1.1/32 is directly connected, GigabitEthernet0/0
    192.168.2.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.2.0/24 is directly connected, Serial0/0/0
L       192.168.2.1/32 is directly connected, Serial0/0/0
R       192.168.3.0/24 [120/1] via 192.168.2.2, 00:00:07, Serial0/0/0
R       192.168.4.0/24 [120/1] via 192.168.2.2, 00:00:07, Serial0/0/0
R       192.168.5.0/24 [120/2] via 192.168.2.2, 00:00:07, Serial0/0/0
    209.165.200.0/24 is variably subnetted, 2 subnets, 2 masks
C       209.165.200.224/30 is directly connected, Serial0/0/1
L       209.165.200.225/32 is directly connected, Serial0/0/1
S*     0.0.0.0/0 is directly connected, Serial0/0/1
```

```
R2#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route
```

Gateway of last resort is 192.168.2.1 to network 0.0.0.0

```
R    192.168.1.0/24 [120/1] via 192.168.2.1, 00:00:17, Serial0/0/0
    192.168.2.0/24 is variably subnetted, 2 subnets, 2 masks
C    192.168.2.0/24 is directly connected, Serial0/0/0
L    192.168.2.2/32 is directly connected, Serial0/0/0
    192.168.3.0/24 is variably subnetted, 2 subnets, 2 masks
C    192.168.3.0/24 is directly connected, GigabitEthernet0/0
L    192.168.3.1/32 is directly connected, GigabitEthernet0/0
    192.168.4.0/24 is variably subnetted, 2 subnets, 2 masks
C    192.168.4.0/24 is directly connected, Serial0/0/1
L    192.168.4.2/32 is directly connected, Serial0/0/1
R    192.168.5.0/24 [120/1] via 192.168.4.1, 00:00:28, Serial0/0/1
R*   0.0.0.0/0 [120/1] via 192.168.2.1, 00:00:17, Serial0/0/0
```

Building Configuration...

[OK]

```
R3#show ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route
```

Gateway of last resort is 192.168.4.2 to network 0.0.0.0

```
R    192.168.1.0/24 [120/2] via 192.168.4.2, 00:00:23, Serial0/0/1
R    192.168.2.0/24 [120/1] via 192.168.4.2, 00:00:23, Serial0/0/1
R    192.168.3.0/24 [120/1] via 192.168.4.2, 00:00:23, Serial0/0/1
    192.168.4.0/24 is variably subnetted, 2 subnets, 2 masks
C    192.168.4.0/24 is directly connected, Serial0/0/1
L    192.168.4.1/32 is directly connected, Serial0/0/1
    192.168.5.0/24 is variably subnetted, 2 subnets, 2 masks
C    192.168.5.0/24 is directly connected, GigabitEthernet0/0
L    192.168.5.1/32 is directly connected, GigabitEthernet0/0
R*   0.0.0.0/0 [120/2] via 192.168.4.2, 00:00:23, Serial0/0/1
```

R3#