

# Development of a Java Framework for Parametric Aircraft Design

## The Performance Analysis Module



UNIVERSITÀ DEGLI STUDI DI NAPOLI  
FEDERICO II

Relatori:

prof. Fabrizio Nicolosi

prof. Agostino De Marco

Candidato:

Vittorio Trifari

M53/411

# Table of Contents

- 1 Introducing JPAD
- 2 Payload Range class
- 3 Specific Range class
- 4 High Lift Devices class
- 5 Take-Off and Landing classes



# Table of Contents

- 1 Introducing JPAD
- 2 Payload Range class
- 3 Specific Range class
- 4 High Lift Devices class
- 5 Take-Off and Landing classes



# Introducing JPAD - Java Programs for Aircraft Design

- A software toolchain for **aircraft preliminary design** and **MDO**
- A modern, user friendly, **modular framework**.
- Support for **simultaneous management/analysis** of several aircraft and/or 'varied' configurations of the same aircraft.
- Conceived for **collaborative design** activities.
- **Interoperability** with other tools/disciplines (CAD/CFD/FEM analysis).



# Main features

- Define a **parametric representations of a complete aircraft** with XML configuration/input files.
- Generate **CAD geometries** of aircraft assembly and sub-components. Measure lengths, areas, volumes.
- Perform various types of analysis (L0, L0.5, L1): **Aerodynamics, Stability & Control, Performance, Weight & Balance, Costs.**
- Exports analysis results in **XML** and **Excel formats**. Produce useful **output charts** for each analysis.
- Perform iterative analysis in order to reach an optimum configuration. (**Work in progress**)




# Java. Why?


- **Language widely supported.** This avoids the library to become obsolete due to the aging of the programming language used.
- The language promote the use of **open source libraries**, especially for I/O tasks and for complex mathematical operations.
- **Widely supported GUI frameworks** (SWT/JFace and JavaFX) and a GUI visual builders.
- **Object-Oriented paradigm** is naturally applied in the abstraction of typical Aircraft Design problems.
- Promotes **modularity**: easier to work with in an ever changing team.



# TIOBE Programming Community Index



# JPAD typical work session




# Input file

The input file type chosen is the **XML** (*eXtensible Markup Language*). It is a markup language that defines a set of rules for encoding documents in a format which is both *human-readable* and *machine-readable*; moreover its design goals of emphasize simplicity, generality and usability across the Internet.

- *Markup Language* due to the use of tags that describes the content.
- *extensible* because the markup symbols are unlimited and self-defining, so that it is possible to use a personal tag for each data.



# Input file structure prototype




```
<?xml version="1.0" encoding="utf-8"?>
<jpad_config>
  <aircraft>
    <wings>
      <wing type="WING" file="wing.xml">
        <position>
          <x unit="m">12.0</x>
          <y unit="m"> 0.0</y>
          <z unit="m"> 2.0</z>
        </position>
        <rigging_angle unit="deg">2.0</rigging_angle>
      </wing>
    </wings>
    <fuselages>
      <fuselage file="fuselage.xml">
        <position>
          <x unit="m">0.0</x>
          <y unit="m">0.0</y>
          <z unit="m">0.0</z>
        </position>
      </fuselage>
    </fuselages>
  </aircraft>
</jpad_config>
```



# JPAD Output

- XML
- Microsoft Excel
- Charts
- CAD model



Multiple aircraft analysis result comparisons

Description	Unit	Value	Value	Value	Value
Material density	kg/m³	2711.00000	2711.00000	2711.00000	2711.00000
Maximum zero fuel mass	kg	19998.24551	34774.75497	56206.95596	192272.98603
Maximum landing mass	kg	20698.42095	40968.19348	68104.61636	305739.45542
Maximum take off mass	kg	22998.24550	45516.48164	75668.59596	339684.42269
Fuselage mass	kg	3203.33333	5378.00000	8392.66667	32349.66667
Wing mass	kg	2332.50000	4722.00000	8519.00000	40195.00000
HTail mass	kg	212.00000	461.50000	619.50000	3429.50000
VTail mass	kg	275.00000	369.50000	459.00000	1938.33333
Nacelle mass	kg	143.50000	389.50000	753.00000	1321.50000
Landing gear mass	kg	763.00000	1656.33333	2076.00000	13485.50000
Structure mass	kg	7072.83333	13366.33333	21572.16667	96684.00000
Power plant mass	kg	1329.14176	4134.85560	7647.87160	22087.08000
Systems mass	kg	2324.25622	3231.22575	4447.76585	12935.29415
Furnishings and Equipment mass	kg	1252.00000	1853.00000	2891.00000	0
Manufacturer empty mass	kg	11978.23131	22585.41468	36558.80412	131706.37415
Crew mass	kg	306.05819	459.08729	535.60184	1377.26187
Operating items mass	kg	585.95600	939.25300	1292.55000	4739.35000
Operating empty mass	kg	12870.24551	23983.75497	38386.95596	137822.98603
Passengers mass	kg	6732.00000	10791.00000	14850.00000	54450.00000
ZeroFuelMass	kg	19602.24551	34774.75497	53236.95596	192272.98603



# ADOpT GUI

- **Menu bar**, holds all the available actions.
- **Toolbar**, holds the actions needed to interact with the application.
- **Project tree**, provides access to all the aircraft components and the analysis results any time.
- **3D view**, shows the CAD model which can be updated each time.
- **Log message window**, tells the status of pending operations.
- **Tab folder**, contains all the windows opened.



# ADOpT GUI - Layout


Menu bar

Toolbar


Project tree

Tab folder

ADOpT 3D Window

DIPARTIMENTO DI  
INGEGNERIA  
INDUSTRIALESEZIONE  
INGEGNERIA AEROSPAZIALE

# Interoperability




# Table of Contents

- 1 Introducing JPAD
- 2 Payload Range class
- 3 Specific Range class
- 4 High Lift Devices class
- 5 Take-Off and Landing classes



# Payload-Range chart construction

- **Point A:** Maximum payload at zero range. (**Already known**)
- **Point B:** Range at maximum payload and maximum take-off weight.
- **Point C:** Range at maximum take-off weight with maximum fuel in fuel tanks.
- **Point D:** Range with maximum fuel in fuel tanks and no payload.



## Breguet equation propeller aircraft

$$R = 603.5 \left( \frac{\eta_p}{SFC} \right) \left( \frac{L}{D} \right) \ln \left( \frac{W_i}{W_f} \right)_{\text{cruise}}$$



## Breguet equation jet aircraft

$$R = \left( \frac{V}{SFCJ} \right) \left( \frac{L}{D} \right) \ln \left( \frac{W_i}{W_f} \right)_{\text{cruise}}$$

# Payload-Range chart construction

- **Point B:**  $W_{TO,max} = W_{OE} + W_{payload,max} + W_{fuel}$
- **Point C:**  $W_{TO,max} = W_{OE} + W_{payload} + W_{fuel,max}$
- **Point D:**  $W_{TO} = W_{OE} + W_{fuel,max}$



# Payload-Range chart construction

- **Point B:**  $W_{TO,max} = W_{OE} + W_{payload,max} + W_{fuel}$
- **Point C:**  $W_{TO,max} = W_{OE} + W_{payload} + W_{fuel,max}$
- **Point D:**  $W_{TO} = W_{OE} + W_{fuel,max}$



# Payload-Range chart construction

- Point B:  $W_{TO,max} = W_{OE} + W_{payload,max} + W_{fuel}$
- Point C:  $W_{TO,max} = W_{OE} + W_{payload} + W_{fuel,max}$
- Point D:  $W_{TO} = W_{OE} + W_{fuel,max}$



# Payload-Range chart construction

- Point B:  $W_{TO,max} = W_{OE} + W_{payload,max} + W_{fuel}$
- Point C:  $W_{TO,max} = W_{OE} + W_{payload} + W_{fuel,max}$
- Point D:  $W_{TO} = W_{OE} + W_{fuel,max}$



# Payload-Range chart construction

- Point B:  $W_{TO,max} = W_{OE} + W_{payload,max} + W_{fuel}$
  - Point C:  $W_{TO,max} = W_{OE} + W_{payload} + W_{fuel,max}$
  - Point D:  $W_{TO} = W_{OE} + W_{fuel,max}$
- 
- $W_{fuel} = (1 - M_{ff}) \cdot W_{TO}$
  - $M_{ff} = \frac{W_1}{W_{TO}} \cdot \frac{W_2}{W_1} \cdot \frac{W_3}{W_2} \cdot \frac{W_4}{W_3} \cdot \frac{W_5}{W_4} \cdot \frac{W_6}{W_5} \cdot \frac{W_7}{W_6} \cdot \frac{W_8}{W_7} \cdot \frac{W_9}{W_8} \cdot \frac{W_{10}}{W_9} \cdot \frac{W_{final}}{W_{10}}$




# Payload-Range chart construction

- Point B:  $W_{TO,max} = W_{OE} + W_{payload,max} + W_{fuel}$
  - Point C:  $W_{TO,max} = W_{OE} + W_{payload} + W_{fuel,max}$
  - Point D:  $W_{TO} = W_{OE} + W_{fuel,max}$
- 
- $W_{fuel} = (1 - M_{ff}) \cdot W_{TO}$
  - $M_{ff} = \frac{W_1}{W_{TO}} \cdot \frac{W_2}{W_1} \cdot \frac{W_3}{W_2} \cdot \frac{W_4}{W_3} \cdot \frac{W_5}{W_4} \cdot \frac{W_6}{W_5} \cdot \frac{W_7}{W_6} \cdot \frac{W_8}{W_7} \cdot \frac{W_9}{W_8} \cdot \frac{W_{10}}{W_9} \cdot \frac{W_{final}}{W_{10}}$
- 
- For each point the couple Range-Payload can be calculated, where the payload for point C is obtained from the previous equations.




# Payload-Range Java class flowchart



## Flowchart for best range and chosen Mach conditions comparison



# Payload-Range Java class flowchart




Flowchart for maximum take-off mass parameterization




# Payload-Range Java class output

	<b>ATR-72</b>	<b>JPAD</b>	<b>Difference(%)</b>
<b>Range</b>	890 nmi	$\approx$ 820 nmi	$\approx$ 7.8%
<b>Payload</b>	68 pass. at 95 kg	65 pass. at 99 kg	

PAYLOAD (kg)





ATR 72-500 data (MTOM optional 22 800 kg)



# Payload-Range Java class output

	B747-100B	JPAD	Difference(%)
Range Payload	≈ 5200 nmi 452 pass. at 95 kg	≈ 5300 nmi 434 pass. at 99 kg	≈ 1.9%




# Table of Contents

- 1 Introducing JPAD
- 2 Payload Range class
- 3 Specific Range class
- 4 High Lift Devices class
- 5 Take-Off and Landing classes



# Specific Range and Cruise Grid chart

- **Cruise grid chart** is a very important tool for pilots because it allows to choose the correct speed, during the cruise phase, in order to follow some mission objectives like minimum fuel consumption or a fast cruise.
- In **Breguet equations** the focus is on the **autonomy factor A.F.**



Autonomy Factor Propeller

$$A.F. = \left( \frac{\eta_p}{SFC} \right) \left( \frac{L}{D} \right)$$

Autonomy Factor Jet

$$A.F. = \left( \frac{V}{SFCJ} \right) \left( \frac{L}{D} \right)$$




# Specific Range calculation


- From the aircraft weight in cruise condition the  $C_L$  can be calculated.
- With this  $C_L$  the related  $C_D$  can be calculated taking into account the wave drag, if present.
- From engine database the SFC can be easily calculated in the given flight condition.
- At a given speed, or with known propeller efficiency, the A.F. can be calculated.
- The specific range can be calculated from the A.F. dividing it by the aircraft weight in cruise.
- This can be done for several Mach numbers, between the maximum and minimum one from the flight envelope at that altitude, and several aircraft weights.



# Specific Range Java class flowchart



# Specific Range Java class output




ATR-72  
(6000m, M=0.43)


B747-100B  
(10000m, M=0.83)



# Specific Range Java class output




ATR-72  
(6000m, M=0.43)




B747-100B  
(10000m, M=0.83)



# Specific Range Java class output



ATR-72  
(6000m,  $M=0.43$ )



B747-100B  
(10000m,  $M=0.83$ )





# Table of Contents

- 1 Introducing JPAD
- 2 Payload Range class
- 3 Specific Range class
- 4 High Lift Devices class
- 5 Take-Off and Landing classes




# Trailing-edge devices effects

- Higher  $C_L$  at a given angle of attack and higher  $C_{L\max}$ .
- Lower stalling angle of attack.
- Lower zero-lift angle due to increasing camber.



# Leading-edge devices effects


- Extension of the linear trait of the lift curve with an increase of the stalling angle of attack and of the  $C_{L\max}$
- Higher zero-lift angle caused by leading edge deflection which reduce the actual angle of attack.
- Higher slope of the linear trait of the lift curve.



SLOTTED LEADING EDGE FLAP (SLAT)



KRUGER FLAP



LEADING EDGE FLAP



LEADING EDGE SLOT


DIPARTIMENTO DI  
INGEGNERIA  
INDUSTRIALESEZIONE  
INGEGNERIA AEROSPAZIALE

# Calculation methodologies

- Charts, semi-empirical equations and experimental data have been used to evaluate high lift devices effects. (e.g.: *Glauert's linearized theory for thin airfoils with flaps*, DATCOM, Young and Hufton experimental data)
- Effects to evaluate:
  - $\Delta C_{l0}$ ,  $\Delta C_{L0}$
  - $\Delta C_{l\max}$ ,  $\Delta C_{L\max}$
  - $C_{L\alpha,\text{flap}}$
  - $\Delta \alpha_{\text{stall,wing}}$
  - $\Delta C_{D0}$
  - $\Delta C_{M,\text{c/4}}$



# High Lift Devices Java class flowchart




# High Lift Devices Java class output

## ATR-72 @ Take-Off

- 2 Single slotted flap
- $\frac{c_f}{c} = 0.35$
- $\delta_f = 20^\circ$
- $\eta_{in, flap1} = 0.08; \eta_{out, flap1} = 0.35$
- $\eta_{in, flap2} = 0.35; \eta_{out, flap2} = 0.8$


	No Flap	Flap
$\alpha_{stall}$	$18.46^\circ$	$15.82^\circ$
$C_Lmax$	1.58	2.11
$C_{Lstar}$	0.98	1.36
$C_{L\alpha}$ (1/rad)	5.19	5.24



# High Lift Devices Java class output

## B747-100B @ Landing

- 2 Triple slotted flap + 3 Krueger slat
- $\frac{c_f}{c} = [0.18, 0.18]$
- $\frac{c_s}{c} = [0.09, 0.136, 0.187]$
- $\delta_f = 30^\circ; \delta_s = 15^\circ$
- $\frac{c'}{c}$  slat = 1.1
- $\eta_{in, flap} = [0.104, 0.411]$
- $\eta_{out, flap} = [0.357, 0.636]$
- $\eta_{in, slat} = [0.192, 0.414, 0.692]$
- $\eta_{out, slat} = [0.364, 0.648, 0.961]$




	No Flap	Flap
$\alpha_{stall}$	21.59°	27.91°
$C_{Lmax}$	1.46	2.55
$C_{Lstar}$	0.83	1.90
$C_{L\alpha}$ (1/rad)	4.121	4.186




# High lift devices effect - sensibility analysis

Input data B747-100B @ Landing		Baseline results	
Variables	Value	Variables	Value
$\delta_f$	30°	$C_{L\max}$	2.55
$\frac{c_f}{c}$	0.18	$\alpha_{\max}$	28°
Trailing edge devices type	Triple Slotted		
$\delta_s$	15°		




# High lift devices effect - sensibility analysis

Input data B747-100B @ Landing		Baseline results	
Variables	Value	Variables	Value
$\delta_f$	30°	$C_{L\max}$	2.55
$\frac{c_f}{c}$	0.18	$\alpha_{\max}$	28°
Trailing edge devices type	Triple Slotted		
$\delta_s$	15°		




# High lift devices effect - sensibility analysis

Input data B747-100B @ Landing		Baseline results	
Variables	Value	Variables	Value
$\delta_f$	30°	$C_{L\max}$	2.55
$c_f$	0.18	$\alpha_{\max}$	28°
Trailing edge devices type	Triple Slotted		
$\delta_s$	15°		



# High lift devices effect - sensibility analysis

Input data B747-100B @ Landing		Baseline results	
Variables	Value	Variables	Value
$\delta_f$	30°	$C_{L\max}$	2.55
$\frac{c_f}{c}$	0.18	$\alpha_{\max}$	28°
Trailing edge devices type	Triple Slotted		
$\delta_s$	15°		




# Table of Contents

- 1 Introducing JPAD
- 2 Payload Range class
- 3 Specific Range class
- 4 High Lift Devices class
- 5 Take-Off and Landing classes



# Take-off run description



# ODE set for the AOE take-off distance calculation

## State space representation

$$\dot{\vec{x}} = \vec{f}(\vec{x}; u)$$

$$\begin{Bmatrix} \dot{s} \\ \dot{V} \\ \dot{\gamma} \\ \dot{h} \end{Bmatrix} = \begin{Bmatrix} f_1(s, V, \gamma, h; \alpha) \\ f_2(s, V, \gamma, h; \alpha) \\ f_3(s, V, \gamma, h; \alpha) \\ f_4(s, V, \gamma, h; \alpha) \end{Bmatrix} \quad \text{with} \quad \begin{Bmatrix} x_1 = s \\ x_2 = V \\ x_3 = \gamma \\ x_4 = h \end{Bmatrix} \quad \text{and} \quad u = \alpha$$

- $f_1(\vec{x}, u) = x_2$
- $f_2(\vec{x}, u) = \frac{g}{W} \begin{cases} T(x_2) - D(x_2, u) - \mu[W - L(x_2, u)] & \text{if } S(x_2, u) < 1 \\ T(x_2) \cos u - D(x_2, u) - W \sin x_3 & \text{if } S(x_2, u) \geq 1 \end{cases}$
- $f_3(\vec{x}, u) = \frac{g}{W x_2} \begin{cases} 0 & \text{if } S(x_2, u) < 1 \\ L(x_2, u) + T(x_2) \sin u - W \cos x_3 & \text{if } S(x_2, u) \geq 1 \end{cases}$
- $f_4(\vec{x}, u) = x_2 \sin x_3$


$$S(x_2, u) = \frac{L(x_2, u)}{W \cos x_3}$$



# ODE set for the AOE take-off distance calculation

**State vector and input**  $\vec{x} = \{x_1 = s; x_2 = V; x_3 = \gamma; x_4 = h\}; u = \alpha$

- $T(x_2)$  is read from the engine database related to the take-off setting.
- $D(x_2, u) = \frac{1}{2} \rho (x_2 + V_w \cos x_3)^2 S C_D(u)$ 
  - $C_D(u) = C_{D0} + (\Delta C_{D0})_{flap+lg} + K_g \frac{C_L^2}{\pi A Re}$
  - $K_g = -622.44x^5 + 624.46x^4 - 255.24x^3 + 47.105x^2 - 0.6378x + 0.0055$
- $L(x_2, u) = \frac{1}{2} \rho (x_2 + V_w \cos x_3)^2 S C_L(u)$ 
  - $C_L(u)$  is the one from the lift curve with flaps, and eventually slats, deflected.




# ODE set for the AOE take-off distance calculation

$$u(t) = \begin{cases} \alpha_g & \text{if } t < t_{\text{Rot}} \\ \alpha_1(t) & \text{if } t \geq t_{\text{Rot}} \end{cases}$$

$$\alpha_1(t) = \dot{\alpha}(t) dt$$

$$\dot{\alpha}(t) = \begin{cases} \dot{\alpha}_0 (1 - k_\alpha \alpha) & \text{if } t_{\text{Rot}} \leq t < t_{\text{Hold}} \\ 0 & \text{if } t_{\text{Hold}} \leq t < t_{\text{Hold}} + \Delta t_{\text{Hold}} \\ \dot{\alpha}_{\text{red}} & \text{if } t_{\text{Hold}} + \Delta t_{\text{Hold}} \leq t < t_{\text{climb}} \\ 0 & \text{if } t \geq t_{\text{climb}} \end{cases}$$



# ODE set modification for the take-off in OEI condition

## OEI continued take-off

- There is a discontinuity in thrust at a specific failure speed  $V_{ef}$ .
- $T(x_2)$  is still read from the database but considering a number of engines reduced by one from the time  $t_{ef}$  at which the engine failure occurs.


## OEI aborted take-off

- The take-off run, up to the engine failure speed  $V_{ef}$ , is the same as the continued take-off one.
- The pilot reacts at a time  $t_{act}$  (generally 3 s after  $t_{ef}$ ) setting  $T(x_2)$  to 0 and activating brakes. The equation  $f_2$  changes in the following.

$$f_2(\vec{x}, u) = \frac{g}{W} \left\{ -D(x_2, u) - \mu_{brakes} [W - L(x_2, u)] \right\}$$



# Take-Off Java class flowchart



# Take-Off Java class output

- **ATR-72 and B747-100B analysis results**


- ATR-72 MTOW = 22500 kg
- B747-100B MTOW = 340194 kg
- ISA condition
- Sea Level

	Flight manual or brochure data	JPAD	Difference(%)
<b>ATR-72</b>	1300 m	1350 m	3.7%
<b>B747-100B</b>	3080 m	2868 m	6.89%



# Take-Off Java class output

- B747-100B W/S and T/W sensibility analysis



$$\text{TOP}_{25} = \frac{\left(\frac{W}{S}\right)_{\text{TO}}}{\sigma \cdot C_{L\max,\text{TO}} \cdot \left(\frac{T}{W}\right)_{\text{TO}}}$$


$$S_{\text{TO,FL}} = 37.5 \cdot \text{TOP}_{25}$$



Difference (%) = 3.40%

# Take-Off Java class output

- B747-100B W/S and T/W sensibility analysis



$$\text{TOP}_{25} = \frac{\left(\frac{W}{S}\right)_{\text{TO}}}{\sigma \cdot C_{L\max,\text{TO}} \cdot \left(\frac{T}{W}\right)_{\text{TO}}}$$

$$S_{\text{TO,FL}} = 37.5 \cdot \text{TOP}_{25}$$




Difference (%) = 4.10%



# Take-Off Java class output

- B747-100B W/S and T/W sensibility analysis



$$\text{TOP}_{25} = \frac{\left(\frac{W}{S}\right)_{\text{TO}}}{\sigma \cdot C_{L\max,\text{TO}} \cdot \left(\frac{T}{W}\right)_{\text{TO}}}$$


$$S_{\text{TO,FL}} = 37.5 \cdot \text{TOP}_{25}$$



Difference (%) = 4.61%

# Take-Off Java class output

- B747-100B W/S and T/W sensibility analysis



$$\text{TOP}_{25} = \frac{\left(\frac{W}{S}\right)_{\text{TO}}}{\sigma \cdot C_{L\max,\text{TO}} \cdot \left(\frac{T}{W}\right)_{\text{TO}}}$$

$$S_{\text{TO,FL}} = 37.5 \cdot \text{TOP}_{25}$$




Difference (%) = 4.84%




# Take-Off Java class output

- **B747-100B Take-off run (SL, 2000ft, 4000ft)**




# Take-Off Java class output

- **B747-100B Take-off run (SL, 2000ft, 4000ft)**




# Take-Off Java class output

- **B747-100B Take-off run (SL, 2000ft, 4000ft)**




# Take-Off Java class output

- **B747-100B Take-off run (SL, 2000ft, 4000ft)**




# Take-Off Java class output

- **B747-100B Take-off run (SL, 2000ft, 4000ft)**




# Take-Off Java class output

- B747-100B Take-off run (SL, 2000ft, 4000ft)



# Take-Off Java class output

- B747-100B Take-off run (SL, 2000ft, 4000ft)




DIPARTIMENTO DI  
INGEGNERIA  
INDUSTRIALE

SEZIONE  
INGEGNERIA AEROSPAZIALE

# Landing distance calculation

## Air run

- $[n = 1.2, V_{\text{Flare}} = 1.23 V_s] \rightarrow R = \frac{V^2}{g(n-1)} = \frac{V_{\text{Flare}}^2}{0.2 g}$
- $[\theta_a \approx 2^\circ \div 3^\circ] \rightarrow h_{\text{Flare}} = R(1 - \cos \theta_a)$
- $[\theta_a, R, h_{\text{Flare}}] \rightarrow S_A = \frac{50 - h_{\text{Flare}}}{\tan \theta_a}; \quad S_{\text{Flare}} = R \sin \theta_a$



# Landing distance calculation

## Ground run


$$\begin{Bmatrix} \dot{s} \\ \dot{V} \end{Bmatrix} = \begin{Bmatrix} f_1(s, V) \\ f_2(s, V) \end{Bmatrix} \quad \text{with} \quad \begin{Bmatrix} x_1 = s \\ x_2 = V \end{Bmatrix}$$

- $f_1(\vec{x}, u) = x_2$
- $f_2(\vec{x}) = \frac{g}{W} \begin{cases} -D(x_2) - \mu[W - L(x_2)] & \text{if } t \leq t_{fr} \\ -T_{Rev}(x_2) - D(x_2) - \mu_{brakes}[W - L(x_2)] & \text{if } t > t_{fr} \end{cases}$

$t_{fr}$  is related to the end of the *free-roll distance* (which represents the distance covered while the pilot reduces the power to idle, retracts the flaps, deploys the spoilers, and applies the brakes) and it's set at 3 s.



# Landing Java class flowchart



# Landing Java class output


- **ATR-72 and B747-100B analysis results**
  - ATR-72 MLW = 20757 kg
  - B747-100B MLW = 267916 kg
  - ISA condition
  - Sea Level

	Flight manual or brochure data	JPAD	Difference(%)
<b>ATR-72</b> $\delta_{flap} = 40^\circ$ $C_{Lmax} = 2.78$	1067 m	1098 m	2.82%
<b>B747-100B</b> $\delta_{flap} = 30^\circ$ $C_{Lmax} = 2.55$	1930 m	1921 m	0.44%
<b>B747-100B</b> $\delta_{flap} = 25^\circ$ $C_{Lmax} = 2.43$	2080 m	1968 m	5.40%



# Landing Java class output

- B747-100B W/S sensibility analysis



$$S_{LND,FL} = 0.3 \cdot V_a^2$$


$$V_a = 1.3 \cdot V_{sLND}$$

Difference (%) = 0.16%



# Landing Java class output

- B747-100B W/S sensibility analysis



$$S_{LND,FL} = 0.3 \cdot V_a^2$$


$$V_a = 1.3 \cdot V_{sLND}$$



Difference (%) = 2.11%


# Landing Java class output

- B747-100B Landing run charts




# Landing Java class output

- B747-100B Landing run charts




# Landing Java class output

- B747-100B Landing run charts



# Landing Java class output

- **B747-100B Landing run charts**



Introducing JPAD  
oooooooooooo

Payload Range class  
oooo

Specific Range class  
oooo

High Lift Devices class  
oooooo

Take-Off and Landing classes  
oooooooo



***THANK YOU  
FOR THE ATTENTION***