

**Bring with you dimu.java****DISTRIBUTED MUTUAL EXCLUSION ALGORITHM**

Requires total ordering of the events in the system.

A collection of threads that do not share memory, are connected to a local area network (LAN). The threads need mutual exclusion over some shared resources. In order to avoid a bottleneck a central server will not be used, rather the Distributed Algorithm for Mutual Exclusion will be used.

There will be  $N$  nodes connected by the LAN and we assume that:

- there are no lost or garbled messages.
- Messages sometimes arrive in a different order than they were sent.
- Nodes do not fail or halt.

When a process wants to enter the CS:

1) It builds a message:

**Message = name of the CS + its process ID + the current time**

2) It sends the message to all processes in the system including itself.

When a process receives a request message from another process (there are three cases):

If the receiver is not in the CS and doesn't intend to enter the CS, it sends back an "OK" message.

If the receiver is in the CS, it doesn't reply and queues the request.

If the receiver wants to enter the CS, it compares the timestamp of the incoming message with the one contained in the message sent by itself. If the incoming message is lower, the receiver sends back an "OK" message, otherwise the receiver queues the incoming request and sends nothing.

A process can enter the CS **after receiving the OK** messages from **all** of the other processes.

**Fig. The distributed algorithm for Mutual Exclusion**

-) In practice there are now  $n$  points of failure.

If one process goes down, the system goes down.

Not so easy to implement, slower and more expensive. Need to keep track of a membership list.

Improving the algorithm:

Allow a process to enter a CS when it has collected permission from a simple majority of other processes rather than from all of them.

**Dimu.java**

For parallelism each site has three threads. The following activities occur in each node:

```
While(true) {
    Noncritical section code           // outsideCS();
    ** preprotocol:
    Choose a sequence number           // chooseNumber();
    SentItToAllOthers                  // sendRequest();
    Wait for replies                   // waitForReply();

    access Critical Section           // insideCS();

    ** postprotocol:
    reply to all others (the deferreds) // replyToDeferredNodes();
}
```

Even if in normal situation the Mutual Exclusion, Progress, No Starvation and Bounded Waiting are satisfied in reality the Distributed Mutual Exclusion Algorithm it is hard to be implemented and many problems might occur.

**Hint: [SH] page 181.**