# Programmatic Modeling of Concurrent Composition and High-Order Observers

## Labeled Finite-State Automata

Zixi Wang

Xi'an Jiaotong University

Summer Research Presentation



# Problem Setting

Consider a finite-state system $G$ observed by two agents.

- Agent $A_1$ estimates the current state of $G$ from its observations.
- Agent $A_2$ has a different observation of the same execution.
- Agent $A_2$ infers the possible state estimates held by Agent $A_1$.

## Target computation

For an observation $\beta$ of Agent $A_2$, compute

$$M_{A_1 \leftarrow A_2}(G, \beta) = \{M_1(G, \ell_1(s)) : s \in L(G),\ \ell_2(s) = \beta\}.$$

# LFSA Observer and Concurrent Composition

**Labeled finite-state automaton**

$$S = (Q, E, \delta, Q_0, \Sigma, \ell), \qquad \ell : E \to \Sigma \cup \{\epsilon\}.$$

The labeling function models what an agent observes.

**Observer**

$$\delta_{\text{obs}}(q_{0,\text{obs}}, \alpha) = M(S, \alpha) \subseteq Q.$$

Each observer state is one current-state estimate.

**Concurrent composition**

$$CC(S_1, S_2)$$

It synchronizes transitions with equal observable labels and interleaves unobservable transitions.

Source: Zhang, *Annual Reviews in Control*, 56, 100902, 2023.

# Order-2 Observer Pipeline

| Stage | Transformation | Program |
|---|---|---|
| 1 | Add Agent $A_1$ labels to $G$ | `fa_agent_to_lfsa.py` |
| 2 | Build $A_1$'s observer | `observer.py` |
| 3 | Compose the system and observer | `CC.py` |
| 4 | Recover the underlying event system | `lfsa_to_fa.py` |
| 5 | Replace labels with Agent $A_2$'s view | `fa_agent_to_lfsa.py` |
| 6 | Build $A_2$'s observer | `observer.py` |

## Programmatic data flow

$$(G, A_1, A_2) \longrightarrow Obs_{A_1} \longrightarrow CC \longrightarrow Obs_{A_1 \leftarrow A_2}(G).$$

# Theorem 25 and Example 27


If reading $\beta$ reaches the order-2 observer state

$$\{(q_1, X_1), \ldots, (q_n, X_n)\},$$

then Theorem 25 gives

$$M_{A_1 \leftarrow A_2}(G, \beta) = \{X_1, \ldots, X_n\}.$$

The second components are precisely the possible estimates of Agent $A_1$.




The implementation reproduces the published five-state, five-transition order-2 observer.

Reference figure: Zhang et al., *High-Order Observers and High-Order State-Estimation-Based Properties*, Example 27.

# Complexity and Summary

Let $n = |Q|$. In the worst case,

$$|Obs_{A_1}| \leq 2^n, \qquad |CC| \leq n2^n, \qquad |Obs_{A_1 \leftarrow A_2}| \leq 2^{n2^n}.$$

Therefore, explicit construction has a double-exponential upper bound in both time and storage, although only reachable states are generated.

**Summary**

- The programs implement LFSA conversion, observers, and concurrent composition.
- The resulting order-2 observer computes Agent $A_2$'s possible inferences about Agent $A_1$.
- Example 27 provides an end-to-end validation case.