


Instruction: You must show all your work clearly for credit. Partial credit will only be given to meaningful answers.

1. (30) Given a set S of 10 records with priorities {15, 7, 10, 5, 18, 20, 15, 12, 6, 15}.
 - (a) Construct the BST T1 for S by inserting the records, in the given order, into an initially empty binary search tree. When done, delete 15 and then 18 from T1.
 - (b) Construct the BST T2 for S by inserting the records, in the reversed given order, into an initially empty binary search tree. When done, delete 15 and then 18 from T2.
 - (c) Illustrate the data structure for the final BST for T1 and T2.


Remark: You must show your BST clearly after each insert/delete operation.

Solution:


(a) BST T1:




delete(15, T1):




delete(18, T1):




(b) BST T2:



delete(15,T2):




delete(18,T2):




Remark: You must show all your BST after each insert/delete operation.

(c) DS for T1:



DS for T2:




Remark: You must illustrate all pointers, including root pointer and all null pointers, for credit.

2. Given a set R of 4 records with keys x_i , $x_1 < x_2 < \dots < x_4$, a key x , and the probability function $\Pr(x = x_i) = p_i$, with $p_1 = 0.35$, $p_2 = 0.2$, $p_3 = 0.15$, $p_4 = 0.3$, $1 \leq i \leq 4$.
- (a) (10) Construct a greedy optimal **binary search tree** T3 for R **using greedy approach** as discussed in class. Compute the average number of comparisons in finding x in T3.
- (b) (20) Construct an optimal binary search tree T4 for R using **dynamic programming technique** such that the average number of comparisons in finding x in T4 is minimized.
- Remark:* You must show your computations for all $c_{i,j}$, $t_{i,j}$, and the reconstruction of the optimal binary search tree clearly as discussed in class. Also, use **smallest k to resolve ambiguity**.

Solution:

(a) Greedy optimal BST T3:

use highest p as a root for each tree
p1, p4, p2, p3



$$T_a(n) = 1*0.35 + 2*0.3 + 3*0.2 + 4*0.15 = 2.15$$

(b) Constructing optimal BST using DP:

Given $\{x_1, x_2, x_3, x_4\}$ with $p_1 = 0.35$, $p_2 = 0.2$, $p_3 = 0.15$, $p_4 = 0.3$.

$$c_{1,1} = 0.35, c_{2,2} = 0.2, c_{3,3} = 0.15, c_{4,4} = 0.3.$$

$$c_{1,2} = \min\{c_{1,0} + c_{2,2}, c_{1,1} + c_{3,2}\} + \sum_{l=1}^2 p_l = \min\{0.2, 0.35\} + 0.55 = 0.75, t_{1,2} = 1.$$

$$c_{2,3} = \min\{c_{2,1} + c_{3,3}, c_{2,2} + c_{4,3}\} + \sum_{l=2}^3 p_l = \min\{0.15, 0.2\} + 0.35 = 0.5, t_{2,3} = 2.$$

$$c_{3,4} = \min\{c_{3,2} + c_{4,4}, c_{3,3} + c_{5,4}\} + \sum_{l=3}^4 p_l = \min\{0.3, 0.15\} + 0.45 = 0.6, t_{3,4} = 4.$$

$$c_{1,3} = \min\{c_{1,0} + c_{2,3}, c_{1,1} + c_{3,3}, c_{1,2} + c_{4,3}\} + \sum_{l=1}^3 p_l = \min\{0.5, 0.5, 0.75\} + 0.7 = 1.20, t_{1,3} = 1.$$

$$c_{2,4} = \min\{c_{2,1} + c_{3,4}, c_{2,2} + c_{4,4}, c_{2,3} + c_{5,4}\} + \sum_{l=2}^4 p_l = \min\{0.6, 0.5, 0.5\} + 0.65 = 1.15, t_{2,4} = 3.$$

$$c_{1,4} = \min\{c_{1,0} + c_{2,4}, c_{1,1} + c_{3,4}, c_{1,2} + c_{4,4}, c_{1,3} + c_{5,4}\} + \sum_{l=1}^4 p_l$$

$$= \min\{1.15, 0.95, 1.05, 1.2\} + 1.0 = 1.95, t_{1,4} = 2.$$

DP-Table:

$$\begin{array}{llll} c_{1,1} = 0.35 & c_{2,2} = 0.20 & c_{3,3} = 0.15 & c_{4,4} = 0.30 \\ t_{1,1} = 1 & t_{2,2} = 2 & t_{3,3} = 3 & t_{4,4} = 4 \end{array}$$


$$\begin{array}{lll} c_{1,2} = 0.75 & c_{2,3} = 0.50 & c_{3,4} = 0.60 \\ t_{1,2} = 1 & t_{2,3} = 2 & t_{3,4} = 4 \end{array}$$

$$\begin{array}{ll} c_{1,3} = 1.20 & c_{2,4} = 1.15 \\ t_{1,3} = 1 & t_{2,4} = 13 \end{array}$$

$$\begin{array}{l} c_{1,4} = 1.95 \\ t_{1,3} = 2 \end{array}$$

$$t_{1,4} = 2$$

Constructing Optimal BST T4:




3. Given a set H of 15 records with priorities {10, 5, 2, 15, 8, 12, 4, 1, 18, 6, 16, 11, 22, 36, 7}.
- (15) Construct the 2-3 tree T5 for H by inserting the records, in the given order, into an initially empty 2-3 tree. When done, delete 1, 15, and then 36 from T5.
 - (15) Construct the 2-3 tree T6 for H by inserting the records, in the reversed given order, into an initially empty 2-3 tree. When done, delete 1, 15, and then 36 from T6.
 - (10) Illustrate the data structure for the final 2-3 tree for T5 and T6.

Remark: You must show your 2-3 tree, including the content of each interior node clearly after each insert/delete operation.


Solution:

(a) 2-3 tree T5:




Remark: Whenever a 3-node becomes a 4-node, you must perform node splitting.


delete(1,T5):



delete(15,T5):




delete(36,T5):




Remark: To resolve ambiguity, you must check the left sibling before the right one. Also, an 1-node will always try to adopt from its immediate sibling before giving up its only child for adoption.


DS for final 2-3 tree T5:




(b) 2-3 tree **T6**:




delete(1,T6):




delete(15,T6):



delete(36,T6):



DS for final 2-3 tree T6:



10/16/18