

Answer Set Programming

(3) Handling of variables in ASP

Abdallah Saffidine

COMP4418

Overview of the Lecture

- Semantics of ASP programs
- Extensions of ASP programs
- **Handling of variables in ASP**
- ASP as modelling language

Programs with Variables

- Atomic propositions may now contain variables, e.g.,
 $p(X, Z) \leftarrow e(X, Y), p(Y, Z).$

Programs with Variables

- Atomic propositions may now contain variables, e.g.,
 $p(X, Z) \leftarrow e(X, Y), p(Y, Z).$
- Herbrand universe of a program P
 - ▶ U contains all constants from P
 - ▶ U contains all $f(t_1, \dots, t_k)$ if f is a k -ary function in P and U contains t_1, \dots, t_k

Programs with Variables

- Atomic propositions may now contain variables, e.g.,
 $p(X, Z) \leftarrow e(X, Y), p(Y, Z).$
- Herbrand universe of a program P
 - ▶ U contains all constants from P
 - ▶ U contains all $f(t_1, \dots, t_k)$ if f is a k -ary function in P and U contains t_1, \dots, t_k
- ASP **grounds** variables with Herbrand universe
 - ▶ Unlike Prolog: instantiation instead of unification
 - ▶ ⚠ the ground program may grow exponentially (or worse)
 - ▶ ⚠ function symbols make grounding Turing-complete
 - ▶ If P is finite and mentions only constants, grounding is finite

Programs with Variables

- $f(X) \leftarrow b(X), \text{ not } a(X).$
 $a(X) \leftarrow p(X).$
 $b(\text{sam}).$
 $b(\text{tweety}).$
 $p(\text{tweety}).$
- $f(\text{sam}) \leftarrow b(\text{sam}), \text{ not } a(\text{sam}).$
 $f(\text{tweety}) \leftarrow b(\text{tweety}), \text{ not } a(\text{tweety}).$
 $a(\text{sam}) \leftarrow p(\text{sam}).$
 $a(\text{tweety}) \leftarrow p(\text{tweety}).$
 $b(\text{sam}).$
 $b(\text{tweety}).$
 $p(\text{tweety}).$