

# Household Water Conservation by the Numbers

## Indoor Efficiency, Outdoor Irrigation, Leakage, Rainwater and Stormwater Management, and Local Water Reuse

Technical Brief — September 7, 2026 (Updated September 17, 2026)

**Qizhong (George) Guo, Ph.D., P.E., BC.WRE**  
Professor, Civil and Environmental Engineering  
Rutgers University–New Brunswick

---

### Context and Purpose

On August 26, 2026, *TIME* published the article “**We Asked Experts For the Easiest Ways to Shrink Your Home Water Usage,**” which included interviews with the author of this brief and two other university professors on practical approaches to household water conservation [1]. The article discussed indoor water-saving practices, household leaks, and outdoor landscape irrigation within the broader context of water scarcity and drought in the United States.

This technical brief is a follow-up to the *TIME* article. It expands the discussion by taking a more quantitative and systems-oriented look at residential water use—including indoor efficiency, household and water-distribution leakage, outdoor irrigation, rainwater and stormwater management, and opportunities for local nonpotable water reuse.

Household water conservation is often communicated through simple advice: fix leaks, take shorter showers, run full loads, or water lawns less frequently. These recommendations are useful, but the quantities involved can vary substantially with climate, season, household characteristics, technology, infrastructure condition, and even the definitions used by different studies. Wherever possible, current federal sources and the newly released 2026 *Residential End Uses of Water* study are used.

This brief focuses primarily on **direct residential water use**—the water supplied to and used in or around a home. The broader **water footprint**, which also includes indirect water use associated with the goods and services people consume, is noted separately in Section 12.

#### **TIME article:**

<https://time.com/article/2026/08/26/water-experts-s-habits-to-reduce-their-water-footprint/>

---

# Key Quantitative Benchmarks

| Quantity                                               | Approximate benchmark              | Important qualification                                                                                     |
|--------------------------------------------------------|------------------------------------|-------------------------------------------------------------------------------------------------------------|
| U.S. domestic water use                                | <b>82 gal/person/day</b>           | USGS 2015 benchmark still cited by EPA; includes indoor + outdoor residential uses                          |
| Current single-family indoor use                       | <b>38.5 gal/person/day</b>         | 2026 Water Research Foundation study                                                                        |
| Change in average single-family indoor use since 1999  | <b>-44.4%</b>                      | 69.3 → 38.5 gal/person/day                                                                                  |
| Outdoor household use                                  | <b>~30% nationally</b>             | Can reach ~70% in hot summer conditions or dry climates                                                     |
| Household leaks                                        | <b>~9,400 gal/family/year</b>      | EPA average potential waste; individual homes vary widely; includes household plumbing and irrigation leaks |
| U.S. household leakage                                 | nearly 900 billion gal/year        | Current EPA WaterSense national estimate                                                                    |
| Loss associated with aging distribution infrastructure | <b>~2.1 trillion gal/year</b>      | EPA cites an ASCE-derived estimate for treated drinking water lost through aging/leaky infrastructure       |
| U.S. drinking-water infrastructure need                | <b>\$625 billion/20 years</b>      | \$422.9 billion (~68%) is for distribution/transmission on EPA's current webpage                            |
| 1 inch of water over 1,000 ft <sup>2</sup>             | <b>623 gallons</b>                 | Basic volume conversion                                                                                     |
| 1 inch of rain on a 2,000-ft <sup>2</sup> roof         | <b>~1,247 gallons</b>              | Gross rainfall volume before collection losses                                                              |
| WaterSense faucet savings                              | <b>~700 gal/family/year</b>        | Replacing old inefficient faucets/aerators                                                                  |
| WaterSense showerhead savings                          | <b>~2,700 gal/family/year</b>      | Average EPA estimate                                                                                        |
| WaterSense toilet savings                              | <b>~13,000 gal/family/year</b>     | When replacing old inefficient toilets                                                                      |
| Smart irrigation controller                            | <b>up to ~15,000 gal/home/year</b> | Depends on controller technology and existing overwatering                                                  |

| Quantity                        | Approximate benchmark                       | Important qualification                                                      |
|---------------------------------|---------------------------------------------|------------------------------------------------------------------------------|
| Southern Nevada turf conversion | ~ <b>55.8 gal/ft<sup>2</sup>/year saved</b> | Highly climate-specific; should not be transferred directly to humid regions |

These values come from different datasets and **should not simply be added, subtracted, or transferred from one climate to another.**

---

## 1. How Much Water Does an American Household Use?

EPA continues to state that the average American uses about **82 gallons per person per day at home** [2,3]. The figure originates in the U.S. Geological Survey's national 2015 water-use assessment rather than a new 2026 measurement. Importantly, USGS defines domestic water use to include both indoor activities—drinking, bathing, toilets, laundry, and dishwashing—and outdoor activities such as lawn and garden irrigation, vehicle washing, and swimming pools.

The **82-gallon figure therefore includes both indoor and outdoor residential water use.**

A major new Water Research Foundation study published in June 2026 provides a much more current measure specifically of **indoor use**. *Residential End Uses of Water, Version 3* included 52 utility partners, billing data from more than 4 million households, single-family end-use data from almost 70,000 households, and multifamily end-use data from 1,000 households across the United States and Canada [4].

The study reports average single-family indoor consumption of only **38.5 gallons per capita per day (gpcd)**.

This compares with **69.3 gpcd in the 1999 study**, a reduction of:

$$(69.3 - 38.5) / 69.3 \times 100 \approx 44.4\%$$

or:

$$69.3 \text{ gpcd} \rightarrow 38.5 \text{ gpcd} = 44.4\% \text{ reduction.}$$

WRF attributes much of this decline to increasingly water-efficient fixtures and appliances. Clothes-washer use declined by 67.6%, approximately 10 gpcd, while average toilet flush volume fell to 1.84 gallons in the 2026 study.

The important point is that **82 and 38.5 gpcd are not directly comparable numbers**. The former is an older national estimate of total residential use, including outdoor use; the latter is a new estimate of indoor single-family use.

It would therefore be incorrect to infer current outdoor use simply as:

$$82 - 38.5 = 43.5 \text{ gpcd.}$$

The datasets, years, samples, and methodologies differ.

---

## 2. Indoor Water Efficiency Has Been a Substantial Success

The long-term decline in indoor household water use did not occur accidentally.

National fixture standards established under the Energy Policy Act of 1992 became effective in the 1990s. Federal standards limited new conventional showerheads to 2.5 gallons per minute, faucets to 2.2 gallons per minute, and toilets to 1.6 gallons per flush [5]. EPA subsequently launched **WaterSense in 2006**, encouraging another generation of products that exceed minimum federal efficiency requirements [6].

Current EPA estimates illustrate the scale of potential household savings.

Replacing old, inefficient toilets with WaterSense models can save an average family nearly **13,000 gallons per year**. WaterSense showerheads can save approximately **2,700 gallons per year**, while efficient bathroom faucets and aerators can save approximately **700 gallons per year** [7–9].

Dishwashers have improved as well. Current ENERGY STAR criteria limit a standard certified dishwasher to approximately **3.2 gallons per cycle** [10]. EPA and ENERGY STAR recommend running dishwashers with full loads and scraping dishes rather than extensively prerinsing them. Modern efficient dishwashers can generally use less water than washing an equivalent quantity of dishes by hand.

EPA estimates that running a dishwasher only when full, thereby eliminating about one load per week, can save the average family nearly **320 gallons of water annually** [2].

Clothes washers have also become substantially more efficient. ENERGY STAR states that certified clothes washers use about **30% less water** than regular washers [10].

Thus, conservation does not always require sacrificing service or convenience. A substantial portion of the improvement in indoor water efficiency has come from providing essentially the **same household services with less water**.

---

### 3. Does Indoor Water Use Change Much Between Winter and Summer?

Indoor water use is generally **much less seasonal than total household water use**, although it should not be assumed to be perfectly constant.

The original Residential End Uses study found no significant overall summer-to-winter change in indoor residential consumption. This observation has subsequently been used by water planners to estimate outdoor consumption from differences between winter and summer water use [11].

More recent U.S. measurements provide useful nuance. A study of homes in Logan and Providence, Utah, found summer-versus-winter differences in some indoor end uses at individual homes, but the differences were not generalizable across sites. By contrast, total household use increased dramatically during the irrigation season.

Other end-use research similarly indicates that some behaviors—particularly showering—may vary seasonally, while toilet flushing, faucets, dishwashing, and clothes washing are generally much less temperature-sensitive than outdoor irrigation.

For a temperate climate such as New Jersey, a reasonable first-order assumption is therefore:

**Summer indoor demand  $\approx$  winter indoor demand, with modest behavioral variability.**

For rigorous analysis, however, this assumption should be tested.

A **December–March baseline** may be cleaner than November–April because outdoor use can begin during April or continue into November. Sensitivity testing at perhaps  $\pm 5\%$  or  $\pm 10\%$  around the winter baseline can help determine whether conclusions depend materially on assumed seasonal indoor variation.

This distinction is particularly useful for estimating outdoor household demand:

**Estimated seasonal outdoor use  $\approx$  summer total household use – estimated indoor baseline**

provided the limitations of such an approximation are recognized.

---

## 4. Water Losses Occur in Homes, Service Lines, and Public Systems

Household leakage receives considerable attention because it is immediately actionable.

EPA estimates that the average family can waste about **180 gallons per week, or 9,400 gallons per year**, through household leaks. Nationwide, household leaks waste **nearly 900 billion gallons annually** [2]. The category is not strictly “indoor” leakage: WaterSense addresses leaks in household plumbing as well as irrigation systems [12].

The national average should not be interpreted as meaning that every well-maintained home quietly loses 9,400 gallons each year. EPA reports that **9% of homes have leaks that waste 50 gallons or more per day** [12]. Leakage is therefore unevenly distributed across homes, and small continuous leaks can accumulate to large annual volumes even when they are difficult to hear or see.

Common household leaks include worn toilet flappers, dripping faucets, defective valves, leaking plumbing connections, and irrigation-system leaks. EPA notes that many easily corrected leaks require only a few tools and inexpensive hardware, and fixing them can reduce household water bills by about 10% [12]. Household leak repair is therefore often a comparatively low-cost and immediately actionable conservation opportunity.

### Public-system losses and infrastructure renewal

At the public-system scale, water can also be lost before it reaches the customer through water-main breaks, leaking joints and valves, service connections, corrosion, storage losses, and other failures in the distribution system.

EPA notes that aging infrastructure—including leaky pipes and water mains—is associated with the loss of approximately **2.1 trillion gallons of treated drinking water annually** in the United States [13]. EPA cites this figure from ASCE-derived non-revenue-water estimates rather than as an independent EPA measurement. Deteriorating distribution systems can also contribute to main breaks, reduced pressure, service interruptions, and water-quality risks.

EPA's current 7th Drinking Water Infrastructure Needs Survey and Assessment webpage reports a national 20-year need of approximately **\$625 billion**, of which **\$422.9 billion—about 68%—is for distribution and transmission infrastructure** [14]. This \$422.9 billion figure is **not the cost of fixing leaks alone**; it covers broader rehabilitation and replacement needs that also address reliability, pressure, water quality, capacity, and resilience.

For scale, EPA's current household-leak estimate of nearly 900 billion gallons per year is about **43% of the 2.1-trillion-gallon public-infrastructure loss estimate**. The two figures are not

directly comparable and should not be added together: they come from different analyses and definitions, the household category includes some outdoor leakage, and utility water-loss accounting also includes service-connection losses up to the meter.

## **Service lines form an important transition zone**

**Public water main → service connection/service line → customer meter → household plumbing**

For drinking-water systems, the pipe connecting the public main to a building is generally called a service line or service connection. Meter location and ownership responsibility vary among utilities, so the physical and financial boundary between “utility” and “customer” leakage is not always the same as the property line.

Under the AWWA/IWA water-audit approach described by EPA, **real losses include leakage from service connections up to and including the customer meter** [15]. Leakage downstream of the meter is generally recorded as customer use even when the leaking pipe is buried outside the building; repair responsibility can also vary by utility.

This distinction has practical consequences for leak detection. A buried service-line leak upstream of the meter may not appear as increased household metered use, whereas a leak downstream of the meter generally will. Service-connection leaks can also be difficult to identify because underground water may not produce visible wet spots at the surface [15].

The repair challenge therefore forms a continuum. A worn toilet flapper or dripping faucet can often be corrected quickly and inexpensively; a customer service-line repair is more involved; and rehabilitation or replacement of public mains is the most capital-intensive. The less expensive household opportunities should be pursued aggressively, but they cannot substitute for renewal of aging public infrastructure.

This leads to an important engineering principle:

**Household leak repair, service-line management, and public-infrastructure renewal are complementary—not competing—water-conservation strategies.**

Household leak repair can often save water at relatively low cost. Service-line leak detection and repair occupy an intermediate scale. Public-system renewal requires much larger capital investment, but it also protects reliability, pressure, water quality, and system resilience while reducing the loss of water that has already been captured, treated, pumped, and conveyed.

---

## 5. Outdoor Water Use Is Where Residential Demand Becomes Highly Variable

EPA estimates that approximately **30% of household water use nationally occurs outdoors**, primarily for landscape irrigation [16].

Current EPA webpages place total U.S. residential outdoor use at roughly **8–9 billion gallons per day**, with some variation among EPA webpages and underlying datasets.

In hot summer months or dry climates, however, outdoor use can rise to **as much as about 70% of an individual household's total water consumption**.

That distinction is important:

**~30% = broad national average**

whereas

**up to ~70% = some hot/dry seasonal or geographic conditions.**

The dramatic summer increase seen on many household water bills is therefore primarily an **outdoor-use phenomenon**, rather than evidence that indoor demand doubles during the summer.

New Jersey provides a useful humid-climate contrast.

Rutgers NJAES notes that established lawns in New Jersey generally require supplemental watering to maintain vigorous growth primarily during **June, July, and August**, with occasional need during May or September. Rutgers also notes that lawns can survive relatively short New Jersey droughts without irrigation by entering dormancy [17].

This distinction matters because turf that is allowed to become temporarily dormant may appear brown but can recover when cooler or wetter conditions return. Keeping turf continuously lush and green therefore represents a landscape preference rather than always a plant-survival requirement.

---

## 6. Lawn Irrigation Involves Larger Volumes Than May Be Apparent

A useful hydrologic conversion is:

**1 inch of water  $\times$  1,000 ft<sup>2</sup> = approximately 623 gallons.**

This follows directly from volume conversion:

**1,000 ft<sup>2</sup>  $\times$  (1/12 ft)  $\times$  7.4805 gal/ft<sup>3</sup>  $\approx$  623 gallons.**

Thus, applying one inch of supplemental irrigation to a modest **1,000-ft<sup>2</sup> lawn once per week for 20 weeks** would represent approximately:

**623  $\times$  20  $\approx$  12,500 gallons**

if rainfall supplied none of the requirement.

This is **not** a recommendation or an estimate of actual annual lawn demand in New Jersey. Natural rainfall can provide much of the required water in a humid climate. The calculation simply illustrates the scale involved.

Rutgers guidance indicates that landscapes may require on the order of **one inch of water per week during periods of greatest summer need**, with irrigation intended to supplement natural rainfall rather than replace it [17].

Dry climates demonstrate the other extreme.

University of Nevada, Reno Extension reports that a typical lawn can consume approximately **10,000 gallons of water over a summer** in northern Nevada [18].

Southern Nevada has particularly extensive field data on turf conversion. The Southern Nevada Water Authority reports that water-smart landscaping uses approximately **55.8 gallons less water per square foot annually than turfgrass** under Southern Nevada conditions [19].

The underlying comparison measured approximately:

- **73.0 gal/ft<sup>2</sup>/year** for turfgrass, versus
- **17.2 gal/ft<sup>2</sup>/year** for xeric landscaping.

Thus, replacing **1,000 ft<sup>2</sup> of irrigated turf** under Southern Nevada conditions can represent water savings on the order of:

$55.8 \times 1,000 \approx 55,800$  gallons/year.

This number should **not be transferred directly to New Jersey or other humid climates.**

Its value is to demonstrate how profoundly climate changes the scale of outdoor residential water use.

---

## 7. Irrigation Timing and Controls Also Matter

Watering during the hottest, sunniest, and often windiest portion of the day increases evaporation, wind drift, and other application losses.

EPA therefore recommends avoiding midday irrigation and generally favors watering during cooler periods [16].

EPA estimates that when inefficient system design and operation, wind, evaporation, runoff, overspray, leaks, and overwatering are considered together, **as much as approximately 50% of outdoor irrigation water may be wasted.**

For New Jersey specifically, Rutgers NJAES states that the most efficient irrigation period is generally **late evening through early morning, approximately 10 p.m. to 8 a.m.**, when temperatures and wind speeds tend to be lower and relative humidity is higher, reducing evaporative losses [17].

For a simple household recommendation, **early morning is particularly attractive** because evaporation is relatively low, winds are often lighter, and foliage can subsequently dry during the day.

One subtle point is important:

**Changing irrigation from noon to nighttime does not automatically reduce the gallons measured by the water meter.**

If a sprinkler operates for exactly 30 minutes in either case, approximately the same nominal volume may be applied.

The conservation benefit occurs when lower evaporative and wind losses allow the required soil moisture to be achieved with **less total applied water.**

Other irrigation-efficiency measures can be equally or more important:

- Water only when plants actually need it.
- Account for recent rainfall.
- Adjust irrigation schedules seasonally.
- Repair leaking or broken sprinkler heads.
- Prevent overspray onto sidewalks and pavement.
- Use shorter “cycle-and-soak” applications where runoff occurs.
- Use drip or microirrigation where appropriate.
- Use weather- or soil-moisture-based controls.

Smart irrigation controllers can produce substantial savings. EPA estimates that replacing a standard clock-based controller with a WaterSense-labeled weather-based irrigation controller can save an average home **nearly 7,600 gallons of water annually**, while installing a WaterSense-labeled soil-moisture-based controller can save an average home with an automatic landscape irrigation system **more than 15,000 gallons annually** [20].

These are potential savings relative to less efficient irrigation practices, not guaranteed savings for every household. Actual savings depend on climate, landscape characteristics, irrigation demand, system condition, and existing watering practices.

---

## 8. Landscape Design Can Reduce Irrigation Demand While Maintaining Function and Ecological Value

Reducing outdoor water demand can involve reducing the area of intensively irrigated turf and replacing portions with native or climate-adapted vegetation.

Rutgers recommends native plants as part of sustainable residential landscapes and notes that unused lawn areas can be converted to native planting beds, rain gardens, or reforested areas [17].

Newly planted native vegetation still requires irrigation during establishment and sometimes during prolonged heat or drought.

Therefore:

**“Native” should not be confused with maintenance-free or water-free.**

Native and adapted landscapes may still require:

- initial establishment watering,
- weed and invasive-species control,

- periodic pruning or cutting,
- maintaining sight distances and walkways,
- controlling unwanted spread, and
- other forms of landscape stewardship.

A practical hierarchy is to retain turf where it serves an actual function—such as recreation, play, gathering, or erosion protection—and use lower-water landscape types where turf is primarily ornamental.

The potential water savings depend greatly on climate.

Southern Nevada's approximately 55.8-gal/ft<sup>2</sup>/year turf-conversion saving is dramatic because evapotranspiration demand is high and rainfall is very low.

In New Jersey, annual precipitation is much greater and more evenly distributed. The absolute potable-water savings from turf conversion will therefore ordinarily be much smaller.

Water-efficient landscaping should consequently be evaluated in its **local climatic, ecological, regulatory, and social context**, rather than treated as a universal one-size-fits-all prescription.

## 9. Rainfall Itself Is a Substantial Household-Scale Water Source

The same basic hydrology provides another useful number:

**1 inch of rain on 1,000 ft<sup>2</sup> of roof  $\approx$  623 gallons**

and therefore:

**1 inch of rain on 2,000 ft<sup>2</sup> of roof  $\approx$  1,247 gallons.**

These are gross rainfall volumes before accounting for gutter losses, first-flush diversion, leakage, storage limitations, roof geometry, and overflow.

For simple volume estimates, roof catchment area refers to the horizontal projected area draining to the gutters, not the larger sloping roof-surface area.

A conventional 55-gallon rain barrel provides a useful unit of comparison, but a household need not be limited to one barrel. A residence may have several downspouts serving different portions of the roof, allowing barrels to be installed at multiple locations or connected together for greater storage. Detached garages, sheds, and other roofed structures can provide additional collection areas where gutters and downspouts are available. The practical number and placement of barrels

depend on roof-drainage configuration, available space, irrigation demand, and the ability to empty storage between storms [17].

On a 1,000-ft<sup>2</sup> roof:

**55 gallons / 623 gallons per inch  $\approx$  0.088 inch**

Thus, only approximately **0.09 inch of rainfall** would theoretically generate enough roof runoff to fill a 55-gallon barrel.

A 1-inch storm generates more than **eleven times** that volume.

Multiple barrels can materially increase household-scale storage. Illustrative capacities for standard 55-gallon barrels are:

| Storage configuration     | Total storage | Equivalent runoff depth on<br>1,000-ft <sup>2</sup> roof | Equivalent runoff depth on<br>2,000-ft <sup>2</sup> roof |
|---------------------------|---------------|----------------------------------------------------------|----------------------------------------------------------|
| 2 $\times$ 55-gal barrels | 110 gal       | $\sim$ 0.18 in                                           | $\sim$ 0.09 in                                           |
| 4 $\times$ 55-gal barrels | 220 gal       | $\sim$ 0.35 in                                           | $\sim$ 0.18 in                                           |
| 6 $\times$ 55-gal barrels | 330 gal       | $\sim$ 0.53 in                                           | $\sim$ 0.26 in                                           |

These values are gross runoff equivalents before collection losses. If barrels are placed at separate downspouts, actual capture depends on the roof area draining to each location and runoff need not be divided evenly among downspouts. Even several barrels may capture only part of the runoff from a larger storm. Storage must also be used or emptied between events; a full barrel has no capacity for the next storm. Rutgers NJAES recommends connecting multiple barrels when greater storage is desired [17].

A **single rain barrel** is therefore useful, but it represents only a small storage element relative to the runoff generated by a residential roof during a substantial storm.

Larger cisterns can capture considerably more water.

EPA recognizes rainwater harvesting, downspout disconnection, and rain gardens as established green-infrastructure practices [21].

**Downspout disconnection** can route roof drainage toward:

- rain barrels,
- cisterns,
- lawns,
- landscaped areas,
- rain gardens, or
- other suitable permeable surfaces

instead of directing runoff immediately to pavement or storm drains.

**Rain gardens** provide temporary storage and support infiltration, plant uptake, evapotranspiration, and potentially water-quality improvement.

These practices are best viewed as complementary:

**Capture and reuse what is practical → safely route overflow → infiltrate or retain additional water where site conditions permit.**

Their objectives are not identical.

A rain barrel or cistern can directly substitute captured rainwater for potable irrigation water.

A rain garden's principal benefits are generally stormwater retention, infiltration, evapotranspiration, water-quality improvement, and runoff reduction. Potable-water savings are an additional rather than automatic benefit. However, Rutgers NJAES notes that replacing irrigated turf with a bioretention practice such as a rain garden can reduce irrigation needs once plants are established, thereby lowering potable-water use [17].

Downspouts should never simply be redirected without considering:

- building foundations,
- site grading,
- neighboring properties,
- soil infiltration capacity,
- utilities,
- erosion,
- easements, and
- local ordinances.

---

## 10. Could Basement Sump Water Also Become a Resource?

Foundation drainage introduces a less frequently discussed household water source.

Many homes collect shallow groundwater or infiltrated water around the foundation and pump it away through a sump system.

The U.S. Department of Energy explicitly identifies **foundation water, or “sump-pump water,” as an alternative water source** and lists irrigation, toilet flushing, cooling-tower makeup, and vehicle washing among possible nonpotable applications [22].

The U.S. General Services Administration similarly recognizes foundation/sump water as a potential alternative source, with appropriate treatment depending on water quality and intended use.

Foundation-drainage water, however, differs hydrologically from conventional roof runoff.

| Characteristic         | Roof runoff                                                              | Foundation/sump drainage                                                   |
|------------------------|--------------------------------------------------------------------------|----------------------------------------------------------------------------|
| Source                 | Rainfall intercepted by roof                                             | Groundwater/soil drainage reaching foundation                              |
| Response               | Immediate during rainfall                                                | May be delayed and prolonged                                               |
| Yield estimation       | Relatively straightforward from rainfall and roof area                   | Highly site-specific                                                       |
| Seasonal control       | Rainfall pattern                                                         | Rainfall + antecedent moisture + soils + groundwater                       |
| Water-quality concerns | Roof material, atmospheric deposition, debris, wildlife                  | Groundwater chemistry, iron/manganese, salts, possible local contamination |
| Storage need           | Often substantial because rainfall and irrigation demand do not coincide | Also potentially substantial; timing may differ                            |
| Research/practice base | Extensively documented                                                   | <b>Less extensively documented for residential beneficial reuse</b>        |

The timing difference may be particularly interesting.

Roof runoff reaches storage immediately during a storm—precisely when landscape irrigation demand is generally low.

Foundation drainage may continue **after rainfall** as infiltration raises shallow groundwater levels and water moves through soil toward the foundation.

Whether that delayed response improves the match between **water availability and subsequent irrigation demand** is an empirical question.

Compared with roof-rainwater harvesting, the federal sources reviewed here recognize foundation-water reuse, but residential-scale quantification appears much more limited with respect to:

- annual yield,
- seasonal reliability,
- source-water quality,
- storage sizing,
- irrigation-demand matching,
- potable-water offset,

- pumping energy, and
- economic feasibility.

This suggests a potentially useful research question:

**Under what hydrogeologic, climatic, and household conditions does residential foundation-drainage reuse provide meaningful value relative to—or in combination with—conventional roof-runoff harvesting?**

A rigorous study could measure sump-pump flow, rainfall, shallow groundwater conditions, and irrigation demand; evaluate water quality; simulate alternative storage capacities; and compare:

1. no reuse,
2. roof-runoff reuse only,
3. foundation-drainage reuse only, and
4. combined roof + foundation-drainage reuse.

The most useful result may not be choosing one source over the other.

A combined system could potentially operate as:

**Roof runoff + foundation drainage → shared storage → landscape irrigation → safe overflow to a rain garden or other appropriate discharge location.**

Such a concept should be evaluated carefully rather than assumed to be advantageous. In many homes, sump flow may be small or highly intermittent; in others, it may occur primarily during wet periods when irrigation is unnecessary. Water quality can also vary substantially from site to site.

Foundation-drainage reuse should therefore be viewed at present as a **promising research and site-specific design question**, rather than a universally established residential conservation practice.

---

## 11. The Value of Conserving a Gallon Depends on Where It Is Conserved

Water conservation also has an economic dimension.

For an **indoor gallon**, reducing consumption can often avoid:

1. the cost of potable water supply,
2. the cost of wastewater conveyance and treatment, and

3. where hot water is involved, the energy required for water heating.

Most indoor water eventually enters the sanitary sewer.

For **outdoor irrigation**, however, the relationship between water use and sewer cost varies by utility.

Some municipalities charge wastewater fees based directly on metered water consumption. Others estimate wastewater production from winter consumption, use separate irrigation meters, or apply seasonal adjustments.

In those systems, reducing outdoor irrigation may lower the **water bill** but may not reduce the **sewer bill**.

A simplified expression for household financial savings is therefore:

**Annual savings  $\approx$**   
**(avoided water volume  $\times$  applicable water rate)**  
**+ (avoided sewer volume  $\times$  applicable sewer rate)**  
**+ avoided water-heating energy cost, where applicable**

This explains why identical gallon savings can have very different economic values in different communities.

Three nearby New Jersey communities can have substantially different conservation incentives because one may use a flat residential sewer fee, another may charge sewer directly from metered water use, and another may use a winter-consumption basis.

Appendix A provides a detailed 2026 comparison for Piscataway, New Brunswick, and Montgomery. It compares water and sewer fee structures, modeled annual household costs at identical water use, and the direct bill savings associated with conservation. New Brunswick's separate stormwater utility fee is analyzed independently and is not included in the water-plus-sewer cost totals.

Water-rate structures may also include:

- fixed monthly service charges,
- increasing block rates,
- seasonal rates,
- minimum charges,
- separate irrigation rates, or
- affordability programs.

Therefore, the household economic value of conservation cannot be inferred from gallons alone.

Efficiency of hot-water fixtures can provide particularly strong combined benefits because it saves both water and energy. EPA notes, for example, that WaterSense showerheads reduce not only water consumption but also the energy needed to heat shower water.

### **Stormwater utilities add a third household cost signal**

Another emerging development is the stormwater utility—a dedicated funding mechanism for stormwater services and infrastructure. New Jersey's Clean Stormwater and Flood Reduction Act (P.L. 2019, c.42) authorized municipalities, counties, and certain authorities to establish stormwater utilities. Fees must be based on a fair and equitable approximation of runoff generated by a property, commonly using impervious area, and the law requires partial fee credits for qualifying onsite measures that reduce, retain, or treat stormwater, including approved green infrastructure [23]. Unlike potable-water charges, stormwater utility fees generally are not based on gallons of water delivered to the property.

New Brunswick became the first municipality in New Jersey to establish a stormwater utility in May 2024, about five years after the State's enabling legislation. Its ordinance defined one Equivalent Residential Unit (ERU) as 2,102 ft<sup>2</sup> of impervious area and set an annual fee of \$77 per ERU. The City subsequently adopted a Stormwater Management Fee Credit & Adjustment Policy Manual, and in 2026 initiated development of a Municipal Stormwater Utility Master Plan to guide stormwater infrastructure, regulatory compliance, and long-term resilience [23].

Two consecutive 2026 New Brunswick property bills examined for Appendix A provide a practical example of this separation: water and sewer were charged against the same meter reading and usage quantity in both quarters, corroborating the City's ordinance-based volumetric sewer structure, while stormwater appeared as a separate quarterly charge. For comparison across the three municipalities, stormwater is therefore reported separately rather than added to the water-plus-sewer totals.

### **Rain gardens can provide dual household cost benefits**

Rain gardens illustrate how water-conservation and stormwater economics can intersect. NJDEP identifies rain gardens as the most widely used green-infrastructure stormwater best management practice [21]. Rutgers NJAES notes that replacing turf with a bioretention system such as a rain garden reduces the need for irrigation once plants are established, which can lower potable-water use and the outdoor water bill [17].

Where a stormwater utility offers credits, a properly designed, approved, and maintained rain garden that reduces, retains, or treats runoff onsite may also qualify for a partial stormwater-fee credit [23]. The two savings mechanisms are distinct: one comes from using fewer metered gallons for irrigation; the other from managing stormwater runoff onsite. Newly installed rain-garden vegetation still requires establishment watering, and actual water savings and stormwater credits depend on site conditions, design, maintenance, and local program requirements.

---

## 12. From Individual Conservation to Water-System Resilience

The numerical picture suggests several levels of water conservation rather than a single solution.

### Inside the home

Efficient fixtures and appliances have already produced a major national decline in per-capita indoor demand.

Remaining opportunities include:

- avoiding unnecessary faucet use,
- running full appliance loads,
- using efficient fixtures and appliances, and
- finding and repairing leaks.

### Outside the home

The opportunity is more geographically variable but can be much larger.

Useful approaches include:

- irrigating according to actual plant need,
- accounting for recent rainfall,
- watering when evaporative and wind losses are relatively low,
- maintaining irrigation equipment,
- reducing unnecessary turf,
- using native or climate-adapted vegetation,
- improving irrigation controls, and
- allowing turf dormancy where appropriate.

### At the property scale

Roof water can be captured or infiltrated through:

- rain barrels,
- cisterns,
- downspout disconnection,
- landscaped infiltration areas, and
- rain gardens.

Foundation-drainage water may provide another local nonpotable source under suitable conditions, although its residential potential deserves considerably more quantitative evaluation.

## **At the community scale**

Household conservation alone cannot solve water loss.

Renewal of aging water infrastructure remains equally important. This includes not only public mains and distribution facilities but also attention to leaking service connections, whose accounting and repair responsibilities depend in part on meter location and utility ownership rules. EPA estimates that enormous quantities of treated drinking water are lost through deteriorating distribution systems, while more than \$400 billion in distribution/transmission investment will be needed over the coming two decades.

Stormwater utilities can complement these investments by providing dedicated funding for drainage-system operation and maintenance, capital improvements, regulatory compliance, flood reduction, and green infrastructure. Credit programs can also create property-scale incentives for onsite runoff reduction and green infrastructure [23].

## **A broader water-footprint perspective**

The water discussed in this brief is primarily direct household water use—the water delivered to and used in or around the home. A consumer’s broader water footprint also includes indirect water use associated with producing the goods and services that the consumer uses. The Water Footprint Assessment Manual defines a consumer’s water footprint as the combination of direct water use at home or in the garden and indirect water use associated with products and services such as food, clothing, paper, energy, and industrial goods [24].

Accordingly, the EPA/USGS benchmark of **82 gallons per person per day** is a measure of direct residential water use, **not a person’s total water footprint**. Reducing food waste and improving water efficiency throughout agricultural, energy, and industrial supply chains can complement conservation at the household tap, but a detailed water-footprint assessment is beyond the scope of this brief.

The broader engineering principle is therefore:

**Use potable water efficiently. Eliminate avoidable losses. Choose landscapes suited to local climate and need. Match water quality to the intended use. Retain and reuse local water where practical. And maintain the infrastructure that delivers the water in the first place.**

---

# References and Web Resources

## 1. TIME article

Shah, S. (2026). “We Asked Experts For the Easiest Ways to Shrink Your Home Water Usage.” *TIME*, August 26, 2026.

<https://time.com/article/2026/08/26/water-experts-s-habits-to-reduce-their-water-footprint/>

---

## 2. U.S. Environmental Protection Agency (EPA), WaterSense. “Statistics and Facts.”

Current EPA benchmark for household water use, household leakage, and household conservation statistics, including the estimate that eliminating about one dishwasher load per week can save the average family nearly 320 gallons annually.

<https://www.epa.gov/watersense/statistics-and-facts>

---

## 3. Dieter, C.A., Maupin, M.A., Caldwell, R.R., Harris, M.A., Ivahnenko, T.I., Lovelace, J.K., Barber, N.L., and Linsey, K.S. (2018). *Estimated Use of Water in the United States in 2015*. U.S. Geological Survey Circular 1441.

<https://pubs.usgs.gov/publication/cir1441>

USGS domestic water-use definitions:

<https://www.usgs.gov/mission-areas/water-resources/science/domestic-water-use>

---

## 4. The Water Research Foundation (2026). *Residential End Uses of Water, Version 3: A Single-Family and Multi-Family Study*, Project 5242.

Project 5242 includes 52 utility partners, billing data from more than 4 million households, single-family end-use data from almost 70,000 households, and multifamily end-use data from 1,000 households across the United States and Canada; it reports average single-family indoor water use of 38.5 gpcd and a 44.4% decline relative to the 1999 study.

Project page:

<https://www.waterrf.org/research/projects/residential-end-uses-water-version-3-single-family-and-multi-family-study>

2026 study findings:

<https://www.waterrf.org/news/water-research-foundation-releases-landmark-update-residential-end-use-study>

---

## **5. U.S. Department of Energy. “Best Management Practice #7: Faucets and Showerheads”; Energy Policy Act of 1992.**

Federal fixture-efficiency standards.

<https://www.energy.gov/cmei/femp/best-management-practice-7-faucets-and-showerheads>

Energy Policy Act of 1992:

<https://afdc.energy.gov/files/pdfs/2527.pdf>

---

## **6. EPA WaterSense. “Accomplishments and History.”**

WaterSense launched in 2006.

<https://www.epa.gov/watersense/accomplishments-and-history>

---

## **7. EPA WaterSense. “Residential Toilets.”**

WaterSense toilet efficiency and household savings estimates.

<https://www.epa.gov/watersense/residential-toilets>

---

## **8. EPA WaterSense. “Showerheads.”**

WaterSense showerhead efficiency and approximately 2,700-gallon/year household savings estimate.

<https://www.epa.gov/watersense/showerheads>

---

## **9. EPA WaterSense. “Bathroom Faucets.”**

Approximately 700-gallon/year average-family savings estimate.

<https://www.epa.gov/watersense/bathroom-faucets>

---

## **10. ENERGY STAR / EPA. “Dishwashers,” “Dishwashers Key Product Criteria,” and “Clothes Washers.”**

Current dishwasher efficiency criteria, guidance on full loads, and ENERGY STAR's current comparison showing certified clothes washers use about 30% less water than regular washers.

<https://www.energystar.gov/products/dishwashers>

[https://www.energystar.gov/products/dishwashers/key\\_product\\_criteria](https://www.energystar.gov/products/dishwashers/key_product_criteria)

[https://www.energystar.gov/products/clothes\\_washers](https://www.energystar.gov/products/clothes_washers)

---

## **11. Interstate Commission on the Potomac River Basin and related seasonal end-use research.**

Conventional use of winter consumption as an indoor baseline and evidence that indoor use is substantially less seasonal than outdoor irrigation.

ICPRB:

<https://www.potomacriver.org/wp-content/uploads/2014/12/ICPRB00-5.pdf>

ASCE study on residential end-use variability:

<https://ascelibrary.org/doi/10.1061/%28ASCE%29WR.1943-5452.0001633>

Additional seasonal end-use study:

<https://www.mdpi.com/2073-4441/7/1/202>

---

## **12. EPA WaterSense. “Fix a Leak Week,” “Getting Started,” and “Home Maintenance.”**

Current household-leak information, including the 9% of homes with leaks wasting 50 gallons or more per day, common low-cost repairs, meter checks, and illustrative leak rates.

<https://www.epa.gov/watersense/fix-leak-week>

<https://www.epa.gov/watersense/getting-started>

<https://www.epa.gov/watersense/home-maintenance>

## **13. EPA. “Drought Resilience and Water Conservation” and “Drinking Water Distribution System Tools and Resources.”**

Distribution-system leakage, aging infrastructure, and water-main issues.

<https://www.epa.gov/water-research/drought-resilience-and-water-conservation>

<https://www.epa.gov/dwreginfo/drinking-water-distribution-system-tools-and-resources>

---

## **14. EPA. *7th Drinking Water Infrastructure Needs Survey and Assessment*.**

EPA's current 7th DWINSA webpage reports an approximately \$625 billion national 20-year drinking-water infrastructure need, including \$422.9 billion (about 68%) for distribution and transmission.

<https://www.epa.gov/dwsrf/epas-7th-drinking-water-infrastructure-needs-survey-and-assessment>

---

## **15. U.S. Environmental Protection Agency. Control and Mitigation of Drinking Water Losses in Distribution Systems, EPA 816-R-10-019 (2010), and Water Audits and Water Loss Control for Public Water Systems.**

EPA guidance on real losses, including leakage from transmission and distribution mains, storage facilities, and service connections up to and including the customer meter; also discusses the treatment of leaks downstream of the meter.

<https://www.epa.gov/sites/default/files/2015-05/documents/epa816r10019.pdf>

<https://nepis.epa.gov/Exe/ZyPURL.cgi?Dockkey=P100MEUZ.TXT>

## **16. EPA WaterSense. Outdoor Water Use and Irrigation.**

National outdoor-use share, climatic variability, irrigation waste, and watering guidance.

Start Saving:

<https://www.epa.gov/watersense/start-saving>

How We Use Water:

<https://www.epa.gov/watersense/how-we-use-water>

When It's Hot:

<https://www.epa.gov/watersense/when-its-hot>

---

## **17. Rutgers New Jersey Agricultural Experiment Station (NJAES). Lawn Watering, Native Plants, Sustainable Landscaping, Green Infrastructure, and Rain Barrels.**

Best Management Practices for Watering Lawns:

<https://njaes.rutgers.edu/pubs/download.php?strPubID=FS555>

Your Lawn and Its Care:

<https://njaes.rutgers.edu/fs102/>

Additional Rutgers landscape-water guidance:

<https://njaes.rutgers.edu/pubs/download.php?strPubID=FS1005>

Native Plants and Sustainable Landscaping:

<https://njaes.rutgers.edu/fs1140/>

---

An Introduction to Green Infrastructure Practices (FS1197):

<https://njaes.rutgers.edu/fs1197/>

Rain Barrels Part II: Installation and Use (FS1118):

<https://njaes.rutgers.edu/fs1118/>

## **18. University of Nevada, Reno Extension. “Designing Landscapes for Northern Nevada's Arid Climate.”**

Dry-climate landscape and lawn-water-use information.

<https://extension.unr.edu/publication.aspx?PubID=3344>

---

## **19. Southern Nevada Water Authority (2026). *Water Resource Plan*.**

Water-smart landscaping savings of approximately 55.8 gal/ft<sup>2</sup>/year relative to turfgrass under Southern Nevada conditions.

<https://www.snwa.com/assets/pdf/water-resource-plan-2026.pdf>

---

## **20. EPA WaterSense. Weather-Based and Soil Moisture-Based Irrigation Controllers**

WaterSense-labeled irrigation controllers and EPA estimates of potential annual household water savings.

Weather-Based Irrigation Controllers:

<https://www.epa.gov/watersense/weather-based-irrigation-controllers>

Soil Moisture-Based Irrigation Controllers:

<https://www.epa.gov/watersense/soil-moisture-based-irrigation-controllers>

---

## **21. EPA and New Jersey Department of Environmental Protection (NJDEP). Green Infrastructure and Rainwater/Stormwater Management Resources.**

Types of Green Infrastructure:

<https://www.epa.gov/green-infrastructure/types-green-infrastructure>

Watering Tips:

<https://www.epa.gov/watersense/watering-tips>

National Stormwater Calculator:

<https://www.epa.gov/water-research/national-stormwater-calculator>

---

NJDEP Green Infrastructure:

<https://dep.nj.gov/dwq/green-infrastructure/>

## **22. U.S. Department of Energy and U.S. General Services Administration. Alternative Water Sources.**

Federal guidance recognizing foundation/sump water as a potential alternative nonpotable source.

DOE — Alternative Water Sources:

<https://www.energy.gov/cmei/femp/best-management-practice-14-alternative-water-sources>

GSA — Water Systems and Alternative Water Sources:

<https://www.gsa.gov/governmentwide-initiatives/federal-highperformance-buildings/highperformance-building-clearinghouse/water/water-systems>

## **23. New Jersey Legislature, NJDEP, New Jersey Future, and City of New Brunswick. Stormwater Utility Law, Guidance, Credits, and New Brunswick Stormwater Utility.**

New Jersey's Clean Stormwater and Flood Reduction Act (P.L. 2019, c.42) authorized stormwater utilities in 2019. NJDEP guidance describes required fee-credit programs for qualifying onsite stormwater measures. New Brunswick became the State's first municipality to establish a stormwater utility in 2024; Ordinance O-052404 defined one ERU as 2,102 ft<sup>2</sup> of impervious area, set an annual fee of \$77 per ERU, and specifies that calculated ERUs are rounded to the nearest 0.5 ERU, with no developed property billed less than 1.0 ERU. The City adopted a fee-credit policy in 2024 and initiated a Municipal Stormwater Utility Master Plan in 2026.

NJDEP Stormwater Utility Resources:

[https://dep.nj.gov/stormwater/swu\\_stormwaterutility/](https://dep.nj.gov/stormwater/swu_stormwaterutility/)

NJDEP Fees, Credits, and Exemptions:

[https://dep.nj.gov/stormwater/swu\\_stormwaterutility/fees-credits-and-exemptions/](https://dep.nj.gov/stormwater/swu_stormwaterutility/fees-credits-and-exemptions/)

New Brunswick Ordinance O-052404:

<https://cms3.revize.com/revize/brunswicknj/O-052404.pdf>

New Brunswick Municipal Stormwater Utility Master Plan (2026):

<https://www.cit-e.net/newbrunswick-nj/cn/PublicNotices/archnews.cfm?DID=2702&jump2=86&theyear=2026&tpid=19236>

Clean Stormwater and Flood Reduction Act (P.L. 2019, c.42):

[https://pub.njleg.gov/bills/2018/AL19/42\\_.HTM](https://pub.njleg.gov/bills/2018/AL19/42_.HTM)

New Jersey Future — New Brunswick as New Jersey's first stormwater utility:

<https://www.njfuture.org/news/new-brunswick-is-njs-first-town-to-set-up-a-stormwater-utility/>

New Brunswick Stormwater Management Fee Credit & Adjustment Policy Manual (2024):

[https://cms3.revize.com/revize/brunswicknj/New%20Brunswick%20Credit%20Manual%202024\\_1112.pdf](https://cms3.revize.com/revize/brunswicknj/New%20Brunswick%20Credit%20Manual%202024_1112.pdf)

**24. Hoekstra, A.Y., Chapagain, A.K., Aldaya, M.M., and Mekonnen, M.M. (2011). The Water Footprint Assessment Manual: Setting the Global Standard. Earthscan, London.**

Defines the water footprint of a consumer as the combination of direct household/garden water use and indirect water use associated with producing the goods and services consumed.

[https://www.waterfootprint.org/resources/TheWaterFootprintAssessmentManual\\_English.pdf](https://www.waterfootprint.org/resources/TheWaterFootprintAssessmentManual_English.pdf)

# Appendix A. Household Water and Sewer Costs and Conservation Savings

## Illustrative Comparison for Piscataway, New Brunswick, and Montgomery, New Jersey

2026 Rates — Updated September 17, 2026

**Purpose.** This appendix illustrates how local water and sewer rate structures affect the household financial value of water conservation. For direct comparison, costs are modeled for the same four-person household and the same annual metered water use in Piscataway, New Brunswick, and Montgomery. For all three municipalities, the applicable sewer billing structures are established by municipal ordinances or codes and the 2026 charges and calculations used in this comparison were checked against actual residential utility bills. Piscataway and Montgomery use the New Jersey American Water (NJAW) water-rate structure, while New Brunswick bills water directly through the City. Stormwater charges are intentionally excluded from the water-plus-sewer cost totals because New Brunswick bills a distinct stormwater utility fee, whereas Piscataway and Montgomery do not have a comparable separately billed household stormwater fee in this comparison. Stormwater funding is discussed separately in Section A.6.

### A.1 Service Providers and Billing Structure

The three municipalities illustrate three distinctly different wastewater-billing structures: a flat residential sewer charge in Piscataway, a volumetric sewer charge based on metered water use in New Brunswick, and a base-plus-volumetric winter-basis formula in Montgomery. They also differ in how stormwater management appears on the household bill.

| Service                          | Piscataway                                                                                                                          | New Brunswick                                                                                                                                                         | Montgomery                                                                                                                                                                                      |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Water                            | NJAW — fixed monthly charges plus volumetric usage charges and surcharges                                                           | City water bill — metered volumetric charge; 1 Usage unit = 100 ft <sup>3</sup> (1 CCF); observed 2026 bills give \$7.582 per unit including the applicable surcharge | NJAW — same modeled tariff structure as Piscataway                                                                                                                                              |
| Sewer                            | \$360/year for a single-family residence; code-confirmed flat charge independent of water use                                       | Ordinance-confirmed volumetric charge based on metered water use; 2026 bills give \$8.809 per 100 ft <sup>3</sup> (1 CCF) including the applicable surcharge          | \$288 base fee plus \$15.96/1,000 gal of billable use; ordinance-confirmed lesser of annual or winter formula                                                                                   |
| Outdoor-use effect on sewer bill | None; residential sewer charge is flat                                                                                              | Yes. Sewer charges are based on metered water use; no seasonal or winter-use adjustment applies.                                                                      | No for summer outdoor use when the winter formula controls; water from meters dedicated exclusively to irrigation or other outdoor uses that do not discharge to sewer is excluded by ordinance |
| Stormwater                       | No separate stormwater utility line item in this comparison; supported through general municipal revenues, including property taxes | \$77/ERU/year; 1 ERU = 2,102 ft <sup>2</sup> of impervious area                                                                                                       | No separate stormwater utility line item in this comparison; supported through general municipal revenues, including property taxes                                                             |

## A.2 Current Water-Rate Components

Piscataway and Montgomery. For the modeled 5/8-inch-meter household, the current NJAW bill separates fixed monthly charges from consumption-related charges. The fixed subtotal is \$28.23/month, or \$338.76/year, and the current marginal volumetric subtotal is \$10.0251 per 1,000 gallons (approximately \$10.03/1,000 gal).

| Component                                     | Current rate                            | Cost behavior                              |
|-----------------------------------------------|-----------------------------------------|--------------------------------------------|
| Water Service Charge                          | \$22.65/month                           | Fixed                                      |
| Distribution System Improvement Charge (DSIC) | \$3.89/month                            | Fixed                                      |
| RESIC — Water                                 | \$1.69/month                            | Fixed                                      |
| Fixed subtotal                                | \$28.23/month = \$338.76/year           | Does not decline with conservation         |
| Base Water Usage Charge                       | \$8.8724/1,000 gal                      | Volumetric                                 |
| Purchased Water Adjustment Clause (PWAC)      | \$0.5330/1,000 gal                      | Volumetric                                 |
| Lead Service Line Replacement Charge (LSLRC)  | \$0.5561/1,000 gal                      | Volumetric                                 |
| Special Program Charge (SPC)                  | \$0.0636/1,000 gal                      | Volumetric                                 |
| Marginal water subtotal                       | \$10.0251/1,000 gal ≈ \$10.03/1,000 gal | Amount avoided when 1,000 gal is conserved |

Check against actual residential bills. For the NJAW water-rate cases used for Piscataway and Montgomery, the 2026 rate components and calculations were checked against actual residential utility bills. For example, at 5,000 gallons of use, the consumption-related charges are  $5 \times \$10.0251 = \$50.13$ . Adding the \$28.23 fixed charges gives \$78.36, matching the water-service-related total on the August 2026 residential bill used in the comparison. The separate optional protection-program charge is excluded.

**New Brunswick.** Two consecutive 2026 quarterly residential bills for the same property provide a direct check of the City's metered-use convention and current effective unit charges. The prior quarter shows Usage = 23, water = \$174.38, and sewer = \$202.60; the current quarter shows Usage = 26, water = \$197.13, and sewer = \$229.03. City Ordinance O-122203 specifies residential water and sewer billing on a per-1,000-cubic-foot basis and a 2% surcharge for accounts using less than 12,031.25 ft<sup>3</sup> per quarter. The 2026 bills therefore identify the portal's displayed Usage unit as 100 ft<sup>3</sup> (1 CCF = 748.05 gallons): Usage = 23 corresponds to 2,300 ft<sup>3</sup> and Usage = 26 to 2,600 ft<sup>3</sup>. The two quarters independently reproduce the same water rate. Using the 2% surcharge,  $\$174.38 \div (2.3 \times 1.02) = \$74.33$  per 1,000 ft<sup>3</sup> and  $\$197.13 \div (2.6 \times 1.02) = \$74.33$  per 1,000 ft<sup>3</sup>. The effective billed water rate is therefore \$75.8166 per 1,000 ft<sup>3</sup>, or approximately \$10.14 per 1,000 gallons. No separate recurring fixed water service charge is shown in these bills; the City rate schedule does include a minimum quarterly water charge at very low use.

| Community     | Annual fixed water charge used in model                                                                                         | Volumetric water rate used in model             |
|---------------|---------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| Piscataway    | \$338.76<br>No separate recurring fixed service charge in sampled bills; minimum quarterly water charge applies at very low use | \$10.0251/1,000 gal ≈ \$10.03/1,000 gal         |
| New Brunswick |                                                                                                                                 | \$7.582/100 ft <sup>3</sup> ≈ \$10.14/1,000 gal |
| Montgomery    | \$338.76                                                                                                                        | \$10.0251/1,000 gal ≈ \$10.03/1,000 gal         |

## A.3 Sewer Rates and Conservation Response

**Piscataway.** The municipal code specifies a \$360 annual sewer service charge for a single-family residence. Because the charge is flat, reducing either indoor or outdoor water use does not reduce the sewer bill.

**New Brunswick.** City Ordinance O-122203, Title 13, Chapter 13.08, Section 13.08.340, Schedule A establishes residential/commercial sewer charges on a quarterly per-1,000-ft<sup>3</sup> basis, with no seasonal or winter-use adjustment. The two consecutive 2026 residential bills use the same metered Usage quantity for water and sewer and confirm continued application of this volumetric structure. The sewer calculations are identical across the two quarters:  $\$202.60 \div (2.3 \times 1.02) = \$86.36$  per 1,000 ft<sup>3</sup> and  $\$229.03 \div (2.6 \times 1.02) = \$86.36$  per 1,000 ft<sup>3</sup>. Including the 2% surcharge, the effective billed sewer rate is \$88.0872 per 1,000 ft<sup>3</sup>, or approximately \$11.78 per 1,000 gallons. Accordingly, reductions in either indoor or outdoor metered water use reduce the sewer charge.

**Montgomery.** Township Code Chapter 12, § 12-10.2, as amended May 14, 2026 by Ordinance No. 26-1775, establishes an annual sewer service charge of \$288 per unit plus \$11.94 per CCF (\$15.96 per 1,000 gallons) of billable use. Billable use is the lesser of prior-year total metered water use or twice the sum of January, February, March, April, November, and December metered water use. When the winter formula controls, summer outdoor irrigation through the household meter is effectively excluded from the sewer bill. Section 12-10.3 further excludes readings from water meters dedicated exclusively to irrigation systems and other outdoor uses that do not discharge to the sewer system. Indoor conservation that persists through the winter period can reduce both the water bill and the sewer bill.

**Important qualification.** For all three municipalities, the sewer billing structures are established by the applicable municipal ordinances or codes, and the charges and calculations used in this comparison were checked against actual residential utility bills. For Montgomery, the Township bills from actual prior-year meter readings; in the illustrative calculations below, annual indoor use is used as a proxy for the annualized winter-basis volume. This is a simplifying modeling assumption for the common household comparison, not the Township's billing method for an individual account. For New Brunswick, the two consecutive 2026 bills are also used to identify the displayed 100-ft<sup>3</sup> Usage unit and derive the effective 2026 water and sewer unit charges. The modeled household totals below are illustrative and are not intended to reconstruct every possible account circumstance.

## A.4 Illustrative Four-Person Household

The 2026 Water Research Foundation single-family indoor benchmark of 38.5 gallons per person per day (gpcd) is used as the indoor baseline [4]. For four persons:

$$38.5 \text{ gpcd} \times 4 \text{ persons} \times 365 \text{ days} = 56,210 \text{ gallons/year of indoor use.}$$

Outdoor demand is more climate- and season-sensitive than indoor use, so three outdoor shares are used as sensitivity cases rather than as forecasts for a specific household.

| Outdoor share                           | Indoor use (gallon) | Outdoor use (gallon) | Total use (gallon/year) | Total use (gallons per capita per day) |
|-----------------------------------------|---------------------|----------------------|-------------------------|----------------------------------------|
| 30% — national-average sensitivity case | 56,210              | 24,090               | 80,300                  | ~55                                    |
| 20% — illustrative moderate outdoor use | 56,210              | 14,053               | 70,263                  | ~48                                    |
| 10% — illustrative low outdoor use      | 56,210              | 6,246                | 62,456                  | ~43                                    |

Water-cost equations used in the comparison:

Piscataway and Montgomery: Annual water cost  $\approx \$338.76 + (\$10.0251/1,000 \text{ gal} \times \text{annual metered use})$ .

New Brunswick: Annual water cost  $\approx \$10.1357/1,000 \text{ gal} \times \text{annual metered use}$ .

Modeled sewer costs: Piscataway remains \$360/year. Montgomery uses 56,210 gallons/year as the proxy winter-basis volume, giving  $\$288 + 56.21 \times \$15.96 \approx \$1,185/\text{year}$ . New Brunswick sewer cost is calculated at approximately  $\$11.776/1,000$  gallons of total metered water use.

Direct annual comparison for the 30% outdoor-use case. Stormwater is excluded from these totals.

| Municipality  | Annual water bill | Annual sewer bill | Water + sewer total |
|---------------|-------------------|-------------------|---------------------|
| Piscataway    | \$1,144           | \$360             | \$1,504             |
| New Brunswick | \$814             | \$946             | \$1,760             |
| Montgomery    | \$1,144           | \$1,185           | \$2,329             |

Sensitivity of combined annual water-plus-sewer cost to outdoor-use share:

| Outdoor-use sensitivity case | Piscataway | New Brunswick | Montgomery |
|------------------------------|------------|---------------|------------|
| 30% — 80,300 gal/year        | \$1,504    | \$1,760       | \$2,329    |
| 20% — 70,263 gal/year        | \$1,403    | \$1,540       | \$2,228    |
| 10% — 62,456 gal/year        | \$1,325    | \$1,369       | \$2,150    |

These totals are illustrative rather than predictions of what a particular household will pay. Actual bills depend on measured use, meter size, the rate components in effect during the billing period, and—especially in Montgomery—the prior-year monthly usage pattern used in the sewer formula. The New Brunswick calculation applies the bill-derived unit charges to the same modeled household use so that the three municipalities can be compared on a common basis.

## A.5 Financial Value of Conservation

The same physical water saving has different direct bill value because the marginal water and sewer charges differ. For all three municipalities, sewer billing structures are ordinance/code-confirmed and the rates and calculations used here were checked against actual residential bills. For Piscataway and Montgomery, fixed NJAW water charges remain unchanged with conservation; New Brunswick applies volumetric water and sewer charges to metered use.

| Conservation case                                                  | Water saving per 1,000 gal | Sewer saving per 1,000 gal | Combined saving per 1,000 gal |
|--------------------------------------------------------------------|----------------------------|----------------------------|-------------------------------|
| Piscataway — indoor or outdoor                                     | \$10.03                    | \$0                        | \$10.03                       |
| New Brunswick — indoor or outdoor conservation                     | \$10.14                    | \$11.78                    | \$21.91                       |
| Montgomery — indoor reduction that lowers winter basis             | \$10.03                    | \$15.96                    | \$25.99                       |
| Montgomery — summer outdoor reduction when winter formula controls | \$10.03                    | \$0                        | \$10.03                       |

| Conservation case                              | 5,000-gal reduction | 10,000-gal reduction | 20,000-gal reduction |
|------------------------------------------------|---------------------|----------------------|----------------------|
| Piscataway — indoor or outdoor                 | \$50                | \$100                | \$201                |
| New Brunswick — indoor or outdoor conservation | \$110               | \$219                | \$438                |
| Montgomery — qualifying indoor                 | \$130               | \$260                | \$520                |
| Montgomery — summer outdoor                    | \$50                | \$100                | \$201                |

For perspective, 10,000 gallons is roughly comparable to EPA’s average-family estimate of about 9,400 gallons per year lost through household leaks (see main Reference [2]), although leakage varies widely among homes. A 10,000-gallon reduction therefore has an estimated direct water-and-sewer value of about \$100 in Piscataway, about \$219 in New Brunswick at the 2026 bill-derived rates, and about \$260 in

Montgomery when the reduction is indoor and lowers the winter-basis sewer volume. For summer outdoor conservation in Montgomery, the modeled value returns to about \$100 because the sewer basis is unchanged.

## A.6 Stormwater Utility Fee as a Separate Emerging Cost Signal

Stormwater is kept separate from the water-plus-sewer totals above because the three municipalities do not place stormwater management costs on household bills in the same way. New Brunswick has a dedicated stormwater utility fee, while Piscataway and Montgomery do not have a comparable separately billed stormwater utility charge in this comparison; their stormwater-management costs are supported through general municipal revenues, including property taxes, and the household-specific allocation is not separately identifiable.

| Municipality  | Separate stormwater utility line item? | Basis used in this brief                                                                | Illustrative household charge                                            |
|---------------|----------------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| Piscataway    | No                                     | General municipal/property-tax-supported services; allocation not separately identified | Not separately quantified                                                |
| New Brunswick | Yes                                    | \$77/ERU/year; 1 ERU = 2,102 ft <sup>2</sup> impervious area                            | Sample property:<br>\$28.88/quarter =<br>\$115.50/year = 1.5 billed ERUs |
| Montgomery    | No                                     | General municipal/property-tax-supported services; allocation not separately identified | Not separately quantified                                                |

The New Brunswick bill shows a quarterly stormwater charge of \$28.88. At \$77 per ERU per year, this corresponds to 1.5 billed ERUs:  $1.5 \times \$77 = \$115.50/\text{year}$ , or  $\$28.875/\text{quarter}$ , which rounds to \$28.88. City Ordinance O-052404 specifies that the User Fee is calculated from impervious surface area divided by the 2,102-ft<sup>2</sup> ERU, with the resulting ERUs rounded to the nearest 0.5 ERU and no developed property billed less than 1.0 ERU.

The policy implication differs from water and sewer conservation. A stormwater utility fee generally does not decline simply because a household uses fewer gallons of potable water. Instead, credits or adjustments can create incentives for qualifying onsite practices that reduce, retain, or treat runoff—such as approved green infrastructure. Thus, water conservation and stormwater management can produce separate economic signals: lower metered water/sewer use on one hand, and potential stormwater-fee credits for runoff management on the other.

## A.7 Key Findings

1. The same household water use can produce substantially different annual water and sewer bills. In the 30% outdoor-use case (80,300 gal/year), modeled water-plus-sewer totals are about \$1,504 in Piscataway, \$1,760 in New Brunswick, and \$2,329 in Montgomery.
2. New Brunswick has the lowest modeled annual water bill of the three in the 30% case—about \$814 versus \$1,144 in Piscataway and Montgomery—even though its bill-derived volumetric water rate is slightly higher. The reason is that the NJAW cases include about \$339/year in fixed water charges.
3. Piscataway’s flat \$360 residential sewer fee does not respond to conservation. Indoor and outdoor conservation therefore have approximately the same direct utility-bill value there, aside from possible energy savings associated with hot water.
4. New Brunswick’s sewer billing structure is confirmed by City Ordinance O-122203: residential/commercial sewer charges are volumetric and based on metered water use, with no seasonal or

winter-use adjustment. Therefore, both indoor and outdoor conservation reduce the sewer bill. At the 2026 bill-derived rates, conservation has a combined marginal value of about \$21.91 per 1,000 gallons—approximately \$10.14 in water charges plus \$11.78 in sewer charges.

5. Montgomery provides the largest modeled direct bill benefit for qualifying indoor conservation. If the reduction lowers the winter-basis volume, 10,000 gallons of indoor conservation saves about \$160 in sewer charges in addition to about \$100 in water charges, for approximately \$260 total.

6. Summer outdoor conservation in Montgomery generally lowers only the water bill when the winter formula controls. In that case, its direct bill value is about \$10.03 per 1,000 gallons—approximately the same as Piscataway.

7. Stormwater should not be mixed into the direct three-community water-plus-sewer cost comparison. New Brunswick separately charges \$77/ERU/year based on impervious area; Piscataway and Montgomery do not have comparable separately billed stormwater utility fees in this comparison. Stormwater management is therefore analyzed as a distinct cost and incentive mechanism.

8. Fixed charges set a floor on the bill. The modeled NJAW fixed water charges total \$338.76/year, Montgomery also has a \$288 sewer base fee, and Piscataway has a \$360 flat sewer charge. These amounts are not reduced by household conservation.

## A.8 Notes and Sources

All annual-cost tables and conservation examples are rounded to the nearest dollar. For all three municipalities, sewer billing structures are established by municipal ordinances or codes, and the 2026 charges and calculations were checked against actual residential utility bills; identifying information is omitted. Rates can change, so future applications should use the rates and fee structures then in effect. Optional service-line protection insurance and household water-heating energy savings are excluded.

1. New Jersey American Water. Water and Wastewater Rates; New Jersey tariff effective July 2026. Current residential tariff and applicable PWAC, DSIC, LSLRC, SPC, and RESIC charges. <https://www.amwater.com/njaw/customer-service-billing/your-water-and-wastewater-rates/>

2. Township of Montgomery, New Jersey. Municipal Code, Chapter 12, §12-10.2, Sewer Service Charge Rate, as amended May 14, 2026 by Ordinance No. 26-1775; and §12-10.3, Meter Readings. Section 12-10.2 establishes the 2026 sewer charge of \$288/unit plus \$11.94/CCF (\$15.96/1,000 gal), applied to the lesser of prior-year annual metered use or twice January–April plus November–December use. Section 12-10.3 separately excludes readings from meters dedicated exclusively to irrigation and other outdoor uses that do not discharge to the sewer system. <https://ecode360.com/34969519>

3. Township of Piscataway, New Jersey. Municipal Code, Chapter 23, § 23-2.3, Service Charges. Single-family residential sewer charge: \$360/year. <https://ecode360.com/34889038>

4. City of New Brunswick. Ordinance O-122203, Title 13, Chapter 13.08, § 13.08.340, Schedule A—Schedule of Charges. Effective January 16, 2023. Establishes volumetric sewer billing per 1,000 ft<sup>3</sup> with no seasonal/winter adjustment and water billing per 1,000 ft<sup>3</sup>. Two 2026 residential bills (Usage 23 and 26) verify 1 Usage unit = 100 ft<sup>3</sup> (1 CCF) and effective billed rates of about \$10.14/1,000 gal for water and \$11.78/1,000 gal for sewer. Ordinance: <https://cms3.revize.com/revize/brunswicknj/CM%20Packet%2022.12.21.pdf> ; USGS conversion: <https://pubs.usgs.gov/wri/wri034154/htdocs/conversions.html>

5. City of New Brunswick / NJDEP stormwater utility materials. Ordinance O-052404 sets \$77/ERU/year, defines 1 ERU as 2,102 ft<sup>2</sup> of impervious area, and rounds calculated ERUs to the nearest 0.5 ERU with a 1.0-ERU minimum for developed property. See main Reference [23].