

Basic Info.

Model NO.	WHYC30P	Cine Loop	>400 Frame
Power Supply	AC110V-240V/50-60Hz	LCD Monitor	9.7 Inch
Display Mode	B, B+B, B+M, B+M/M, M, 4b	Used for	Human or Veterinary
Transport Package	Carton	Specification	ISO, CE
Trademark	Poweam	Origin	China
HS Code	90181210	Production Capacity	500PCS/Month

Product Description

Below is tech spec
Veterinary Ultrasound scanner WHYC30P parameter
High resolution LCD display,Full digital with latest ultrasonic imaging techniques
Portable design, easy for carrying
Applicable for abdomen, GYN, OB, cardiac, urology and small parts
Back-light, silicon-gel alphabetic keyboard

Probe		C1-7/60R/3.5MHz convex array	L1-3/7.5MHz HF linear	C1-8/20R/5.0MHz micro convex	EC1-2/13R/6.5MHz endo-vaginal
Display depth (mm)		250 (max)			
Maximal detect depth (mm)		≥160	≥50	≥80	≥40
Resolution (mm)	Lateral	≤3 (depth≤80) ≤4 (80<depth≤130)	≤2 (depth≤40)	≤2 (depth≤40)	≤2 (depth≤40)

Product Description		Company Info.			
		≤3 (80<depth≤130)	(depth≤50)	(depth≤40)	(depth≤30)
Blind zone(mm)		≤5	≤3	≤5	≤4
Geometric position precision	Horizontal	≤15	≤10	≤20	≤10
	Vertical	≤10	≤5	≤10	≤5
Monitor size		9.7 Inch			
Display mode		B, B+B, B+M, B+M/M, M, 4B			
Image gray scale		256 Scale			
Cine loop		≥400 Frame			
Image storage		64 Frame			
Focus		Focus Number, Focus position, Focal space			
Scan depth		40mm-250mm			
Image flip		Up/down, left/right, black/ white			
Image Process		GAMA, Image Smoothen, THI, Histogram, Zoom			
Scan angle		Adjustable			
Measure		Distance, circumference, area, volume, heart, GA, FW, EDD			
Character display		Date, clock, name, PID, age, Sex, hospital name, doctor,			
Notation		full- screen character editor, posture mark, Position indication			
Output report		4 types			
USB port		USB2.0			
power consumption (MAX)		90VA			
Net weight		6.4kg			
Size		289.16mm×304.96mm×222.02mm			