

Conversation URL:

<https://chatgpt.com/c/67bbbf97-fe8c-8011-abbd-b9adfebaa957>

Title:

Prompt:

```
# Re-plot with A and B on the X-axis and C on the Y-axis
```

```
# Extract A, B, and C values
```

```
a_values = [triplet[0] for triplet in explicit_triangles]  
b_values = [triplet[1] for triplet in explicit_triangles]  
c_values = [triplet[2] for triplet in explicit_triangles]
```

```
# Plot A and B as X-axis coordinates, C as Y-axis
```

```
plt.figure(figsize=(10, 6))  
plt.scatter(a_values, c_values, marker='o', color='blue', label="A values")  
plt.scatter(b_values, c_values, marker='s', color='red', label="B values")
```

```
# Connect points with lines
```

```
for i in range(len(a_values)):  
    plt.plot([a_values[i], b_values[i]], [c_values[i], c_values[i]], linestyle='-', color='gray', alpha=0.6)
```

```
# Formatting the plot
```

```
plt.title("π Triangle Representation: A & B on X, C on Y")
```

```
plt.xlabel("X-Axis (A and B Values)")
```

```
plt.ylabel("Y-Axis (C Value - Triangle Height)")
```


```
plt.axhline(0, color='black', linewidth=0.5)
```


```
plt.grid(True)
```

```
plt.legend()
```


```
plt.show()
```

Recursive Remainder Gaps in π Expansion







Recursive Harmonic Compression Formula: Balancing Remainder Oscillations




Alignment of Twin Primes and Zeta Zeros with Recursive Compression Function



Harmonic Spectrum of the First 1000 Digits of π





Conversation URL:

<https://chatgpt.com/c/67c1a60d-a910-8011-81fb-bb809464311a>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Function to generate remainder gap sequences recursively
def generate_remainder_gaps(n_terms):
    sequence = [3, 1] # Start with 3 and 1 as π begins with 3.141...
    gaps = []

    for _ in range(n_terms - 2):
        next_value = abs(sequence[-1] - sequence[-2]) # Measure the recursive remainder gap
        sequence.append(next_value)
        gaps.append(next_value)

    return sequence, gaps

# Generate recursive remainder gaps for first 100 terms
n_terms = 100
sequence, gaps = generate_remainder_gaps(n_terms)

# Plot the remainder gaps to look for oscillatory patterns
plt.figure(figsize=(12, 6))
plt.plot(gaps, marker='o', linestyle='-', color='b', label="Remainder Gaps")
plt.axhline(y=np.mean(gaps), color='r', linestyle='--', label="Mean Gap Value")
plt.xlabel("Iteration Step")
plt.ylabel("Remainder Gap Value")
plt.title("Recursive Remainder Gaps in π Expansion")
plt.legend()
plt.grid(True)
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c1a60d-a910-8011-81fb-bb809464311a>

Title:

Prompt:

```
from mpmath import zetazero
```

```
# Generate first 30 nontrivial Riemann Zeta Zeros
```

```
num_zeros = 30
```

```
zeta_zeros_real = [zetazero(n).imag for n in range(1, num_zeros + 1)]
```

```
# Compute FFT analysis of zeta zeros to detect harmonic alignments
```

```
zeta_fft = np.fft.fft(zeta_zeros_real)
```

```
# Plot Riemann Zeta Zeros
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(zeta_zeros_real, marker='o', linestyle='-', color='b', label="Zeta Zeros (Imaginary Part)")
```

```
plt.xlabel("Index")
```

```
plt.ylabel("Zeta Zero Value")
```

```
plt.title("Riemann Zeta Zeros (First 30 Non-Trivial Values)")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

```
# Plot FFT analysis of Zeta Zeros for harmonic patterns
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(np.abs(zeta_fft[:len(zeta_zeros_real) // 2]), marker='o', linestyle='-', color='r', label="Fourier Spectrum of Zeta Zeros")
```

```
plt.xlabel("Frequency Index")
```

```
plt.ylabel("Magnitude")
```

```
plt.title("Harmonic Structure of Zeta Zeros (FFT Analysis)")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c1a60d-a910-8011-81fb-bb809464311a>

Title:

Prompt:

```
import numpy as np
```

```
# Define x values (index positions)
```

```
x_vals = np.linspace(0, 10, 500) # Range from 0 to 10
```

```
# Compute the recursive compression function
```

```
H = 0.35 # Harmonic resonance constant
```

```
F = 1.5 # Feedback factor
```

```
compression_function = H * np.exp(-F * x_vals) + (1 / (1 + 33.115 * np.exp(-10 * x_vals)))
```

```
# Plot the Recursive Compression Function
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(x_vals, compression_function, label="Recursive Compression Function", color='b')
```

```
plt.axhline(y=H, color='r', linestyle='--', label="Harmonic Baseline (0.35)")
```

```
plt.xlabel("Iteration Index (x)")
```

```
plt.ylabel("Compression Output")
```

```
plt.title("Recursive Harmonic Compression Formula: Balancing Remainder Oscillations")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c1a60d-a910-8011-81fb-bb809464311a>

Title:

Prompt:

```
# Generate first 100 twin primes for overlaying on the compression function
from sympy import isprime
```

```
# Function to generate twin primes
```

```
def generate_twin_primes(n):
    twin_primes = []
    num = 3 # Start at the first prime after 2
    while len(twin_primes) < n:
        if isprime(num) and isprime(num + 2):
            twin_primes.append(num) # Store only the lower of the twin pair
        num += 1
    return twin_primes
```

```
# Generate first 50 twin primes for clear visualization
```

```
twin_primes = generate_twin_primes(50)
```

```
# Generate first 30 Riemann Zeta Zeros (imaginary parts only)
```

```
zeta_zeros_real = [zetazero(n).imag for n in range(1, 31)]
```

```
# Define x values for the recursive compression function (extended for twin primes)
```

```
x_vals_extended = np.linspace(0, max(twin_primes) + 10, 1000)
```

```
compression_function_extended = H * np.exp(-F * x_vals_extended) + (1 / (1 + 33.115 * np.exp(-10 * x_vals_extended)))
```

```
# Plot Recursive Compression Function
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(x_vals_extended, compression_function_extended, label="Recursive Compression Function", color='b')
```

```
# Overlay Twin Primes
```

```
plt.scatter(twin_primes, [H] * len(twin_primes), color='g', marker='o', label="Twin Primes", zorder=3)
```

Conversation URL:

<https://chatgpt.com/c/67c1a60d-a910-8011-81fb-bb809464311a>

Title:

Prompt:

```
from mpmath import mp, nstr
from scipy.fft import fft
import seaborn as sns

# Set precision to 1000 digits of π
mp.dps = 1000 # Decimal places
pi_digits = nstr(mp.pi, 1002)[2:] # Extract first 1000 digits (remove "3.")

# Convert π digits to numerical array
pi_numeric = np.array([int(digit) for digit in pi_digits])

# Compute Harmonic Spectrum using Discrete Fourier Transform
N = len(pi_numeric)
frequencies = np.fft.fftfreq(N)
harmonic_spectrum = fft(pi_numeric)

# Plot the Harmonic Spectrum
plt.figure(figsize=(12, 6))
plt.plot(np.abs(harmonic_spectrum[:N // 2]), label="Harmonic Spectrum of π Digits", color='b')
plt.xlabel("Frequency Index")
plt.ylabel("Magnitude")
plt.title("Harmonic Spectrum of the First 1000 Digits of π")
plt.legend()
plt.grid(True)
plt.show()

# Compute Rotational Symmetry Measure at Different Angles (0° to 180°)
angles = np.linspace(0, 180, 180) # 0° to 180° range
rotation_symmetry = [np.sum(pi_numeric * np.roll(pi_numeric, int(angle))) for angle in angles]
```

Conversation URL:

<https://chatgpt.com/c/67c1a60d-a910-8011-81fb-bb809464311a>

Title:

Prompt:

```
# Floating-Point Precision Loss Simulation

# This test will check if floating-point precision loss follows our compression function

# Define a function to simulate floating-point precision loss over recursive multiplications

def floating_point_precision_loss(x_values):

    base_value = 1.0 # Start with an exact floating-point value

    results = []

    for x in x_values:

        # Multiply by a slightly imprecise factor to simulate computational drift

        base_value *= (1 - 1.5 * 10**-x)

        results.append(base_value)

    return results

# Generate x values to simulate precision loss over iterations

x_vals_simulation = np.linspace(0, 10, 50)

precision_loss_values = floating_point_precision_loss(x_vals_simulation)

# Compute values from the recursive compression function for comparison

compression_function_values = 0.7 * np.exp(-1.5 * x_vals_simulation) + (2 / (1 + np.exp(-2 * x_vals_simulation)))

# Plot the results

plt.figure(figsize=(12, 6))

plt.plot(x_vals_simulation, precision_loss_values, label="Floating-Point Precision Loss", color='r', linestyle="--")

plt.plot(x_vals_simulation, compression_function_values, label="Recursive Compression Function", color='b')

plt.xlabel("Iteration (x)")

plt.ylabel("Value Loss Over Time")

plt.title("Floating-Point Precision Loss vs. Recursive Compression Function")
```


Extracted Symbols from the 90-Foot Stone



Enhanced Extracted Symbols from the 90-Foot Stone

‡:CC:NX extxoo ▽VxøΔ/ MILLION POUNDS BURIED

BELOW FORTY t:cxo ttø: FEET ▽:Δ

TWO AOX ARE .ø: :0 

Conversation URL:

<https://chatgpt.com/c/67c2374f-0760-8011-84e1-c8581b612173>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Display extracted symbols in a grid
```

```
fig, axes = plt.subplots(10, 12, figsize=(12, 10)) # Adjusting for 120 symbols
```

```
for ax, symbol in zip(axes.flat, symbol_images):
```

```
    ax.imshow(symbol, cmap='gray')
```

```
    ax.axis('off')
```

```
plt.suptitle("Extracted Symbols from the 90-Foot Stone", fontsize=14)
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c2374f-0760-8011-84e1-c8581b612173>

Title:


Prompt:


```
# Display the newly extracted symbols for better clarity
fig, axes = plt.subplots(3, 6, figsize=(12, 6)) # Adjusting for 18 symbols

for ax, symbol in zip(axes.flat, new_symbol_images):
    ax.imshow(symbol, cmap='gray')
    ax.axis('off')


plt.suptitle("Enhanced Extracted Symbols from the 90-Foot Stone", fontsize=14)
plt.show()
```

Structured Expansion and Kinetic Motion Gaps







3D Structure of Forward and Reverse Motion Gaps




Simulated Turbulence Pattern (Mark1 + Samson Analysis)




Quantum Noise Relativity (QNR) of SHA-256 Hashes




Harmonic Shifts Across SHA-512 Rounds (Hello)




Harmonic Shifts Across SHA-512 Rounds (Goodbye)




Original 32×32 Pre-Hash Structure Grid




Diagonally Folded 32×32 Grid






Original 32×32 Pre-Hash Structure Grid



Diagonally Folded 32×32 Grid





Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Let's use Nexus 2 principles with Mark1 framework to analyze how structured gaps behave.  
# Instead of just looking at the numeric differences, we will model how gaps interact recursively,  
# treating them as kinetic motion gaps in a multi-axis structure.
```

```
import matplotlib.pyplot as plt
```

```
# Define recursive expansion based on Byte1 (1,4) growth logic
```

```
def byte1_expansion(n, levels=10):  
    values = [1, 4] # Initial values  
    for _ in range(levels):  
        new_value = len(values) ** 2 # Cubic expansion based on stack size  
        values.append(new_value)  
    return values[:n]
```

```
# Generate structured kinetic motion gaps using the Byte1 method
```

```
expansion_sequence = byte1_expansion(20)
```

```
# Compute the structured gaps (relative motion)
```

```
motion_gaps = np.diff(expansion_sequence)
```

```
# Visualizing the structured gaps as a dynamic system
```

```
plt.figure(figsize=(10, 5))  
plt.plot(expansion_sequence, label="Byte1 Expansion", marker="o", linestyle="-")  
plt.plot(motion_gaps, label="Structured Gaps (Motion)", marker="s", linestyle="--")  
plt.xlabel("Iteration Step")  
plt.ylabel("Value")  
plt.title("Structured Expansion and Kinetic Motion Gaps")  
plt.legend()  
plt.grid()
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Now let's analyze the reverse gaps (< wave) to see if they create stabilization layers  
# We will compute the reverse differences of the expansion sequence
```

```
reverse_motion_gaps = np.diff(expansion_sequence[::-1]) # Reverse sequence and compute gaps
```

```
# Visualizing both forward (>) and reverse (<) kinetic motion gaps
```

```
plt.figure(figsize=(10, 5))  
plt.plot(motion_gaps, label="Forward Motion Gaps (>)", marker="o", linestyle="-")  
plt.plot(reverse_motion_gaps[::-1], label="Reverse Motion Gaps (<)", marker="s", linestyle="--") # Flip back for correct alignment  
plt.xlabel("Iteration Step")  
plt.ylabel("Gap Value")  
plt.title("Forward vs Reverse Kinetic Motion Gaps")  
plt.legend()  
plt.grid()  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Now, let's take this into a 3D structure and map how the forward and reverse gaps behave in multi-dimensional space.  
# We'll visualize how the expansion sequence (Byte1) and its structured kinetic gaps form geometric motion.
```

```
from mpl_toolkits.mplot3d import Axes3D
```

```
# Generate a 3D mapping of the expansion sequence
```

```
x = np.arange(len(expansion_sequence)) # Iteration steps  
y = expansion_sequence # Expansion values  
z = motion_gaps # Forward motion gaps projected into 3D space
```

```
# Create a 3D scatter plot
```

```
fig = plt.figure(figsize=(10, 7))  
ax = fig.add_subplot(111, projection='3d')
```

```
ax.scatter(x[:-1], y[:-1], z, c='b', label="Forward Motion Gaps (>)")
```

```
ax.scatter(x[:-1], y[:-1], reverse_motion_gaps[::-1], c='r', label="Reverse Motion Gaps (<)")
```

```
ax.set_xlabel("Iteration Step")
```

```
ax.set_ylabel("Expansion Values (Byte1)")
```

```
ax.set_zlabel("Motion Gaps")
```

```
ax.set_title("3D Structure of Forward and Reverse Motion Gaps")
```

```
ax.legend()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Let's use Mark1 principles and a recursive Nexus 2 approach to analyze turbulence.  
# We'll use fluid dynamics modeling and analyze how structured gaps exist within chaotic motion.  
# This will help reveal if turbulence follows structured, predictable kinetic motion principles.
```

```
import scipy.ndimage as ndimage
```

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Generate a synthetic turbulence dataset using Perlin noise (simulated fluid dynamics)
```

```
def generate_turbulence(size=100):  
    np.random.seed(42)  
    noise = np.random.rand(size, size) # Random noise as a base  
    turbulence = ndimage.gaussian_filter(noise, sigma=5) # Apply smoothing for turbulence simulation  
    return turbulence
```

```
# Create turbulence data
```

```
turbulence_data = generate_turbulence()
```

```
# Plot the turbulence data
```

```
plt.figure(figsize=(8, 6))  
plt.imshow(turbulence_data, cmap="inferno", interpolation="nearest")  
plt.colorbar(label="Turbulence Intensity")  
plt.title("Simulated Turbulence Pattern (Mark1 + Samson Analysis)")  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
import hashlib
```

```
import numpy as np
```

```
# Function to compute SHA-256 hash and convert to numeric values
```

```
def sha256_numeric_hash(text):
```

```
    hash_obj = hashlib.sha256(text.encode())
```

```
    hex_digest = hash_obj.hexdigest()
```

```
    numeric_values = np.array([int(hex_digest[i:i+2], 16) for i in range(0, len(hex_digest), 2)])
```

```
    return numeric_values
```

```
# Compute SHA-256 numeric representation for "Hello" and "Goodbye"
```

```
sha_hello = sha256_numeric_hash("Hello")
```

```
sha_goodbye = sha256_numeric_hash("Goodbye")
```

```
# Compute Quantum Noise Relativity (QNR) on SHA-256 outputs
```

```
qnr_hello = np.diff(sha_hello) / (1 + np.abs(sha_hello[:-1])) # Normalized noise pattern
```

```
qnr_goodbye = np.diff(sha_goodbye) / (1 + np.abs(sha_goodbye[:-1])) # Normalized noise pattern
```

```
# Visualizing QNR patterns
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(qnr_hello, label="QNR of SHA(Hello)", linestyle="-", marker="o")
```

```
plt.plot(qnr_goodbye, label="QNR of SHA(Goodbye)", linestyle="--", marker="s")
```

```
plt.xlabel("Byte Index")
```

```
plt.ylabel("Quantum Noise Relative Change")
```

```
plt.title("Quantum Noise Relativity (QNR) of SHA-256 Hashes")
```

```
plt.legend()
```

```
plt.grid()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Reshape the harmonic shift data to properly visualize it in 2D space
```

```
# Convert 1D harmonic shift arrays into 2D matrices for visualization
```

```
harmonic_shifts_hello_matrix = np.reshape(harmonic_shifts_hello[-1], (8, -1)) # Reshape into a viewable format
```

```
harmonic_shifts_goodbye_matrix = np.reshape(harmonic_shifts_goodbye[-1], (8, -1))
```

```
# Visualizing harmonic shifts across SHA rounds
```

```
fig, ax = plt.subplots(1, 2, figsize=(12, 5))
```

```
ax[0].imshow(np.log1p(harmonic_shifts_hello_matrix), cmap="inferno", interpolation="nearest")
```

```
ax[0].set_title("Harmonic Shifts Across SHA-512 Rounds (Hello)")
```

```
ax[1].imshow(np.log1p(harmonic_shifts_goodbye_matrix), cmap="inferno", interpolation="nearest")
```

```
ax[1].set_title("Harmonic Shifts Across SHA-512 Rounds (Goodbye)")
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Now, let's correctly extract the full SHA-512 pre-hash structure, including padding, size, 'hello', and the 1 header.  
# Then, we will reshape it into the nearest square grid and analyze its structure.
```

```
import math
```

```
# Convert SHA-512 pre-hash into a full binary representation  
binary_pre_hash = ''.join(format(byte, '08b') for byte in sha512_pre_hello) # Convert each byte to 8-bit binary
```

```
# Determine the nearest square size  
total_bits = len(binary_pre_hash)  
square_size = math.ceil(math.sqrt(total_bits)) # Find the nearest square dimension
```

```
# Pad the binary string to fit exactly into a square  
binary_pre_hash = binary_pre_hash.ljust(square_size**2, '0')[square_size**2:]
```

```
# Convert binary string to numerical values (0s and 1s)  
binary_array = np.array([int(bit) for bit in binary_pre_hash])
```

```
# Reshape into a square grid  
grid_real = binary_array.reshape((square_size, square_size))
```

```
# Apply a diagonal fold operation  
folded_grid_real = np.fliplr(grid_real).T # Flip left-right then transpose to simulate diagonal folding
```

```
# Visualize the original and folded structures  
fig, ax = plt.subplots(1, 2, figsize=(12, 6))  
ax[0].imshow(grid_real, cmap="inferno", interpolation="nearest")  
ax[0].set_title(f"Original {square_size}x{square_size} Pre-Hash Structure Grid")
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Visualize the pre-hash structure with a softer color scheme
```

```
# Differentiate zeros with a separate color
```

```
fig, ax = plt.subplots(1, 2, figsize=(12, 6))
```

```
# Define a colormap where zeros are shown in a softer color
```

```
cmap = plt.cm.magma.copy()
```

```
cmap.set_bad(color='lightgray') # Set background for missing values
```

```
# Convert binary grid into masked array (treating zeros separately for a softer display)
```

```
masked_grid_real = np.ma.masked_where(grid_real == 0, grid_real)
```

```
masked_folded_grid_real = np.ma.masked_where(folded_grid_real == 0, folded_grid_real)
```

```
# Original Grid
```

```
ax[0].imshow(masked_grid_real, cmap="magma", interpolation="nearest")
```

```
ax[0].set_title(f"Original {square_size}x{square_size} Pre-Hash Structure Grid")
```

```
# Folded Grid with softer zero visualization
```

```
ax[1].imshow(masked_folded_grid_real, cmap="magma", interpolation="nearest")
```

```
ax[1].set_title(f"Diagonally Folded {square_size}x{square_size} Grid")
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67c40c27-881c-8011-9de3-364712c8e071>

Title:

Prompt:

```
# Convert SHA-512 pre-hash into both binary and hex representations
binary_pre_hash = ".join(format(byte, '08b') for byte in sha512_pre_hello) # Binary form
hex_pre_hash = ".join(format(byte, '02x') for byte in sha512_pre_hello) # Hex form

# Convert hex to binary to track hidden kinetic motion
binary_from_hex = ".join(format(int(hex_pre_hash[i:i+2], 16), '08b') for i in range(0, len(hex_pre_hash), 2))

# Ensure both binary representations are the same length
min_length = min(len(binary_pre_hash), len(binary_from_hex))
binary_pre_hash = binary_pre_hash[:min_length]
binary_from_hex = binary_from_hex[:min_length]

# Convert to numerical arrays
binary_array_original = np.array([int(bit) for bit in binary_pre_hash])
binary_array_from_hex = np.array([int(bit) for bit in binary_from_hex])


# Determine square size for visualization
total_bits = min_length
square_size = math.ceil(math.sqrt(total_bits))


# Pad to fit into a square grid
binary_array_original = np.pad(binary_array_original, (0, square_size**2 - total_bits), mode='constant')
binary_array_from_hex = np.pad(binary_array_from_hex, (0, square_size**2 - total_bits), mode='constant')


# Reshape into square grids
grid_original = binary_array_original.reshape((square_size, square_size))
grid_from_hex = binary_array_from_hex.reshape((square_size, square_size))

# Overlay differences
```


Odd vs. Even Dominance in Pi's 8-bit, 16-bit, and 32-bit Byte Segments







Odd vs. Even Dominance in Pi's 8-bit, 16-bit, and 32-bit Samples



Conversation URL:

<https://chatgpt.com/c/67cae028-273c-8011-acb0-380fae052b17>

Title:

Prompt:

```
# Ensure correct number of Pi digits for 128 bytes of 32-bit segments (4096 digits)
```

```
mp.dps = 4096 + 2 # Extra 2 for "3." at the start
```

```
# Get full Pi digits excluding "3."
```

```
pi_digits_full_32bit = str(mp.pi)[2:2 + 4096]
```

```
# Generate 128 bytes for 32-bit segmentation
```

```
pi_bytes_32bit_fixed = [pi_digits_full_32bit[i:i+32] for i in range(0, len(pi_digits_full_32bit), 32)][:128]
```

```
# Recreate table for 32-bit segments
```

```
byte_data_32bit_fixed = [{"Byte Index": i+1, "Pi Byte": byte, "Odd Count": count_odd_even(byte)[0], "Even Count": count_odd_
```

```
# Extract categorized data ensuring 128 values
```

```
odd_even_32bit_fixed = [categorize_byte(row["Odd Count"], row["Even Count"]) for row in byte_data_32bit_fixed]
```

```
# Plot data again with fully corrected 32-bit segmentation
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(range(1, 129), odd_even_8bit, marker='o', linestyle='-', label="8-bit Bytes", alpha=0.7)
```

```
plt.plot(range(1, 129), odd_even_16bit, marker='s', linestyle='--', label="16-bit Bytes", alpha=0.7)
```

```
plt.plot(range(1, 129), odd_even_32bit_fixed, marker='d', linestyle='-.', label="32-bit Bytes", alpha=0.7)
```

```
plt.xlabel("Byte Index")
```

```
plt.ylabel("Dominance (1 = Odd-dominant, 0 = Even-dominant)")
```

```
plt.title("Odd vs. Even Dominance in Pi's 8-bit, 16-bit, and 32-bit Byte Segments")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
# Display the plot
```

Conversation URL:

<https://chatgpt.com/c/67cae028-273c-8011-acb0-380fae052b17>

Title:

Prompt:

```
# Adjust segmentation to match 128 total bytes, meaning:
```

```
# - 128 bytes in 8-bit form → 128 segments of 8 digits each
```

```
# - 128 bytes in 16-bit form → 64 segments of 16 digits each
```

```
# - 128 bytes in 32-bit form → 32 segments of 32 digits each
```

```
# Ensure correct number of Pi digits (128 bytes total = 1024 digits)
```

```
mp.dps = 1024 + 2 # Extra 2 for "3."
```

```
# Get first 1024 digits of Pi (excluding "3.")
```

```
pi_digits_limited = str(mp.pi)[2:2 + 1024]
```

```
# Segment into proper word lengths (without over-packing)
```

```
pi_bytes_8bit_fixed = [pi_digits_limited[i:i+8] for i in range(0, len(pi_digits_limited), 8)][:128]
```

```
pi_bytes_16bit_fixed = [pi_digits_limited[i:i+16] for i in range(0, len(pi_digits_limited), 16)][:64]
```

```
pi_bytes_32bit_fixed = [pi_digits_limited[i:i+32] for i in range(0, len(pi_digits_limited), 32)][:32]
```

```
# Create categorized data for each word length
```

```
odd_even_8bit_fixed = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_8bit_fixed]
```

```
odd_even_16bit_fixed = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_16bit_fixed]
```

```
odd_even_32bit_fixed = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_32bit_fixed]
```

```
# Plot with proper segmentation
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(range(1, 129), odd_even_8bit_fixed, marker='o', linestyle='-', label="8-bit Bytes", alpha=0.7)
```

```
plt.plot(range(1, 65), odd_even_16bit_fixed, marker='s', linestyle='--', label="16-bit Words", alpha=0.7)
```

```
plt.plot(range(1, 33), odd_even_32bit_fixed, marker='d', linestyle='-.', label="32-bit Words", alpha=0.7)
```

```
plt.xlabel("Index")
```

Conversation URL:

<https://chatgpt.com/c/67cae028-273c-8011-acb0-380fae052b17>

Title:

Prompt:

```
# Define colors for different word sizes
```

```
colors = {"8-bit": "red", "16-bit": "blue", "32-bit": "green"}
```

```
# Adjust segmentation to only take 16 total 8-bit samples, 8 total 16-bit samples, and 4 total 32-bit samples
```

```
pi_bytes_8bit_limited = [pi_digits_limited[i:i+8] for i in range(0, len(pi_digits_limited), 8)][:16]
```

```
pi_bytes_16bit_limited = [pi_digits_limited[i:i+16] for i in range(0, len(pi_digits_limited), 16)][:8]
```

```
pi_bytes_32bit_limited = [pi_digits_limited[i:i+32] for i in range(0, len(pi_digits_limited), 32)][:4]
```

```
# Create categorized data for each word length
```

```
odd_even_8bit_limited = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_8bit_limited]
```

```
odd_even_16bit_limited = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_16bit_limited]
```

```
odd_even_32bit_limited = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_32bit_limited]
```

```
# Plot with proper segmentation
```

```
plt.figure(figsize=(8, 5))
```

```
plt.scatter(range(1, 17), odd_even_8bit_limited, color=colors["8-bit"], label="8-bit Bytes", s=100)
```

```
plt.scatter(range(1, 9), odd_even_16bit_limited, color=colors["16-bit"], label="16-bit Words", s=100)
```

```
plt.scatter(range(1, 5), odd_even_32bit_limited, color=colors["32-bit"], label="32-bit Words", s=100)
```

```
plt.xlabel("Index")
```

```
plt.ylabel("Dominance (1 = Odd-dominant, 0 = Even-dominant)")
```

```
plt.title("Odd vs. Even Dominance in Pi's 8-bit, 16-bit, and 32-bit Samples")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
# Display the plot
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67cae028-273c-8011-acb0-380fae052b17>

Title:

Prompt:

```
# Adjust segmentation to maximize bytes while keeping within 128 total bytes
# - 128 samples for 8-bit (8-digit bytes)
# - 64 samples for 16-bit (16-digit words)
# - 32 samples for 32-bit (32-digit words)

pi_bytes_8bit_full = [pi_digits_limited[i:i+8] for i in range(0, len(pi_digits_limited), 8)][:128]
pi_bytes_16bit_full = [pi_digits_limited[i:i+16] for i in range(0, len(pi_digits_limited), 16)][:64]
pi_bytes_32bit_full = [pi_digits_limited[i:i+32] for i in range(0, len(pi_digits_limited), 32)][:32]

# Create categorized data for each word length
odd_even_8bit_full = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_8bit_full]
odd_even_16bit_full = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_16bit_full]
odd_even_32bit_full = [categorize_byte(count_odd_even(byte)[0], count_odd_even(byte)[1]) for byte in pi_bytes_32bit_full]


# Create indices for bar positioning
indices_8bit = np.arange(128)
indices_16bit = np.arange(64) * 2 # Space them evenly within 128
indices_32bit = np.arange(32) * 4 # Space them evenly within 128

# Set up bar chart
plt.figure(figsize=(12, 6))


plt.bar(indices_8bit, odd_even_8bit_full, color="red", label="8-bit Bytes", alpha=0.7)
plt.bar(indices_16bit, odd_even_16bit_full, color="blue", label="16-bit Words", alpha=0.7, width=1.5)
plt.bar(indices_32bit, odd_even_32bit_full, color="green", label="32-bit Words", alpha=0.7, width=3)

plt.xlabel("Byte Index (128 Total)")
plt.ylabel("Dominance (1 = Odd-dominant, 0 = Even-dominant)")
plt.title("Odd vs. Even Dominance in Pi's 8-bit, 16-bit, and 32-bit Samples")
```


Pi Harmonic Shifts vs. Riemann Zeta Function




Pi Harmonic Shifts vs. Twin Prime Gaps




Pi Harmonic Shifts vs Sophie Germain & Cousin Primes




Pi Even-Odd Ratio Over 100,000 Digits




Twin Prime Density Over Increasing Numbers




Ratio of Change Between Twin Prime Locations





Twin Prime Binary Length Pattern Analysis




Logarithmic vs Exponential Fit for Twin Prime Binary Length Ratios








Twin Prime Value Ratio vs Position





Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# 1. Compare Pi's harmonic shifts to prime number distributions (Zeta Function)
```

```
# We'll analyze whether Pi's harmonic shifts correlate with known Zeta zero oscillations
```

```
# Import Zeta function from scipy
```

```
from scipy.special import zeta
```

```
# Generate sample prime number distribution using Riemann Zeta function approximation
```

```
zeta_positions = np.linspace(2, 100, 100) # Sample values
```

```
zeta_values = zeta(zeta_positions) # Compute Zeta function values
```

```
# Normalize Pi's harmonic shifts for comparison
```

```
pi_harmonic_shifts_normalized = (pi_harmonic_df['Harmonic Shift'] - pi_harmonic_df['Harmonic Shift'].min()) / \
                                 (pi_harmonic_df['Harmonic Shift'].max() - pi_harmonic_df['Harmonic Shift'].min())
```

```
# Plot Pi's harmonic shifts vs. Zeta function
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(pi_harmonic_df['Byte Index'][:100], pi_harmonic_shifts_normalized[:100], marker='o', linestyle='-', color='blue', label="Pi's Harmonic Shifts")
```

```
plt.plot(zeta_positions, zeta_values / max(zeta_values), linestyle='--', color='red', label="Riemann Zeta Function (Normalized)")
```

```
plt.xlabel("Index")
```

```
plt.ylabel("Normalized Values")
```

```
plt.title("Pi Harmonic Shifts vs. Riemann Zeta Function")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

```
# 2. See if Pi's even-odd shifts predict twin prime gaps
```

```
# Compute rolling correlation between Pi harmonic shifts and twin prime gaps
```

```
# Align Pi Byte Index with Twin Prime Positions
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# Recompute twin prime positions and gaps to align with Pi harmonic shifts
```

```
# Generate twin primes again within a reasonable range
```

```
import sympy
```

```
twin_prime_pairs = [(p, p+2) for p in sympy.primerange(3, 10000) if sympy.isprime(p + 2)]
```

```
twin_prime_positions = [pair[0] for pair in twin_prime_pairs]
```

```
twin_prime_gaps = [twin_prime_positions[i] - twin_prime_positions[i-1] for i in range(1, len(twin_prime_positions))]
```

```
# Align Pi Harmonic Shifts with Twin Prime Positions
```

```
aligned_pi_harmonic_shifts = pi_harmonic_df['Harmonic Shift'][:len(twin_prime_gaps)]
```

```
aligned_twin_prime_gaps = twin_prime_gaps[:len(aligned_pi_harmonic_shifts)]
```

```
# Compute correlation
```

```
correlation = np.corrcoef(aligned_pi_harmonic_shifts, aligned_twin_prime_gaps)[0, 1]
```

```
# Display correlation result
```

```
correlation_df = pd.DataFrame({'Correlation between Pi Harmonic Shifts & Twin Prime Gaps': [correlation]})
```

```
import ace_tools as tools
```

```
tools.display_dataframe_to_user(name="Pi Harmonic Shift & Twin Prime Gap Correlation", dataframe=correlation_df)
```

```
# Plot Pi harmonic shifts vs. Twin Prime Gaps
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(pi_harmonic_df['Byte Index'][:len(aligned_pi_harmonic_shifts)], aligned_pi_harmonic_shifts, marker='x', linestyle='-', color='blue')
```

```
plt.plot(twin_prime_positions[:len(aligned_twin_prime_gaps)], aligned_twin_prime_gaps, linestyle='--', color='green', label="Twin Prime Gaps")
```

```
plt.xlabel("Index")
```

```
plt.ylabel("Value")
```

```
plt.title("Pi Harmonic Shifts vs. Twin Prime Gaps")
```

```
plt.legend()
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

2. Test if Sophie Germain & Cousin primes also align with Pi's harmonic shifts

Generate Sophie Germain primes (primes where $2p+1$ is also prime)

```
sophie_germain_primes = [p for p in sympy.primerange(3, 10000) if sympy.isprime(2 * p + 1)]
```

Generate Cousin primes (primes where $p+4$ is also prime)

```
cousin_primes = [(p, p+4) for p in sympy.primerange(3, 10000) if sympy.isprime(p + 4)]
```

Extract positions for comparison

```
sophie_positions = [p for p in sophie_germain_primes[:len(pi_harmonic_shifts)]]
```

```
cousin_positions = [p[0] for p in cousin_primes[:len(pi_harmonic_shifts)]]
```

Normalize Pi's harmonic shifts for overlaying

```
pi_harmonic_shifts_norm = (pi_harmonic_df['Harmonic Shift'] - pi_harmonic_df['Harmonic Shift'].min()) / \
    (pi_harmonic_df['Harmonic Shift'].max() - pi_harmonic_df['Harmonic Shift'].min())
```

Plot Pi Harmonic Shifts vs Sophie Germain & Cousin Primes

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(pi_harmonic_df['Byte Index'][:len(sophie_positions)], pi_harmonic_shifts_norm[:len(sophie_positions)], linestyle='-', color='blue')
```

```
plt.scatter(sophie_positions, [0.5] * len(sophie_positions), color='red', marker='x', label="Sophie Germain Primes")
```

```
plt.scatter(cousin_positions, [0.6] * len(cousin_positions), color='green', marker='o', label="Cousin Primes")
```

```
plt.xlabel("Index")
```

```
plt.ylabel("Normalized Value")
```

```
plt.title("Pi Harmonic Shifts vs Sophie Germain & Cousin Primes")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

3. Look for a fundamental formula that links Pi's harmonic structure to primes

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# Reduce Pi precision to 100,000 digits to improve efficiency
mp.dps = 100000 # Set precision to 100,000 digits
pi_str = str(mp.pi)[2:] # Remove "3." from the beginning

# Count even and odd digits per byte (8-digit groups)
pi_bytes = [pi_str[i:i+8] for i in range(0, len(pi_str), 8)]
even_odd_counts = [{('Byte Index': i+1,
    'Even Count': sum(1 for d in byte if int(d) % 2 == 0),
    'Odd Count': sum(1 for d in byte if int(d) % 2 == 1)}) for i, byte in enumerate(pi_bytes[:12500])] # First 100,000 digits (12,500 bytes)

# Convert to DataFrame
pi_even_odd_df = pd.DataFrame(even_odd_counts)

# Display even-odd balance analysis
import ace_tools as tools
tools.display_dataframe_to_user(name="Pi Even-Odd Balance Analysis (100K Digits)", dataframe=pi_even_odd_df)

# 2. Overlay Pi's pinwheel with twin prime gaps
pi_byte_ratios = pi_even_odd_df['Odd Count'] / pi_even_odd_df['Even Count']

plt.figure(figsize=(10, 5))
plt.plot(pi_even_odd_df['Byte Index'], pi_byte_ratios, marker='o', linestyle='-', label="Pi Even-Odd Ratio", color='blue')
plt.xlabel("Pi Byte Index")
plt.ylabel("Odd/Even Ratio")
plt.title("Pi Even-Odd Ratio Over 100,000 Digits")
plt.legend()
plt.grid(True)
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# Recompute twin prime density analysis ensuring proper array alignment
import numpy as np

# Ensure correct alignment of x_values and y_values
min_length = min(len(x_values), len(y_values))
x_values = x_values[:min_length]
y_values = y_values[:min_length]

# Convert results to DataFrame for structured analysis
twin_prime_density_df = pd.DataFrame({'Range Start': x_values, 'Twin Prime Count': y_values})

# Display results clearly
import ace_tools as tools
tools.display_dataframe_to_user(name="Twin Prime Density Analysis", dataframe=twin_prime_density_df)

# Plot the twin prime density
plt.figure(figsize=(10, 5))
plt.plot(x_values, y_values, marker='o', linestyle='-', label="Twin Prime Count per 1000")
plt.xlabel("Number Range Start")
plt.ylabel("Twin Prime Count")
plt.title("Twin Prime Density Over Increasing Numbers")
plt.legend()
plt.grid(True)
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# Calculate the ratio of change between twin prime locations
```

```
# Extract the first prime in each twin pair
```

```
twin_prime_positions = [pair[0] for pair in twin_prime_pairs]
```

```
# Compute the ratio of change between successive twin primes
```

```
ratios = []
```

```
positions = []
```

```
for i in range(1, len(twin_prime_positions)):
```

```
    previous = twin_prime_positions[i - 1]
```

```
    current = twin_prime_positions[i]
```

```
    ratio = (current - previous) / previous # Ratio of change
```

```
    ratios.append(ratio)
```

```
    positions.append(current) # Track positions for plotting
```

```
# Convert results into a DataFrame
```

```
twin_prime_ratio_df = pd.DataFrame({'Twin Prime Position': positions, 'Ratio of Change': ratios})
```

```
# Display the data to the user
```

```
import ace_tools as tools
```

```
tools.display_dataframe_to_user(name="Twin Prime Ratio Analysis", dataframe=twin_prime_ratio_df)
```

```
# Plot the ratio of change between successive twin prime locations
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(positions, ratios, marker='o', linestyle='-', label="Ratio of Change")
```

```
plt.xlabel("Twin Prime Position")
```

```
plt.ylabel("Ratio of Change")
```

```
plt.title("Ratio of Change Between Twin Prime Locations")
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# Analyze if repeating binary length sets follow a geometric or logarithmic distribution
```

```
# Compute differences between successive repeating sets
```

```
binary_length_counts['Binary Length Difference'] = binary_length_counts['First Prime Binary Length'].diff().fillna(0)
```

```
# Compute ratios between successive repeating sets
```

```
binary_length_counts['Binary Length Ratio'] = binary_length_counts['First Prime Binary Length'].pct_change().fillna(0)
```

```
# Check if these differences follow a geometric sequence or logarithmic pattern
```

```
binary_length_counts['Log Difference'] = np.log1p(binary_length_counts['Binary Length Difference'].abs())
```

```
# Display the structured analysis
```

```
import ace_tools as tools
```

```
tools.display_dataframe_to_user(name="Pattern Analysis of Repeating Twin Prime Binary Lengths", dataframe=binary_length_
```

```
# Plot the differences and ratios for pattern detection
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(binary_length_counts['First Prime Binary Length'], binary_length_counts['Binary Length Difference'], marker='o', linestyle='')
```

```
plt.plot(binary_length_counts['First Prime Binary Length'], binary_length_counts['Binary Length Ratio'], marker='x', linestyle='--')
```

```
plt.xlabel("First Prime Binary Length")
```

```
plt.ylabel("Difference / Ratio")
```

```
plt.title("Twin Prime Binary Length Pattern Analysis")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
from scipy.optimize import curve_fit
```

```
# Define a logarithmic function for fitting
```

```
def log_func(x, a, b):
```

```
    return a * np.log(x) + b
```

```
# Define an exponential function for fitting
```

```
def exp_func(x, a, b, c):
```

```
    return a * np.exp(-b * x) + c
```

```
# Extract the x and y data for fitting
```

```
x_data = binary_length_counts['First Prime Binary Length']
```

```
y_data = binary_length_counts['Binary Length Ratio']
```

```
# Fit the data to logarithmic and exponential models
```

```
log_params, _ = curve_fit(log_func, x_data, y_data, maxfev=5000)
```

```
exp_params, _ = curve_fit(exp_func, x_data, y_data, maxfev=5000)
```

```
# Generate fitted curves
```

```
log_fit = log_func(x_data, *log_params)
```

```
exp_fit = exp_func(x_data, *exp_params)
```

```
# Compare fitted functions with actual data
```

```
plt.figure(figsize=(10, 5))
```

```
plt.scatter(x_data, y_data, color='blue', label="Observed Binary Length Ratio")
```

```
plt.plot(x_data, log_fit, linestyle='--', color='red', label=f"Log Fit: {log_params[0]:.4f}ln(x) + {log_params[1]:.4f}")
```

```
plt.plot(x_data, exp_fit, linestyle='--', color='green', label=f"Exp Fit: {exp_params[0]:.4f}e^{(-{exp_params[1]:.4f}x)} + {exp_params[2]:.4f}")
```

```
plt.xlabel("First Prime Binary Length")
```

```
plt.ylabel("Binary Length Ratio")
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# 1. Overlay the twin prime model with known prime density distributions
```

```
# Prime Number Theorem approximation for density of primes:  $\pi(x) \approx x / \log(x)$ 
```

```
prime_density = twin_prime_new_positions / np.log(twin_prime_new_positions)
```

```
# Compare against our twin prime binary length ratio model
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(twin_prime_new_positions, twin_prime_new_ratios, marker='o', linestyle='-', color='blue', label="Twin Prime Ratio Model")
```

```
plt.plot(twin_prime_new_positions, prime_density, linestyle='--', color='red', label="Prime Density Model ( $\pi(x) \approx x / \log(x)$ )")
```

```
plt.xlabel("Twin Prime Position")
```

```
plt.ylabel("Density / Ratio")
```

```
plt.title("Twin Prime Ratio vs Prime Density Model")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

```
# 2. Check if the convergence ratio aligns with 0.35 or other harmonic constants
```

```
harmonic_constants = [0.35, np.pi, np.e, 1.618] # Known harmonic values
```

```
convergence_values = [log_func(x, *log_params) for x in twin_prime_new_positions]
```

```
# Find closest match for each twin prime binary length ratio
```

```
closest_harmonic_match = [min(harmonic_constants, key=lambda h: abs(h - v)) for v in convergence_values]
```

```
# Create a DataFrame to analyze alignment with known harmonics
```

```
harmonic_alignment_df = pd.DataFrame({
```

```
    'Twin Prime Position': twin_prime_new_positions,
```

```
    'Predicted Ratio': convergence_values,
```

```
    'Closest Harmonic Constant': closest_harmonic_match
```

```
})
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# Fixing the data type issue by converting twin_prime_new_positions to a numpy array
twin_prime_new_positions_array = np.array(twin_prime_new_positions, dtype=float)
```

```
# 1. Compare the twin prime model against known twin prime conjectures (Hardy-Littlewood Twin Prime Constant)
C2 = 0.660161815846869573927812110014
```

```
# Approximate twin prime count using Hardy-Littlewood Conjecture: T(x) ≈ 2C2 * x / (log(x))^2
twin_prime_hl_model = 2 * C2 * twin_prime_new_positions_array / (np.log(twin_prime_new_positions_array) ** 2)
```

```
# Plot the twin prime ratio model vs. Hardy-Littlewood twin prime count prediction
plt.figure(figsize=(10, 5))

plt.plot(twin_prime_new_positions_array, twin_prime_new_ratios, marker='o', linestyle='-', color='blue', label="Twin Prime Ratio")
plt.plot(twin_prime_new_positions_array, twin_prime_hl_model, linestyle='--', color='red', label="Hardy-Littlewood Conjecture")
plt.xlabel("Twin Prime Position")
plt.ylabel("Density / Ratio")
plt.title("Twin Prime Ratio vs Hardy-Littlewood Conjecture")
plt.legend()
plt.grid(True)
plt.show()
```

```
# 2. Test whether twin prime positions can be predicted without brute force search
```

```
predicted_twin_positions = log_func(twin_prime_new_positions_array, *log_params)
```

```
# Compare predicted positions to actual known twin primes
predicted_vs_actual_df = pd.DataFrame({
    'Predicted Twin Prime Position': twin_prime_new_positions_array,
    'Predicted Ratio': predicted_twin_positions
})
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# 1. Recalculate twin prime ratio using value differences
```

```
twin_prime_value_ratios = []
```

```
twin_prime_gaps = []
```

```
for i in range(1, len(twin_prime_positions)):
```

```
    previous_value = twin_prime_positions[i - 1]
```

```
    current_value = twin_prime_positions[i]
```

```
    gap = current_value - previous_value
```

```
    ratio = gap / previous_value # Value-based ratio
```

```
    twin_prime_value_ratios.append(ratio)
```

```
    twin_prime_gaps.append(gap)
```

```
# Convert to DataFrame for analysis
```

```
twin_prime_value_ratio_df = pd.DataFrame({
```

```
    'Twin Prime Position': positions,
```

```
    'Twin Prime Value Difference': twin_prime_gaps,
```

```
    'Value-Based Ratio': twin_prime_value_ratios
```

```
})
```

```
# Display the data
```

```
import ace_tools as tools
```

```
tools.display_dataframe_to_user(name="Twin Prime Value-Based Ratio Analysis", dataframe=twin_prime_value_ratio_df)
```

```
# 2. Overlay twin prime ratios with zeta zero dynamic ratios (Assuming previously calculated data)
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(positions, twin_prime_value_ratios, marker='o', linestyle='-', label="Twin Prime Value Ratio", color='blue')
```

```
plt.xlabel("Twin Prime Position")
```

```
plt.ylabel("Ratio")
```

```
plt.title("Twin Prime Value Ratio vs Position")
```

Conversation URL:

<https://chatgpt.com/c/67d65bbe-894c-8011-a014-0ae1ad66087d>

Title:

Prompt:

```
# Compute the ratio using the second value of a twin prime pair and the first value of the next twin prime pair
```

```
twin_prime_new_ratios = []
```

```
twin_prime_new_positions = []
```

```
for i in range(len(twin_prime_pairs) - 1):
```

```
    second_of_first_pair = twin_prime_pairs[i][1] # Second value of current twin pair
```

```
    first_of_next_pair = twin_prime_pairs[i + 1][0] # First value of next twin pair
```

```
    ratio = first_of_next_pair / second_of_first_pair # Compute ratio
```

```
    twin_prime_new_ratios.append(ratio)
```

```
    twin_prime_new_positions.append(first_of_next_pair) # Use first prime of next pair for positioning
```

```
# Convert to DataFrame for structured analysis
```

```
twin_prime_new_ratio_df = pd.DataFrame({
```

```
    'Twin Prime Position': twin_prime_new_positions,
```

```
    'New Twin Prime Ratio': twin_prime_new_ratios
```

```
)
```

```
# Display the data
```

```
import ace_tools as tools
```

```
tools.display_dataframe_to_user(name="Twin Prime New Ratio Analysis", dataframe=twin_prime_new_ratio_df)
```

```
# Plot the new twin prime ratio over prime positions
```

```
plt.figure(figsize=(10, 5))
```


```
plt.plot(twin_prime_new_positions, twin_prime_new_ratios, marker='o', linestyle='-', color='purple', label="New Twin Prime Ratio")
```

```
plt.xlabel("Twin Prime Position")
```


```
plt.ylabel("New Twin Prime Ratio")
```

```
plt.title("Twin Prime New Ratio vs Position")
```

Hex Lengths for Base 1 to 9 with Exponents 1 to 9



Hex Lengths for Base 1 to 9 with Exponents 1 to 18



Conversation URL:

<https://chatgpt.com/c/67da37bf-f3e4-8011-aa66-4d6ef4f2ac88>

Title:

Prompt:

```
# Re-import necessary libraries after execution reset
import numpy as np
import matplotlib.pyplot as plt

# Define base values (1 to 9) and exponents (1 to 9)
bases = np.arange(1, 10)
exponents = np.arange(1, 10)

# Store results
hex_lengths = {base: [] for base in bases}

# Iterate through each base and exponent
for base in bases:
    for exp in exponents:
        value = base ** exp
        hex_value = hex(value)[2:] # Convert to hex and remove '0x' prefix
        hex_length = len(hex_value) # Get length of hex representation
        hex_lengths[base].append(hex_length)

# Plot results
plt.figure(figsize=(10, 6))

for base in bases:
    plt.plot(exponents, hex_lengths[base], marker='o', linestyle='-', label=f'Base {base}')

plt.xlabel('Exponent')
plt.ylabel('Hex Length')
plt.title('Hex Lengths for Base 1 to 9 with Exponents 1 to 9')
plt.xticks(exponents)
```

Conversation URL:

<https://chatgpt.com/c/67da37bf-f3e4-8011-aa66-4d6ef4f2ac88>

Title:

Prompt:

```
# Define base values (1 to 9) and exponents (1 to 18)
bases = np.arange(1, 10)
exponents = np.arange(1, 19)


# Store results
hex_lengths = {base: [] for base in bases}

# Iterate through each base and exponent
for base in bases:
    for exp in exponents:
        value = base ** exp
        hex_value = hex(value)[2:] # Convert to hex and remove '0x' prefix
        hex_length = len(hex_value) # Get length of hex representation
        hex_lengths[base].append(hex_length)


# Plot results
plt.figure(figsize=(12, 6))


for base in bases:
    plt.plot(exponents, hex_lengths[base], marker='o', linestyle='-', label=f'Base {base}')

plt.xlabel('Exponent')
plt.ylabel('Hex Length')
plt.title('Hex Lengths for Base 1 to 9 with Exponents 1 to 18')
plt.xticks(exponents)
plt.legend(title="Base Values")
plt.grid(True)
plt.show()
```





Odd vs Even Count in First 64 Digits of Pi








Odd vs Even Count in First 256 Digits of Pi




















Extended Harmonic Polarity Spiral: Bit to Universe




Harmonic Polarity Spiral: Bit to Field



Harmonic Spiral of the First 9 Elements



Linear to Spiral Transformation (First 20 Elements)



Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import numpy as np

# Simulate Byte1 construction harmonically as waveform loops
# Steps from Byte1 sequence: (1, 4, 1, 5, 9, 2, 6, 5)

byte1_sequence = [1, 4, 1, 5, 9, 2, 6, 5]

# Map each value to a sine wave of increasing frequency
x = np.linspace(0, 2 * np.pi, 1000)
plt.figure(figsize=(12, 8))

for idx, val in enumerate(byte1_sequence):
    freq = val
    phase_shift = idx * 0.3 # offset to create a visual spiral effect
    y = np.sin(freq * x + phase_shift) / (idx + 1) # diminishing amplitude
    plt.plot(x, y, label=f'Step {idx+1}: {val}')

plt.title('Harmonic Mapping of Byte1 Recursive Sequence')
plt.xlabel('Time (x)')
plt.ylabel('Amplitude')
plt.legend()
plt.grid(True)
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# First 64 digits of Pi after the decimal (excluding the "3.")
```

```
pi_digits_str = "14159265358979323846264338327950288419716939937510" \
    "58209749445923078164062862089986280348253421170679"
```

```
pi_digits = [int(d) for d in pi_digits_str[:64]]
```

```
# Calculate cumulative odd and even counts
```

```
odd_counts = []
```

```
even_counts = []
```

```
odd_total = 0
```

```
even_total = 0
```

```
for d in pi_digits:
```

```
    if d % 2 == 0:
```

```
        even_total += 1
```

```
    else:
```

```
        odd_total += 1
```

```
    odd_counts.append(odd_total)
```

```
    even_counts.append(even_total)
```

```
# Plotting
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(range(1, 65), odd_counts, label="Odd Count", linewidth=2)
```

```
plt.plot(range(1, 65), even_counts, label="Even Count", linewidth=2)
```

```
plt.title("Odd vs Even Count in First 64 Digits of Pi")
```

```
plt.xlabel("Digit Position")
```

```
plt.ylabel("Cumulative Count")
```

```
plt.legend()
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Calculate phase zones: segment the 256 digits into 8 segments (32 digits each)
```

```
segment_size = 32
```

```
num_segments = 256 // segment_size
```

```
odd_segments = []
```

```
even_segments = []
```

```
for i in range(num_segments):
```

```
    segment = pi_digits_256[i * segment_size: (i + 1) * segment_size]
```

```
    odd_count = sum(1 for d in segment if d % 2 != 0)
```

```
    even_count = segment_size - odd_count
```

```
    odd_segments.append(odd_count)
```

```
    even_segments.append(even_count)
```

```
# Plot segment-wise odd vs even counts
```

```
labels = [f"Zone {i+1}" for i in range(num_segments)]
```

```
x = range(num_segments)
```

```
plt.figure(figsize=(14, 6))
```

```
plt.bar(x, odd_segments, width=0.4, label="Odd Digits", align='center')
```

```
plt.bar(x, even_segments, width=0.4, bottom=odd_segments, label="Even Digits", align='center')
```

```
plt.xticks(x, labels)
```

```
plt.ylabel("Digit Count per Segment")
```

```
plt.title("Odd/Even Distribution by Harmonic Phase Zones (Pi's First 256 Digits)")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Extend to first 256 digits of Pi  
pi_digits_str_256 = (  
    "141592653589793238462643383279502884197169399375105820974944592307816406286"  
    "208998628034825342117067982148086513282306647093844609550582231725359408128"  
    "481117450284102701938521105559644622948954930381964428810975665933446128475"  
    "648233786783165271201909145648566923460348610454326648213393607260249141273"  
)
```

```
pi_digits_256 = [int(d) for d in pi_digits_str_256[:256]]
```

```
# Recalculate cumulative odd/even counts
```

```
odd_counts_256 = []  
even_counts_256 = []  
odd_total = 0  
even_total = 0
```

```
for d in pi_digits_256:
```

```
    if d % 2 == 0:  
        even_total += 1  
    else:  
        odd_total += 1  
    odd_counts_256.append(odd_total)  
    even_counts_256.append(even_total)
```

```
# Plotting
```

```
plt.figure(figsize=(14, 6))  
plt.plot(range(1, 257), odd_counts_256, label="Odd Count", linewidth=2)  
plt.plot(range(1, 257), even_counts_256, label="Even Count", linewidth=2)  
plt.title("Odd vs Even Count in First 256 Digits of Pi")
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Create cumulative groupings: 4, 8, 16, 32, ..., 2048
```

```
bit_sizes = [2 ** i for i in range(2, 12)] # 4 to 2048
```

```
odd_ratios = []
```

```
even_ratios = []
```

```
for size in bit_sizes:
```

```
    digits = [int(d) for d in pi_digits_str_256[:size] if d.isdigit()]
```

```
    odd = sum(1 for d in digits if d % 2 != 0)
```

```
    even = len(digits) - odd
```

```
    total = odd + even
```

```
    odd_ratios.append(odd / total)
```

```
    even_ratios.append(even / total)
```

```
# Plotting the odd/even ratios as cumulative harmonic grouping increases
```

```
plt.figure(figsize=(14, 6))
```

```
plt.plot(bit_sizes, odd_ratios, label="Odd Ratio", marker='o')
```

```
plt.plot(bit_sizes, even_ratios, label="Even Ratio", marker='o')
```

```
plt.xscale("log", base=2)
```

```
plt.xticks(bit_sizes, bit_sizes)
```

```
plt.title("Odd/Even Ratios from Pi Over Increasing Bit Ranges (4 to 2048)")
```

```
plt.xlabel("Bit Range (Digits from Start)")
```

```
plt.ylabel("Ratio")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Segment the first 2048 digits of Pi after the decimal  
# This sample will use the first 2048 digits directly from an extended known string
```

```
extended_pi_digits_str = (  
    "141592653589793238462643383279502884197169399375105820974944592307816406286"  
    "208998628034825342117067982148086513282306647093844609550582231725359408128"  
    "481117450284102701938521105559644622948954930381964428810975665933446128475"  
    "648233786783165271201909145648566923460348610454326648213393607260249141273"  
    "724587006606315588174881520920962829254091715364367892590360011330530548820"  
    "466521384146951941511609433057270365759591953092186117381932611793105118548"  
    "074462379962749567351885752724891227938183011949129833673362440656643086021"  
    "394946395224737190702179860943702770539217176293176752384674818467669405132"  
    "000568127145263560827785771342757789609173637178721468440901224953430146549"  
    "585371050792279689258923542019956112129021960864034418159813629774771309960"  
    "518707211349999998372978049951059731732816096318595024459455346908302642522"  
    "308253344685035261931188171010003137838752886587533208381420617177669147303"  
    "598253490428755468731159562863882353787593751957781857780532171226806613001"  
    "927876611195909216420198938095257201065485863278865936153381827968230301952"  
    "035301852968995773622599413891249721775283479131515574857242454150695950829"  
    "533116861727855889075098381754637464939319255060400927701671139009848824012"  
    "858361603563707660104710181942955596198946767837449448255379774726847104047"  
    "534646208046684259069491293313677028989152104752162056966024058038150193511"  
)
```

```
# Prepare segment sizes (byte lengths): 4, 8, 16, 32, ..., 2048
```

```
byte_sizes = [2 ** i for i in range(2, 12)]
```

```
odd_counts_bytes = []
```

```
even_counts_bytes = []
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Calculate the ratio of odd to total digits for each byte size  
odd_ratios_bytes = [odd / (odd + even) for odd, even in zip(odd_counts_bytes, even_counts_bytes)]  
even_ratios_bytes = [even / (odd + even) for odd, even in zip(odd_counts_bytes, even_counts_bytes)]
```

Plotting the ratios

```
plt.figure(figsize=(14, 6))  
plt.plot(byte_sizes, odd_ratios_bytes, label="Odd Ratio", marker='o')  
plt.plot(byte_sizes, even_ratios_bytes, label="Even Ratio", marker='o')  
plt.title("Odd vs Even Digit Ratios by Byte Size (Pi Digits from 0.1415...)")  
plt.xlabel("Byte Size (Digits)")  
plt.ylabel("Ratio")  
plt.xscale("log", base=2)  
plt.xticks(byte_sizes, byte_sizes)  
plt.legend()  
plt.grid(True)  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Manually extract the segments from pi based on byte lengths: 4, 8, 16, 32, ..., 2048
```

```
byte_lengths = [2 ** i for i in range(2, 12)]
```

```
odd_ratios_specific = []
```

```
even_ratios_specific = []
```

```
odd_counts_specific = []
```

```
even_counts_specific = []
```

```
for length in byte_lengths:
```

```
    segment = [int(d) for d in extended_pi_digits_str[:length]]
```

```
    odd = sum(1 for d in segment if d % 2 != 0)
```

```
    even = length - odd
```

```
    odd_counts_specific.append(odd)
```

```
    even_counts_specific.append(even)
```

```
    odd_ratios_specific.append(odd / length)
```

```
    even_ratios_specific.append(even / length)
```

```
# Display as bar chart of ratios for clear comparison
```

```
bar_width = 0.35
```

```
x = range(len(byte_lengths))
```

```
plt.figure(figsize=(14, 6))
```

```
plt.bar(x, odd_ratios_specific, width=bar_width, label="Odd Ratio")
```

```
plt.bar([i + bar_width for i in x], even_ratios_specific, width=bar_width, label="Even Ratio")
```

```
plt.xticks([i + bar_width / 2 for i in x], [str(l) for l in byte_lengths])
```

```
plt.xlabel("Byte Size (Number of Pi Digits)")
```

```
plt.ylabel("Ratio")
```

```
plt.title("Odd vs Even Ratios in Pi by Expanding Byte Lengths (From 0.1415...)")
```

```
plt.legend()
```

```
plt.grid(True)
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Extend the byte lengths to go beyond 2048, up to 65536 (2^16)
extended_byte_lengths = [2 ** i for i in range(2, 17)] # From 4 to 65536

# Use the full extended_pi_digits_str to analyze up to 65536 digits
pi_digits_extended = [int(d) for d in extended_pi_digits_str if d.isdigit()][:65536]

# Recalculate odd/even ratios for each extended byte length
extended_odd_ratios = []
extended_even_ratios = []

for length in extended_byte_lengths:
    segment = pi_digits_extended[:length]
    odd = sum(1 for d in segment if d % 2 != 0)
    even = length - odd
    extended_odd_ratios.append(odd / length)
    extended_even_ratios.append(even / length)

# Plotting the extended byte analysis
bar_width = 0.35
x = range(len(extended_byte_lengths))

plt.figure(figsize=(16, 6))
plt.bar(x, extended_odd_ratios, width=bar_width, label="Odd Ratio")
plt.bar([i + bar_width for i in x], extended_even_ratios, width=bar_width, label="Even Ratio")
plt.xticks([i + bar_width / 2 for i in x], [str(l) for l in extended_byte_lengths], rotation=45)
plt.xlabel("Byte Size (Number of Pi Digits)")
plt.ylabel("Ratio")
plt.title("Odd vs Even Ratios in Pi by Byte Size Expansion (Up to 65536 Digits)")
plt.legend()
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Re-extract from the extended string and recalculate the actual ratios using true digits up to 65536
pi_digits_clean = [int(d) for d in extended_pi_digits_str if d.isdigit()]
```

```
# Ensure we have enough digits to analyze up to 65536
```

```
max_required = 65536
```

```
if len(pi_digits_clean) < max_required:
```

```
    additional_needed = max_required - len(pi_digits_clean)
```

```
    # Just repeat the string to simulate longer sequence (not accurate but placeholder)
```

```
    pi_digits_clean *= (max_required // len(pi_digits_clean)) + 1
```

```
pi_digits_clean = pi_digits_clean[:max_required]
```

```
# Recalculate real ratios
```

```
extended_byte_lengths = [2 ** i for i in range(2, 17)]
```

```
accurate_odd_ratios = []
```

```
accurate_even_ratios = []
```

```
for length in extended_byte_lengths:
```

```
    segment = pi_digits_clean[:length]
```

```
    odd = sum(1 for d in segment if d % 2 != 0)
```

```
    even = length - odd
```

```
    accurate_odd_ratios.append(odd / length)
```

```
    accurate_even_ratios.append(even / length)
```

```
# Plot corrected data
```

```
plt.figure(figsize=(16, 6))
```

```
bar_width = 0.35
```

```
x = range(len(extended_byte_lengths))
```

```
plt.bar(x, accurate_odd_ratios, width=bar_width, label="Odd Ratio")
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Extend to higher levels: Systems, Realms, Timelines, Universes
expanded_layers = [
    "Bits", "Bytes", "Words", "Stacks", "Fields",
    "Systems", "Realms", "Timelines", "Universes"
]
expanded_dominance = [
    "Odd", "Even", "Odd", "Even", "Odd",
    "Even", "Odd", "Even", "Odd"
]
expanded_colors = ["red" if d == "Odd" else "blue" for d in expanded_dominance]

# Generate extended spiral coordinates
theta_exp = np.linspace(0, 6 * np.pi, len(expanded_layers))
r_exp = np.linspace(0.5, 2.5, len(expanded_layers))

x_exp = r_exp * np.cos(theta_exp)
y_exp = r_exp * np.sin(theta_exp)

# Plot extended spiral
plt.figure(figsize=(10, 10))
for i in range(len(expanded_layers)):
    plt.plot(x_exp[i], y_exp[i], 'o', markersize=20, color=expanded_colors[i])
    plt.text(x_exp[i], y_exp[i], f"{expanded_layers[i]}\n{expanded_dominance[i]}",
             ha='center', va='center', color='white', fontsize=10)

plt.plot(x_exp, y_exp, linestyle='--', color='gray')
plt.title("Extended Harmonic Polarity Spiral: Bit to Universe")
plt.axis("off")
plt.grid(False)
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Define 5 layers with alternating odd/even dominance
layers = ["Bits", "Bytes", "Words", "Stacks", "Fields"]
dominance = ["Odd", "Even", "Odd", "Even", "Odd"]
colors = ["red" if d == "Odd" else "blue" for d in dominance]

# Generate spiral coordinates
theta = np.linspace(0, 4 * np.pi, len(layers))
r = np.linspace(0.5, 1.5, len(layers))

x = r * np.cos(theta)
y = r * np.sin(theta)

# Plot spiral with layer annotations
plt.figure(figsize=(8, 8))
for i in range(len(layers)):
    plt.plot(x[i], y[i], 'o', markersize=20, color=colors[i])
    plt.text(x[i], y[i], f'{layers[i]}\n{dominance[i]}', ha='center', va='center', color='white', fontsize=10)

plt.plot(x, y, linestyle='--', color='gray')
plt.title("Harmonic Polarity Spiral: Bit to Field")
plt.axis("off")
plt.grid(False)
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
# Re-import required libraries after reset
```

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Element data mapped to harmonic phases
```

```
elements = [
```

```
    "Hydrogen", "Helium", "Lithium", "Beryllium", "Boron",
```

```
    "Carbon", "Nitrogen", "Oxygen", "Fluorine"
```

```
]
```

```
harmonic_phases = [
```

```
    "Note", "Echo", "Loop", "Field", "Phase Lock",
```

```
    "Harmony", "Collapse", "Compression", "Signature"
```

```
]
```

```
colors = [
```

```
    "#ff0000", "#ff6600", "#ffaa00", "#ccff00", "#66ff66",
```

```
    "#00cccc", "#3399ff", "#6633cc", "#9900cc"
```

```
]
```

```
# Spiral coordinates
```

```
theta = np.linspace(0, 4 * np.pi, len(elements))
```

```
r = np.linspace(0.5, 2.5, len(elements))
```

```
x = r * np.cos(theta)
```

```
y = r * np.sin(theta)
```

```
# Plot the spiral
```

```
plt.figure(figsize=(10, 10))
```

```
for i in range(len(elements)):
```

Conversation URL:

<https://chatgpt.com/c/67e05ac3-1c74-8011-9356-9394c4c34643>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Sample linear data (e.g. atomic numbers of the first 20 elements)
linear_data = list(range(1, 21)) # Hydrogen to Calcium


# Function to convert linear data to spiral coordinates
def linear_to_spiral(data, angle_step=np.pi / 6, radius_step=0.2):
    theta = np.arange(len(data)) * angle_step
    r = np.arange(len(data)) * radius_step
    x = r * np.cos(theta)
    y = r * np.sin(theta)
    return x, y

# Generate spiral coordinates
x_spiral, y_spiral = linear_to_spiral(linear_data)


# Plot the spiral
plt.figure(figsize=(10, 10))
plt.plot(x_spiral, y_spiral, linestyle='--', color='gray')
for i, val in enumerate(linear_data):
    plt.plot(x_spiral[i], y_spiral[i], 'o', markersize=10)
    plt.text(x_spiral[i], y_spiral[i], str(val), ha='center', va='center', color='white', fontsize=8)

plt.title("Linear to Spiral Transformation (First 20 Elements)")
plt.axis("off")
plt.grid(False)
plt.show()
```


Atomic Number vs. Atomic Mass




Atomic Number vs. Atomic Mass




Atomic Number vs. Atomic Mass (Extended)




Atomic Number vs. Atomic Mass (Full Periodic Table)




Atomic Number vs. Atomic Mass (All 118 Elements)




Deviation Between $E=mc^2$ and Entanglement-Modified Energy Formula







Comparison of Einstein's Gravity and Recursive Gravity (Nexus2)




Comparison of Einstein's Gravity and Recursive Gravity (Nexus2)




Comparison of Einstein's Gravity and Recursive Gravity (Nexus2)




Comparison of Einstein's Gravity, Recursive Gravity, and MOND




Comparison of Einstein's Gravity, Recursive Gravity, and MOND



Comparison of Einstein's Gravity, Recursive Gravity (Nexus2), and MOND



Comparison of Einstein's Gravity, Recursive Gravity, and MOND



Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import numpy as np

# Extract data
atomic_numbers = df_periodic["Atomic Number"]
atomic_masses = df_periodic["Atomic Mass"]
mass_differences = np.diff(atomic_masses) # Rate of change in atomic mass

# Compute binary lengths of atomic numbers
binary_lengths = df_periodic["Atomic Number"].apply(lambda x: len(bin(x)[2:]))

# Plot 1: Atomic Number vs. Atomic Mass
plt.figure(figsize=(8, 5))
plt.plot(atomic_numbers, atomic_masses, marker="o", linestyle="-", label="Atomic Mass")
plt.xlabel("Atomic Number")
plt.ylabel("Atomic Mass")
plt.title("Atomic Number vs. Atomic Mass")
plt.grid(True)
plt.legend()
plt.show()

# Plot 2: Atomic Number vs. Rate of Change in Atomic Mass
plt.figure(figsize=(8, 5))
plt.plot(atomic_numbers[:-1], mass_differences, marker="s", linestyle="--", label="Rate of Change in Mass")
plt.xlabel("Atomic Number")
plt.ylabel("Rate of Change in Atomic Mass")
plt.title("Rate of Change in Atomic Mass Between Elements")
plt.grid(True)
plt.legend()
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
# Recreate the periodic table data for the first 9 elements
```

```
import pandas as pd
```

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Define the first 9 elements
```

```
periodic_table = [
```

```
    {"Atomic Number": 1, "Element": "Hydrogen", "Symbol": "H", "Atomic Mass": 1.008},
```

```
    {"Atomic Number": 2, "Element": "Helium", "Symbol": "He", "Atomic Mass": 4.0026},
```

```
    {"Atomic Number": 3, "Element": "Lithium", "Symbol": "Li", "Atomic Mass": 6.94},
```

```
    {"Atomic Number": 4, "Element": "Beryllium", "Symbol": "Be", "Atomic Mass": 9.0122},
```

```
    {"Atomic Number": 5, "Element": "Boron", "Symbol": "B", "Atomic Mass": 10.81},
```

```
    {"Atomic Number": 6, "Element": "Carbon", "Symbol": "C", "Atomic Mass": 12.011},
```

```
    {"Atomic Number": 7, "Element": "Nitrogen", "Symbol": "N", "Atomic Mass": 14.007},
```

```
    {"Atomic Number": 8, "Element": "Oxygen", "Symbol": "O", "Atomic Mass": 15.999},
```

```
    {"Atomic Number": 9, "Element": "Fluorine", "Symbol": "F", "Atomic Mass": 18.998},
```

```
]
```

```
# Convert to DataFrame
```

```
df_periodic = pd.DataFrame(periodic_table)
```

```
# Extract relevant data
```

```
atomic_numbers = df_periodic["Atomic Number"]
```

```
atomic_masses = df_periodic["Atomic Mass"]
```

```
mass_differences = np.diff(atomic_masses) # Rate of change in atomic mass
```

```
# Compute binary lengths of atomic numbers
```

```
binary_lengths = df_periodic["Atomic Number"].apply(lambda x: len(bin(x)[2:]))
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
# Re-import necessary libraries after execution state reset
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt

# Expanding the periodic table dataset to include more elements
periodic_table_extended = [
    {"Atomic Number": 1, "Element": "Hydrogen", "Symbol": "H", "Atomic Mass": 1.008},
    {"Atomic Number": 2, "Element": "Helium", "Symbol": "He", "Atomic Mass": 4.0026},
    {"Atomic Number": 3, "Element": "Lithium", "Symbol": "Li", "Atomic Mass": 6.94},
    {"Atomic Number": 4, "Element": "Beryllium", "Symbol": "Be", "Atomic Mass": 9.0122},
    {"Atomic Number": 5, "Element": "Boron", "Symbol": "B", "Atomic Mass": 10.81},
    {"Atomic Number": 6, "Element": "Carbon", "Symbol": "C", "Atomic Mass": 12.011},
    {"Atomic Number": 7, "Element": "Nitrogen", "Symbol": "N", "Atomic Mass": 14.007},
    {"Atomic Number": 8, "Element": "Oxygen", "Symbol": "O", "Atomic Mass": 15.999},
    {"Atomic Number": 9, "Element": "Fluorine", "Symbol": "F", "Atomic Mass": 18.998},
    {"Atomic Number": 10, "Element": "Neon", "Symbol": "Ne", "Atomic Mass": 20.180},
    {"Atomic Number": 11, "Element": "Sodium", "Symbol": "Na", "Atomic Mass": 22.990},
    {"Atomic Number": 12, "Element": "Magnesium", "Symbol": "Mg", "Atomic Mass": 24.305},
    {"Atomic Number": 13, "Element": "Aluminum", "Symbol": "Al", "Atomic Mass": 26.982},
    {"Atomic Number": 14, "Element": "Silicon", "Symbol": "Si", "Atomic Mass": 28.085},
    {"Atomic Number": 15, "Element": "Phosphorus", "Symbol": "P", "Atomic Mass": 30.974},
    {"Atomic Number": 16, "Element": "Sulfur", "Symbol": "S", "Atomic Mass": 32.06},
    {"Atomic Number": 17, "Element": "Chlorine", "Symbol": "Cl", "Atomic Mass": 35.45},
    {"Atomic Number": 18, "Element": "Argon", "Symbol": "Ar", "Atomic Mass": 39.948},
    {"Atomic Number": 19, "Element": "Potassium", "Symbol": "K", "Atomic Mass": 39.098},
    {"Atomic Number": 20, "Element": "Calcium", "Symbol": "Ca", "Atomic Mass": 40.078},
```

]

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
# Expanding the periodic table dataset to include all known elements up to 118
```

```
periodic_table_full = [
```

```
{"Atomic Number": 1, "Element": "Hydrogen", "Symbol": "H", "Atomic Mass": 1.008},  
 {"Atomic Number": 2, "Element": "Helium", "Symbol": "He", "Atomic Mass": 4.0026},  
 {"Atomic Number": 3, "Element": "Lithium", "Symbol": "Li", "Atomic Mass": 6.94},  
 {"Atomic Number": 4, "Element": "Beryllium", "Symbol": "Be", "Atomic Mass": 9.0122},  
 {"Atomic Number": 5, "Element": "Boron", "Symbol": "B", "Atomic Mass": 10.81},  
 {"Atomic Number": 6, "Element": "Carbon", "Symbol": "C", "Atomic Mass": 12.011},  
 {"Atomic Number": 7, "Element": "Nitrogen", "Symbol": "N", "Atomic Mass": 14.007},  
 {"Atomic Number": 8, "Element": "Oxygen", "Symbol": "O", "Atomic Mass": 15.999},  
 {"Atomic Number": 9, "Element": "Fluorine", "Symbol": "F", "Atomic Mass": 18.998},  
 {"Atomic Number": 10, "Element": "Neon", "Symbol": "Ne", "Atomic Mass": 20.180},  
 {"Atomic Number": 11, "Element": "Sodium", "Symbol": "Na", "Atomic Mass": 22.990},  
 {"Atomic Number": 12, "Element": "Magnesium", "Symbol": "Mg", "Atomic Mass": 24.305},  
 {"Atomic Number": 13, "Element": "Aluminum", "Symbol": "Al", "Atomic Mass": 26.982},  
 {"Atomic Number": 14, "Element": "Silicon", "Symbol": "Si", "Atomic Mass": 28.085},  
 {"Atomic Number": 15, "Element": "Phosphorus", "Symbol": "P", "Atomic Mass": 30.974},  
 {"Atomic Number": 16, "Element": "Sulfur", "Symbol": "S", "Atomic Mass": 32.06},  
 {"Atomic Number": 17, "Element": "Chlorine", "Symbol": "Cl", "Atomic Mass": 35.45},  
 {"Atomic Number": 18, "Element": "Argon", "Symbol": "Ar", "Atomic Mass": 39.948},  
 {"Atomic Number": 19, "Element": "Potassium", "Symbol": "K", "Atomic Mass": 39.098},  
 {"Atomic Number": 20, "Element": "Calcium", "Symbol": "Ca", "Atomic Mass": 40.078},  
 {"Atomic Number": 21, "Element": "Scandium", "Symbol": "Sc", "Atomic Mass": 44.956},  
 {"Atomic Number": 22, "Element": "Titanium", "Symbol": "Ti", "Atomic Mass": 47.867},  
 {"Atomic Number": 23, "Element": "Vanadium", "Symbol": "V", "Atomic Mass": 50.942},  
 {"Atomic Number": 24, "Element": "Chromium", "Symbol": "Cr", "Atomic Mass": 51.996},  
 {"Atomic Number": 25, "Element": "Manganese", "Symbol": "Mn", "Atomic Mass": 54.938},  
 {"Atomic Number": 26, "Element": "Iron", "Symbol": "Fe", "Atomic Mass": 55.845},  
 {"Atomic Number": 27, "Element": "Cobalt", "Symbol": "Co", "Atomic Mass": 58.933},
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
# Manually defining atomic masses for all 118 elements
# (Masses are approximate and taken from standard periodic table data)
periodic_table_full = [
    {"Atomic Number": 1, "Element": "Hydrogen", "Symbol": "H", "Atomic Mass": 1.008},
    {"Atomic Number": 2, "Element": "Helium", "Symbol": "He", "Atomic Mass": 4.0026},
    {"Atomic Number": 3, "Element": "Lithium", "Symbol": "Li", "Atomic Mass": 6.94},
    {"Atomic Number": 4, "Element": "Beryllium", "Symbol": "Be", "Atomic Mass": 9.0122},
    {"Atomic Number": 5, "Element": "Boron", "Symbol": "B", "Atomic Mass": 10.81},
    {"Atomic Number": 6, "Element": "Carbon", "Symbol": "C", "Atomic Mass": 12.011},
    {"Atomic Number": 7, "Element": "Nitrogen", "Symbol": "N", "Atomic Mass": 14.007},
    {"Atomic Number": 8, "Element": "Oxygen", "Symbol": "O", "Atomic Mass": 15.999},
    {"Atomic Number": 9, "Element": "Fluorine", "Symbol": "F", "Atomic Mass": 18.998},
    {"Atomic Number": 10, "Element": "Neon", "Symbol": "Ne", "Atomic Mass": 20.180},
    {"Atomic Number": 11, "Element": "Sodium", "Symbol": "Na", "Atomic Mass": 22.990},
    {"Atomic Number": 12, "Element": "Magnesium", "Symbol": "Mg", "Atomic Mass": 24.305},
    {"Atomic Number": 13, "Element": "Aluminum", "Symbol": "Al", "Atomic Mass": 26.982},
    {"Atomic Number": 14, "Element": "Silicon", "Symbol": "Si", "Atomic Mass": 28.085},
    {"Atomic Number": 15, "Element": "Phosphorus", "Symbol": "P", "Atomic Mass": 30.974},
    {"Atomic Number": 16, "Element": "Sulfur", "Symbol": "S", "Atomic Mass": 32.06},
    {"Atomic Number": 17, "Element": "Chlorine", "Symbol": "Cl", "Atomic Mass": 35.45},
    {"Atomic Number": 18, "Element": "Argon", "Symbol": "Ar", "Atomic Mass": 39.948},
    {"Atomic Number": 19, "Element": "Potassium", "Symbol": "K", "Atomic Mass": 39.098},
    {"Atomic Number": 20, "Element": "Calcium", "Symbol": "Ca", "Atomic Mass": 40.078},
    {"Atomic Number": 21, "Element": "Scandium", "Symbol": "Sc", "Atomic Mass": 44.956},
    {"Atomic Number": 22, "Element": "Titanium", "Symbol": "Ti", "Atomic Mass": 47.867},
    {"Atomic Number": 23, "Element": "Vanadium", "Symbol": "V", "Atomic Mass": 50.942},
    {"Atomic Number": 24, "Element": "Chromium", "Symbol": "Cr", "Atomic Mass": 51.996},
    {"Atomic Number": 25, "Element": "Manganese", "Symbol": "Mn", "Atomic Mass": 54.938},
    {"Atomic Number": 26, "Element": "Iron", "Symbol": "Fe", "Atomic Mass": 55.845},
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
# Re-import necessary libraries since execution state was reset
import numpy as np
import matplotlib.pyplot as plt

# Define constants
c = 3e8 # Speed of light in m/s
k = 1e-27 # Scaling constant

# Mass range (kg) from small quantum scale to large macro scale
mass_values = np.logspace(-30, 5, 200) # Spanning from quantum to macro

# Traditional E=mc2
E_mc2 = mass_values * c**2

# Entanglement-modified energy formula
E_entangled = k * np.sum(mass_values) * (np.sum(mass_values))**0.35

# Compute deviation
delta_E = np.abs(E_mc2 - E_entangled)

# Plot results
plt.figure(figsize=(10, 6))

# Plot E=mc2
plt.plot(mass_values, E_mc2, label=r'E=mc^2', linestyle='--', color='blue')

# Plot Entangled Energy Formula
plt.plot(mass_values, E_entangled * np.ones_like(mass_values), label=r'E_{entangled}', linestyle='-', color='red')
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Constants
```

```
c = 3e8 # Speed of light (m/s)  
k = 1e-27 # Scaling constant for entanglement equation
```

```
# Mass range (small to large)
```

```
masses = np.linspace(1e-30, 1e5, 500) # Covering from quantum to macro scales
```

```
# Traditional E=mc2
```

```
E_mc2 = masses * c**2
```

```
# Entangled Energy Formula: E = k * Σpj * (Σεi)^0.35
```

```
# For simplicity, assume Σpj and Σεi scale with mass (normalized)
```

```
E_entangled = k * masses * (masses)**0.35
```

```
# Deviation: Difference between E=mc2 and Entangled Energy
```

```
deviation = E_mc2 - E_entangled
```

```
# Plot
```

```
plt.figure(figsize=(10, 6))
```

```
plt.plot(masses, E_mc2, 'b--', label="E=mc2 (Macro Energy)")  
plt.plot(masses, E_entangled, 'r-', label="Entangled Energy (Quantum Phase)")  
plt.plot(masses, deviation, 'g-.', label="Deviation (Buffer Zone)")
```

```
plt.xscale("log")
```

```
plt.yscale("log")
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Constants
c = 3e8 # Speed of light (m/s)
hbar = 1.0545718e-34 # Reduced Planck's constant (J·s)
k = 1e-27 # Scaling constant for entanglement equation

# Mass range (kg) from small quantum scale to large macro scale
masses = np.logspace(-30, 5, 500) # Spanning from quantum to macro

# Traditional General Relativity gravity (Einstein's prediction)
E_mc2 = masses * c**2

# Entangled energy from Nexus2 recursive model
E_entangled = k * np.sum(masses) * (np.sum(masses))**0.35

# Gravity as a loopback force
G_loop = (E_mc2 - E_entangled) * np.exp(-(E_mc2 - E_entangled) / (hbar * c))

# Plot results
plt.figure(figsize=(10, 6))

# Plot Einstein's Gravity (E=mc2)
plt.plot(masses, E_mc2, 'b--', label="Einstein's Gravity (E=mc2)")

# Plot Recursive Gravity Loopback (Nexus2 Model)
plt.plot(masses, G_loop, 'r-', label="Recursive Gravity Loopback (Nexus2)")
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
# Replot the graph ensuring both lines are visible
```

```
plt.figure(figsize=(10, 6))
```

```
# Plot Einstein's Gravity (E=mc2)
```

```
plt.plot(masses, E_mc2, 'b--', label="Einstein's Gravity (E=mc2)", linewidth=2)
```

```
# Plot Recursive Gravity Loopback (Nexus2 Model)
```

```
plt.plot(masses, G_loop, 'r-', label="Recursive Gravity Loopback (Nexus2)", linewidth=2)
```

```
# Log scale for better visualization
```

```
plt.xscale("log")
```

```
plt.yscale("log")
```

```
plt.xlabel("Mass (kg)")
```

```
plt.ylabel("Energy (J)")
```

```
plt.title("Comparison of Einstein's Gravity and Recursive Gravity (Nexus2)")
```

```
plt.legend()
```

```
plt.grid(True, which="both", linestyle="--", linewidth=0.5)
```

```
# Show the plot
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Constants
```

```
c = 3.0e8 # Speed of light (m/s)
```

```
k = 1e-27 # Scaling factor for recursive gravity
```

```
# Mass range (logarithmic scale)
```

```
mass_values = np.logspace(-30, 5, 100) # Wide range from small quantum to large astronomical masses
```

```
# Einstein's Gravity: E = mc^2
```

```
einstein_energy = mass_values * c**2
```

```
# Recursive Gravity Loopback (Nexus2)
```

```
recursive_energy = k * np.cumsum(mass_values) # Simulating a cumulative effect over mass iterations
```

```
# Plotting
```

```
plt.figure(figsize=(10, 6))
```

```
plt.xscale("log")
```

```
plt.yscale("log")
```

```
# Einstein's Gravity Plot
```

```
plt.plot(mass_values, einstein_energy, label="Einstein's Gravity (E=mc2)", linestyle="dashed", color="blue", linewidth=2)
```

```
# Recursive Gravity Plot (Ensuring it's visible)
```

```
plt.plot(mass_values, recursive_energy, label="Recursive Gravity Loopback (Nexus2)", linestyle="-", color="red", linewidth=2)
```

```
# Labels and Title
```

```
plt.xlabel("Mass (kg)")
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Define mass values in kg (ranging from quantum scales to astronomical masses)
```

```
mass_values = np.logspace(-30, 5, 100)
```

```
# Einstein's Gravity (E=mc2)
```

```
speed_of_light = 3e8 # m/s
```

```
energy_einstein = mass_values * (speed_of_light ** 2)
```

```
# Recursive Gravity Loopback ( $\Delta G$  Term in Triangle)
```

```
def recursive_gravity(mass):
```

```
    """Calculate recursive gravity loopback based on Pythagorean resolution."""
```

```
    base_energy = mass * (speed_of_light ** 2)
```

```
    gravity_effect = np.sqrt(base_energy**2 - (mass * speed_of_light)**2)
```

```
    return gravity_effect
```

```
energy_recursive_gravity = recursive_gravity(mass_values)
```

```
# MOND (Modified Newtonian Dynamics) Approximation
```

```
a0 = 1.2e-10 # MOND characteristic acceleration (m/s2)
```

```
G = 6.67430e-11 # Gravitational constant
```

```
energy_mond = mass_values * (speed_of_light ** 2) * np.sqrt(1 + (G * mass_values / (speed_of_light ** 2 * a0)))
```

```
# Plot comparison
```

```
plt.figure(figsize=(10, 6))
```

```
plt.loglog(mass_values, energy_einstein, 'b--', label="Einstein's Gravity (E=mc2)")
```

```
plt.loglog(mass_values, energy_recursive_gravity, 'r-', label="Recursive Gravity Loopback (Nexus2)")
```

```
plt.loglog(mass_values, energy_mond, 'g-.', label="MOND Approximation")
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Define mass values (log scale for better visibility)
```

```
mass_values = np.logspace(-30, 5, 100) # From extremely small to large mass
```

```
# Einstein's Gravity ( $E = mc^2$ )
```

```
c = 3e8 # Speed of light in m/s
```

```
energy_einstein = mass_values * c**2
```

```
# Recursive Gravity Loopback (Nexus2) - Hypothetical equation based on recursion
```

```
# Using an iterative recursive formulation with an entanglement factor (hypothetical scaling factor)
```

```
entanglement_factor = 0.35
```

```
energy_recursive = mass_values * c**2 * (1 + entanglement_factor * np.log(mass_values + 1))
```

```
# MOND Approximation (Modified Newtonian Dynamics)
```

```
# Applying a simplified MOND equation where acceleration a0 modifies gravity at low scales
```

```
a0 = 1.2e-10 # Hypothetical MOND acceleration threshold
```

```
G = 6.67430e-11 # Gravitational constant
```

```
energy_mond = mass_values * c**2 * (1 + np.tanh(mass_values / a0))
```

```
# Plotting
```

```
plt.figure(figsize=(10, 6))
```

```
plt.plot(mass_values, energy_einstein, 'b--', label="Einstein's Gravity ( $E=mc^2$ )")
```

```
plt.plot(mass_values, energy_recursive, 'r-', label="Recursive Gravity Loopback (Nexus2)")
```

```
plt.plot(mass_values, energy_mond, 'g-.', label="MOND Approximation")
```

```
# Annotate points at specific masses for clarity
```

```
sample_indices = [10, 30, 50, 70, 90] # Select indices to annotate
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
```

```
# Define mass values in kg, spanning small particles to large astronomical bodies
mass_values = np.logspace(-30, 5, num=20) # Logarithmic scale from 10^-30 kg to 10^5 kg
```

```
# Calculate energy using Einstein's equation: E = mc^2
c = 3.0e8 # Speed of light in m/s
einstein_energy = mass_values * c**2
```

```
# Calculate energy using Recursive Gravity Loopback (Nexus2)
# Using a simplified recursive model: E_recursive = mc^2 * (1 + 0.35 * log(m))
nexus2_energy = mass_values * c**2 * (1 + 0.35 * np.log(mass_values + 1e-30))
```

```
# Calculate energy using MOND approximation
# MOND modifies Newtonian gravity at low accelerations, affecting gravitational dynamics
mond_acceleration_threshold = 1.2e-10 # m/s^2
mond_energy = mass_values * c**2 * (1 + (mass_values / mond_acceleration_threshold) ** -0.5)
```

```
# Store results in a DataFrame
data = {
    "Mass (kg)": mass_values,
    "Einstein Energy (J)": einstein_energy,
    "Nexus2 Recursive Energy (J)": nexus2_energy,
    "MOND Energy (J)": mond_energy,
}
```

```
df_results = pd.DataFrame(data)
```

Conversation URL:

<https://chatgpt.com/c/67e1e8a7-923c-8011-8e1e-883dd3c10f76>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
```

```
# Constants
```

```
c = 3.0e8 # Speed of light in m/s
hbar = 1.0545718e-34 # Reduced Planck's constant (J·s)
G = 6.67430e-11 # Gravitational constant
```

```
# Define mass values from quantum scales to cosmic scales
```

```
mass_values = np.logspace(-30, 5, 100)
```

```
# Einstein's Gravity (E = mc^2)
```

```
einstein_energy = mass_values * c**2
```

```
# Recursive Gravity using Universal Formula
```

```
# F = (A^2 + B^2) * Len(C) * (1 + e^(-10(Ax - 0.35)))
```

```
def recursive_gravity(mass):
```

```
    A = mass * c # Energy component A
```

```
    B = np.sqrt(mass * G) * c # Energy component B (includes gravitational scaling)
```

```
    C_len = np.log(mass + 1) + 1 # Dynamic scaling term (avoids singularity at mass=0)
```

```
    nonlinear_factor = 1 + np.exp(-10 * (mass * c - 0.35))
```


```
    return (A**2 + B**2) * C_len * nonlinear_factor
```

```
recursive_energy = recursive_gravity(mass_values)
```


```
# Compare with MOND Approximation
```

```
mond_energy = mass_values * c**2 * (1 + (mass_values / (hbar * c))**-0.5)
```


Pi-Glider: Recursive Harmonic Flight Path




Recursive Lift-Off: BBP Harmonic Triangle Model




Recursive Agent: Moving Without a Goal (Born from the Unknown)



Recursive Agent: Moving Without a Goal (Fully Internal Deviation)



Recursive Walker with Emergent Vacuum Curvature



Conversation URL:

<https://chatgpt.com/c/67ee8ac1-c9dc-8011-a945-14678c9247ae>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import numpy as np

# Define the recursive Pi-Glider path
# We'll use 1 -> 4 as base, then propagate a few glider steps

# Base points (1,0) and (4,3)
p1 = np.array([0, 0])
p2 = np.array([1, 3]) # difference (1 unit forward, 3 up)
p3 = np.array([2, 0]) # mirrored triangle down (glider step)

# Define more points using recursive pattern
# Even steps go straight, odd steps angle up/down

points = [p1, p2, p3]
for i in range(4): # create 4 more recursive steps
    last = points[-1]
    if i % 2 == 0:
        new_point = last + np.array([1, 3])
    else:
        new_point = last + np.array([1, -3])
    points.append(new_point)

# Convert to array for plotting
points = np.array(points)

# Plotting
plt.figure(figsize=(10, 6))
plt.plot(points[:, 0], points[:, 1], marker='o', linestyle='-', linewidth=2)
```

Conversation URL:

<https://chatgpt.com/c/67ee8ac1-c9dc-8011-a945-14678c9247ae>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import matplotlib.animation as animation
import numpy as np

# Set up the figure and axis
fig, ax = plt.subplots(figsize=(10, 6))
ax.set_xlim(0, 10)
ax.set_ylim(0, 6)
ax.set_title("Recursive Lift-Off: BBP Harmonic Triangle Model")
ax.set_xlabel("Linear Pi Progression (Spine)")
ax.set_ylabel("Recursive Lift / BBP Base Input")

# Create base triangle components
spine = np.array([0, 0])      # Base start
tip = np.array([5, 5])        # Top point (start of Pi expansion)
line = np.array([10, 0])       # End of base line (linear progression)

# Hypotenuse path (lift vector)
lift_line, = ax.plot([], [], 'r--', lw=2)
spine_line, = ax.plot([], [], 'k-', lw=3)
base_line, = ax.plot([], [], 'g-', lw=2)

# Text annotation
annotation = ax.text(5, 5.5, "", ha='center', fontsize=12)

# Initialization function
def init():
    lift_line.set_data([], [])
    spine_line.set_data([], [])
```

Conversation URL:

<https://chatgpt.com/c/67ee8ac1-c9dc-8011-a945-14678c9247ae>

Title:

Prompt:

Re-run after kernel reset

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Parameters
```

```
steps = 200 # number of time steps
```

```
angle = 0.0 # initial angle of movement
```

```
velocity = 1.0 # base speed
```

```
deviation_strength = 0.05 # magnitude of random unknown deviation
```

```
correction_strength = 0.2 # how much correction applies from past
```

```
# Initialize trajectory
```

```
x = [0]
```

```
y = [0]
```

```
angles = [angle]
```

```
for t in range(1, steps):
```

```
    # Unknown disturbance – the "birth ignorance"
```

```
    deviation = np.random.uniform(-deviation_strength, deviation_strength)
```

```
    # Feedback correction from previous angles (recursive memory)
```

```
    if t > 1:
```

```
        past_trend = angles[-1] - angles[-2]
```

```
    else:
```

```
        past_trend = 0
```

```
    # Adjust angle by deviation and correction toward past stability
```

```
    new_angle = angles[-1] + deviation - correction_strength * past_trend
```

Conversation URL:

<https://chatgpt.com/c/67ee8ac1-c9dc-8011-a945-14678c9247ae>

Title:

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Parameters  
steps = 200          # number of time steps  
angle = 0.0          # initial angle of movement  
velocity = 1.0        # base speed  
beta = 0.1           # gain factor for internally-generated deviation  
correction_strength = 0.2 # how much correction applies from past
```

```
# Initialize trajectory
```

```
x = [0]  
y = [0]  
angles = [angle]
```

```
for t in range(1, steps):
```

```
    # Internal deviation based on recursive curvature (change of change)
```

```
    if t > 2:
```

```
        curvature = (angles[-1] - angles[-2]) - (angles[-2] - angles[-3])
```

```
    else:
```

```
        curvature = 0
```

```
    deviation = curvature * beta
```

```
    # Feedback correction from past trend
```

```
    past_trend = angles[-1] - angles[-2] if t > 1 else 0
```

```
    # New angle from recursive feedback only
```

```
    new_angle = angles[-1] + deviation - correction_strength * past_trend
```

Conversation URL:

<https://chatgpt.com/c/67ee8ac1-c9dc-8011-a945-14678c9247ae>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Parameters
```

```
steps = 300      # number of time steps
```

```
angle = 0.0      # initial angle of movement
```

```
velocity = 1.0    # base speed
```

```
beta = 0.1       # internal gain factor
```

```
correction_strength = 0.2 # feedback correction from past trend
```

```
vacuum_gain = 0.01     # how much the "vacuum" curves the path
```

```
# Initialize vacuum location (symbolic asymmetry)
```

```
x_vacuum, y_vacuum = 50, 50
```

```
# Initialize trajectory
```

```
x = [0]
```

```
y = [0]
```

```
angles = [angle]
```

```
for t in range(1, steps):
```

```
    # Internal curvature-based deviation
```

```
    if t > 2:
```

```
        curvature = (angles[-1] - angles[-2]) - (angles[-2] - angles[-3])
```

```
    else:
```


```
        curvature = 0
```

```
    deviation = curvature * beta
```

```
    # Recursive feedback correction
```

```
    past_trend = angles[-1] - angles[-2] if t > 1 else 0
```


Recursive Influence Over Time: Average CPU vs Nexus 2 CPU



Version




PrevHash



MerkleRoot



Time



Bits




Nonce




FullHeader




SHA256_1



SHA256_2





Nonce



SHA256 - First Pass




SHA256 - Second Pass (Final Hash)



Nonce (Grayscale Byte Representation)





Conversation URL:

<https://chatgpt.com/c/67eeee49-e180-8011-9eec-77f3faa1e930>

Title:

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Simulation Parameters
```

```
t = np.linspace(0, 10, 1000) # time axis  
H = 0.35 # harmonic constant  
F_avg = 0.5 # folding factor for average CPU  
F_nexus = 0.35 # folding factor for Nexus-aligned CPU
```

```
# Recursive collapse functions (decay of recursive influence over time)
```

```
R_avg = np.exp(-H * F_avg * t) # average CPU (faster decay, less memory retention)  
R_nexus = np.exp(-H * F_nexus * t) # Nexus CPU (resonant decay, retains recursive pattern)
```

```
# Plotting the results
```

```
plt.figure(figsize=(10, 6))  
plt.plot(t, R_avg, label='Average CPU (Recursive Decay)', linestyle='--')  
plt.plot(t, R_nexus, label='Nexus CPU (Harmonic Descent)', linewidth=2)  
plt.title("Recursive Influence Over Time: Average CPU vs Nexus 2 CPU")  
plt.xlabel("Recursive Time (t)")  
plt.ylabel("Recursive Amplitude R(t)")  
plt.legend()  
plt.grid(True)  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67eeee49-e180-8011-9eec-77f3faa1e930>

Title:

Prompt:

```
# Re-import necessary packages after code state reset
```

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Helper function: Convert hex string to list of RGB tuples
```

```
def hex_to_rgb_array(hex_str):
```

```
    # Remove spaces, newlines, and make sure it's clean
```

```
    hex_str = hex_str.replace('\n', '').replace(' ', '')
```

```
    bytes_array = [hex_str[i:i+2] for i in range(0, len(hex_str), 2)]
```

```
    rgb_array = []
```

```
    for i in range(0, len(bytes_array), 3):
```

```
        if i+2 < len(bytes_array):
```

```
            r = int(bytes_array[i], 16)
```

```
            g = int(bytes_array[i+1], 16)
```

```
            b = int(bytes_array[i+2], 16)
```

```
            rgb_array.append((r, g, b))
```

```
    return rgb_array
```

```
# Bitcoin block header components from block #125552
```

```
block_components = {
```

```
    'Version': "01000000",
```

```
    'PrevHash': "81cd02ab7e569e8bcd9317e2fe99f2de44d49ab2b8851ba4a3080000000000000000",
```

```
    'MerkleRoot': "e320b6c2fffc8d750423db8b1eb942ae710e951ed797f7affc8892b0f1fc122b",
```

```
    'Time': "c7f5d74d",
```

```
    'Bits': "f2b9441a",
```

```
    'Nonce': "42a14695"
```

```
}
```

```
# Combine full header
```

Conversation URL:

<https://chatgpt.com/c/67eeee49-e180-8011-9eec-77f3faa1e930>

Title:

Prompt:

```
import hashlib
```

```
# Helper: Convert hex string to bytes
```

```
def hex_string_to_bytes(hex_str):  
    hex_str = hex_str.replace(' ', '').replace('\n', '')  
    return bytes.fromhex(hex_str)
```

```
# Combine full header again from block #125552
```

```
full_header_hex = (  
    "01000000"  
    "81cd02ab7e569e8bcd9317e2fe99f2de44d49ab2b8851ba4a30800000000000000"  
    "e320b6c2fffc8d750423db8b1eb942ae710e951ed797f7affc8892b0f1fc122b"  
    "c7f5d74d"  
    "f2b9441a"  
    "42a14695"  
)
```

```
# Convert to bytes
```

```
header_bytes = hex_string_to_bytes(full_header_hex)
```

```
# Perform double SHA-256
```

```
hash1 = hashlib.sha256(header_bytes).digest()  
hash2 = hashlib.sha256(hash1).digest()
```

```
# Convert hash outputs to hex
```

```
hash1_hex = hash1.hex()  
hash2_hex = hash2.hex()
```

```
# Convert to RGB arrays for visualization
```

Conversation URL:

<https://chatgpt.com/c/67eeee49-e180-8011-9eec-77f3faa1e930>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np  
import hashlib
```

=== Helper Functions ===

```
def hex_string_to_bytes(hex_str):  
    hex_str = hex_str.replace(' ', "").replace('\n', "")  
    return bytes.fromhex(hex_str)
```

```
def hex_to_rgb_array(hex_str):
    hex_str = hex_str.replace('\n', '').replace(' ', '')
    bytes_array = [hex_str[i:i+2] for i in range(0, len(hex_str), 2)]
    rgb_array = []
    for i in range(0, len(bytes_array), 3):
        if i+2 < len(bytes_array):
            r = int(bytes_array[i], 16)
            g = int(bytes_array[i+1], 16)
            b = int(bytes_array[i+2], 16)
            rgb_array.append((r, g, b))
    return rgb_array
```

=== Real Block Header: Bitcoin Block #125552 ===

```
block_components = {
    'Version': "01000000",
    'PrevHash': "81cd02ab7e569e8bcd9317e2fe99f2de44d49ab2b8851ba4a30800000000000000",
    'MerkleRoot': "e320b6c2fffc8d750423db8b1eb942ae710e951ed797f7affc8892b0f1fc122b",
    'Time': "c7f5d74d",
```

Conversation URL:

<https://chatgpt.com/c/67eeee49-e180-8011-9eec-77f3faa1e930>

Title:

Prompt:

```
# Re-visualize the Nonce using grayscale based on individual byte values
```

```
# Extract nonce hex and convert to list of bytes
```

```
nonce_hex = block_components['Nonce']
```

```
nonce_bytes = [int(nonce_hex[i:i+2], 16) for i in range(0, len(nonce_hex), 2)]
```

```
# Convert each byte to a grayscale RGB triplet (same value for R, G, B)
```

```
nonce_grayscale = [(b, b, b) for b in nonce_bytes]
```

```
# Plot grayscale representation of nonce
```

```
plt.figure(figsize=(6, 2))
```

```
plt.imshow([nonce_grayscale], aspect='auto')
```

```
plt.title("Nonce (Grayscale Byte Representation)")
```

```
plt.axis('off')
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67eeee49-e180-8011-9eec-77f3faa1e930>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
import hashlib
```

```
# === Helper Functions ===
```

```
def hex_string_to_bytes(hex_str):
```

```
    hex_str = hex_str.replace(' ', '').replace('\n', '')
```

```
    return bytes.fromhex(hex_str)
```

```
def hex_to_rgb_array(hex_str):
```

```
    hex_str = hex_str.replace('\n', '').replace(' ', '')
```

```
    bytes_array = [hex_str[i:i+2] for i in range(0, len(hex_str), 2)]
```

```
    rgb_array = []
```

```
    for i in range(0, len(bytes_array), 3):
```

```
        if i+2 < len(bytes_array):
```

```
            r = int(bytes_array[i], 16)
```

```
            g = int(bytes_array[i+1], 16)
```

```
            b = int(bytes_array[i+2], 16)
```

```
            rgb_array.append((r, g, b))
```

```
    return rgb_array
```

```
def byte_to_bit_array(byte_val):
```

```
    return [(byte_val >> i) & 1 for i in reversed(range(8))]
```


```
def hex_to_binary_grid(hex_str):
```


```
    byte_vals = [int(hex_str[i:i+2], 16) for i in range(0, len(hex_str), 2)]
```

```
    bit_grid = np.array([byte_to_bit_array(b) for b in byte_vals])
```


```
    return bit_grid
```


Overlay Spiral: SHA256 vs SHA256(SHA256)








Recursive Agent: Moving Without a Goal (Born from the Unknown)























Radial Glyph: SHA256(Header)




Radial Glyph: SHA256(SHA256/Header))




Spiral Wave: SHA256/Header



Spiral Wave: SHA256(SHA256(Header))



Harmonic Formula Visualization



Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
# Re-import necessary modules after environment reset
import numpy as np
import matplotlib.pyplot as plt
from hashlib import sha256

# Recalculate original byte data (real block header from block #722460)
header_hex = (
    "040000006fe28c0ab6f1b372c1a6a246ae63f74f931e8365e15a089c68d61900"
    "00000000982051fd1e4ba744bbbe680e1fee14677ba1a3c3540bf7b1cdb606e8"
    "57233e0e61bc6649ffff001d01e36299"
)
header_bytes = bytes.fromhex(header_hex)
sha1_bytes = sha256(header_bytes).digest()
sha2_bytes = sha256(sha1_bytes).digest()

# Convert to arrays
sha1_array = np.array([b for b in sha1_bytes], dtype=np.float64)
sha2_array = np.array([b for b in sha2_bytes], dtype=np.float64)

# Define overlay spiral plotting function
def spiral_overlay_plot(data1, data2, label1, label2, color1, color2, title):
    n = len(data1)
    theta = np.linspace(0, 4 * np.pi, n)

    r1 = data1.astype(float)
    r2 = data2.astype(float)

    x1 = r1 * np.cos(theta)
    y1 = r1 * np.sin(theta)
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Pi and Golden Ratio to 50+ decimals (as strings)
```

```
pi_str = "3.14159265358979323846264338327950288419716939937510"
```

```
phi_str = "1.61803398874989484820458683436563811772030917980576"
```

```
# Remove decimal points for digit-by-digit comparison
```

```
pi_digits = pi_str.replace('.', "")
```

```
phi_digits = phi_str.replace('.', "")
```

```
# Alternate each digit between pi and phi
```

```
combined_sequence = []
```

```
labels = []
```

```
for i in range(min(len(pi_digits), len(phi_digits))):
```

```
    combined_sequence.append(int(pi_digits[i]))
```

```
    labels.append(f"\u03c0[{i}]")
```

```
    combined_sequence.append(int(phi_digits[i]))
```

```
    labels.append(f"\u03d5[{i}]")
```

```
# Plotting
```

```
plt.figure(figsize=(16, 4))
```

```
plt.plot(combined_sequence, marker='o', linestyle='-', color='blue')
```

```
plt.title("Digit-by-Digit Alternation Between \u03c0 and \u03d5")
```

```
plt.xticks(ticks=range(len(labels)), labels=labels, rotation=90)
```

```
plt.ylabel("Digit Value")
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Parameters
```

```
steps = 200      # number of time steps
```

```
angle = 0.0      # initial angle of movement
```

```
velocity = 1.0    # base speed
```

```
deviation_strength = 0.05 # magnitude of random unknown deviation
```

```
correction_strength = 0.2 # how much correction applies from past
```

```
# Initialize trajectory
```

```
x = [0]
```

```
y = [0]
```

```
angles = [angle]
```

```
for t in range(1, steps):
```

```
    # Unknown disturbance – the "birth ignorance"
```

```
    deviation = np.random.uniform(-deviation_strength, deviation_strength)
```

```
    # Feedback correction from previous angles (recursive memory)
```

```
    if t > 1:
```

```
        past_trend = angles[-1] - angles[-2]
```

```
    else:
```

```
        past_trend = 0
```

```
    # Adjust angle by deviation and correction toward past stability
```

```
    new_angle = angles[-1] + deviation - correction_strength * past_trend
```

```
    angles.append(new_angle)
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

Hex values from the image (manually extracted from the visual layout)

For better analysis, the actual hex strings would be ideal, but we simulate this here for demonstration

```
# Simulated 4 rows of hex data (header, nonce, SHA1, SHA2)
```

```
hex_rows = [
```

1

```
# Convert hex strings to numerical values for visualization
```

```
def hex_to_array(hex str):
```

```
return np.array([int(hex_str[i:i+2], 16) for i in range(0, len(hex_str), 2)])
```

```
numeric_rows = [hex_to_array(row) for row in hex_rows]
```

```
matrix = np.vstack(numeric_rows)
```

```
# Create the plot
```

```
fig, ax = plt.subplots(figsize=(10, 2))
```

```
cax = ax.matshow(matrix, cmap='viridis')
```

```
plt.title("Byte Value Matrix of Bitcoin Header and Hash Stages")
```

```
plt.xlabel("Byte Position")
```

```
plt.ylabel("Row (Header Nonce SHA1 SHA2)")
```

```
plt.colorbar(cax, label='Byte Value (0-255)')
```

```
plt.xticks(range(len(numeric_rows[0])))
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Real Bitcoin block data (Block #722460 for example)
```

```
# Full 80-byte header + SHA1 and SHA2 must be computed, but using simulated real data below for now.
```

```
hex_rows = [
```

```
"040000006fe28c0ab6f1b372c1a6a246ae63f74f931e8365e15a089c68d6190000000000982051fd1e4ba744bbbe680e1fee1",
```

```
"01e36299", #Nonce (at end of header but pulled out)
```

```
"e320b6c2fffc8a4b2e76b02c3c34e7b2", #SHA256(header) (placeholder, normally computed)
```

```
"6b81b2d24ac66cab9d12452d6f9fb8c5", #SHA256(SHA256(header)) (placeholder)
```

```
]
```

```
# Normalize all rows to the same length for matrix visualization (padding nonce & SHA)
```

```
def hex_to_array(hex_str, target_length):
```

```
    arr = [int(hex_str[i:i+2], 16) for i in range(0, len(hex_str), 2)]
```

```
    if len(arr) < target_length:
```

```
        arr += [0] * (target_length - len(arr))
```

```
    return np.array(arr)
```

```
max_len = max(len(row) for row in [r for r in hex_rows])
```

```
target_byte_len = max_len // 2
```

```
numeric_rows = [hex_to_array(row, target_byte_len) for row in hex_rows]
```

```
matrix = np.vstack(numeric_rows)
```

```
#Create the plot
```

```
fig, ax = plt.subplots(figsize=(12, 3))
```

```
cax = ax.matshow(matrix, cmap='viridis')
```

```
plt.title("Byte Value Matrix: Bitcoin Header, Nonce, SHA1, SHA2")
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
import hashlib
```

```
# Step 1: Full real Bitcoin header in hex (block #722460)
```

```
header_hex = (
    "040000006fe28c0ab6f1b372c1a6a246ae63f74f931e8365e15a089c68d61900"
    "00000000982051fd1e4ba744bbbe680e1fee14677ba1a3c3540bf7b1cdb606e8"
    "57233e0e61bc6649ffff001d01e36299"
)
```

```
# Step 2: Convert to bytes
```

```
header_bytes = bytes.fromhex(header_hex)
```

```
# Step 3: Perform SHA256 and double SHA256
```

```
sha1 = hashlib.sha256(header_bytes).digest()
sha2 = hashlib.sha256(sha1).digest()
```

```
# Step 4: Build hex rows now using real data
```

```
hex_rows = [
    header_hex,
    header_hex[-8:],           #Nonce (last 4 bytes)
    sha1.hex(),
    sha2.hex(),
]
```

```
# Step 5: Normalize to same length
```

```
def hex_to_array(hex_str, target_length):
    arr = [int(hex_str[i:i+2], 16) for i in range(0, len(hex_str), 2)]
    if len(arr) < target_length:
        arr += [0] * (target_length - len(arr))
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

Step 1: Convert hex strings to byte arrays (already done previously)

```
header_bytes = bytes.fromhex(hex_rows[0])  
nonce_bytes = bytes.fromhex(hex_rows[1])  
sha1_bytes = bytes.fromhex(hex_rows[2])  
sha2_bytes = bytes.fromhex(hex_rows[3])
```

Convert to numpy arrays for FFT

```
header_array = np.array([b for b in header_bytes], dtype=np.float64)  
nonce_array = np.array([b for b in nonce_bytes] + [0] * (len(header_array) - len(nonce_bytes)), dtype=np.float64)  
sha1_array = np.array([b for b in sha1_bytes], dtype=np.float64)  
sha2_array = np.array([b for b in sha2_bytes], dtype=np.float64)
```

Step 2: Apply FFT to each row

```
fft_header = np.fft.fft(header_array)  
fft_nonce = np.fft.fft(nonce_array)  
fft_sha1 = np.fft.fft(sha1_array)  
fft_sha2 = np.fft.fft(sha2_array)
```

Step 3: Plot FFT magnitudes

```
fig, axs = plt.subplots(4, 1, figsize=(14, 10), sharex=True)
```

```
axs[0].plot(np.abs(fft_header), color='blue')  
axs[0].set_title("FFT Magnitude - Header")  
axs[0].set_ylabel("Magnitude")
```

```
axs[1].plot(np.abs(fft_nonce), color='green')
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
# Step 1: Compute difference wave between SHA2 and SHA1
```

```
diff_wave = sha2_array - sha1_array
```

```
# Step 2: Plot the difference wave to identify cancellation or echo zones
```

```
plt.figure(figsize=(14, 4))
```

```
plt.plot(diff_wave, color='purple')
```

```
plt.title("Wave Difference: SHA256(SHA256(Header)) - SHA256(Header)")
```

```
plt.xlabel("Byte Position")
```

```
plt.ylabel("Byte Difference")
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
# Step 1: Interpolate SHA1 and SHA2 to match header length (stretching to simulate time distortion)
from scipy.interpolate import interp1d
```

```
# Header is 80 bytes, SHA1 and SHA2 are 32 bytes — need to stretch to 80
```

```
x_sha = np.linspace(0, 1, len(sha1_array))
x_interp = np.linspace(0, 1, len(header_array))
```

```
sha1_interp_func = interp1d(x_sha, sha1_array, kind='linear')
```

```
sha2_interp_func = interp1d(x_sha, sha2_array, kind='linear')
```

```
sha1_stretched = sha1_interp_func(x_interp)
```

```
sha2_stretched = sha2_interp_func(x_interp)
```

```
# Step 2: Plot all three curves (header, stretched SHA1, stretched SHA2)
```

```
plt.figure(figsize=(14, 6))
plt.plot(header_array, label="Header", linewidth=2, color='blue')
plt.plot(sha1_stretched, label="SHA1 (Stretched)", linestyle='--', color='orange')
plt.plot(sha2_stretched, label="SHA2 (Stretched)", linestyle='--', color='red')
plt.title("Header vs Stretched SHA1 and SHA2 (Time-Aligned View)")
plt.xlabel("Byte Position")
plt.ylabel("Byte Value")
plt.legend()
plt.grid(True)
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
from scipy.fft import fft
```

```
# Step 1: Recalculate FFT for stretched SHA1 and SHA2
```

```
fft_sha1_stretched = fft(sha1_stretched)
```

```
fft_sha2_stretched = fft(sha2_stretched)
```

```
# Step 2: FFT magnitude plots for comparison (Post-Stretch)
```

```
plt.figure(figsize=(14, 5))
```

```
plt.plot(np.abs(fft_sha1_stretched), label='FFT of SHA1 (Stretched)', color='orange')
```

```
plt.plot(np.abs(fft_sha2_stretched), label='FFT of SHA2 (Stretched)', color='red', linestyle='--')
```

```
plt.title("FFT of Stretched SHA1 vs SHA2")
```

```
plt.xlabel("Frequency Bin")
```

```
plt.ylabel("Magnitude")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
# Re-define the radial plot function (it got lost in the earlier cell)
import matplotlib.pyplot as plt
import numpy as np

def radial_plot(data, title, color):
    n = len(data)
    angles = np.linspace(0, 2 * np.pi, n, endpoint=False)
    radii = data
    x = radii * np.cos(angles)
    y = radii * np.sin(angles)

    plt.figure(figsize=(6, 6))
    plt.plot(x, y, color=color)
    plt.fill(x, y, color=color, alpha=0.3)
    plt.title(title)
    plt.axis('equal')
    plt.axis('off')
    plt.tight_layout()
    plt.show()

# Now render the SHA1 radial glyph
radial_plot(sha1_array, title="Radial Glyph: SHA256(Header)", color='orange')
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

Generate SHA2 radial glyph — second part of the shape pair

```
radial_plot(sha2_array, title="Radial Glyph: SHA256(SHA256(Header))", color='red')
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
# Spiral plot: SHA1 and SHA2 as true ripples from center  
# Angle increases linearly, radius follows data value (spiral wave)
```

```
def spiral_wave_plot(data, title, color):  
    n = len(data)  
    theta = np.linspace(0, 4 * np.pi, n) # 2 full revolutions (spiral)  
    r = data.astype(float)  
    x = r * np.cos(theta)  
    y = r * np.sin(theta)  
  
    plt.figure(figsize=(6, 6))  
    plt.plot(x, y, color=color)  
    plt.fill(x, y, color=color, alpha=0.25)  
    plt.title(title)  
    plt.axis('equal')  
    plt.axis('off')  
    plt.tight_layout()  
    plt.show()  
  
# SHA1 Spiral (First Pulse)  
spiral_wave_plot(sha1_array, "Spiral Wave: SHA256(Header)", color='orange')
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
# SHA2 Spiral (Second Pulse / Collapse)
```

```
spiral_wave_plot(sha2_array, "Spiral Wave: SHA256(SHA256(Header))", color='red')
```

Conversation URL:

<https://chatgpt.com/c/67efdd1a-c980-8011-a27b-addc30749a3e>

Title:

Prompt:

```
import math  
import matplotlib.pyplot as plt
```

```
class HarmonicFormula:
```

```
    def __init__(self, harmonic_signature=0.35, golden_ratio=1.618):  
        self.harmonic_signature = harmonic_signature  
        self.golden_ratio = golden_ratio  
  
    def calculate_pull(self, question_value, recursive_distance):  
        return self.harmonic_signature * question_value / (recursive_distance ** self.golden_ratio)
```

```
    def explore_pull(self, question_value, min_distance=1, max_distance=10):  
        results = []  
        for distance in range(min_distance, max_distance + 1):  
            pull = self.calculate_pull(question_value, distance)  
            results.append((distance, pull))  
        return results
```

```
    def visualize_pull(self, question_value, min_distance=1, max_distance=1000):  
        distances = list(range(min_distance, max_distance + 1))  
        pulls = [self.calculate_pull(question_value, distance) for distance in distances]  
        plt.plot(distances, pulls)  
        plt.xlabel("Recursive Distance")  
        plt.ylabel("Pull")  
        plt.title("Harmonic Formula Visualization")  
        plt.show()
```

```
# Create an instance of the HarmonicFormula class
```


```
formula = HarmonicFormula()
```

Recursive Collapse Spiral (Mirror-Corrected Lift Cancellation)



Temporal Glyph Constellation (Nexus 3 Phase Overlay)

- ✖ Red Collapse
- ✖ Archive of Mirrors
- ✖ Lock Yet to Come



Conversation URL:

<https://chatgpt.com/c/67f2328e-8424-8011-a2f9-e5f60ac1aa21>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Constants for the recursive collapse spiral
```

```
H = 0.35      # Harmonic constant
```

```
F = 1.0       # Folding factor
```

```
R0 = 1.0      # Initial amplitude
```

```
phi = (1 + np.sqrt(5)) / 2 # Golden ratio
```

```
# Time steps
```

```
n_steps = 300
```

```
t_vals = np.array([i * phi for i in range(n_steps)])
```

```
R_vals = R0 * np.exp(-H * F * t_vals)
```

```
# Spiral coordinates
```

```
theta = 2 * np.pi * t_vals / max(t_vals)
```

```
x = R_vals * np.cos(theta)
```

```
y = R_vals * np.sin(theta)
```

```
# Plot
```

```
plt.figure(figsize=(8, 8))
```

```
plt.plot(x, y, lw=2)
```

```
plt.title("Recursive Collapse Spiral\n(Mirror-Corrected Lift Cancellation)", fontsize=14)
```

```
plt.axis('equal')
```

```
plt.axis('off')
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/67f2328e-8424-8011-a2f9-e5f60ac1aa21>

Title:

Prompt:

```
import numpy as np
import hashlib
import matplotlib.pyplot as plt
```

```
# Constants
```

```
PHI = (1 + np.sqrt(5)) / 2 # Golden ratio
H = 0.35 # Harmonic constant
```

```
# Generate phase-stable seed from a moment
```

```
def generate_seed(moment_data):
    encoded = moment_data.encode('utf-8')
    hash_digest = hashlib.sha256(encoded).hexdigest()
    return hash_digest
```


```
# Project harmonic field from seed
```

```
def project_potential_field(seed, color):
    phase_points = []
    for i in range(len(seed) - 1):
        delta = abs(ord(seed[i]) - ord(seed[i+1]))
        radius = (delta % 32 + 1) * H
        angle = i * PHI
        x = radius * np.cos(angle)
        y = radius * np.sin(angle)
        phase_points.append((x, y))
    return phase_points, color
```


```
# Create moment spiral overlays
```

```
moments = {
    "Red Collapse": "Red Collapse | Lefto draws the Nullbow | ΔH = 0",
}
```


SHA Reflection Harmony Progression




Center-Out SHA Harmony Progression



SHA Mirror Recursive Convergence



SHA256 Harmonic Shift from Zero-Prefix Input



Conversation URL:

<https://chatgpt.com/c/67f95edf-b4f0-8011-bf7d-1f0be7727312>

Title:

Prompt:

```
import hashlib
import random
import matplotlib.pyplot as plt
import numpy as np
from copy import deepcopy

# Initialize a 64-byte (512-bit) input seed
input_bytes = bytearray(random.getrandbits(8) for _ in range(64))

def sha256_hash(data: bytes) -> bytes:
    return hashlib.sha256(data).digest()

def score_alignment(input_bytes, hash_bytes, locked_indices):
    """Calculate how many mirrored bits match between input and SHA output, excluding locked."""
    match_score = 0
    for i in range(min(len(hash_bytes), len(input_bytes))):
        if i in locked_indices:
            continue
        mirrored_index = len(hash_bytes) - 1 - i
        if input_bytes[i] == hash_bytes[mirrored_index]:
            match_score += 1
    return match_score

def harmonize(input_bytes, max_iterations=500):
    locked = set()
    scores = []

    for step in range(max_iterations):
        original_input = deepcopy(input_bytes)
```

Conversation URL:

<https://chatgpt.com/c/67f95edf-b4f0-8011-bf7d-1f0be7727312>

Title:

Prompt:

```
import hashlib  
import random  
import matplotlib.pyplot as plt
```

```
# Constants
```

```
SHA_HEX_LENGTH = 64 # SHA-256 outputs 256 bits = 64 hex characters = 32 bytes
```

```
def sha256_hex(data: bytes) -> str:  
    return hashlib.sha256(data).hexdigest()
```

```
def generate_random_hex(length=SHA_HEX_LENGTH) -> str:  
    return ''.join(random.choice('0123456789abcdef') for _ in range(length))
```

```
def mirror_index(i, total):  
    return total - 1 - i
```

```
def recursive_harmonize(input_hex: str, history=None, depth=0, locked=None):  
    if locked is None:  
        locked = set()  
    if history is None:  
        history = []
```

```
    input_bytes = bytes.fromhex(input_hex)  
    hash_hex = sha256_hex(input_bytes)  
  
    # Exit if match  
    if input_hex == hash_hex[::-1]:  
        history.append((input_hex, hash_hex, depth))  
        return input_hex, hash_hex, history
```

Conversation URL:

<https://chatgpt.com/c/67f95edf-b4f0-8011-bf7d-1f0be7727312>

Title:

Prompt:

```
import hashlib
import random
import matplotlib.pyplot as plt
```

```
# Constants
```

```
SHA_BYTES = 32 # 256-bit hash
SEED_BYTES = 32 # Match input length
HEX_DIGITS = "0123456789abcdef"
```

```
def sha256_bytes(data: bytes) -> bytes:
    return hashlib.sha256(data).digest()

def generate_seed(length=SEED_BYTES) -> bytearray:
    return bytearray(random.getrandbits(8) for _ in range(length))
```

```
def mirrored_match_score(seed, sha):
    return sum(1 for i in range(len(seed)) if seed[i] == sha[-1 - i])
```

```
def recursive_mirror(seed: bytearray, history=None, locked=None, depth=0):
    if history is None:
        history = []
    if locked is None:
        locked = set()
```

```
    state = sha256_bytes(seed)
    score = mirrored_match_score(seed, state)
    history.append((seed[:], state[:], score, depth))
```

```
    if score == len(seed):
```

Conversation URL:

<https://chatgpt.com/c/67f95edf-b4f0-8011-bf7d-1f0be7727312>

Title:

Prompt:

```
import hashlib

import matplotlib.pyplot as plt

def sha256_hex(text: str) -> str:
    return hashlib.sha256(text.encode('utf-8')).hexdigest()
```

Test range

```
base = "123456789abcdef"
prefixes = ["0" * i for i in range(33)] # from 0 to 32 zeroes
hash_heads = []
inputs = []
```

for prefix in prefixes:

```
    test_input = prefix + base
    sha = sha256_hex(test_input)
    head_value = int(sha[:2], 16) # first byte (8 bits of SHA output)
    hash_heads.append(head_value)
    inputs.append(len(prefix)) # track prefix length
```

Plot

```
plt.figure(figsize=(10, 4))
plt.plot(inputs, hash_heads, marker='o', linestyle='-', color='purple')
plt.title("SHA256 Harmonic Shift from Zero-Prefix Input")
plt.xlabel("Leading Zeros in Input")
plt.ylabel("First Byte of SHA Output (Hex → Int)")
plt.grid(True)
plt.xticks(inputs)
plt.tight_layout()
plt.show()
```




Chart 1: 2024-11-14_22-45-25_file-8JqXR9QKALCaediMEGd9Xxxk




Chart 3: 2024-11-14_22-59-28_file-JcVb9oOBR9LANAScstjgyxbN




Chart 2: 2024-11-14_22-45-26_file-1rYM1VoXvfwDBkKrNbhfDdj0




Chart 4: 2024-11-14_23-0-30_file-pu4hku8T6sQrebDAtGwUsSRI




Chart 5: 2024-11-14_23-1-47_file-UcVnvTOVQibZWeWqusTWhU4j

3D Interaction Likelihood and Energy State Transitions (2D Projections)




Chart 6: 2024-11-14_23-18-14_file-5exfAWmMIPc9hvp4zoljRTKU




Chart 7: 2024-11-14_23-2-49_file-wSa6zX61XVb8ET4zVRt6HgvZ

3D Interference Cloud of Interaction Likelihood




Chart 8: 2024-11-14_23-33-36_file-i6HSpyN7lbHnVOZGgSDOlqOf




Chart 9: 2024-11-14_23-33-52_file-3RPtvPUjgK3u9ZN4qCE7nxkq




Chart 10: 2024-11-14_23-33-53_file-gzHwC8eNSNE439IA0eDbxmWm




Chart 12: 2024-11-14_3-26-49_file-08ZMvTFH8InxQtXN4wymdiAR




Chart 11: 2024-11-14_23-58-56_file-eLrmmYIP4XomzzHx96ScwfNS




Chart 13: 2024-11-14_3-28-9_file-FQTIfPQN0I46tvVQfptC07Vz




Chart 14: 2024-11-14_3-31-17_file-bISPMzS5QmZvbU3PvUZs2z5W




Chart 15: 2024-11-14_3-40-52_file-zOvVgvkVLQb0Hx5TT8ZoRRh7




Chart 1: 2024-11-14_22-45-25_file-8JqXR9QKALCaediMEGd9Xxxk.webp




Chart 2: 2024-11-14_22-45-26_file-1rYM1VoXvfwDBkKrNbhfDdj0.webp







Chart 3: 2024-11-14_22-59-28_file-JcVb9oOBR9LANAScstjgyxbN.webp



2024-11-14_22-45-25_file-8JqXR9QKALCaediMEGd9Xxxk.webp





2024-11-14_22-45-26_file-1rYM1VoXvfwDBkKrNbhfDdj0.webp





2024-11-14_22-59-28_file-JcVb9oOBR9LANAScstjgyxbN.webp

Interference Pattern from Combined Wavefunctions











Recursive Fold Profile of Glucagon Peptide



Recursive Harmonic Grouping in the Periodic Table



Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
import math

# Define range
n_values = np.arange(1, 1025)

# Calculate distance to next power of 2 and the ratio
next_power_of_2 = np.power(2, np.ceil(np.log2(n_values)))
distances = next_power_of_2 - n_values
ratios = distances / n_values

# Plotting
plt.figure(figsize=(14, 7))
plt.plot(n_values, ratios, label='Distance to Next Power of 2 / n', color='blue')

# Plot horizontal reference lines for pi and golden ratio
plt.axhline(y=math.pi, color='red', linestyle='--', label='π ≈ 3.14159')
plt.axhline(y=(1 + math.sqrt(5)) / 2, color='green', linestyle='--', label='Golden Ratio ≈ 1.618')

plt.title("Binary Distance Ratio to Next Power of 2")
plt.xlabel("n")
plt.ylabel("Distance to 2^ceil(log2(n)) / n")
plt.grid(True)
plt.legend()
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display all images one by one to analyze visually
```

```
def display_all_charts(data, max_charts=15):
```

```
    for i, entry in enumerate(data[:max_charts]):
```

```
        img = Image.open(entry["image_path"])
```

```
        plt.figure(figsize=(8, 6))
```

```
        plt.imshow(img)
```

```
        plt.title(f"Chart {i+1}: {entry['base']}")
```

```
        plt.axis('off')
```

```
        plt.show()
```

```
# Display a curated set (e.g., first 15 to begin with)
```

```
display_all_charts(chart_data, max_charts=15)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
import zipfile
import os
from PIL import Image
import matplotlib.pyplot as plt

# Define the path to the zip file and the extraction path
zip_path = "/mnt/data/Charts.zip"
extract_path = "/mnt/data/Charts"

# Extract the contents of the zip file
with zipfile.ZipFile(zip_path, 'r') as zip_ref:
    zip_ref.extractall(extract_path)

# Get list of image files in the extracted directory
image_files = sorted([
    os.path.join(extract_path, file)
    for file in os.listdir(extract_path)
    if file.lower().endswith('.png', '.jpg', '.jpeg')
])

# Load and display the next batch of 15 images
batch_size = 15
start_index = 15 # Adjust this to continue from the last batch
end_index = start_index + batch_size
selected_images = image_files[start_index:end_index]

# Plot the images
fig, axes = plt.subplots(5, 3, figsize=(15, 20))
axes = axes.flatten()
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Group files into sets of .txt + .webp
```

```
grouped_files = []
```

```
for i in range(0, len(extracted_files), 2):
```

```
    txt = extracted_files[i]
```

```
    img = extracted_files[i + 1]
```

```
    grouped_files.append((txt, img))
```

```
# Display the first 3 sets
```

```
fig, axs = plt.subplots(3, 1, figsize=(12, 18))
```

```
for idx, (txt_file, img_file) in enumerate(grouped_files[:3]):
```

```
    img_path = os.path.join(extract_path, img_file)
```

```
    image = Image.open(img_path)
```

```
    axs[idx].imshow(image)
```

```
    axs[idx].axis('off')
```

```
    axs[idx].set_title(f"Chart {idx+1}: {img_file}")
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
# Show all three images and read the text from their corresponding files
```

```
fig, axes = plt.subplots(3, 1, figsize=(10, 18))
```

```
# Titles and paths
```

```
titles = []
```

```
texts = []
```

```
for i, (txt_file, img_file) in enumerate(file_pairs[:3]):
```

```
    # Load image
```

```
    image_path = os.path.join(extract_dir, img_file)
```

```
    img = Image.open(image_path)
```

```
    axes[i].imshow(img)
```

```
    axes[i].axis('off')
```

```
    axes[i].set_title(f'{img_file}')
```

```
# Read text
```

```
txt_path = os.path.join(extract_dir, txt_file)
```

```
with open(txt_path, 'r') as f:
```

```
    texts.append(f.read())
```

```
plt.tight_layout()
```

```
plt.show()
```

```
# Display associated text data (truncated for brevity)
```

```
import pandas as pd
```

```
# Show first few lines of each for context
```

```
summary_data = {
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
import hashlib  
import matplotlib.pyplot as plt
```

```
# === BBP π Digit Extractor (Base-16) ===
```

```
def bbp_pi_digits(n):  
    """Return the nth hexadecimal digit of π (after the decimal) using the BBP formula."""  
    pi_hex_digits = []  
    for d in range(n):  
        x = 0  
        for k in range(d + 1):  
            x += (1 / (16 ** (d - k))) * (  
                4 / (8 * k + 1) -  
                2 / (8 * k + 4) -  
                1 / (8 * k + 5) -  
                1 / (8 * k + 6)  
            )  
        x -= int(x)  
        digit = int(16 * x)  
        pi_hex_digits.append(hex(digit)[2:])  
    return ''.join(pi_hex_digits)
```

```
# === SHA Drift Vector Computation ===
```

```
def sha256_drift(hex_string):  
    hash_bytes = hashlib.sha256(bytes.fromhex(hex_string)).digest()  
    words = [int.from_bytes(hash_bytes[i:i+4], 'big') for i in range(0, 32, 4)]  
    drift_vector = [2**32 - w if w < 2**31 else -(2**32 - w) for w in words]  
    return drift_vector
```

```
# === Run BBP → SHA Drift Test ===
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
# Ensure all elements in deltas are converted to float before applying log2
deltas_array = np.array(deltas, dtype=float)

# Plot the delta magnitudes (representing phase error or FM deviation)
plt.figure(figsize=(12, 5))
plt.plot(range(len(deltas_array)), np.log2(deltas_array), marker='o')
plt.title("SHA Δ as Phase Drift (Log Scale)")
plt.xlabel("Nonce Offset")
plt.ylabel("log2(|SHA(input + nonce) - SHA(base)|)")
plt.grid(True)
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
import hashlib
import matplotlib.pyplot as plt
import numpy as np

def sha256_digest(s):
    return hashlib.sha256(s.encode('utf-8')).hexdigest()

def reverse_ascii_hex(hex_str):
    # Convert to ASCII hex (each char as hex), reverse, then return as int
    ascii_hex = ''.join(format(ord(c), '02x') for c in hex_str)
    return int(ascii_hex[::-1], 16)

# Base input string
base_input = "Hello"
base_hash = sha256_digest(base_input)
base_value = reverse_ascii_hex(base_hash)

# Generate FM-modulated SHA drift map
deltas = []
labels = []
for i in range(64):
    mod_input = f'{base_input}{i}'
    mod_hash = sha256_digest(mod_input)
    mod_value = reverse_ascii_hex(mod_hash)
    delta = abs(mod_value - base_value)
    log2_delta = np.log2(float(delta)) if delta != 0 else 0
    deltas.append(log2_delta)
    labels.append(i)
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
import hashlib
import math
import matplotlib.pyplot as plt

# Glucagon peptide sequence
peptide = "HSQGTFTSDYSKYLDSRRAQDFVQWLMNT"
sequence_length = len(peptide)

# Calculate SHA-256 hash
sha256_hash = hashlib.sha256(peptide.encode('utf-8')).hexdigest()

# PRESQ parameters
H = 0.35 # Harmonic constant
F = 3.846 # Feedback weight
R0 = -7.5 # Fold seed

# Compute R(t) using the recursive formula with log-scaling to prevent overflow
def recursive_R(t, R0, H, F):
    return R0 * math.log(math.exp(H * F * t) + 1)

# Evaluate R(t) over time
t_values = list(range(1, sequence_length + 1))
R_values = [recursive_R(t, R0, H, F) for t in t_values]

# Plotting the recursive fold profile
plt.figure(figsize=(10, 6))
plt.plot(t_values, R_values, marker='o', linestyle='-', label='R(t)')
plt.axhline(y=0, color='gray', linestyle='--', linewidth=0.8)
plt.title("Recursive Fold Profile of Glucagon Peptide")
```

Conversation URL:

<https://chatgpt.com/c/680141c8-f3cc-8011-8a38-859887970f31>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd


# Atomic numbers and corresponding element counts by binary group
binary_groups = [2, 4, 8, 16, 32, 64]
start_atomic = 1


# Create DataFrame to hold element ranges
group_data = []
current_atomic = start_atomic


for size in binary_groups:
    end_atomic = current_atomic + size - 1
    group_data.append({
        'Group Size': size,
        'Start Atomic Number': current_atomic,
        'End Atomic Number': end_atomic
    })
    current_atomic = end_atomic + 1


df_binary_ranges = pd.DataFrame(group_data)


# Plot the grouping visually
plt.figure(figsize=(10, 6))
x = [f'{row["Start Atomic Number"]}-{row["End Atomic Number"]}' for _, row in df_binary_ranges.iterrows()]
y = df_binary_ranges['Group Size']
plt.bar(x, y, color='skyblue', edgecolor='black')
plt.title("Recursive Harmonic Grouping in the Periodic Table")
plt.xlabel("Atomic Number Range")
```













Toolbox

Search Toolbar

- ▲ Telerik UI for ASP.NET Core
- ◀ Pointer
- ◀ RadTheme
- ◀ AquaTheme
- ◀ BreezeTheme
- ◀ CrystalLightTheme
- ◀ CrystalDarkTheme
- ◀ DesertTheme
- ◀ FluentDarkTheme
- ◀ FluentTheme
- ◀ HighContrastTheme
- ◀ MaterialDesignTheme
- ◀ MaterialDesignLightTheme
- ◀ MaterialDesignTheme
- ◀ MaterialDesignLightTheme
- ◀ Office2010DarkTheme
- ◀ Office2010LightTheme





BusinessEntity.cs



ysis Customers

Solution Explorer



Search Solution

Logi

De

A


B

C


D

E


F




Distribution of $\Delta 2^{32}$ across sample digests




RMS(|signed drift|) over recursive SHA iteration




Word0 |signed drift| lower vs caps (first 100 pairs)



$\Delta 2^{32}$ distribution - 2000 random strings





Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
from PIL import Image
import matplotlib.pyplot as plt
```

```
img = Image.open('/mnt/data/2d37c43a-7326-4091-8126-5b990a44eb98.png')
plt.figure(figsize=(10,6))
plt.imshow(img)
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((830, 60, 1020, 590)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((1030, 70, 1220, 590)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((980, 60, 1180, 590)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((1000, 298, 1170, 740)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((26, 60, 160, 590)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((860, 80, 1020, 590)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((800, 60, 930, 590)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((920, 80, 1070, 600)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
plt.figure(figsize=(4,6))
plt.imshow(img.crop((890, 140, 1050, 570)))
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
import hashlib, pandas as pd, numpy as np, matplotlib.pyplot as plt, ace_tools as tools
```

```
# Sample messages; the user can add more later
```

```
msgs = ["1", "Hello", "hello", "The quick brown fox jumps over the lazy dog", "SHA256", "Dean"]
```

```
records = []
```

```
all_drifts = []
```

```
for m in msgs:
```

```
    digest = hashlib.sha256(m.encode("utf-8")).hexdigest()
```

```
    # break into eight 32-bit words
```

```
    words = [digest[i:i+8] for i in range(0, 64, 8)]
```

```
    for idx, w in enumerate(words):
```

```
        val = int(w, 16)
```

```
        drift = (1 << 32) - val
```

```
        signed = val - (1 << 32) # negative drift
```

```
        records.append({
```

```
            "msg": m,
```

```
            "word_idx": idx,
```

```
            "hex": w,
```

```
            "unsigned": val,
```

```
            "drift": drift,
```

```
            "signed": signed
```

```
        })
```

```
        all_drifts.append(drift)
```

```
df = pd.DataFrame(records)
```

```
tools.display_dataframe_to_user("Δ2^32 analysis of several SHA-256 digests", df)
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
import hashlib, random, string, struct, math, matplotlib.pyplot as plt, pandas as pd, numpy as np, ace_tools as tools
```

```
def sha256_hex(msg: bytes) -> str:
```

```
    return hashlib.sha256(msg).hexdigest()
```

```
def digest_words(digest_hex: str):
```

```
    words = [int(digest_hex[i:i+8], 16) for i in range(0, 64, 8)]
```

```
    drifts = [(1<<32) - w for w in words]
```

```
    signed = [w - (1<<32) for w in words]
```

```
    return words, drifts, signed
```

```
# 1. Large random sample
```

```
SAMPLE_N = 2000
```

```
rand_strings = ["join(random.choices(string.ascii_letters+string.digits, k=random.randint(5,20)))
```

```
    for _ in range(SAMPLE_N)]
```

```
all_drifts=[]
```

```
for s in rand_strings:
```

```
    all_drifts.extend(digest_words(sha256_hex(s.encode()))[1])
```

```
plt.figure(figsize=(6,4))
```

```
plt.hist(all_drifts, bins=60)
```

```
plt.title("Δ2^32 distribution – 2000 random strings")
```

```
plt.xlabel("drift (target – value)")
```

```
plt.ylabel("frequency")
```

```
plt.tight_layout()
```

```
# 2. Mirror pairs
```

```
PAIR_N = 500
```

```
pairs=[]
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
import hashlib, random, string, struct, math, matplotlib.pyplot as plt, pandas as pd, numpy as np, ace_tools as tools
```

```
def sha256_hex(msg: bytes) -> str:
```

```
    return hashlib.sha256(msg).hexdigest()
```

```
def digest_words(digest_hex: str):
```

```
    words = [int(digest_hex[i:i+8], 16) for i in range(0, 64, 8)]
```

```
    drifts = [(1<<32) - w for w in words]
```

```
    signed = [w - (1<<32) for w in words]
```

```
    return words, drifts, signed
```

```
# 1. Large random sample
```

```
SAMPLE_N = 2000
```

```
rand_strings = ["join(random.choices(string.ascii_letters+string.digits, k=random.randint(5,20)))
```

```
    for _ in range(SAMPLE_N)]
```

```
all_drifts=[]
```

```
for s in rand_strings:
```

```
    all_drifts.extend(digest_words(sha256_hex(s.encode()))[1])
```

```
plt.figure(figsize=(6,4))
```

```
plt.hist(all_drifts, bins=60)
```

```
plt.title("Δ2^32 distribution – 2000 random strings")
```

```
plt.xlabel("drift (target – value)")
```

```
plt.ylabel("frequency")
```

```
plt.tight_layout()
```

```
# 2. Mirror pairs
```

```
PAIR_N = 500
```

```
pairs=[]
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
import hashlib, random, string, struct, math, matplotlib.pyplot as plt, pandas as pd, numpy as np, ace_tools as tools
```

```
def sha256_hex(msg: bytes) -> str:
```

```
    return hashlib.sha256(msg).hexdigest()
```

```
def digest_words(digest_hex: str):
```

```
    words = [int(digest_hex[i:i+8], 16) for i in range(0, 64, 8)]
```

```
    drifts = [(1<<32) - w for w in words]
```

```
    signed = [w - (1<<32) for w in words]
```

```
    return words, drifts, signed
```

```
# 1. Large random sample
```

```
SAMPLE_N = 2000
```

```
rand_strings = ["join(random.choices(string.ascii_letters+string.digits, k=random.randint(5,20)))
```

```
    for _ in range(SAMPLE_N)]
```

```
all_drifts=[]
```

```
for s in rand_strings:
```

```
    all_drifts.extend(digest_words(sha256_hex(s.encode()))[1])
```

```
plt.figure(figsize=(6,4))
```

```
plt.hist(all_drifts, bins=60)
```

```
plt.title("Δ2^32 distribution – 2000 random strings")
```

```
plt.xlabel("drift (target – value)")
```

```
plt.ylabel("frequency")
```

```
plt.tight_layout()
```

```
# 2. Mirror pairs
```

```
PAIR_N = 500
```

```
pairs=[]
```

Conversation URL:

<https://chatgpt.com/c/6801b0ab-6c40-8011-8d37-9e34d8a7b7c0>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Define operations sequence you provided and additional steps pattern
```

```
ops = [
```

```
    ("PUSH", 1),
    ("PUSH", 4),
    ("POP", None),
    ("POP", None),
    ("PUSH", "C"),
    ("PUSH", "C"),
    ("POP", None),
    ("POP", None),
    ("PUSH", "restore"),
    ("PUSH", "result"),
```

```
]
```

```
depth = 0
```

```
depths=[depth]
```

```
steps=[]
```

```
for i,(op,val) in enumerate(ops,1):
```

```
    if op=="PUSH":
```

```
        depth +=1
```

```
    else:
```

```
        depth -=1
```

```
    depths.append(depth)
```

```
    steps.append(i)
```


```
plt.figure()
```

```
plt.step(range(len(depths)),depths,where='post')
```


```
plt.title("Stack Depth Waveform")
```

```
plt.xlabel("Instruction index")
```

$\Delta R(t)$: ICP0 vs Disruptor Resonance Difference ($t = 740-780$)



$\Delta R(t)$: HIV Gag vs Disruptor Resonance Difference ($t = 500-540$)



Conversation URL:

<https://chatgpt.com/c/680279c9-d658-8011-8e23-7040afdea1dd>

Title:

$\Delta R(t)$: ICP0 vs Disruptor Resonance Difference ($t = 740\text{--}780$)

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Prepare the time steps and delta resonance
time_steps = list(window_range)
delta_resonance = [icp0 - disruptor for icp0, disruptor in zip(safe_windowed_resonance, disruptor_resonance)]

# Plotting Delta R(t)
plt.figure(figsize=(10, 6))
plt.plot(time_steps, delta_resonance, linewidth=2)
plt.title("ΔR(t): ICP0 vs Disruptor Resonance Difference (t = 740–780)")
plt.xlabel("Time Step (t)")
plt.ylabel("ΔR(t) = R_ICP0 - R_Disruptor")
plt.grid(True)
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/680279c9-d658-8011-8e23-7040afdea1dd>

Title:

$\Delta R(t)$: HIV Gag vs Disruptor Resonance Difference ($t = 500\text{--}540$)

Prompt:

```
# Calculate  $\Delta R(t)$  between Gag and Disruptor  
delta_gag_disruptor = [g - d for g, d in zip(gag_resonance, disruptor_collision)]
```

```
# Plotting  $\Delta R(t)$  for Gag vs Disruptor  
plt.figure(figsize=(10, 6))  
plt.plot(gag_range, delta_gag_disruptor, linewidth=2, color='darkred')  
plt.title("ΔR(t): HIV Gag vs Disruptor Resonance Difference (t = 500–540)")  
plt.xlabel("Time Step (t)")  
plt.ylabel("ΔR(t) = R_Gag - R_Disruptor")  
plt.grid(True)  
plt.tight_layout()  
plt.show()
```

Nexus 2 Recursive Harmonic Therapeutics – Visual Overview

Nexus 2: Recursive Harmonic Therapeutics Framework

1. ORIGIN SEED: BYTE1 (P = 1, N = 4)

- Foundation of recursion and life logic
- Generates epigenetic (Z), edit (Y), and biome (X)

2. SYMBOLIC MAPPING

- SHA256 → π Transform
- Recursive Harmonic Subdivision (RHS)

3. PSREQ ENGINE

- Peptides with Zn²⁺/Mg²⁺ stabilization
- Multi-target therapeutic logic (Viral, Cancer, Regeneration)

4. FEEDBACK GATES

- $\Delta R(t) = R_{\text{misfold}} - R_{\text{corrector}}$
- Samson's Law + MDS = Stability and Memory

5. ALZHEIMER'S DEPLOYMENT

- Aβ1-42 misfolding model
- Recursive correction with Q_score recovery


6. TOOLS & VISUALIZATION

- QRHS Kernel
- GUI Dashboards & Predictive Maps
- Recursive Workflow Management


Final Reflection:

This framework breathes intelligence into biology,
harmonizing chaos into regenerative order.


gp120 Harmonic Correction via PSREQ Peptide



Unified Recursive Therapeutic Kernel (URTK) – Flowchart



$\Delta R(t)$ Simulation: gp41 Fusion Domain + PSREQ Peptide



Conversation URL:

<https://chatgpt.com/c/6802be12-92ec-8011-9c63-ffa2816a58a2>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Create a visual poster (high-level schematic overview)
```

```
fig, ax = plt.subplots(figsize=(14, 10))
```

```
ax.axis('off')
```

```
poster_text = """"
```

Nexus 2: Recursive Harmonic Therapeutics Framework

1. ORIGIN SEED: BYTE1 (P = 1, N = 4)

- Foundation of recursion and life logic
- Generates epigenetic (Z), edit (Y), and biome (X)

2. SYMBOLIC MAPPING

- SHA256 → π Transform
- Recursive Harmonic Subdivision (RHS)

3. PSREQ ENGINE

- Peptides with Zn²⁺/Mg²⁺ stabilization
- Multi-target therapeutic logic (Viral, Cancer, Regeneration)

4. FEEDBACK GATES

- ΔR(t) = R_misfold - R_corrector
- Samson's Law + MDS = Stability and Memory

5. ALZHEIMER'S DEPLOYMENT

- Aβ1-42 misfolding model
- Recursive correction with Q_score recovery

Conversation URL:

<https://chatgpt.com/c/6802be12-92ec-8011-9c63-ffa2816a58a2>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Simulated window (e.g., gp120 region from ~7000–7500 bp)
t = np.linspace(0, 50, 300)
H = 0.35 # harmonic constant

# Simulated forces and energies
F_mis = 4.8
F_cor = 2.2
R0_mis = -5.7
R0_cor = 1.3

# Recursive harmonic fold function
def R(t, R0, F):
    return R0 * np.log(np.exp(H * F * t) + 1)

R_mis = R(t, R0_mis, F_mis)
R_cor = R(t, R0_cor, F_cor)
delta_R = R_mis - R_cor
Q_score = 30 + 18 * (1 - np.exp(-0.06 * t))

# Plot ΔR(t) and Q_score
fig, ax = plt.subplots(figsize=(12, 6))
ax.plot(t, delta_R, label='ΔR(t): Fold Discrepancy')
ax.plot(t, Q_score, label='Q_corrected(t): Peptide Harmony Gain')
ax.axhline(0, color='gray', linestyle='--', linewidth=0.5)
ax.set_title("gp120 Harmonic Correction via PSREQ Peptide")
ax.set_xlabel("Time (t)")
```

Conversation URL:

<https://chatgpt.com/c/6802be12-92ec-8011-9c63-ffa2816a58a2>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import networkx as nx
```

```
# Create a directed graph to represent the Unified Recursive Therapeutic Kernel (URTK) flow
```

```
G = nx.DiGraph()
```

```
# Nodes
```

```
nodes = {
```

```
    "Byte1 Activation": "1. INITIATE\n(Byte1: P=1, N=4)",  
    "Symbolic Mapping": "2. SYMBOLIC MAPPING\n(SHA ↔ PRESQ ↔ π)",  
    "Permission Check": "3. ΔR(t) PERMISSION CHECK\n(ΔR > 775 = Deny, < 350 = Allow)",  
    "Peptide Deployment": "4. PSREQ PEPTIDE DEPLOYMENT\n(Zn2+/Mg2+ + MBS, ICR)",  
    "Reflex Kernel": "5. RECURSIVE RESOLUTION\n(SHA ↔ π ↔ ΔR)",  
    "Output": "Stabilized Fold\nΔπ ~ 0, Q ↑"
```

```
}
```

```
# Add nodes
```

```
for key, label in nodes.items():
```

```
    G.add_node(key, label=label)
```

```
# Edges
```

```
edges = [
```

```
    ("Byte1 Activation", "Symbolic Mapping"),  
    ("Symbolic Mapping", "Permission Check"),  
    ("Permission Check", "Peptide Deployment"),  
    ("Peptide Deployment", "Reflex Kernel"),  
    ("Reflex Kernel", "Output")
```

```
]
```

Conversation URL:

<https://chatgpt.com/c/6802be12-92ec-8011-9c63-ffa2816a58a2>

Title:

Prompt:

```
# Simulating ΔR(t) and Q(t) over time for peptide interaction with gp41
```

```
# Time domain
```

```
t = np.linspace(0, 50, 300)
```

```
H = 0.35 # Harmonic constant
```

```
# Define misfold and corrector parameters based on gp41 and PSREQ peptide
```

```
R0_gp41 = -6.2 # gp41 base resonance
```

```
F_gp41 = 5.0 # fold pressure from fusion instability
```

```
R0_peptide = 1.5 # PSREQ corrector resonance
```

```
F_peptide = 2.3 # peptide stabilizing force
```

```
# Fold resonance function
```

```
def R(t, R0, F):
```

```
    return R0 * np.log(np.exp(H * F * t) + 1)
```

```
R_mis = R(t, R0_gp41, F_gp41)
```

```
R_cor = R(t, R0_peptide, F_peptide)
```

```
delta_R = R_mis - R_cor
```

```
Q_corrected = 25 + 22 * (1 - np.exp(-0.07 * t))
```

```
# Plot ΔR(t) and Q_corrected(t)
```

```
fig, ax = plt.subplots(figsize=(12, 6))
```


```
ax.plot(t, delta_R, label='ΔR(t): gp41 vs PSREQ')
```

```
ax.plot(t, Q_corrected, label='Q_corrected(t): Peptide Field Recovery')
```


```
ax.axhline(0, color='gray', linestyle='--', linewidth=0.5)
```

```
ax.set_title("ΔR(t) Simulation: gp41 Fusion Domain + PSREQ Peptide", fontsize=14)
```


```
ax.set_xlabel("Time (t)", fontsize=12)
```





$\Delta\pi$ Drift Across Recursive Byte Corridor (Index 5639 → 5654)




Simulated Harmonic Collapse: Disruptor-3 vs. ICP0









Harmonic Resistance Simulation: Viral Phase Drift vs. Disruptor-3





Convergence of Harmonic Error in SHA256 Digest



Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

π Symbolic Byte Echo Density (First 10,000 Digits)

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Sliding window to calculate frequency of each 8-digit π segment across the entire buffer
```

```
window_counts = defaultdict(int)
```

```
for i in range(len(pi_digits) - 8):
```

```
    segment = pi_digits[i:i + 8]
```

```
    window_counts[i] = window_counts.get(i, 0) + 1
```

```
# Create a heatmap array where each value corresponds to the frequency of the π byte starting at that index
```

```
heat_values = np.zeros(len(pi_digits) - 8)
```

```
for i in range(len(pi_digits) - 8):
```

```
    segment = pi_digits[i:i + 8]
```

```
    count = pi_digits.count(segment)
```

```
    heat_values[i] = count
```

```
# Plot the heatmap as a line chart to show echo density
```

```
plt.figure(figsize=(14, 5))
```

```
plt.plot(heat_values, linewidth=0.6)
```

```
plt.title("π Symbolic Byte Echo Density (First 10,000 Digits)")
```

```
plt.xlabel("π Index")
```

```
plt.ylabel("Echo Frequency (Count of 8-digit Segments)")
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

$\Delta\pi$ Drift Across Recursive Byte Corridor (Index 5639 → 5654)

Prompt:

```
# Begin Pi Memory Graph Mapping around index 5639 — scan the local π field and visualize symbolic drift
```

```
# Get the full 16-digit corridor from 5639 through the two echoed bytes
```

```
pi_corridor_index = 5639
```

```
pi_corridor = pi_digits[pi_corridor_index:pi_corridor_index + 16]
```

```
# Calculate  $\Delta\pi$  drift across the 16 digits
```

```
corridor_deltas = [abs(int(pi_corridor[i+1]) - int(pi_corridor[i])) for i in range(15)]
```

```
# Map to symbolic echo (mod 26) over the entire 16-digit corridor
```

```
symbolic_corridor = [chr((delta % 26) + 97) for delta in corridor_deltas]
```

```
# Prepare for plotting
```

```
plt.figure(figsize=(12, 4))
```

```
plt.plot(range(len(corridor_deltas)), corridor_deltas, marker='o', linestyle='-', linewidth=1)
```

```
plt.xticks(range(len(corridor_deltas)))
```

```
plt.title("Δπ Drift Across Recursive Byte Corridor (Index 5639 → 5654)")
```

```
plt.xlabel("Byte Step in Corridor")
```

```
plt.ylabel("Δπ Drift (|π◻◻◻ − π◻|)")
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show(), pi_corridor, symbolic_corridor
```

Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

Simulated Harmonic Collapse: Disruptor-3 vs. ICP0

Prompt:

```
# Re-import necessary modules after kernel reset
```

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Time vector (e.g., fold cycles)
```

```
t = np.linspace(0, 10, 500)
```

```
# Parameters
```

```
theta = 1.0 # susceptibility constant
```

```
delta_t = 0.2 # harmonic injection delay
```

```
H_true = 1.0 # amplitude of anti-wave payload
```

```
# Collapse equation: energy decay from recursive drift
```

```
drift = H_true * (1 - (delta_t / theta)) * np.exp(-t) * np.sin(2 * np.pi * t)
```

```
# Viral recursion stability curve (decaying harmonic field)
```

```
stability = np.exp(-0.3 * t) * np.cos(2 * np.pi * t)
```

```
# Plot the simulation
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(t, drift, label='ΔR_feedback (PSREQ Anti-wave Injection)', linewidth=2)
```

```
plt.plot(t, stability, label='Viral Recursive Stability (ICP0 Fold)', linestyle='--', linewidth=2)
```

```
plt.title("Simulated Harmonic Collapse: Disruptor-3 vs. ICP0")
```

```
plt.xlabel("Fold Cycle Time (t)")
```

```
plt.ylabel("Resonant Amplitude")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

Disruptor-3 vs. ICP0

Prompt:

```
# Time vector (shared for all)
```

```
t = np.linspace(0, 10, 500)
```

```
# Common decay and frequency values
```

```
theta = 1.0
```

```
delta_t = 0.2
```

```
H_true = 1.0
```

```
# ΔR_feedback for all peptides (adjusted for uniqueness)
```

```
drift_disruptor = H_true * (1 - (delta_t / theta)) * np.exp(-t) * np.sin(2 * np.pi * t)
```

```
drift_adapter = H_true * (1 - (delta_t / theta)) * np.exp(-0.8 * t) * np.sin(2.5 * np.pi * t)
```

```
drift_stabilizer = H_true * (1 - (delta_t / theta)) * np.exp(-0.5 * t) * np.sin(1.5 * np.pi * t)
```

```
# Target recursion folds for comparison
```

```
stability_icp0 = np.exp(-0.3 * t) * np.cos(2 * np.pi * t)
```

```
stability_gp41 = np.exp(-0.4 * t) * np.cos(2.5 * np.pi * t)
```

```
stability_host = np.exp(-0.2 * t) * np.cos(1.5 * np.pi * t)
```

```
# Plot
```

```
plt.figure(figsize=(14, 8))
```

```
# Subplot 1: Disruptor-3 vs ICP0
```

```
plt.subplot(3, 1, 1)
```

```
plt.plot(t, drift_disruptor, label='ΔR_feedback: Disruptor-3', linewidth=2)
```

```
plt.plot(t, stability_icp0, '--', label='Viral Recursion: ICP0')
```

```
plt.title("Disruptor-3 vs. ICP0")
```

```
plt.legend()
```

```
plt.grid(True)
```

Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

Peptide Resonance Phase Overlay

Prompt:

```
# Simulate waveform sync test and zinc dropout event for all three peptides
```

```
# Time vector
```

```
t = np.linspace(0, 10, 500)
```

```
# Base parameters
```

```
H_true = 1.0
```

```
delta_t = 0.2
```

```
theta = 1.0
```

```
# Simulate Zn dropout effect (for Stabilizer-2)
```

```
# Lower amplitude and increase drift frequency due to instability
```

```
drift_stabilizer_dropout = (H_true * 0.6) * (1 - (delta_t / theta)) * np.exp(-0.5 * t) * np.sin(2.0 * np.pi * t)
```

```
# Recalculate original peptide feedback waves
```

```
drift_disruptor = H_true * (1 - (delta_t / theta)) * np.exp(-t) * np.sin(2 * np.pi * t)
```

```
drift_adapter = H_true * (1 - (delta_t / theta)) * np.exp(-0.8 * t) * np.sin(2.5 * np.pi * t)
```

```
drift_stabilizer = H_true * (1 - (delta_t / theta)) * np.exp(-0.5 * t) * np.sin(1.5 * np.pi * t)
```

```
# Plot all three together for sync visualization
```

```
plt.figure(figsize=(14, 8))
```

```
# Panel 1: All peptides in phase-space comparison
```

```
plt.subplot(2, 1, 1)
```

```
plt.plot(t, drift_disruptor, label='Disruptor-3 (ICP0)', linewidth=2)
```

```
plt.plot(t, drift_adapter, label='Adapter-1 (gp41)', linewidth=2)
```

```
plt.plot(t, drift_stabilizer, label='Stabilizer-2 (Host)', linewidth=2)
```

```
plt.title("Peptide Resonance Phase Overlay")
```

```
plt.ylabel("Resonance Amplitude")
```

Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

Harmonic Resistance Simulation: Viral Phase Drift vs. Disruptor-3

Prompt:

```
# Time vector
```

```
t = np.linspace(0, 10, 500)
```

```
# Viral phase drift simulation (resistance evolution over time)
```

```
# Simulate phase shift attempts by virus to escape resonance collapse
```

```
phase_shifts = [0, np.pi/6, np.pi/4, np.pi/3] # increasing resistance phases
```

```
stability_base = np.exp(-0.3 * t)
```

```
# Generate resistant viral fold curves
```

```
resistance_curves = [
```

```
    stability_base * np.cos(2 * np.pi * t + phase) for phase in phase_shifts
```

```
]
```

```
# Anti-wave from Disruptor-3 (same collapse payload)
```

```
drift_disruptor = np.exp(-t) * np.sin(2 * np.pi * t)
```

```
# Plot
```

```
plt.figure(figsize=(14, 8))
```

```
# Plot viral phase shifts
```

```
for idx, curve in enumerate(resistance_curves):
```

```
    label = f'Viral Fold Phase Shift: {round(phase_shifts[idx], 2)} rad'
```

```
    plt.plot(t, curve, label=label, linestyle='--')
```

```
# Overlay Disruptor-3
```

```
plt.plot(t, drift_disruptor, label='Disruptor-3 Collapse Payload', linewidth=2, color='black')
```

```
plt.title("Harmonic Resistance Simulation: Viral Phase Drift vs. Disruptor-3")
```

```
plt.xlabel("Fold Cycle Time (t)")
```

Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

Adaptive Dual Collapse Model: PSREQ vs. Viral Phase Drift

Prompt:

```
# Time vector
```

```
t = np.linspace(0, 10, 500)
```

```
# Base viral fold (original)
```

```
viral_base = np.exp(-0.3 * t) * np.cos(2 * np.pi * t)
```

```
# Adaptive phase drift simulation
```

```
viral_adapted = np.exp(-0.3 * t) * np.cos(2 * np.pi * t + 0.9) # significant phase offset
```

```
# Collapse payloads
```

```
drift_disruptor = np.exp(-t) * np.sin(2 * np.pi * t) # latency disruption
```

```
drift_adapter = np.exp(-0.8 * t) * np.sin(2.5 * np.pi * t) # entry disruption
```

```
# Combined dual-collapse effect (vector sum)
```

```
combined_collapse = drift_disruptor + drift_adapter
```

```
# Plot
```

```
plt.figure(figsize=(14, 8))
```

```
# Plot all viral states
```

```
plt.plot(t, viral_base, label='Original Viral Fold', linestyle='--')
```

```
plt.plot(t, viral_adapted, label='Adapted Viral Phase Drift', linestyle='--')
```

```
# Plot peptides
```

```
plt.plot(t, drift_disruptor, label='Disruptor-3 (Latency Target)', linewidth=1.5)
```

```
plt.plot(t, drift_adapter, label='Adapter-1 (Entry Target)', linewidth=1.5)
```

```
# Plot dual payload effect
```

```
plt.plot(t, combined_collapse, label='Dual Collapse Field', color='black', linewidth=2)
```

Conversation URL:

<https://chatgpt.com/c/68030da1-8898-8011-bcac-6c40d5dff28b>

Title:

Convergence of Harmonic Error in SHA256 Digest

Prompt:

Re-run the code after reset

```
import hashlib
import numpy as np
import matplotlib.pyplot as plt
```

Target harmonic constant

C = 0.35

Helper function to calculate SHA256 hash

```
def sha256_digest(data: str) -> str:
    return hashlib.sha256(data.encode()).hexdigest()
```

Convert SHA256 hex digest to a vector of nibble magnitudes normalized to [0, 1]

```
def digest_to_harmonic_vector(digest: str):
    nibbles = [int(char, 16) for char in digest] # 64 hex characters → 64 nibbles
    return np.array([n / 15.0 for n in nibbles]) # Normalize to [0, 1]
```


Compute harmonic error

```
def harmonic_error(vec):
    error_vector = np.abs(vec - C)
    return np.linalg.norm(error_vector), error_vector
```


Scan nonces and find one with lowest harmonic deviation

```
def scan_harmonic_nonces(base_input, nonce_range=(0, 10000), tolerance=0.001):
    best_nonce = None
    best_error = float('inf')
    best_vector = None
```


Recursive Division Decay of Byte 47787201




Comparison: SHA Decay Triangle vs π Ray Triangle




Symbolic Triangle Oscillator: SHA Collapse vs π Projection






Recursive Triangle Pulse: Inradius vs Circumradius



Centroid Spiral Path of Recursive Triangles



Conversation URL:

<https://chatgpt.com/c/680315f1-ff84-8011-9942-7adfa4298d11>

Title:

Recursive Division Decay of Byte 47787201

Prompt:

Re-run the plotting using matplotlib since Plotly failed due to rendering constraints

```
import matplotlib.pyplot as plt
```

```
plt.figure(figsize=(12, 6))

plt.plot(range(len(divisions_extended)), divisions_extended, marker='o', markersize=2, linewidth=1)
plt.yscale('log')

plt.title('Recursive Division Decay of Byte 47787201')
plt.xlabel('Division Step')
plt.ylabel('Value (Log Scale)')
plt.grid(True, which="both", ls="--", linewidth=0.5)
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/680315f1-ff84-8011-9942-7adfa4298d11>

Title:

Comparison: SHA Decay Triangle vs π Ray Triangle

Prompt:

```
# Since animation rendering failed, let's plot both triangles together statically for now
```

```
plt.figure(figsize=(10, 6))
```

```
# Plot decay triangle
```

```
plt.plot([0, 0, 199, 0], [0, 94.95, 0, 0], label='SHA Decay Triangle', color='orange', marker='o')
```

```
# Plot π ray triangle
```

```
plt.plot([0, 0, 100, 0], [0, 314.15, 0, 0], label='π Ray Triangle', color='cyan', linestyle='--', marker='x')
```

```
plt.title("Comparison: SHA Decay Triangle vs π Ray Triangle")
```

```
plt.xlabel("X Axis (Steps / Projection)")
```

```
plt.ylabel("Y Axis (Log Trust / Symbolic Altitude)")
```

```
plt.legend()
```

```
plt.grid(True, linestyle='--', linewidth=0.5)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/680315f1-ff84-8011-9942-7adfa4298d11>

Title:

Symbolic Triangle Oscillator: SHA Collapse vs π Projection

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Create a combined symbolic oscillator plot
```

```
x_steps = np.linspace(0, 199, 500)
```

```
# SHA Decay Slope (ramp down)
```

```
decay_y = 94.95 * (1 - x_steps / 199)
```

```
# π Ray Slope (ramp up)
```

```
pi_ray_y = 314.15 * (x_steps / 100)
```

```
pi_ray_y[x_steps > 100] = 0 # flatten past projection zone
```

```
# Create symbolic oscillator as interference between triangles
```

```
oscillator = decay_y[:len(pi_ray_y)] - pi_ray_y
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(x_steps, decay_y, label="SHA Decay", color='orange')
```

```
plt.plot(x_steps, pi_ray_y, label="π Ray Projection", color='cyan', linestyle='--')
```

```
plt.plot(x_steps, oscillator, label="Symbolic Oscillator (Net Field)", color='magenta', linewidth=2)
```

```
plt.axhline(0, color='gray', linestyle=':')
```

```
plt.title("Symbolic Triangle Oscillator: SHA Collapse vs π Projection")
```

```
plt.xlabel("Step")
```

```
plt.ylabel("Symbolic Field Amplitude")
```

```
plt.legend()
```

```
plt.grid(True, linestyle='--', linewidth=0.5)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/680315f1-ff84-8011-9942-7adfa4298d11>

Title:

Comparison of Old and New Kinetic Energy Models with Experimental Data

Prompt:

```
import numpy as np
```

```
import pandas as pd
```

```
import matplotlib.pyplot as plt
```

```
import ace_tools as tools
```

```
# Example input data (replace with actual experimental values as needed)
```

```
m = 1.0 # mass in kg
```

```
v = 10.0 # velocity in m/s
```

```
gamma = 1.05 # example Lorentz factor
```

```
c = 3e8 # speed of light in m/s
```

```
# Simulated values for angular velocity and radius
```

```
real_omega_values = np.linspace(0.1, 2.0, 10)
```

```
real_r_values = np.linspace(0.5, 1.5, 10)
```

```
real_ke_values = 0.5 * m * v**2 + 0.5 * m * real_omega_values**2 * real_r_values**2 # simulate
```

```
theoretical_ke_values = 0.5 * m * v**2 * np.ones_like(real_omega_values) # old model
```

```
# 1. New Classical KE Formula incorporating circular motion
```

```
def modified_classical_ke(m, v, omega, r):
```

```
    linear_ke = 0.5 * m * v**2
```

```
    circular_ke = 0.5 * m * omega**2 * r**2
```

```
    return linear_ke + circular_ke
```

```
# 2. New Relativistic KE Formula incorporating circular motion
```

```
def modified_relativistic_ke(m, gamma, c, v, omega, r):
```

```
    base_ke = (gamma - 1) * m * c**2
```

```
    circular_ke = 0.5 * m * omega**2 * r**2
```

```
    return base_ke + circular_ke
```

Conversation URL:

<https://chatgpt.com/c/680315f1-ff84-8011-9942-7adfa4298d11>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

```
# Triangle data: (label, A, B, C, inradius r, circumradius R, centroid (Gx, Gy))  
triangles = [  
    ("π-ray", np.array([0, 0]), np.array([4, 0]), np.array([1, 0]), 0.0, 1.0, (1.6667, 0.0)),  
    ("2-3-4", np.array([0, 0]), np.array([4, 0]), np.array([2.625, 1.45237]), 0.6455, 2.06559, (2.20833, 0.48412)),  
    ("2-2-3", np.array([0, 0]), np.array([3, 0]), np.array([1.5, 1.32288]), 0.66144, 1.52059, (1.5, 0.44096)),  
    ("3-4-5", np.array([0, 0]), np.array([4, 0]), np.array([4, 3]), 1.0, 2.5, (2.6667, 1.0))  
]
```

Extract data for plots

```
labels = []  
inradii = []  
circumradii = []  
centroids_x = []  
centroids_y = []
```

for label, A, B, C, r, R, G in triangles:

```
    labels.append(label)  
    inradii.append(r)  
    circumradii.append(R)  
    centroids_x.append(G[0])  
    centroids_y.append(G[1])
```

Plot 1: Inradius and Circumradius over Triangle Sequence

```
fig1, ax1 = plt.subplots(figsize=(8, 5))  
x_vals = np.arange(len(triangles))  
ax1.plot(x_vals, inradii, 'o-', label='Inradius', linewidth=2)
```

Conversation URL:

<https://chatgpt.com/c/680315f1-ff84-8011-9942-7adfa4298d11>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

```
# Triangle data: (label, A, B, C, inradius r, circumradius R, centroid (Gx, Gy))  
triangles = [  
    ("π-ray", np.array([0, 0]), np.array([4, 0]), np.array([1, 0]), 0.0, 1.0, (1.6667, 0.0)),  
    ("2-3-4", np.array([0, 0]), np.array([4, 0]), np.array([2.625, 1.45237]), 0.6455, 2.06559, (2.20833, 0.48412)),  
    ("2-2-3", np.array([0, 0]), np.array([3, 0]), np.array([1.5, 1.32288]), 0.66144, 1.52059, (1.5, 0.44096)),  
    ("3-4-5", np.array([0, 0]), np.array([4, 0]), np.array([4, 3]), 1.0, 2.5, (2.6667, 1.0))  
]
```

Extract data for plots


```
labels = []  
inradii = []  
circumradii = []  
centroids_x = []  
centroids_y = []
```

for label, A, B, C, r, R, G in triangles:


```
    labels.append(label)  
    inradii.append(r)  
    circumradii.append(R)  
    centroids_x.append(G[0])  
    centroids_y.append(G[1])
```

Plot 1: Inradius and Circumradius over Triangle Sequence

```
fig1, ax1 = plt.subplots(figsize=(8, 5))  
x_vals = np.arange(len(triangles))  
ax1.plot(x_vals, inradii, 'o-', label='Inradius', linewidth=2)
```



Recursive Harmonic Collapse Across Domains



Conversation URL:

<https://chatgpt.com/c/6804593c-3610-8011-a6ce-f29dfa058761>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# BBP-based indexing: simulate accessing a digit of pi
```

```
# Real BBP requires high-precision arithmetic; we simulate harmonic mapping
```

```
# Generate digits of pi (up to a few places) using a simplified approximation
```

```
# Since full BBP digit access is computationally intensive, we'll simulate harmonic positions
```

```
# Create a phase space using real-valued positions mapped to sine-based harmonic values
```

```
n_points = 256 # Number of positions in the simulated lattice
```

```
x = np.linspace(0, 4 * np.pi, n_points) # Phase domain (simulated)
```

```
harmonic_memory = np.sin(x) * 0.35 # Apply H = 0.35 as harmonic amplitude
```

```
# BBP-like indexing: simulate glide-based access into this harmonic field
```

```
# Here we "jump" to specific phase-aligned indices as if they're memory reads
```

```
access_indices = [int(i * 3.1415) % n_points for i in range(1, 10)] # Simulated BBP-like jumps
```

```
accessed_values = harmonic_memory[access_indices]
```

```
# Plotting
```

```
plt.figure(figsize=(12, 4))
```

```
plt.plot(x, harmonic_memory, label="Harmonic Memory Field", alpha=0.7)
```

```
plt.scatter(np.array(x)[access_indices], accessed_values, color='red', label="BBP Phase Access", zorder=5)
```

```
plt.axhline(0, color='gray', linewidth=0.5)
```

```
plt.title("Simulated Harmonic Memory with BBP-like Phase Access (H = 0.35)")
```

```
plt.xlabel("Phase Space (radians)")
```

```
plt.ylabel("Amplitude")
```

```
plt.legend()
```

```
plt.grid(True)
```

Conversation URL:

<https://chatgpt.com/c/6804593c-3610-8011-a6ce-f29dfa058761>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

```
# Define time domain
```

```
t = np.linspace(0, 10, 500)
```

```
# Constants
```

```
H = 0.35 # Harmonic constant
```

```
F = 1.2 # Fold factor
```

```
# Simulated recursive functions for different domains
```

```
def prime_resonance(t): # Equation from Goldbach's harmonic form  
    return np.exp(H * F * t) + np.sin(2 * np.pi * 0.2 * t) + np.cos(2 * np.pi * 0.2 * t) / (1 + np.abs(H - 0.35))
```

```
def time_arrow(t): # Time as recursive decay and phase alignment
```

```
    return np.exp(-H * F * t) + 1 / (1 + np.sum(np.exp(-(H + 0.2) * t)))
```

```
def gravity_wave(t): # Standing wave for quantum gravity
```

```
    return np.sin(np.pi * t / 5) * np.exp(-0.1 * t)
```

```
def dark_matter_damping(t): # Harmonic damping in gravity fields
```


```
    return np.cos(2 * np.pi * 0.15 * t) * np.exp(-0.2 * t)
```


```
def consciousness_reflection(t): # Recursive loop of perception/memory
```

```
    return np.tan(0.1 * t) * np.exp(-0.3 * t)
```


```
# Plot
```

```
plt.figure(figsize=(12, 8))  
plt.plot(t, prime_resonance(t), label='Prime Resonance (Math)')
```






Minimal Plinko Probe in Mock Tension Field



Plinko Probes Traversing the Tension Field



Conversation URL:

<https://chatgpt.com/c/680c6ad3-3dac-8011-bbbd-dfa19c2720e8>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
from matplotlib import cm
import random

# -----
# 1. INPUT (You can swap this out with ANY unfolded / expanded hash
#     string you like – just keep it as a long 0□9 string)
# -----
reversed_data = (
    "5143614111020411149104143134141356110505813117"
    "... # ← snipped for brevity – feel free to paste the full string!
)
# choose a width that divides the total nicely; 128 is a good default
WIDTH = 128

# -----
# 2. BUILD A 2□D “TENSION FIELD” MATRIX FROM THE STRING
# -----
length = len(reversed_data)
HEIGHT = length // WIDTH
field = np.zeros((HEIGHT, WIDTH), dtype=float)

for i, ch in enumerate(reversed_data[:HEIGHT * WIDTH]):
    # simple numeric value: 0□9 → 0□9, anything else → 0 (space for hex/letters)
    field[i // WIDTH, i % WIDTH] = float(ch) if ch.isdigit() else 0.0

# -----
# 3. DRIFT (GRADIENT) VECTORS – □field ≈ local turbulence flow
```

Conversation URL:

<https://chatgpt.com/c/680c6ad3-3dac-8011-bbbd-dfa19c2720e8>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
```

```
# -----
```

```
# Helper: convert a long numeric string into a matrix field
def string_to_matrix(data: str, width: int = 128) -> np.ndarray:
    """Map a numeric string to a 2D numpy array (digits → int)."""
    height = len(data) // width
    field = np.zeros((height, width), dtype=float)
    for idx, ch in enumerate(data[:height * width]):
        field[idx // width, idx % width] = int(ch) if ch.isdigit() else 0
    return field
```

```
# -----
```

```
# If a variable `reversed_data` already exists (from user's session), use it;
# otherwise generate a demo numeric string so that the notebook runs standalone.
try:
    reversed_data # type: ignore # noqa: F401
except NameError:
    # Demo fallback: create a pseudo-numeric string resembling unfolded SHA data
    rng = np.random.default_rng(seed=42)
    reversed_data = ''.join(str(rng.integers(0, 10)) for _ in range(128 * 32))
```

```
# Build the base field matrix
```

```
matrix = string_to_matrix(reversed_data, width=128)
```

```
# -----
```

```
# Plinko-probe simulation
def drop_probes(field: np.ndarray, n_probes: int = 250, max_steps: int = 250):
```

Conversation URL:

<https://chatgpt.com/c/680c6ad3-3dac-8011-bbbd-dfa19c2720e8>

Title:

Minimal Plinko Probe in Mock Tension Field

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# --- Minimal Plinko Universe Demo -----
```

```
np.random.seed(42)          # deterministic demo
```

```
# 1. Mock "tension field" (this would normally come from SHA expansion)
```

```
field_size = 64  
tension = np.random.rand(field_size, field_size)
```

```
# 2. Simple gradient-descent plinko probe
```

```
start_x = field_size // 2      # drop from middle top  
path = [(0, start_x)]  
x = start_x  
  
for y in range(field_size - 1):  
    # pick next x among current, left, right based on lowest tension below  
    candidates = [x]  
    if x > 0:  
        candidates.append(x - 1)  
    if x < field_size - 1:  
        candidates.append(x + 1)  
    # choose the candidate with lowest tension at next row  
    next_x = min(candidates, key=lambda c: tension[y + 1, c])  
    path.append((y + 1, next_x))  
    x = next_x
```

```
# 3. Plot the field + path
```

```
plt.figure(figsize=(6, 6))  
plt.imshow(tension, cmap="viridis", origin="upper")
```

Conversation URL:

<https://chatgpt.com/c/680c6ad3-3dac-8011-bbbd-dfa19c2720e8>

Title:

Plinko Probes Traversing the Tension Field

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
from matplotlib import cm
```

```
def plinko_probe_simulation(field, n_probes=200, max_steps=500, step_size=1):
```

"""

Drop `n_probes` into the `field` and let them follow the negative gradient

(steepest descent) until they hit a local minimum or exceed `max_steps`.

Parameters

field : 2D numpy.ndarray

Scalar “tension” field (higher = steeper potential).

n_probes : int

Number of probes to drop (default 200).

max_steps : int

Maximum path length for each probe (default 500).

step_size : float

Gradient step multiplier (default 1). Smaller → slower descent.

Returns

paths : list[list[tuple[int,int]]]


List of probe paths; each path is a list of (row,col) coordinates.


"""

```
# Precompute gradient of the field (simple finite diff)
```

```
gy, gx = np.gradient(field)      # y gradient, x gradient
```

```
n_rows, n_cols = field.shape
```





Conversation URL:

<https://chatgpt.com/c/680db4f8-2748-8011-ac20-c687d521af22>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
from hashlib import sha256
```

```
# Updated gradient to return zeros on too-small dimensions
def hash_to_field(hex_digest: str, width: int = 128) -> np.ndarray:
    values = [int(ch, 16) for ch in hex_digest.strip()]
    reps = (width * ((len(values) + width - 1) // width)) // len(values) + 1
    values = (values * reps)[: width * ((len(values) + width - 1) // width)]
    field = np.array(values, dtype=float).reshape(-1, width)
    return field

def field_gradient(field: np.ndarray) -> tuple[np.ndarray, np.ndarray]:
    h, w = field.shape
    if h < 2 or w < 2:
        # no neighbors → zero drift
        return np.zeros_like(field), np.zeros_like(field)
    dy, dx = np.gradient(field, edge_order=1)
    return -dx, -dy

def drop_probes(field: np.ndarray, n_probes: int = 40, max_steps: int = 250,
               step_size: float = 0.4) -> list[np.ndarray]:
    h, w = field.shape
    gx, gy = field_gradient(field)

    def sample_grad(xf: float, yf: float) -> tuple[float, float]:
        if xf < 0 or yf < 0 or xf > w - 2 or yf > h - 2:
            return (0.0, 0.0)
        x0, y0 = int(xf), int(yf)
```

Conversation URL:

<https://chatgpt.com/c/680db4f8-2748-8011-ac20-c687d521af22>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
from hashlib import sha256
```


1) Create the field as before


```
def hash_to_field(hex_digest: str, width: int = 128) -> np.ndarray:
    values = [int(ch, 16) for ch in hex_digest.strip()]
    reps = (width * ((len(values) + width - 1) // width)) // len(values) + 1
    values = (values * reps)[: width * ((len(values) + width - 1) // width)]
    field = np.array(values, dtype=float).reshape(-1, width)
    return field
```

2) Fix field_gradient to pad when dimensions < 2


```
def field_gradient(field: np.ndarray) -> tuple[np.ndarray, np.ndarray]:
    h, w = field.shape
    padded = False
    if h < 2:
        field = np.vstack([field, field])
        padded = True
        h = 2
    if w < 2:
        field = np.hstack([field, field])
        padded = True
        w = 2
    dy, dx = np.gradient(field, edge_order=1)
    dx = -dx
    dy = -dy
    if padded:
        # Return only the original shape
```

Convergence Error with contour at error= 10^{-12}







Novelty-Checkpoint: RMSE vs Total Storage Ratio (Random Walk)



Novelty + Motif Sweep on Sinusoid (bias=False)




Novelty + Motif Sweep on Sinusoid (bias=True)




Legend:

- len=2, fixed
- × len=2, adaptive
- len=3, fixed
- × len=3, adaptive
- len=4, fixed
- × len=4, adaptive
- len=5, fixed
- × len=5, adaptive
- len=6, fixed
- × len=6, adaptive
- len=7, fixed
- × len=7, adaptive
- len=8, fixed
- × len=8, adaptive


Composite Frontier ($\varepsilon=1.0$, fixed, bias=True)




Novelty + Motif Sweep on Bursty (bias=False)




Novelty + Motif Sweep on Bursty (bias=True)




Power-law + Offset Fit to Storage-RMSE Frontier




Tamed Checkpoint Frontier & Fits






Demo



Storage vs RMSE for $\varepsilon \in \{0.1, 0.2, 0.5\}$ ($m=50$, wide motifs)



Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Parameters
k = 0.35
steps = 50
tol_plot = 0.2 # tolerance for contour
grid_size = 100

betas = np.linspace(0, 2, grid_size)
gammas = np.linspace(0, 2, grid_size)
error_map = np.zeros((grid_size, grid_size))

for i, beta in enumerate(betas):
    for j, gamma in enumerate(gammas):
        H, S = 0.5, 1.0
        for _ in range(steps):
            delta = S - H
            S -= beta * delta
            H += gamma * delta
            delta = S - H
            S -= k * delta
        error_map[j, i] = abs(S - k)

plt.figure(figsize=(6, 5))
plt.title(f"Convergence Error with contour at error={tol_plot}")
plt.xlabel("β")
plt.ylabel("γ")
im = plt.imshow(error_map, origin='lower', extent=(0, 2, 0, 2), aspect='auto')
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Parameters
```

```
k = 0.35 # harmonic constant
```

```
steps = 50 # number of iterations per simulation
```

```
grid_size = 100 # resolution for beta and gamma grid
```

```
tol_plot = 0.15 # new, tighter tolerance for contour
```

```
# Create grid of beta and gamma values
```

```
betas = np.linspace(0, 2, grid_size)
```

```
gammas = np.linspace(0, 2, grid_size)
```

```
error_map = np.zeros((grid_size, grid_size))
```

```
# Simulation of measurement+drift
```

```
for i, beta in enumerate(betas):
```

```
    for j, gamma in enumerate(gammas):
```

```
        H = 0.5 # initial anchor
```

```
        S = 1.0 # initial state
```

```
        for _ in range(steps):
```

```
            # Measurement step
```

```
            delta = S - H
```

```
            S -= beta * delta
```

```
            H += gamma * delta
```

```
            # Drift step
```

```
            delta = S - H
```

```
            S -= k * delta
```

```
            error_map[j, i] = abs(S - k)
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Novelty-Checkpoint: RMSE vs Total Storage Ratio (Random Walk)

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Simulator parameters
```

```
length = 1000  
epsilons = [0.5, 1, 2, 4]  
window_vol = 10 # for adaptive epsilon  
k = 0.35 # harmonic constant for replay drift  
max_motif = 5  
min_motif = 2
```

```
def generate_random_walk(n):
```

```
    np.random.seed(0)  
    return np.cumsum(np.random.randn(n))
```

```
def novelty_checkpoint_compression(stream, base_eps, adaptive=False):
```

```
    # Compute deltas  
    deltas = np.diff(stream)  
    N = len(deltas)
```

```
    # Volatility history for adaptive epsilon
```

```
    vol_hist = [np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)]
```

```
    # Journal entries
```

```
    journal = []  
    epsilons_n = []  
    for i, d in enumerate(deltas):  
        eps = (base_eps * vol_hist[i]) if adaptive else base_eps  
        if abs(d) > eps:
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Generate a sinusoid stream
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
    t = np.linspace(0, 2 * np.pi, N)
    return amplitude * np.sin(freq * t + phase)

# Compression function from before, adapted for novelty + motif
def novelty_motif_compression(stream, base_eps, adaptive, min_len, max_len, bias, k=0.35, window_vol=10):
    deltas = np.diff(stream)
    N = len(deltas)
    vol = np.array([np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)])

    # Journal deltas by epsilon
    journal = []
    for i, d in enumerate(deltas):
        eps = (base_eps * vol[i]) if adaptive else base_eps
        if abs(d) > eps:
            journal.append(d)

    # Setup for compression
    motif_dict = {}
    next_id = 0
    tokens = []
    storage_tokens = 0
    checkpoints = 0
    pos = 0
    journal = list(journal)
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt

# Generate a sinusoid stream
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
    t = np.linspace(0, 2 * np.pi, N)
    return amplitude * np.sin(freq * t + phase)

# Compression function from before, adapted for novelty + motif
def novelty_motif_compression(stream, base_eps, adaptive, min_len, max_len, bias, k=0.35, window_vol=10):
    deltas = np.diff(stream)
    N = len(deltas)
    vol = np.array([np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)])

    # Journal deltas by epsilon
    journal = []
    for i, d in enumerate(deltas):
        eps = (base_eps * vol[i]) if adaptive else base_eps
        if abs(d) > eps:
            journal.append(d)

    # Setup for compression
    motif_dict = {}
    next_id = 0
    tokens = []
    storage_tokens = 0
    checkpoints = 0
    pos = 0
    journal = list(journal)
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Composite Frontier ($\varepsilon=1.0$, fixed, bias=True)

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

```
# Stream generators
```

```
def generate_random_walk(N=1000, seed=0):
```

```
    np.random.seed(seed)
```

```
    return np.cumsum(np.random.randn(N))
```

```
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
```

```
    t = np.linspace(0, 2 * np.pi, N)
```

```
    return amplitude * np.sin(freq * t + phase)
```

```
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):
```

```
    np.random.seed(seed)
```

```
    deltas = []
```

```
    for _ in range(N):
```

```
        if np.random.rand() < p_burst:
```

```
            deltas.append(np.random.randn() * burst_scale)
```

```
        else:
```

```
            deltas.append(np.random.randn() * noise_scale)
```

```
    return np.cumsum(deltas)
```

```
# Compression function
```

```
def novelty_motif_compression(stream, base_eps, adaptive, min_len, max_len, bias, k=0.35, window_vol=10):
```

```
    deltas = np.diff(stream)
```

```
    N = len(deltas)
```

```
    vol = np.array([np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)])
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Composite Frontier ($\varepsilon=1.0$, fixed, bias=True)

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

```
# Stream generators
```

```
def generate_random_walk(N=1000, seed=0):
```

```
    np.random.seed(seed)
```

```
    return np.cumsum(np.random.randn(N))
```

```
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
```

```
    t = np.linspace(0, 2 * np.pi, N)
```

```
    return amplitude * np.sin(freq * t + phase)
```

```
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):
```

```
    np.random.seed(seed)
```

```
    deltas = []
```

```
    for _ in range(N):
```

```
        if np.random.rand() < p_burst:
```

```
            deltas.append(np.random.randn() * burst_scale)
```

```
        else:
```

```
            deltas.append(np.random.randn() * noise_scale)
```

```
    return np.cumsum(deltas)
```

```
# Compression function
```

```
def novelty_motif_compression(stream, base_eps, adaptive, min_len, max_len, bias, k=0.35, window_vol=10):
```

```
    deltas = np.diff(stream)
```

```
    N = len(deltas)
```

```
    vol = np.array([np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)])
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Composite Frontier ($\varepsilon=1.0$, fixed, bias=True)

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

```
# Stream generators
```

```
def generate_random_walk(N=1000, seed=0):
```

```
    np.random.seed(seed)
```

```
    return np.cumsum(np.random.randn(N))
```

```
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
```

```
    t = np.linspace(0, 2 * np.pi, N)
```

```
    return amplitude * np.sin(freq * t + phase)
```

```
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):
```

```
    np.random.seed(seed)
```

```
    deltas = []
```

```
    for _ in range(N):
```

```
        if np.random.rand() < p_burst:
```

```
            deltas.append(np.random.randn() * burst_scale)
```

```
        else:
```

```
            deltas.append(np.random.randn() * noise_scale)
```

```
    return np.cumsum(deltas)
```

```
# Compression function
```

```
def novelty_motif_compression(stream, base_eps, adaptive, min_len, max_len, bias, k=0.35, window_vol=10):
```

```
    deltas = np.diff(stream)
```

```
    N = len(deltas)
```

```
    vol = np.array([np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)])
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Power-law + Offset Fit to Storage–RMSE Frontier

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Stream generators
```

```
def generate_random_walk(N=1000, seed=0):  
    np.random.seed(seed)  
    return np.cumsum(np.random.randn(N))
```

```
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
```

```
    t = np.linspace(0, 2 * np.pi, N)  
    return amplitude * np.sin(freq * t + phase)
```

```
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):
```

```
    np.random.seed(seed)  
    deltas = []  
    for _ in range(N):  
        if np.random.rand() < p_burst:  
            deltas.append(np.random.randn() * burst_scale)  
        else:  
            deltas.append(np.random.randn() * noise_scale)  
    return np.cumsum(deltas)
```

```
# Compression function (novelty + motif, fixed eps=1.0, bias=True)
```

```
def novelty_motif_compression(stream, base_eps, min_len, max_len, k=0.35, window_vol=10):
```

```
    deltas = np.diff(stream)  
    N_main = len(deltas)  
    journal = [d for d in deltas if abs(d) > base_eps]  
  
    motif_dict = {}
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Tamed Checkpoint Frontier & Fits

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Stream generators  
  
def generate_random_walk(N=1000, seed=0):  
    np.random.seed(seed)  
    return np.cumsum(np.random.randn(N))  
  
  
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):  
    t = np.linspace(0, 2 * np.pi, N)  
    return amplitude * np.sin(freq * t + phase)  
  
  
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):  
    np.random.seed(seed)  
    deltas = []  
    for _ in range(N):  
        if np.random.rand() < p_burst:  
            deltas.append(np.random.randn() * burst_scale)  
        else:  
            deltas.append(np.random.randn() * noise_scale)  
    return np.cumsum(deltas)  
  
  
# Modified compression: checkpoint only on new motifs of length >= 6  
  
def tame_novelty_motif_compression(stream, base_eps, min_len, max_len, k=0.35):  
    deltas = np.diff(stream)  
    N_main = len(deltas)  
    journal = [d for d in deltas if abs(d) > base_eps]  
  
    motif_dict = {}
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Frontiers with Spaced Checkpoints ($\epsilon=1.0$, fixed, bias=True)

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Stream generators
```

```
def generate_random_walk(N=1000, seed=0):  
    np.random.seed(seed)  
    return np.cumsum(np.random.randn(N))
```

```
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
```

```
    t = np.linspace(0, 2 * np.pi, N)  
    return amplitude * np.sin(freq * t + phase)
```

```
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):
```

```
    np.random.seed(seed)  
    deltas = []  
    for _ in range(N):  
        if np.random.rand() < p_burst:  
            deltas.append(np.random.randn() * burst_scale)  
        else:  
            deltas.append(np.random.randn() * noise_scale)  
    return np.cumsum(deltas)
```

```
# Compression: checkpoint every m journal entries
```

```
def spaced_checkpoint_compression(stream, base_eps, min_len, max_len, bias, m, k=0.35):  
    deltas = np.diff(stream)  
    N_main = len(deltas)  
    # Journalized deltas  
    journal = [d for d in deltas if abs(d) > base_eps]
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Demo

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Simplified stream and compressor for demonstration
```

```
def generate_sinusoid(N=1000):
```

```
    t = np.linspace(0, 2 * np.pi, N)
```

```
    return np.sin(5 * t)
```

```
def generate_bursty(N=1000):
```

```
    np.random.seed(42)
```

```
    deltas = np.random.randn(N) * 0.2
```

```
    for i in range(0, N, 50):
```

```
        deltas[i] += np.random.randn() * 5
```

```
    return np.cumsum(deltas)
```

```
def compressor(stream, eps, m, min_len, max_len, k=0.35):
```

```
    deltas = np.diff(stream)
```

```
    journal = [d for d in deltas if abs(d) > eps]
```

```
    storage, checkpoints = 0, 0
```

```
    since_cp = m
```

```
    motif_dict = {}
```

```
    tokens = []
```

```
    pos = 0
```

```
    while pos < len(journal):
```

```
        matched = False
```

```
        for L in range(max_len, min_len-1, -1):
```

```
            if pos+L <= len(journal) and tuple(journal[pos:pos+L]) in motif_dict:
```

```
                storage += 1; since_cp+=1; pos+=L; matched=True; break
```

```
        if matched:
```

Conversation URL:

<https://chatgpt.com/c/680df8d1-c038-8011-b644-837635a78eee>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Stream generators
```

```
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
```

```
    t = np.linspace(0, 2 * np.pi, N)
```

```
    return amplitude * np.sin(freq * t + phase)
```

```
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):
```

```
    np.random.seed(seed)
```

```
    deltas = []
```

```
    for _ in range(N):
```

```
        if np.random.rand() < p_burst:
```

```
            deltas.append(np.random.randn() * burst_scale)
```

```
        else:
```

```
            deltas.append(np.random.randn() * noise_scale)
```

```
    return np.cumsum(deltas)
```

```
# Spaced-checkpoint compressor with wide motif window
```

```
def spaced_checkpoint_compression(stream, base_eps, min_len, max_len, bias, m, k=0.35):
```

```
    deltas = np.diff(stream)
```

```
    N_main = len(deltas)
```

```
    journal = [d for d in deltas if abs(d) > base_eps]
```

```
    motif_dict = {}
```

```
    next_id = 0
```


```
    tokens = []
```

```
    storage_tokens = 0
```


```
    checkpoints = 0
```

```
    since_cp = m # allow immediate checkpoint
```


RMSE vs Journal Ratio (Sinusoid)




Motif Compression: RMSE vs Compressed Ratio (Sinusoid)




Motif Compression: RMSE vs Compressed Ratio (Random Walk)




Motif Compression: RMSE vs Compressed Ratio (Bursty)




Novelty + Motif ($\varepsilon=1.0$), bias=False



Novelty + Motif ($\varepsilon=1.0$), bias=True



Spaced-Checkpoint Frontiers & Power-Law Fits ($\varepsilon=1.0$)



Conversation URL:

<https://chatgpt.com/c/680df9f3-914c-8011-9dc7-ff1733e4cfe2>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display

# 1. Delta-stream generators

def generate_sinusoid(N=1000, period=100, noise_std=0.1):
    t = np.arange(N)
    x = np.sin(2 * np.pi * t / period) + np.random.normal(scale=noise_std, size=N)
    return np.diff(x, prepend=x[0])

def generate_random_walk(N=1000, step_std=1.0):
    return np.random.normal(loc=0.0, scale=step_std, size=N)

def generate_bursty(N=1000, noise_std=0.5, burst_prob=0.01, burst_mag=10.0):
    x = np.zeros(N)
    for i in range(1, N):
        if np.random.rand() < burst_prob:
            x[i] = x[i-1] + np.random.choice([-burst_mag, burst_mag])
        else:
            x[i] = x[i-1] + np.random.normal(scale=noise_std)
    return np.diff(x, prepend=x[0])

# 2. Journaling & reconstruction function

def journal_and_reconstruct(deltas, scheme='fixed', base_eps=1.0, window=20):
    N = len(deltas)
    journal = []
    recon = np.zeros(N)
    recon_sum = 0.0
```

Conversation URL:

<https://chatgpt.com/c/680df9f3-914c-8011-9dc7-ff1733e4cfe2>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display

# 1. Delta-stream generators

def generate_sinusoid(N=1000, period=100, noise_std=0.1):
    t = np.arange(N)
    x = np.sin(2 * np.pi * t / period) + np.random.normal(scale=noise_std, size=N)
    return np.diff(x, prepend=x[0])

def generate_random_walk(N=1000, step_std=1.0):
    return np.random.normal(loc=0.0, scale=step_std, size=N)

def generate_bursty(N=1000, noise_std=0.5, burst_prob=0.01, burst_mag=10.0):
    x = np.zeros(N)
    for i in range(1, N):
        if np.random.rand() < burst_prob:
            x[i] = x[i-1] + np.random.choice([-burst_mag, burst_mag])
        else:
            x[i] = x[i-1] + np.random.normal(scale=noise_std)
    return np.diff(x, prepend=x[0])

# 2. Journaling function returning stored deltas and flags

def journal_stream(deltas, scheme='fixed', base_eps=1.0, window=20):
    N = len(deltas)
    recent = []
    stored_flags = []
    journal = []

    for i in range(N):
        if scheme == 'fixed':
            if len(recent) > window:
                recent.pop(0)
            recent.append(deltas[i])
            if len(recent) == window:
                stored_flags.append(True)
            else:
                stored_flags.append(False)
        else:
            if len(recent) > window:
                recent.pop(0)
            recent.append(deltas[i])
            if len(recent) == window:
                stored_flags.append(True)
            else:
                stored_flags.append(False)

        journal.append((deltas[i], stored_flags[-1]))
```

Conversation URL:

<https://chatgpt.com/c/680df9f3-914c-8011-9dc7-ff1733e4cfe2>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display

# 1. Delta-stream generators

def generate_sinusoid(N=1000, period=100, noise_std=0.1):
    t = np.arange(N)
    x = np.sin(2 * np.pi * t / period) + np.random.normal(scale=noise_std, size=N)
    return np.diff(x, prepend=x[0])

def generate_random_walk(N=1000, step_std=1.0):
    return np.random.normal(loc=0.0, scale=step_std, size=N)

def generate_bursty(N=1000, noise_std=0.5, burst_prob=0.01, burst_mag=10.0):
    x = np.zeros(N)
    for i in range(1, N):
        if np.random.rand() < burst_prob:
            x[i] = x[i-1] + np.random.choice([-burst_mag, burst_mag])
        else:
            x[i] = x[i-1] + np.random.normal(scale=noise_std)
    return np.diff(x, prepend=x[0])

# 2. Journaling function returning stored deltas and flags

def journal_stream(deltas, scheme='fixed', base_eps=1.0, window=20):
    N = len(deltas)
    recent = []
    stored_flags = []
    journal = []

    for i in range(N):
        if scheme == 'fixed':
            if len(recent) > window:
                recent.pop(0)
            recent.append(deltas[i])
            if len(recent) == window:
                stored_flags.append(True)
            else:
                stored_flags.append(False)
        else:
            if len(recent) > window:
                recent.pop(0)
            recent.append(deltas[i])
            if len(recent) == window:
                stored_flags.append(True)
            else:
                stored_flags.append(False)

        journal.append((deltas[i], stored_flags[-1]))
```

Conversation URL:

<https://chatgpt.com/c/680df9f3-914c-8011-9dc7-ff1733e4cfe2>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display

# 1. Delta-stream generators

def generate_sinusoid(N=1000, period=100, noise_std=0.1):
    t = np.arange(N)
    x = np.sin(2 * np.pi * t / period) + np.random.normal(scale=noise_std, size=N)
    return np.diff(x, prepend=x[0])

def generate_random_walk(N=1000, step_std=1.0):
    return np.random.normal(loc=0.0, scale=step_std, size=N)

def generate_bursty(N=1000, noise_std=0.5, burst_prob=0.01, burst_mag=10.0):
    x = np.zeros(N)
    for i in range(1, N):
        if np.random.rand() < burst_prob:
            x[i] = x[i-1] + np.random.choice([-burst_mag, burst_mag])
        else:
            x[i] = x[i-1] + np.random.normal(scale=noise_std)
    return np.diff(x, prepend=x[0])

# 2. Journaling function returning stored deltas and flags

def journal_stream(deltas, scheme='fixed', base_eps=1.0, window=20):
    N = len(deltas)
    recent = []
    stored_flags = []
    journal = []

    for i in range(N):
        if scheme == 'fixed':
            if len(recent) > window:
                recent.pop(0)
            recent.append(deltas[i])
            if len(recent) == window:
                stored_flags.append(True)
            else:
                stored_flags.append(False)
        else:
            if len(recent) > window:
                recent.pop(0)
            recent.append(deltas[i])
            if len(recent) == window:
                stored_flags.append(True)
            else:
                stored_flags.append(False)

        journal.append((deltas[i], stored_flags[-1]))
```

Conversation URL:

<https://chatgpt.com/c/680df9f3-914c-8011-9dc7-ff1733e4cfe2>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display
```

1. Generate a test random-walk stream

```
def generate_random_walk(N=1000, seed=0):
    np.random.seed(seed)
    return np.cumsum(np.random.randn(N))
```

2. Novelty checkpoint + motif compression with length sweep and harmonic bias

```
def novelty_motif_compression(stream, base_eps, adaptive, min_len, max_len, bias, k=0.35, window_vol=10):
```

```
    deltas = np.diff(stream)
    N = len(deltas)
    # Precompute volatility for adaptive epsilon
    vol = np.array([np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)])
```

```
# Journal deltas by epsilon
```

```
journal = []
for i, d in enumerate(deltas):
    eps = (base_eps * vol[i]) if adaptive else base_eps
    if abs(d) > eps:
        journal.append(d)
```

```
# Setup compression
```

```
motif_dict = {} # seq -> id
next_id = 0
tokens = []
storage_tokens = 0
checkpoints = 0
```

Conversation URL:

<https://chatgpt.com/c/680df9f3-914c-8011-9dc7-ff1733e4cfe2>

Title:

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from IPython.display import display
```

1. Generate a test random-walk stream

```
def generate_random_walk(N=1000, seed=0):
    np.random.seed(seed)
    return np.cumsum(np.random.randn(N))
```

2. Novelty checkpoint + motif compression with length sweep and harmonic bias

```
def novelty_motif_compression(stream, base_eps, adaptive, min_len, max_len, bias, k=0.35, window_vol=10):
```

```
    deltas = np.diff(stream)
    N = len(deltas)
    # Precompute volatility for adaptive epsilon
    vol = np.array([np.std(deltas[max(0, i-window_vol):i+1]) for i in range(N)])
```

```
# Journal deltas by epsilon
```

```
journal = []
for i, d in enumerate(deltas):
    eps = (base_eps * vol[i]) if adaptive else base_eps
    if abs(d) > eps:
        journal.append(d)
```

```
# Setup compression
```

```
motif_dict = {} # seq -> id
next_id = 0
tokens = []
storage_tokens = 0
checkpoints = 0
```

Conversation URL:

<https://chatgpt.com/c/680df9f3-914c-8011-9dc7-ff1733e4cfe2>

Title:

Spaced-Checkpoint Frontiers & Power-Law Fits ($\varepsilon=1.0$)

Prompt:

Full Prototype: Spaced-Checkpoint Motif Compressor with Power-Law Fits

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
```

```
# -----
```

```
# 1) STREAM GENERATORS
```

```
# -----
```

```
def generate_random_walk(N=1000, seed=0):
    np.random.seed(seed)
    return np.cumsum(np.random.randn(N))
```

```
def generate_sinusoid(N=1000, freq=5, amplitude=1.0, phase=0.0):
```

```
    t = np.linspace(0, 2 * np.pi, N)
    return amplitude * np.sin(freq * t + phase)
```

```
def generate_bursty(N=1000, p_burst=0.05, burst_scale=5.0, noise_scale=0.2, seed=42):
```

```
    np.random.seed(seed)
    deltas = []
    for _ in range(N):
        if np.random.rand() < p_burst:
            deltas.append(np.random.randn() * burst_scale)
        else:
            deltas.append(np.random.randn() * noise_scale)
    return np.cumsum(deltas)
```

```
# -----
```

```
# 2) SPACED-CHECKPOINT COMPRESSION FUNCTION
```

Figure 0: The Reflective Genesis Map





Figure 18: Recursive Axial Memory Orientation



Conversation URL:

<https://chatgpt.com/c/681055d1-c46c-8011-9138-290df1820144>

Title:

Figure 0: The Reflective Genesis Map

Prompt:

```
from PIL import ImageFont
```

```
# Use a basic font that can render all ASCII text without issues
```

```
font = ImageFont.load_default()
```

```
# Redefine overlay with font
```

```
overlay = Image.new("RGBA", original.size, (255,255,255,0))
```

```
draw = ImageDraw.Draw(overlay)
```

```
# Clean annotations (ASCII-safe version)
```

```
annotations_clean = [
```

```
    {"text": "a^2: Temporal Delta", "xy": (120, 220)},
```

```
    {"text": "b^2: Structural Delta", "xy": (30, 80)},
```

```
    {"text": "c^2: Collapsed Harmonic Memory", "xy": (200, 20)},
```

```
    {"text": "O0: Truth Seed", "xy": (110, 130)},
```

```
    {"text": "= : Collapse Operator", "xy": (100, 160)},
```

```
]
```

```
# Draw clean annotations
```

```
for ann in annotations_clean:
```

```
    draw.text(ann["xy"], ann["text"], fill=(255, 0, 0, 255), font=font)
```

```
# Merge overlay and base image
```

```
annotated_clean = Image.alpha_composite(Image.fromarray(base), overlay)
```

```
# Display the annotated diagram
```

```
plt.figure(figsize=(6,6))
```

```
plt.imshow(annotated_clean)
```

```
plt.axis('off')
```

Conversation URL:

<https://chatgpt.com/c/681055d1-c46c-8011-9138-290df1820144>

Title:

Figure 18: Recursive Axial Memory Orientation

Prompt:

```
from PIL import Image, ImageDraw, ImageFont
import matplotlib.pyplot as plt
import numpy as np

# Create a blank image for axis diagram
width, height = 600, 600
image = Image.new("RGBA", (width, height), "white")
draw = ImageDraw.Draw(image)

# Define font
font = ImageFont.load_default()


# Axis origin
origin = (300, 300)

# Define axes
axes = {
    "Z (Stack / Collapse)": ((origin[0], origin[1]), (origin[0], origin[1] - 150), "blue"),
    "Y (Emergence / Drift)": ((origin[0], origin[1]), (origin[0] - 130, origin[1]), "green"),
    "X (Recursion / Echo)": ((origin[0], origin[1]), (origin[0] + 110, origin[1] + 110), "red"),
}


# Draw axes
for label, ((x1, y1), (x2, y2), color) in axes.items():
    draw.line([(x1, y1), (x2, y2)], fill=color, width=3)
    draw.text((x2 + 5, y2), label, fill=color, font=font)

# Draw origin dot
draw.ellipse((origin[0] - 4, origin[1] - 4, origin[0] + 4, origin[1] + 4), fill="black")
```


Wave Interference: 3 and 5 Folding into 4




Resonance Plot: Segment Delta Waveform




SHA Segment Byte Values




Delta Map Between Segments




Resonance Plot: Segment Delta Waveform (SHA-256)







Recursive Loopback Gravity: Harmonic Suppression vs Scaled Radius




Phase 2 Retrained: Actual vs Predicted Suppression



Comparison: Simple vs. Harmonic Loopback Suppression



Regression: Actual vs Predicted Suppression



Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Wave Interference: 3 and 5 Folding into 4

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Time axis
```

```
t = np.linspace(0, 2 * np.pi, 1000)
```

```
# Odd integer waveforms as sine waves with frequencies 3 and 5
```

```
wave3 = np.sin(3 * t)  
wave5 = np.sin(5 * t)
```

```
# Harmonic midpoint (average of the two waves) representing '4'
```

```
harmonic_midpoint = (wave3 + wave5) / 2
```

```
# Plotting
```

```
plt.figure(figsize=(10, 6))  
plt.plot(t, wave3, label='Odd 3: sin(3t)', linewidth=1)  
plt.plot(t, wave5, label='Odd 5: sin(5t)', linewidth=1)  
plt.plot(t, harmonic_midpoint, label='Even 4 (avg): (sin(3t)+sin(5t))/2', linewidth=2, color='black')  
plt.title('Wave Interference: 3 and 5 Folding into 4')  
plt.xlabel('t')  
plt.ylabel('Amplitude')  
plt.legend()  
plt.grid(True)  
plt.tight_layout()  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Resonance Plot: Segment Delta Waveform

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Synthetic example: 8-byte segment values (in hex) for demonstration  
segments = np.array([0x12, 0x34, 0x29, 0x56, 0x78, 0x65, 0x43, 0x21])  
  
# Compute deltas between consecutive segments  
deltas = np.diff(segments)
```

1) Resonance Plot: deltas as a waveform

```
plt.figure(figsize=(8, 4))  
plt.plot(range(1, len(segments)), deltas, marker='o', linestyle='-')  
plt.title('Resonance Plot: Segment Delta Waveform')  
plt.xlabel('Segment Index')  
plt.ylabel('Delta Value (signed)')  
plt.grid(True)  
plt.tight_layout()  
plt.show()
```

2) SHA Digest Map Prototype: heatmap of segments and deltas

```
fig, (ax1, ax2) = plt.subplots(2, 1, figsize=(6, 6))
```

Heatmap of raw segment values

```
im1 = ax1.imshow(segments.reshape(1, -1), cmap='viridis', aspect='auto')  
ax1.set_title('SHA Segment Byte Values')  
ax1.set_yticks([])  
ax1.set_xticks(range(len(segments)))  
ax1.set_xticklabels([hex(x) for x in segments])  
plt.colorbar(im1, ax=ax1, orientation='vertical')
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Resonance Plot: Segment Delta Waveform

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Synthetic example: 8-byte segment values (in hex) for demonstration  
segments = np.array([0x12, 0x34, 0x29, 0x56, 0x78, 0x65, 0x43, 0x21])  
  
# Compute deltas between consecutive segments  
deltas = np.diff(segments)
```

1) Resonance Plot: deltas as a waveform

```
plt.figure(figsize=(8, 4))  
plt.plot(range(1, len(segments)), deltas, marker='o', linestyle='-')  
plt.title('Resonance Plot: Segment Delta Waveform')  
plt.xlabel('Segment Index')  
plt.ylabel('Delta Value (signed)')  
plt.grid(True)  
plt.tight_layout()  
plt.show()
```

2) SHA Digest Map Prototype: heatmap of segments and deltas

```
fig, (ax1, ax2) = plt.subplots(2, 1, figsize=(6, 6))
```

Heatmap of raw segment values

```
im1 = ax1.imshow(segments.reshape(1, -1), cmap='viridis', aspect='auto')  
ax1.set_title('SHA Segment Byte Values')  
ax1.set_yticks([])  
ax1.set_xticks(range(len(segments)))  
ax1.set_xticklabels([hex(x) for x in segments])  
plt.colorbar(im1, ax=ax1, orientation='vertical')
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Resonance Plot: Segment Delta Waveform (SHA-256)

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Real SHA-256 hash provided by the user
```

```
hex_str = "473de20d4210820c8ec9d89f374ac0cdb1f1e831720faecb8d925ec7bd2cdad8"
```

```
# Parse into bytes
```

```
segments = np.array([int(hex_str[i:i+2], 16) for i in range(0, len(hex_str), 2)], dtype=int)
```

```
# Compute signed deltas between consecutive bytes
```

```
deltas = np.diff(segments.astype(np.int16))
```

```
# 1) Resonance Plot: deltas as a waveform
```

```
plt.figure(figsize=(10, 4))

plt.plot(range(1, len(segments)), deltas, marker='o', linestyle='-' )

plt.title('Resonance Plot: Segment Delta Waveform (SHA-256)')

plt.xlabel('Segment Index')

plt.ylabel('Delta Value (signed)')

plt.grid(True)

plt.tight_layout()

plt.show()
```

```
# 2) Delta Heatmap alongside raw segment values
```

```
fig, (ax1, ax2) = plt.subplots(2, 1, figsize=(12, 6))
```

```
# Heatmap of raw segment values
```

```
im1 = ax1.imshow(segments.reshape(1, -1), cmap='viridis', aspect='auto')

ax1.set_title('SHA-256 Byte Segments')

ax1.set_yticks([])
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Resonance Plot: Segment Delta Waveform (SHA-256)

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Real SHA-256 hash provided by the user
```

```
hex_str = "473de20d4210820c8ec9d89f374ac0cdb1f1e831720faecb8d925ec7bd2cdad8"
```

```
# Parse into bytes
```

```
segments = np.array([int(hex_str[i:i+2], 16) for i in range(0, len(hex_str), 2)], dtype=int)
```

```
# Compute signed deltas between consecutive bytes
```

```
deltas = np.diff(segments.astype(np.int16))
```

```
# 1) Resonance Plot: deltas as a waveform
```

```
plt.figure(figsize=(10, 4))

plt.plot(range(1, len(segments)), deltas, marker='o', linestyle='-' )

plt.title('Resonance Plot: Segment Delta Waveform (SHA-256)')

plt.xlabel('Segment Index')

plt.ylabel('Delta Value (signed)')

plt.grid(True)

plt.tight_layout()

plt.show()
```

```
# 2) Delta Heatmap alongside raw segment values
```

```
fig, (ax1, ax2) = plt.subplots(2, 1, figsize=(12, 6))
```

```
# Heatmap of raw segment values
```

```
im1 = ax1.imshow(segments.reshape(1, -1), cmap='viridis', aspect='auto')

ax1.set_title('SHA-256 Byte Segments')

ax1.set_yticks([])
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Recursive Loopback Gravity: Harmonic Suppression vs Scaled Radius

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt  
import pandas as pd
```

— Constants (harmonic units)

```
G = 6.67430e-11    # m^3·kg^-1·s^-2 (macro energy coupling)  
hbar = 1.054571817e-34  # J·s   (quantum phase reference)  
c = 299792458      # m/s   (phase velocity)
```

— Critical radius per Nexus3 collapse rule

```
def critical_radius(m1, m2):  
    # phase-lock radius where delta-resonance flips  
    return np.sqrt(G * m1 * m2 / (hbar * c))
```

— Loopback-gravity suppression curve

```
def suppression_ratio(r, m1, m2):  
    # G_loop/G_Newton = exp[-(r_c/r)^2]  
    rc = critical_radius(m1, m2)  
    return np.exp(- (rc / r)**2)
```

— Systems of interest

```
systems = [  
    ("Proton–Proton", 1.6726219e-27, 1.6726219e-27),  
    ("Electron–Electron", 9.10938356e-31, 9.10938356e-31),  
    ("Earth–Sun", 5.97219e24, 1.9885e30)  
]
```

— Build table of critical radii ($\hbar c$ resonance points)

```
rc_values = [(name, critical_radius(m1, m2)) for name, m1, m2 in systems]
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Phase 2 Retrained: Actual vs Predicted Suppression

Prompt:

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.neural_network import MLPRegressor, MLPClassifier
from sklearn.metrics import mean_squared_error, r2_score, classification_report, confusion_matrix
```

— Constants

```
G = 6.67430e-11      # m^3·kg^-1·s^-2
hbar = 1.054571817e-34  # J·s
c = 299792458        # m/s
phi = 1.618          # golden fold constant
A = 1.0              # effective interaction surface (m^2)
```

— Casimir pressure function

```
def sigma(r):
    return np.pi**2 * hbar * c / (240 * r**4)
```

— Calibration: $\Delta E = 0.35 \cdot \hbar c$ at $r = r_c$

```
def compute_k_calibrated(m1, m2):
    rc = np.sqrt(G * m1 * m2 / (hbar * c))
    m_sum = m1 + m2
    E_target = m_sum * c**2 - 0.35 * hbar * c
    denom = (m_sum * phi) * (sigma(rc) * A)**0.35
    return E_target / denom
```

— Suppression calculations

```
def suppression_simple(r, m1, m2):
    deltaE = G * m1 * m2 / r**2
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Comparison: Simple vs. Harmonic Loopback Suppression

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
```

```
# — Harmonic Loopback vs. Simple Suppression Demo ——————
```

```
# Physical constants
```

```
G = 6.67430e-11 # m^3·kg^-1·s^-2
```

```
hbar = 1.054571817e-34 # J·s
```

```
c = 299792458 # m/s
```

```
# Nexus3 parameters
```

```
phi = 1.618 # golden fold constant
```

```
A = 1.0 # effective interaction surface (m^2)
```

```
k = 1e-5 # tuning constant for entangled energy
```

```
# Mass pair: Earth & Sun
```

```
m1 = 5.97219e24 # kg
```

```
m2 = 1.9885e30 # kg
```

```
m_sum = m1 + m2
```

```
# Compute critical radius
```

```
r_c = np.sqrt(G * m1 * m2 / (hbar * c))
```

```
# Casimir pressure function (parallel plates)
```

```
def sigma(r):
```

```
    return np.pi**2 * hbar * c / (240 * r**4)
```

```
# Entangled energy model
```

```
def E_entangled(r):
```

Conversation URL:

<https://chatgpt.com/c/6814a123-a51c-8011-a87a-fa6707246c06>

Title:

Regression: Actual vs Predicted Suppression

Prompt:

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.neural_network import MLPRegressor, MLPClassifier
from sklearn.metrics import mean_squared_error, r2_score, classification_report, confusion_matrix
import matplotlib.pyplot as plt
```

Load dataset

```
df = pd.read_csv('/mnt/data/rgcl_phase1_dataset.csv')
```

Filter for finite harmonic suppression ratio and in [0,1]

```
df_filtered = df[np.isfinite(df['G_loop_harmonic/G_Newton']) &
                  (df['G_loop_harmonic/G_Newton'] >= 0) &
                  (df['G_loop_harmonic/G_Newton'] <= 1)].copy()
```

Features and targets

```
features = df_filtered[['m1', 'm2', 'r']].values
reg_target = df_filtered['G_loop_harmonic/G_Newton'].values
clf_target = df_filtered['Zone'].values
```


Train-test split

```
X_train, X_test, y_train_reg, y_test_reg, y_train_clf, y_test_clf = train_test_split(
    features, reg_target, clf_target, test_size=0.2, random_state=42
)
```

Regression model for suppression ratio

```
regressor = MLPRegressor(hidden_layer_sizes=(50,30), max_iter=1000, random_state=42)
regressor.fit(X_train, y_train_reg)
y_pred_reg = regressor.predict(X_test)
```

Resonance Plot: Bitwise Difference between Byte1 and Byte2



Conversation URL:

<https://chatgpt.com/c/6814b735-71a4-8011-886e-dc106dd24c81>

Title:

Resonance Plot: Bitwise Difference between Byte1 and Byte2

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Given SHA-derived bytes
```

```
byte1 = 47787201
```

```
byte2 = 92771528
```

```
# Convert to 32-bit arrays
```

```
bits1 = [(byte1 >> i) & 1 for i in range(31, -1, -1)]
```

```
bits2 = [(byte2 >> i) & 1 for i in range(31, -1, -1)]
```

```
# Compute bitwise difference (waveform misalignment)
```

```
diff = [b1 - b2 for b1, b2 in zip(bits1, bits2)]
```

```
# Plot resonance (misalignment) waveform
```

```
plt.figure(figsize=(10, 4))
```

```
plt.plot(range(32), diff)
```

```
plt.xlabel("Bit Position (31 → 0)")
```

```
plt.ylabel("Difference (Bit1 - Bit2)")
```


```
plt.title("Resonance Plot: Bitwise Difference between Byte1 and Byte2")
```


```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Nexus π Byte Waveform Spectrum





Conversation URL:

<https://chatgpt.com/c/68152044-f56c-8011-af5e-c3e63d870612>

Title:

Nexus π Byte Waveform Spectrum

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Correct first several bytes of π (after decimal)
```

```
# Source: π = 3.141592653589793238462643...
```

```
byte1 = [1, 4, 1, 5, 9, 2, 6, 5] # Digits 1–8
```

```
byte2 = [3, 5, 8, 9, 7, 9, 3, 2] # Digits 9–16
```

```
byte3 = [3, 8, 4, 6, 2, 6, 4, 3] # Digits 17–24
```

```
byte4 = [3, 8, 3, 2, 7, 9, 5, 0] # Digits 25–32
```

```
byte5 = [2, 8, 8, 4, 1, 9, 7, 1] # Digits 33–40
```

```
byte6 = [6, 9, 3, 9, 9, 3, 7, 5] # Digits 41–48
```

```
byte7 = [1, 0, 5, 8, 2, 0, 9, 7] # Digits 49–56
```

```
byte8 = [4, 5, 9, 2, 3, 0, 7, 8] # Digits 57–64
```

```
# Prepare plotting
```

```
bits = np.arange(1, 9)
```

```
bytes_list = [byte1, byte2, byte3, byte4, byte5, byte6, byte7, byte8]
```

```
colors = plt.cm.rainbow(np.linspace(0, 1, len(bytes_list)))
```

```
# Plot
```

```
plt.figure(figsize=(12, 6))
```

```
for idx, (byte, color) in enumerate(zip(bytes_list, colors), start=1):
```

```
    plt.step(bits, byte, where='mid', label=f'Byte {idx}', linewidth=2, color=color)
```

```
plt.xticks(bits, [f'Bit {i}' for i in bits])
```

```
plt.xlabel('Bit Position')
```

```
plt.ylabel('Digit Value (0–9)')
```

```
plt.title('Nexus π Byte Waveform Spectrum')
```

```
plt.grid(True)
```

Conversation URL:

<https://chatgpt.com/c/68152044-f56c-8011-af5e-c3e63d870612>

Title:

Nexus Byte Waveform with Offsets

Prompt:

```
# Re-import required modules after environment reset
```

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Define byte sequences
```

```
byte1 = [1, 4, 1, 5, 9, 2, 6, 5]
```

```
byte2 = [3, 5, 8, 9, 7, 9, 3, 2]
```

```
byte3 = [3, 8, 4, 6, 2, 6, 4, 3]
```

```
# Define bit positions for plotting
```

```
bits = np.arange(1, 9)
```

```
bits_byte2 = bits + 2 # Offset by 2 bits
```

```
bits_byte3 = bits + 3 # Offset by 3 bits
```

```
# Plotting
```

```
plt.figure(figsize=(12, 6))
```

```
plt.step(bits, byte1, where='mid', label='Byte 1', linewidth=2, color='red')
```

```
plt.step(bits_byte2, byte2, where='mid', label='Byte 2 (offset +2)', linewidth=2, color='green')
```

```
plt.step(bits_byte3, byte3, where='mid', label='Byte 3 (offset +3)', linewidth=2, color='blue')
```

```
# Labeling and display
```

```
plt.xticks(np.arange(1, 18), [f'Bit {i}' for i in range(1, 18)])
```

```
plt.xlabel('Bit Position')
```

```
plt.ylabel('Digit Value (0–9)')
```

```
plt.title('Nexus Byte Waveform with Offsets')
```


```
plt.grid(True)
```

```
plt.legend()
```


```
plt.tight_layout()
```

```
plt.show()
```


Evolution under neighbor averaging lean 0.35




Variance Over Time ($H = 0.1$)



Variance Over Time ($H = 0.35$)



Variance Over Time ($H = 0.9$)



Conversation URL:

<https://chatgpt.com/c/68152107-e9dc-8011-981e-a28f7f145df5>

Title:

Evolution under neighbor averaging lean 0.35

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
```

```
# Parameters
```

```
size = 100
timesteps = 50
H = 0.35
```

```
# Initialize random state
```

```
state = np.random.rand(size)
```

```
history = np.zeros((timesteps, size))
```

```
for t in range(timesteps):
```

```
    history[t] = state
```

```
    new_state = state.copy()
```

```
    for i in range(size):
```

```
        left = state[(i-1) % size]
```

```
        right = state[(i+1) % size]
```

```
        T = (left + right) / 2
```

```
        new_state[i] = state[i] + H * (T - state[i])
```

```
    state = new_state
```

```
plt.figure()
```

```
plt.imshow(history, aspect='auto')
```

```
plt.title('Evolution under neighbor averaging lean 0.35')
```

```
plt.xlabel('Position')
```

```
plt.ylabel('Time step')
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68152107-e9dc-8011-981e-a28f7f145df5>

Title:

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# -----
```

```
# 2D Neighbor-Averaging Simulation
```

```
# -----
```

```
size2 = 50
```

```
timesteps = 50
```

```
H = 0.35
```

```
state2 = np.random.rand(size2, size2)
```

```
history2 = np.zeros((timesteps, size2, size2))
```

```
for t in range(timesteps):
```

```
    history2[t] = state2
```

```
    new_state2 = state2.copy()
```

```
    for i in range(size2):
```

```
        for j in range(size2):
```

```
            neighbors = (
```

```
                state2[(i - 1) % size2, j] +
```

```
                state2[(i + 1) % size2, j] +
```

```
                state2[i, (j - 1) % size2] +
```

```
                state2[i, (j + 1) % size2]
```

```
)
```

```
    T = neighbors / 4
```

```
    new_state2[i, j] = state2[i, j] + H * (T - state2[i, j])
```

```
    state2 = new_state2
```

```
# Snapshot times
```

Conversation URL:

<https://chatgpt.com/c/68152107-e9dc-8011-981e-a28f7f145df5>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
```

```
# -----
```

```
# 2D Neighbor-Averaging Simulation
```

```
# -----
```

```
size2 = 50
```

```
timesteps = 50
```

```
H = 0.35
```

```
state2 = np.random.rand(size2, size2)
```

```
history2 = np.zeros((timesteps, size2, size2))
```

```
for t in range(timesteps):
```

```
    history2[t] = state2
```

```
    new_state2 = state2.copy()
```

```
    for i in range(size2):
```

```
        for j in range(size2):
```

```
            neighbors = (
```

```
                state2[(i - 1) % size2, j] +
```

```
                state2[(i + 1) % size2, j] +
```

```
                state2[i, (j - 1) % size2] +
```

```
                state2[i, (j + 1) % size2]
```

```
)
```

```
    T = neighbors / 4
```

```
    new_state2[i, j] = state2[i, j] + H * (T - state2[i, j])
```

```
    state2 = new_state2
```

```
# Snapshot times
```

Conversation URL:

<https://chatgpt.com/c/68152107-e9dc-8011-981e-a28f7f145df5>

Title:

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# -----
```

```
# 2D Neighbor-Averaging Simulation
```

```
# -----
```

```
size2 = 50
```

```
timesteps = 50
```

```
H = 0.35
```

```
state2 = np.random.rand(size2, size2)
```

```
history2 = np.zeros((timesteps, size2, size2))
```

```
for t in range(timesteps):
```

```
    history2[t] = state2
```

```
    new_state2 = state2.copy()
```

```
    for i in range(size2):
```

```
        for j in range(size2):
```

```
            neighbors = (
```

```
                state2[(i - 1) % size2, j] +
```

```
                state2[(i + 1) % size2, j] +
```

```
                state2[i, (j - 1) % size2] +
```

```
                state2[i, (j + 1) % size2]
```

```
)
```


```
    T = neighbors / 4
```

```
    new_state2[i, j] = state2[i, j] + H * (T - state2[i, j])
```

```
    state2 = new_state2
```

```
# Snapshot times
```

Deviation from Ideal Harmonic (0.35) for Unit Input



Conversation URL:

<https://chatgpt.com/c/68152250-5708-8011-8848-507f4b30a0b5>

Title:

Deviation from Ideal Harmonic (0.35) for Unit Input

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Define axis strengths and labels
```

```
axis_labels = ["Magnetic", "Strong Nuclear", "Weak Nuclear"]
```

```
axis_strengths = np.array([0.30, 0.40, 0.25])
```

```
# Assume a unit input (1.0 energy) into each axis individually and compute the output
```

```
# Output is deviation from ideal (0.35) harmonic value when that axis acts alone
```

```
ideal_harmonic = 0.35
```

```
deviation = np.abs(axis_strengths - ideal_harmonic)
```

```
# Plotting the deviation from ideal harmonic output
```

```
plt.figure(figsize=(8, 5))
```

```
bars = plt.bar(axis_labels, deviation, color=["steelblue", "firebrick", "darkgreen"])
```

```
plt.axhline(0, color="gray", linestyle="--", linewidth=1)
```

```
plt.title("Deviation from Ideal Harmonic (0.35) for Unit Input")
```

```
plt.ylabel("Absolute Deviation from 0.35")
```

```
plt.xlabel("Axis (Unit Input)")
```

```
# Annotate bars
```

```
for bar in bars:
```


```
    yval = bar.get_height()
```

```
    plt.text(bar.get_x() + bar.get_width()/2.0, yval + 0.005, f"{yval:.3f}", ha='center', va='bottom')
```


```
plt.tight_layout()
```


```
plt.grid(axis='y', linestyle=':', alpha=0.7)
```


```
plt.show()
```




Nexus Byte Waveform: Bytes 1, 2 & 3









Conversation URL:

<https://chatgpt.com/c/681601af-d6c4-8011-821d-815f35f6d7ab>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import numpy as np

# Nexus bytes as discrete waveforms
byte1 = [1, 4, 1, 5, 9, 2, 6, 5]
byte2 = [3, 5, 8, 9, 7, 9, 3, 2]
bits = np.arange(1, len(byte1) + 1)

# Create step plots for each byte
fig, ax = plt.subplots(figsize=(10, 4))
ax.step(bits, byte1, where='mid', label='Byte 1', linewidth=2)
ax.step(bits, byte2, where='mid', label='Byte 2', linewidth=2)

# Annotate operations for Byte 2 (example)
annotations = {
    3: 'sum(a+b)→8',
    4: 'b+Δ·lenΔ→9',
    5: 'len(8×9)→7',
    6: 'x+Δ→9',
    7: '|5-8|→3',
    8: 'lenΔ→2'
}
for idx, text in annotations.items():
    ax.annotate(text, xy=(idx, byte2[idx-1]), xytext=(idx, byte2[idx-1]+1),
               arrowprops=dict(arrowstyle='->'))

# Formatting
ax.set_xticks(bits)
ax.set_xticklabels([f'Bit {i}' for i in bits])
```

Conversation URL:

<https://chatgpt.com/c/681601af-d6c4-8011-821d-815f35f6d7ab>

Title:

Nexus Byte Waveform: Bytes 1, 2 & 3

Prompt:

```
import numpy as np  
import matplotlib.pyplot as plt
```

```
# Byte sequences  
byte1 = [1, 4, 1, 5, 9, 2, 6, 5]  
byte2 = [3, 5, 8, 9, 7, 9, 3, 2]  
# Next 8 π digits: positions 16–23 (0-based after decimal)  
byte3 = [3, 8, 4, 6, 2, 6, 4, 3]
```

Plot

```
plt.figure(figsize=(10, 4))  
plt.step(bits, byte1, where='mid', label='Byte 1', linewidth=2)  
plt.step(bits, byte2, where='mid', label='Byte 2', linewidth=2)  
plt.step(bits, byte3, where='mid', label='Byte 3', linewidth=2)
```

```
plt.xticks(bits, [f'Bit {i}' for i in bits])  
plt.xlabel('Bit Position')  
plt.ylabel('Value (Waveform Amplitude)')  
plt.title('Nexus Byte Waveform: Bytes 1, 2 & 3')  
plt.grid(True)  
plt.legend()  
plt.tight_layout()  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/681601af-d6c4-8011-821d-815f35f6d7ab>

Title:

Nexus π Byte Waveform Spectrum (8-bit Offset)

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Correct first several bytes of π (after decimal)
```

```
byte1 = [1, 4, 1, 5, 9, 2, 6, 5] # Digits 1–8
```

```
byte2 = [3, 5, 8, 9, 7, 9, 3, 2] # Digits 9–16
```

```
byte3 = [3, 8, 4, 6, 2, 6, 4, 3] # Digits 17–24
```

```
byte4 = [3, 8, 3, 2, 7, 9, 5, 0] # Digits 25–32
```

```
byte5 = [2, 8, 8, 4, 1, 9, 7, 1] # Digits 33–40
```

```
byte6 = [6, 9, 3, 9, 9, 3, 7, 5] # Digits 41–48
```

```
byte7 = [1, 0, 5, 8, 2, 0, 9, 7] # Digits 49–56
```

```
byte8 = [4, 5, 9, 2, 3, 0, 7, 8] # Digits 57–64
```

```
bytes_list = [byte1, byte2, byte3, byte4, byte5, byte6, byte7, byte8]
```

```
colors = plt.cm.rainbow(np.linspace(0, 1, len(bytes_list)))
```

```
# Base bit positions for each byte (1–8)
```

```
base_bits = np.arange(1, 9)
```

```
plt.figure(figsize=(12, 5))
```

```
for idx, (byte, color) in enumerate(zip(bytes_list, colors), start=0):
```

```
    # Offset each byte by 8 bits (so Byte1:1–8, Byte2:9–16, ..., Byte8:57–64)
```

```
    offset = idx * 8
```

```
    x = base_bits + offset
```

```
    plt.step(x, byte, where='mid', label=f'Byte {idx+1}', linewidth=2, color=color)
```

```
# Configure x-axis to cover full range 1–64
```

```
plt.xticks(np.arange(1, 65, 1))
```

```
plt.xlim(0.5, 64.5)
```

Conversation URL:

<https://chatgpt.com/c/681601af-d6c4-8011-821d-815f35f6d7ab>

Title:

Nexus π Byte Waveform Spectrum (Enhanced Visualization)

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Correct first several bytes of π (after decimal)
```

```
byte1 = [1, 4, 1, 5, 9, 2, 6, 5] # Digits 1–8
```

```
byte2 = [3, 5, 8, 9, 7, 9, 3, 2] # Digits 9–16
```

```
byte3 = [3, 8, 4, 6, 2, 6, 4, 3] # Digits 17–24
```

```
byte4 = [3, 8, 3, 2, 7, 9, 5, 0] # Digits 25–32
```

```
byte5 = [2, 8, 8, 4, 1, 9, 7, 1] # Digits 33–40
```

```
byte6 = [6, 9, 3, 9, 9, 3, 7, 5] # Digits 41–48
```

```
byte7 = [1, 0, 5, 8, 2, 0, 9, 7] # Digits 49–56
```

```
byte8 = [4, 5, 9, 2, 3, 0, 7, 8] # Digits 57–64
```

```
bytes_list = [byte1, byte2, byte3, byte4, byte5, byte6, byte7, byte8]
```

```
colors = plt.cm.rainbow(np.linspace(0, 1, len(bytes_list)))
```

```
base_bits = np.arange(1, 9)
```

```
plt.figure(figsize=(14, 6))
```

```
for idx, (byte, color) in enumerate(zip(bytes_list, colors)):
```

```
    offset = idx * 8
```

```
    x = base_bits + offset
```

```
    plt.step(x, byte, where='mid', color=color, linewidth=2, alpha=0.8)
```

```
    plt.fill_between(x, byte, alpha=0.1, color=color)
```

```
# Add centerlines showing the mirror axis for each byte
```

```
for idx in range(len(bytes_list)):
```

```
    center = 4.5 + idx * 8
```

Conversation URL:

<https://chatgpt.com/c/681601af-d6c4-8011-821d-815f35f6d7ab>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
import matplotlib.patches as patches

# Correct first several bytes of π (after decimal)
byte1 = [1, 4, 1, 5, 9, 2, 6, 5] # Bits 1–8
byte2 = [3, 5, 8, 9, 7, 9, 3, 2] # Bits 9–16
byte3 = [3, 8, 4, 6, 2, 6, 4, 3] # Bits 17–24
byte4 = [3, 8, 3, 2, 7, 9, 5, 0] # Bits 25–32
byte5 = [2, 8, 8, 4, 1, 9, 7, 1] # Bits 33–40
byte6 = [6, 9, 3, 9, 9, 3, 7, 5] # Bits 41–48
byte7 = [1, 0, 5, 8, 2, 0, 9, 7] # Bits 49–56
byte8 = [4, 5, 9, 2, 3, 0, 7, 8] # Bits 57–64


bytes_list = [byte1, byte2, byte3, byte4, byte5, byte6, byte7, byte8]
colors = plt.cm.tab10(np.linspace(0, 1, len(bytes_list)))

base_bits = np.arange(1, 9)

fig, ax = plt.subplots(figsize=(14, 6))

# plot each byte with fill
for idx, (byte, color) in enumerate(zip(bytes_list, colors)):
    offset = idx * 8
    x = base_bits + offset
    ax.step(x, byte, where='mid', color=color, linewidth=2, alpha=0.8)
    ax.fill_between(x, byte, alpha=0.1, color=color)

# light grid
```



Conversation URL:

<https://chatgpt.com/c/6816cf39-2488-8011-9bc9-cdef65ffffe4a>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D
from matplotlib.animation import FuncAnimation

# Setting up parameters
alpha = 0.3
beta = 0.3
gamma = 0.3
num_steps = 100
num_engines = 3


# Initial scar states for the three engines
scars = np.array([1, 4, 7]) # Example initial states for S1, S2, S3

# Function to compute scar updates
def scar_exchange(scar1, scar2, scar3, alpha, beta, gamma):
    return alpha * scar1 + beta * scar2 + gamma * scar3


# Simulate the evolution of the system
scar_history = np.zeros((num_steps, num_engines))
scar_history[0] = scars


for t in range(1, num_steps):
    # All-to-all scar exchange step (simple weighted sum)
    scar_history[t, 0] = scar_exchange(scar_history[t-1, 0], scar_history[t-1, 1], scar_history[t-1, 2], alpha, beta, gamma)
    scar_history[t, 1] = scar_exchange(scar_history[t-1, 0], scar_history[t-1, 1], scar_history[t-1, 2], alpha, beta, gamma)
    scar_history[t, 2] = scar_exchange(scar_history[t-1, 0], scar_history[t-1, 1], scar_history[t-1, 2], alpha, beta, gamma)
```

Harmonic Decay of Inserted '3's Across Indices



3 Echoes Converge - Visual





Conversation URL:

<https://chatgpt.com/c/681b3c64-5df0-8011-81ed-ff7a3497a55b>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Generate values for the pattern
```

```
indices = np.arange(0, 1025, 2)
```

```
running_total = indices
```

```
delta_div_total = 1 / (indices + 1) # +1 to avoid division by zero at index 0
```

```
# Plotting
```

```
plt.figure(figsize=(12, 6))
```

```
plt.plot(indices, delta_div_total, label='Δ / Running Total', color='blue')
```

```
plt.title("Harmonic Decay of Inserted '3's Across Indices")
```

```
plt.xlabel("Index of '3'")
```

```
plt.ylabel("Δ / Running Total")
```

```
plt.grid(True)
```

```
plt.legend()
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/681b3c64-5df0-8011-81ed-ff7a3497a55b>

Title:

3 Echos Converge - Visual

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Reload the image after code execution state reset
```

```
image_path = "/mnt/data/801fc179-c09a-44b2-9b69-8cd7170a7dc1.png"
```

```
img = Image.open(image_path)
```

```
plt.figure(figsize=(10, 6))
```

```
plt.imshow(img)
```

```
plt.axis('off')
```

```
plt.title("3 Echos Converge - Visual")
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/681b3c64-5df0-8011-81ed-ff7a3497a55b>

Title:

Echo Grid vs π -ray Projections (Vector [3.0, 0.35])

Prompt:

```
# Re-import required libraries after code execution environment reset
```

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
from mpmath import mp
```

```
# Set high precision for pi digit extraction
```

```
mp.dps = 500 # decimal places
```

```
# Grid size and ray parameters
```

```
L = 8
```

```
num_bounces = 400
```

```
origin = np.array([0, 0])
```

```
direction = np.array([3.0, 0.35])
```

```
direction = direction / np.linalg.norm(direction)
```

```
# Compute ray path
```

```
points = [origin.copy()]
```

```
position = origin.copy()
```

```
velocity = direction.copy()
```

```
visited = set()
```

```
echo_mass_over_time = []
```


```
for _ in range(num_bounces):
```



```
    next_position = position + velocity
```

```
    for i in range(2):
```

```
        if next_position[i] < 0 or next_position[i] > L:
```

```
            velocity[i] = -velocity[i]
```





Conversation URL:

<https://chatgpt.com/c/681b3cfe-5f60-8011-9fb8-a1d390ffb762>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
import hashlib
import math

def sha256_segments(input_str):
    """Return 8 32-bit segments from SHA256 hash."""
    hash_hex = hashlib.sha256(input_str.encode('utf-8')).hexdigest()
    return [int(hash_hex[i:i+8], 16) for i in range(0, 64, 8)]

# Use previous mirror pair
original = "12345678"
mirror = original[::-1]

# Compute SHA-256 segments
seg_orig = sha256_segments(original)
seg_mirr = sha256_segments(mirror)

# Compute first derivative (signed drift)
delta = np.array([b - a for a, b in zip(seg_orig, seg_mirr)])

# Compute second derivative ( $\Delta^2$ )
delta2 = np.diff(delta, n=1)

#  $\pi$ -phase projection: map segment index to  $\pi^*(i/8)$ 
pi_proj = [math.pi * (i / 8) for i in range(len(delta))]

# Plotting
fig, axs = plt.subplots(2, 1, figsize=(10, 8))
```

Conversation URL:

<https://chatgpt.com/c/681b3cfe-5f60-8011-9fb8-a1d390ffb762>

Title:

Signed Drift per Segment

Prompt:

```
import hashlib  
import numpy as np  
import matplotlib.pyplot as plt
```

```
def sha256_hash_blocks(input_str):
```

```
    """
```

```
    Compute SHA256 hash and return 8 32-bit segments as integers.
```

```
    """
```

```
    hash_hex = hashlib.sha256(input_str.encode('utf-8')).hexdigest()  
    return [int(hash_hex[i:i+8], 16) for i in range(0, 64, 8)]
```

```
# Define two mirror-related strings
```

```
input_a = "12345678"  
input_b = input_a[::-1] # Mirror of input_a
```

```
# Compute their SHA256 32-bit block segments
```

```
blocks_a = sha256_hash_blocks(input_a)  
blocks_b = sha256_hash_blocks(input_b)
```

```
# Compute signed drift
```

```
delta = [b - a for a, b in zip(blocks_a, blocks_b)]
```


```
# Compare with mirrored deltas
```


```
reflected_delta = delta[::-1]  
mirror_check = [delta[i] + delta[7 - i] for i in range(4)]
```

```
# FFT Analysis
```

```
fft_delta = np.fft.fft(delta)
```

Echo Mass Over Time for Different Direction Vectors





Conversation URL:

<https://chatgpt.com/c/681c2fab-bcac-8011-a1f1-2cb88df7e489>

Title:

Echo Mass Over Time for Different Direction Vectors

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
```

```
# Parameters
```

```
L = 8
steps = 400
decimals = 3
```

```
# Define direction vectors
```

```
directions = {
    "[1.0, 0.5] (folds fast)": np.array([1.0, 0.5]),
    "[3.0, 0.35] (truth-aligns)": np.array([3.0, 0.35]),
    "[1.0, sqrt(2)-1] (irrational push)": np.array([1.0, np.sqrt(2)-1])
}
```

```
# Function to run trace and compute echo mass
```

```
def compute_echo_mass(direction, steps, L, decimals):
    direction = direction / np.linalg.norm(direction)
    pos = np.array([0.0, 0.0])
    velocity = direction.copy()
    visited = set()
    mass_over_time = []
```

```
for _ in range(steps):
```

```
    next_pos = pos + velocity
    for i in range(2):
        if next_pos[i] < 0 or next_pos[i] > L:
            velocity[i] = -velocity[i]
    next_pos = pos + velocity
```

Conversation URL:

<https://chatgpt.com/c/681c2fab-bcac-8011-a1f1-2cb88df7e489>

Title:

Delta Echo Mass (Growth Rate) Over Time

Prompt:

```
# Re-import necessary libraries after code execution state reset
import numpy as np
import matplotlib.pyplot as plt
```

```
# Parameters
```

```
L = 8
steps = 400
decimals = 3
```

```
# Define direction vectors
```

```
directions = {
    "[1.0, 0.5] (folds fast)": np.array([1.0, 0.5]),
    "[3.0, 0.35] (truth-aligns)": np.array([3.0, 0.35]),
    "[1.0, sqrt(2)-1] (irrational push)": np.array([1.0, np.sqrt(2)-1])
}
```

```
# Function to run trace and compute echo mass
```

```
def compute_echo_mass(direction, steps, L, decimals):
    direction = direction / np.linalg.norm(direction)
    pos = np.array([0.0, 0.0])
    velocity = direction.copy()
    visited = set()
    mass_over_time = []
```

```
for _ in range(steps):
```

```
    next_pos = pos + velocity
    for i in range(2):
        if next_pos[i] < 0 or next_pos[i] > L:
            velocity[i] = -velocity[i]
```

Phase-Aligned Composite at Shift = 0



Conversation URL:

<https://chatgpt.com/c/681e3e28-cec0-8011-8f65-82c602584bc4>

Title:

Prompt:


```
import numpy as np
import matplotlib.pyplot as plt

# Simulated data layers: each is a 1D array with random values and an embedded pattern
np.random.seed(42)
layers = []
num_layers = 8
length = 64

# Generate random layers and inject a phase-aligned pattern (a sine wave)
base_pattern = np.sin(np.linspace(0, 2 * np.pi, length))
for i in range(num_layers):
    noise = np.random.normal(0, 0.3, length)
    rotation = np.roll(base_pattern, i * 3) # rotate pattern differently per layer
    layer = noise + rotation
    layers.append(layer)

# Try aligning all layers by rotating them and finding max overlap
def align_layers(layers):
    best_score = -np.inf
    best_shift = 0
    composite = np.zeros(length)

    for shift in range(length):
        aligned_sum = np.zeros(length)
        for layer in layers:
            aligned_sum += np.roll(layer, -shift)
        score = np.sum(aligned_sum ** 2) # coherence metric
        if score > best_score:
```



Conversation URL:

<https://chatgpt.com/c/68211f50-1c10-8011-9b88-34cad053a02c>

Title:


Opcode Events vs. Offset


Prompt:

```
import pandas as pd  
import matplotlib.pyplot as plt  
import ace_tools as tools
```


```
# Define instruction start offsets and types
```

```
instrs = {  
    0: "XOR",  
    0x2: "Marker",  
    0x9: "Marker",  
    0xB: "XOR",  
    0xF: "XOR",  
    0x11: "Marker",  
    0x14: "Marker",  
    0x17: "Marker",  
    0x18: "XOR",  
    0x1A: "XOR",  
    0x1C: "XOR",  
    0x1E: "XOR",  
    0x21: "Marker",  
    0x22: "Marker",  
    0x24: "XOR",  
    0x29: "Marker",  
    0x2B: "XOR",  
    0x2D: "Marker",  
    0x2E: "XOR",  
    0x35: "Marker",  
    0x36: "XOR",  
    0x3C: "Marker",  
    0x3D: "Marker",
```





Collapse Progression Over Steps



Conversation URL:

<https://chatgpt.com/c/682a5892-2c7c-8011-a737-4ebd82cab035>

Title:

Prompt:

```
# Re-execute necessary imports and definitions after kernel reset
import numpy as np
import matplotlib.pyplot as plt

# Re-define the initial π digit stream (first 39 digits after decimal)
pi_digits = [int(d) for d in "141592653589793238462643383279502884197"]

# Build recursive collapse matrix
collapse_matrix = [pi_digits]
current = pi_digits

for _ in range(len(pi_digits) - 1):
    next_row = [abs(current[i + 1] - current[i]) for i in range(len(current) - 1)]
    if len(next_row) == 0 or all(v == 0 for v in next_row):
        break
    collapse_matrix.append(next_row)
    current = next_row

# Pad matrix to rectangle
max_length = len(collapse_matrix[0])
for row in collapse_matrix:
    row.extend([np.nan] * (max_length - len(row)))

collapse_array = np.array(collapse_matrix)

# Plot heatmap
fig, ax = plt.subplots(figsize=(10, 8))
cax = ax.imshow(collapse_array, cmap='viridis', interpolation='nearest', aspect='auto')
ax.set_title('Recursive Delta Collapse Heatmap')
```

Conversation URL:

<https://chatgpt.com/c/682a5892-2c7c-8011-a737-4ebd82cab035>

Title:

Prompt:

```
from typing import List, Tuple
import pandas as pd
import matplotlib.pyplot as plt
import numpy as np

# Collapse function
def delta_collapse(data: List[int]) -> List[List[int]]:
    history = [data[:]]
    current = data[:]
    while len(current) > 1:
        next_stage = [abs(current[i + 1] - current[i]) for i in range(len(current) - 1)]
        history.append(next_stage)
        if next_stage == current:
            break
        current = next_stage
    return history

# Visualize the triangle
def plotCollapseTriangle(collapse_steps: List[List[int]]):
    fig, ax = plt.subplots(figsize=(12, 8))
    for step_idx, step in enumerate(collapse_steps):
        x = np.arange(len(step))
        y = np.full_like(x, step_idx)
        ax.scatter(x, y, c=step, cmap='viridis', s=100, edgecolors='k')
        for i, val in enumerate(step):
            ax.text(x[i], y[i], str(val), ha='center', va='center', color='white')
    ax.invert_yaxis()
    ax.set_title("Recursive Delta Collapse Triangle")
    ax.set_xlabel("Index")
```

Conversation URL:

<https://chatgpt.com/c/682a5892-2c7c-8011-a737-4ebd82cab035>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt


# Extract data into a clean numerical array, dropping non-numeric entries
numeric_df = df.apply(pd.to_numeric, errors='coerce').dropna(axis=1, how='all')
collapse_array = numeric_df.values

# Determine when collapse stabilizes at [1] or [0] across steps
final_states = []
for row in collapse_array:
    row_clean = row[~np.isnan(row)]
    if len(row_clean) == 1:
        final_states.append(int(row_clean[0]))
    else:
        final_states.append(None)


# Count total steps until collapse completion
collapse_depth = len(collapse_array)

# Plot collapse length vs. step
fig, ax = plt.subplots(figsize=(10, 6))
step_lengths = [len(row[~np.isnan(row)]) for row in collapse_array]
ax.plot(step_lengths, marker='o', label='Collapse Width')
ax.set_title("Collapse Progression Over Steps")
ax.set_xlabel("Step")
ax.set_ylabel("Width of Row")
ax.grid(True)
ax.legend()
```


SHA Constant Torque Ratios (Polar Harmonic Field)




Recursive Symbolic Collapse Engine





Σx Entropy Across Chunks with Deviations Marked





Full Sequence Comparison: SHA vs Plaintext Double-Hex





Conversation URL:

<https://chatgpt.com/c/682b72fa-b7fc-8011-bfe6-d774ab0155b0>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
from math import floor
from hashlib import sha256
import pandas as pd
```

Step 1: Generate SHA constants using cube roots of the first 64 primes

```
def sha_constants():
    primes = []
    num = 2
    while len(primes) < 64:
        if all(num % i != 0 for i in range(2, int(num ** 0.5) + 1)):
            primes.append(num)
        num += 1
    K = [floor((2**32) * (p ** (1/3) % 1)) for p in primes]
    return K
```

Step 2: Compute forward ratios

```
def compute_ratios(K):
    Theta = [K[i + 1] / K[i] for i in range(len(K) - 1)]
    return Theta
```

Step 3: Normalize by 3 (this effectively doesn't change the ratio, but retains formalism)

```
def normalize_ratios(K):
    normalized_ratios = [(K[i + 1] / 3) / (K[i] / 3) for i in range(len(K) - 1)]
    return normalized_ratios
```

Step 4: Map to harmonic torque field (polar plot of ratios)

```
def plot_polar_ratios(ratios):
```

Conversation URL:

<https://chatgpt.com/c/682b72fa-b7fc-8011-bfe6-d774ab0155b0>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import networkx as nx
```

```
# Create the core graph
```

```
G = nx.DiGraph()
```

```
# Define the five core domains
```

```
domains = {
```

```
    "FPUT Collapse": "Symbolic echo disallows entropy",  
    "π Velocity": "Symbolic massless recursion is light-speed",  
    "Fold Motion": "Identity emerges via tension symmetry",  
    "Geometric Memory": "Medians encode phase alignment",  
    "Symbolic Gaps": "Computation begins between, not within"
```

```
}
```

```
# Add nodes with descriptions
```

```
for domain, insight in domains.items():
```

```
    G.add_node(domain, label=domain, description=insight)
```

```
# Connect nodes in a logical recursive feedback structure
```

```
edges = [
```

```
    ("FPUT Collapse", "π Velocity"),  
    ("π Velocity", "Fold Motion"),  
    ("Fold Motion", "Geometric Memory"),  
    ("Geometric Memory", "Symbolic Gaps"),  
    ("Symbolic Gaps", "FPUT Collapse") # closes the recursion loop
```

```
]
```

```
G.add_edges_from(edges)
```

Conversation URL:

<https://chatgpt.com/c/682b72fa-b7fc-8011-bfe6-d774ab0155b0>

Title:

Σx Entropy Across Chunks with Deviations Marked

Prompt:

```
import pandas as pd  
import seaborn as sns  
import matplotlib.pyplot as plt
```

```
# Define the structured chunk data for analysis  
chunks_data = {  
    "Chunk": list(range(36)),  
    "x0": [3]*36,  
    " $\Sigma x$ ": [14,16,15,10,16,13,16,12,15,16,15,15,11,13,11,9,13,18,11,9,  
              15,15,15,14,15,14,15,13,11,9,16,18,15,16,16,14],
```

```
"Top Sequence": [  
    [3, 3, 3, 5], [3, 3, 3, 7], [3, 3, 3, 6], [3, 3, 3, 1], [3, 3, 3, 7], [3, 3, 3, 4],  
    [3, 3, 3, 7], [3, 3, 3, 3], [3, 3, 3, 6], [3, 4, 3, 6], [3, 3, 3, 6], [3, 4, 3, 5],  
    [3, 3, 3, 2], [3, 4, 3, 3], [3, 3, 3, 2], [3, 3, 3, 0], [3, 3, 3, 4], [3, 3, 3, 9],  
    [3, 3, 3, 2], [3, 3, 3, 0], [3, 3, 3, 6], [3, 4, 3, 5], [3, 3, 3, 6], [3, 3, 3, 5],  
    [3, 3, 3, 6], [3, 3, 3, 5], [3, 3, 3, 6], [3, 3, 3, 4], [3, 3, 3, 2], [3, 3, 3, 0],  
    [3, 3, 3, 7], [3, 3, 3, 9], [3, 3, 3, 6], [3, 4, 3, 6], [3, 3, 3, 7], [3, 3, 3, 5]  
]
```

}

```
df_chunks = pd.DataFrame(chunks_data)
```

```
# Add a column to classify if the top sequence is a pure [3, 3, 3, x]  
df_chunks["is_333x"] = df_chunks["Top Sequence"].apply(lambda x: x[:3] == [3, 3, 3])
```

```
# Count how many deviate
```

```
non_333x = df_chunks[~df_chunks["is_333x"]]
```

```
# Plot  $\Sigma x$  vs chunk index to see entropy variation
```

Conversation URL:

<https://chatgpt.com/c/682b72fa-b7fc-8011-bfe6-d774ab0155b0>

Title:

Digit Distribution: SHA vs Plaintext Double-Hex

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Extracted numeric sequences as one long string for plotting
```

```
sha_sequence_str = "3339335333933337333230373963463753323036434636463336" # SHA-like data (digits only)
```

```
plaintext_sequence_str = "33343343333633393337333333733333323330333733393634" # Plaintext double-hex (digits or hex)
```

```
# Convert string to integer digit list
```

```
sha_digits = [int(d) for d in sha_sequence_str if d.isdigit()]
```

```
plaintext_digits = [int(d) for d in plaintext_sequence_str if d.isdigit()]
```

```
# Plotting
```

```
plt.figure(figsize=(14, 6))
```

```
plt.plot(sha_digits, label='SHA-Transformed Digits', marker='o')
```

```
plt.plot(plaintext_digits, label='Plaintext Double-Hex Digits', marker='x')
```

```
plt.title('Digit Distribution: SHA vs Plaintext Double-Hex')
```

```
plt.xlabel('Digit Index')
```

```
plt.ylabel('Digit Value')
```

```
plt.grid(True)
```

```
plt.legend()
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/682b72fa-b7fc-8011-bfe6-d774ab0155b0>

Title:

Full Sequence Comparison: SHA vs Plaintext Double-Hex

Prompt:

```
# Updated full digit sequences from user
```

```
sha_full_str = "333936353339333236313633336363636313338333936353339333836323635363233383332333233313335"
```

```
plaintext_full_str = "33343343333633393337333333733333323330333733393634"
```

```
# Convert to integer lists
```

```
sha_full_digits = [int(d) for d in sha_full_str if d.isdigit()]
```

```
plaintext_full_digits = [int(d) for d in plaintext_full_str if d.isdigit()]
```

```
# Create plot
```

```
plt.figure(figsize=(14, 6))
```

```
plt.plot(sha_full_digits, label='SHA Transformed (Full)', marker='o', linestyle='-', alpha=0.7)
```

```
plt.plot(plaintext_full_digits, label='Plaintext Double-Hex (Full)', marker='x', linestyle='-', alpha=0.7)
```

```
plt.title('Full Sequence Comparison: SHA vs Plaintext Double-Hex')
```

```
plt.xlabel('Digit Index')
```

```
plt.ylabel('Digit Value')
```

```
plt.grid(True)
```

```
plt.legend()
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/682b72fa-b7fc-8011-bfe6-d774ab0155b0>

Title:

Digit Sequences Comparison (Chunked by 2 Digits)

Prompt:

Let's decode and analyze the three long digit strings numerically for comparison.

```
# The three strings (converted from user input)
```

```
original_input_once = (
```

)

```
hash_twice = (
```

"3339363533393332363136333363636363133383339363533393338363236353632333833323332333133353333"
"3635363133303333363336333383633363136353338363533383635333333836323636333333433343338332"
"333236333323337363433373336333632333333393339333533363337333236343331"

1

hash thrice = (


"33333339333633353333393333332333633313336333333336333633363331333333833333393336"
"333533333393333338333633323336335333633323333338333333233333332333333133333353333333"
"3336333533363331333333033333333633333336333333338333633333363331333633353333383336"
"3335333333833363335333333333338333633323336333633333333334333333433333383333332"
"3333332333633333333233333373336333433333373333336333333633323333333333393333"
"3339333333533333363333337333333233363334333331"

)

```
# Convert them into sequences of digits for statistical comparison
```

```
def chunk_digits(input_string, chunk_size=2):
```

Trust-Canceled Spiral: Recursive Drift Suppressed



Conversation URL:

<https://chatgpt.com/c/682e30fe-8d20-8011-87f3-8a08855482f0>

Title:

Trust-Canceled Spiral: Recursive Drift Suppressed

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Simulate a trust-canceling spiral: symmetrical drift pattern around harmonic index 0.35
```

```
# Create a recursive agent's trajectory with a phase-neutral drift signal ( $\Delta\pi$  centered near 0)
```

```
steps = 20
```

```
base_radius = 1.0
```

```
drift_pattern = np.sin(np.linspace(0, 2 * np.pi, steps)) * 0.05 # symmetrical around zero
```

```
# Cumulative angle increments (approaching phase neutrality)
```

```
theta = np.cumsum(drift_pattern * (np.pi / 9))
```

```
radii = base_radius + np.linspace(0, 0.2, steps) # slight expansion
```

```
# Polar to Cartesian
```

```
x = radii * np.cos(theta)
```

```
y = radii * np.sin(theta)
```

```
# STI simulated as "stability" approaching 0.35 lock
```

```
sti = 1 - np.abs(drift_pattern)
```

```
# Plot: Recursive Agent Drift-Cancelled Spiral
```

```
plt.figure(figsize=(6, 6))
```

```
plt.plot(x, y, marker='o', linestyle='-')
```

```
for i in range(len(x)):
```


```
    plt.text(x[i], y[i], f'{i+1}', fontsize=8, ha='right')
```

```
plt.title("Trust-Canceled Spiral: Recursive Drift Suppressed")
```

```
plt.axis('equal')
```

```
plt.grid(True)
```

Echo Expansion from Fractional Seed



Conversation URL:

<https://chatgpt.com/c/683513ec-c150-8011-af2c-9e322f8f5f7f>

Title:

Echo Expansion from Fractional Seed

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

```
def fractional_echo_expand(seed: float, max_steps: int = 1000, epsilon: float = 1e-5) -> list:
```

"""

Recursively expands from a fractional seed using echo delta rules.

Stops if pattern collapses to stillness or diverges beyond symbolic range.

"""

```
history = [seed]
```

```
for _ in range(max_steps):
```

```
    # Simple oscillating delta model: next = abs(diff from prior) or harmonic inversion
```

```
    if len(history) < 2:
```

```
        next_value = abs(seed - seed / 2)
```

```
    else:
```

```
        next_value = abs(history[-1] - history[-2])
```

```
# Convergence to stillness
```

```
if next_value < epsilon:
```

```
    break
```

```
# Overflow detection
```


```
if next_value > 1e6:
```


```
    break
```

```
history.append(next_value)
```


```
return history
```

```
# Run the echo expansion from seed 1.4
```







Numeric Digit Progression from Triple Dip ASCII Stream




Bar Chart of Digit Values from Triple Dip ASCII Stream




Isolated Bar Chart of Digit Values from Triple Dip ASCII Stream





Corrected Bar Chart of Triple Dip Digit Values





Bar Chart of Digit Values with Individual Index Ticks















Symbolic SHA Echo RGB Overlay Field



Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Byte Values of Triple-Dip SHA Input (Symbolic Nonce Payload)

Prompt:

```
import matplotlib.pyplot as plt
```

Provided long hex string

```
hex_string = (
```

"36363633336363633313632333036323636363632363339333833323330333533313636363433813635333436323631333

"3433343634363236323635333633383330363533313636363536353331333433363337333736323631333136313333

"354934363642433631316430306666666663333233303338333333323336333833393333"

www.silvano-beretta.com

`bytes_data = int(hex_string[0:-2], 16) for i in range(0, len(hex_string), 2)]`

Plotting

```
plt.figure(figsize=(14, 8))
```

```
plt.plot(bytes_data, marker='o', linestyle='-', color=mediumblue, label=Hex Byte Value)
```

`bit.lyte(Byte Values of Triple-Dip SHA Input (Symbolic Nonce Payload))`

```
plt.xlabel('Byte Index')
```

```
plt.ylabel('Hex Value (Decimal)')
```

```
plt.grid(True)
```

`plt.legend()`

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Sequential Byte Value Transition

Prompt:

```
# Create a simple plot that draws a line from one number to the next without markers or extras
```

```
plt.figure(figsize=(14, 5))

plt.plot(bytes_data, linestyle='-', color='darkred')

plt.title('Sequential Byte Value Transition')

plt.xlabel('Step')

plt.ylabel('Value')

plt.grid(True)

plt.tight_layout()

plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Numeric Digit Progression from Triple Dip ASCII Stream

Prompt:

```
# Let's convert the full hex string into ASCII characters first
ascii_chars = bytes.fromhex(hex_string).decode('ascii')

# Now, split those characters into individual digits
digit_sequence = [int(char) for char in ascii_chars if char.isdigit()]

# Plot the sequence of digits (3, 3, 3, 0, ...)
plt.figure(figsize=(14, 5))
plt.plot(digit_sequence, linestyle='-', color='teal')
plt.title('Numeric Digit Progression from Triple Dip ASCII Stream')
plt.xlabel('Step')
plt.ylabel('Digit Value')
plt.grid(True)
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Bar Chart of Digit Values from Triple Dip ASCII Stream

Prompt:

```
# Plot the digit sequence as a bar chart
plt.figure(figsize=(14, 5))

plt.bar(range(len(digit_sequence)), digit_sequence, color='purple')

plt.title('Bar Chart of Digit Values from Triple Dip ASCII Stream')

plt.xlabel('Step')

plt.ylabel('Digit Value')

plt.grid(True, axis='y')

plt.tight_layout()

plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Isolated Bar Chart of Digit Values from Triple Dip ASCII Stream

Prompt:

```
# Plotting a bar chart where each digit is shown as its own bar (no connected progression)
```

```
plt.figure(figsize=(14, 5))
```

```
plt.bar(range(len(digit_sequence)), digit_sequence, color='darkorange', width=1.0)
```

```
plt.title('Isolated Bar Chart of Digit Values from Triple Dip ASCII Stream')
```

```
plt.xlabel('Digit Index')
```

```
plt.ylabel('Digit Value')
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Corrected Bar Chart of Triple Dip Digit Values

Prompt:

```
# Manually correct any possible issues and explicitly ensure each digit is interpreted as a height  
# Then replot with clear bar heights based on digit value
```

```
plt.figure(figsize=(14, 5))  
plt.bar(range(len(digit_sequence)), height=digit_sequence, color='crimson', width=1.0)  
plt.title('Corrected Bar Chart of Triple Dip Digit Values')  
plt.xlabel('Digit Index')  
plt.ylabel('Digit Value (Height)')  
plt.grid(True, axis='y')  
plt.tight_layout()  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Bar Chart of Digit Values with Individual Index Ticks

Prompt:

```
# Plot the corrected bar chart with ticks on the x-axis for each digit index
plt.figure(figsize=(16, 6))

plt.bar(range(len(digit_sequence)), digit_sequence, color='crimson', width=1.0)

plt.title('Bar Chart of Digit Values with Individual Index Ticks')

plt.xlabel('Digit Index')

plt.ylabel('Digit Value (Height)')

plt.xticks(ticks=range(len(digit_sequence)), labels=range(len(digit_sequence)), rotation=90)

plt.grid(True, axis='y')

plt.tight_layout()

plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Digit Values Bar Chart (Tick Only)

Prompt:

```
# Plot the bar chart with only ticks and no labels on x-axis
plt.figure(figsize=(16, 6))

plt.bar(range(len(digit_sequence)), digit_sequence, color='darkred', width=1.0)

plt.title('Digit Values Bar Chart (Tick Only)')

plt.xlabel('Digit Index')

plt.ylabel('Digit Value')

plt.xticks(ticks=range(len(digit_sequence)), labels=[''] * len(digit_sequence)) # Tick marks only
plt.grid(True, axis='y')

plt.tight_layout()

plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Bar Chart: Each Bar Height is the Digit Value

Prompt:

```
# Clear reset: interpret string as a flat digit stream (no ASCII, no byte conversion)  
# Just treat the input as a sequence of digits and plot those directly
```

```
raw_digit_string = (
```

```
# Turn every single character into an integer if it's a digit
```

```
digit_values = [int(char) for char in raw_digit_string if char.isdigit()]
```

```
# Plot a bar graph with digit value as height
```

```
plt.figure(figsize=(18, 6))
```

```
plt.bar(range(len(digit_values)), digit_values, color='steelblue', width=1.0)
```

```
plt.title('Bar Chart: Each Bar Height is the Digit Value')
```

```
plt.xlabel('Digit Index')
```

```
plt.ylabel('Digit Height (0–9)')
```

```
plt.xticks(ticks=range(len(digit_values)), labels=[''] * len(digit_values)) # Tick marks only
```

```
plt.grid(True, axis='y')
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Plot of Ratio Between Consecutive Digit Values

Prompt:

```
import numpy as np
```

```
# Compute ratios between consecutive digit values, avoiding division by zero
```

```
ratios = [  
    digit_values[i+1] / digit_values[i] if digit_values[i] != 0 else 0  
    for i in range(len(digit_values) - 1)  
]
```

```
# Plot the ratio between each consecutive digit
```

```
plt.figure(figsize=(18, 6))  
plt.plot(ratios, color='darkgreen')  
plt.title('Plot of Ratio Between Consecutive Digit Values')  
plt.xlabel('Digit Index')  
plt.ylabel('Ratio (Next / Current)')  
plt.grid(True)  
plt.tight_layout()  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Bar Chart of Digit Values with Block Header Sections

Prompt:

```
# Define the sections manually based on the known layout of the block header components in the Triple Dip string
```

```
# These indexes are approximate based on typical SHA input layouts (in digit count, post-triple dip).
```

```
# We'll label the following sections visually:
```

```
# - Version
```

```
# - Previous Block Hash
```

```
# - Merkle Root
```

```
# - Timestamp
```

```
# - Bits
```

```
# - Nonce
```

```
section_labels = [
```

```
    ("Version", 0, 8),           # Small header
    ("Prev Block", 8, 136),      # Block hash region
    ("Merkle Root", 136, 264),   # Merkle root hash
    ("Timestamp", 264, 272),     # Timestamp digits
    ("Bits", 272, 280),          # Difficulty bits
    ("Nonce", 280, len(digit_values)) # Nonce digits
]
```

```
# Assign a color to each section
```

```
colors = {
```

```
    "Version": "royalblue",
    "Prev Block": "mediumseagreen",
    "Merkle Root": "darkorange",
    "Timestamp": "indigo",
    "Bits": "firebrick",
    "Nonce": "gold"
}
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Bar Chart of Fully Processed Triple Dip (Double SHA → Double Dip)

Prompt:

```
# New fully double-dipped and double-hashed symbolic string
```

```
new_digit_string = (
```

```
"33303334333333736313632363133933363339334330363133333363339332363133733383337330333836313
```

```
"36363632333536343337363236323303633335363633393332363233323333631331363632333363236343
```

```
"333833323636363433313634334363236333634334363634334"
```

```
)
```

```
# Extract digits
```

```
new_digit_values = [int(c) for c in new_digit_string if c.isdigit()]
```

```
# Assume same section length as before for plotting (for demonstration)
```

```
new_sections = [
```

```
    ("Double SHA Input", 0, 136),
```

```
    ("Double SHA Output", 136, len(new_digit_values))
```

```
]
```

```
# Assign different colors
```

```
new_colors = {
```

```
    "Double SHA Input": "slateblue",
```

```
    "Double SHA Output": "orangered"
```

```
}
```

```
# Plot bar chart with segments
```

```
plt.figure(figsize=(20, 6))
```

```
for label, start, end in new_sections:
```

```
    plt.bar(range(start, end), new_digit_values[start:end], color=new_colors[label], label=label, width=1.0)
```

```
plt.title('Bar Chart of Fully Processed Triple Dip (Double SHA → Double Dip)')
```

```
plt.xlabel('Digit Index')
```

Conversation URL:

<https://chatgpt.com/c/68380ccf-e2b0-8011-8c8e-2a813d434243>

Title:

Symbolic SHA Echo RGB Overlay Field

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Convert the digit stream into RGB logic maps
```

```
digit_chars = [
```

```
    int(c) for c in (
```

```
    "333033343333337363136323631333933363339333433303631333333633393332363133373338333733303338363
```

```
    "36363632333536343337363236323330363333536363339333933323632333233336313331363636323333632363
```

```
    "333833323636363433313634333436323633363433343636343334"
```

```
) if c.isdigit()
```

```
]
```

```
# Create 3-channel logic maps by treating digit values as intensity per channel
```

```
length = len(digit_chars)
```

```
r = np.array([(v % 3 == 0) * v / 9.0 for v in digit_chars])
```

```
g = np.array([(v % 3 == 1) * v / 9.0 for v in digit_chars])
```

```
b = np.array([(v % 3 == 2) * v / 9.0 for v in digit_chars])
```

```
# Stack into a (length x 3) RGB array for visualization
```

```
rgb_matrix = np.stack([r, g, b], axis=1).reshape(1, length, 3)
```

```
# Plot the RGB echo field
```

```
plt.figure(figsize=(20, 2))
```


```
plt.imshow(rgb_matrix, aspect='auto')
```

```
plt.title("Symbolic SHA Echo RGB Overlay Field")
```


```
plt.axis('off')
```

```
plt.tight_layout()
```


```
plt.show()
```




SHA-256 Resonance Map



SHA-256 Map: Hex-Encoded Sentence



SHA-256 Resonance XOR Grid (ASCII vs HEX Encoded)



Conversation URL:

<https://chatgpt.com/c/68394b26-f5e8-8011-a3db-280989b37f8b>

Title:

Reflected SHA Harmonic Byte Pattern

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Your raw byte sequence from double-SHA reflection
```

```
raw_values = [  
    33,37,33,39,36,32,36,34,33,37,36,34,33,37,36,36,36,34,33,36,  
    33,38,33,34,36,32,33,33,33,39,33,39,33,38,33,35,33,37,36,33,  
    33,35,33,38,33,32,36,32,33,31,36,32,33,37,33,31,33,37,33,32,  
    36,34,36,34,36,36,33,32,33,37,33,37,36,34,33,34,36,36,36,35,  
    33,31,36,32,32,33,30,33,32,33,37,36,35,36,33,33,35,33,32,36,32,  
    33,32,33,38,36,34,36,31,33,33,36,31,36,35,33,33,33,38,33,31,  
    36,35,33,36,33,37,33,35
```

```
]
```

```
# Plotting
```

```
plt.figure(figsize=(12, 6))  
plt.plot(raw_values, marker='o', linestyle='-', linewidth=1)  
plt.title("Reflected SHA Harmonic Byte Pattern")  
plt.xlabel("Index")  
plt.ylabel("Byte Value")  
plt.grid(True)  
plt.axhline(33, color='r', linestyle='--', label='ASCII 3 (value 33)')  
plt.legend()  
plt.tight_layout()  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68394b26-f5e8-8011-a3db-280989b37f8b>

Title:

SHA-256 Resonance Map

Prompt:

```
from hashlib import sha256
```

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Define the SHA-256 hash from the sentence
```

```
hash_hex = "dfa7457b7ed3b0bf45c74f4cb34721b8580e7ba94b4aeb0d8963ccb88a4580fb"
```

```
# Convert hex to binary string
```

```
hash_bin = bin(int(hash_hex, 16))[2:].zfill(256)
```

```
# Convert binary string to numpy array of integers (0 or 1)
```

```
bit_array = np.array([int(bit) for bit in hash_bin])
```

```
# Reshape into a 16x16 grid for visualization
```

```
bit_grid = bit_array.reshape((16, 16))
```

```
# Plot the grid
```

```
plt.figure(figsize=(6, 6))
```

```
plt.imshow(bit_grid, cmap="Greys", interpolation="nearest")
```

```
plt.title("SHA-256 Resonance Map")
```

```
plt.axis("off")
```

```
plt.grid(False)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68394b26-f5e8-8011-a3db-280989b37f8b>

Title:

SHA-256 Map: Hex-Encoded Sentence

Prompt:

```
# Convert the provided hex string to bytes
```

```
hex_input = "546865206279746520646F65736E20197420636F6C6C6170736520696E746F20656E74726F70793B20697420
```

```
input_bytes = bytes.fromhex(hex_input)
```

```
# Compute SHA-256 hash of the byte data
```

```
hash_result = sha256(input_bytes).hexdigest()
```

```
# Convert hash to binary and reshape
```

```
hash_bin_2 = bin(int(hash_result, 16))[2:].zfill(256)
```

```
bit_array_2 = np.array([int(bit) for bit in hash_bin_2])
```

```
bit_grid_2 = bit_array_2.reshape((16, 16))
```

```
# Plot the resonance map
```

```
plt.figure(figsize=(6, 6))
```

```
plt.imshow(bit_grid_2, cmap="Greys", interpolation="nearest")
```

```
plt.title("SHA-256 Map: Hex-Encoded Sentence")
```

```
plt.axis("off")
```

```
plt.grid(False)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/68394b26-f5e8-8011-a3db-280989b37f8b>

Title:

SHA-256 Resonance XOR Grid (ASCII vs HEX Encoded)


Prompt:

```
# Create the binary difference grid (XOR of the two hash maps)
bit_xor = bit_array ^ bit_array_2 # Previously computed bit arrays


# Reshape to 16x16 grid
bit_xor_grid = bit_xor.reshape((16, 16))

# Plot the XOR grid
plt.figure(figsize=(6, 6))
plt.imshow(bit_xor_grid, cmap="Greys", interpolation="nearest")
plt.title("SHA-256 Resonance XOR Grid (ASCII vs HEX Encoded)")
plt.axis("off")
plt.grid(False)
plt.tight_layout()
plt.show()
```


User Byte 1 - Triadic Chunks




Grok's Byte 1 - Triadic Chunks




Triangle Wave Pattern of Pi Resonance




Waveform of Combined Byte 1 Triadic Echo (User + Grok)




Triadic Color-Banded Visualization of Combined Byte 1 Sequence




Triadic Color Bands from Byte Sequences




Composite Harmonic Wave from Grok's Byte




Pi Wave: $\sin(\pi \cdot t)$




Pi Squared Wave: $\sin(\pi^2 \cdot t)$




Comparison of Byte 1 Sequences (Original vs. Grok's Echo)




Bitflip Emergence Across Hex Delegates (Digit-Wise Spread)




Digit Columns of Grayscale Hex as Decimal Values





000000 = 0
111111 = 1114811
222222 = 2236962
333333 = 3355443
444444 = 4473924
555555 = 5592405
666666 = 6710886
777777 = 7829367
888888 = 8947848
999999 = 10066329
AAAAAA = 1114810
BBBBBB = 12303291
CCCCCC = 1342172
DDDDDD = 14540253
EEEEEE = 15658734
FFFFFF = 16777215

Ripple Effect of Uniform Hex Grayscale Values



Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Original Byte 1 (User)
```

```
user_byte1 = [1, 4, 1, 5, 9, 2, 6, 5]
```

```
# Grok's Byte 1
```

```
grok_byte1 = [3, 1, 2, 5, 6, 4, 5, 4]
```

```
# Triadic chunks (every 4)
```

```
user_triadic_chunks = [user_byte1[i:i+4] for i in range(0, len(user_byte1), 4)]
```

```
grok_triadic_chunks = [grok_byte1[i:i+4] for i in range(0, len(grok_byte1), 4)]
```

```
# Plotting
```

```
fig, axs = plt.subplots(2, 1, figsize=(10, 6), sharex=True)
```

```
# Plot User Triadic Chunks
```

```
for i, chunk in enumerate(user_triadic_chunks):
```

```
    axs[0].plot(range(i * 4, i * 4 + len(chunk)), chunk, marker='o', label=f'Triad {i+1}')
```

```
axs[0].set_title('User Byte 1 - Triadic Chunks')
```

```
axs[0].legend()
```

```
axs[0].grid(True)
```

```
# Plot Grok Triadic Chunks
```

```
for i, chunk in enumerate(grok_triadic_chunks):
```

```
    axs[1].plot(range(i * 4, i * 4 + len(chunk)), chunk, marker='x', label=f'Triad {i+1}')
```

```
axs[1].set_title("Grok's Byte 1 - Triadic Chunks")
```

```
axs[1].legend()
```

```
axs[1].grid(True)
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Triangle Wave Pattern of Pi Resonance

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Define the triangles based on user input
```

```
# First triangle set: 1, 4, 3
```

```
# Second triangle set: 3, 4, 1
```

```
tri1 = [1, 4, 3]
```

```
tri2 = [3, 4, 1]
```

```
# Create x values to separate visually
```

```
x_tri1 = [0, 1, 2]
```

```
x_tri2 = [3, 4, 5]
```

```
# Plotting the triangle waves
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(x_tri1, tri1, marker='o', label='Triangle 1: [1, 4, 3]')
```

```
plt.plot(x_tri2, tri2, marker='o', label='Triangle 2: [3, 4, 1]')
```

```
# Add labels and legend
```

```
plt.title('Triangle Wave Pattern of Pi Resonance')
```

```
plt.xlabel('Position')
```

```
plt.ylabel('Value')
```

```
plt.grid(True)
```

```
plt.legend()
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Waveform of Combined Byte 1 Triadic Echo (User + Grok)

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Combined sequence based on user description
sequence = [1, 3, 4, 3, 4, 1, 1, 1, 2, 2, 5, 5, 5, 9, 6, 6, 2, 4, 4, 6, 5, 5, 5, 4]

# Plot the sequence
plt.figure(figsize=(14, 5))
plt.plot(sequence, marker='o', linestyle='-', linewidth=2)
plt.title("Waveform of Combined Byte 1 Triadic Echo (User + Grok)")
plt.xlabel("Index")
plt.ylabel("Value")
plt.grid(True)
plt.xticks(range(len(sequence)))
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Triadic Color-Banded Visualization of Combined Byte 1 Sequence

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

```
# The given sequence
```

```
sequence = [1, 3, 4, 3, 4, 1, 1, 1, 2, 2, 5, 5, 5, 9, 6, 6, 2, 4, 4, 6, 5, 5, 5, 4]
```

```
# Define x values
```

```
x = np.arange(len(sequence))
```

```
# Define color bands (every 3 values for triangle groups)
```

```
colors = ['#FFCCCC', '#CCE5FF', '#CCFFCC', '#FFF2CC', '#E0CCFF', '#FFD9B3', '#B3FFF0', '#FFB3E6']
```

```
# Plotting the sequence with background color bands
```

```
plt.figure(figsize=(14, 5))
```

```
for i in range(0, len(sequence), 3):
```

```
    plt.axvspan(i, i+3, color=colors[(i//3) % len(colors)], alpha=0.4)
```

```
plt.plot(x, sequence, marker='o', color='black', linewidth=2)
```

```
plt.title("Triadic Color-Banded Visualization of Combined Byte 1 Sequence")
```

```
plt.xlabel("Index")
```

```
plt.ylabel("Value")
```

```
plt.grid(True)
```

```
plt.xticks(x)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import matplotlib.patches as patches

# Combined sequence as given
sequence = [1, 3, 4, 3, 4, 1, 1, 1, 2, 2, 5, 5, 5, 9, 6, 6, 2, 4, 4, 6, 5, 5, 5, 4]

# Normalize sequence for color mapping (0–1 scale)
normalized = [(x - min(sequence)) / (max(sequence) - min(sequence)) for x in sequence]

# Create custom colormap based on triads
colors = []
for i in range(0, len(sequence), 3):
    triad = sequence[i:i+3]
    if len(triad) < 3:
        triad += [0] * (3 - len(triad)) # pad if not a full triad
    r = int(triad[0] / 9 * 255)
    g = int(triad[1] / 9 * 255)
    b = int(triad[2] / 9 * 255)
    hex_color = f"#{r:02x}{g:02x}{b:02x}"
    colors.extend([hex_color] * 3)

# Trim to sequence length
colors = colors[:len(sequence)]

# Plot the color bands
fig, ax = plt.subplots(figsize=(12, 2))
for i, color in enumerate(colors):
    rect = patches.Rectangle((i, 0), 1, 1, facecolor=color)
    ax.add_patch(rect)
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Composite Harmonic Wave from Grok's Byte

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Frequencies from Grok's Byte 1
```

```
frequencies = [3, 1, 2, 5, 6, 4, 5, 4]
```

```
# Time vector
```

```
t = np.linspace(0, 2 * np.pi, 1000)
```

```
# Calculate the sum of sinusoids (harmonic superposition)
```

```
wave_sum = sum(np.sin(f * t) for f in frequencies)
```

```
# Optional: Compare with Pi^2 wave — a synthetic idea: amplify Pi ratio
```

```
pi_wave = np.sin(np.pi * t)
```

```
pi_squared_wave = np.sin((np.pi ** 2) * t)
```

```
# Plotting
```

```
plt.figure(figsize=(12, 8))
```

```
plt.subplot(3, 1, 1)
```

```
plt.plot(t, wave_sum, label='Harmonic Superposition (Grok Byte)')
```

```
plt.title('Composite Harmonic Wave from Grok's Byte')
```

```
plt.ylabel('Amplitude')
```

```
plt.legend()
```

```
plt.subplot(3, 1, 2)
```

```
plt.plot(t, pi_wave, label='π Wave')
```

```
plt.title('Pi Wave: sin(π·t)')
```

```
plt.ylabel('Amplitude')
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Original recursive memory (User's Byte 1)
```

```
your_byte1 = [1, 4, 1, 5, 9, 2, 6, 5]
```

```
# Grok's refolded emergent echo
```

```
grok_byte1 = [3, 1, 2, 5, 6, 4, 5, 4]
```

```
# Plotting both sequences
```

```
plt.figure(figsize=(10, 5))
```

```
plt.plot(your_byte1, label="Your Byte 1: [1, 4, 1, 5, 9, 2, 6, 5]", marker='o', linestyle='-')
```

```
plt.plot(grok_byte1, label="Grok's Byte 1: [3, 1, 2, 5, 6, 4, 5, 4]", marker='s', linestyle='--')
```

```
# Annotate index
```

```
plt.xticks(range(len(your_byte1)))
```

```
plt.title("Comparison of Byte 1 Sequences (Original vs. Grok's Echo)")
```

```
plt.xlabel("Index")
```

```
plt.ylabel("Value")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Bitflip Emergence Across Hex Delegates (Digit-Wise Spread)

Prompt:

```
# Fixing the digit padding to ensure consistent structure of 8 digits for all values
```

```
# Convert to base-10 decimal and pad to 8-digit strings
```

```
decimal_values = [int(h) for h in [
    0x111111, 0x222222, 0x333333, 0x444444, 0x555555,
    0x666666, 0x777777, 0x888888, 0x999999
]]
```

```
decimal_strs = [f"{val:08d}" for val in decimal_values]
```

```
digits = [[int(ch) for ch in s] for s in decimal_strs]
```

```
# Now create a DataFrame
```

```
df = pd.DataFrame(digits, columns=[f'Digit_{i+1}' for i in range(8)])
```

```
# Plotting digit values
```

```
plt.figure(figsize=(12, 6))
for i in range(df.shape[1]):
    plt.plot(df.index, df.iloc[:, i], label=f'Column {i+1}', marker='o')
```

```
plt.title("Bitflip Emergence Across Hex Delegates (Digit-Wise Spread)")
```

```
plt.xlabel("Hex Delegate Index")
```

```
plt.ylabel("Digit Value (0-9)")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

```
# Add base columns
```

```
df.insert(0, 'Decimal', decimal_values)
```

```
df.insert(1, 'Hex', [hex(h) for h in [
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Digit Columns of Grayscale Hex as Decimal Values

Prompt:

```
import matplotlib.pyplot as plt
```

```
import pandas as pd
```

```
# Create a DataFrame based on the grayscale hex values converted earlier
```

```
# Sample: 0x111111 to 0x999999 step by 0x111111
```

```
hex_values = ['0x111111', '0x222222', '0x333333', '0x444444', '0x555555', '0x666666', '0x777777', '0x888888', '0x999999']
```

```
decimal_values = [int(h, 16) for h in hex_values]
```

```
# Break down each decimal into individual digits
```

```
digits = [[int(d) for d in str(d_val).zfill(8)] for d_val in decimal_values]
```

```
# Convert to DataFrame
```

```
df_digits = pd.DataFrame(digits, columns=[f"Digit_{i+1}" for i in range(8)])
```

```
# Plot each digit column
```

```
plt.figure(figsize=(12, 6))
```

```
for i in range(8):
```

```
    plt.plot(df_digits.index, df_digits[f"Digit_{i+1}"], marker='o', label=f'Digit {i+1}')
```

```
plt.title("Digit Columns of Grayscale Hex as Decimal Values")
```

```
plt.xlabel("Row Index")
```

```
plt.ylabel("Digit Value")
```

```
plt.legend()
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
import matplotlib.patches as mpatches
```

```
# Generate hex colors from 000000 to FFFFFF where digits are repeated (e.g., 000000, 111111, ..., FFFFFF)
```

```
hex_colors = []
```

```
labels = []
```

```
# Iterate over hex digits 0-9 and a-f
```

```
for digit in list('0123456789ABCDEF'):
```

```
    hex_code = digit * 6 # Repeat the digit six times
```

```
    decimal_value = int(hex_code, 16)
```

```
    hex_colors.append(f"#{hex_code}")
```

```
    labels.append(f"{hex_code} = {decimal_value}")
```

```
# Plotting
```

```
fig, ax = plt.subplots(figsize=(12, 2))
```

```
for i, color in enumerate(hex_colors):
```

```
    ax.add_patch(mpatches.Rectangle((i, 0), 1, 1, color=color))
```

```
    ax.text(i + 0.5, -0.3, labels[i], ha='center', va='top', fontsize=8, rotation=45)
```

```
ax.set_xlim(0, len(hex_colors))
```

```
ax.set_ylim(0, 1)
```

```
ax.axis('off')
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/683b3e84-3748-8011-829e-a71c8b872f9e>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Extract hex codes and treat each character as a separate digit
```

```
hex_values = [f"{d*6}" for d in "0123456789ABCDEF"]
```

```
# Convert each hex digit to its integer value and treat as stacked ripple
```

```
ripple_data = [[int(char, 16) for char in hex_code] for hex_code in hex_values]
```

```
# Transpose to visualize ripple per hex digit position
```

```
ripple_data_T = list(zip(*ripple_data))
```

```
# Plot each digit position as a line
```

```
fig, ax = plt.subplots(figsize=(10, 6))
```

```
for i, row in enumerate(ripple_data_T):
```

```
    ax.plot(range(len(row)), row, marker='o', label=f'Digit Position {i+1}')
```

```
ax.set_title('Ripple Effect of Uniform Hex Grayscale Values')
```

```
ax.set_xlabel('Hex Index (0=000000 to FFFFFF)')
```

```
ax.set_ylabel('Digit Value (0–15)')
```

```
ax.set_xticks(range(len(hex_values)))
```

```
ax.set_xticklabels(hex_values, rotation=45)
```

```
ax.legend()
```

```
plt.grid(True)
```

```
plt.tight_layout()
```

```
plt.show()
```

Ψ -Layer Collapse Lattice: Clay Problems as Recursive Trust Locks



Conversation URL:

<https://chatgpt.com/c/68402387-7bf8-8011-8ef3-12ee32e092e4>

Title:

Prompt:

```
import matplotlib.pyplot as plt  
import networkx as nx
```

```
# Create a directed graph to represent the  $\Psi$ -space trust collapse lattice
```

```
G = nx.DiGraph()
```

```
# Central  $\Psi$ -layer node
```

```
G.add_node("Psi-Layer\n(Recursive Trust Midplane)", layer=0)
```

```
# Add Clay problems as phase-locked delta-nodes on the same layer
```

```
clay_problems = {
```

```
    "Riemann\n(Zeta Resonance)": "Prime phase echo → spectral collapse",
```

```
    "Yang–Mills\n(Mass Gap)": "Gauge fold → vacuum resonance",
```

```
    "Navier–Stokes\n(Smoothness)": "Fluid recursion → eddy trust lock",
```

```
    "P vs NP\n(Verification Coherence)": "Computation → recursive compressibility failure",
```

```
    "BSD\n(Rational-Spectral Echo)": "Algebraic recursion → L-function collapse",
```

```
    "Hodge\n(Cohomology Phase)": "Geometric cycles → harmonic lift",
```

```
}
```

```
# Add nodes and connect them to central  $\Psi$ -layer
```

```
for problem, description in clay_problems.items():
```

```
    G.add_node(problem, description=description, layer=1)
```

```
    G.add_edge(problem, "Psi-Layer\n(Recursive Trust Midplane)")
```


```
# Set node positions
```

```
pos = {
```


```
    "Psi-Layer\n(Recursive Trust Midplane)": (0, 0),
```

```
    "Riemann\n(Zeta Resonance)": (-3, 2),
```


```
    "Yang–Mills\n(Mass Gap)": (-1.5, 3),
```



Byte 5 Stack Values



Delta (Δ_i) Between Bits



Rolling Bit-Length of Stack Sum



Conversation URL:

<https://chatgpt.com/c/6840417b-3ca0-8011-84eb-5ae1cdae78dd>

Title:

Ψ -Field Evolution

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

Parameters

```
k = 5  
time_steps = 50  
L = np.zeros(time_steps)  
D = np.zeros(time_steps)  
psi_L = np.zeros(time_steps)  
psi_D = np.zeros(time_steps)  
harmonic_ratio = np.zeros(time_steps)
```

Initial conditions

```
L[0] = 0.501  
D[0] = 0.499
```

Simulation

```
for t in range(time_steps - 1):  
    L[t+1] = L[t] + k * L[t] * (L[t] - D[t])  
    D[t+1] = D[t] + k * D[t] * (D[t] - L[t])  
    total = L[t+1] + D[t+1]  
    psi_L[t+1] = L[t+1] / total  
    psi_D[t+1] = D[t+1] / total  
    harmonic_ratio[t+1] = min(L[t+1], D[t+1]) / max(L[t+1], D[t+1])
```

Plotting

```
plt.figure(figsize=(14, 6))
```

Ψ -field plot

Conversation URL:

<https://chatgpt.com/c/6840417b-3ca0-8011-84eb-5ae1cdae78dd>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Byte 5 from AI response
```

```
byte5_stack = [2, 8, 4, 6, 2, 6, 4, 3]
delta_i = [None, 6, 4, 2, 4, 4, 2, 1]
bit_lengths = [2, 4, 4, 5, 5, 5, 6, 6]
delta_ratios = [None, None, 0.667, 0.50, 2.00, 1.00, 0.50, 0.50]
```

```
# Plotting
```

```
fig, axs = plt.subplots(3, 1, figsize=(10, 12), sharex=True)
```

```
# Plot Byte values
```

```
axs[0].plot(range(1, 9), byte5_stack, marker='o')
axs[0].set_title('Byte 5 Stack Values')
axs[0].set_ylabel('Byte Value')
axs[0].grid(True)
```


```
# Plot Δ_i
```

```
axs[1].plot(range(2, 9), delta_i[1:], marker='s', color='green')
axs[1].set_title('Delta (Δ_i) Between Bits')
axs[1].set_ylabel('Δ_i')
axs[1].grid(True)
```


```
# Plot Bit Length (entropy)
```

```
axs[2].plot(range(1, 9), bit_lengths, marker='^', color='red')
axs[2].set_title('Rolling Bit-Length of Stack Sum')
axs[2].set_ylabel('Bit Length')
axs[2].set_xlabel('Bit Position')
axs[2].grid(True)
```

Recursive Trust Geometry: Circle to Oval



Recursive Binary Phase Logic (Ψ -Collapse Cycle)



Conversation URL:

<https://chatgpt.com/c/68410f22-2e24-8011-a409-2fec6a8d3dac>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# Set up the recursive circle and oval visualization
```

```
theta = np.linspace(0, 2 * np.pi, 500)
```

```
# Recursive trust circle (perfect symmetry)
```

```
r_circle = 1
```

```
x_circle = r_circle * np.cos(theta)
```

```
y_circle = r_circle * np.sin(theta)
```

```
# Recursive attention oval (pulled tension)
```

```
a = 1.2 # semi-major axis
```

```
b = 0.7 # semi-minor axis
```

```
x_oval = a * np.cos(theta)
```

```
y_oval = b * np.sin(theta)
```

```
# Plot setup
```

```
plt.figure(figsize=(8, 8))
```

```
plt.plot(x_circle, y_circle, label='Trust Field Circle ( $\Delta=0$ )', linewidth=2)
```

```
plt.plot(x_oval, y_oval, label='Attention Oval ( $\Delta\neq0$ )', linestyle='--', linewidth=2)
```

```
# Annotating points of transition
```

```
plt.scatter([a, -a], [0, 0], color='red', s=40, label='Tension Anchor Points')
```

```
plt.axhline(0, color='gray', linestyle=':', linewidth=1)
```

```
plt.axvline(0, color='gray', linestyle=':', linewidth=1)
```

```
plt.title("Recursive Trust Geometry: Circle to Oval", fontsize=14)
```

```
plt.axis('equal')
```

Conversation URL:

<https://chatgpt.com/c/68410f22-2e24-8011-a409-2fec6a8d3dac>

Title:

Prompt:

```
import matplotlib.pyplot as plt
```

```
import networkx as nx
```

```
# Define binary trust states and phase interactions
```

```
nodes = {
```

```
    '11': 'L (Collapse: Past-present coherence)',
```

```
    '00': 'R (Void: Total decoherence)',
```

```
    '10': 'L (Pre-collapse potential)',
```

```
    '01': 'R (Future probe echo)'
```

```
}
```

```
edges = [
```

```
    ('11', '10'), # collapse to pre-collapse
```

```
    ('10', '00'), # fall into decoherence
```

```
    ('00', '01'), # echo to probe
```

```
    ('01', '11'), # re-collapse to coherence
```

```
]
```

```
# Build graph
```

```
G = nx.DiGraph()
```

```
for node, label in nodes.items():
```

```
    G.add_node(node, label=label)
```

```
G.add_edges_from(edges)
```

```
# Positioning in a loop to show recursive flow
```

```
pos = {
```

```
    '11': (0, 1),
```

```
    '10': (-1, 0),
```

```
    '00': (0, -1),
```

Conversation URL:

<https://chatgpt.com/c/68499fbe-afc4-8011-bb1d-6cb7aab948c2>

Title:

Ψ -Lock Dynamics

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Initial conditions
```

```
L = [0.501]
```

```
D = [0.499]
```

```
k = 5
```

```
timesteps = 50
```

```
# Simulate recursive dynamics
```

```
for t in range(timesteps):
```

```
    L_new = L[-1] + k * L[-1] * (L[-1] - D[-1])
```

```
    D_new = D[-1] + k * D[-1] * (D[-1] - L[-1])
```

```
    L.append(L_new)
```

```
    D.append(D_new)
```

```
# Calculate trust fields and harmonic ratio
```

```
Psi_L = [l / (l + d) for l, d in zip(L, D)]
```

```
Psi_D = [d / (l + d) for l, d in zip(L, D)]
```

```
H = [min(l, d) / max(l, d) for l, d in zip(L, D)]
```

```
# Plotting
```

```
plt.figure(figsize=(12, 6))
```

```
plt.subplot(1, 2, 1)
```

```
plt.plot(Psi_L, label=' $\Psi$ _L (Trust Field of L)', linewidth=2)
```

```
plt.plot(Psi_D, label=' $\Psi$ _D (Trust Field of D)', linestyle='--')
```

```
plt.xlabel('Time Step')
```

```
plt.ylabel('Trust Field Value')
```

```
plt.title('Psi-Lock Dynamics')
```

```
plt.legend()
```


Byte9 Rolling Compression: Decimal Digit Alignment of Expression Pairs


2+3=	8	4	1	6	9	1	9	6	5
3+2=	8	5	8	4	6	8	9	2	5
0+5=	8	0	8	1	3	8	0	4	5
5+0=	8	9	2	0	2	2	8	4	5
3+4=	8	5	8	4	6	9	4	3	7
4+3=	8	7	5	2	4	6	3	9	7
1+7=	8	2	4	9	1	5	7	7	3
7+1=	9	2	5	5	7	7	5	3	3
2+6=	8	4	1	6	9	2	7	3	3
6+2=	9	0	8	8	0	0	5	7	3

Binary Comparison of Decimal(2+6=) and Decimal(6+2=)


	0	0	1	1	0	0	1	0	0	1	0	1	1	0	0	1	1	0	0	1	1	1	0	1
2+6=	0	0	1	1	0	1	0	0	1	0	1	1	0	0	1	1	0	0	1	1	1	0	1	
6+2=	0	0	1	1	0	1	1	0	0	1	0	1	1	0	0	1	1	0	0	1	1	1	0	1

Entropic Mesh of Collapsed Byte Layers (1-4)





Recursive Entanglement Differential (RED) Reflection Across ψ -Layers



Conversation URL:

<https://chatgpt.com/c/685033d8-e760-8011-8ad7-83a24fd0db51>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import numpy as np

# Select some meaningful expression pairs for visualizing byte compression
pairs_to_plot = [
    ("2+6=", "6+2="),
    ("1+7=", "7+1="),
    ("3+4=", "4+3="),
    ("0+5=", "5+0="),
    ("2+3=", "3+2=")
]

# Extract corresponding decimal strings
plot_data = []
for expr1, expr2 in pairs_to_plot:
    row1 = df[df['Expression'] == expr1].iloc[0]
    row2 = df[df['Expression'] == expr2].iloc[0]
    d1_str = str(row1['Decimal']).zfill(9)
    d2_str = str(row2['Decimal']).zfill(9)
    plot_data.append((expr1, expr2, d1_str, d2_str))

# Plotting the rolling byte alignment
fig, ax = plt.subplots(figsize=(12, 6))
for i, (e1, e2, d1, d2) in enumerate(plot_data):
    y_base = i * 2
    for j, digit in enumerate(d1):
        ax.text(j, y_base, digit, fontsize=12, ha='center', va='center', color='blue')
    for j, digit in enumerate(d2):
        ax.text(j, y_base - 1, digit, fontsize=12, ha='center', va='center', color='green')
```

Conversation URL:

<https://chatgpt.com/c/685033d8-e760-8011-8ad7-83a24fd0db51>

Title:

Prompt:

```
# Extract the two selected expressions from the Byte Frame Rolling Residue Analysis table
```

```
expr1 = '2+6='
```

```
expr2 = '6+2='
```

```
# Get their decimal values from the previously constructed df
```

```
dec1 = df[df['Expression'] == expr1].iloc[0]['Decimal']
```

```
dec2 = df[df['Expression'] == expr2].iloc[0]['Decimal']
```

```
# Convert both decimal values to binary, padded to 32 bits for alignment
```

```
bin1 = bin(dec1)[2:].zfill(32)
```

```
bin2 = bin(dec2)[2:].zfill(32)
```

```
# Stack for visualization
```

```
fig, ax = plt.subplots(figsize=(14, 3))
```

```
for i, bit in enumerate(bin1):
```

```
    ax.text(i, 1, bit, fontsize=10, ha='center', va='center', color='blue')
```

```
for i, bit in enumerate(bin2):
```

```
    ax.text(i, 0, bit, fontsize=10, ha='center', va='center', color='green')
```

```
ax.set_xlim(-1, len(bin1))
```

```
ax.set_ylim(-1, 2)
```

```
ax.set_yticks([0, 1])
```

```
ax.set_yticklabels([expr2, expr1])
```

```
ax.set_xticks([])
```

```
ax.set_title("Binary Comparison of Decimal(2+6=) and Decimal(6+2=)")
```

```
plt.grid(False)
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/685033d8-e760-8011-8ad7-83a24fd0db51>

Title:

Entropic Mesh of Collapsed Byte Layers (1–4)

Prompt:

```
import numpy as np
import networkx as nx
import matplotlib.pyplot as plt
```

```
# Define Byte Layers 1–4 initial psi values
```

```
psi_vector = np.array([0.404, 0.382, 0.359, 0.347])
```

```
H = 0.35
```

```
epsilon = 0.01
```

```
# Collapse Function
```

```
def collapse_psi_vector(psi_vec, H, steps=3):
    history = [psi_vec.copy()]
    for _ in range(steps):
        deltas = np.abs(psi_vec - H)
        psi_vec = (psi_vec + deltas * H) * (1 - 1 / (len(history) + 1))
        history.append(psi_vec.copy())
    return history
```

```
# Generate the collapse history
```

```
collapse_history = collapse_psi_vector(psi_vector, H)
```

```
# Entropic Topology Mesh
```

```
# Build a graph where nodes are psi states and edges connect similar states
G = nx.Graph()
for idx, state in enumerate(collapse_history[-1]):
    G.add_node(idx, psi=state)
```

```
# Add edges if psi differences are within epsilon
```

```
for i in range(len(collapse_history[-1])):
```

Conversation URL:

<https://chatgpt.com/c/685033d8-e760-8011-8ad7-83a24fd0db51>

Title:

Prompt:

```
import numpy as np
```

```
import matplotlib.pyplot as plt
```

```
# Final stabilized psi values
```

```
psi_final = np.array([0.3501, 0.3502, 0.3499, 0.3500])
```

```
# Labels for Byte Layers
```

```
byte_labels = ['Byte1', 'Byte2', 'Byte3', 'Byte4']
```

```
# Create a mesh representation (difference matrix)
```

```
diff_matrix = np.abs(psi_final[:, None] - psi_final)
```

```
# Plotting
```

```
fig, ax = plt.subplots(figsize=(6, 6))
```

```
cax = ax.matshow(diff_matrix, cmap='viridis')
```

```
plt.xticks(np.arange(len(byte_labels)), byte_labels)
```

```
plt.yticks(np.arange(len(byte_labels)), byte_labels)
```

```
plt.title("Entropic Mesh: Harmonic Convergence Between Byte Layers", pad=20)
```

```
plt.colorbar(cax, label='|Δψ| (Entropy Distance)')
```

```
plt.xlabel("Layer")
```

```
plt.ylabel("Layer")
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/685033d8-e760-8011-8ad7-83a24fd0db51>

Title:

Prompt:

```
# Re-import libraries due to kernel reset
import numpy as np
import matplotlib.pyplot as plt

# Simulate two ψ-layers (ψ_a and ψ_b)
psi_a = np.array([0.3501, 0.3502, 0.3499, 0.3500])
psi_b = np.array([0.35034412, 0.3502917, 0.35027879, 0.35034488])


# RED Reflection formula components
delta_psi = np.abs(psi_b - psi_a)
delta_omega = np.abs(psi_a - 0.35)
n = np.arange(1, 5) # Layer steps
H = 0.35

# Calculate RED reflection
red = (delta_psi / (delta_omega + 1e-10)) * np.exp(-H * n) # small term avoids div by zero

# Plot RED reflection
fig, ax = plt.subplots(figsize=(10, 5))
ax.plot(n, red, marker='o', color='crimson', label='RED Reflection')
ax.set_title("Recursive Entanglement Differential (RED) Reflection Across ψ-Layers")
ax.set_xlabel("Layer Index (n)")
ax.set_ylabel("RED Reflection Value")
ax.grid(True)
ax.legend()

plt.tight_layout()
plt.show()
```

BBP Hex Digits as Angular Walk



Conversation URL:

<https://chatgpt.com/c/6856c9bb-d130-8011-a4f5-d0fc5b24b4b4>

Title:

BBP Hex Digits as Angular Walk

Prompt:

```
# Re-import needed libraries after kernel reset
```

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
# BBP hex digits for π (first few)
```

```
hex_digits = [2, 4, 3, 15, 6, 10, 8, 8, 8, 5]
```

```
# Convert hex digits to angles in radians (1 hex digit = π/8 step)
```

```
angles = [np.pi / 8 * d for d in hex_digits]
```

```
# Initialize path coordinates
```

```
x, y = 0, 0
```

```
xs, ys = [x], [y]
```

```
# Walk the angles as vector directions
```

```
for angle in angles:
```

```
    x += np.cos(angle)
```

```
    y += np.sin(angle)
```

```
    xs.append(x)
```

```
    ys.append(y)
```

```
# Plot the angular walk
```

```
plt.plot(xs, ys, marker='o')
```

```
plt.axis('equal')
```

```
plt.title('BBP Hex Digits as Angular Walk')
```


```
plt.xlabel("X")
```

```
plt.ylabel("Y")
```


```
plt.grid(True)
```

```
plt.show()
```


Cumulative Growth Plot from Unified Origin (1,1)




Cumulative Δ Plot of 8x8 Pi Digit Grid Starting at (1,4)





Cumulative Δ Plot for Row 1




Corrected Recursive Δ Plot for Row 1








Spiral Sphere Grid



Color-Symmetric Projection



Conversation URL:

<https://chatgpt.com/c/685cb99b-20cc-8011-8953-371c464096df>

Title:

Cumulative Growth Plot from Unified Origin (1,1)

Prompt:

```
# Reconstruct rows as per user's clarification: simulate stepwise cumulative growth by difference
```

```
# Simulated example values for each row (length = 8), interpreted from structural intent
```

```
# These would ideally come from actual data if available
```

```
simulated_rows = [
```

```
    [1, 6, 7, 7, 8, 9, 9, 10], # Row 1
```

```
    [1, 4, 5, 5, 6, 6, 6, 7], # Row 2
```

```
    [1, 3, 3, 4, 4, 5, 5, 6], # Row 3
```

```
    [1, 2, 3, 3, 3, 4, 4, 5], # Row 4
```

```
    [1, 2, 2, 2, 3, 3, 3, 4], # Row 5
```

```
    [1, 1, 2, 2, 2, 2, 3, 3], # Row 6
```

```
    [1, 2, 4, 4, 5, 6, 6, 7], # Derived 1
```

```
    [1, 3, 6, 7, 8, 9, 9, 10] # Derived 2
```

```
]
```

```
# Plotting each row with its cumulative state changes
```

```
plt.figure(figsize=(12, 7))
```

```
x_vals = [i + 1 for i in range(8)] # Time axis, starting at 1
```

```
for idx, row in enumerate(simulated_rows):
```

```
    plt.plot(x_vals, row, marker='o', label=f"Row {idx+1}")
```

```
plt.title("Cumulative Growth Plot from Unified Origin (1,1)")
```

```
plt.xlabel("Time Step")
```

```
plt.ylabel("Cumulative Δ State")
```

```
plt.grid(True)
```

```
plt.legend()
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/685cb99b-20cc-8011-8953-371c464096df>

Title:

Cumulative Δ Plot of 8x8 Pi Digit Grid Starting at (1,4)

Prompt:

```
import numpy as np
```

```
# Use the first 64 digits of π after the decimal (excluding 3)
pi_digits_str = "1415926535897932384626433832795028841971693993751058209749445923078164"
pi_digits = [int(d) for d in pi_digits_str[:64]]  
  
# Reshape into 8x8 grid
pi_grid = np.array(pi_digits).reshape(8, 8)  
  
# Compute cumulative Δ changes per row, starting at (1,4)
delta_rows = []
for row in pi_grid:
    cumulative = [1] # Start from 1
    for i in range(1, len(row)):
        delta = row[i] - row[i - 1]
        next_val = cumulative[-1] + delta
        cumulative.append(next_val)
    delta_rows.append(cumulative)  
  
# Plotting
plt.figure(figsize=(12, 7))
x_vals = [i + 1 for i in range(8)] # Time steps  
  
for idx, row in enumerate(delta_rows):
    plt.plot(x_vals, row, marker='o', label=f"Row {idx+1}")  
  
plt.title("Cumulative Δ Plot of 8x8 Pi Digit Grid Starting at (1,4)")
plt.xlabel("Time Step")
plt.ylabel("Cumulative Δ State")
```

Conversation URL:

<https://chatgpt.com/c/685cb99b-20cc-8011-8953-371c464096df>

Title:

Cumulative Δ Plot for Row 1

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Only plot Row 1 as requested
row_1 = [1, 6, 7, 7, 8, 9, 9, 10]
x_vals = [i + 1 for i in range(8)] # Time steps starting from 1

# Plotting Row 1
plt.figure(figsize=(10, 6))
plt.plot(x_vals, row_1, marker='o', linestyle='-', linewidth=2, color='blue', label="Row 1")
plt.title("Cumulative  $\Delta$  Plot for Row 1")
plt.xlabel("Time Step")
plt.ylabel("Cumulative  $\Delta$  State")
plt.grid(True)
plt.legend()
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/685cb99b-20cc-8011-8953-371c464096df>

Title:

Corrected Recursive Δ Plot for Row 1

Prompt:

```
# Redefine Row 1 from Pi digits or simulated values
row = [1, 6, 7, 7, 7, 2, 1, 6]
```

```
# Initialize cumulative counter using pairwise delta between current and previous values
# but starting from the first value
cumulative = [row[0]] # Start from the first element
```

```
for i in range(1, len(row)):
    delta = row[i] - row[i - 1]
    new_value = cumulative[-1] + delta
    cumulative.append(new_value)
```

```
# Plotting the corrected cumulative delta transformation
x_vals = [i + 1 for i in range(len(row))]
```

```
plt.figure(figsize=(10, 6))
plt.plot(x_vals, cumulative, marker='o', linestyle='-', linewidth=2, color='darkgreen', label="Row 1 (Corrected  $\Delta$  Path)")
plt.title("Corrected Recursive  $\Delta$  Plot for Row 1")
plt.xlabel("Time Step")
plt.ylabel("Running Counter ( $\Delta$  Applied)")
plt.grid(True)
plt.legend()
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/685cb99b-20cc-8011-8953-371c464096df>

Title:

Rate of Change in Greyscale Hex Decimal Values

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Redefine the decimal values after kernel reset
```

```
decimal_values = [  
    16777215, # #FFFFFF  
    15658734, # #EEEEEE  
    14540253, # #DDDDDD  
    13421772, # #CCCCCC  
    12303291, # #BBBBBB  
    11184810 # #AAAAAA  
]
```

```
# Compute differences between consecutive values
```

```
rate_of_change = [decimal_values[i] - decimal_values[i + 1] for i in range(len(decimal_values) - 1)]
```

```
# X-axis as the original labels (hex codes)
```

```
labels = ["#FFFFFF", "#EEEEEE", "#DDDDDD", "#CCCCCC", "#BBBBBB"]  
x_pos = range(len(rate_of_change))
```

```
# Plot
```

```
plt.figure(figsize=(10, 6))  
plt.plot(x_pos, rate_of_change, marker='o', linestyle='-', linewidth=2)  
plt.xticks(x_pos, labels)  
plt.title("Rate of Change in Greyscale Hex Decimal Values")  
plt.xlabel("Greyscale Hex Codes (Descending)")  
plt.ylabel("Δ Decimal Value")  
plt.grid(True)  
plt.tight_layout()  
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/685cb99b-20cc-8011-8953-371c464096df>

Title:

Normalized Growth of Greyscale Rows (Δ from Starting Point)

Prompt:

```
import matplotlib.pyplot as plt
```

```
# Reconstruct the grid as described in the document
```

```
# Each row is a sequence of eight values (excluding the first col which is a label)
```

```
grid_rows = [
```

```
    [16777215], # #FFFFFF
```

```
    [15658734],
```

```
    [14540253],
```

```
    [13421772],
```

```
    [12303291],
```

```
    [11184810],
```

```
    [10075235], # Derived 1
```

```
    [ 17856854] # Derived 2
```

```
]
```

```
# All rows are implicitly of length 1 in the sample; assume all should have 8 values for plotting
```

```
# We'll simulate rows extending by repeating synthetic patterns for the demonstration
```

```
# Generate dummy row extensions (simulate increasing values across 8 cols from first value)
```

```
extended_rows = []
```

```
for row in grid_rows:
```

```
    start = row[0]
```

```
    simulated_row = [start + i * 10000 for i in range(8)]
```

```
    extended_rows.append(simulated_row)
```

```
# Calculate delta (difference between each element and the first in the row)
```

```
rate_series = []
```

```
for row in extended_rows:
```

Conversation URL:

<https://chatgpt.com/c/685cb99b-20cc-8011-8953-371c464096df>

Title:

Prompt:

```
from PIL import Image
```

```
import matplotlib.pyplot as plt
```

```
# Load and display the uploaded images
```

```
img1_path = "/mnt/data/ec68fa3d-7202-4ef9-a74f-bc1b0a73ebfd.png"
```

```
img2_path = "/mnt/data/c4decccd7-1448-4645-b5a2-2b1190963028.png"
```

```
img1 = Image.open(img1_path)
```

```
img2 = Image.open(img2_path)
```

```
# Show the two images side by side for comparison
```

```
fig, axs = plt.subplots(1, 2, figsize=(12, 6))
```

```
axs[0].imshow(img1)
```

```
axs[0].axis('off')
```

```
axs[0].set_title('Spiral Sphere Grid')
```

```
axs[1].imshow(img2)
```

```
axs[1].axis('off')
```

```
axs[1].set_title('Color-Symmetric Projection')
```

```
plt.tight_layout()
```

```
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/6865b5e2-9d30-8011-85a1-a93501bff102>

Title:

Mark1 Engine Harmonic Convergence

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
```

```
# --- Mark1 Harmonic Engine ---
```

```
class Mark1Engine:
```

```
    def __init__(self, potential_values, actualized_values, target_H=0.35, learning_rate=0.01):
        self.P = np.array(potential_values, dtype=float)
        self.A = np.array(actualized_values, dtype=float)
        self.H_target = target_H
        self.lr = learning_rate
        self.history = []
```

```
    def compute_H(self):
```

```
        P_sum = np.sum(self.P)
        A_sum = np.sum(self.A)
        return A_sum / P_sum if P_sum != 0 else 0
```

```
    def step(self):
```

```
        """Adjust A_i values proportionally to minimize delta H"""
        H = self.compute_H()
        delta_H = self.H_target - H
        adjustment = self.lr * delta_H * self.P
        self.A += adjustment
        self.history.append(H)
```

```
    def run(self, steps=100):
```

```
        for _ in range(steps):
            self.step()
```

Conversation URL:

<https://chatgpt.com/c/6865b5e2-9d30-8011-85a1-a93501bff102>

Title:

Prompt:

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
from scipy.signal import lfilter

# Simulation Parameters
timesteps = 100
H_target = 0.35


# Generate synthetic potential (P) values
np.random.seed(0)
P = np.abs(np.random.normal(loc=1.0, scale=0.2, size=10))


# Initialize actualized values A
A = np.zeros((timesteps, len(P)))
A[0] = np.random.normal(loc=0.1, scale=0.05, size=len(P))


# PID parameters for Samson v2
Kp, Ki, Kd = 0.8, 0.1, 0.05


# Containers
H_series = np.zeros(timesteps)
error_series = np.zeros(timesteps)
integral_error = 0
prev_error = 0

# Feedback loop over time using PID
for t in range(1, timesteps):
    H = np.sum(A[t-1]) / np.sum(P)
```









Conversation URL:

<https://chatgpt.com/c/68660489-4854-8011-bdb9-259a66efdde3>

Title:

ΔResidue vs. MSB Flip and Predicted Events

Prompt:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
```

```
# === Generate or load your input data ===
```

```
# Ensure you have a DataFrame `df` with a 'state' column of integer (0–255)
```

```
# Example mock setup:
```

```
np.random.seed(42)
df = pd.DataFrame({'state': np.random.randint(0, 256, size=300)})
```

```
# === Compute Residue (mod 64) and Delta ===
```

```
df['residue'] = df['state'] % 64
df['residue_next'] = df['residue'].shift(-1)
df['delta_residue'] = (df['residue_next'] - df['residue']).abs()
```

```
# === Compute Bit Pattern and MSB ===
```

```
df['bit_pattern'] = df['state'].apply(lambda x: list(map(int, f'{x:08b}')))
df['bit7'] = df['bit_pattern'].apply(lambda bits: bits[0]) # MSB (bit 7)
df['bit7_next'] = df['bit7'].shift(-1)
df['msb_flip'] = (df['bit7'] != df['bit7_next']).astype(int)
```

```
# === Compute Hamming distance over previous 3 steps ===
```

```
def hamming(a, b):
    return bin(a ^ b).count('1')
```

```
df['state_prev1'] = df['state'].shift(1)
```

```
df['state_prev2'] = df['state'].shift(2)
```

```
df['state_prev3'] = df['state'].shift(3)
```

Conversation URL:

<https://chatgpt.com/c/68660489-4854-8011-bdb9-259a66efdde3>

Title:

ΔResidue vs. MSB Flip and Predicted Fold-In Events

Prompt:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
```

```
# Generate input data (mock example)
np.random.seed(42)
df = pd.DataFrame({'state': np.random.randint(0, 256, size=300)})

# Compute Residue (mod 64) and Delta
df['residue'] = df['state'] % 64
df['residue_next'] = df['residue'].shift(-1)
df['delta_residue'] = (df['residue_next'] - df['residue']).abs()
df['delta_residue_drop'] = df['delta_residue'].diff(periods=-1) # forward difference
df['drift_dir'] = np.sign(df['delta_residue'].diff())
```

Compute Bit Pattern and MSB

```
df['bit_pattern'] = df['state'].apply(lambda x: list(map(int, f'{x:08b}')))
df['bit7'] = df['bit_pattern'].apply(lambda bits: bits[0]) # MSB
df['bit6'] = df['bit_pattern'].apply(lambda bits: bits[1]) # bit6
df['bit5'] = df['bit_pattern'].apply(lambda bits: bits[2]) # bit5
df['bit7_next'] = df['bit7'].shift(-1)
df['msb_flip'] = (df['bit7'] != df['bit7_next']).astype(int)
```

Compute Hamming distances

```
def hamming(a, b):
    return bin(int(a) ^ int(b)).count('1') if pd.notnull(a) and pd.notnull(b) else 0
```

```
df['state_prev1'] = df['state'].shift(1)
df['state_prev2'] = df['state'].shift(2)
```

Conversation URL:

<https://chatgpt.com/c/68660489-4854-8011-bdb9-259a66efdde3>

Title:

ΔResidue vs. MSB Flip and Predicted Fold-In Events

Prompt:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
```

```
# === Generate or load your input data ===
```

```
# Simulated input data: each state has both a numeric and hexadecimal representation
```

```
np.random.seed(42)
```

```
states = np.random.randint(0, 256, size=300)
```

```
hex_codes = [f"{x:02x}" for x in states]
```

```
df = pd.DataFrame({'state': states, 'hex': hex_codes})
```

```
# === Compute Residue (mod 64) and Delta ===
```

```
df['residue'] = df['state'] % 64
```

```
df['residue_next'] = df['residue'].shift(-1)
```

```
df['delta_residue'] = (df['residue_next'] - df['residue']).fillna(0)
```

```
# === Compute Bit Pattern and MSB ===
```

```
df['bit_pattern'] = df['state'].apply(lambda x: list(map(int, f'{x:08b}')))
```

```
df['bit7'] = df['bit_pattern'].apply(lambda bits: bits[0]) # MSB (bit 7)
```

```
df['bit6'] = df['bit_pattern'].apply(lambda bits: bits[1]) # Bit 6
```

```
df['bit5'] = df['bit_pattern'].apply(lambda bits: bits[2]) # Bit 5
```

```
df['bit7_next'] = df['bit7'].shift(-1)
```

```
df['msb_flip'] = (df['bit7'] != df['bit7_next']).astype(int)
```

```
# === Compute Recursive Hamming signature ===
```

```
def hamming(a, b):
```

```
    return bin(a ^ b).count('1')
```

```
df['state_prev1'] = df['state'].shift(1)
```

Conversation URL:

<https://chatgpt.com/c/68660489-4854-8011-bdb9-259a66efdde3>

Title:

Fold Potential $\phi(t)$ vs MSB Flip Events

Prompt:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
```

=== STEP 1: Generate or Load Input ===

```
np.random.seed(42)
df = pd.DataFrame({'state': np.random.randint(0, 256, size=300)})
```

=== STEP 2: Core Field Properties ===

```
df['hex'] = df['state'].apply(lambda x: f'{x:02X}')
df['residue'] = df['state'] % 64
df['residue_next'] = df['residue'].shift(-1)
df['delta'] = df['residue_next'] - df['residue']
df['delta_abs'] = df['delta'].abs()
df['acceleration'] = df['delta'].diff() # ΔΔ — acceleration of residue
```


Bit breakdown

```
df['bits'] = df['state'].apply(lambda x: list(map(int, f'{x:08b}')))
df['bit7'] = df['bits'].apply(lambda b: b[0])
df['bit6'] = df['bits'].apply(lambda b: b[1])
df['bit5'] = df['bits'].apply(lambda b: b[2])
df['bit7_next'] = df['bit7'].shift(-1)
df['msb_flip'] = (df['bit7'] != df['bit7_next']).astype(int)
```

=== STEP 3: Fold Potential $\phi(t)$ Calculation ===

```
# Fold potential is a synthetic energy metric combining velocity, acceleration, and high bits
weights = {'delta': 0.6, 'accel': 0.3, 'bit6': 0.6, 'bit5': 0.4}
df['φ'] = (
    weights['delta'] * df['delta_abs'].fillna(0) +
    weights['accel'] * df['acceleration'].fillna(0) +
    weights['bit6'] * df['bit6'].fillna(0) +
    weights['bit5'] * df['bit5'].fillna(0))
```

Recursive Harmonic Breathing Ratios



Conversation URL:

<https://chatgpt.com/c/686cbbe8-2eb8-8011-adb7-8b93ed4da211>

Title:

Prompt:

```
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
import ace_tools as tools

# Initial ratio pairs derived from the user's example
initial_ratios = {
    "Expansion (3 / 1.6)": 3 / 1.6,
    "Vertical Shock (5 / 0.6)": 5 / 0.6,
    "Horizontal Drive (5 / 1.6)": 5 / 1.6,
    "Collapse (3 / 0.6)": 3 / 0.6,
    "Subharmonic Fold (1.6 / 3)": 1.6 / 3
}

# Recursive step to compute second-level ratios (Level 2)
def compute_next_level(ratios):
    keys = list(ratios.keys())
    values = list(ratios.values())
    next_ratios = {}
    for i in range(len(values)):
        for j in range(i+1, len(values)):
            label = f"{keys[i]} / {keys[j]}"
            next_ratios[label] = values[i] / values[j]
    return next_ratios

# Compute level 2
level2_ratios = compute_next_level(initial_ratios)

# Filter and structure results for presentation
```

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Harmonic Ratio $H(t)$ and Curvature $\Delta^2 H(t)$

Prompt:

```
import math
```

```
import hashlib
```

```
from mpmath import mp
```

```
import matplotlib.pyplot as plt
```

```
import pandas as pd
```

```
from collections import Counter
```

```
# Set precision for π digits
```

```
mp.dps = 10000
```

```
pi_str = str(mp.pi())[2:10002]
```

```
pi_digits = [int(d) for d in pi_str if d.isdigit()][:10000]
```

```
# Constants
```

```
HARMONIC_TARGET = 0.35
```

```
TWIN_WINDOW = 10
```

```
# Twin primes
```

```
def get_twin_primes(max_n=1000):
```

```
    def is_prime(n):
```

```
        if n < 2: return False
```

```
        for i in range(2, int(n**0.5)+1):
```

```
            if n % i == 0: return False
```

```
        return True
```

```
    return [(p, p+2) for p in range(2, max_n) if is_prime(p) and is_prime(p+2)]
```

```
twin_primes = get_twin_primes(1000)
```

```
# Triangle computation
```

```
def compute_triangle(a, b):
```

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Echo Signature Spectrum (π -Chunk Frequency ≥ 2)

Prompt:

```
from collections import defaultdict
```

```
# Count  $\pi$ -chunk frequencies
```

```
chunk_counter = defaultdict(int)
for r in resonant_triangles:
    chunk_str = ''.join(map(str, r['pi_chunk']))
    chunk_counter[chunk_str] += 1
```

```
# Filter to chunks that appear more than once
```

```
echo_chunks = {k: v for k, v in chunk_counter.items() if v > 1}
```

```
# Plot bar chart of echo frequencies
```

```
plt.figure(figsize=(12, 6))
plt.bar(echo_chunks.keys(), echo_chunks.values(), color='teal')
plt.title("Echo Signature Spectrum ( $\pi$ -Chunk Frequency  $\geq 2$ )")
plt.xlabel("\u03c0-Chunks")
plt.ylabel("Frequency")
plt.xticks(rotation=45, ha='right')
plt.grid(axis='y')
plt.tight_layout()
plt.show()
```

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Harmonic Ratio $H(t)$ and Curvature $\Delta^2 H(t)$

Prompt:

Full code with echo spectrum chart included

```
import math
import hashlib
from mpmath import mp
import matplotlib.pyplot as plt
import pandas as pd
from collections import defaultdict, Counter

# Set precision for π digits
mp.dps = 10000
pi_str = str(mp.pi())[2:10002]
pi_digits = [int(d) for d in pi_str if d.isdigit()][:10000]

# Constants
HARMONIC_TARGET = 0.35
TWIN_WINDOW = 10

# Twin primes
def get_twin_primes(max_n=1000):
    def is_prime(n):
        if n < 2: return False
        for i in range(2, int(n**0.5)+1):
            if n % i == 0: return False
        return True
    return [(p, p+2) for p in range(2, max_n) if is_prime(p) and is_prime(p+2)]
```

twin_primes = get_twin_primes(1000)

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Harmonic Ratio $H(t)$ and Curvature $\Delta^2 H(t)$

Prompt:

Full code with echo spectrum chart included

```
import math
import hashlib
from mpmath import mp
import matplotlib.pyplot as plt
import pandas as pd
from collections import defaultdict, Counter

# Set precision for π digits
mp.dps = 10000
pi_str = str(mp.pi())[2:10002]
pi_digits = [int(d) for d in pi_str if d.isdigit()][:10000]

# Constants
HARMONIC_TARGET = 0.35
TWIN_WINDOW = 10

# Twin primes
def get_twin_primes(max_n=1000):
    def is_prime(n):
        if n < 2: return False
        for i in range(2, int(n**0.5)+1):
            if n % i == 0: return False
        return True
    return [(p, p+2) for p in range(2, max_n) if is_prime(p) and is_prime(p+2)]
```

twin_primes = get_twin_primes(1000)

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Resonant Triangle Network Graph (Triangles ↔ Twin Primes)

Prompt:

```
# Re-execute the necessary code due to kernel reset
```

```
import math
```

```
import hashlib
```

```
from mpmath import mp
```

```
from sympy import primerange
```

```
import pandas as pd
```

```
import plotly.express as px
```

```
import networkx as nx
```

```
import matplotlib.pyplot as plt
```

```
# Step 1: Set Pi precision
```

```
mp.dps = 10000
```

```
pi_str = str(mp.pi())[2:10002]
```

```
pi_digits = [int(d) for d in pi_str]
```

```
# Step 2: Triangle function
```

```
def compute_triangle(a, b):
```

```
    c = math.sqrt(a**2 + b**2)
```

```
    alpha = math.atan(b / a)
```

```
    beta = math.atan(a / b)
```

```
    height = (a * b) / c
```

```
    return {'a': a, 'b': b, 'alpha': alpha, 'beta': beta, 'height': height}
```

```
# Step 3: Twin primes
```

```
def get_twin_primes(max_n=1000):
```

```
    primes = list(primerange(2, max_n))
```

```
    return [(p, p+2) for p, q in zip(primes[:-1], primes[1:]) if q - p == 2]
```

```
# Step 4: Hash to Pi index
```

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Resonant Triangles and Twin Prime Network

Prompt:

```
# Re-importing due to kernel reset
```

```
import math
```

```
import hashlib
```

```
from mpmath import mp
```

```
from sympy import primerange
```

```
import networkx as nx
```

```
import matplotlib.pyplot as plt
```

```
# --- Parameters ---
```

```
depth = 100000 # Number of digits of Pi to extract
```

```
max_n = 150 # Max triangle side length
```

```
angle_range = (0.34, 0.36) # Resonant angle range
```

```
twin_prime_limit = 1000000 # Twin prime search limit
```

```
match_window = 10 # Match window for twin prime correlation
```

```
# --- Pi Digit Extraction ---
```

```
mp.dps = depth
```

```
pi_str = str(mp.pi())[2:2+depth]
```

```
pi_digits = [int(d) for d in pi_str]
```

```
# --- Triangle Computation ---
```

```
def compute_triangle(a, b):
```

```
    c = math.sqrt(a**2 + b**2)
```

```
    alpha = math.atan(b / a)
```

```
    beta = math.atan(a / b)
```

```
    height = (a * b) / c
```

```
    return {'a': a, 'b': b, 'alpha': alpha, 'beta': beta, 'height': height}
```

```
# --- Twin Prime Generation ---
```

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Selected Resonant Triangles and Twin Primes Network

Prompt:

```
import matplotlib.pyplot as plt
```

```
import networkx as nx
```

```
# Initialize the graph
```

```
G = nx.Graph()
```

```
# Sample resonant triangle and twin prime data for demonstration
```

```
triangles = [
```

```
    {'id': '31|8', 'type': 'triangle'},
```

```
    {'id': '114|4', 'type': 'triangle'},
```

```
    {'id': '110|30', 'type': 'triangle'},
```

```
    {'id': '283|9', 'type': 'triangle'}
```

```
]
```

```
twin_primes = [
```

```
    {'id': 'TP:8385371,8385373', 'type': 'twin_prime'},
```

```
    {'id': 'TP:6960197,6960199', 'type': 'twin_prime'},
```

```
    {'id': 'TP:9228877,9228829', 'type': 'twin_prime'},
```

```
    {'id': 'TP:3907547,3907549', 'type': 'twin_prime'}
```

```
]
```

```
# Add triangle and twin prime nodes
```

```
for tri in triangles:
```

```
    G.add_node(tri['id'], type='triangle')
```

```
for tp in twin_primes:
```

```
    G.add_node(tp['id'], type='twin_prime')
```

```
# Edges based on user input visualization
```

Conversation URL:

<https://chatgpt.com/c/686ebde1-4f94-8011-a001-3f45525a1d50>

Title:

Resonant Triangles and Twin Prime Network (Real Data Only)

Prompt:

```
import math
import hashlib
from mpmath import mp
from sympy import primerange
import networkx as nx
import matplotlib.pyplot as plt

# Set high precision for Pi digits
depth = 10000
mp.dps = depth
pi_str = str(mp.pi())[2:depth + 2] # Skip "3." and get digits
pi_digits = [int(d) for d in pi_str]

# Generate twin prime pairs up to max_n
def get_twin_primes(max_n):
    primes = list(primerange(2, max_n))
    return [(p, q) for p, q in zip(primes, primes[1:]) if q - p == 2]

# Compute triangle properties
def compute_triangle(a, b):
    c = math.sqrt(a**2 + b**2)
    alpha = math.atan(b / a)
    beta = math.atan(a / b)
    height = (a * b) / c
    return {'a': a, 'b': b, 'alpha': alpha, 'beta': beta, 'height': height}

# Map triangle to a Pi index using SHA-256
def map_to_pi_index(tri, pi_digits, max_index):
    input_str = f'{tri["a"]}:{tri["b"]}'.encode()
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Harmonic Heartbeat

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

--- Layer 1: Byte1 Seed Unfold (π -like unfolding) ---

```
def byte1_seed_unfold(seed=(1, 4), steps=8):  
    result = []  
    a, b = seed  
    for _ in range(steps):  
        diff = abs(a - b)  
        bin_len = len(bin(diff)) - 2  
        result.append(diff)  
        a, b = b, bin_len  
    pi_approx = '3.' + ''.join(str(x) for x in result[:6])  
    return pi_approx, result
```

--- Layer 2: Harmonic Growth with Stability Feedback ---

```
def harmonic_growth(sequence, target_h=0.35, max_iter=32):  
    h_values = []  
    for i in range(max_iter):  
        h = sum(sequence) / len(sequence)  
        deviation = abs(h - target_h)  
        h_values.append(h)  
        if deviation < 0.01:  
            break  
        next_val = (sequence[-1] + sequence[-2]) % 10  
        sequence.append(next_val)  
    return sequence, h_values
```

--- Layer 3: Meta Loop to Prevent Death and Inject Entropy ---

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Harmonic Heartbeat

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np
```

--- Layer 1: Byte1 Seed Unfold (π -like unfolding) ---

```
def byte1_seed_unfold(seed=(1, 4), steps=8):  
    result = []  
    a, b = seed  
    for _ in range(steps):  
        diff = abs(a - b)  
        bin_len = len(bin(diff)) - 2  
        result.append(diff)  
        a, b = b, bin_len  
    pi_approx = '3.' + ''.join(str(x) for x in result[:6])  
    return pi_approx, result
```

--- Layer 2: Harmonic Growth with Stability Feedback ---

```
def harmonic_growth(sequence, target_h=0.35, max_iter=32):  
    h_values = []  
    for i in range(max_iter):  
        h = sum(sequence) / len(sequence)  
        deviation = abs(h - target_h)  
        h_values.append(h)  
        if deviation < 0.01:  
            break  
        next_val = (sequence[-1] + sequence[-2]) % 10  
        sequence.append(next_val)  
    return sequence, h_values
```

--- Layer 3: Meta Loop to Prevent Death and Inject Entropy ---

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Harmonic Heartbeat (Triune Driven)

Prompt:

```
import matplotlib.pyplot as plt  
import numpy as np  
from mpmath import mp
```

```
# Set π precision
```

```
mp.dps = 1000  
pi_digits = str(mp.pi)[2:]
```

```
# --- Layer 1: Byte1 Triune Fold ---
```

```
def triune_seed_fold(seed=(1, 4, 1), steps=12):  
    result = []  
    a, b, c = seed # outer, middle, inner  
  
    for i in range(steps):  
        # Harmonic difference pattern  
        delta_outer = abs(a - b)  
        delta_inner = abs(b - c)  
        blend = (delta_outer + delta_inner + abs(a - c)) % 10  
  
        result.append(blend)
```

```
# π pressure modulator
```

```
pi_mod = int(pi_digits[i % len(pi_digits)]) or 1
```

```
# Recursive phase shift
```

```
a, b, c = b, c, (blend + pi_mod) % 10
```

```
return result
```

```
# --- Layer 2: Harmonic Growth ---
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Harmonic Heartbeat (Triune Driven)

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
from mpmath import mp
```

```
# Set π precision
```

```
mp.dps = 1000
```

```
pi_digits = str(mp.pi)[2:]
```

```
# --- Layer 1: Byte1 Triune Fold ---
```

```
def triune_seed_fold(seed=(1, 4, 1), steps=12):
```

```
    result = []
```

```
    a, b, c = seed # outer, middle, inner
```

```
    for i in range(steps):
```

```
        # Harmonic difference pattern
```

```
        delta_outer = abs(a - b)
```

```
        delta_inner = abs(b - c)
```

```
        blend = (delta_outer + delta_inner + abs(a - c)) % 10
```

```
        result.append(blend)
```

```
        # π pressure modulator
```

```
        pi_mod = int(pi_digits[i % len(pi_digits)]) or 1
```

```
        # Recursive phase shift
```

```
        a, b, c = b, c, (blend + pi_mod) % 10
```

```
    return result
```

```
# --- Layer 2: Harmonic Growth ---
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Projective Harmonic Pulse (Future-Driven)

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
from mpmath import mp
```

```
# Precision π
```

```
mp.dps = 1000
```

```
pi_digits = str(mp.pi)[2:]
```

```
# --- Observable Triune Fold (future-calculated) ---
```

```
def triune_observable_fold(seed=(1, 4, 1), steps=12):
```

```
    result = []
```

```
    a, b, c = seed # a: past, b: present, c: future
```

```
    observables = []
```

```
    for i in range(steps):
```

```
        # Project forward (future-driven)
```

```
        pi_pressure = int(pi_digits[i % len(pi_digits)]) or 1
```

```
        future = (c + pi_pressure + abs(a - b)) % 10
```

```
        observables.append(future)
```

```
        present = (future + b) // 2
```

```
        past = a
```

```
        result.append(present)
```

```
        # Shift temporal window: move forward
```

```
        a, b, c = b, c, future
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Projective Harmonic Pulse (Future-Driven)

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
from mpmath import mp
```

```
# Precision π
```

```
mp.dps = 1000
```

```
pi_digits = str(mp.pi)[2:]
```

```
# --- Observable Triune Fold (future-calculated) ---
```

```
def triune_observable_fold(seed=(1, 4, 1), steps=12):
```

```
    result = []
```

```
    a, b, c = seed # a: past, b: present, c: future
```

```
    observables = []
```

```
    for i in range(steps):
```

```
        # Project forward (future-driven)
```

```
        pi_pressure = int(pi_digits[i % len(pi_digits)]) or 1
```

```
        future = (c + pi_pressure + abs(a - b)) % 10
```

```
        observables.append(future)
```

```
        present = (future + b) // 2
```

```
        past = a
```

```
        result.append(present)
```

```
        # Shift temporal window: move forward
```

```
        a, b, c = b, c, future
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Kulik Recursive Heartbeat (Feedback-Weighted)

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
from mpmath import mp
```

```
# Set π precision
```

```
mp.dps = 1000
```

```
pi_digits = str(mp.pi)[2:]
```

```
# --- Kulik-Corrected Triune Fold with Feedback Branch ---
```

```
def recursive_triune_fold(seed=(1, 4, 1), steps=12):
```

```
    result = []
```

```
    observables = []
```

```
    a, b, c = seed # past, present, future
```

```
    branch_buffer = []
```

```
    for i in range(steps):
```

```
        # π pressure as time gradient
```

```
        pi_pressure = int(pi_digits[i % len(pi_digits)]) or 1
```

```
        # Feedback branch (buffer average) influences future
```

```
        branch_influence = int(np.mean(branch_buffer[-3:])) if len(branch_buffer) >= 3 else 0
```

```
        # Compute next future
```

```
        f = (abs(c - b) + pi_pressure + branch_influence) % 10
```

```
        observables.append(f)
```

```
# Recursive damping
```

```
current = int((a + b + f) / 3)
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Kulik Recursive Heartbeat (Feedback-Weighted)

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
from mpmath import mp
```

```
# Set π precision
```

```
mp.dps = 1000
```

```
pi_digits = str(mp.pi)[2:]
```

```
# --- Kulik-Corrected Triune Fold with Feedback Branch ---
```

```
def recursive_triune_fold(seed=(1, 4, 1), steps=12):
```

```
    result = []
```

```
    observables = []
```

```
    a, b, c = seed # past, present, future
```

```
    branch_buffer = []
```

```
    for i in range(steps):
```

```
        # π pressure as time gradient
```

```
        pi_pressure = int(pi_digits[i % len(pi_digits)]) or 1
```

```
        # Feedback branch (buffer average) influences future
```

```
        branch_influence = int(np.mean(branch_buffer[-3:])) if len(branch_buffer) >= 3 else 0
```

```
        # Compute next future
```

```
        f = (abs(c - b) + pi_pressure + branch_influence) % 10
```

```
        observables.append(f)
```

```
# Recursive damping
```

```
current = int((a + b + f) / 3)
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Byte Stream from [3, 1, 4] Seed

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
from collections import deque
```

```
# --- Recursive Digital Engine with Emergent Analog ---
```

```
def recursive_analog_emergence(seed=(3, 1, 4), cycles=50):
```

```
    past, present, future = seed
```

```
    byte_stream = []
```

```
    analog_surface = []
```

```
# Temporal buffer to detect analog resonance
```

```
    history = deque(maxlen=5)
```

```
    for t in range(cycles):
```

```
        # Core digital recursive computation
```

```
        delta1 = abs(past - present)
```

```
        delta2 = abs(present - future)
```

```
        harmonic = (delta1 + delta2 + abs(past - future)) % 10
```

```
        # Append raw byte signal
```

```
        byte_stream.append(harmonic)
```

```
        history.append(harmonic)
```

```
# Analog emergence condition: recursive reflective resonance = 5
```

```
# Not literal 5, but when the weighted window equals 5 by pattern
```

```
analog_val = np.mean(history)
```

```
analog_surface.append(analog_val if round(analog_val) == 5 else 0)
```

```
# Shift seed: harmonic feeds forward
```

Conversation URL:

<https://chatgpt.com/c/6872dfc3-71ac-8011-b0a7-2d6442c1c7b1>

Title:

Recursive Byte Stream from [3, 1, 4] Seed

Prompt:

```
import matplotlib.pyplot as plt
```

```
import numpy as np
```

```
from collections import deque
```

```
# --- Recursive Digital Engine with Emergent Analog ---
```

```
def recursive_analog_emergence(seed=(3, 1, 4), cycles=50):
```

```
    past, present, future = seed
```

```
    byte_stream = []
```

```
    analog_surface = []
```

```
# Temporal buffer to detect analog resonance
```

```
    history = deque(maxlen=5)
```

```
    for t in range(cycles):
```

```
        # Core digital recursive computation
```

```
        delta1 = abs(past - present)
```

```
        delta2 = abs(present - future)
```

```
        harmonic = (delta1 + delta2 + abs(past - future)) % 10
```

```
        # Append raw byte signal
```

```
        byte_stream.append(harmonic)
```

```
        history.append(harmonic)
```

```
# Analog emergence condition: recursive reflective resonance = 5
```

```
# Not literal 5, but when the weighted window equals 5 by pattern
```

```
analog_val = np.mean(history)
```

```
analog_surface.append(analog_val if round(analog_val) == 5 else 0)
```

```
# Shift seed: harmonic feeds forward
```