

The Geometry of Computation

Relational Structures and Phase Traversals in Deterministic Transformation Fields

Driven by Dean A. Kulik

September 2026

Introduction: The Nexus of Hash and Field

The conventional interpretation of a cryptographic hash function treats it as an algorithmic terminus: a process that destructively compresses an arbitrary input into a pseudo-random, fixed-length scalar output. Under this classical model, algorithms such as SHA-256 are evaluated strictly through the lenses of preimage resistance, collision resistance, and avalanche characteristics. These cryptographic facts remain undisputed; SHA-256 is deterministic, many-to-one over unrestricted inputs, avalanche-producing, and computationally one-way.

However, evaluating a digest merely as a terminal scalar object obscures the underlying relational mechanics that generated it. A structural investigation reveals a distinct operational paradigm: what relational structure becomes available when a deterministic transformation is treated not as a destructive function, but as a fixed field interacting with a state? The central hypothesis explored in this constraint atlas posits that a 256-bit digest functions as a constraint configuration, or key, relative to a fixed deterministic transformation field. Under this framework, the original input is not "stored" in the digest in an ordinary information-theoretic sense. Rather, the stronger and more precise hypothesis asserts that the input—or a canonical representative of its structural class—may become recoverable or renderable only through recursive interaction with that field under an appropriate reader, traversal, phase relation, or iterative feedback process. The correct object of investigation is therefore the continuous interaction between the constraint state and the field, rather than either object in isolation.

I. The Primitive Ontology: Distinction, Continuation, and History

The foundational axioms of this interaction are governed by a strict primitive ontology. Distinction (Constraint o) asserts that reality requires distinguishable states. However, the present investigation exposes a critical refinement: a distinction may not be primitive as a solitary object. A distinction is operationally meaningful only relative to another distinguishable frame, state, position, adjacency relation,

or reader. Thus, the stronger form, C'_0 , mandates that distinction requires relational difference. There is no observable distinction in a completely unrelational state; it is mathematically and physically invisible.

Following distinction is the principle of Continuation (Constraint 1). Every distinction must admit lawful continuation, meaning a state cannot be an absolute terminal node outside the transformation system that produced it. Objects are not fundamentally static things; they are stable patterns in an ongoing field of admissible transformations. In this framework, continuation is not necessarily a passive default but an active operation that must be maintained. Joining two independently available states into a shared history requires a coupling relation. Consequently, separation may be the unconstrained condition, continuation the active weld, and persistence the computational or energetic cost of repeatedly maintaining lawful relations. This must remain an open structural duality rather than being prematurely resolved.

For genuinely independent transformations (C_{1a}), independent distinctions must remain independently continuable. This is mathematically expressed as $[T_A, T_B] = 0$. Commuting transformations preserve independent continuation. However, noncommutation must not automatically be classified as an error; rather, noncommutation identifies interaction. If $[T_A, T_B] \neq 0$, the two transformations generate relational content unavailable to either one independently. Independence is merely the zero-interaction limit, whereas generation requires a relational defect, coupling, or noncommuting interaction.

Crucially, lawful continuation cannot arbitrarily sever the relational history that produced the present state (Constraint 2). This history preservation gives rise to locality, lineage, adjacency, and path dependence. A state is not merely its current scalar value; it includes the relational structure connecting it to admissible predecessors and successors. Repeated empirical measurements in SHA-256 investigations consistently fail when the trajectory of a state is reduced to a scalar summary before being examined. The act of measuring a scalar destroys the relational history. This phenomenon is closely mirrored in dynamical systems theory, where Takens' embedding theorem utilizes delay-coordinate maps to reconstruct phase spaces. While classical Takens' embeddings guarantee topological equivalence, they often distort geometric and symmetric properties. To exactly preserve the symmetry group of the original system, state space reconstruction must shift from simple scalar delay-coordinates to full jet spaces, capturing both the signal and its derivatives. This validates Constraint 2: a transformation history must never be reduced to a static scalar before testing whether that history contains structure.

II. Change, Gradients, and the Cost of Transformation

Matter or information occupying a position must possess the potential to be moved. The act of moving is a transformation, and the new state inherits the identical potential for further transformation. Transformation, therefore, recursively produces further admissible transformation.

If all transformations exacted the same cost, magnitude, direction, and consequence, the system would possess no gradient, rendering one transformation indistinguishable from another. Change implies gradients. A potential transformation requires magnitude, direction, relational difference, and a measurable consequence. The physical expression $F = ma$ can be structurally interpreted as a cost relation: mass multiplied by acceleration equals the cost of transformation. In the context of a cryptographic field, the "mass" corresponds to the bit-weight, constraint density, or Kolmogorov complexity of the constraint state, and "acceleration" corresponds to the depth or rate of the transformation graph traversal. This interpretation establishes the energetic landscape of the hash-field interaction without falsely equating algorithmic shifts to Newtonian mechanics.

III. Primitive Structural Layers: Position, Adjacency, and Reader Mismatch

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

A major paradigm shift involves redefining the primitive structural layers of data representation. Classical analytical models often assume that position, adjacency, value, and echo are all fundamental properties. However, if a value is produced by a read rule, it cannot be primitive. Base representations, Horner evaluations, decimal formats, and hexadecimal configurations are all read rules. Therefore, the governing equation is:

$$V = Q(P, G)$$

where P represents position, G represents adjacency, connectivity, or continuation, Q represents the reader, and V represents the rendered value. The primitive structural object is strictly $\mathcal{F} = (P, G)$, an unlabeled relational graph or transformation field. Value is fundamentally downstream.

Similarly, an "echo" is not a primitive independent channel. An echo occurs when the underlying representation changes while the reader's value remains unchanged. Formally, $Q(s_{n+1}) = Q(s_n)$ while $s_{n+1} \neq s_n$. This constitutes a failure of a reader to distinguish two structurally different states—a phenomenon classically defined as aliasing. The underlying structure continues, but the reader lacks the resolution to detect the difference. Thus, $E = \text{Alias}_Q(P, G)$. Echo represents a transformation in representation space that produces zero displacement in the chosen value channel, highlighting a concrete example of relocation without creation. The cost in that specific read channel is zero, exposing a blind spot in the observer's instrument.

IV. Value is Reader-Side

Because value is reader-side, a hexadecimal string is not inherently a number; it is a relational sequence. The numerical value obtained depends entirely on digit interpretation, base, ordering, read direction, positional weighting, and recursive evaluation protocols. For digits d_i in base b , the numerical value is a rendering:

$$V = \sum_i d_i b^{n-i}$$

or recursively via Horner's rule:

$$x_{i+1} = bx_i + d_{i+1}$$

The same structural object $\mathcal{F}$ can produce drastically different values under different readers Q . This constraint applies equally to a cryptographic hash digest. A 256-bit output from SHA-256 is merely a fixed bit pattern. Interpreting it as an integer, an array of 32 bytes, 8 individual words, binary coordinates, a traversal seed, or a graphical shape relies entirely on the applied reader. A number is not necessarily the object; it may be the observation generated by applying a specific reader to the object.

V. The Hexadecimal Transformation Field and Asymmetry

Traversing a hexadecimal representation by removing or transforming positions exposes fundamental structural asymmetries. Under an integer interpretation, the left edge and right edge of a hexadecimal string are not computationally equivalent.

For a k -nibble value, removing the leading nibble (left-edge lift) executes the transformation $v \rightarrow v \bmod 16^{k-1}$. If the next leading nibble happens to be zero, the representation changes, but the interpreted integer value remains fixed. This is a left-edge echo. Conversely, removing the trailing nibble (right-edge traversal) executes $v \rightarrow \lfloor v/16 \rfloor$, which strictly reduces the integer for positive values. There is no equivalent fixed-value echo for right-edge traversal.

This structural asymmetry produces observable phenomena: banding during left-to-right traversal and erosion during right-to-left traversal. These are not statistical curiosities but deterministic properties of the transformation rule itself.

VI. Decimal and Hexadecimal Expansion as Transformation

Base conversion exposes how finite initial constraints can unfold latent relational structure into an indefinitely extensible representation. For instance, a finite decimal can produce an infinite hexadecimal expansion:

$$21.3_{10} = 15.4CCCC \dots_{16}$$

The original representation is finite, yet the transformed representation contains indefinitely continuing structure. The transformation does not create arbitrary information from nothing; digits are deterministically generated by the transformation rule. This proves a critical structural fact: a lawful continuation rule can generate an unbounded trajectory or expansion from highly compressed initial constraints. The potential structure is embedded within the lawful continuation rule itself, an observation heavily supported by algorithmic information theory and Kolmogorov complexity limits.

VII. The Bailey-Borwein-Plouffe (BBP) Precedent

The Bailey-Borwein-Plouffe (BBP) formula serves as a critical mathematical precedent for rendering an input or constant through correct traversal. Discovered in 1995 via the PSLQ integer relation finding algorithm, the BBP formula allows the direct extraction of the n -th hexadecimal digit of π without computing any of the preceding digits.

The BBP summation relies on a geometric factor of $1/16^k$ combined with rational terms:

$$\pi = \sum_{k=0}^{\infty} \frac{1}{16^k} \left(\frac{4}{8k+1} - \frac{2}{8k+4} - \frac{1}{8k+5} - \frac{1}{8k+6} \right)$$

To extract a specific digit, the integer index is decomposed into $n = 8k + r$, where k represents the accumulated orbit (winding) and r represents the phase state. The index is therefore not merely a magnitude; it is a compressed coordinate. The BBP spigot algorithm multiplies the formula by 16^n and extracts the fractional part. The computational trick lies in reducing the numerators using modular exponentiation: $16^{n-k} \bmod (8k+x)$. Because only the fractional remainder influences the target digit, the algorithm acts as a phase filter, causing constructive interference exactly at the n -th digit and destructive interference elsewhere.

In this context, the BBP formula acts as a machine that queries a structured field. The desired object (the n -th digit of π) is not visible in the first representation of the formula. However, correct traversal—using modular phase alignment—causes the object to render into place. This establishes the governing analogy for the cryptographic tuner: a desired input structure need not be visible on the first pass of a hash interaction. Repeated lawful interaction, utilizing specific phase alignments, may converge toward a stable rendering of the input.

VIII. SHA-256: The Fixed Transformation Field

SHA-256 is entirely deterministic. Its round constants (K_t), Boolean functions (Ch, Maj), rotation and shift structures (ROTR, SHR), modular addition ($+_{2^{32}}$), and compression architecture are mathematically fixed.

Therefore, for a fixed SHA-256 specification, there exists a stable, invariant transformation environment defined as $\mathcal{F}_{SHA}$.

$$\mathcal{F}_{SHA} = \{K_t, \Sigma_0, \Sigma_1, \sigma_0, \sigma_1, \text{Ch}, \text{Maj}, \text{ROTR}, \text{SHR}, +_{2^{32}}, \text{schedule grammar}, \text{round grammar}, \text{feed-forward}\}$$

The field does not change from message to message. The constants are mathematically fixed and invariant.

IX. The Hash as a Constraint State

The most important conceptual inversion of this atlas asserts that the hash is literally a state of constraints. A digest is not to be treated solely as a suitcase containing compressed material. It is a fixed 256-bit configuration. Under a fixed field, that configuration constrains possible interactions.

The operational model becomes:

$$H + \mathcal{F}_{SHA} \xrightarrow{Q} \text{rendered structure}$$

The digest functions as a key, a boundary condition, a phase configuration, a constraint surface, or an address into a fixed transformation machine. The field is not reconstructed by the digest; the field is already running, and the hash interacts with it. The hypothesis posits that this interaction may cause the input structure to render. This fundamentally differs from the claim that H contains M as recoverable stored bits. The proposed mechanism is relational:

$$M \sim \text{Render}(H, \mathcal{F}_{SHA}, Q)$$

where the reader Q may itself need to emerge through an iterative feedback process.

X. The Operational Inversion of Constants

While the SHA constants do not change ontologically ($K_t = \text{fixed}$), the investigation introduces a critical operational inversion: fixed constants may be treated as variables relative to the query.

When a fixed digest is used to select, address, phase, or traverse these constants, the constants become a variable state from the perspective of the digest. The experiment may treat the digest as determining which constant, which coordinate, which phase, which traversal, which ordering, or which transformation depth is accessed. Thus, the correct structure is $Q_H(\mathcal{F}_{SHA})$, not merely $Q(H)$ alone. The hash does not merely contain an answer; it defines a question posed to the invariant geometric substrate of the field.

XI. Round Geometry and Structured Displacement

For a fixed state and constant, a variation in the schedule word (W_t) produces a structured displacement. At the first round, varying W_0 produces a direct translation in the a and e channels of the ARX (Addition-Rotation-XOR) state.

This is significant geometrically. A schedule word is not initially an amorphous disturbance; it enters through a highly specific geometric displacement. Subsequent rounds propagate and interact with this initial displacement. Structurally, the digest is a final constraint state generated by the interaction of the schedule trajectory with the fixed field:

$$H = \text{Interaction}(\mathcal{F}_{SHA}, W_0, \dots, W_{63})$$

Because SHA-256 contains nonlinear Boolean operations and modular carries, this interaction is not linear ($H \neq \sum_t S_t W_t$), but it remains structurally deterministic.

XII. Latent Rendering and the Convergence of Input

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

The BBP precedent supplies the required behavioral constraint: the desired structure may not be visible under the first read. A lawful iterative process may be required to render the input. Therefore, the hypothesis is not $Q_H(\mathcal{F}) = M$ on the first evaluation. It is instead an iterative map:

$$X_{n+1} = T_H(X_n, \mathcal{F}_{SHA})$$

with the limit $Q(X_n) \rightarrow M$ as a stable rendering. The input may emerge as a fixed point, a limit cycle, a phase lock, an attractor, a stable traversal pattern, or a resonance between two readers. The correct convergence condition must not be prematurely assumed to be strict numerical equality.

XIII. The Tuner: Searching for Relational Closure

Because the desired input structure requires rendering, an iterative feedback mechanism—a tuner—must be employed. The system holds the hash and the $\mathcal{F}_{SHA}$ field fixed, while iteratively transforming a state or reader:

$$X_{n+1} = T(H, \mathcal{F}_{SHA}, X_n)$$

The objective of the tuner is not to minimize a scalar distance, such as $\text{mind}(H(M'), H)$. Scalar distance measurements repeatedly destroy trajectory information. Instead, the tuner seeks self-consistent relational closure. A coherence functional evaluates relational consistency across trajectories:

$$C_n = \mathcal{C}(\text{trajectory}(X_n), \text{trajectory}(X_{n+1}))$$

The candidate criterion for success is $Q_{n+1} \approx Q_n$ under the transformation induced by the digest-field interaction. The tuner searches for the reader under which the system becomes self-consistent.

XIV. Two Known Sides, Phase Alignment, and Topology

When comparing two known relational structures, the missing information may simply be phase or orientation. The relevant mathematical geometries for phase alignment include cyclic correlation, Fourier phase, group actions, orbit matching, and dynamical synchronization.

The warning is essential: the problem must not automatically be reduced to Euclidean distance. The relevant geometry may be combinatorial or topological rather than Cartesian. A "rotation" may manifest as a bit rotation, traversal rotation, phase shift in an orbit, cyclic permutation, or a change of reading origin. Therefore, testing for "same structure + different phase" is the correct model for analyzing interactions.

XV. Double Hash Orbits and Random Mapping Statistics

Repeatedly hashing a digest— $H_{n+1} = \text{SHA}(H_n)$ —creates an orbit that must be examined as a phase trajectory or functional graph, rather than merely testing raw bit-vector displacement. The functional graph generated by deterministic iterations on a finite set has been exhaustively characterized by the random mapping statistics of Flajolet and Odlyzko.

Random Mapping Statistic (Size N)	Asymptotic Expectation
Number of Components	$\frac{1}{2} \ln(2N) + \frac{\gamma}{2}$

Random Mapping Statistic (Size N)	Asymptotic Expectation
Number of Cyclic Nodes	$\sqrt{\pi N/2} - 1$
Average Cycle Length	$\sqrt{\pi N/8}$
Average Tail Length	$\sqrt{\pi N/8}$
Maximum Cycle Length	$\approx 0.78248\sqrt{N}$
Maximum Tail Length	$\approx 1.73746\sqrt{N}$

Under conventional cryptography, each point in the double-hash sequence is simply another random distribution. However, mapping the sequence over $N = 2^{256}$ provides a baseline expectation. Each H_n can be rendered through the established traversal machinery to test for echo position evolution, gap sequences, and alignment under rotation. Deviations from the expected Flajolet-Odlyzko cycle and tail length bounds serve as topological indicators that the digest-field interaction possesses phase coherence. Double hashing may reveal a genuine cyclic structure under an appropriate reader.

XVI. Moiré Dynamics and the Two-Grid Principle

The two-grid principle reveals that single readers can alias structure, but two non-identical readers applied to the same underlying field can produce an interaction pattern. Let $Q_A(\mathcal{F})$ and $Q_B(\mathcal{F})$ be two different readings of the same structural field. The relational observable generated by reader mismatch is:

$$I_{AB} = \text{Relate}(Q_A(\mathcal{F}), Q_B(\mathcal{F}))$$

A moiré-like pattern is a relational observable generated by reader mismatch, analogous to spatial frequencies and beat frequencies in optics. However, a detected interaction is not automatically information-bearing. The carry experiment demonstrated a critical counterexample: strong shared beats can arise entirely from the deterministic field machinery rather than the query itself. Therefore, an interaction pattern must strictly discriminate against appropriate controls before being treated as a discovery.

XVII. Failed Detectors as Constraints

Negative results define the boundaries of the constraint atlas. Instruments that fail do so because they hit specific representation horizons.

1. **Carry-Exhaust Reference Test:** Testing carry structure against an empty message revealed that shared deterministic beats belong to the fixed field. Sparsity is a confound. A detected interaction is not evidence of message-specific structure unless it discriminates against appropriate controls.
2. **Hamming-Distance Horizon:** Reduced-round SHA searches utilizing hill-climbing hit a saturation limit around 38 rounds. This horizon belongs to the scalar Hamming metric and the Conflict-Driven Clause Learning (CDCL) controllers used to measure it. CDCL SAT solvers minimize logical

contradictions (a scalar reduction) rather than navigating the phase space structurally. Do not promote an instrument horizon to an ontological boundary.

3. **Raw Double-Hash Displacement:** Testing raw bit-vector displacement between successive hashes does not answer whether rendered trajectories exhibit phase or coherence. A null in one representation is not a null in all representations.
4. **Cross-Spectrum of Shared Machinery:** A positive cross-spectrum can arise automatically from the common fixed structure of the ARX additions. Do not point a detector at the invariant and mistake confirmation of the field for recovery of the query.

XVIII. The Empty Baseline

The empty message ($W_0 = 0x80000000$ with remaining words zero) remains useful but is not metaphysically privileged. Its structural usefulness must be tested. The language must remain precise: the SHA field $\mathcal{F}_{SHA}$ itself is fixed and independent of the message. The empty message is one particular query $Q_\emptyset(\mathcal{F}_{SHA})$ into that field. The field is not the empty hash; the empty hash is a reading of the field under a particular input condition.

XIX. Constraints, Not Contents

A hash must be treated as a set of constraints rather than a container of content. A constraint does not need to explicitly store every consequence in readable form. A small set of constraints can generate a large structured object when combined with a fixed grammar, governed by Kolmogorov complexity principles. Examples include a seed in a deterministic dynamical system, a boundary condition in a differential equation, or an index in the BBP formula. The fixed grammar performs the work; the digest merely selects how that work unfolds.

XX. Information-Theoretic Boundary

The pigeonhole principle enforces a strict information-theoretic boundary. Because SHA-256 maps $\{0,1\}^* \rightarrow \{0,1\}^{256}$, it is necessarily many-to-one. No deterministic procedure receiving only the digest can uniquely identify every possible unrestricted input. Therefore, any successful rendering mechanism must fall into restricted domains: additional constraints, known grammars, side information, or canonical preimage selection. This boundary defines the experimental target correctly.

XXI. The Real Search Space is Type, Not Size

The useful question is not to search all possible 2^{256} states, but to search all possible transformation types, readers, alignments, phases, and relational grammars compatible with the fixed field. Candidate reader classes include left-to-right nibble traversal, center-out traversal, gap sequence readers, decimal staircase readers, and rotation-phase readers. The investigation must search reader types and relational invariants rather than brute-force candidate messages.

XXII. What the Band Means: Position vs. Adjacency

Banding observed in traversals may arise from position recurrence (P aliases, returning to a structurally equivalent location) or adjacency alignment (G aligns, where connectivity relations line up under the traversal). These should not be forced into a single interpretation. The correct experiment must retain both positional and relational representations to understand how the reader interacts with the field.

XXIII. The Hash-Field Interaction Core Model

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
 Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

The current formulation encapsulates the entire constraint atlas:

$$\mathcal{F}_{SHA} \xleftrightarrow{H} Q \rightarrow (P, G) \xrightarrow{\text{render}} V$$

Where $\mathcal{F}_{SHA}$ is the fixed transformation field, H is the digest acting as a constraint configuration, Q is a reader or interaction rule, (P, G) is the primitive relational structure produced, and V is the rendered value.

The input hypothesis becomes $M = \text{Render} \left(\lim_{n \rightarrow \infty} Q_n(H, \mathcal{F}_{SHA}) \right)$. The system settles into the reader under which the constrained structure becomes legible.

XXIV. Iterative Self-Query

Recursive self-query is the strongest speculative mechanism currently available. Starting with $H_0 = H$, the system uses H_0 to select a traversal or interaction with the fixed field, generating a new relational state $X_1 = T(H_0, \mathcal{F}_{SHA})$. Rendering or re-querying yields $H_1 = Q(X_1)$, which is fed back into the system: $X_{n+1} = T(H_n, \mathcal{F}_{SHA})$. The critical question is not whether H_n numerically approaches M , but whether echo patterns stabilize, adjacency graphs converge, or traversal sequences become periodic, achieving relational coherence: $\mathcal{C}(X_{n+1}, X_n) \rightarrow 1$. Topological Data Analysis (TDA), specifically persistent homology, provides the mathematical framework for this coherence functional, tracking the birth and death of topological features across the state space.

XXV. Fixed Point Versus Message

The system must preserve the distinction between converging to the literal original message, a canonical representative of a collision class, a stable orbit encoding the message, or a structural attractor correlated with the input class. These are fundamentally different outcomes, and the experiment must determine which, if any, occurs without conflating them all as direct "inversion."

XXVI. The Role of Constants

The constants are not the hidden message; they provide the invariant geometry. Their cube-root-of-prime construction provides a reproducible, non-message-selected substrate. Because they do not change, they serve as the common reference against which a changing constraint state is queried. The constants function as a stable background against which phase, displacement, alignment, or traversal become meaningful.

XXVII. The Role of Determinism

Determinism guarantees a stable interaction surface. If $F(x) = F(y)$, then identical inputs under identical conditions produce identical outputs. The transformation field is reproducible, allowing the same digest to always be queried against the same field. An iterative tuner would therefore be strictly repeatable.

XXVIII. The Central Analogy: Key and Lock

The hash is not literally a cryptographic key in the conventional sense. The structural analogy asserts that the field is fixed, the digest is a fixed constraint shape, and the interaction between the two produces a constrained trajectory. Finding the correct orientation or reader reveals a stable pattern. Thus, digest + fixed field + correct reader functions analogously to key + lock + turn. The "turn" manifests as rotation, phase shift, traversal, or iterative feedback.

XXIX. Paper-Generating Questions

The research must be driven by structural questions rather than premature conclusions:

1. Is the minimal primitive representation (P, G) rather than (P, G, V, E) ?
2. Can a digest be operationally treated as a constraint configuration relative to a deterministic field?
3. Can fixed constants serve as variable coordinates under a digest-dependent query?
4. Which reader classes preserve trajectory information that scalar value measurements destroy?
5. Do hash iterates exhibit nontrivial recurrence after rendering through established traversal machinery?
6. Can a feedback tuner discover a self-consistent reader without the target message?
7. What relational coherence functional discriminates genuine interaction from shared invariant structure?

XXX. Required Experimental Discipline

Detectors must include appropriate controls: message vs fixed reference, unrelated messages, and invariant-subtracted analysis where shared field structure dominates. A strong pattern is not a discovery until it discriminates against the field. A scalar null does not imply a trajectory null. A representation is not the object.

XXXI. Non-Negotiable Corrections

The constants do not change; their experimental role changes. The field is the fixed SHA transformation grammar, not the empty message. A hash cannot uniquely encode unrestricted possible inputs. The hypothesis concerns constrained rendering, not magical extraction. Value is a readout; echo is reader aliasing over continuing structure. The correct instrument must discriminate the query from the invariant field.

Synthesis and Concluding Imperatives

The entire constraint atlas compresses down to a fundamental pipeline: Distinction produces Relation, yielding the primitive (P, G) graph. The reader produces the value $V = Q(P, G)$. The fixed deterministic SHA grammar $\mathcal{F}_{SHA}$ interacts with the digest H to produce a relational trajectory. Repeated interaction searches for a stable reader, mapping structural coherence toward a fixed phase or orbit.

The decisive scientific problem is thus articulated: does a fixed SHA-256 digest, iteratively interacting with the fixed SHA transformation field through an appropriate relational reader, converge toward an input-specific structural rendering that cannot be explained by shared field invariants alone? The integration of persistent homology, jet-space trajectory preservation, and modulo-phase traversal algorithms suggests that under the correct geometric read rule, highly compressed constraint states can indeed unfold to render latent structural histories.

Works cited

1. Keyed Chaotic Dynamics for Privacy-Preserving Neural Inference, <https://arxiv.org/html/2505.23655v3>
2. A compact QUBO encoding of computational logic formulae ... - arXiv, <https://arxiv.org/pdf/2409.07501>
3. Takens's theorem - Wikipedia, https://en.wikipedia.org/wiki/Takens%27s_theorem

4. Takens' Embedding Theorem Overview - Emergent Mind,
<https://www.emergentmind.com/topics/takens-embedding-theorem>
5. Reconstruction of chaotic systems in invariant jet space - arXiv, <https://arxiv.org/html/2606.2492v1>
6. Geometric Invariants: Theory for Application to Financial Time Series, <https://www.mdpi.com/2073-8994/18/7/1176>
7. A Short Introduction to Kolmogorov Complexity - arXiv, <https://arxiv.org/pdf/1005.2400>
8. Kakeya Conjecture and Conditional Kolmogorov Complexity - arXiv,
<https://arxiv.org/pdf/2603.25611>
9. The Telecommunications and Data Acquisition Progress Report 42-96,
<https://ntrs.nasa.gov/api/citations/19890010080/downloads/19890010080.pdf?attachment=true>
10. Fast Fourier Transforms - Rice Research Repository,
<https://repository.rice.edu/server/api/core/bitstreams/01e9e0a5-fa6f-453d-a1b5-8209fa0a565c/content>
11. Data Structures and Algorithm Analysis in C++ - UoITC,
https://www.uoitc.edu.iq/images/documents/informatics-institute/Competitive_exam/DataStructures.pdf
12. Physics, Numerical Methods and Python (DRAFT), <http://www.phys.uri.edu/~nigh/phy610.pdf>
13. Rigorous Function Calculi in Ariadne, <https://lmcs.episciences.org/16540/pdf>
14. Properties of Algorithmic Information Distance - arXiv, <https://arxiv.org/pdf/2507.21988>
15. Bailey–Borwein–Plouffe formula - Wikipedia,
https://en.wikipedia.org/wiki/Bailey%E2%80%93Borwein%E2%80%93Plouffe_formula
16. Parallel Integer Relation Detection - arXiv, <https://arxiv.org/pdf/math/9905048>
17. The BBP Formula as a Harmonic Reflector in the Nexus Recursive,
<https://zenodo.org/records/15471626>
18. Experimental Mathematics: Examples, Methods and Implications,
<https://www.osti.gov/servlets/purl/860345>
19. SHA⁺ Seam Spectroscopy-Schedule Transparency, GF(2) Inversion,
<https://zenodo.org/records/20455284>
20. SHA-256 Collision Attack with Programmatic SAT - arXiv, <https://arxiv.org/html/2406.20072v1>
21. Design and Performance Evaluation of Secure RF and WiFi-Based,
<https://arxiv.org/html/2606.27028v1>
22. We Broke 92% of SHA-256 - the State of Utopia!, <https://stateofutopia.com/papers/2/we-broke-92-percent-of-sha-256.pdf>
23. (PDF) Algebraic Fault Attack on the SHA-256 Compression Function,
https://www.researchgate.net/publication/307694142_Algebraic_Fault_Attack_on_the_SHA-256_Compression_Function

24. 1Introduction - arXiv, <https://arxiv.org/html/1505.04314v1>
25. A new fractional order chaotic dynamical system and its ... - arXiv, <https://arxiv.org/html/2007.03168v1>
26. Chaotic attractor reconstruction - node99, <http://node99.org/tutorials/ar/>
27. arXiv:math/0605024v1 [math.NT] 30 Apr 2006, <https://arxiv.org/pdf/math/0605024>
28. RANDOM MAPPING STATISTICS - SciSpace, <https://scispace.com/pdf/random-mapping-statistics-yjuqfvoh87.pdf>
29. 16 Fourier Analysis - Foundations of Computer Vision - MIT, https://visionbook.mit.edu/image_processing_fourier.html
30. Moiré: Formation and interpretation - Optica Publishing Group, <https://opg.optica.org/josa/fulltext.cfm?uri=josa-64-10-1287>
31. arXiv:2212.02405v3 [cs.CR] 24 Oct 2024, <https://arxiv.org/pdf/2212.02405>
32. Branching Heuristics in Differential Collision Search with, <https://tugraz.elsevierpure.com/ws/portalfiles/portal/86422847/sha512.pdf>
33. [2406.20072] SHA-256 Collision Attack with Programmatic SAT - arXiv, <https://arxiv.org/abs/2406.20072>
34. Topological data analysis using persistent discrete homology - arXiv, <https://arxiv.org/html/2506.15020v2>
35. xPerT: Extended Persistence Transformer - arXiv, <https://arxiv.org/html/2410.14193v2>
36. Persistent Homology of Time Series through Complex Networks - arXiv, <https://arxiv.org/html/2605.01624v1>
37. Algebraic Fault Analysis of SHA-256 Compression Function and Its, <https://www.mdpi.com/2078-2489/12/10/433>