The Ceiling and the Descent

Identification repeats: the residual programme inverted, with a third order, a persistence module over declared relations, and what the descent counts

Driven by Dean A. Kulik

September 2026

What this is, and what changed

This is not a theorem paper. It proves nothing and is separable from every result it draws on. Its purpose is the move the programme has always required: state the thing forward, run it backward, and look at where the two readings cancel.

The first version of this piece concluded that a reader has two coordinates — resolution, which decides what can be told apart, and relation, which decides what counts as having happened twice. That was too weak, and the correction is the substance of this version.

There are not two coordinates. There is one operation — declare some differences inessential, keep what survives — applied at successive orders of structure. Resolution is that operation acting on states and transitions. Relation is the same operation acting on routes. What looked like a second axis is the next application of the first.

That correction is not adopted on its merits as prose. It makes a prediction, the prediction is testable, and it was tested: if the operation recurs, it must recur again at the order above, and each order must keep its own remainder. Section 5 reports that computation. It does recur, and the remainders disagree case by case — which is the strongest available evidence that this is a tower and not a metaphor for two things.

Three computations anchor the piece and are marked where they occur. Everything else is interpretation and labelled as such. Nothing here licenses any claim in the technical papers, and no claim in the technical papers depends on anything here.

1. The forward reading

Stated plainly, the programme so far says this. A substrate supports a field of admissible transformations. A reader is finite and therefore partial. Projection loses distinctions, but loss of distinction in the projection is not destruction in the field: structure is extended, re-expressed or hidden, and the only operation producing a genuine kernel is a restriction of what may exist, which produces it as a relative class with an exact dimension. Forgetting is monotone. Memory is not a dent in the substrate; it is the inherited state constraining which continuation is selected next.

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

The rule that governs all of it: never place the incompleteness in the object. π has no gap; your truncation does.

In that reading the reader has one coordinate, and it is resolution. A reader is a partition, a block size, a window, a cut. The reader papers make it quantitative: a balanced two-block reader on 32 cells recovers 3.55 bits of a 716-bit space and never determines the cycle type, while a reader with the agency to move the cut leaves 1.218 bits hidden and recovers the unoriented cycle structure exactly. Agency dominates duration — but agency there means moving the cut, which is the resolution axis traversed rather than refined.

2. The reverse

Run it from the reader inward and one question is forced. If the reader contributes only a resolution, two readers with the same resolution looking at the same field must agree about what is there.

They do not. The Relation Layer exhibits one substrate, one token count, one symmetry group, one invariant 1-skeleton and one residual dimension ε = 8, on which two readers differ about whether a surviving channel exists — one finds ε_harm = 1, the other 0. What distinguishes them is which four-step journeys they have declared to be the same journey.

$$(X, K, G, C^1_G, d_0) \not\Rightarrow H^1_G \quad \textit{across admissible relation predicates.}$$

Stated exactly, and this is the form that survives every qualification: changing $\mathcal{K}$ changes $\ker d_1$ without changing C^1_G or $\operatorname{im} d_0$.

3. The correction: one operation, successive orders

The obvious reading of Section 2 is that the reader has a second knob. That reading is available, it is what the first version of this paper said, and it is wrong in an instructive way: it treats two manifestations of one operation as unrelated coordinates.

Look at what each stage actually does.

Order	What is compared	The identification	What remains
states	configurations x, x′	symmetry, or a reader's partition	distinguishable states
transitions	1-cochains ω	$\omega \sim \omega + d_0 f$: differ by an endpoint function	the residual, of dimension ε
routes	pairs of paths	a 2-cell declares two routes one journey	$\ker \partial_1$, of dimension ε_harm
relations	pairs of 2-cells	a 3-cell declares two identifications one	the order-2 residual, ε^2_harm

One grammar, four instances: possible differences → an equivalence is declared → quotient → residual differences, which become the next thing to compare. The operators are genuinely different — a symmetry quotient is not an exact-form quotient is not a 2-cell closure condition — and they must not be conflated formally. What is shared is the logical role.

So the sentence to keep is not that the reader has two coordinates. It is:

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

The reader has one operation, applied at successive relational orders.

Resolution and relation are independently specifiable as input data — the spectator filtration is defined on C^1 through the edge parametrisation alone, and the predicate enters only through d_1, so neither is computable from the other. But they are independently specifiable because the same operation is being applied to different structural levels, not because they are different operations.

4. Where the two readings cancel

The naive conclusion from Section 2 is that the reader invents structure the field does not contain. That would place the incompleteness in the reader — the mirror image of the error the programme forbids, and just as wrong.

The correction is the monotonicity theorem: predicates ordered by inclusion give residuals ordered the other way, so declaring more relations can only shrink what survives, and at the empty predicate $d_1 = 0$ and everything survives. Mathematically that says the admissible relation systems form an ordered structure of the model, with

$$\varepsilon = \max \text{ over } \mathcal{K} \text{ of } \varepsilon_harm(\mathcal{K}).$$

Under the programme's reading — and this is interpretation, not theorem — that ordering suggests the relation coordinate is intrinsic to the continuation structure rather than invented by observation. A reader is a position in an ordered family; nothing is manufactured and nothing is absent from the object. The reader's finiteness simply has more structure than a single resolution parameter.

The gap stayed in the reader. What moved is how many orders the reader's finiteness occupies.

5. The test: does the operation recur again?

A framing that cannot fail is not worth adopting. If identification is one operation at successive orders, then the order above relations must behave the same way: there must be a third stage, it must be a genuine cochain complex, and it must keep a residual of its own.

The third stage is built from commuting cubes. Three pairwise vertex-disjoint moves from a common configuration generate eight configurations, twelve arena edges and six faces, each face a disjoint-support square. The cube is the statement that those six identifications are themselves compatible — a relation among relations. Its boundary gives $d_2 : C^2 \to C^3$.

Formally. Fix a configuration S and three base edges that are pairwise vertex-disjoint, each moving an occupied site to an empty one — six distinct vertices. Corners are indexed by (b_1,b_2,b_3) in $\{0,1\}^3$, corner b being S with token i moved iff $b_i = 1$; a cube is admitted only when all eight corners are legal and distinct. The boundary is the alternating face sum

$$\partial[A,B,C] = [B,C]_{A=1} - [B,C]_{A=0} - [A,C]_{B=1} + [A,C]_{B=0} + [A,B]_{C=1} - [A,B]_{C=0},$$

each face a disjoint-support square. Every edge of the cube lies in exactly two faces with opposite induced orientation, so $\partial^2 = 0$ by pairwise cancellation and $d_2 d_1 = 0$ follows from the construction rather than from a

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

computation. The check below is a test of the implementation, reported because an orientation bug is exactly what it catches.

The recursion is not inevitable in general. A complex can terminate: a system may supply no coherent cells at the next order. The correct statement is conditional — whenever a system supplies coherent (q+1)-cells as relations among its q-cells, the identification-and-residual construction extends to order q+1. The token arena supplies them because three independent disjoint moves commute.

Validity first, computed.

d2 . d1 must be exactly zero, or the order-3 complex is not a complex

C8 K=3 squares= 80 cubes= 16 max|d2.d1| = 0.0e+00

Q3 K=3 squares= 168 cubes= 44 max|d2.d1| = 0.0e+00

prism K=3 squares= 36 cubes= 4 max|d2.d1| = 0.0e+00

CE8 K=3 squares= 356 cubes= 118 max|d2.d1| = 0.0e+00

Petersen K=3 squares= 450 cubes= 145 max|d2.d1| = 0.0e+00

The residual one order up, computed.

eps2_harm = dim C^2_G - rank(d1 | C^1_G) - rank(d2 | C^2_G)

substrate K dimC1_G dimC2_G cubes rk d1 rk d2 eps_harm eps2_harm

C8 3 6 4 16 2 2 0 0

C9 3 9 6 30 3 3 0 0

Q3 3 3 3 44 1 2 0 0

Petersen 3 4 2 145 1 1 0 0

prism 3 3 3 4 1 1 0 1

bull 3 7 1 0 1 0 1 0

caterpillar 3 38 13 2 12 1 2 0

CE8 3 32 42 118 22 17 1 3

C5+2pend 3 34 17 4 15 2 1 0

wheel6 3 6 3 5 3 0 0 0

The operation recurs, and the two remainders are not the same remainder. The columns disagree case by case, in both directions.

substrate	ε_harm	ε²_harm	reading
prism, K = 3	0	1	closed at the route order, a residual at the relation order
bull, K = 3	1	0	a residual at the route order, closed above it
caterpillar, K = 3	2	0	two channels below, nothing above

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

CE8, K = 3	1	3	residuals at both orders, of different size

The prism is the case that matters. A reader who computes H^1 and finds zero has answered the H^1 question correctly. What the calculation cannot do is speak for the order above it: one order up, a residual survives. The mathematical statement is that vanishing at order r does not imply vanishing at order r+1; the reading follows afterwards, and it is that a calculation can be complete at its own order while remaining silent about the next.

This is what makes the framing of Section 3 a finding rather than a way of talking. A two-coordinate model does not logically forbid a third coordinate, so the table does not refute it by arithmetic. What the table establishes is what the tower actually claims: the same identification principle admits a nontrivial realisation at the next order, and the residual at order r does not determine the residual at order r+1 in any tested case. The data require no terminal relational order at order two.

6. Does the recurrence itself recur?

The previous version of this paper named the decisive experiment and did not run it: is the order-3 residual predicate-dependent the way the order-2 one is — self-similar, or merely tall? Hold C^1_G, C^2_G and d_1 fixed and vary only the 3-cell family.

Two families are available without inventing anything. The first is the commuting cubes. The second declares every 2-cycle of the square complex trivial. Cubes are themselves 2-cycles — that is precisely why $d_2d_1 = 0$ — so the first sits inside the second, and the monotonicity argument applies one order up.

Computed.

substrate	K	dim C2_G	rk d1	cubes	dim Z2	e2(cubes)	e2(all cycles)	
C8	3	4	2	16	16	0	0	
Q3	3	3	1	44	49	0	0	
Petersen	3	2	1	145	155	0	0	
prism	3	3	1	4	6	1	0	<== changes
CE8	3	42	22	118	153	3	0	<== changes
bull	3	1	1	0	0	0	0	
caterpillar	3	13	12	2	2	0	0	
wheel6	3	3	3	5	5	0	0	

Self-similar. The exact analogue of the order-2 non-determination holds one order up:

$$(X, K, G, C^1_G, C^2_G, d_0, d_1) \not\Rightarrow H^2_G \quad \textit{across admissible 3-cell predicates.}$$

The dim Z_2 column carries a second point. The cubes do not span the 2-cycles — 44 against 49 on Q_3, 145 against 155 on Petersen, 118 against 153 on CE8 — so there is genuine room between the two families, exactly as the disjoint-support squares sit strictly inside the 4-cycles one order down.

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

7. What the descent is counting

The order-3 result arrived with a pattern that explains the whole tower, and it is a consequence of duality rather than a new discovery.

A declared cell is a cycle, and the differential evaluates a cochain on the declared cells, so its kernel is the annihilator of their span. The image of the differential below is the annihilator of the full cycle space Z at that order. Subtracting dimensions:

$$\varepsilon_harm = \dim Z - \dim \text{span(declared cells)}.$$

The residual counts exactly the cycles the declared relation system fails to span. Verified on the full complex at 20 of 20 order-1 cases across both predicates, and 12 of 12 order-2 cases across both 3-cell families.

In the invariant sector this is not a new theorem — it reduces to the Hodge identity of the companion paper, checked here at 28 of 28. What the form adds is that both sides acquire names: the ceiling is the invariant cycle count, and the descent is the span of the declared relations.

With that, four earlier statements stop being separate facts.

- The ceiling. At the empty predicate the span is zero and every cycle survives.
- Monotonicity. A larger predicate has a larger span, so the residual can only fall.
- The maximal predicate closes the order. When the span exhausts Z the residual is zero, at every order — which is why declaring all 2-cycles gives zero in every case above, and why the phenomenon is invisible to a reader who declares everything equivalent.
- Predicate dependence. Two predicates with different spans give different residuals, at any order — which is why the phenomenon recurs rather than being a peculiarity of 2-cells.

It also explains the persistence thresholds below without further argument: a channel dies exactly when an added orbit enlarges the span. The nine size-four orbits on CE8 added cells already inside it; the first size-eight orbit added something independent.

8. Three kinds of zero

The programme's entry principle holds that apparent flatness and genuine flatness look identical from the surface, and that telling them apart is the work. That distinction is now arithmetic, and it has three cases rather than two.

Case	Condition	What the zero means
genuine absence	$\varepsilon = 0$	no residual channel exists to address (paw)
closure at the route order	$\varepsilon > 0$, $\varepsilon_harm = 0$	channels exist; the declared relations closed all of them (W_6: $\varepsilon = 3$, $\dim C^2_G = 3$)
closure at one order only	$\varepsilon_harm = 0$, $\varepsilon^2_harm > 0$	closed below, residual above; the reader stopped one order too early (prism, $K = 3$)

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

All three report nothing to a reader looking at one place, and the three are distinguished by looking elsewhere in a specified direction. Screening is a frame fact, not an ontological one: removed tells you to give up, not projected tells you to find another address. There are now two addresses to try, and both are procedures rather than hopes — move down the predicate order until content reappears, or move up an order and look again.

9. The persistence module over declared relations

If the relation systems are ordered, then a residual channel does not merely exist or not. It has a lifetime: it survives some predicates and dies at others. That is a persistence module, filtered by added relations rather than by geometric scale, and it can be computed.

Take the smaller predicate, add the symmetry orbits of the extra 4-cycles one at a time — each step a legitimate predicate, since a predicate must be symmetry-stable — and record the residual at each step.

Computed.

two bridged 4-cycles, K = 2: eps = 54, cells 48 -> 70, 22 extra orbits

K_disj	cells= 48 eps_harm=7
+orbit1	cells= 49 eps_harm=6 <-- a channel dies
+orbit3	cells= 51 eps_harm=5 <-- a channel dies
+orbit4	cells= 52 eps_harm=4 <-- a channel dies
+orbit8	cells= 56 eps_harm=3 <-- a channel dies
+orbit10	cells= 58 eps_harm=2 <-- a channel dies
+orbit19	cells= 67 eps_harm=1 <-- a channel dies
+orbit20	cells= 68 eps_harm=0 <-- a channel dies
+orbit21, +orbit22	cells= 70 eps_harm=0

CE8, K = 2: eps = 8, cells 89 -> 165, 14 extra orbits

K_disj through +orbit9	cells=125 eps_harm=1 (all |orbit| = 4)
+orbit10	cells=133 eps_harm=0 <-- dies at the first |orbit| = 8

Seven distinct death events in the first case, at seven different thresholds. The last two orbits change nothing at all — by then there is nothing left to close. So the relation coordinate is not a dial with a reading; it is a filtration, and the natural question is not what ε_harm is but which channels die where.

The CE8 pattern is worth one sentence: the single channel survives all ten orbits of size four and dies at the first orbit of size eight. Whether orbit size is the operative variable or a coincidence of this substrate is not determined by two examples, and is left open.

10. Curvature is tested, not created

The memory paper partitions invariant cochains by circulation: exact when it vanishes on every loop, flat but not exact when it vanishes on every square yet records global winding, curved when some square carries nonzero circulation. Every square in that sentence is a declared square.

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

Computed, not asserted.

witness: the eight-vertex substrate of The Relation Layer, K = 2

max |circulation| over the 89 disjoint-support squares : 1.665e-16

max |circulation| over the 165 arena 4-cycles : 5.000e-01

4-cycles carrying nonzero circulation : 24 of 165

the same cochain is flat under K_disj and curved under K_4

on two bridged 4-cycles at K = 2, all 7 harmonic classes are of this kind

The right statement is careful and it is stronger than the loose one. The predicate does not create curvature; it changes the domain on which curvature is tested. That a specified loop carries circulation 0.5 is an algebraic fact about the cochain and that loop, true under every predicate. What the predicate decides is whether that loop is among the elementary relations, and therefore whether the failure registers in d_1.

Curvature is not a property of ω. It is a property of the pair (ω, $\mathcal{K}$).

One precision the trichotomy needs: exactness is not predicate-relative. It is fixed by d_0, and C^0, C^1 and d_0 do not move when the predicate does. What the predicate decides is the flat-versus-curved classification of the non-exact cochains. The order residue is real; its classification is joint. This qualifies the trichotomy of the memory paper and leaves that paper's main line intact — memory decoupled from substrate curvature survives, and trees carrying harmonic content at $\beta_1(X) = 0$ is a stronger form of that decoupling than it had.

11. The monodromy result was the first sighting

The reader paper contains a result that did not fit the resolution picture and was recorded as an anomaly. At three sectors the orientation sign is not a function of the permutation being observed: holding the field and the boundaries fixed and permuting the sector labels gives the same magnitude with both signs, and no refinement resolves it, because a function cannot return two values on one input. The sign comes from the holonomy of the reader's own configuration space.

That is an identification at the route order, seen once and not recognised: which closed walks lift, and to what, is a declaration about which loops are trivial. The 2-cell predicate is the same declaration written on the arena instead of on the space of readers. In both, the field supplies the magnitude and the reader's relational structure supplies whether a consistent global assignment exists.

12. The ladder's blindness is its address

At trivial site stabiliser the capacity ladder depends on the substrate through three integers: |V|, |E(X)| and deg m. Eight non-isomorphic pairs (X, m) with degree sequences from [1,1,2,3,3,4] to [2,2,2,2,3,3] and triangle counts 0, 1 and 2 carry the identical ladder [1, 8, 17, 13, 2, −1].

Forward, that is information loss: a compressed observable can be exactly correct and structurally incomplete. Reverse, it is not a defect. The ladder is not a failed measurement of the substrate; it is an exact measurement of something else, and its blindness specifies which something. A projection that does not carry a structure has not destroyed it, and has also not failed — it has told you precisely which structure it does carry.

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

13. What this puts in the constraint chain, and what it does not

The numbered chain reaches Constraint 3: all change is equal. Law 3 is open. This paper does not close it.

What the mathematics supplies is a constraint on the shape of any answer. If "equal" means identified as the same, then equality of change is exactly what a 2-cell declares, and the non-determination result says that declaration is not recoverable from the transformations. So:

Equality of transformations is a relation on transformations, not a scalar recoverable from the transformations in isolation.

Any Law 3 must therefore specify the equivalence structure under which changes are compared, and cannot name an intrinsic scalar of the 1-skeleton and claim it determines which changes are equal. That is a constraint on the form of the answer, not the answer.

Section 5 sharpens it once more. If identification recurs, then "all change is equal" is not a statement at one level. Each order has its own notion of equality and its own surviving remainder, and the orders do not determine one another. Whether the chain wants equality at the route order, the relation order, or all of them at once is a question the chain has not yet asked. Naming an object here would be the failure mode this programme keeps a list of.

14. The null results, read backward

Five hypotheses died in the work behind The Relation Layer, all of the form: some scalar property of the substrate explains whether the residual is nonzero. Girth, automorphism-group order, vertex-orbit count, confinement of harmonic content to multi-body levels, vanishing forced by two vertex orbits.

Forward, a list of mistakes. Backward, one signal repeated five times: the field kept refusing the address because the question was mis-typed. A property of X cannot answer a question whose answer is not a function of X. Every failed predictor was the mathematics saying the object does not live where the search was running — and Section 5 says it does not live at a single order either.

which graphs carry it? $\rightarrow$ *when is* $\tilde{d}_1$ *injective?* $\rightarrow$ *what survives at each order?*

The strongest evidence for the relation layer is not the counterexample. It is that nothing else worked, five times in a row.

15. What is not established

- No physical identification is made. ε, ε_harm and ε²_harm are dimensions of invariant cochain sectors. Nothing here supplies a map to mass, energy, price, curvature of an ambient manifold, or information loss.
- "Reader" means a choice of symmetry group, resolution and relation predicate — a model specification or access map. It is not a claim about observers, measurement or consciousness, and no such claim is needed for any statement above.

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

- The tower is established as a structure of these finite complexes, to three orders. That a physical theory must factor the same way is not established and no argument here would show it. Whether the orders terminate, and where, is open.
- The ordered family of predicates is an ordered structure of the model. It is not shown that a physical system selects from such a family, nor that any predicate is canonical.
- Monotonicity is proved for predicates ordered by inclusion. Predicates that are not nested are not covered.
- The order-3 results use two 3-cell families. Whether an intermediate geometric family behaves the way all-4-cycles does one order down, and whether the tower terminates and where, is untested. The identity of Section 7 predicts every order behaves alike; that has been checked only to order two.

The technical results these readings draw on stand on their own proofs and certificates in the companion paper. This one stands on none of them, and removing it changes nothing there.

Appendix. The three computations

All run on the engine of The Relation Layer: itertools, collections, numpy, fractions; no imports from earlier artifacts. The order-3 complex is new to this paper and its validity check — $d_2d_1 = 0$ exactly — is reported in Section 5 before any number derived from it.

A. Flat under one predicate, curved under another (Section 8).

substrate	K	eps	cells_disj	cells_all4	h(disj)	h(all4)	flat&curved
bull	2	2	3	3	1	1	0
CE8	2	8	89	165	1	0	1
CE8	3	23	356	615	1	0	1
caterpillar	2	6	8	8	1	1	0
two C4s	2	54	48	70	7	0	7

The bull row matters as much as the CE8 row: its class is flat under both predicates, so the effect distinguishes cases rather than being an artefact of the construction.

B. The orders do not determine one another (Section 5).

Full table in Section 5. The load-bearing rows are prism K=3 with (ε_harm, ε²_harm) = (0, 1) and bull K=3 with (1, 0): each order can be empty while the other is not, in both directions.

C. Persistence over the relation poset (Section 7).

Full output in Section 7. Seven distinct death thresholds on two bridged 4-cycles; a single late death on CE8.

For completeness, the coordinate-separation check from the first version of this paper stands unchanged: ε is identical under both predicates in 90 of 90 checks, while 45 cases show a strict drop in ε_harm, with the spectator profile moving level by level — [2,4] → [1,4], [2,3,1] → [1,1,0].

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com

References

D. Kulik, The Relation Layer: invariant cohomology of token-configuration 2-complexes. QuHarmonics, September 2026.

D. Kulik, Transformation without loss: residual cohomology of token-configuration arenas under change of substrate, symmetry, and admissibility. QuHarmonics, September 2026.

D. Kulik, Residual sectors of symmetric token configuration graphs under change of substrate. QuHarmonics, September 2026.

D. Kulik, Topological and algebraic constraints on accessible continuations in discrete configuration spaces. QuHarmonics, September 2026.

D. Kulik, The topology of transformation: the NEXUS framework, configuration cohomology, and direct-coupled reader logic. QuHarmonics, September 2026.

Copyright Dean A. Kulik – Orcid ID # 0009-0003-3128-8828
Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0)
github.com/QuHarmonics/The-Nexus-Harmonic-Reality info@quharmonics.com