

Optimizing the Number of Gates in Quantum Search

Srinivasan Arunachalam* Ronald de Wolf†

March 31, 2018

arXiv:1512.07550v2 [quant-ph] 21 Oct 2016

Abstract

In its usual form, Grover's quantum search algorithm uses $O(\sqrt{N})$ queries and $O(\sqrt{N}\log N)$ other elementary gates to find a solution in an N-bit database. Grover in 2002 showed how to reduce the number of other gates to $O(\sqrt{N}\log\log N)$ for the special case where the database has a unique solution, without significantly increasing the number of queries. We show how to reduce this further to $O(\sqrt{N}\log^{(r)} N)$ gates for any constant r, and sufficiently large N. This means that, on average, the circuits between two queries barely touch more than a constant number of the $\log N$ qubits on which the algorithm acts. For a very large N that is a power of 2, we can choose r such that the algorithm uses essentially the minimal number $\frac{\pi}{4}\sqrt{N}$ of queries, and only $O(\sqrt{N}\log(\log^{\star} N))$ other gates.

1 Introduction

One of the main successes of quantum algorithms so far is Grover's algorithm for *database search* [Gro96, BHMT02]. Here a database of size N is modeled as a binary string $x \in \{0,1\}^N$, whose bits are indexed by $i \in \{0,\ldots,N-1\}$. A *solution* is an index i such that $x_i = 1$. The goal of the search problem is to find such a solution given access to the bits of x. If our database has Hamming weight $|x| = 1$, we say it has a *unique* solution.

The standard version of Grover's algorithm finds a solution with high probability using $O(\sqrt{N})$ database queries and $O(\sqrt{N}\log N)$ other elementary gates. It starts from a uniform superposition over all database-indices i, and then applies $O(\sqrt{N})$ identical "iterations," each of which uses one query and $O(\log N)$ other elementary gates. Together these iterations concentrate most of the amplitude on the solution(s). A measurement of the final state then yields a solution with high probability. For the special case of a database with a unique solution its number of iterations (= number of queries) is essentially $\frac{\pi}{4}\sqrt{N}$, and Zalka [Zal99] showed that this number of queries is optimal. Grover's algorithm, in various forms and generalizations, has been applied as a subroutine in many other quantum algorithms, and is often the main source of speed-up for those. See for example [BHT97, BCW98, BDH$^+$05, DH96, DHHM04, Dör07].

In [Gro02], Grover gave an alternative algorithm to find a unique solution using slightly more (but still $(\frac{\pi}{4}+o(1))\sqrt{N}$) queries, and only $O(\sqrt{N}\log\log N)$ other elementary gates. The algorithm is more complicated than the standard Grover algorithm, and no longer consists of $O(\sqrt{N})$ identical iterations. Still, it acts on $O(\log N)$ qubits, so on average a unitary sitting between two queries acts on only a tiny $O(\log\log N/\log N)$ fraction of the qubits. It is quite surprising that such mostly-very-sparse unitaries suffice for quantum search.

*QuSoft, CWI Amsterdam, the Netherlands. Supported by ERC Consolidator Grant QPROGRESS.

†QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by ERC Consolidator Grant QPROGRESS and by the European Commission FET-Proactive project Quantum Algorithms (QALGO) 600700.