


Clean quantum and classical communication protocols

Harry Buhrman,[1] Matthias Christandl,[2] Christopher Perry,[2] and Jeroen Zuiddam[1]

[1] *QuSoft, CWI Amsterdam and University of Amsterdam, Science Park 123, 1098 XG Amsterdam, Netherlands*

[2] *QMATH, Department of Mathematical Sciences, University of Copenhagen, Universitetsparken 5, 2100 Copenhagen, Denmark*

By how much must the communication complexity of a function increase if we demand that the parties not only correctly compute the function but also return all registers (other than the one containing the answer) to their initial states at the end of the communication protocol? Protocols that achieve this are referred to as *clean* and the associated cost as the *clean communication complexity*. Here we present clean protocols for calculating the Inner Product of two n-bit strings, showing that (in the absence of pre-shared entanglement) at most $n+3$ qubits or $n+O(\sqrt{n})$ bits of communication are required. The quantum protocol provides inspiration for obtaining the optimal method to implement distributed $CNOT$ gates in parallel whilst minimizing the amount of quantum communication. For more general functions, we show that nearly all Boolean functions require close to $2n$ bits of classical communication to compute and close to n qubits if the parties have access to pre-shared entanglement. Both of these values are maximal for their respective paradigms.

arXiv:1605.07948v3 [quant-ph] 30 Sep 2016

Introduction. In a communication task two players, traditionally named Alice and Bob, receive inputs x and y and wish to calculate the value of some function f. To achieve this, messages will have to be exchanged between them and, depending on the resources available to them, these may consist of classical or quantum communication in the form of bits and qubits respectively. Typically in such scenarios one is interested in minimizing the amount of communication that has to take place to evaluate the function and the number of bits/qubits that must be exchanged to do this is referred to as the classical/quantum *communication complexity* [1, 2].

A protocol for calculating a function will act on three distinct types of registers. Each player will receive an input register, containing x or y, and an ancillary working space, initialized in some standard state such as a string of bits all set to 0, a number of qubits provided in the $|0\rangle$ state or possibly containing entangled states shared between the parties. The final type of register is the answer register which will contain the value of $f(x,y)$ at the end of the protocol. On the completion of a generic protocol for computing f, the input and ancillary registers will no longer be in their starting states and will depend upon both x and y.

However, leaving these registers in such states can be problematic. Firstly, if Alice and Bob wish to keep private the particular protocol that they ran, then discarding these unclean states may leak information regarding this to a third party. Secondly, in the quantum setting, if the players wish to run the protocol over a superposition of input states (perhaps as a subroutine of a larger computation), then allowing the ancillary registers to end up in some unclean, input dependent state and then discarding them can lead to a loss of coherence in the superposition over answers. Finally, the players' computational space may be in short supply and without knowing the registers' final states they cannot easily use them for future calculations.

To avoid such issues we can demand that a protocol (in addition to computing f) returns the input and ancillary registers to their starting state. Following [3], we call such a protocol *clean* and the minimum number of bits/qubits that a clean protocol needs to exchange to compute a given function is the *clean communication complexity*. We shall denote these quantities by $C_{clean}(f)$ and $Q_{clean}(f)$. In the case where the players have access to pre-shared entanglement (which they must restore at the end of the protocol), the associated cost will be written Q^*_{clean}. We focus on the scenario where the players must compute the function exactly.

In all three scenarios, an unclean communication protocol can be converted into a clean one at the cost of doubling the communication. To do this, the players run the unclean protocol, copy the output to another location and then run the unclean protocol backwards. At first glance it may appear that clean, classical protocols are even easier to construct: the players keep a copy of their input and then simply erase all ancillary bits once the protocol is complete. However, Landauer's principle [4–6] implies that such irreversible manipulations will generate heat or else cost work. As such, if one is interested in avoiding such costs, it makes sense to consider protocols where all operations must be reversible. In light of these constructions, it is natural to ask: do more efficient clean protocols, without this doubling in communication, exist?

In the first part of this paper we focus on the clean communication complexity of computing the Inner Product of two distributed bit strings of length n, showing that (in the absence of pre-shared entanglement) this can be done by exchanging $n+3$ qubits. As a clean protocol for this function must exchange at least $n+1$ qubits, this is very close to tight. We also provide a clean, classical protocol that computes Inner Product while exchanging only $n+O(\sqrt{n})$ bits. This provides a saving over the most obvious protocol which, as we shall show, are close to optimal for the clean, classical computation of most functions.